

**Oracle<sup>®</sup> Retail Invoice Matching  
Installation Guide  
Release 12.0  
May 2006**

Copyright © 2006, Oracle. All rights reserved.

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software—Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

# Contents

<b>Preface</b> .....	<b>v</b>
Audience .....	v
Related Documents .....	v
Customer Support .....	v
<b>1 Pre-Installation Tasks</b> .....	<b>1</b>
Check Database Server Requirements .....	1
Check Application Server Requirements .....	1
Check Client PC and Web Browser Requirements .....	2
Client PC requirements .....	2
Browser requirements .....	2
<b>2 Database Installation Tasks</b> .....	<b>3</b>
Invoice Matching Database Installer .....	3
Expand the ReIM Database Schema Distribution.....	3
Run the ReIM Database Schema Installer .....	3
Values to Remember for the Application Installer .....	4
Resolving Errors Encountered During Database Schema Installation .....	4
<b>3 Application Installation UNIX (Sun Solaris/AIX/HP-UX)</b> .....	<b>5</b>
Create a New OC4J Instance for ReIM .....	5
Expand the ReIM Application Distribution .....	6
Run the ReIM Application Installer.....	7
Resolving Errors Encountered During Application Installation .....	7
Backups Created by Installer .....	7
Test the ReIM Application .....	7
reim.properties .....	8
ReIM Batch Scripts.....	8
Web Help Files .....	8
<b>A Appendix: ReIM Database Schema Installer Screens</b> .....	<b>9</b>
<b>B Appendix: ReIM Application Installer Screens</b> .....	<b>11</b>
<b>C Appendix: Installer Silent Mode</b> .....	<b>17</b>
Repeating an Installation Attempt.....	17
Re-Using ant.install.properties in a Different Staging Directory .....	17
<b>D Appendix: URL Reference</b> .....	<b>19</b>
<b>E Appendix: Common Installation Errors</b> .....	<b>20</b>
Database Installer Hangs on Startup .....	20
Unreadable Buttons in the Installer.....	20
“Unable to get a deployment manager” Message .....	20
“Could not create system preferences directory” Warning.....	21



Oracle Retail Installation Guides contain the requirements and procedures that are necessary for the retailer to install Oracle Retail products.

## Audience

This Installation Guide is written for the following audiences:

- Database administrators (DBA)
- System analysts and designers
- Integrators and implementation staff

## Related Documents

You can find more information about this product in these resources:

- Oracle Retail Allocation Release Notes
- Oracle Retail Allocation Operations Guide
- Oracle Retail Allocation User Guide
- Oracle Retail Allocation Data Model
- Oracle Retail Allocation Batch Schedule
- Oracle Retail Allocation Online Help

## Customer Support

- <https://metalink.oracle.com>

When contacting Customer Support, please provide:

- Product version and program/module name.
- Functional and technical description of the problem (include business impact).
- Detailed step-by-step instructions to recreate.
- Exact error message received.
- Screen shots of each step you take.



---

## Pre-Installation Tasks

### Check Database Server Requirements

General Requirements for a database server running RMS include:

- UNIX based OS certified with Oracle RDBMS 10g Enterprise Edition (options are AIX5.2, AIX5.3, Solaris 9, and HP-UX 11.11)
- Oracle RDBMS 10g Release 2 Enterprise Edition (minimum 10.2.0.1.0 patchset required) with the following patches and components:

Patches:

- 4516865 (WRONG PERMISSIONS AFTER INSTALLATION IN OH AND SUBSEQUENT DIRECTORIES)

Components:

- Oracle Database 10g
- Oracle Partitioning
- Oracle Net Services
- Oracle Call Interface (OCI)
- Oracle Programmer
- Oracle XML Development Kit
- ANSI compliant C compiler (certified with OS and database version)
- Perl compiler 5.0 or later
- x-Windows interface

### Check Application Server Requirements

General requirements for an application server capable of running the Invoice Matching application include:

- UNIX based OS certified with Oracle Application Server 10g 10.1.3. Options include AIX 5.2, AIX 5.3, Solaris 9, and HP-UX 11.11.
- Oracle Application Server 10g 10.1.3 with the following patches:
  - 4992357 (ILLEGALACCESSERROR WHEN ATTEMPTING TO LOAD ORACLE.SQL.CHARACTERSET CLASS)
  - 4959854 (CANNOT RESTART MDB THROUGH OC4J ASCONSOLE)
  - 4645524 (RETEK : RMIINITIALCONTEXTFACTORY DOES NOT WORK PROPERLY WITH GLOBAL JNDI)
  - 4619599 (ABILITY TO CONTROL MDBS INITIAL STATE)

---

**Note:** This release of ReIM is only supported in a managed OC4J instance as part of OracleAS 10g. It is not supported on OC4J standalone

---

## Check Client PC and Web Browser Requirements

### Client PC requirements

- Operating system is Windows 2000 or XP
- Display resolution: 1024x768
- Processor; minimum 1GHz
- Memory; minimum of 512MBytes
- Networking; Intranet with at least 10Mbps data rate.
- Sun JRE 1.4.2 32 bit

### Browser requirements

- Microsoft Internet Explorer; version 5.5 or higher

## Database Installation Tasks

### Invoice Matching Database Installer



GUI mode installer

### Expand the ReIM Database Schema Distribution

1. Log into the UNIX server as a user which has sufficient access to run sqlplus from the Oracle RDBMS installation.
2. Create a staging directory for the ReIM database installation software. There should be a minimum of 8 MB disk space available.
3. Copy the reim12dbschema.zip file to the staging directory. This will be referred to as INSTALL\_DIR for the remainder of this chapter.
4. Change directories to INSTALL\_DIR and extract the reim12dbschema.zip file.

### Run the ReIM Database Schema Installer

---

**Note:** Appendix A contains details on every screen and field in the database schema installer.

---

1. Change directories to INSTALL\_DIR/reim/dbschema.
2. Set the ORACLE\_HOME and ORACLE\_SID environment variables with the values for your Oracle RDBMS installation. The **oraenv** script can be used for this.
3. Set the JAVA\_HOME environment variable to a Java 1.4.2 JDK. The installer is not compatible with earlier versions of Java. If you have JRE instead of a JDK, set JAVA\_HOME to the **jre** subdirectory (Example: /usr/java14/jre instead of /usr/java14). JAVA\_HOME needs to be set such that the JAVA\_HOME/bin/java binary can be found.
4. If you are using an X server such as Exceed, set the DISPLAY environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset DISPLAY for text mode.
5. Run the install.sh script to start the installer.

6. After the installer is complete, you can check its log file: `reim12install-db.<timestamp>.log`. The individual sql scripts leave behind various logs under `INSTALL_DIR/reim/dbschema`. A `.dbhistory` file is created with a listing of all of the sql scripts that were run by the installer. A `.dberrors` file is created if any errors are encountered.

### Values to Remember for the Application Installer

After it has completed the schema installation, the installer will print some database settings that you will need for the application installation. These settings are also written to the end of the installer log file (`reim12install-db_<time>.log`). These settings include the JDBC URL and database users. Record these settings for use during the application installation.

### Resolving Errors Encountered During Database Schema Installation

See Appendix E for a list of common installation errors.

If the database schema installer encounters any errors, it will halt execution immediately and print to the screen which SQL script it was running when the error occurred. It will also write the path to this script to the `.dberrors` file. When this happens, you must run that particular script using `sqlplus`. After you are able to complete execution of the script, delete the `.dberrors` file and run the installer again. You can run the installer in silent mode so that you don't have to retype the settings for your environment. See Appendix C of this document for instructions on silent mode.

Subsequent executions of the installer will skip the SQL scripts which have already been executed in previous installer runs. This is possible because the installer maintains a **.dbhistory** file with a listing of the SQL scripts that have been run. If you have dropped the ReIM database tables and wish to run a fresh install again, you can delete the `.dbhistory` file so that the installer runs through all of the scripts again. It is recommended that you allow the installer to skip the files that it has already run.

The ReIM database schema distribution includes a script that you can use to drop the ReIM 12.0 tables from the RMS schema and start over with their installation. These scripts are located under `INSTALL_DIR/reim/dbschema/dbscripts/clean`. Follow the instructions in the **README.txt** file located with these scripts.

---

## Application Installation UNIX (Sun Solaris/AIX/HP-UX)

Before proceeding you must install Oracle Application Server 10g 10.1.3 plus the patches listed in the Chapter 1 of this document. The ReIM application will be deployed to an OC4J instance within the OracleAS10g installation. You must also have the Java 1.4.2 SDK installed on your system.

It is assumed Oracle RDBMS has already been configured and loaded with the appropriate ReIM schema for your installation.

### Create a New OC4J Instance for ReIM

You can skip this section if you are redeploying to an existing OC4J instance.

The ReIM application must be deployed to its own dedicated OC4J instance. For instructions on how to create a new OC4J instance, see *Adding and Deleting OC4J Instances* in the *Reconfiguring Application Server Instances* chapter of the *Oracle Application Server Administrator's Guide*.

1. Log into the server which is running your OracleAS10g installation. Set your ORACLE\_HOME environment variable to point to this installation.
2. Choose a name for the new OC4J instance.

---

**Example:** reim-oc4j-instance

---

Create this OC4J instance as documented in the Oracle Application Server Administrator's Guide.

---

**Example:**  
\$ORACLE\_HOME/bin/createinstance  
-instanceName reim-oc4j-instance

---

When prompted for the oc4jadmin password, provide the same administrative password you gave for the AS10g installation. All OC4J instances running Oracle Retail applications must have the same oc4jadmin password.

3. Configure the JDK for this OC4J instance. By default, new OC4J instances use the Java 1.5 JDK that is shipped with the application server. This release of ReIM requires Java 1.4.2.

For instructions on how to change the JDK for an OC4J instance, see the *Specifying the JDK in a Managed Configuration* section of the *OC4J Runtime Configuration* chapter of the *Oracle Containers for J2EE Configuration and Administration Guide*.

- (AIX only) If the AS10g installation is on AIX, you must set the **ibm.cl.eagerresolution** property in \$ORACLE\_HOME/opmn/conf/opmn.xml. Add the definition of this property to the startup **java-options** for the OC4J instance.

**Example:**

```
<process-type id="reim-oc4j-instance" module-id="OC4J" status="enabled">
  <module-data>
    <category id="start-parameters">
      <data id="java-bin" value="/usr/java14/bin/java"/>
      <data id="java-options" value="-Dibm.cl.eagerresolution
-Djava.security.policy=$ORACLE_HOME/j2ee/reim-oc4j-
instance/config/java2.policy -Dhttp.webdir.enable=false"/>
```

Force OPMN to reload the configuration file.

---

**Example:** \$ORACLE\_HOME/opmn/bin/opmnctl reload

---

- Start the OC4J instance. You can do this through the Enterprise Manager web interface, or on the command line using the opmnctl utility:

---

**Example:** \$ORACLE\_HOME/opmn/bin/opmnctl startproc  
process-type=reim-oc4j-instance

---

- Verify that the OC4J instance was fully started. If you are using the Enterprise Manager web interface, the instance should have a green arrow indicating that it is running. On the command line, verify that the instance has a status of "Alive".

---

**Example:** \$ORACLE\_HOME/opmn/bin/opmnctl status

---

If you are unable to start the OC4J instance after several attempts, try increasing the startup timeouts in ORACLE\_HOME/opmn/conf/opmn.xml. If that does not help, consult the Oracle Application Server documentation for further assistance.

## Expand the ReIM Application Distribution

- Log into the UNIX server as the user who owns the OracleAS 10g installation. Create a new staging directory for the ReIM application distribution (reim12application.zip). There should be a minimum of 50 MB disk space available for the application installation files.

---

**Example:** \$ORACLE\_HOME/j2ee/reim-oc4j-instance/reim-  
staging

---

This location will be referred to as INSTALL\_DIR for the remainder of this chapter.

- Copy reim12application.zip to INSTALL\_DIR and extract its contents.

## Run the ReIM Application Installer

Once you have an OC4J instance that is configured and started, you can run the ReIM application installer. This installer will configure and deploy the ReIM application.

---

**Note:** Appendix B contains details on every screen and field in the application installer.

---

1. Change directories to `INSTALL_DIR/reim/application`.
2. Set the `ORACLE_HOME` and `JAVA_HOME` environment variables. `ORACLE_HOME` should point to your AS10g installation. `JAVA_HOME` should point to a Java 1.4.2 JDK. The installer is not compatible with earlier versions of Java.
3. If you are using an X server such as Exceed, set the `DISPLAY` environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset `DISPLAY` for text mode.
4. Run the `install.sh` script. This will launch the installer. After installation is completed, a detailed installation log file is created: `reim12install.<timestamp>.log`.

## Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it will halt execution immediately. You can run the installer in silent mode so that you don't have to retype the settings for your environment. See Appendix C of this document for instructions on silent mode.

See Appendix E of this document for a list of common installation errors.

Since the application installation is a full reinstall every time, any previous partial installs will be overwritten by the successful installation.

## Backups Created by Installer

The ReIM application installer will back up a previous batch script installation by renaming it from `reim-batch` to `reim-batch.<timestamp>`. This is done to prevent the removal of any custom changes you might have. These backup directories can be safely removed without affecting the current installation.

---

**Example:** `reim-batch.200605011726`

---

## Test the ReIM Application

After the application installer completes you should have a working ReIM application installation. To launch the application, open a web browser and go to `http://host:httpport/contextroot/index.jsp`

---

**Example:** `http://myhost:7777/reim/index.jsp`

---

## reim.properties

The reim.properties file contains most of the settings for the ReIM application. Many properties in this file are set by the installer to get a working application up and running, but you may want to modify other settings in this file.

You can find this file under

ORACLE\_HOME/j2ee/<instancename>/applications/<appname>/<appname>/WEB-INF/classes/com/rettek/reim.

See the ReIM Operations Guide regarding the settings in reim.properties.

## ReIM Batch Scripts

The ReIM application installer configures and installs the batch scripts under ORACLE\_HOME/j2ee/<instance>/reim-batch.

The batch scripts are copies of the same generic file. Their file names determine which functionality is run.

The two settings that are needed for the scripts to run correctly are the REIMHOME and JAVA\_HOME variables.

- REIMHOME = application directory created during deployment
- JAVA\_HOME = Java 1.4.2 location on the server

---

**Example:** REIMHOME=J2EE\_HOME/applications/reim  
JAVA\_HOME=/usr/java

---

## Web Help Files

The application installer automatically copies the web help files to the proper location. They are accessible from the help links within the application.

## Appendix: ReIM Database Schema Installer Screens

You will need the following details about your environment for the installer to successfully create the ReIM database schema. Depending on the options you select, you may not see some screens or fields.

Screen: Database Schema Details



Fields on this screen:

<b>Field Title</b>	SYSTEM user password
<b>Field Description</b>	Password for the SYSTEM user..
<b>Notes</b>	

<b>Field Title</b>	RMS 12 schema (existing)
<b>Field Description</b>	The RMS schema in your database. This should be an existing RMS 12.0 schema in which the ReIM tables are to be installed.
<b>Example</b>	RMS12
<b>Notes</b>	

<b>Field Title</b>	RMS 12 schema password
<b>Field Description</b>	Password for the RMS schema
<b>Notes</b>	

<b>Field Title</b>	Oracle database SID
<b>Field Description</b>	Oracle System Identifier for your database instance
<b>Example</b>	mydatabase
<b>Notes</b>	

<b>Field Title</b>	ReIM/RMS 12 JDBC URL
<b>Field Description</b>	URL used by the ReIM application to access the ReIM database schema. See <i>Appendix D: URL Reference</i> for expected syntax.
<b>Example</b>	jdbc:oracle:thin:@myhost:1525:mydatabase
<b>Notes</b>	

<b>Field Title</b>	Temporary tablespace name
<b>Field Description</b>	an existing temporary tablespace to use during installation
<b>Example</b>	TEMP
<b>Notes</b>	

Screen: ReIM Demo Data (optional)



Fields on this screen:

<b>Field Title</b>	Do you want demo data inserted into the RMS TERMS and INVC* tables?
<b>Field Description</b>	There are demo data scripts which are included with ReIM 12.0. Their use is optional. <b>Warning:</b> If you choose not to load demo data by selecting “No”, then you will not be able to log into the ReIM application until you add users to the IM_USER_AUTHORIZATION table.
<b>Notes</b>	

## Appendix: ReIM Application Installer Screens

You will need the following details about your environment for the installer to successfully deploy the ReIM application. Depending on the options you select, you may not see some screens or fields.

Screen: Data Source Details



Fields on this screen:

<b>Field Title</b>	ReIM/RMS 12 JDBC URL
<b>Field Description</b>	URL used by the ReIM application to access the ReIM/RMS database schema. See <i>Appendix D: URL Reference</i> for expected syntax.
<b>Destination</b>	reim.properties
<b>Example</b>	jdbc:oracle:thin:@myhost:1525:mydatabase
<b>Notes</b>	

<b>Field Title</b>	ReIM/RMS 12 schema
<b>Field Description</b>	RMS database user for accessing the ReIM tables. This should match what was given in the <i>RMS 12 schema</i> field of the ReIM database installer.
<b>Destination</b>	reim.properties
<b>Example</b>	RMS12USER
<b>Notes</b>	

<b>Field Title</b>	ReIM/RMS 12 schema password
<b>Field Description</b>	Password for the JDBC username. This should match what was given in the <i>ReIM 12 schema password</i> field of the ReIM database installer.
<b>Destination</b>	reim.properties
<b>Notes</b>	

<b>Field Title</b>	RMS 12 schema owner
<b>Field Description</b>	Database user which owns the RMS and ReIM tables. This will usually have the same value as the <i>ReIM/RMS 12 schema</i> field above.
<b>Destination</b>	reim.properties
<b>Example</b>	RMS12USER
<b>Notes</b>	


Screen: OC4J Server Type: Managed or Standalone?



Fields on this screen:

<b>Field Title</b>	Which type of OC4J server are you deploying to?
<b>Field Description</b>	A managed OC4J server is part of a larger AS10g enterprise environment and is managed by OPMN. A standalone OC4J server is a single instance installed by itself and is not controlled by OPMN. This Oracle Retail application release is only supported on managed OC4J.
<b>Example</b>	managed
<b>Notes</b>	

Screen: Application Server Details – AS10g Enterprise



Fields on this screen:

<b>Field Title</b>	Hostname
<b>Field Description</b>	Hostname of the application server
<b>Example</b>	myhost
<b>Notes</b>	

<b>Field Title</b>	OPMN request port
<b>Field Description</b>	Port on which OPMN listens for requests to forward on to OC4J instances. This port can be found in the ORACLE_HOME/opmn/conf/opmn.xml file:  <code>&lt;port local="6100" remote="6200" request="6003"/&gt;</code>
<b>Example</b>	6003
<b>Notes</b>	

Screen: Application Server Details – OC4J Standalone




Fields on this screen:

<b>Field Title</b>	Hostname
<b>Field Description</b>	Hostname of the application server
<b>Example</b>	myhost
<b>Notes</b>	

<b>Field Title</b>	OC4J RMI port
<b>Field Description</b>	Port on which the standalone OC4J server listens for connections. This setting can be found in the ORACLE_HOME/j2ee/home/config/rmi.xml file.  <pre>&lt;rmi-server   xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"   xsi:noNamespaceSchemaLocation="http://xmlns.oracle.com/oracleas/schema/rmi-server-10_0.xsd"   port="23791"</pre>
<b>Example</b>	23791
<b>Notes</b>	

Screen: Application Deployment Details



Fields on this screen:

<b>Field Title</b>	ReIM 12 app deployment name
<b>Field Description</b>	Name by which this ReIM application will be identified in the application server
<b>Example</b>	reim12
<b>Notes</b>	

<b>Field Title</b>	ReIM 12 context root
<b>Field Description</b>	Path under the HTTP URL that will be used to access the ReIM application. For example, a context root of 'reim' will result in the application being accessed at http://host:port/reim/index.jsp.
<b>Example</b>	reim
<b>Notes</b>	

<b>Field Title</b>	ReIM 12 OC4J instance
<b>Field Description</b>	Name of the OC4J instance that was created for this ReIM application.
<b>Example</b>	reim-oc4j-instance
<b>Notes</b>	

Screen: OC4J Administrative User



Fields on this screen:

<b>Field Title</b>	OC4J admin user
<b>Field Description</b>	Username of the admin user for OC4J instance to which the ReIM application is being deployed.
<b>Example</b>	oc4jadmin
<b>Notes</b>	

<b>Field Title</b>	OC4J admin password
<b>Field Description</b>	Password for the OC4J admin user. You chose this password when you created the OC4J instance (managed OC4J) or when you started the instance for the first time (standalone OC4J).
<b>Notes</b>	

---

## Appendix: Installer Silent Mode

### Repeating an Installation Attempt

In addition to the GUI and text interfaces of the ReIM installer, there is a silent mode that can be run. This mode is useful if you wish to run a repeat installation without retyping the settings you provided in the previous installation. It is also useful if you encounter errors in the middle of an installation and wish to continue.

The installer runs in two distinct phases. The first phase involves gathering settings from the user. At the end of the first phase, a properties file named `ant.install.properties` is created with the settings that were provided. Then the second phase begins, where this properties file is used to provide your settings for the installation.

To skip the first phase and re-use the `ant.install.properties` file from a previous run, follow these instructions:

1. Edit the `ant.install.properties` file and correct any invalid settings that may have caused the installer to fail in the previous run.
2. the installer again with the **silent** argument.

---

**Example:** `install.sh silent`

---

### Re-Using `ant.install.properties` in a Different Staging Directory

`ant.install.properties` is the input file for the installer back-end and is created after you answer all of the prompts. This file can be used for repeat attempts from the same staging area (see *Repeating an Installation Attempt* above). If this file is moved to a different staging directory, then the **basedir** property needs to be removed from the file before running the installer again. Simply delete the line containing the `basedir` property from the file.



---

## Appendix: URL Reference

Both the database schema and application installers for the Invoice Matching product will ask for certain URLs. These include the following.

### JDBC URL for a database

Used by the Java application and by the installer to connect to the database.

Syntax: **jdbc:oracle:thin:@<host>:<port>:<sid>**

<host>: hostname of the database server

<port>: database listener port

<sid>: system identifier for the database

---

**Example:** jdbc:oracle:thin:@myhost:1521:mysid

---

### Deployer URI

Used by the Oracle ANT tasks to deploy an application to an OC4J instance. The application installer does not ask the user for this value; it is constructed based on other inputs and written to the ant.install.properties file for input to the installation script. For repeat installations using silent mode, you may need to correct mistakes in the deployer URI.

---

**Note:** There are several different formats for the deployer URI depending on your cluster topology. Consult the *Deploying with the OC4J Ant Tasks* chapter of the *OC4J Deployment Guide* for further details.

---

Syntax (managed OC4J):

**deployer:cluster:opmn://<host>:<port>/<instance>**

<host>: hostname of the OracleAS environment

<port>: OPMN request port of the OracleAS environment. This can be found in the <ORACLE\_HOME>/opmn/conf/opmn.xml file.

<instance>: Name of the OC4J instance where the application will be deployed.

---

**Example:** deployer:cluster:opmn://myhost:6003/reim-oc4j-instance

---

Syntax (standalone OC4J):

**deployer:oc4j:<host>:<port>**

<host>: hostname of the OracleAS environment

<port>: RMI port of the OC4J server. This can be found in the ORACLE\_HOME/j2ee/home/config/rmi.xml file.

---

**Example:** deployer:oc4j:myhost:23791

---

---

## Appendix: Common Installation Errors

This section provides some common errors encountered during installation of ReIM.

### Database Installer Hangs on Startup

#### Symptom:

When the database schema installer is run, the following is written to the console and the installer hangs indefinitely:

```
Running pre-install checks
Running tnsping to get listener port
```

#### Solution:

The installer startup script is waiting for control to return from the **tnsping** command, but tnsping is hanging. Type Control+C to cancel the installer, and investigate and solve the problem that is causing the tnsping <sid> command to hang. This can be caused by duplicate database listeners running.

### Unreadable Buttons in the Installer

If you are unable to read the text within the installer buttons, it probably means that your JAVA\_HOME is pointed to a pre-1.4.2 JDK. Set JAVA\_HOME to a Java development kit of version 1.4.2 or later and run the installer again.

### “Unable to get a deployment manager” Message

#### Symptom:

The application installer quits with the following error message:

```
[oracle:deploy] Unable to get a deployment manager.
[oracle:deploy]
[oracle:deploy] This is typically the result of an invalid deployer URI
format being supplied, the target server not being in a started state or
incorrect authentication details being supplied.
[oracle:deploy]
[oracle:deploy] More information is available by enabling logging --
please see the Oracle Containers for J2EE Configuration and
Administration Guide for details.
```

#### Solution:

This error can be caused by any of the following conditions:

- OC4J instance provided is not running.
- Incorrect OC4J instance name provided
- Incorrect OC4J administrative username and/or password
- Incorrect OPMN request port provided.

Make sure that the OC4J instance is running, and then check the **ant.install.properties** file for entry mistakes. Pay close attention to the input.deployer.uri (see Appendix D: *URL Reference*), input.oc4j.instance, input.admin.user, and input.admin.password properties. If you need to make a correction, you can run the installer again with this file as input by running silent mode (see Appendix C of this document).

## “Could not create system preferences directory” Warning

### Symptom:

The following text appears in the installer Errors tab:

```
May 22, 2006 11:16:39 AM java.util.prefs.FileSystemPreferences$3 run
WARNING: Could not create system preferences directory. System
preferences are unusable.
May 22, 2006 11:17:09 AM java.util.prefs.FileSystemPreferences
checkLockFile0ErrorCode
WARNING: Could not lock System prefs. Unix error code -264946424.
```

### Solution:

This is related to Java bug 4838770. The `/etc/.java/.systemPrefs` directory may not have been created on your system. See <http://bugs.sun.com> for details.

This is an issue with your installation of Java and does not affect the Oracle Retail product installation.