

---

# Enterprise PeopleTools 8.48 Installation for Oracle

---

**June 2006**

Enterprise PeopleTools 8.48  
Installation for Oracle  
SKU itools848\_062706\_itora  
Copyright © 2006, Oracle. All rights reserved.

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

### **U.S. GOVERNMENT RIGHTS**

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are “commercial computer software” or “commercial technical data” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee’s responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

### **Open Source Disclosure**

Oracle takes no responsibility for its use or distribution of any open source or shareware software or documentation and disclaims any and all liability or damages resulting from use of said software or documentation. The following open source software may be used in Oracle’s PeopleSoft products and the following disclaimers are provided.

#### *Apache Software Foundation*

This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>). Copyright © 2000-2003. The Apache Software Foundation. All rights reserved. Licensed under the Apache License, Version 2.0 (the “License”); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0>.

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an “AS IS” BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

### *OpenSSL*

Copyright © 1998-2005 The OpenSSL Project. All rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>).

THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT “AS IS” AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### *Loki Library*

Copyright © 2001 by Andrei Alexandrescu. This code accompanies the book: Alexandrescu, Andrei. “Modern C++ Design: Generic Programming and Design Patterns Applied”. Copyright © 2001 Addison-Wesley. Permission to use, copy, modify, distribute and sell this software for any purpose is hereby granted without fee, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation.

### *Helma Project*

Copyright © 1999-2004 Helma Project. All rights reserved. THIS SOFTWARE IS PROVIDED “AS IS” AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE HELMA PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Helma includes third party software released under different specific license terms. See the licenses directory in the Helma distribution for a list of these license.

### *Sarissa*

Copyright © 2004 Manos Batsis.

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA.

### *ICU*

ICU License - ICU 1.8.1 and later COPYRIGHT AND PERMISSION NOTICE Copyright © 1995-2003 International Business Machines Corporation and others. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, provided that the above copyright notice(s) and this permission notice appear in all copies of the Software and that both the above copyright notice(s) and this permission notice appear in supporting documentation. THE SOFTWARE IS PROVIDED "AS IS," WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE. Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

All trademarks and registered trademarks mentioned herein are the property of their respective owners.

*Sun's JAXB Implementation – JSDK 1.5 relaxngDatatype.jar 1.0 License*

Copyright © 2001, Thai Open Source Software Center Ltd, Sun Microsystems. All rights reserved.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*W3C IPR SOFTWARE NOTICE*

Copyright © 2000 World Wide Web Consortium, (Massachusetts Institute of Technology, Institut National de Recherche en Informatique et en Automatique, Keio University). All Rights Reserved.

Note: The original version of the W3C Software Copyright Notice and License could be found at <http://www.w3.org/Consortium/Legal/copyright-software-19980720>.

THIS SOFTWARE AND DOCUMENTATION IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE OR DOCUMENTATION WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS. COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE SOFTWARE OR DOCUMENTATION.

# Contents

## Preface

<b>About This Documentation.....</b>	<b>xxiii</b>
Audience.....	xxiii
Products Referenced in this Book.....	xxiii
Related Publications.....	xxiv

## Chapter 1

<b>Preparing for Installation.....</b>	<b>1</b>
Understanding the PeopleSoft Installation.....	1
Assembling Related Documentation.....	2
Verifying Hardware and Software Requirements .....	2
Considering Project Planning.....	3
Planning Your Initial Configuration.....	3
Understanding Workstations.....	4
Defining the File Server.....	5
Defining the Database Server.....	5
Defining the Application Server.....	5
Defining the Batch Server.....	6
Defining the Web Server.....	6
Using Laser Printers.....	7
Planning Database Creation.....	7
Understanding Database Creation.....	8
Determining Databases and Database Names.....	8
Defining Oracle and PeopleSoft Databases.....	8
Planning Multilingual Strategy.....	10
Understanding Multilingual Issues.....	10
Choosing a Base Language.....	11
Selecting Additional Languages.....	13
Selecting a Database Character Set.....	13
Reviewing Updates and Fixes Required at Installation.....	14
Installing Supporting Applications.....	15
Installing the Database Engine.....	16
Understanding the Database Engine.....	17
Creating a Seed Database.....	17

Installing Oracle Net on the Server.....	17
Installing Oracle Net on Your Workstation.....	18
Testing Oracle Net Connectivity.....	19
Performing Backups.....	19
Using PeopleSoft Change Assistant and PeopleSoft Change Impact Analyzer.....	20

## Chapter 2

<b>Installing Web Server Products.....</b>	<b>21</b>
Installing Oracle Application Server.....	21
Understanding the Oracle Application Server Installation.....	21
Prerequisites.....	22
Preparing for the Oracle Application Server Installation.....	22
Installing the Oracle Application Server on Windows and UNIX.....	25
Updating the IBM JDK to Version 1.4.2.....	35
Uninstalling the Oracle Application Server.....	36
Installing BEA WebLogic Server.....	37
Understanding the WebLogic Installation.....	37
Installing WebLogic.....	38
Installing WebSphere Application Server.....	39
Understanding WebSphere Application Server Installation.....	39
Prerequisites.....	41
Preparing for WebSphere Installation.....	41
Installing WebSphere Base.....	42
Installing WebSphere Base with the Silent Method.....	45
Verifying the WebSphere Base Installation.....	46
Uninstalling the Default WebSphere Application.....	46
Installing the WebSphere Base 5.1 Plug-in for HTTP Proxy Server.....	46
Installing WebSphere Network Deployment Manager.....	48
Upgrading WebSphere 5.1 Base and WebSphere ND to 5.1.1.7.....	48
Troubleshooting the WebSphere Installation and Upgrade.....	49

## Chapter 3

<b>Installing Additional Components.....</b>	<b>51</b>
Installing Tuxedo on Windows.....	51
Understanding Tuxedo.....	52
Prerequisites.....	52
Uninstalling Tuxedo from Windows (Recommended).....	53
Designating the Application Server Administrator.....	54

Installing Tuxedo on Windows.....	55
Checking the Service Account.....	55
Setting Up the Tuxedo Services.....	56
Verifying the Server Installation.....	58
Ensuring that Tuxedo Coexists with Earlier Versions.....	59
Installing Tuxedo on UNIX.....	59
Understanding Tuxedo.....	60
Prerequisites.....	61
Removing Tuxedo on UNIX.....	61
Completing the Preinstallation Checklist.....	62
FTPing Tuxedo Installation Files to UNIX.....	62
Designating the Tuxedo Owner.....	63
Installing Tuxedo on UNIX.....	63
Verifying the Server Installation.....	64
Installing Micro Focus Net Express for Windows.....	65
Understanding the Net Express Installation.....	65
Prerequisites.....	65
Installing Net Express.....	65
Installing Micro Focus Server Express for UNIX and Linux.....	65
Understanding Micro Focus Server Express.....	66
Prerequisites.....	66
Installing Server Express.....	67
Installing Remotely.....	74
Mounting and Unmounting CD-ROMs.....	75

## Chapter 4

<b>Using the PeopleSoft Installer.....</b>	<b>77</b>
Understanding the PeopleSoft Installer.....	77
Defining the PeopleSoft Installer.....	77
Understanding PeopleSoft Servers.....	78
Defining Supported Server Combinations.....	78
Prerequisites.....	79
Using E-Delivery for the PeopleSoft Installation.....	80
Mounting and Unmounting CD-ROMs (UNIX Only).....	80
Understanding CD-ROM Mounting and Unmounting.....	81
Mounting a CD-ROM on HP-UX.....	81
Unmounting a CD-ROM.....	82
Running the PeopleSoft Installer with a Single CD-ROM Drive (Optional).....	82
Running the PeopleSoft Installer Without Swapping CDs (Optional).....	83

Running the PeopleSoft Installer.....	84
Understanding the PeopleSoft Installer.....	84
Starting the PeopleSoft Installer.....	85
Running the PeopleSoft Installer in GUI Mode.....	86
Running the PeopleSoft Installer in Console Mode.....	88
Installing the Application CD.....	91
Loading the Multilanguage CD.....	92

## Chapter 5

<b>Setting Up the Windows File Server.....</b>	<b>95</b>
Understanding the File Server.....	95
Mapping a Drive on the Install Workstation.....	96
Installing the PeopleTools CD to the File Server.....	97
Installing the Application CD.....	99
Loading the Multilanguage CD.....	100

## Chapter 6

<b>Setting Up the Install Workstation.....</b>	<b>101</b>
Understanding the Install Workstation.....	101
Prerequisites.....	101
Starting Configuration Manager.....	102
Setting Startup Options.....	102
Editing the Default Profile.....	103
Running Client Setup.....	104

## Chapter 7A

<b>Creating a Database on Windows.....</b>	<b>107</b>
Understanding the Database Configuration Wizard.....	107
Fulfilling PeopleSoft Database Configuration Wizard Prerequisites.....	108
Installing the PeopleSoft Database Server Components on the Database Server.....	108
Obtaining Windows Administrator Authority.....	109
Meeting the Minimum Memory Requirements .....	109
Installing the Oracle RDBMS Software.....	109
Creating an INIT<SID>.ORA File.....	109
Creating Target Directory Paths.....	110
Setting Up Target Database Connectivity.....	112
Update Connection Information on the Server.....	112



Unsetting the ORACLE_SID Environment Variable.....	112
Running the Database Configuration Wizard.....	113
Checking the Log Files and Troubleshooting.....	121
Checking the Log Files.....	121
Troubleshooting.....	121
Optimizing for Performance.....	123
Updating Database to Latest PeopleTools Release.....	124
Understanding Database Updates.....	125
Cleaning Up Data.....	126
Updating PeopleTools System Tables.....	126
Updating PeopleTools Database Objects.....	128
Updating PeopleTools Multilingual Objects.....	130
Deleting Obsolete PeopleTools Database Objects.....	132
Altering PeopleTools Tables.....	134
Migrating Records to New Tablespaces.....	138
Updating PeopleTools System Data.....	143
Running PeopleTools Conversions.....	145
Converting Integration Broker.....	148
Changing the User Interface.....	150
Running Additional Data Mover Scripts.....	151
Installing a Multilingual PeopleTools System Database.....	151
Understanding the Multilingual Database Project.....	151
Applying the Multilingual Database Project.....	152
Populating the Translated System Data.....	152
Running VERSION Application Engine Program.....	152
Running SQR Reports.....	153
Running SQRs on the Client Workstation.....	153
Creating a Shortcut to Run SQRs .....	154
Checking the Database.....	155
Running SETSPACE.SQR.....	156
Running Alter Audit.....	157

## Chapter 7B

<b>Creating a Database on UNIX.....</b>	<b>163</b>
Understanding the Database Configuration Wizard.....	163
Fulfilling PeopleSoft Database Configuration Wizard Prerequisites.....	164
Installing the PeopleSoft Database Server Components on the Database Server.....	164
Installing the Oracle RDBMS Software.....	165
Creating an INIT<SID>.ORA File.....	165

Creating Target Directory Paths.....	166
Setting Up Target Database Connectivity.....	168
Update Connection Information on the Server.....	168
Running the Shell Script psconfig.sh.....	168
Setting the ORACLE_SID Environment Variable.....	168
Running the Database Configuration Wizard.....	169
Checking the Log Files and Troubleshooting.....	184
Checking the Log Files.....	184
Troubleshooting.....	184
Optimizing for Performance.....	188
Updating Database to Latest PeopleTools Release.....	188
Understanding Database Updates.....	189
Cleaning Up Data.....	190
Updating PeopleTools System Tables.....	190
Updating PeopleTools Database Objects.....	192
Updating PeopleTools Multilingual Objects.....	194
Deleting Obsolete PeopleTools Database Objects.....	196
Altering PeopleTools Tables.....	198
Migrating Records to New Tablespaces.....	202
Updating PeopleTools System Data.....	207
Running PeopleTools Conversions.....	209
Converting Integration Broker.....	212
Changing the User Interface.....	214
Running Additional Data Mover Scripts.....	215
Installing a Multilingual PeopleTools System Database.....	215
Understanding the Multilingual Database Project.....	215
Applying the Multilingual Database Project.....	216
Populating the Translated System Data.....	216
Running VERSION Application Engine Program.....	216
Running SQR Reports.....	217
Running SQRs on the Client Workstation.....	217
Creating a Shortcut to Run SQRs .....	218
Checking the Database.....	219
Running SETSPACE.SQR.....	220
Running Alter Audit.....	221

## Chapter 8A

<b>Configuring the Application Server on Windows.....</b>	<b>227</b>
Understanding the Application Server.....	227

Prerequisites.....	228
Setting Up COBOL for Remote Call.....	228
Verifying Database Connectivity.....	229
Creating, Configuring, and Starting an Initial Application Server Domain.....	229
Creating, Configuring, and Starting the Application Server Domain.....	229
Testing the Three-Tier Connection.....	232
Importing an Existing Application Server Domain Configuration.....	232
Setting Up a Custom Application Server Domain Configuration.....	234
Troubleshooting Common Errors.....	236
Configuring Fonts for Languages.....	237
Configuring Asian Language Fonts.....	237

## Chapter 8B

<b>Configuring the Application Server on UNIX.....</b>	<b>239</b>
Understanding the Application Server.....	239
Understanding the Application Server Domain Processes.....	240
Prerequisites.....	241
Setting Environment Variables.....	241
Setting Up COBOL for Remote Call.....	242
Verifying Database Connectivity.....	242
Creating, Configuring, and Starting an Initial Application Server Domain.....	242
Creating, Configuring, and Starting the Application Server Domain.....	243
Testing the Three-Tier Connection.....	245
Importing an Existing Application Server Domain Configuration.....	246
Setting Up a Custom Application Server Domain Configuration.....	248
Troubleshooting Common Errors.....	249
Configuring Fonts for Languages.....	250
Configuring Asian Language Fonts.....	250
Installing TrueType Fonts for Tru64 UNIX.....	251

## Chapter 9A

<b>Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode.....</b>	<b>253</b>
Understanding PeopleSoft Pure Internet Architecture.....	253
Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation.....	255
Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server in GUI Mode.....	256
Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server.....	256
Uninstalling the PeopleSoft Pure Internet Architecture from Oracle Application Server.....	266
Installing the PeopleSoft Pure Internet Architecture on WebLogic in GUI Mode.....	266

Installing the PeopleSoft Pure Internet Architecture on WebSphere.....	274
Prerequisites.....	274
Installing the PeopleSoft Pure Internet Architecture on WebSphere.....	275
Uninstalling the PeopleSoft Pure Internet Architecture from WebSphere.....	281
Encrypting the Password (AIX Only).....	281
Testing the PeopleSoft Pure Internet Architecture Installation.....	282
Starting and Stopping Oracle Application Server.....	282
Starting and Stopping WebLogic.....	283
Starting WebSphere.....	283
Accessing the PeopleSoft Signon.....	284
Updating Database Information.....	285
Updating PeopleTools Options.....	286

## Chapter 9B

<b>Setting Up the PeopleSoft Pure Internet Architecture in Console Mode.....</b>	<b>287</b>
Understanding PeopleSoft Pure Internet Architecture.....	287
Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation.....	289
Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server in Console Mode.....	290
Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server.....	290
Uninstalling the PeopleSoft Pure Internet Architecture from Oracle Application Server.....	294
Installing the PeopleSoft Pure Internet Architecture on WebLogic in Console Mode.....	294
Installing the PeopleSoft Pure Internet Architecture on WebSphere in Console Mode.....	299
Prerequisites.....	299
Installing the PeopleSoft Pure Internet Architecture on WebSphere.....	300
Uninstalling the PeopleSoft Pure Internet Architecture from WebSphere.....	303
Encrypting the Password (AIX Only).....	304
Testing the PeopleSoft Pure Internet Architecture Installation.....	304
Starting and Stopping Oracle Application Server.....	304
Starting and Stopping WebLogic.....	305
Starting WebSphere.....	306
Accessing the PeopleSoft Signon.....	306
Updating Database Information.....	307
Updating PeopleTools Options.....	308

## Chapter 10A

<b>Setting Up Process Scheduler on Windows.....</b>	<b>309</b>
Prerequisites.....	309

Setting Up Process Scheduler Security.....	310
Understanding Process Scheduler Security.....	310
Changing User Account to Start BEA ProcMGR V8.1 .....	310
Granting Process Scheduler Administrative Rights.....	312
Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository.....	313
Understanding Report Distribution.....	314
Setting Up Single Signon to Navigate from PIA to Report Repository.....	315
Determining the Transfer Protocol.....	316
Starting the Distribution Agent.....	316
Setting Up the Report Repository.....	316
Setting Up the Distribution for Your Process Scheduler Server.....	322
Setting Up Sending and Receiving of Report Folders in the Report Manager.....	323
Setting Environment Variables.....	324
Setting Up Process Scheduler Server Agent.....	324
Understanding Process Scheduler Server Agent.....	324
Creating and Configuring a Process Scheduler Server.....	325
Reconfiguring a Process Scheduler Server.....	328
Verifying the Process Scheduler Server Status.....	329
Starting Process Scheduler as a Windows Service (Optional).....	331
Configuring the Process Scheduler for Word for Windows (Optional).....	334
Configuring Setup Manager.....	334

## **Chapter 10B**

<b>Setting Up Process Scheduler on UNIX.....</b>	<b>337</b>
Prerequisites.....	337
Setting Up Process Scheduler Security.....	338
Understanding Process Scheduler Security.....	338
Granting Process Scheduler Administrative Rights.....	338
Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository.....	339
Understanding Report Distribution.....	340
Setting Up Single Signon to Navigate from PIA to Report Repository.....	341
Determining the Transfer Protocol.....	342
Starting the Distribution Agent.....	342
Setting Up the Report Repository.....	342
Setting Up the Distribution for Your Process Scheduler Server.....	347
Setting Up Sending and Receiving of Report Folders in the Report Manager.....	348
Setting Up Process Scheduler Server Agent.....	348
Understanding Process Scheduler Server Agent.....	348
Changing the Default Operating System.....	349

Setting Up Your Environment.....	349
Creating and Configuring a Process Scheduler Server.....	350
Reconfiguring a Process Scheduler Server.....	354
Verifying the Process Scheduler Server Status.....	355

## Chapter 11

<b>Installing and Configuring Software for Crystal Reports.....</b>	<b>357</b>
Understanding Crystal Reports Software Installation and Configuration.....	357
Determining the Crystal Reports Runtime Environment.....	359
Installing Crystal Reports 9.....	360
Understanding the Crystal Reports 9 Installation.....	360
Installing Crystal Reports 9.....	360
Installing BusinessObjects Enterprise XI.....	361
Understanding the BusinessObjects Enterprise XI Installation.....	362
Understanding Integration Between BusinessObjects Enterprise XI and PeopleSoft Enterprise.....	366
Understanding Query Access Services.....	368
Reviewing Key BusinessObjects Enterprise XI Components.....	370
Planning your BusinessObjects Enterprise XI Integration.....	370
Installing the PeopleSoft Application Environment.....	372
Installing BusinessObjects Enterprise XI on Windows.....	372
Installing BusinessObjects Enterprise XI Integration on Windows.....	380
Installing Patches Required at Installation Time.....	383
Creating a Web Server for BusinessObjects Enterprise XI on Windows.....	383
Installing BusinessObjects Enterprise XI on UNIX or Linux.....	399
Installing PeopleSoft BusinessObjects Enterprise XI Integration on UNIX or Linux.....	401
Installing Patches Required at Installation.....	404
Creating a Web Server for BusinessObjects Enterprise on UNIX or Linux.....	404
Confirming Access to the BusinessObjects Enterprise XI Administration and User Launchpad Applications.....	416
Configuring the PeopleSoft Application for BusinessObjects Enterprise XI Integration.....	418
Configuring the BusinessObjects Enterprise XI Server.....	427
Verifying the PeopleSoft to BusinessObjects Enterprise XI Integration.....	431
Migrating your BusinessObjects Enterprise XI Installation to a New Version of PeopleTools.....	432
Installing Crystal Reports XI.....	433
Removing Crystal Reports XI.....	436
Administering and Using BusinessObjects Enterprise XI.....	437
Understanding PeopleSoft Permission Lists, Roles, and Users Involved in PeopleSoft Integration with BusinessObjects Enterprise XI.....	437
Installing Patches.....	439

Changing the Data Source of the BusinessObjects Enterprise XI Report Repository.....	439
Uninstalling BusinessObjects Enterprise XI Integration.....	441
Switching to Crystal 9 from BusinessObjects Enterprise XI.....	445
Using Logging in BusinessObjects Enterprise XI.....	445
Understanding BusinessObjects Enterprise XI License Codes.....	448
Converting Crystal Reports.....	451
Selecting the Crystal Reports Conversion Method.....	451
Converting pre-PeopleTools 8 Crystal Reports to PeopleTools 8 Crystal Reports.....	452
Converting Reports from Crystal Reports 9 Format to Crystal Reports XI Format.....	454

## Chapter 12A

<b>Compiling COBOL on Windows.....</b>	<b>469</b>
Understanding COBOL.....	469
Prerequisites.....	469
Compiling COBOL Source Files.....	470
Understanding COBOL Compilation.....	470
Compiling COBOL with CBLBLD.BAT.....	470
Compiling COBOL with CBLMAKE.BAT.....	471
Defining the GNT and INT Files.....	473
Distributing COBOL Binaries.....	473

## Chapter 12B

<b>Compiling COBOL on UNIX.....</b>	<b>475</b>
Understanding COBOL.....	475
Prerequisites.....	475
Setting Environment Variables.....	476
Modifying the Liblist (IBM AIX 5.1, IBM AIX 5.2, and HP-UX Only).....	476
Understanding Liblist Modifications.....	477
Modifying the Liblist File.....	477
Compiling COBOL Programs.....	478
Understanding COBOL Compilation.....	478
Compiling COBOL on UNIX.....	478
Linking COBOL.....	479
Understanding COBOL Linking.....	479
Linking COBOL Components on UNIX.....	480
Recompiling COBOL on UNIX.....	480

## Chapter 13

<b>Installing PeopleSoft Change Assistant.....</b>	<b>483</b>
Understanding PeopleSoft Change Assistant.....	483
Installing and Configuring PeopleSoft Change Assistant.....	483
Installing PeopleSoft Change Assistant.....	484
Setting Up Security for Change Assistant.....	485
Scanning the Workstation.....	486
Specifying Options.....	486
Specifying Change Assistant Options.....	486
Setting Email Options.....	487
Setting Up Web Services Options.....	487
Setting Environment Management Options.....	488
Exporting Jobs to XML, HTML, or Microsoft Excel Format.....	489
Validating Change Assistant Settings.....	489

## Chapter 14

<b>Installing PeopleSoft Change Impact Analyzer.....</b>	<b>493</b>
Prerequisites.....	493
Installing Change Impact Analyzer.....	493

## Appendix A

<b>Adding New Product Modules.....</b>	<b>497</b>
Adding New Module(s) to PeopleSoft 8.4 Installations.....	497

## Appendix B

<b>Installing PeopleBooks.....</b>	<b>499</b>
Understanding PeopleBooks.....	499
Installing PeopleBooks.....	499
Prerequisites.....	500
Installing the PeopleBooks CD.....	500
Implementing the PSOL Server for PeopleBooks.....	502
Understanding PeopleBooks in the PeopleSoft Pure Internet Architecture.....	503
Starting Oracle Application Server Components.....	503
Creating the PSOL Server on WebSphere with Existing 8.4x PeopleSoft Pure Internet Architecture.....	504
Managing the PSOL Server on WebLogic or WebSphere.....	505
Setting up a Reverse Proxy Server.....	507



Configuring Context-Sensitive Help.....	507
Enabling the Help Link from the Application Pages.....	507
Enabling F1 Help.....	508
Administering PeopleBooks.....	509

## Appendix C

<b>Installing PeopleTools Mobile Agent.....</b>	<b>511</b>
Understanding PeopleTools Mobile Agent.....	511
Finding the Installation Program.....	511
Installing PeopleTools Mobile Agent on a Laptop.....	512
Installing PeopleTools Mobile Agent on a PDA.....	513
Modifying, Repairing, or Removing PeopleTools Mobile Agent.....	514
Expediting the Initialization of a PDA.....	514
Troubleshooting Installation Issues.....	515
Resolving Port Conflicts.....	515
Configuring the Web Server.....	515

## Appendix D

<b>Installing Web Application Deployment Tools.....</b>	<b>517</b>
Prerequisites.....	517
Installing the Web Application Deployment Tools on Oracle Application Server in GUI Mode.....	518
Installing the Web Application Deployment Tools on WebLogic in GUI Mode.....	524
Installing the Web Application Deployment Tools on WebSphere in GUI Mode.....	529
Installing the Web Application Deployment Tools on Oracle Application Server in Console Mode.....	534
Installing the Web Application Deployment Tools on WebLogic in Console Mode.....	536
Installing the Web Application Deployment Tools on WebSphere in Console Mode.....	540
Testing and Troubleshooting the Web Application Deployment.....	543

## Appendix E

<b>Creating a Database Manually on Windows.....</b>	<b>545</b>
Understanding Database Creation.....	546
PeopleSoft Database Installation Prerequisites.....	546
Installing the PeopleSoft Database Server Components on the Database Server.....	546
Installing the Oracle RDBMS Software.....	547
Obtaining Windows Administrator Authority.....	547
Creating an INIT<SID>.ORA File.....	547
Creating Target Directory Paths.....	548

Setting the ORACLE_SID Environment Variable.....	549
Creating the Windows Service for the Database Instance.....	550
Editing Database Scripts.....	551
Understanding Database Scripts.....	551
Modifying Database Scripts.....	551
Using SQL Tools.....	552
Creating an Oracle Instance.....	552
Creating Catalog Views and Utility Tablespaces.....	553
Creating PS.PSDBOWNER Table.....	553
Creating Application-Specific Dbspaces and Tablespaces.....	554
Creating PeopleSoft Database Roles.....	554
Creating the PeopleSoft Database Owner ID.....	555
Setting Up Connect ID.....	555
Understanding Connect ID.....	555
Defining the Connect ID.....	556
Creating the Connect ID.....	556
Updating Connection Information.....	556
Updating Connection Information on the Client.....	557
Updating Connection Information on the Server.....	557
Setting NLS_LANG in the Windows Registry.....	557
Creating Data Mover Import Scripts.....	558
Running Data Mover Import Scripts.....	563
Understanding Data Mover Import Scripts.....	563
Populating Tables in the PeopleSoft Database.....	563
Validating Files.....	564
Troubleshooting.....	564
Improving Performance.....	566
Updating Database to Latest PeopleTools Release.....	566
Understanding Database Updates.....	567
Cleaning Up Data.....	568
Updating PeopleTools System Tables.....	568
Updating PeopleTools Database Objects.....	570
Updating PeopleTools Multilingual Objects.....	572
Deleting Obsolete PeopleTools Database Objects.....	574
Altering PeopleTools Tables.....	576
Migrating Records to New Tablespaces.....	580
Updating PeopleTools System Data.....	585
Running PeopleTools Conversions.....	587
Converting Integration Broker.....	590
Changing the User Interface.....	592

Running Additional Data Mover Scripts.....	593
Installing a Multilingual PeopleTools System Database.....	593
Understanding the Multilingual Database Project.....	593
Applying the Multilingual Database Project.....	594
Populating the Translated System Data.....	594
Running VERSION Application Engine Program.....	594
Changing the Base Language.....	595
Running SQR Reports.....	595
Running SQRs on the Client Workstation.....	595
Creating a Shortcut to Run SQRs .....	597
Checking the Database.....	597
Running SETSPACE.SQR.....	598

## Appendix F

<b>Creating a Database Manually on UNIX.....</b>	<b>601</b>
Understanding Database Creation.....	602
Editing Database Scripts.....	602
Understanding Database Scripts.....	602
Modifying Database Scripts.....	602
Creating an Oracle Instance.....	604
Using SQL Tools.....	605
Setting NLS_LANG in the Windows Registry.....	606
Creating an Oracle Database.....	607
Creating Catalog Views and Utility Tablespaces.....	607
Creating PS.PSDBOWNER Table.....	608
Creating Application-Specific Dbspaces and Tablespaces.....	608
Creating PeopleSoft Database Roles.....	609
Creating the PeopleSoft Database Owner ID.....	609
Setting Up Connect ID.....	609
Understanding Connect ID.....	610
Defining the Connect ID.....	610
Creating the Connect ID.....	610
Updating Connection Information.....	611
Updating Connection Information on the Client.....	611
Updating Connection Information on the Server.....	611
Creating Data Mover Import Scripts.....	611
Running Data Mover Import Scripts.....	616
Understanding Data Mover Import Scripts.....	616
Populating Tables in the PeopleSoft Database.....	616

Validating Files.....	617
Troubleshooting.....	617
Improving Performance.....	619
Updating Database to Latest PeopleTools Release.....	619
Understanding Database Updates.....	620
Cleaning Up Data.....	621
Updating PeopleTools System Tables.....	621
Updating PeopleTools Database Objects.....	623
Updating PeopleTools Multilingual Objects.....	625
Deleting Obsolete PeopleTools Database Objects.....	627
Altering PeopleTools Tables.....	629
Migrating Records to New Tablespaces.....	633
Updating PeopleTools System Data.....	638
Running PeopleTools Conversions.....	640
Converting Integration Broker.....	643
Changing the User Interface.....	645
Running Additional Data Mover Scripts.....	646
Installing a Multilingual PeopleTools System Database.....	646
Understanding the Multilingual Database Project.....	646
Applying the Multilingual Database Project.....	647
Populating the Translated System Data.....	647
Running VERSION Application Engine Program.....	647
Changing the Base Language.....	648
Running SQR Reports.....	648
Running SQRs on the Client Workstation.....	648
Creating a Shortcut to Run SQRs .....	650
Checking the Database.....	650
Running SETSPACE.SQR.....	651

## Appendix G

<b>Relinking SQR on UNIX.....</b>	<b>653</b>
Understanding SQR Relinking.....	653
Relinking SQR on UNIX.....	653
Relinking SQR on HP-UX.....	654

## Appendix H

<b>Securing the Report Repository for HTTP.....</b>	<b>659</b>
Setting Up Security in the Web Server.....	659

Understanding Web Server Security.....	659
Setting Up Basic Authentication in Oracle Application Server.....	659
Setting Up Basic Authentication in WebLogic.....	664
Setting Up Basic Authentication in WebSphere.....	664
Updating the Report Node Definition.....	667

## **Appendix I**

<b>Using the XSLT Mapper with Oracle BPEL Process Manager.....</b>	<b>669</b>
Understanding the XSLT Mapper.....	669
Installing BPEL Process Manager.....	669
Setting Up the XSLT Mapper.....	670

## **Appendix J**

<b>Setting Up the PeopleSoft Installation with Oracle 10g RAC.....</b>	<b>671</b>
Understanding the PeopleSoft Installation on Oracle 10g RAC.....	671
Prerequisites.....	671
Setting Up the Database.....	672
Understanding the Database Setup.....	672
Creating Raw Devices.....	672
Editing the CREATEDB10.SQL Script.....	673
Editing the UTLSPACE.SQL Script.....	674
Editing the XXDDL Script.....	675
Creating Initialization Files.....	675
Configuring Database Security.....	676
Configuring the Tnsnames and Listener Files.....	676
Configuring the Application Server.....	678

<b>Index .....</b>	<b>679</b>
--------------------	------------



# About This Documentation

This preface discusses:

- Audience
- Products Referenced in this Book
- Related Publications

---

**Note.** This book is designed to direct you through a basic PeopleSoft installation. It is not a substitute for the database administration manuals provided by your RDBMS vendor, the network administration manuals provided by your network vendor, or the installation and configuration manuals for additional software components used with PeopleSoft.

---

---

**Note.** Required updates to this installation documentation are provided in the form of “Required at Install” incidents, available on PeopleSoft Customer Connection. In addition, *application-specific installation steps are provided in a separate document specific to the application.* For instance, if you are performing Oracle’s PeopleSoft CRM installation, you need both this PeopleTools installation guide and any additional instructions provided by CRM. To find the installation documentation specific to your application, go to Customer Connection, choose *Site Index*, the letter *I*, *Installation Guides and Notes*, and then look under the subcategory for your particular application.

---

---

**Note.** Before proceeding with your installation, check PeopleSoft Customer Connection to ensure that you have the latest version of this installation guide for the correct version of PeopleTools.

---

## Audience

This book is written for the individuals responsible for installing and administering the PeopleSoft environment. We assume that you are familiar with your operating environment and RDBMS and that you have the necessary skills to support that environment. You should also have a working knowledge of SQL. We recommend that you have completed at least one PeopleSoft introductory training course (particularly the Server Administration and Installation course) and have a basic understanding of the PeopleSoft System. Probably the most important component in the installation and maintenance of your PeopleSoft system is your onsite expertise. Only qualified and experienced individuals should attempt to install PeopleSoft. If you have any doubts as to whether your onsite staff is capable of successfully completing an installation, contact your PeopleSoft representative.

---

## Products Referenced in this Book

This installation guide refers to these products:

- Oracle’s PeopleSoft Enterprise PeopleTools, referred to as PeopleTools
- Oracle’s PeopleSoft Enterprise products, referred to as PeopleSoft
- Oracle’s PeopleSoft Pure Internet Architecture
- Oracle’s PeopleSoft Change Assistant

- Oracle's PeopleSoft Change Impact Analyzer
- Oracle Application Server
- Oracle Enterprise Manager
- Oracle BPEL Process Manager
- Applications such as Oracle's PeopleSoft Enterprise Human Capital Management and Oracle's PeopleSoft Enterprise Customer Relationship Management

See All PeopleSoft Enterprise Products on Oracle's web site, [http://www.oracle.com/applications/peoplesoft/all\\_ent\\_products.html](http://www.oracle.com/applications/peoplesoft/all_ent_products.html)

---

## Related Publications

To install additional component software products for use with PeopleSoft, including those products that are packaged with your PeopleSoft shipment, you should refer to the documentation provided with those products as well as this documentation.

For reference information on PeopleTools, you may wish to consult the following books:

- *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*: This includes information on configuring the PeopleSoft application server and supported web servers, data integrity tools, database level auditing, and PeopleTools utilities, including Configuration Manager.
- *Enterprise PeopleTools 8.48 PeopleBook: Security Administration*: This includes information on setting up and modifying user access to PeopleSoft applications, and defines the various IDs and passwords used in installation.
- *Enterprise PeopleTools 8.48 PeopleBook: Data Management*: This includes information on PeopleSoft administrative utilities, such as Data Mover, Data Archive Manager, and so on.
- *Enterprise PeopleTools 8.48 PeopleBook: PeopleCode Language Reference*: This includes reference information on the PeopleCode language, such as built-in functions, classes, meta-SQL, system variables, and so on.
- *Enterprise PeopleTools 8.48 PeopleBook: PeopleCode Developer's Guide*: This includes general information about the PeopleCode editor, the Component Processor, the data buffers, and how to use specific functions and classes.
- *Reporting and Analysis Tools*: For information on PeopleSoft's reporting and analysis tools, see the Enterprise PeopleTools 8.48 PeopleBooks on Crystal Reports for PeopleSoft, PS/nVision, PeopleSoft Query, PeopleSoft Tree Manager, PeopleSoft Process Scheduler, and PeopleSoft Cube Manager.
- *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Application Designer*: This includes information about the main tool for developing PeopleTools applications.
- *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*: This includes information on the role of PeopleTools in the globalization of PeopleSoft applications.
- *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Application Engine*: This includes information on the PeopleSoft proprietary batch programming tool.

For information on a tool to help you write transformation Application Engine programs see the appendix "Using XSLT Mapper with Oracle BPEL Process Manager."



For reference information on your particular application, refer to the documentation for your application.



# CHAPTER 1

## Preparing for Installation

This chapter discusses:

- Understanding the PeopleSoft Installation
- Assembling Related Documentation
- Verifying Hardware and Software Requirements
- Considering Project Planning
- Planning Your Initial Configuration
- Planning Database Creation
- Planning Multilingual Strategy
- Reviewing Updates and Fixes Required at Installation
- Installing Supporting Applications
- Installing the Database Engine
- Installing Oracle Net on the Server
- Installing Oracle Net on Your Workstation
- Testing Oracle Net Connectivity
- Performing Backups
- Using PeopleSoft Change Assistant and PeopleSoft Change Impact Analyzer

---

## Understanding the PeopleSoft Installation

This chapter will help you plan and prepare for a basic PeopleSoft installation. Before you begin the installation, please note:

- If you will be upgrading your current release after you perform this installation, you also need to install the Upgrade Assistant or Change Assistant. The upgrade page on PeopleSoft Customer Connection includes information on which tool you need.
- For critical issues related to the installation process, see the PeopleSoft Customer Connection web site. Be sure to read the “Required for Installation or Upgrade” incidents for the PeopleTools version that you are installing.
- For online, interactive technical support information, use the Oracle Metalink web site.

See Oracle Metalink, <https://metalink.oracle.com>

- To download software and documentation, use the Oracle Technology Network.  
See Oracle Technology Network, <http://www.oracle.com/technology/index.html>
- This installation guide may refer you to PeopleBooks for more information or instructions. If you install PeopleBooks to your web server, you can easily refer to the documentation during the installation process.

## See Also

“Installing PeopleBooks”

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Upgrade Assistant*

*Enterprise PeopleTools 8.48 PeopleBook: Software Updates*

“Installing PeopleSoft Change Assistant”

---

## Task 1-1: Assembling Related Documentation

Before you begin your installation, you should have the following documentation ready for reference:

- Locate the supplemental installation documentation for any PeopleSoft applications that you plan to install.  
Be sure to use both the PeopleTools Installation Guide for your database platform *and* the supplemental application installation instructions. (For example, if you are installing CRM, you need to have the PeopleTools Installation Guide for the appropriate PeopleTools release and the supplemental CRM installation instructions.) The application installation instructions are available on Customer Connection.
- Locate the database administration manuals provided by your RDBMS vendor, the network administration manuals provided by your network vendor, and the installation and configuration manuals for additional software components used with PeopleSoft.
- For administration information regarding your database platform, please refer to the relevant appendix in the following PeopleBook.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*.

---

## Task 1-2: Verifying Hardware and Software Requirements

Before you install PeopleSoft you must verify that you have the correct hardware and software in place to support a successful installation.

---

**Warning!** If you are unable to meet any of the criteria outlined in the Enterprise PeopleTools 8.48 Hardware and Software Requirements documentation and Supported Platforms on PeopleSoft Customer Connection, contact PeopleSoft before going forward with the installation. Attempting to complete an installation on an unsupported configuration can be a *very* costly decision, and PeopleSoft will not provide support for such installations.

---

Use the following sources of information on currently supported hardware and software:

- The Enterprise PeopleTools 8.48 Hardware and Software Requirements book provides an overview of PeopleSoft architecture, as well as general information on the hardware and software required for a successful installation.

This book is a snapshot of supported configurations; it does not provide up-to-the-minute information on supported maintenance releases or required patches. Be sure to check Supported Platforms on PeopleSoft Customer Connection (discussed next) to verify time-sensitive information, such as supported versions of additional software components used with PeopleTools. To find the hardware and software requirements guide, sign on to PeopleSoft Customer Connection, select Site Index, select the letter H, select the entry hardware and software requirements, and then select PeopleTools.

- Supported Platforms on PeopleSoft Customer Connection provides the most current support information on hardware platforms, RDBMS versions, client connectivity versions, required compiler versions, and additional component versions.

The information in this database supplements and supersedes any information in the Enterprise PeopleTools 8.48 Hardware and Software Requirements book. To go to Supported Platforms, sign on to PeopleSoft Customer Connection, and select the link Implement, Optimize + Upgrade. Then select Implementation Guide, Supported Platforms, PeopleSoft Enterprise.

- Before you begin your installation, read the version of the document "Required Operating System, RDBMS & Additional Component Patches Required for Installation" that is appropriate for your database platform and other configuration.

See "Required Operating System, RDBMS & Additional Component Patches Required for Installation," PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise.)

---

## Task 1-3: Considering Project Planning

Identify the maintenance schedule for upcoming PeopleTools and application releases. These releases are typically on a regular schedule (for example, quarterly, biannually) and should be included in your project planning and budgeting processes. Release dates are posted on Customer Connection. It is important to plan regular maintenance in your overall project plans. For example, for a year-long enterprise upgrade, development, and conversion project, make sure to set aside time for applying the PeopleTools minor releases that ship during that time frame. Otherwise, if you fall behind, you may find that you need a fix shipped with one of the minor releases that cannot be backported as a patch.

---

## Task 1-4: Planning Your Initial Configuration

This section discusses:

- Understanding Workstations
- Defining the File Server
- Defining the Database Server
- Defining the Application Server
- Defining the Batch Server

- Defining the Web Server
- Using Laser Printers

---

**Note.** COBOL is not needed for PeopleTools or for applications that contain no COBOL programs. Check Supported Platforms on Customer Connection for details about whether your application requires COBOL.

---

See “PeopleSoft Application COBOL Requirements,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise, By PeopleTools release, Platform Communications by Topic, Batch).

## Understanding Workstations

This section discusses:

- Using the PeopleTools Development Environment (Windows-Based Clients)
- Using Workstations Equipped with Supported Web Browsers

---

**Note.** With the PeopleSoft Pure Internet Architecture, Windows-based clients are primarily used as a development environment. End users can use any machine equipped with a supported web browser.

---

### Using the PeopleTools Development Environment (Windows-Based Clients)

Windows-based clients are now called the PeopleTools Development Environment. These clients—which run on Windows XP and Windows Server 2003—can connect to the PeopleSoft database directly using client connectivity software (a two-tier connection) or through a PeopleSoft application server (a three-tier connection).

Three-tier connectivity offers great performance advantages over two-tier (especially over a WAN), reduces network traffic, and generally does not require that you install database connectivity on the client. However, any Windows-based clients that will be running Data Mover scripts against the database, or running COBOL or Structured Query Report (SQR) batch processes on the client, must have database connectivity installed.

You need to have the PeopleTools Development Environment set up to create your database. For more information on setting up the PeopleTools Development Environment, refer to the following PeopleBook.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Using PeopleSoft Configuration Manager.”

For installation purposes, you must set up at least one Windows-based client for sign-on using a two-tier connection to the database, so that it can create and populate the PeopleSoft database. This documentation refers to this client as the install workstation. Depending on your installation plan, you may want to set up more than one install workstation so that you can perform asynchronous installation tasks in parallel.

---

**Note.** The Windows machine that you use to perform your PeopleTools installation must be running in 256-color mode or higher when running the CD install, Internet install, and Database configuration in Windows. This is not necessary for UNIX or console mode.

---

### Using Workstations Equipped with Supported Web Browsers

To run the PeopleSoft Pure Internet Architecture, the client workstation only needs a web browser that is HTML 4.0 compliant. You may need an additional workstation for demonstration and testing purposes if you plan to use a browser running on a platform other than Windows—such as Macintosh or UNIX.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

## Task 1-4-1: Defining the File Server

The file server is the environment (or file) repository for the PeopleTools Development Environment, which is needed for the Database Configuration Wizard. The file server is also the repository for the files necessary to perform an upgrade. This includes Upgrade Assistant or Change Assistant, and all of the executables and scripts that are necessary to perform an upgrade. In addition, the file server is a source repository for COBOL and SQR (you will apply patches and updates from Customer Connection directly to the file server and then copy the updated files to your other servers).

---

**Important!** Remember, a COBOL compiler is not needed for PeopleTools unless your application contains COBOL programs. If your application requires COBOL and you're running on Windows, we require that you maintain a central repository of your COBOL source code on the Windows file server.

---

See the following task later in this chapter for details on where you should install your COBOL compiler.

See Installing Supporting Applications.

If you follow the default procedures recommended in this documentation, the install workstations, Windows batch servers, and Windows report servers will access the PeopleSoft files on the file server by pointing to a directory conventionally referred to as <PS\_HOME> on a shared network drive. You can install SQR and Crystal Reports on the file server, or install them locally on Windows batch servers and on Windows-based clients that will be running these processes locally.

## Task 1-4-2: Defining the Database Server

The servers that host your PeopleSoft databases need sufficient processing, storage, and networking resources to process the database requests, store the data and transaction logs, and communicate freely to the clients of this data. These databases will include your own PeopleSoft database prototypes as well as any system and demonstration databases delivered directly from PeopleSoft on the PeopleSoft CDs.

See Planning Database Creation.

Database sizes vary depending on the applications that you install. The size of your prototype PeopleSoft database will also depend on the amount of data to be converted from your legacy system. A good rule of thumb for estimating the size of your prototype PeopleSoft database is to estimate the amount of disk space needed for the data to be converted from your legacy system, add to this the size required for the PeopleSoft System database, and then add an additional 50 percent of this combined figure to allow for growth.

## Task 1-4-3: Defining the Application Server

The application server is the centerpiece of the PeopleSoft Pure Internet Architecture. It connects to the PeopleSoft database and handles almost all SQL-intensive interactions with the database server required during online transaction processing. Windows-based clients, in three-tier, communicate with the application server using Tuxedo messages. In the PeopleSoft Pure Internet Architecture, the application server interacts with user workstations through a web server.

The application server also provides functionality required for application messaging and for implementing the PeopleSoft Pure Internet Architecture. An application server is required in all PeopleSoft installations.

If you are installing on an Oracle for UNIX RDBMS, you can install the application server on the same machine as the database server, a configuration called *logical three-tier*. You can also install application servers on one or more separate UNIX or Windows machines. This configuration is called *physical three-tier*.

If you are installing on an Oracle for Windows RDBMS, you may use a Windows application server. This application server can be installed on the same machine as the Oracle database server, but for Windows installations you will most likely get better results by installing one or more dedicated application servers (that is, a physical three-tier configuration).

All application servers require database connectivity to the database server. Before beginning your installation, make sure that you can connect from the application server to the database server using a SQL client tool. This topic will be addressed later in this chapter.

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*

## Task 1-4-4: Defining the Batch Server

The term *batch server* is equivalent to the term *Process Scheduler server*. PeopleSoft batch processes, such as COBOL and SQR, are scheduled and invoked by a Process Scheduler server. In almost all configurations, batch server SQR and COBOL files are located and executed on the same computer as the database server.

With Oracle Windows databases, a Process Scheduler server running on the batch server may point to and invoke files that are physically located on the file server. With an Oracle UNIX database, the SQR and COBOL files must be installed to the batch server through the PeopleSoft Installer; and COBOL source files must be compiled.

PeopleSoft supports setting up the batch environments on a dedicated server, an application server, or even on the database server.

For Windows-specific batch processes—such as Crystal Reports, nVision reports, Microsoft Word, or Cube Manager—you need to set up a Windows batch environment on a Windows application server or on a dedicated Windows workstation.

Any computer operating as a batch server must have database connectivity installed so that it can make a two-tier connection to the PeopleSoft database.

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler.*

## Task 1-4-5: Defining the Web Server

A web server is required to run the PeopleSoft Pure Internet Architecture. The PeopleSoft Pure Internet Architecture is certified to work with either of the following three J2EE web application servers (also commonly referred to as web servers):

- Oracle Application Server
- BEA WebLogic Server
- IBM WebSphere Server

These web servers are supported on the following operating systems:

Oracle Application Server	BEA WebLogic Server	IBM WebSphere Server
Windows Server 2003	Windows Server 2003	Windows Server 2003



Oracle Application Server	BEA WebLogic Server	IBM WebSphere Server
HP-UX (Intel Itanium, PA-RISC 64-bit)	HP-UX (Intel Itanium, PA-RISC 64-bit)	HP-UX (PA-RISC 64-bit)
Solaris (64-bit SPARC)	Solaris	Solaris
Red Hat Linux Enterprise Server	Red Hat Linux Enterprise Server	Red Hat Linux Enterprise Server
SUSE Linux Enterprise Server	SUSE Linux Enterprise Server	SUSE Linux Enterprise Server
AIX	AIX	AIX
	Tru64	

In conjunction with BEA WebLogic and IBM WebSphere, PeopleSoft has also certified the use of the following HTTP servers as reverse proxy servers (RPS):

- With Oracle Application Server, Oracle/PeopleSoft supports the Oracle HTTP Server and Oracle Application Server Web Cache as reverse proxy servers.
- With BEA WebLogic, the certified HTTP servers are Microsoft IIS, iPlanet web server, Apache HTTP server, and BEA WebLogic Server.
- With IBM WebSphere, the certified HTTP servers are IBM HTTP Server (IHS), Microsoft IIS, and iPlanet web server.

WebLogic, WebSphere, and the above reverse proxy servers will provide out-of-the-box SSL support across all supported operating systems. WebLogic and WebSphere provide demo digital certificates, but for production grade SSL you must purchase digital certificates from a Certificate Authority supported by the web server that you are using (for example, Verisign, Baltimore, Entrust, and so on).

## Task 1-4-6: Using Laser Printers

Along with the printer you will need a Windows printer driver to print the online reports that produce 180-character-wide reports using the HP LinePrinter font. Your printer must be configured with sufficient memory (typically 1.5 MB) to produce graphics images for page printouts.

### See Also

Verifying Hardware and Software Requirements

*Enterprise PeopleTools 8.48 Hardware and Software Requirements*

Supported Platforms, PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise)

---

## Task 1-5: Planning Database Creation

This section discusses:

- Understanding Database Creation
- Determining Databases and Database Names

- Defining Oracle and PeopleSoft Databases

## Understanding Database Creation

When performing a PeopleSoft installation, you will create these types of PeopleSoft databases:

- System (also called SYS) databases, which contain the PeopleTools and product-specific metadata required for development of a production database.
- Demo (DMO) databases, which are populated with sample data for study, demonstration, or training purposes.

---

**Note.** To properly install a Demo database, you must select both the System Database and the Demo Database options during the installation of PeopleSoft applications.

---

It is important to note the distinction between an Oracle database and a PeopleSoft database, which is a set of SQL objects that reside within a single Oracle database and share the same owner ID. PeopleSoft recommends that you install only one PeopleSoft database per Oracle instance. For details, see the section “Defining Oracle and PeopleSoft Databases” later in this task.

If you are installing PeopleSoft on an Oracle 10g Real Application Cluster (RAC) database, you must use the manual procedure for database setup, and complete other configuration procedures.

See “Creating a Database Manually (on UNIX or Windows).”

See “Setting Up the PeopleSoft Installation with Oracle 10g RAC.”

---

**Note.** Before installing PeopleSoft, you should install the Oracle RDBMS software. This documentation does not cover installation of Oracle software. Please refer to the Oracle RDBMS installation documentation that accompanied your Oracle software for information.

---

### Task 1-5-1: Determining Databases and Database Names

Before you begin the installation process, you should determine how many PeopleSoft databases (System or Demo) of which type you need and how you intend to use them. You should also determine the names of the databases at this point, using database names that:

- Are limited to eight characters, all UPPERCASE.
- Capture information about the PeopleSoft product line and the type of database.

For example, you may want to create two databases with the names PSHRDMO and PSHRSYS, using the two characters HR (for Human Resources) to indicate the product line.

### Task 1-5-2: Defining Oracle and PeopleSoft Databases

An Oracle database is a set of SQL objects defined by one system catalog in the SYSTEM tablespace and one SID (system identifier), using one instance of the Oracle server executables and associated files. Within Oracle shops, the Oracle database is commonly referred to as the *Oracle SID*.

A PeopleSoft database is a set of SQL objects defined as having the same owner ID. These tables are always contained within a single Oracle database. A PeopleSoft database includes the PeopleSoft objects and application data for one or more products in a PeopleSoft product line.

This owner ID (an Oracle user ID) may also be referred to as an Oracle schema or Oracle logical database. Each PeopleSoft database needs its own owner. We refer to this as the *PeopleSoft owner ID*, which is also the PeopleSoft access ID.

We recommend that you install no more than one PeopleSoft database per Oracle instance. When each PeopleSoft database has its own instance, the system is more robust for the following reasons:

- Your developers can bring down their instance of the Oracle server executables, but the others will remain running.
- You have added security with one PeopleSoft database per Oracle instance.
- It is more efficient to tune each instance to the requirements of its corresponding PeopleSoft application database.

If you are unable to run extra Oracle database instances because of resource limitations, such as memory and system semaphores, you can install multiple PeopleSoft databases in the same Oracle instance. Keep the following points in mind if installing multiple PeopleSoft databases within one Oracle database instance:

- When supporting multiple databases in one Oracle instance, increase maxdatafiles from the default of 32 when you create the database.

Check the limits of maxdatafiles for your operating system and increase the value accordingly.

- You need to increase the size of the tablespaces if you use the same ones for each PeopleSoft database schema.

Sharing tablespaces is not recommended.

- Each PeopleSoft database should have different operator IDs (also known as user IDs) to avoid problems with passwords.
- Each PeopleSoft database needs its own PeopleSoft database name.

This is the database name users enter during the PeopleSoft logon process. It appears in the following locations:

Location	Reference
PeopleSoft logon screen	Database Name
TNSNAMES.ORA	The service name defined in TNSNAMES.ORA must be the same as that in PS.PSDBOWNER.
PS.PSDBOWNER table	<p>DBNAME column</p> <p>A single table, PS.PSDBOWNER, is created in the Oracle SID as part of the database creation procedures. PS.PSDBOWNER is maintained and acts as directory during the sign-on process to all of the PeopleSoft databases in the Oracle database/SID. There is a single row in the PS.PSDBOWNER for each PeopleSoft DB contained in the SID.</p>

Here's an example of four PeopleSoft databases in one Oracle database:

Database Use	PeopleSoft Database Name	Owner ID and Access ID (Oracle Schema)	Owner/Access Password	SID
Testing	HRTST	sysadm	sysadm	hrdm
Development	HRDVLP	sysadm2	sysadm2	hrdm
Training	HRTRAIN1	sysadm3	sysadm3	hrdm
Training	HRTRAIN2	sysadm4	sysadm4	hrdm

## Task 1-6: Planning Multilingual Strategy

This section discusses:

- Understanding Multilingual Issues
- Choosing a Base Language
- Selecting Additional Languages
- Selecting a Database Character Set

### Understanding Multilingual Issues

Before beginning your installation, you should determine which languages your PeopleSoft system will need to support. If multiple languages are required, determine which language will be used most often. These decisions will affect tasks at various stages of the installation, including file server setup, database creation, and the ability to change the base language of the PeopleSoft database after it is created. Even if you do not plan on running your system in more than one language, you should decide the following information before completing this task:

- Database base language
- Additional languages (if any)
- Database character set

The current languages provided by PeopleSoft and their language codes are listed below. These are the languages for which PeopleSoft provides pretranslated products. If you plan to provide users access to your applications in these languages, PeopleSoft recommends that you install the translations during your initial installation. This approach will keep you from having to perform an upgrade if you decide to add the PeopleSoft-provided translations at a later date. After installation, you also have the option of performing your own translations, and adding additional languages.

Code	Language
ARA	Arabic
CFR	Canadian French
CZE	Czech

Code	Language
DAN	Danish
DUT	Dutch
ENG	US English
FIN	Finnish
ESP	Spanish
FRA	French
GER	German
HUN	Hungarian
ITA	Italian
JPN	Japanese
KOR	Korean
NOR	Norwegian
POL	Polish
POR	Portuguese
RUS	Russian
SVE	Swedish
THA	Thai
ZHS	Simplified Chinese
ZHT	Traditional Chinese

---

**Note.** PeopleSoft MultiChannel Framework users who want to display certain Japanese characters should install JDK 1.4.2\_11+.

---

### See Also


*Enterprise PeopleTools 8.48 PeopleBook: Global Technology*

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft MultiChannel Framework*

## Task 1-6-1: Choosing a Base Language

Each PeopleSoft database can have only one base language. PeopleSoft databases ship with English as the default base language. Typically, the base language of your database should match the language most commonly used by your organization, as it affects the performance of PeopleSoft applications.

When PeopleTools attempts to open language-sensitive objects (such as pages and menus), it first compares the operator's preferred language to the base language of the database. If the preferred language matches the base language, PeopleTools immediately loads the required definition from the base language PeopleTools tables. However, if the user's preferred language differs from the database's base language, PeopleTools must first query the related language tables for the object. Should a translation of the object not be found in the operator's preferred language, a query is then performed on the base language tables. The following flowchart shows this logic:



Language selection process

While these queries typically occur very quickly, they still take up valuable processing time. To optimize performance you should set the base language of your database as the language that is used most often by your users.

## Task 1-6-2: Selecting Additional Languages

Because more than one language can coexist in a single PeopleSoft database, you should decide which languages to install. PeopleSoft provides translations of all end-user objects on the Global Multi-Language CD. It is much easier to install additional languages upon initial database creation than to add them later in your implementation process, so we recommend that you choose which additional languages may be required now. There is no limit to the number of languages that can coexist in a single PeopleSoft database; however, remember that each language will require additional storage space, primarily for PeopleTools objects.

## Task 1-6-3: Selecting a Database Character Set

This section discusses:

- Understanding Character Sets
- Using Unicode Databases
- Using Non-Unicode Databases

### Understanding Character Sets

Depending on the languages that you have selected for installation, you need to determine which character set can represent these languages. There are two main steps in selecting a character set. First, if your database supports Unicode, you should decide whether to use it. Second, if you choose not to or cannot yet use Unicode, you should decide which legacy character set is appropriate for the language combination that you've selected.

See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*, “Selecting and Configuring Character Sets and Language Input and Output.”

### Using Unicode Databases

In addition to supporting several legacy character sets, PeopleSoft supports creating Oracle databases using Unicode. Unicode enables you to maintain data in virtually any modern language in a single database. Prior to Unicode, many languages could not coexist in one database, as they did not share a common character set.

To create an Oracle Unicode database, you must specify the character set UTF8 in the CREATE DATABASE statement. PeopleSoft triples column sizes when running against a Unicode Oracle database, as all Oracle column sizes are measured in bytes, and PeopleSoft uses character-based column sizes. This tripling in size represents the worst-case 1-to-3 ratio of characters-to-byte for Basic Multilingual Plane Unicode characters when represented in UTF8.

Unicode databases are particularly important if the languages that you selected do not share the same character set. Typically, a single character set can encode all languages written in a single script. For example, English, French, and Spanish all share the same script (Latin), so they can coexist in a non-Unicode database. However, Japanese does not share the same script as French, so if you need to have Japanese and French coexist in a single system, you need a Unicode database.

---

**Note.** The characters required for the English language exist in all Unicode and non-Unicode character sets. For example, Japanese and English can coexist in a single Unicode or non-Unicode database.

---

If you plan on installing or supporting a combination of languages that do not share the same character set, you should use a Unicode database. On Oracle, Unicode characters require between 1 and 3 bytes of storage each. As characters needed to write English are represented with one byte in UTF8, you should see no additional space requirements for a UTF8 database when using primarily English characters.

If you decide to use Unicode for your database, you do not need to select a character set as described below.

## Using Non-Unicode Databases

You can safely use a non-Unicode character set only if your selected languages share the same character set. In this case, you need to decide in which character set your database should be created.

On Oracle, PeopleSoft supports the following Oracle character sets:

Character Set	Description	Languages Supported
WE8ISO8859P1	ISO 8859-1 West European	All Western European (English, French, Spanish, Portuguese, German, Dutch, and so on)
WE8ISO8859P15	ISO 8859-15 West European	All Western European (English, French, Spanish, Portuguese, German, Dutch, and so on), and includes the euro symbol
WE8MSWIN1252	MS Windows Code Page 1252 8-bit European	All Western European (English, French, Spanish, Portuguese, German, Dutch and so on), and includes the euro symbol
US7ASCII	ASCII 7-bit American	English
JA16SJIS	Shift-JIS 16-bit Japanese	Japanese, English

---

**Note.** Other languages—such as Arabic, Czech, Greek, Hebrew, Hungarian, Japanese, Korean, Polish, Russian, Thai, Turkish, Simplified Chinese, and Traditional Chinese—are only supported with Unicode.

---

## Task 1-7: Reviewing Updates and Fixes Required at Installation

Before beginning the installation, check the Updates and Fixes database on PeopleSoft Customer Connection to identify any updates and fixes required at installation that you will need to apply, based on the products, product version, and PeopleTools version that you are installing. Specific instructions for applying the updates and fixes are included in each listed incident.

Make note of all the updates and fixes, and plan to apply them at appropriate stages during the installation procedure. For example, a replacement for a PeopleTools executable would be applied after installing the CDs to the appropriate server, and so on.

The following procedure describes how to access the Updates and Fixes database. Contact PeopleSoft if you don't have a user ID and password for PeopleSoft Customer Connection.

To review updates and fixes required at installation:

1. Go to the PeopleSoft Internet Home Page at [www.peoplesoft.com](http://www.peoplesoft.com).
2. Select the link Log in now under Customer Connection.
3. Enter your user name and password to log in.

---

**Note.** Be sure to log on, or you will not see all of the menu options.

---



4. Select Updates and Fixes.
5. Select Required for Install or Upgrade.
6. Select PeopleTools as the product line, PeopleTools as the product, and select the appropriate PeopleTools release.

Make sure that the Required for Install option is selected and click the search button (the arrow).

7. Note any PeopleTools updates and fixes that apply to your installation.
8. Return to the Updates and Fixes search page and search for any application-related incidents by selecting the appropriate product line, product, and release.

Make sure the Required for Install option is selected and click the search button (the arrow).

9. Note any application-specific updates and fixes that apply to your installation.

---

**Note.** Keep in mind that your installation may require additional software components. In this case you will also need to check for updates and patches for the additional component software. Later chapters cover this topic in detail.

---

After this installation, you can upgrade your Java Runtime Engine (JRE) to a newer version without upgrading PeopleTools, as long as the new JRE is certified.

### See Also

“Installing Web Server Products”

“Installing Additional Components”

“Required Operating System, RDBMS, and Additional Component Patches Required for Installation,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise. Select your database platform.)

---

## Task 1-8: Installing Supporting Applications

PeopleSoft requires that a number of supporting applications be installed on batch servers and on any Windows-based client on which batch processes will be run locally. (Throughout the rest of this section we refer to these Windows-based clients as *two-tier clients*.) Be sure to check PeopleSoft Customer Connection to ensure that you are installing software versions that are certified by PeopleSoft.

See PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise).

- For PeopleSoft applications written in COBOL, install the appropriate version of the COBOL compiler on the server where you will compile:

---

**Note.** Remember, COBOL is not needed for PeopleTools or for applications that do not contain COBOL programs. See PeopleSoft Customer Connection to verify whether your application requires COBOL.

---

See “PeopleSoft Application COBOL Requirements,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise, By PeopleTools release, Platform Communications by Topic, Batch).

- For UNIX servers, install the appropriate version of Micro Focus ServerExpress.

- For Windows servers, install the appropriate version of Micro Focus NetExpress.
- If all your servers are on Windows, we recommend that you install a COBOL compiler on the file server.

You can install PeopleTools plus any patches on the file server, compile your COBOL there, and then copy the COBOL binaries to your application and batch servers.

- If your application and batch servers are on UNIX, we recommend that you designate a single server as the compile server, so that you can compile COBOL from this central location and then distribute it to the rest of your application and batch servers.

If you use this approach, you only need to copy patches or customizations over to the compile server. Note that this server must have the same operating system as any destination application or batch servers. For example, if your compile server is an HP-UX machine, you can only copy COBOL compiled there to other HP-UX application and batch servers. PeopleSoft recommends this approach. It will help you keep your COBOL source code in sync and only requires that you install COBOL in a single location.

- If you prefer, you can copy patches or customizations to all of your UNIX application and batch servers and compile the COBOL on each machine.

However, PeopleSoft does not recommend this approach. It requires that you install multiple versions of the COBOL compiler, and makes it more likely that your COBOL source code will get out of sync.

---

**Note.** Before PeopleTools 8.4, PeopleSoft delivered both source and compiled COBOL for Windows users; on UNIX COBOL had to be compiled. From 8.4 onwards, we deliver source only on both Windows and UNIX. If your application requires COBOL, you will need to compile it.

If your application requires COBOL and you are running UNIX, you need to install the COBOL runtime on every application and batch server. This is not necessary for Windows.

---

- You must install SQR on any non-Windows batch server.
- On Windows batch servers and Windows two-tier clients, you have the option of installing SQR locally, or mapping to a copy installed on the file server.

Because SQR does not require any local registry settings, you can execute SQR from any Windows batch server or two-tier client once SQR has been installed to a shared directory. Installing SQR locally will result in improved performance; over a slow network connection the improvement will be significant.

- Install Microsoft Office (Excel and Word) on any Windows batch server or two-tier client that will be running nVision or Microsoft Word batch processes.

Microsoft Office must be installed locally, because it requires registry settings.

## See Also

*Enterprise PeopleTools 8.48 Hardware and Software Requirements*

---

## Task 1-9: Installing the Database Engine

This section discusses:

- Understanding the Database Engine
- Creating a Seed Database

## Understanding the Database Engine

If you have not already done so, install the Oracle database engine on your database server.

When installing the Oracle RDBMS, installation option selection influences the resulting generated Oracle Shared Library. The PeopleSoft product calls the Oracle Shared library when making calls to the Oracle RDBMS.

### Task 1-9-1: Creating a Seed Database

Create the seed database during the installation of your Oracle database engine. This will not be your PeopleSoft database, so keep it small and give it a name that is not related to your application. After successfully installing your Oracle database engine, use the seed database to test Oracle Net connectivity from your application servers, batch servers, and workstations.

---

## Task 1-10: Installing Oracle Net on the Server

You need to carry out this step for the database server, batch server, and application server. You need to load the Oracle Net listener and the communication protocol adapter you are using, such as TCP/IP, IPX, or NetBIOS.

Additionally you should do the following:

- Configure the listener to start automatically upon booting.  
Refer to your Oracle documentation for details on setting up the listener.
- Verify that Oracle Net is loaded on the database server by connecting to a database using SQL\*PLUS.  
Issue the complete connect string including the TCP/IP address or some other node identifier. For example, if you are on TCP/IP, your logon might resemble the following example:

```
oracleid/password@TNS:service_name
```

---

**Note.** If you have someone outside your company install Oracle Net, make sure that they install the workstation end as well. Also, make sure they demonstrate connectivity between the workstations and the database server.

---

- Set required Oracle network configuration file parameters.

---

**Note.** PeopleTools 8.44 introduced a new feature called Query Kill. For Query Kill to work successfully, your application server must be using a remote network connection (for example, Oracle Net). In addition, you need to set the `SQLNET.EXPIRE_TIME = nn` parameter in the `SQLNET.ORA` network configuration file, as discussed below. If you are using a local connection, Query Kill will not work. However, the `BEQUEATH_DETACH=YES` parameter in the `SQLNET.ORA` network configuration file should also be set to keep UNIX defunct processes from being created on aborted batch server processes.

---

PeopleSoft requires its customers to use one of the following two Oracle SQLNET.ORA parameters to force the Oracle database server to terminate “dead” or “defunct” threads: SQLNET.EXPIRE\_TIME or BEQUEATH\_DETACH.

- The Dead Connection Detection parameter, `SQLNET.EXPIRE_TIME = nn`, applies only to connections being done through Oracle Net (for example, through `tnsnames.ora`).

This parameter sets a dead connection time-out value. Oracle Net sends a probe periodically to verify that a client-server connection is still active. (Oracle recommends a value of 10. The time increment is in seconds.) This ensures that connections are not left open indefinitely, due to an abnormal client termination. (Client in this context can be an application server thread.) If the probe finds a dead connection or a connection that is no longer in use, it returns an error, causing the server process to exit.

---

**Note.** This parameter works with all the supported versions of Oracle with PeopleTools 8.4x.

---

Limitations on using the dead connection detection feature are:

- Dead connection detection is not allowed on bequeathed connections.
- Though very small, a probe packet generates additional traffic that may downgrade network performance.
- The server may need to perform additional processing to distinguish the connection probing event from other events that occur, depending on which operating system is in use.

This may also downgrade network performance.

- The parameter Turn Off Unix Signal Handling, `BEQUEATH_DETACH=YES`, applies only to local connections using the BEQ protocol.

Because the client application spawns a server process internally through the Bequeath protocol as a child process, the client application becomes responsible for cleaning up the child process when it completes. When the server process completes its connection responsibilities, it becomes a defunct process. Signal handlers are responsible for cleaning up these defunct processes. Setting this parameter configures the client profile to pass this process to the UNIX init process by disabling signal handlers.

---

## Task 1-11: Installing Oracle Net on Your Workstation

You must install Oracle Net on each workstation that will connect to the PeopleSoft database server in a two-tier connection. Workstations making a three-tier connection normally do not need connectivity software. However, bear in mind that batch processes (such as COBOL and SQR) that are executed on the client workstation require that database connectivity software be installed on the client workstation. This is necessary because these batch processes must maintain their own SQL connection to the database server.

---

**Note.** You must also install Oracle Net on each application server and batch server that will connect to the PeopleSoft database server.

---

Oracle Net works with many communication protocols, so ensure that the listener on your database server is using the same protocol as the workstation. Also, keep in mind that the client workstations need simultaneous access to the database server (through Oracle Net) and to the PeopleTools software on the file server.

You must use the same version of Oracle Net (version 9i or 10g) on your workstations, applications servers, batch servers, and database servers. PeopleTools 8.4 requires at a minimum the NET9i (version 9.2.x) functionality. Note as well that you must install the necessary protocol driver for your environment, such as the Oracle TCP/IP Adapter.

---

**Note.** Please ensure that Oracle Net client connectivity is installed prior to performing a PeopleSoft workstation installation. Failure to do so will result in problems with the Crystal Reports product. Always check the most recent version of Supported Platforms on PeopleSoft Customer Connection for the currently supported Oracle Net versions.

---

See PeopleSoft Customer Connection, (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise).

---

## Task 1-12: Testing Oracle Net Connectivity

Once you have installed Oracle Net on the database server, application server, or workstation, test that the connection works using the SQL\*PLUS utility provided with Oracle Net.

Connect to a database on your database server as the SYSTEM user, and issue the following SQL statement:

```
SQL> select * from all_users;
```

---

**Note.** Pinging or using Telnet does not test the Oracle Net connection.

---

Oracle, or your Oracle vendor, is best equipped to assist you if you have any problems installing any Oracle products or connecting to your Oracle database.

---

## Task 1-13: Performing Backups

Before proceeding, you should back up all servers and workstations that are set up for installation so you can recover to this point if necessary. Do the following:

- Back up any changes you made to the database server in setting up your PeopleSoft system.
- Back up any changes you made to your file server while setting aside space for your PeopleSoft system and setting up access privileges.
- Once you set up your install workstations to access the file server and database server simultaneously, back up the workstations.

---

## Task 1-14: Using PeopleSoft Change Assistant and PeopleSoft Change Impact Analyzer

After you have completed the tasks in this book to install PeopleTools, including installing any necessary patches and fixes, you need to install PeopleSoft Change Assistant. PeopleSoft Change Assistant is a standalone application that enables you to assemble and organize all of the steps necessary to apply patches and fixes for maintenance updates.

PeopleSoft Change Assistant gathers all the necessary information for a maintenance update from the Environment Management Hub and uploads it to PeopleSoft Customer Connection. With the environment data available, PeopleSoft Customer Connection can determine what updates are applicable to your environment. PeopleSoft Change Assistant carries out the following tasks:

- Uploads environment
- Finds required updates
- Downloads updates
- Applies all change packages

You can also install PeopleSoft Change Impact Analyzer, either as part of the PeopleTools installation, or by itself. PeopleSoft Change Impact Analyzer is a Windows-based tool that you can use to evaluate the effect of changes you make on your installation.

### See Also

“Installing PeopleSoft Change Assistant”

“Installing PeopleSoft Change Impact Analyzer”

*Enterprise PeopleTools 8.48 PeopleBook: Software Updates*

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Change Impact Analyzer*

## CHAPTER 2

# Installing Web Server Products

This chapter discusses:

- Installing Oracle Application Server
- Installing BEA WebLogic Server
- Installing WebSphere Application Server

### See Also

“Clustering and High Availability for PeopleSoft 8.4,” PeopleSoft Customer Connection (Site Index, Red Papers)

“Required Operating System, RDBMS, and Additional Component Patches Required for Installation,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise. Select your database platform or release number.)

---

## Task 2-1: Installing Oracle Application Server

This section discusses:

- Understanding the Oracle Application Server Installation
- Prerequisites
- Preparing for the Oracle Application Server Installation
- Installing the Oracle Application Server on Windows and UNIX
- Updating the IBM JDK to Version 1.4.2
- Uninstalling the Oracle Application Server

### Understanding the Oracle Application Server Installation

This section describes the installation of the J2EE and Web Cache edition of the Oracle Application Server 10g (OAS) Release 2 (10.1.2.0.2). This documentation is concerned only with the installation of OAS for use as a web server with PeopleSoft software. Further information on the configuration of OAS can be found on Customer Connection and on the Oracle web site.

Before beginning the installation, be sure to obtain any required patches for the installation from <ftp://ftp.peoplesoft.com/outgoing/ptools/Oracle/OAS/101202>.

---

**Important!** PeopleSoft customers are granted a license of Oracle Application Server J2EE and Web Cache Edition for use exclusively with PeopleSoft Enterprise at no additional cost. PeopleSoft Enterprise customers can choose Oracle Application Server J2EE and Web Cache Edition as an alternative to BEA WebLogic or IBM WebSphere for use with PeopleSoft Enterprise. This license is provided solely for use with PeopleSoft Enterprise and any other use of Oracle Application Server J2EE and Web Cache Edition outside of use with PeopleSoft Enterprise requires the purchase of an Oracle Application Server license. Please note that a separate installation of Oracle Application Server J2EE and Web Cache Edition is required for use with PeopleSoft Enterprise.

---

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with Oracle Application Server 10g (10.1.2.0.2)”

Oracle Application Server 10g Release 2 (10.1.2.0.2) Documentation, <http://www.oracle.com/technology/documentation/appserver101202html>

## Prerequisites

The OAS can be used as a web server for Enterprise PeopleTools for the following operating systems:

- Windows
- Solaris
- HP-UX
- Linux
- AIX

See “Preparing for Installation,” Defining the Web Server.

For a complete list of prerequisites, see the installation documentation for the OAS on Oracle’s web site.

See <http://www.oracle.com/technology/documentation/appserver101202.html>. Select the View Library link for the appropriate operating system.

## Task 2-1-1: Preparing for the Oracle Application Server Installation

This section discusses:

- Creating a Group for the Inventory Directory
- Creating oraInst.loc
- Creating the Operating System User
- Reviewing the Environment Variables
- Using Custom Port Numbers

### Creating a Group for the Inventory Directory

If you plan to install Oracle Application Server on a computer that does not have Oracle products, create a group to own the inventory directory. The installer writes its files in the inventory directory to keep track of the Oracle products installed on the computer.



This guide uses the name *oinstall* for this operating system group.

By having a separate group for the inventory directory, you allow different users to install Oracle products on the computer. Users need write permission for the inventory directory. They can achieve this by belonging to the *oinstall* group.

For the first time installation of any Oracle product on a computer, the installer displays a screen where you enter a group name for the inventory directory, and a screen where you enter the location of the inventory directory. The default name of the inventory directory is *oraInventory*. If you are unsure if there is already an inventory directory on the computer, look in the */etc/oraInst.loc* file for Linux and AIX systems and the */var/opt/oracle/oraInst.loc* file for other UNIX platforms. This file lists the location of the inventory directory and the group which owns it. If the file does not exist, the computer does not have Oracle products installed on it.

## Creating oraInst.loc

If the *oraInst.loc* file does not exist in the */etc* directory for Linux and AIX systems or the */var/opt/oracle* directory for other UNIX platforms, you must create it before starting the silent and non-interactive installation of Oracle Application Server. This file is used by the installer.

1. Log in as the root user:

```
% su
```

2. Using a text editor such as *vi* or *emacs*, create the *oraInst.loc* file in the */etc* directory for Linux and AIX platforms, and in the */var/opt/oracle* directory for other UNIX platforms.
3. Enter the following line in the file, where *oui\_inventory\_directory* is the full path to the directory where you want the installer to create the inventory directory:

```
inventory_loc=oui_inventory_directory
```

Make sure that the *oinstall* operating system group has write permission to this directory.

See *Creating a Group for the Inventory Directory*.

4. Create an empty */etc/oratab* file:

```
# touch /etc/oratab
```

5. Exit from the root user.

```
# exit
```

## Creating the Operating System User

*Windows:*

The operating system user performing the installation must belong to the Administrators group.

*UNIX:*

Create an operating system user to install and upgrade Oracle products. This guide refers to this user as the *oracle* user. The *oracle* user running the installer must have write permission for these directories:

- the Oracle home directory, which contains files for the product you are installing
- the inventory directory, which is used by the installer for all Oracle products

If the computer contains other Oracle products, you might already have a user for this purpose. Look in the `/etc/oraInst.loc` file for Linux and AIX platforms, and in the `/var/opt/oracle/oraInst.loc` file for other UNIX platforms. This file lists the location of the inventory directory and the group who owns it. If the file does not exist, the computer does not have Oracle products installed on it.

See `Creating oraInst.loc`.

If you do not already have a user for installing Oracle products, create a user with the following properties:

<b>Login name</b>	Select a name for the user. This guide uses <i>oracle</i> .
<b>Group identifier</b>	Select a name for the group. This guide uses <i>oinstall</i> . The primary group of the oracle user must have write permission for the oraInventory directory.
<b>Home directory</b>	The home directory path must not include any spaces. The home directory for the oracle user can be the same as the home directories of other users.
<b>Login shell</b>	The default login shell can be the C, Bourne, or Korn shell.

## Reviewing the Environment Variables

Make sure the following conditions for environment variables are met:

- ENV, ORACLE\_HOME, and ORACLE\_SID must *not* be set. If necessary, unset these variables.
- PATH, CLASSPATH, and LD\_LIBRARY\_PATH must not contain references to directories in any Oracle home directories.
- Set DISPLAY to the monitor where you want the installer window to appear.

---

**Note.** On AIX platform, DISPLAY should be set even when using the OAS silent installation procedure.

---

- TNS\_ADMIN must not be set.
- TMP is optional. If TMP is not set, the value defaults to `/tmp`.

---

**Note.** If you use the `su` command to switch users (for example, switching from the root user to the oracle user), check the environment variables when you are the new user because the environment variables might not be passed to the new user.

---

## Using Custom Port Numbers

By default, the installer configures Oracle HTTP Server to use port 7777, not port 80. Port 7777 is the default port because on UNIX, components that use port numbers lower than 1024 require additional steps to be done as the root user before the components can run. Because the installer does not have root access, it has to use a port greater than 1024.

If you want Oracle HTTP Server to use a different port, such as port 80, use the "static ports" feature, which enables you to specify port numbers for components. Although you can change the port number after installation, it is easier to set the port number during installation. The OAS cannot use port numbers that are less than 1024 and greater than 50000.

To instruct the installer to assign custom port numbers for components:

1. Create a file containing the component names and port numbers.

This file is typically called the `staticports.ini` file, but you can name it anything you want. A sample `staticports.ini` file is located at `<INSTALL_DIR>\Disk1\stage\Response`.

2. During the installation, on the Specify Port Configuration Options window, select Manual and enter the full path to the staticports.ini file.

If you do not specify the full path to the file, the installer will not be able to find the file. The installer will then assign default ports for all the components, and it will do this without displaying any warning.

## Task 2-1-2: Installing the Oracle Application Server on Windows and UNIX

This procedure describes the installation of the OAS middle tier software, which comprises the OAS J2EE and Web Cache. The OAS software is provided to the customer using Oracle E-Delivery.

See Oracle E-Delivery, <https://edelivery.oracle.com/>

1. Download the zipped files containing the OAS from Oracle E-Delivery.
2. Create a temporary folder, <INSTALL\_DIR>, for your operating system.
3. Extract each zipped file into a separate folder labelled Disk<#> under <INSTALL\_DIR>.
4. Start the installation:

---

**Note.** For AIX, it will prompt you to run rootpre.sh. Enter y if rootpre.sh has already been run. If this is the first time any Oracle product is being installed on this AIX machine, please stop the OAS installation and run rootpre.sh as the "root" user before continuing with OAS installation.

---


- For Windows, double-click <INSTALL\_DIR>\Disk1\setup.exe.
  - For UNIX, run <INSTALL\_DIR>/Disk1/runInstaller.
5. Click Next.

The product selection window appears. Oracle Application Server 10g 10.1.2.0.2 is the default product. Accept the default.

---

**Note.** English is the default language. To install different languages, click the Product Languages button. Make the selection in the popup window and click OK.


---



Product selection window

6. Click Next.


The Installation type selection window appears. J2EE and Web Cache is the default installation type. Accept the default.



Installation type selection window

7. Click Next.

A window appears listing the pre-installation requirements. Select the Administrator privileges check box.



Confirm Pre-Installation Requirements window


8. Click Next.

Confirm that the Oracle HTTP Server and OracleAS 10g Containers for J2EE are selected.

---


**Note.** Select Oracle Application Server 10g Web Cache only if the customer has purchased Web Cache license from Oracle.

---



Select Configuration Options window

9. Click Next.



Specify Port Configuration Options window

Select one of the following radio buttons to specify the port configuration:


- Automatic: Select this option to use the default port values.
- Manual: Select this option to instruct the installer to assign custom port numbers for components. Specify the full path and name of the file containing the component names and port numbers.

See Preparing for the Oracle Application Server Installation, Using Custom Port Numbers.

10. Click Next.

Specify the OAS instance name and password. The Oracle instance name can be different from the Oracle home name.






Specify Instance Name and ias\_admin Password


11. Click Next.

Review the summary information. To make changes in the installation information, click Back. If you are ready to begin the installation, click Install.




Summary

12. Windows appear showing the progress of the installation and configuration.




Install window



Configuration Assistants window

13. When the installation is complete, the end of installation window appears.

Make note of the information displayed on the installation log file and login URL. Click Exit.




End of Installation window

14. On UNIX, the following message box appears.

Open a new window and run the script `<OAS_HOME>/root.sh` as root.

Click OK to complete the installation.



Setup Privileges for Oracle Application Server

### Task 2-1-3: Updating the IBM JDK to Version 1.4.2

This is a post-installation step for AIX only.


To update the IBM JDK build:

1. Download IBM JDK ca142-20050609 from <http://www-128.ibm.com/developerworks/java/jdk/aix/service.html>.
2. Extract to a temp directory. For example, /tmp/jdk142.
3. Rename <ORACLE\_HOME>/jdk to <ORACLE\_HOME>/jdk.old
4. Move /tmp/jdk142 to <ORACLE\_HOME>/jdk
5. Run the command <ORACLE\_HOME>/bin/emctl stop iasconsole.
6. Run the command <ORACLE\_HOME>/bin/emctl start iasconsole.

## Task 2-1-4: Uninstalling the Oracle Application Server

To remove the OAS 10.1.2.0.2 installation:

1. Navigate to the directory, <INSTALL\_DIR>, that contains the extracted installation files for OAS.
2. Change directory to Disk1.
3. On Windows, run `setup.exe -deinstall`.  
On UNIX, run `./runInstaller -deinstall`
4. On the Inventory dialog box, select the OAS\_HOME that you want to uninstall and click the Remove button.



Inventory dialog box for OAS

5. Review and accept the next two confirmation dialog boxes.
6. When the Inventory dialog box reappears, click Close.
7. On Windows, you must reboot and remove the OAS\_HOME directory after the uninstall process.

---

## Task 2-2: Installing BEA WebLogic Server

This section discusses:

- Understanding the WebLogic Installation
- Installing WebLogic

### Understanding the WebLogic Installation

PeopleSoft ships a licensed edition of BEA WebLogic Server 8.1. The Windows distribution of BEA WebLogic is located on the WebLogic CD-ROMs provided by PeopleSoft.

---

**Note.** The WebLogic server installation can be run from our CD or from a copy of the CD as long as the path to the CD is not a UNC and does not contain spaces.

---



---

**Note.** To familiarize yourself with the most current support information and information about any required WebLogic Service packs based on OS platform or PeopleTools versions, consult PeopleSoft Customer Connection or the Hardware and Software Requirements guide. Note that WebLogic Server Service packs are cumulative, and you must uninstall any previous service packs before upgrading (or downgrading).

---



---

**Note.** The installation of Weblogic Server 8.1 requires 500 MB of free temporary space to extract the required files and run. By default, /tmp and %TEMP% are used on UNIX and Windows, respectively. In addition 500 MB of free space is required on the drive/device to which you opt to install WebLogic Server. If adequate space is not available, you will be prompted for alternate locations.

---

## See Also

*Enterprise PeopleTools 8.48 Hardware and Software Requirements*

BEA's official installation instructions: <http://e-docs.bea.com/wls/docs81/>

PeopleSoft Customer Connection, Supported Platforms (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise)

## Task 2-2-1: Installing WebLogic

The following steps assume that you have the PeopleTools WebLogic CD for your platform in the D drive.

---

**Note.** BEA WebLogic Server 5.1, 6.1 and 8.1 can coexist on a single machine. If you choose to install this version of WebLogic in an existing BEA\_HOME directory (for example, c:\bea), you must shut down all instances of WebLogic Server running in that BEA\_HOME before performing this installation.

---

To install the WebLogic Server 8.1:

1. Insert the WebLogic Server 8.1 CD for your OS platform into an accessible CD-ROM drive and run the provided install command (install.cmd on Windows and ./install.sh on UNIX).

---

**Note.** Running install.sh on SuSE 9 Linux generates the message "cat: /etc/redhat-release: No Such file or directory". This message is benign. You can safely ignore the message and continue the installation.

---

The install process will perform the base and service pack install, patch install, license install, and a JRE install if applicable. With prior releases of PeopleTools and WebLogic, each of these steps had to be run manually.

Platform	WebLogic Server CD
Windows Server 2003, Red Hat and SuSE Linux Enterprise Server	CD1
AIX, HP-UX Intel Itanium	CD2
HP-UX PA-RISC 64-bit	CD3



Platform	WebLogic Server CD
Solaris	CD4
Tru64	CD5

---

**Note.** The installation script accepts command line arguments for silent installs. For usage, run `install -?` or `install -help`.

---

- Specify the directory where you want to install WebLogic 8.1. This directory is known as `BEA_HOME`.

---

**Note.** When you install WebLogic Server, a JRE, and at least a partial JDK is installed. PeopleSoft's JRE/JDK certification for WebLogic Server is based on extending BEA's JRE/JDK certification of WebLogic Server.

---

## Task 2-3: Installing WebSphere Application Server

This section discusses:

- Understanding WebSphere Application Server Installation
- Prerequisites
- Preparing for WebSphere Installation
- Installing WebSphere Base
- Installing WebSphere Base with the Silent Method
- Verifying the WebSphere Base Installation
- Uninstalling the Default WebSphere Application
- Installing the WebSphere Base 5.1 Plug-in for HTTP Proxy Server
- Installing WebSphere Network Deployment Manager
- Upgrading WebSphere 5.1 Base and WebSphere ND to 5.1.1.7
- Troubleshooting the WebSphere Installation and Upgrade

### Understanding WebSphere Application Server Installation

This section covers the installation of the IBM WebSphere products IBM WebSphere 5.1.1.7 Application Server (Base) and WebSphere Network Deployment. For convenience and brevity, this documentation refers to these products as WebSphere Base and WebSphere ND, respectively, or collectively as WebSphere. You also have the option of installing IBM HTTP Server (IHS). The directory where you install the WebSphere products is referred to as `<WAS_HOME>`. This section concerns that portion of the installation that is needed for a basic PeopleTools installation.

Install the WebSphere components in the following order:

- Confirm that minimum system requirements, including those for hardware and software, have been met.  
See Prerequisites.
- Install WebSphere Base in GUI or silent mode.  
See Installing WebSphere Base.

See Installing WebSphere Base with the Silent Method.

3. Install IHS (optional).

You can install IHS with the WebSphere Base install, or separately in silent mode.

See Installing the WebSphere 5.1 Plug-in for HTTP Proxy Server.

4. Verify Base installation using the IVT program.

See Verifying the WebSphere Base Installation.

5. Uninstall Default Application and stop the WebSphere Base server.

6. Upgrade WebSphere Base to version 5.1.1.7 using Fix Pack 1, Cumulative Fix 7, and JDK Fix.

See Upgrading WebSphere 5.1 Base or WebSphere ND to 5.1.1.7.

7. Install WebSphere ND if planning to cluster WebSphere Base environment.

See Installing WebSphere Network Deployment Manager

8. Upgrade WebSphere ND to version 5.1.1.7 using Fix Pack 1, Cumulative Fix 7, and JDK Fix.

See Upgrading WebSphere 5.1 Base or WebSphere ND to 5.1.1.7.

Enterprise PeopleTools 8.48 comes with 3 WebSphere CDs for each platform—WebSphere Base (CD1), WebSphere ND (CD2) and WebSphere Maintenance packs (CD3). The operating system is listed on each CD.

Here is an example for the AIX platform:

CD	Name	Contents
CD1	IBM WebSphere Application Server Version 5.1 for AIX	Application server IBM HTTP Server
CD2	IBM WebSphere Application Server Version 5.1 for AIX	Network Deployment
CD3	IBM WebSphere Application Server Version 5.1.1.7 for AIX	Maintenance packs for: <ul style="list-style-type: none"> <li>• Application Server</li> <li>• Network Deployment</li> <li>• IBM HTTP Server</li> <li>• JRE upgrade (if applicable)</li> </ul>

Enterprise PeopleTools 8.48 comes with 4 CDs for HP and Windows platforms. The contents of CD1 and CD2 are the same as in the table above. Here are the contents for CD3 and CD4:

CD	Contents
CD3	Maintenance packs for : <ul style="list-style-type: none"> <li>• Application Server</li> <li>• IBM HTTP Server</li> <li>• JRE upgrade (if applicable)</li> </ul>
CD4	Maintenance packs for: <ul style="list-style-type: none"> <li>• Network Deployment</li> <li>• JRE upgrade (if applicable)</li> </ul>

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with IBM WebSphere”

## Prerequisites

The full list of prerequisites for WebSphere Base and ND are available on the IBM website.

See <http://www-3.ibm.com/software/webservers/appserv/doc/latest/prereq.html>

If your operating system is not at the required patch level, a warning message will appear at the beginning of the installation. It is important to stop the installation and apply the requested patches to the system. Along with the hardware and software requirements above, you must complete the steps in the next section.

## Task 2-3-1: Preparing for WebSphere Installation

The following steps are required for WebSphere Base and the WebSphere ND Embedded Messaging service:

*Microsoft Windows:*

- Define the process user ID with these authorizations:
  - Assign the user ID to the Administrator group.
  - Give the user ID the advanced user right *Act as part of the operating system*.
  - Give the user ID the advanced user right *Log on as a service*.
- Allocate space for Base Messaging and Message Broker.

The following table lists the default locations for the base messaging functions and the messaging broker functions (for publish or subscribe messaging).

	Base Messaging	Messaging Broker
Installation directory	C:\Program Files\IBM\WebSphere MQ	C:\Program Files\IBM\WebSphere MQ\WEMPS
Typical space needed	70 MB (server) or 15 MB (client)	45 MB (server)

See Troubleshooting the WebSphere Installation and Upgrade.

*UNIX:*

Define the operating system groups and users needed for embedded messaging:

1. If you have not already done so, create the groups *mqm* and *mqbrkrs*.
2. Add the users *mqm* and *root* to the *mqm* group.
3. Add the user *root* to the *mqbrkrs* group.
4. Log in once as user *mqm*, then log in again as *root*.

*Solaris and HP-UX only:*

Before installing Embedded Messaging PeopleSoft recommends that you review the machine's configuration appropriate kernel settings as described on the IBM web site.

See WebSphere Software Information Center, [http://publib.boulder.ibm.com/infocenter/wasinfo/index.jsp?topic=/com.ibm.websphere.base.doc/info/aes/ae/rins\\_prereq.html](http://publib.boulder.ibm.com/infocenter/wasinfo/index.jsp?topic=/com.ibm.websphere.base.doc/info/aes/ae/rins_prereq.html).

---

**Note.** User IDs longer than 12 characters cannot be used for authentication with the embedded messaging. Also we recommend that you run the JMS server process for Embedded Messaging under the root user ID.

---

Embedded Messaging is installed in fixed locations. The following table shows the required disk space and installation directories for UNIX platforms:

	Base code	Broker code	Base data	Broker data
<i>AIX:</i> Installation directory	/usr/mqm	/usr/opt/wemps	/var/mqm	/var/wemps
<i>AIX:</i> Required disk space	40 MB (server) or 15 MB (client)	80 MB (server) or 15 MB (client)	8 MB (server) or 5 MB (client)	5 MB (server)
<i>Linux/Intel/HP-UX and Solaris:</i> Installation directory	/opt/mqm	/opt/wemps	/var/mqm	/var/wemps
<i>Linux/Intel/HP-UX:</i> Required disk space	40 MB (server) or 15 MB (client)	105 MB (server) or 15 MB (client)	8 MB (server) or 5 MB (client)	5 MB (server)
<i>Solaris:</i> Required disk space	40 MB (server) or 15 MB (client)	70 MB (server) or 15 MB (client)	20 MB (server) or 15 MB (client)	5 MB (server)

---

**Note.** The /var file system is used to store all the security logging information for the system, and is used to store the temporary files for email and printing. Therefore, it is critical that you maintain free space in /var for these operations.

---

## Task 2-3-2: Installing WebSphere Base

PeopleTools 8.48 supports the IBM HTTP Server (IHS) embedded within WebSphere for both http and https. Use of an external proxy server is optional. Supported proxy servers are IHS, Sun Java System Web Server and Internet Information Server (Windows only).

---

**Important!** You must be a member of the Administrator group (or root on UNIX) to install WebSphere Base and IHS.

---

WebSphere Base can be installed using a GUI or silent installation option. This section explains the GUI installation. The silent installation option is covered in PeopleBooks.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with IBM WebSphere.”

To install WebSphere Base from the CD:

1. If you plan to use an HTTP proxy server other than IHS, you must install it before beginning the WebSphere Base installation.

---

**Note.** If you are planning to use IHS as the HTTP server, it can be installed as a part of WebSphere install and does not require any additional installation.

---

2. Stop any HTTP server (for example, IIS or Sun ONE Web Server and so on) running on the system.
3. Insert the WebSphere CD into your CD-ROM drive.
4. Navigate to the CD-ROM drive.

Run the command `installBase.bat` (`installBase.sh` for UNIX) from a command prompt, which will start the installation of WebSphere Base.

This invokes the default GUI install.

5. If you are prompted to select a language, select *English* (the default) and click OK.  
If you are running on a UNIX system and a window does not appear, check that the `DISPLAY` environment variable is set properly.
6. Click Next on the Welcome to IBM WebSphere Application Server, Version 5.1 panel.
7. On the Software License Agreement panel, check I accept the terms in the license agreement and click Next.

---

**Note.** If the installation is on a machine that has no other copies of WebSphere on it, you will not see the panel described in steps 8 and 9. If WebSphere is already installed, use the next panel to specify whether you want multiple versions of WebSphere to coexist and run on the same computer.

---

8. Select Modify ports for coexistence to allow multiple versions to coexist and run on this computer by modifying the port numbers and click Next.
9. Click Next.

A panel appears with the ports listed. PeopleSoft recommends that you add 10000 to the value of each listed port. That is, add *1* in front of the existing value.

---

**Note.** The install wizard suggests new ports by incrementing various digits in the default ports.

---

Please write down these port changes, especially the HTTP Transport Port (Default 9080), HTTPS Transport Port (Default 9443), and Admin Console Port (Default 9090).

The port for IBM HTTP Server port (Default 80) should not be changed from port 80. Change the value back to 80 if necessary.


---

**Note.** The installation wizard will ensure all of the prerequisites are satisfied. If you have not met all of the prerequisites, you are warned about this situation, but the installation of the product continues.

---

10. Select Custom on the next panel and click Next.
11. On the panel shown below, deselect the check boxes for Application server samples and Java docs.

Select IBM HTTP Server Version 1.3.28 and Plug-in for IBM HTTP Server v1.3 if you want to install the proxy server on the same machine. Other HTTP (web server) proxy plug-ins (for example, IIS or Sun ONE Web Server) may also be selected. Select a plug-in only if the corresponding HTTP server is already installed



Custom Installation Selections for WebSphere Application Server

See Installing the WebSphere 5.1 Plug-in for HTTP Proxy Server.

12. Click Next.
13. Accept the default location for the WebSphere installation directory (<WAS\_HOME>), or enter a new location.

On Windows the default location is C:\WebSphere51\AppServer. On UNIX, the default location is the current directory, usually the cdrom drive. You must change this to a directory on a file system with enough space to install WebSphere. The default installation location for Solaris, HP-UX, and Linux is /opt/WebSphere51/AppServer. For AIX it is /usr/WebSphere51/AppServer.

14. Accept the default location for the WebSphere Embedded Messaging installation directory, or, on Windows, enter the installation directory where you installed embedded messaging.

On Windows the default installation location is C:\Program Files\WebSphere MQ. The default locations for UNIX platforms were listed in a previous section.

---

**Note.** On UNIX, WebSphere fix packs expect embedded messaging to be at the default location.

---

See Preparing for WebSphere Installation.

15. If you selected the IBM HTTP Server in step 11, accept the default path or update the path to reflect the version number, for example, C:\IHS1.3.28.

16. Click Next.

The next panel allows you to enter the WebSphere node name and the machine's hostname (or IP address). The default node name is `<hostname>Node` where `<hostname>` is your machine's hostname. The default for Hostname or IP Address is `<hostname>`. You can modify these fields to include the fully qualified hostname or the IP address of the machine, but PeopleSoft recommends that you keep these defaults.

17. Click Next.

18. If you are running on Windows, you can choose the option to Run WebSphere Application Server as a server.

Enter the password for the user id you are using.

---

**Note.** By choosing to run the Application server as a service, you can use the Control Panel – Service to manage the Application Server. The specified username must be part of the Administrator group. Enter the password for the user id you are using.

---

19. Click Next.

20. Verify the selected options and click Next to begin the installation.

21. Deselect the option Select Register this product now.

22. Click Next and then Finish to complete the installation.

---

**Note.** Check the log for any errors encountered during installation. For WebSphere this is found in `<WAS_HOME>/logs/log.txt` and for IHS it is found in `<WAS_HOME>/logs/log_ihs.txt`

---

Refer to the Customer Connection link <ftp://ftp.peoplesoft.com/outgoing/PTools/websphere/511PT848> to check whether any iFixes are needed. If they are present, you must install them.

## Task 2-3-3: Installing WebSphere Base with the Silent Method

To install WebSphere Base from the CD using the silent method, navigate to the CD-ROM drive and run one of the following commands:

Windows:

```
installBase.bat -silent
```

UNIX:

```
installBase.sh -silent
```

---

**Important!** The silent installation does not install any HTTP proxy server plug-ins or the IBM HTTP Server.

---

## Task 2-3-4: Verifying the WebSphere Base Installation

After the installation process completes, carry out these steps to verify the WebSphere Base installation:

1. Select Verify Installation on the window titled WebSphere Application Server - First Steps.
2. Check the Install Verification Test (IVT) results for a message similar to this: “WebSphere Application Server is started and open for e-business with a *process id*.”  
This message indicates a successful installation. If the installation was not successful and the server could not be started, check the log file at <WAS\_HOME>\logs\ivt.log.
3. Invoke the WebSphere Administration Console by typing the URL *http://localhost:9090/admin* (where 9090 is the default administration port) from a browser window.
4. If you are running on AIX, you may see a message indicating that the AIX Web-based System Manager (WSM) is running on port 9090.

The WSM will prevent the WebSphere Admin Console from running on port 9090. Please change the WebSphere Admin Console port in these two config files:

- server.xml: <WAS\_HOME>/config/cells/machine-cell/nodes/machine-node/servers/server-name
- virtualhosts.xml: <WAS\_HOME>/config/cells/machine-cell/nodes/machine-node


## Task 2-3-5: Uninstalling the Default WebSphere Application

The default application will cause a conflict with the PeopleTools software, so it must be un-installed. This conflict is due to the default use of the context root “/” by both programs.

1. Start WebSphere and invoke the WebSphere Administration Console.  
From the Admin console, expand Applications, Enterprise Applications.
2. Select the check box for the (1) DefaultApplication.
3. Click Stop and then click the Uninstall button to begin removing the default installation.  
If the Default Application is not present, then it was not installed.
4. Save the configuration and log out.

## Task 2-3-6: Installing the WebSphere Base 5.1 Plug-in for HTTP Proxy Server

WebSphere Application Server (Base) Version 5.1 supports a variety of HTTP proxy servers (such as IBM HTTP Server and IIS). The plug-in forwards requests from the HTTP server to WebSphere. When a client makes a request to the HTTP Server, it delegates the request to its plug-in, which forwards the request to WebSphere. Here is an example of such an environment:



Example of WebSphere plugin

Additionally, most production architectures will use the HTTP server with WebSphere Network Deployment. Such topics are fully addressed in the PeopleSoft Red Paper on clustering.



See “Clustering and High Availability for PeopleSoft 8.4,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Implementation Documentation and Software, Red Paper Library).

To install the plug-in:

1. Copy the .resp file, based on your HTTP Server as shown in the table, from the cdrom /base directory to the temp directory.

HTTP Server	resp File	Command
IBM HTTP Server & plug-in	IHS_N_Plugin.resp	install -options /temp/IHS_N_Plugin.resp
IBM HTTP Server plug-in only	IHSproxyPlugin.resp	install -options /temp/IHSproxyPlugin.resp
Sun Java System Web Server	SunOneProxyPlugin.resp	install -options /temp/SunOneProxyPlugin.resp
Microsoft IIS	IISproxyPlugin.resp	install -options C:\temp\IISproxyPlugin.resp

2. Update the .resp file for the HTTP server you installed as follows, substituting the correct name for <HTTP-Server>:
  - Set <HTTP-Server>.installLocation to the directory location where you want to install the HTTP server. For example,
 

```
ihsFeatureBean.installLocation=C:\IBMHttpServer
```
  - Set wasBean.installLocation to the directory location where you want the plug-in modules installed. For example:
 

```
wasBean.installLocation=C:\WebSphere51\plugin
```
3. From the cdrom/base/<OS> directory, issue the command listed in the Command column in the table above. This will start the silent install with the selected options. You can monitor the installation by viewing the file log.txt in the temp directory.
4. If you are running on Windows, reboot the machine.
5. Locate plugin-cfg.xml on Http (Reverse Proxy) Server machine.

For example, if you are using IHS, locate the file IBM\_HTTP\_Server\_HOME/conf/httpd.conf, and search for the text plugin-cfg.xml to determine the location of the file. Similarly on Sun Java Web Server, search for the text plugin-cfg.xml in the file magnus.conf, and on Microsoft IIS use HKEY\_LOCAL\_MACHINE > SOFTWARE > IBM.

---

**Note.** Before proceeding to the next step, it is a good idea to make a back-up copy of the original plugin-cfg.xml file on HTTP Server machine.

---

6. Copy the file plugin-cfg.xml from <WAS\_HOME>/config/cells/plugin-cfg.xml, and overwrite plugin-cfg.xml on the HTTP server (Reverse Proxy Server) machine.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with IBM WebSphere.”

## Task 2-3-7: Installing WebSphere Network Deployment Manager

WebSphere Application Server (Base) Version 5.1 also contains the Network Deployment (ND) component. If you plan on implementing a WebSphere Base clustered environment, install WebSphere 5.1 ND.

---

**Note.** WebSphere ND can be installed using either GUI or silent install method. You only need to choose one of these methods to install an instance of WebSphere ND.

---

In order to use WebSphere ND, you will first install the Deployment Manager:

1. Stop any HTTP Server (IHS, IIS, or Sun ONE) running on the system.

Open a Command prompt window on Windows, (or xterm on UNIX), navigate to <WAS\_HOME>\bin, and type `stopserver servern` (where *n* is the server number, for example server1). Wait until you get a confirmation message that the server has stopped.

If you get the error “Could not create SOAP connector”, the server was not running.

2. Run the following command from the CD-ROM drive directory.

- Windows:

```
installDeployMgr.bat
```

- UNIX:

```
installDeployMgr.sh
```

## Task 2-3-8: Upgrading WebSphere 5.1 Base and WebSphere ND to 5.1.1.7

### Prerequisites

This section discusses upgrading WebSphere Base or ND to version 5.1.1.7 using Fix pack 1, Cumulative Fix 7, and JDK Fix.

If you are planning to use WebSphere Base or ND and IHS on the same machine, then install IHS first before upgrading WebSphere.

- Stop both WebSphere Base and IHS.
- Ensure you have adequate space in your respective <base-home> and <ND-home> directories for the Fix pack installation.
- If WebSphere ND is used in the environment, apply the Fixpack to ND first before upgrading WebSphere Base.
- Set the JAVA\_HOME variable to *WAS\_Home/java*.

On AIX, for example: `export JAVA_HOME=/usr/WebSphere51/AppServer/java`

### Applying the Fix Pack, Cumulative Fix, and JDK Fix

To apply Fix Pack 1 to WebSphere Base and ND:

1. Run one of the following command from the cdrom directory:
  - For WebSphere Base, run `UpdateBase.sh (bat)`
  - For WebSphere ND, run `UpdateDeployMgr.sh (bat)`

2. Enter the WebSphere and IHS home directories.

The install program will then start to apply the fix pack based on these user inputs.

---

**Note.** On Windows, if you have installed WebSphere Base 5.1 in “c:\Program Files\WebSphere\AppServer”, please enter the WebSphere home directory as *c:\progra~1\WebSphere\AppServer* when you run *UpdateBase.cmd*.

---

3. After the fix pack has been applied, run the *versionInfo.sh (bat)* program from *<WAS\_HOME>/bin* directory to verify the installation of the fix pack.

The WebSphere Installed Product should be at version 5.1.1.7 and IBM WebSphere JDK at 1.4.2.1.1.

4. Check PeopleSoft Customer Connection at <ftp://ftp.peoplesoft.com/outgoing/PTools/websphere/511PT848> to check whether any iFixes are needed.

If iFixes are present, you must install them.

---

**Note.** If the upgrade did not complete successfully, refer to the next section on troubleshooting.

---



---

**Note.** Upgrade IBM HTTP Server only: If you are planning to use IHS on a separate machine, then invoke the *UpdateIHSOnly.sh (bat)* script from the *cdrom* directory to apply the fixpack to IHS only.

---

The *UpdateBase* or *UpdateDeployMgr* scripts generate the following output logs in the *TMP* directory on Windows:

<b>Fixpack</b>	<i>fixpack.log</i>
<b>Cumulative Fix</b>	<i>CumlFix5117.log</i>
<b>JdkFix 1421</b>	<i>JdkFix5117.log</i>
<b>iFix log</b>	<i>ifixes.log</i>

## Task 2-3-9: Troubleshooting the WebSphere Installation and Upgrade

Read this section if you were not able to upgrade WebSphere Base or WebSphere ND or to apply the Fix Pack, Cumulative Fix pack, or JDK Fix successfully.

1. If the installation of the Fix Pack 1 does not complete successfully, check for errors in the following logs, where *<fixpack>.log* is the package name:
  - UNIX: */tmp/<fixpack>.log*
  - Windows: *C:/temp/<fixpack>.log*
  - WebSphere update logs: *<WAS\_HOME>/logs/update*
2. Try applying the Fix Pack, Cumulative Fix, or JDK fix using GUI mode, by running the command

*<WAS\_HOME>/update/UpdateWizard.sh (bat)*

For example:

On UNIX: */usr/WebSphere51/AppServer/update/UpdateWizard.sh*

On Windows: *C:\websphere511\AppServer\update\UpdateWizard.bat*

Use this method if you are running on Windows, and you are unable to upgrade WebSphere Base or WebSphere ND due to the installation of Embedded Messaging in a non-default location.

3. Enter the home directories for WebSphere Base or ND.


Select the Install fix packs radio button.



Update Installation wizard - Select installation type

4. Enter the Fix Pack location.

The location of the Fix Pack for WebSphere Base is typically <WAS\_HOME>/update/fixPacks\_base and the location for WebSphere ND is <ND\_HOME>/update/fixPacks\_nd. The GUI Wizard also asks you to specify the location of Embedded Messaging to be upgraded.



Update Installation wizard - Specify fix pack location

## See Also

IBM WebSphere 5.1.1 InfoCenter, <http://publib.boulder.ibm.com/infocenter/ws51help/index.jsp>

## CHAPTER 3

# Installing Additional Components

This chapter discusses:

- Installing Tuxedo on Windows
- Installing Tuxedo on UNIX
- Installing Micro Focus Net Express for Windows
- Installing Micro Focus Server Express for UNIX and Linux

### See Also

“Clustering and High Availability for PeopleSoft 8.4,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Implementation Documentation and Software, Red Paper Library)

“Required Operating System, RDBMS, and Additional Component Patches Required for Installation,” PeopleSoft Customer Connection, (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise. Select your database platform or release number.)

“Installing and Configuring Software for Crystal Reports”

---

## Task 3-1: Installing Tuxedo on Windows

This section discusses:

- Understanding Tuxedo
- Prerequisites
- Uninstalling Tuxedo from Windows (Recommended)
- Designating the Application Server Administrator
- Installing Tuxedo on Windows
- Checking the Service Account
- Setting Up the Tuxedo Services
- Verifying the Server Installation
- Ensuring that Tuxedo Coexists with Earlier Versions

## Understanding Tuxedo

The PeopleSoft application server uses BEA's middleware product, Tuxedo, to perform transaction management, messaging, and administration. This task guides you through the installation of Tuxedo on your server. It is essential that you install PeopleSoft Edition - BEA Tuxedo version 8.1, which you receive with your PeopleSoft shipment as part of the CD-ROM Library. You need to install Tuxedo before you go any further in setting up your application server and your PeopleSoft Pure Internet Architecture. After you perform the installation described here, you will configure the application server environment to incorporate Tuxedo with the PeopleSoft components.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*.

---

**Note.** Only one instance of Tuxedo 8.1 can be installed on a Windows machine at any given time, due to system-wide registry settings.

---

The installation process uses a single installation script (`install.sh` on UNIX and `pstuxinstall.exe` on Windows) to automatically install Tuxedo.

---

**Note.** It is critical that you use the PeopleSoft Edition - BEA/Tuxedo 8.1 delivered with PeopleSoft; the version of Tuxedo that you receive with your PeopleSoft shipment is the only version of Tuxedo that PeopleSoft supports with this version of PeopleTools. You cannot use any other version of Tuxedo with PeopleSoft applications. For example, if you obtain BEA/Tuxedo 8.1 directly from BEA, it may not support all functions required due to patch-level differences.

---

---

**Note.** All customers receive the 128-bit version of the CD-ROM, which allows users to enable 128-bit encryption.

---

The PeopleSoft Edition - BEA/Tuxedo CD-ROM installs serial and license information transparently to the user; there are no numbers to obtain. If you encounter a serial or licensing error on installation, you probably have an old version of Tuxedo installed.

PeopleSoft Edition - BEA/Tuxedo CD-ROM licenses users to use Tuxedo's runtime/administration environment for the purposes of installing, monitoring, and tuning their Tuxedo-based PeopleSoft application servers. Users *are not* licensed to directly use the Tuxedo development environment. Users will be able to use any higher level API or tools that PeopleTools developers build with Tuxedo and will be able to run applications that are processed with our Tuxedo enhanced tools. If you wish to extend the PeopleSoft application's functionality by directly using the Tuxedo development API, you need to acquire a full-use license for Tuxedo from BEA Systems.

### See Also

*Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*

## Prerequisites

Before you begin to install Tuxedo, make sure that you have the following resources in place:

- PeopleSoft Edition - BEA/Tuxedo System 8.1 Installation for Windows and UNIX CD-ROM
- TCP/IP connectivity (required for PeopleSoft 8.4x) between the client machine and the application server
- Approximately 235 MB of free disk space on the application server
- A CD-ROM drive or access—locally or through the network—for the machine on which you plan to install Tuxedo

## Task 3-1-1: Uninstalling Tuxedo from Windows (Recommended)

You may already have Tuxedo 8.1 installed on your system from an earlier version of PeopleTools. There may be patch level differences between the release which you are using and that to which you are upgrading. In this case you must uninstall the existing version plus patch and reinstall using the latest version provided by PeopleSoft.

Note that you can verify the required Tuxedo patch level for this release in the Release Notes. You can verify that patch level which has been installed by examining the file %TUXDIR%\udataobj\patchlev. This file will indicate the patch level installed. At the end of the file you will see an entry such as:

```
192. CR229736 TUX8.1 : Please propagate CR208755 from Tuxedo7.1
```

The above entry indicates that patch level 192 has been installed. The absence of this file indicates that no patch has been installed.

This version of Tuxedo is only supported for PeopleTools 8.44 and above, and will not work with earlier versions of PeopleTools. If you have a previous version of BEA/Tuxedo installed, we recommend that you uninstall the old version or use another machine. Only one instance of Tuxedo 8.1 can exist on a Windows box since the BEA ProcMGR service is a machine-level service capable of searching a single registry tree.

---

**Note.** If you wish to use two versions of PeopleTools that depend on different versions of Tuxedo, you should read the section “Ensuring that Tuxedo Coexists with Earlier Versions” before continuing.

---

You may have to uninstall Tuxedo for these reasons:

- You are having problems starting Tuxedo and decide to reinstall.
- You no longer need Tuxedo on a machine.
- You are installing a newer release of Tuxedo.
- Patch differences exist between the version of Tuxedo 8.1 that is currently installed and that required for this PeopleTools release.

To uninstall Tuxedo from Windows:

1. Using PSADMIN, shut down any application server and process scheduler domains that may be running on the machine.
2. Stop the processes for the Tuxedo Monitor and the Tuxedo Administrative Web Server (wlisten and tuxwsvr), if applicable.
  - a. Right-click on the taskbar and select Task Manager.
  - b. Highlight wlisten, and click the End Task button.
  - c. Highlight tuxwsvr and click the End Task button.
  - d. Exit Task Manager.
3. Stop and set the TListen 8.1 service to manual, if applicable.
  - a. Select Start, Settings, Control Panel. Double-click Administrative Tools, and double-click the Services icon.
  - b. Select TListen 8.1 and click the Stop button.
  - c. Choose the Startup Type and set to Manual.
4. Stop and set the BEA ProcMGR V8.1 service to manual.

- a. Select Start, Settings, Control Panel. Double-click Administrative Tools, and double-click the Services icon.
  - b. Select BEA ProcMGR V8.1 and click the Stop button.
  - c. Choose the Startup Type and set to Manual.
5. Reboot your machine.
6. Uninstall Tuxedo in one of the following ways:
  - Using the Tuxedo 8.1 installation CD provided by PeopleSoft, open a Command Window, navigate to the root of the CD, and enter `pstuxinstall rmall`. This will remove Tuxedo 8.1 plus any delivered Tuxedo patches from your system.
  - Using the Add/Remove Programs dialog, in sequence remove: Tuxedo 8.1 RP and then Tuxedo 8.1.
7. Go to the Control Panel, double-click on the System icon, and then perform the following:
  - a. Make sure `<TUXDIR>\bin` is deleted from PATH.
  - b. Delete the environment variable TUXDIR.
  - c. Make sure you click on Apply and OK to save your changes.
8. Using Explorer, delete the Tuxedo home directory, such as `c:\bea\tuxedo8.1`.  
If you are unable to delete any files, reboot your machine and retry.

## Task 3-1-2: Designating the Application Server Administrator

First you need to designate an existing user—or create a new user such as TUXADM or some other account—to be the Application Server Administrator.

---

**Note.** The designated user must be a local Windows administrator and must have full system privileges. The Tuxedo install program creates a new service for Windows—called BEA ProcMGR V8.1—for which you need administrator privileges. This service was developed to port BEA/Tuxedo from UNIX to Windows. Administrator rights are required since system registry settings are updated. Once this new service is created, you must reboot to start it.

---



---

**Note.** The Application Server Administrator, not the Windows Administrator, will install Tuxedo.

---

To designate the Application Server Administrator:

1. To add the user, add the user ID by choosing Start, Settings, Control Panel, Administrative Tools, Computer Management, Local Users and Groups.  
Keep in mind that you can also use an existing account if you don't care to create a new one. You can set this to the system account or an account that is a domain administrator (if there is a need to access files on the domain).
2. Expand Local Users and Groups.
3. If the user ID does not yet exist, highlight the Users folder, and select Action, New User.
4. On the New User dialog box, specify the information for the new account.  
Make sure to deselect the User must change password at next logon check box.
5. Expand the Groups folder.
6. Right-click the Administrators group, and select All Tasks, Add to Group, Add.



7. Click Locations to select the local machine or the network domain in which you created the new user.
8. Enter the new user name you created in the object names box.
9. Click OK, and click Apply and OK again to accept the changes.

## Task 3-1-3: Installing Tuxedo on Windows

Here is how to properly install the Tuxedo component of your application server.

To install Tuxedo on Windows:

1. Insert the PeopleSoft Tuxedo CD-ROM labeled “Tuxedo 8.1 CD-1” into the CD-ROM drive.  
Using Explorer, navigate to the root directory on the CD:  
  
D:\
- (This assumes that your CD-ROM drive is your D drive.)
2. Double-click pstuxinstall.exe to begin the installation process.
3. You are prompted for the BEA Home directory. If you have existing BEA products on the machine, you may supply an already designated BEA Home location or accept the default of c:\bea.
4. You are prompted for the Tuxedo installation directory. This can be a subdirectory of the BEA Home directory or a directory of your choice.
5. You are prompted for the TListen port. The TListen service is not used by PeopleSoft application servers so you can accept the default unless you intend to use the Tuxedo Web Monitor. Unless you use the Tuxedo Web Monitor, you should disable the TListen service following the installation.

---

**Note.** If you intend to maintain multiple versions of Tuxedo on the same physical machine, it is wise to choose a port other than the default 3050 because the default port may clash with an existing TListen entry for an earlier version of Tuxedo.

---

See Ensuring that Tuxedo Coexists with Earlier Versions.

6. You are prompted for the TListen password. Again, unless you plan to use the Tuxedo Web Monitor, this service will be disabled following installation so you may go ahead and accept the default.

---

**Note.** If you intend to use the Tuxedo Web monitor for domain administration, PeopleSoft recommends that the TListen password be hard to guess and securely protected, since the Web monitor can start and stop production application server domains.

---

7. If you are satisfied with your selections confirm this when requested. This is your final opportunity to choose your Tuxedo installation location.
8. Tuxedo 8.1 plus patch will now be installed to your system. When the installation has completed you are notified by the command line installer.
9. Reboot your machine to complete the installation.

## Task 3-1-4: Checking the Service Account

Now you need to ensure that the Windows services are properly configured. PeopleSoft recommends installing the application server binaries locally on your C drive, for best performance, and using the Local System account radio button (see below) to start the BEA ProcMGR V8.1 service, with these exceptions:

- If you plan to install the PeopleSoft application server binaries (as in, psappsrv.exe and so on) on a remote file server, you must select the This Account radio button. If you intend to use this Windows service to start Process Scheduler, you must *always* select the This Account radio button. Enter the name of your Domain/Windows username—not the machine name—and your password. Then click OK.
- If the PeopleSoft application server binaries are *local*, that is, they exist on your local hard drive, you can use either the Local System account or This Account radio button.

---


**Note.** When using Tuxedo with Process Scheduler, you must use the Windows username that starts the Process Scheduler server agent. This is necessary because the installation of the PeopleSoft ODBC driver sets up the registry settings to be accessible only by this username. If you do not use the correct Windows username, processes that require the ODBC registry information (such as Crystal Reports) will fail.

---

## Task 3-1-5: Setting Up the Tuxedo Services

To set up the Tuxedo services:

1. Log on again as the Application Server Administrator, TUXADM, or a designated user ID.
2. Open the Control Panel and double-click Administrative Tools.
3. Select Computer Management and expand Services and Applications.
4. Select Services and locate the service labeled *BEA ProcMGR V8.1*.  
Double-click BEA ProcMGR V8.1 to open the properties dialog box.
5. On the General tab, if the Stop button is enabled, click on it to stop the current BEA ProcMGR V8.1 process.
6. Select Log On.



BEA ProcMGR V8.1 Properties dialog box: Log On tab

7. Choose either Local System account or This Account.

---

**Note.** When you configure your application server domain, the user ID designated to be the Application Server Administrator must have read and write permissions to the PeopleSoft file directory and read permission to the %TUXDIR% directory, such as c:\bea\tuxedo8.1.

---

See “Configuring the Application Server on Windows.”


---

**Note.** If you are running on Windows and are configuring a search index that resides on a mapped network drive, you must ensure that the User ID of the BEA ProcMGR service has access to network drives accessed by the search engine. The search engine stores the search indexes at <PS\_HOME>/data/search. However, this path can be changed in the application or the Process Scheduler's configuration. If this path is changed in these configurations and it points to a network drive, please ensure that the user ID that starts the BEA ProcMGR V8.1 service has access to these network drives. The application server and the process scheduler are started by the BEA ProcMGR V8.1 service and therefore inherit the same permissions as the BEA ProcMGR V8.1 service.

---

8. Select General.

Make sure that Startup Type is set to *Automatic*.



BEA ProcMGR V8.1 Properties dialog box: General tab

9. Select Start.

A message in the Services dialog box will indicate the Started status. Close the dialog box to return to the Control Panel.

10. As mentioned, unless you intend to use the Tuxedo Web Monitor, you should disable the TListen 8.1 service.

## Task 3-1-6: Verifying the Server Installation

At this point, you should verify that the server installation was successful.

To verify the server installation:

1. Go to the udataobj directory under <TUXDIR>.
2. Ensure that the lic.txt file exists.
3. Verify that the file patchlev exists.

If neither of these files exist:

- Verify that no error messages were displayed during installation of Tuxedo 8.1.
- Verify that you have sufficient disk space on the directory or file system used for <TUXDIR>.
- Reinstall BEA/Tuxedo 8.1.

## Task 3-1-7: Ensuring that Tuxedo Coexists with Earlier Versions

This section discusses:

- Understanding the Use of Multiple Tuxedo Versions
- Checking Your Environment Variables
- Changing the TListen Port

### Understanding the Use of Multiple Tuxedo Versions

PeopleTools 8.44 and above use Tuxedo 8.1. Earlier versions of PeopleTools rely on earlier versions of Tuxedo—for example, PeopleTools 8.41 uses Tuxedo 6.5. If you are installing only PeopleTools 8.48, you can safely skip this section. If you need to run application servers on PeopleTools 8.48 and earlier PeopleTools versions on the same machine, read this section to learn about coexistence issues. Although Tuxedo 8.1 coexists with earlier Tuxedo versions on the same machine, you may need to take a number of manual steps to ensure that these products share the same environment gracefully.

### Checking Your Environment Variables

Installing Tuxedo changes your TUXDIR and PATH environment variables. Although you do not need to change these environment variables to successfully run PeopleTools 8.48 with Tuxedo 8.1, earlier versions of PeopleTools rely on these environment variables being set.

To change your environment variables:

1. Set your <TUXDIR> environment variable to reflect the installation directory of your earlier Tuxedo release. For example, Tuxedo 6.5 may be installed to c:\tux65. This means that TUXDIR=C:\tux65 is the correct setting.
2. Your <PATH> environment variable must contain <TUXDIR>\bin for the earlier Tuxedo version before any entries for Tuxedo 8.1 <TUXDIR>\bin. For example the setting PATH=c:\winnt;c:\bea\tuxedo8.1\bin;c:\tux65\bin will cause your pre-8.44 application server domains to no longer work. You would need to change this to PATH=c:\winnt;c:\tux65\bin;c:\bea\tuxedo8.1\bin;

---

**Note.** PeopleTools 8.44 and later do not use the environment variables to discover the installation location of Tuxedo 8.1. The PSADMIN tool retrieves these values from the Windows registry.

---

### Changing the TListen Port

Installing Tuxedo 8.1 and earlier creates a new service known as TListen. In most cases, you can disable this service as it is not required to run PeopleTools application server domains. However, if you intend to use the Tuxedo Web Monitor you may wish to ensure that there is no port clash with earlier versions. This port is determined at installation and should be changed to a port other than the default 3050 if you intend on using the TListen service for Tuxedo 8.1 and an earlier version concurrently.

---

## Task 3-2: Installing Tuxedo on UNIX

This section discusses:

- Understanding Tuxedo
- Prerequisites
- Removing Tuxedo on UNIX

- Completing the Preinstallation Checklist
- FTPing Tuxedo Installation Files to UNIX
- Designating the Tuxedo Owner
- Installing Tuxedo on UNIX
- Verifying the Server Installation

## Understanding Tuxedo

The PeopleSoft application server uses BEA's middleware product, Tuxedo, to perform transaction management, messaging, and administration. This chapter guides you through the installation of Tuxedo on your server. It is essential that you install PeopleSoft Edition - BEA Tuxedo version 8.1, which you receive with your PeopleSoft shipment as part of the CD-ROM Library. You need to install Tuxedo before you go any further in setting up your application server and your PeopleSoft Internet Architecture. After you perform the installation described here, you will configure the application server environment to incorporate Tuxedo with the PeopleSoft components.

---

**Note.** PeopleSoft ships Tuxedo 8.1 with PeopleTools 8.44 and above. If you have a previous version of Tuxedo installed, you need to install the new version of Tuxedo, and re-create your application server domains. (You must create your domains using PSADMIN; you cannot migrate existing domains.) You can also use PSADMIN's domain import utility.

---

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*.

---

**Note.** Tuxedo should only be installed once for each release on a machine, regardless of the number of PeopleSoft applications or databases the server supports. For example, if you are a PeopleTools 8.1x customer and have Tuxedo 6.5 installed, you may install Tuxedo 6.5 and 8.1 on the same machine in separate directories (for example, /bea/tuxedo/8.1 and /prod/tuxedo/6.5).

---

The installation process uses a single installation script (`install.sh` on UNIX and `pstuxinstall.exe` on Windows) to automatically install all of these products.

---

**Note.** It is critical that you use the PeopleSoft Edition - BEA/Tuxedo 8.1 delivered with PeopleSoft; the version of Tuxedo that you receive with your PeopleSoft shipment is the only version of Tuxedo that PeopleSoft supports with this version of PeopleTools. You cannot use any other version of Tuxedo with PeopleSoft applications. For example, if you obtain BEA/Tuxedo 8.1 directly from BEA, it may not support all functions required due to patch-level differences.

---

---

**Note.** All customers receive the 128-bit version of the CD-ROM, which allows users to enable 128-bit encryption.

---

The PeopleSoft Edition - BEA/Tuxedo CD-ROM installs serial and license information transparently to the user; there are no numbers to obtain. If you encounter a serial or licensing error on installation, you probably have an old version of Tuxedo installed.

PeopleSoft Edition - BEA/Tuxedo CD-ROM licenses users to use Tuxedo's runtime/administration environment for the purposes of installing, monitoring, and tuning their Tuxedo-based PeopleSoft application servers. Users *are not* licensed to directly use the Tuxedo development environment. Users will be able to use any higher level API or tools that PeopleTools developers build with Tuxedo and will be able to run applications that are processed with our Tuxedo enhanced tools. If you wish to extend the PeopleSoft application's functionality by directly using the Tuxedo development API, you need to acquire a full-use license for Tuxedo from BEA Systems.

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*

## Prerequisites

Before you begin to install Tuxedo, make sure that you have the following resources in place:

- PeopleSoft Edition - BEA/Tuxedo System 8.1 Installation for Windows and UNIX CD-ROM
- TCP/IP connectivity (required for PeopleSoft 8.4x) between the client machine and the application server
- A CD-ROM drive or access—locally or through the network—for the machine on which you plan to install Tuxedo

---

**Note.** If CD-ROM access is unavailable, you must FTP files from the BEA/Tuxedo CD to UNIX, using the instructions provided below.

---

- Root access on the UNIX machine
- Approximately 250 MB of free disk space on the application server

## Task 3-2-1: Removing Tuxedo on UNIX

You may already have Tuxedo 8.1 installed on your system from an earlier release of PeopleTools. There may be patch level differences between the release which you are using and that to which you are upgrading. Note that you can verify the required Tuxedo patch level for this release in the Release Notes. You can verify that patch level which has been installed by examining the file \$TUXDIR/udataobj/patchlev. This file will indicate the patch level installed. At the end of the file you will see an entry such as:

```
192. CR229736 TUX8.1 : Please propagate CR208755 from Tuxedo7.1
```

The above entry indicates that patch level 192 has been installed. The absence of this file indicates that no patch has been installed.

You may have to remove your Tuxedo installation on UNIX for the following reasons:

- You are having problems starting Tuxedo and decide to reinstall.
- You no longer need Tuxedo on a machine.
- You are installing a newer release of Tuxedo.
- Patch differences exist between the version of Tuxedo 8.1 that is currently installed and that required for this PeopleTools release.

To remove Tuxedo from UNIX:

1. Using PSADMIN, shut down any application server and process scheduler domains that may be running on the machine.

2. Use the UNIX `rm` command to directly remove the Tuxedo installation.  
Be sure to remove the directory containing Tuxedo, commonly known as TUXDIR.
3. Remove the TUXDIR environment variable and any entries containing your platform-specific LIBRARY PATH and PATH environment variables.

## Task 3-2-2: Completing the Preinstallation Checklist

We recommend that you complete the following preinstallation checklist before you begin the Tuxedo installation. Specify your values in the Real Value column. Completing this information first should save you time during your installation.

Item	Description	Example Value	Real Value
BEAHOME	The high level directory where you converge the installation for all BEA products	[/bea]	
TUXDIR	The directory where Tuxedo system software will be installed.	[/bea/tuxedo/8.1]	
Username	The UNIX user name of the Application Server Administrator (Tuxedo owner).	[tuxedo]	
Groupname	Specify the UNIX group name of the Tuxedo owner.	[tuxedo]	

---

**Note.** You can select any user name and group name you want; however, you might want to use the tuxedo convention for simplicity.

---

## Task 3-2-3: FTPing Tuxedo Installation Files to UNIX

In the event that a CD-ROM drive is not directly accessible from the UNIX Host OS, it is necessary to insert the CD into the CD-ROM drive on a Windows system and transfer the files to the UNIX host. This procedure details how to perform that task, using FTP.

To FTP the Tuxedo installation files to UNIX:

1. Obtain the BEA/Tuxedo CD-ROM.
2. From the \$PS\_HOME/setup directory of your UNIX system, ftp pstuxftp.txt (ASCII mode) to your C: drive for editing.
3. Insert BEA/Tuxedo's CD into the Windows CD-ROM drive.

Use Explorer to examine the CD-ROM's directory structure. Write down the first two directory levels of the UNIX system you use—for example, ibm, aix51.

---

**Note.** The Tuxedo binaries for AIX 5.1 are certified to run under AIX 4.3.3 and AIX 5.2. If you are using AIX 4.3.3, select AIX 5.1 (or the most recent version of the platform).

---

4. Edit pstuxftp.txt:



- a. Replace the *tuxadmin* and *password* entries with an appropriate user name and password to install the Tuxedo binaries on the destination machine.  
This user name and password should correspond to the correct set of privileges to install and administer Tuxedo on the UNIX machine.
- b. Replace *vendor* with the vendor name, such as *ibm*, and *release* with the OS release, such as *aix51*.  
These are the details that you noted in the previous step. Be sure to enter these values in lowercase *only*.
- c. Replace all */home/tux81cd* entries with the directory name you wish to use as your high-level, virtual CD directory, such as */cdromtux*.

Make this change for the lines beginning with `mkdir`, `put`, and `cd`.

---

**Note.** Do not forget about case sensitivity. Windows file names are case insensitive; it does not matter what case you enter them in. UNIX directory names must be in the correct case, matching the case on the CD.

---

- d. You may also need to replace all *d:\* entries if your CD-ROM drive is not installed as the D: drive.
5. Run the `pstuxftp.txt` script to transfer files to UNIX. This script should be run using `ftp` from a DOS command prompt. This script should be run as follows:

```
ftp -n -s:pstuxftp.txt unix_machinename
```

6. On UNIX, `chmod` the `install.sh` file to make it executable. For example:

```
chmod +x install.sh
```

7. Continue to step 5 in the following section, Installing Tuxedo on UNIX.

## Task 3-2-4: Designating the Tuxedo Owner

A new or existing user must be designated as the Tuxedo owner.

To designate the Tuxedo owner:

1. Log in as root.
2. Create the UNIX group and the user name of the individual who will be the owner of Tuxedo.

Using the values from the preinstallation checklist, create the group and specify the group name. Then create the user who will be the Tuxedo owner, specifying the user name, group name, and home directory, denoted by `TUXDIR` from the checklist.

---

**Note.** Depending on your operating system, the utility you use to create the user and group is different. For example, HP-UX uses the "sam" utility, AIX uses the "smit" utility, and so on. For the exact utility, refer to your operating system documentation.

---

## Task 3-2-5: Installing Tuxedo on UNIX

The following procedure describes how to properly install Tuxedo plus the latest patch on your UNIX server.

---

**Note.** Remove any existing version of Tuxedo 8.1 delivered with an earlier version of PeopleTools, plus any existing Tuxedo patches, before continuing. The Tuxedo installation CD delivered with this package contains the latest patches required for this release.

---

To install Tuxedo on UNIX:

1. Insert the CD-ROM into the CD-ROM drive, and mount the CD-ROM from the root login.  
For mounting instructions, consult the operating system manufacturer's documentation or the UNIX manual page on mounting (use the command `man mount`).
2. List the root directory on the CD-ROM.
3. Log in as the Tuxedo administrator.  
You should no longer be logged on as root.
4. Change to the root directory on the CD-ROM.
5. Execute the shell script, `install.sh`.

```
sh ./install.sh
```

6. Follow the selected prompts as indicated in the following table:

Prompt	Standard PeopleSoft Response
Please select a platform <b>Note.</b> This question is only asked if you did not use the ftp script.	Specify the number associated with the desired operating system platform you wish to install.
BEA Home being defaulted to /bea (y/n)	Type y to indicate Yes or suggest an alternative BEA HOME.
Tuxedo 8.1 will be installed to /bea/tuxedo81 (y/n):	Acknowledge the Tuxedo installation location or suggest an alternative
Accept default TListen password 'password' (y/n):	Enter password. You will need to enter this password again if you use the BEA WebGUI Monitor. Otherwise, you can just use 'password,' the default.

## Task 3-2-6: Verifying the Server Installation

At this point, you should verify that the server installation was successful.

To verify the server installation:

1. Go to the `udataobj` directory under `<TUXDIR>`.
2. Ensure that the file `lic.txt` exists.
3. Ensure that the file `tlisten.pw` exists.
4. If the files `lic.txt` and `tlisten.pw` do not exist:
  - Verify that no error messages were displayed during installation of Tuxedo 8.1.
  - Verify that you have sufficient disk space on the directory or file system used for `<TUXDIR>`.
  - Reinstall BEA/Tuxedo 8.1.

---

**Note.** If you will be booting Application Server or Process Scheduler in a shell using a locale other than C, create a symlink in `<TUXDIR>` to the C directory. For instance, if the locale is `Ja_JP`, run this command:

```
ln -s <TUXDIR>/locale/C <TUXDIR>/locale/Ja_JP
```

---

---

## Task 3-3: Installing Micro Focus Net Express for Windows

This section discusses:

- Understanding the Net Express Installation
- Prerequisites
- Installing Net Express

### Understanding the Net Express Installation

Micro Focus® Net Express™ 4.0 is supplied on two CDs. CD-1 contains the Net Express and Net Express Studio software and documentation, and Microsoft Internet Explorer. CD-2 contains the Microsoft Win32 Software Development Kit for Microsoft Windows.

In the following sections, *d:* refers to the drive-ID of your CD-ROM drive, and the Run dialog is the dialog box you see if you select the *Run...* option on the Windows Start menu.

### Prerequisites

To install and use Net Express you must have Microsoft Internet Explorer 5.0 or later installed. You can install Internet Explorer 6.0 from the Net Express 4.0 CD home page.

### Task 3-3-1: Installing Net Express

To install Net Express 4.0:

1. Insert CD-1 into your CD-ROM drive. After a few moments, you should see the Net Express 4.0 CD home page in your browser.
2. If the home page does not appear, enter the following command in the Run dialog box:  
  
`d:\setup.exe`
3. Select Installing on the contents list on the Net Express home page, then select the link Click here to install or upgrade Net Express 4.0. The Startup process begins.
4. Follow the instructions displayed. For information on which of the options to choose for PeopleSoft software, see the instructions for installing Server Express on UNIX.

If you encounter any problems during or after the installation, refer to the Installation Notes on the home page.

---

## Task 3-4: Installing Micro Focus Server Express for UNIX and Linux

This section discusses:

- Understanding Micro Focus Server Express
- Prerequisites

- Installing Server Express
- Installing Remotely
- Mounting and Unmounting CD-ROMs

## Understanding Micro Focus Server Express

This section provides installation instructions for Micro Focus® Server Express™ 4.0 SP2 COBOL compiler and the License Management Facility used to manage product licenses. These instructions are specifically for installing the Server Express COBOL compiler to use with PeopleSoft software. For more general installation instructions or other supporting documentation concerning Server Express, consult the documentation that you received with your Server Express CD.

Throughout this section references are made to \$COBDIR. \$COBDIR is the location at which you install your COBOL products.

All example command lines are specific to sh and ksh. If you are using csh you should use the equivalent csh commands for the examples provided.

### See Also

Micro Focus web site: <http://supportline.microfocus.com/>

Server Express Documentation CD-ROM

## Prerequisites

Each application created using a Server Express product that will be deployed in a UNIX environment must include a Micro Focus Application Server for Server Express license from Micro Focus or from your Micro Focus licensed supplier. Application Server must be installed on the machine on which the application is to run. Please contact your Micro Focus Account Representative or your Micro Focus licensed supplier for details on purchasing Application Server licenses.

If you have a previous Micro Focus COBOL product installed we recommend that you make a backup of any COBOL systems files that you have changed. Examples include cobkeymp, ADISCTRL, cobopt and cobconfig. After you have installed Server Express you might want to apply to the new COBOL product the changes previously applied to these files.

If you are installing a COBOL system over an existing COBOL system, you must first delete the existing system. Alternatively, you might prefer to move your existing COBOL system to another directory until you have verified the new installation.

If you have installed, or plan to install, Application Server or any other Micro Focus product on the same machine as this product, you must install them in different directories.

This Micro Focus product is managed by a License Management Facility (LMF). This facility helps you keep track of the number of licenses you have for the product. In order to use this product it is necessary for you to install the License Management Facility (which is provided with the Server Express software). This software should be installed in a different directory to Server Express; the default directory is /opt/lib/mflmf for HP-UX, /usr/lib/mflmf for RS/6000 and PowerPC systems running AIX, and /opt/lib/mflmf on other systems. If /opt/lib does not exist, use /usr/lib/mflmf instead.

## Task 3-4-1: Installing Server Express

This section provides instructions for extracting the software from CD-ROM on the target environment, and installing the software on the target environment. If the target environment does not have a CD-ROM drive go to the section Installing Remotely. The CDs are in ISO 9660 format and should be mounted using appropriate system-specific mount options. Examples are provided in the section Mounting and Unmounting CD-ROMs.

---

**Note.** The prompts and messages displayed during an installation may vary depending upon the operating system and its version. The examples here are from an installation on an AIX 5.2 operating system.

---

1. Login as root.
2. Insert the CD labeled Server Express into the CD-ROM drive.

There are three different installation CDs, each labeled for use on various UNIX platforms and Linux. Choose the appropriate CD for your installation. If the CD-ROM is not automatically mounted, mount it using the appropriate system commands.

See Mounting and Unmounting CD-ROMs.

3. Change to the CD-ROM directory, then run the setup script:

```
sh ./setup.sh
```

4. Read and accept the license agreement.

The following License Agreement appears. Answer yes (y) when asked if you agree to the terms of the license agreement to continue with the installation.

*Before installing and using this software product you must agree to be bound by the terms and conditions of the end user license agreement ("License Agreement") which accompanies this product. Please take this time to read the License Agreement. If you are not in agreement with the terms and conditions of the License Agreement, please return the product to your Account Representative and your money will be refunded. If you require a replacement copy of the License Agreement, please contact your Account Representative before proceeding with the install process.*

*Do you agree to the terms of the License Agreement? (y/n): y*

5. A prompt appears with a list of the operating systems and hardware platforms for the products included on the CD. Enter a number corresponding to your operating system, and then enter y to continue with the installation.

Here are examples of the lists provided with CDs for various platforms:

- List from the CD labeled “For HP PA-RISC, HP Itanium and Tru64”:

```
----- Server Express 4.0 products on this CD (part number CD-SX-MF014-2) -----
Products for the following platforms are supplied on this CD:
```

```
1)  HP   PA-RISC   running HP/UX 11.x                32/64-bit
2)  HP   Itanium   running HP/UX 11.23            32/64-bit
3)  HP   Alpha     running Tru64 5.1B             32/64-bit

q)  Quit
```

```
Please enter which product you want to install:
```

- List from the CD labeled “For Red Hat Linux and SuSe Linux”:

```
----- Server Express 4.0 products on this CD (part number CD-SX-MF015-3) -----
Products for the following platforms are supplied on this CD:
```

- |    |               |  |           |
|----|---------------|--|-----------|
| 1) | Intel x86     | running Red Hat Enterprise Linux Rel 3/4 | 32-bit    |
| 2) | Intel Itanium | running Red Hat Enterprise Linux Rel 3/4 | 64-bit    |
| 3) | IBM pSeries   | running Red Hat Enterprise Linux Rel 3   | 64-bit    |
| 4) | Intel x86     | running SuSE Linux (SLES 8/9)            | 32-bit    |
| 5) | Intel Itanium | running SuSE Linux (SLES 9)              | 64-bit    |
| 6) | IBM pSeries   | running SuSE Linux (SLES 9)              | 64-bit    |
| 7) | IBM zSeries   | running SuSE Linux (SLES 8/9)            | 31/64-bit |

q) Quit

Please enter which product you want to install:

---

**Note.** For Intel x86 Redhat Enterprise Linux Release 4, choose *1* to install the 32-bit version.

For Intel x86 SuSE Linux, SLES 9, choose *4*, to install the 32-bit version.

For zSeries SuSE Linux, SLES 9, choose *7*, to install the 31/64-bit version.

---

- List from the CD labeled “For AIX, Solaris SPARC and UnixWare”

```
----- Server Express 4.0 products on this CD (part number CD-SX-MF015) -----
Products for the following platforms are supplied on this CD:
```

- |    |            |                                      |           |
|----|------------|--------------------------------------|-----------|
| 1) | Intel x86  | running SCO UnixWare 7.1.3/7.1.4/OS6 | 32-bit    |
| 2) | IBM RS6000 | running AIX 5.1/5.2/5.3              | 32/64-bit |
| 3) | Sun SPARC  | running Solaris 8/9/10               | 32/64-bit |
| 4) | x64        | running Solaris 10                   | 32-bit    |

q) Quit

Please enter which product you want to install: 2

Platform 2 selected: IMB RS6000 running AIX 5.1/5.2/5.3

---

**Note.** For AIX, either 5.1, 5.2, or 5.3, choose 2 to install the 32/64-bit version.

For Solaris, either 8, 9, or 10, choose 3 to install the 32/64-bit version.

---

6. Specify which Server Express product you want to install. Enter *1* to install the Server Express Development System.

Select the product to be installed:

- 1) Server Express Development System - 32/64-bit - PRN=RXCAK/AAL:9i.T4.40.02  
(COBOL and Enterprise Server Development System)

- 2) Enterprise Server Development System

(for installation over previously installed Server Express Development System as in 1 above)

3) Server Express Application Server - 32/64-bit - PRN=R1CAK/AAC:9i.T4.40.02  
(COBOL Deployment System, not required if you are using Development System)

4) Enterprise Server - 32-bit - PRN=RBCAK/AAB:9i.T4.40.02  
(Enterprise Server Deployment System, not required if you are using Development System)

5) Server Express SQL Option - 32-bit  
(for Development only)

q) quit

Enter choice: 1

7. Enter y to confirm that you have enough disk space to install the Server Express Development System software.

Installing the Server Express Development System product.

This product will need a maximum of approximately 92 Mb of disk space.

At a later stage you can choose not to install Enterprise Server Development System which will reduce the final amount of disk space used.

Do you want to continue? (y/n): y

8. Enter the directory name where you want to install the Server Express product, and then press ENTER.  
The example here uses the directory /products/mf/sx40sp2-64bit. If you want to accept the default directory /opt/lib/cobol, just press ENTER. If the directory does not exist, you will be asked if the script should create the directory. When the system asks if you want to continue with the installation, enter y.

---

**Note.** This can be any directory on any file system that has the requisite disk space.

---

Enter the name of the directory where you want to install this product  
(Press Enter for default directory /opt/microfocus/cobol)  
/products/mf/sx40sp2-64bit

/products/mf/sx40sp2-64bit does not exist, do you want to create it? (y/n): y

Installing into /products/mf/sx40sp2-64bit

Do you want to continue? (y/n): y

Copying files. This can take several minutes. Please wait....

9. Reply y if you see a message stating that the product was built on a different version of the operating system. Here is an example from HP-UX:

## Micro Focus Install

This product was built on version B.11.00 of this Operating System, this machine is running B.11.11.

Please confirm that you want to continue with this installation (y/n): **y**

## 10. Verify the system environment details displayed.

The system displays a list of the operating system features. This report will vary depending upon the operating system and its version. The example here is from an installation on an AIX operating system. At the end of the report, the system asks if you understand the reference environment details. Enter y to continue with the installation.

---

**Note.** The report output is presented in “more” format. You can use standard “more” navigation to view the report. For example, press the space bar to page through the report.

---

When you press return you will be shown details of the reference environment (and any compatibility environments).

Please press return when you are ready

This product is certified on the following reference environment:

The command(s) used to gather the information is given following each entry.

## Operating System

-----

AIX 5.1 Maintenance Level 3 plus 'APAR' IY22854.

uname -s

oslevel

## Operating System Patches

-----

instfix -ik IY22854

## C Compiler

-----

/usr/vac/bin/xlc 6.0.0.6

lslpp -L vac.C | grep vac.C | cut -c29-36

## C++ Compiler

-----

/usr/vacpp/bin/xlC 6.0.0.0

lslpp -L vacpp.cmp.core | grep vacpp.cmp.core | cut -c29-36

## Assembler

-----

as 5.1.0.25



```
lslpp -L bos.adt.base | grep bos.adt.base | cut -c29-36
```

Supported versions of Java

-----

```
Java version = 1.3.1
Java vendor = IBM Corporation
Java OS name = AIX
Java OS arch = ppc
Java OS version = 5.1
```

```
Java version = 1.4.1
Java vendor = IBM Corporation
Java OS name = AIX
Java OS arch = ppc
Java OS version = 5.1
```

```
$JAVA_HOME/bin/java -classpath $COBDIR/lib WhatJava
```

Unicode

-----

Unicode mapping tables must be installed for J2EE and Web Services to function correctly. These tables are required for converting between any combination of UTF-16/UCS-2, UTF-8 and other installed locales.

J2EE and Web Services

-----

J2EE and Web Services have been tested with :-

WebSphere 5.1

-----

This product is also certified on the following environment:

Operating System

-----

AIX 5.2.0.0

```
uname -s
oslevel
```

C Compiler

-----

```
/usr/vac/bin/xlc 6.0.0.7
```

```
lslpp -L vac.C | grep vac.C | cut -c29-36
```

```

C++ Compiler
-----
/usr/vacpp/bin/xlC 6.0.0.8

lslpp -L vacpp.cmp.core | grep vacpp.cmp.core | cut -c29-36

Assembler
-----
as 5.2.0.0

lslpp -L bos.adt.base | grep bos.adt.base | cut -c29-36

Please confirm your understanding of the above reference environment
details (y/n): y

```

11. Enter *n* when asked whether you want to use COBOL and Java EJB components together.

The COBOL/Java EJB components of Server Express are not required for PeopleSoft COBOL applications.

Do you want to make use of COBOL and Java working together? (y/n) **n**

After pressing Enter, you see the following message:

```

OK skipping Java setup
Should you want to use Java with COBOL later on
as super user run the command /products/mf/srvexp-4.0.sp1/bin/java_setup
to select the version of Java you want to use.

```

12. Enter *y* when asked whether you want to install Micro Focus LMF. LMF is the License Management Facility. PeopleSoft recommends that LMF be installed as part of the Server Express installation.

This product is protected using the Micro Focus License Management Facility (LMF). Please refer to the Development System Licensing Guide for information relating to the installation of the licensing system and licenses.

If you do not have LMF installed or want to upgrade to the latest version, we recommend you install it now.

Would you like to install LMF now? (y/n)

---

**Note.** You may either install LMF as part of the Server Express installation or you can install it separately. PeopleSoft recommends that you install LMF as part of the Server Express installation.

---



---

**Note.** We suggest that you install LMF in its own directory, not in a subdirectory of Server Express. You should have your Server Express serial number and license keys available to continue with the installation.

---

13. If the installation program detects another version of the license manager, you see a message similar to this asking whether you want to upgrade your License Manager. PeopleSoft recommends upgrading. Enter *y* to upgrade the License Manager.

An older version of License Manager than this one is currently running on the system. It is installed in `/products/mf/svrex-2.0.11/mflmf`.

It is recommended that you upgrade by installing this version. Existing installed licenses will be retained and not affected. If you want to install this new version of License Manager into `/products/mf/sx2011/mflmf`, then the currently running version must be⇒ stopped.

Do you want to proceed with installation into `/products/mf/sx2011/mflmf`

(this will STOP the currently running License Manager) ? (y/n) **y**

14. Enter the name for the directory where you want to install LMF, and then press ENTER.

If you want to accept the default directory `/opt/microfocus/mflmf`, just press ENTER. The directory used for this example is `/products/mflmf40sp2`.

Enter **y** when asked if you want to create the directory and continue with the installation.

Enter the directory name where you wish to install License Manager

(Press Enter for default directory `/opt/microfocus/mflmf`):

**/products/mflmf40sp2**

`/products/mflmf40sp2` does not exist

Do you wish to create it ? (y/n) **y**

Empty database created ok

15. Enter **y** when asked if you want only superuser to access LMF. We recommend that only superuser be allowed to access the license administration system.

you want only superuser to be able to access the License Admin System? (y/n): **y**

16. Enter **y** when asked if you want to enable autostart. We recommend that you allow LMF to start automatically. It is recommended that you let license manager autostart at boot time.

It is recommended that you let license manager autostart at boot time.

Do you want license manager to be automatically started at boot time? (y/n): **y**

When the license manager installation is finished, the follow message will display:

LMF installation complete

Please consult the Development Licensing Guide for detailed information on how to install licenses.

This may be done by changing directory to where the LMF was installed, and typing

`./mflicense`

To run your applications you need a deployment license installed using Apptrack. See your Deployment Licensing Guide for details.

Installing Apptrack...

License availability and use is affected by application design as well as the actual number of users of the application at any given time.

If you are using Model 2 user licenses, you should monitor the license usage closely in the first few weeks after installation in order to ensure that your application is not impacted by unexpected 'out of license' conditions.

For more information please refer to the Deployment Licensing Guide.  
Apptack installation complete

#### 17. Enter *n* when asked if you want to install the Enterprise Server Development System.

The Enterprise Server Development System of Server Express is not required for PeopleSoft COBOL applications.

Do you want to install the Enterprise Server Development System - J2EE, Web Services, etc.? (y/n) **n**

Please wait while the Enterprise Server part of this product is removed.  
This may take a few minutes...

#### 18. For AIX, HP-UX PA-RISC, HP-Itanium, HP ALPHA/Tru64, Solaris, and zSeries SuSE 9, specify the default mode for COBOL: 32-bit or 64-bit.

This product can be used in either 32- or 64-bit modes.  
Please enter either 32 or 64 to set the system default mode.

**64**

System default COBMODE has been set to 64.

- Enter *64* for AIX, HP-UX PA-RISC, HP-Itanium, HP ALPHA/Tru64, Solaris, and zSeries SuSE 9.
- Enter *32* for x86 SuSE9 Linux or x86 Redhat 4.0 Linux.

## Task 3-4-2: Installing Remotely

If your UNIX system does not have a CD-ROM you can install the product by mounting the CD-ROM on another machine, transferring the product to your machine, then running the install. Before you start, make sure you have enough disk space for the product. The space needed is the same as the size of the tar files you use. In addition you need the same amount of temporary space to store the tar files.

1. Mount the CD-ROM on the machine you have selected, using whichever commands are appropriate to the operating system of that machine.

See Mounting and Unmounting CD-ROMs.

2. Look at the file prodlist.txt. This lists the directory names and the products those directories contain.
3. Change to the directory containing the product you want to install.

The products are stored as tar files with filenames in the format *vabccppp.tar* where abcc represents the version number (a.b.cc) of the product (for example, 4000 for version 4.0.00), and *ppp* is cob for Server Express and asp for Application Server.

4. Select the product you want to install and transfer that file (for example, by using ftp) to the required UNIX machine. If you want to install the ODBC drivers, you should also transfer any files called *odbc.tar*
5. On the target UNIX system, create the directory into which you want to install the product, for example:

```
mkdir /opt/lib/cobol
```

6. Extract the contents of the tar file into that directory, for example:

```
cd /opt/lib/cobol
tar -xvf /tmp/v4000cob.tar
```

where /tmp is the path of the directory into which the tar file was transferred from the machine upon which the CD-ROM was mounted.

7. Install the software by entering the following command:

```
sh ./install
```

8. Continue with the installation as described in the previous section.

See Installing Server Express.

## Task 3-4-3: Mounting and Unmounting CD-ROMs

Below are examples of mount and unmount commands for several UNIX systems.

- The mount directory is /cdrom. If /cdrom does not already exist, you must first create it using the command: `mkdir /cdrom`
- Device names differ from system to system.
- The name starting /dev/ is the name of the CD-ROM drive.

Use these commands to mount and unmount the CD-ROM on your machine:

Platform	Mounting Command	Unmounting Command
Compaq Alpha systems running TRU64 UNIX	<code>mount -t cdfs -o noversion /dev/disk/cdrom0c /cdrom</code>	<code>umount /cdrom</code>
HP9000 Series running HP-UX	<code>mount -F cdfs -o cdcase /dev/dsk/c0t4d0 /cdrom</code>	<code>umount /cdrom</code>
IBM RS/6000 and Power PC systems running AIX	<code>mount -v cdrfs -o ro /dev/cd0 /cdrom</code>	<code>umount /cdrom</code>
RedHat Linux	<code>mount /mnt/cdrom</code>	<code>umount /cdrom</code>
SuSE Linux	<code>mount /mnt/cdrom</code>	<code>umount /cdrom</code>
Sun SPARC running Solaris V2.4 or later	CD-ROM is automatically mounted at /cdrom/cdrom0	<code>eject cdrom</code>



## CHAPTER 4

# Using the PeopleSoft Installer

This chapter discusses:

- Understanding the PeopleSoft Installer
- Prerequisites
- Using E-Delivery for the PeopleSoft Installation
- Mounting and Unmounting CD-ROMs (UNIX Only)
- Running the PeopleSoft Installer with a Single CD-ROM Drive (Optional)
- Running the PeopleSoft Installer Without Swapping CDs (Optional)
- Running the PeopleSoft Installer
- Installing the Application CD
- Loading the Multilanguage CD

---

**Note.** You must install the necessary web server products and any additional component software as described in the previous chapters before you run the PeopleSoft Installer.

---

## Understanding the PeopleSoft Installer

This section discusses:

- Defining the PeopleSoft Installer
- Understanding PeopleSoft Servers
- Defining Supported Server Combinations

### Defining the PeopleSoft Installer

The PeopleSoft Installer is a Java-based tool that delivers software to your servers.

The PeopleSoft Installer enables you to transfer files directly to various PeopleSoft servers—including application servers, batch servers, web servers, and database servers—without first copying all files to a file server.

You run the PeopleSoft installer to install the necessary products on the target machines. Which files are installed depends on which products you are licensed for, the operating system on the target machine, the database platform, and the selected server option. The PeopleSoft Installer installs files directly to Windows, UNIX, and Linux machines. PeopleTools and PeopleSoft Applications use the same PeopleSoft Install template. This chapter discusses the installation of PeopleTools, followed by the installation of applications CDs and the Multilanguage CD.

To obtain the software from an FTP site, see “Using E-Delivery for the PeopleSoft Installation.”

---

**Note.** During the installation you select the servers you want to install. Keep in mind that you can install multiple servers at the same time, but they will all be installed on the same machine. If you want to install servers on separate machines, you need to run the PeopleSoft installer on each server machine.

---



---

**Note.** If you need to set up the file server on a separate Windows machine, you should install PeopleTools, any applications CDs, and the Multilanguage CD, as discussed in the next chapter.

---

See “Setting Up the File Server on Windows.”

All licensed components of the PeopleSoft Architecture must be installed on each server. Ideally, you should install the Windows file server component first and then take your PeopleSoft CDs to a CD Jukebox connected to your UNIX systems. If you have multiple servers but no Jukebox for your UNIX environment, you may need to use the CD for each server.

You can install multiple logical servers to the same machine. For example, you can have the application server and the batch server on the same machine. But, if you want to install different servers to different machines, you have to run the PeopleSoft Installer once for each server.

## Understanding PeopleSoft Servers

You can install the whole range of PeopleSoft servers (file server, application server, and so on) with the PeopleSoft Installer. You can install PeopleSoft server software separately or together. Keep in mind which PeopleTools functionality resides in each server:

- *File Server:* All Client executables (PSIDE...), Nvision, Upgrade Assistant or Change Assistant, files and directories necessary to perform upgrade, and Client SQR.
- *Application Server:* PSADMIN, COBOL for remote call, Verity.
- *Web Server:* Windows PeopleSoft Pure Internet Architecture (PIA) install, UNIX web files and shell scripts, Portal Search data files, Verity, and Enterprise Resource Planning Connectors.
- *Process Scheduler Server:* PSADMIN, COBOL, SQR, Verity.
- *Database Server:* Scripts and data directories, files necessary to run Data Mover.

## Defining Supported Server Combinations

The following table lists the supported operating systems for the various PeopleSoft servers for your database platform.

See *Enterprise PeopleTools 8.48 Hardware and Software Requirements*.

---

**Note.** If you plan to install PeopleTools and application software on Red Hat Linux, you must first install X11 client software.

---



Supported operating systems for database servers	Supported operating systems for application servers and batch servers	Supported operating systems for file servers	Supported operating systems for web servers
<ul style="list-style-type: none"> <li>• AIX</li> <li>• HP-UX PA-RISC</li> <li>• HP-UX IPF</li> <li>• SUSE Linux</li> <li>• Red Hat Linux</li> <li>• Solaris</li> <li>• Tru64</li> <li>• Windows</li> </ul>	<ul style="list-style-type: none"> <li>• AIX</li> <li>• HP-UX PA-RISC</li> <li>• HP-UX IPF</li> <li>• SUSE Linux</li> <li>• Red Hat Linux</li> <li>• z/Linux (batch server only)</li> <li>• Solaris</li> <li>• Tru64</li> <li>• Windows</li> </ul>	<ul style="list-style-type: none"> <li>• z/Linux</li> <li>• Windows</li> </ul>	<ul style="list-style-type: none"> <li>• AIX</li> <li>• HP-UX PA-RISC</li> <li>• HP-UX IPF</li> <li>• SUSE Linux</li> <li>• Red Hat Linux</li> <li>• Solaris</li> <li>• Tru64</li> <li>• Windows</li> </ul>

## Prerequisites

The PeopleSoft Installer requires Java Virtual Machine (JVM), which is bundled for all OS platforms. The PeopleSoft Installer searches for the JVMs in the directories in which users would typically install JVM. If the search fails, the bundled JVM will be used. For the PeopleSoft Installer to run successfully, you must have JRE/JDK version 1.4.x or higher.

If you are running on AIX, you must have the JDK package (a normal AIX configuration includes JDK). The default directory for the JDK installation is /usr/java14/jre/bin/java. You cannot change the default directory.

Before running the PeopleSoft installer, you must verify that you have the correct patches for your JVM level.

- For version 1.4.1, see <http://www-106.ibm.com/developerworks/java/jdk/aix/service141.html>.
- For version 1.4.2, see <http://www-106.ibm.com/developerworks/java/jdk/aix/service.html>.

**Note.** If your installation is different than the vendor-defined JVM Search Path, specify where you installed the Java home directory like this:

```
-is:javahome <JAVA_HOME>
```

For example: -is:javahome /jre/prod/1.4.1.

You can always specify your Java home to minimize time searching JVM.

Make sure you have at least 4.5 GB of free space to perform your installation. If you are installing Enterprise Resource Planning Connectors, you will need an additional 400 MB of disk space.

See Running the PeopleSoft Installer.

The installation process also requires at least 1.5 GB of free temporary disk space, which is needed only for the duration of the process. The process uses the directory defined by the TEMP environment variable on your installation computer.

The user who installs PeopleTools must be root or the owner of <PS\_HOME>.

You must have admin privileges to install the PeopleSoft web server.

---

## Task 4-1: Using E-Delivery for the PeopleSoft Installation

You can obtain the software by downloading it as a zip file from a secure FTP site. E-Delivery customers receive a welcome letter that includes the URL for the PeopleSoft E-Delivery site. When you unzip the downloaded file, it creates a folder and extracts all the files into the folder. You can then copy the folder and its contents to any machines that you will use as servers.

The E-Delivery installation process asks for your license code. Obtain your license code by going to the URL included in your welcome letter.

If you obtain your software using E-Delivery, follow the instructions in this chapter for installing PeopleTools, but skip the sections concerning mounting and unmounting CD-ROMs:

- Mounting and Unmounting CD-ROMs (UNIX Only)
- Running the PeopleSoft Installer with a Single CD (Optional)
- Running the PeopleSoft Installer Without Swapping CDs (Optional)

If you obtain your software using E-Delivery, you must carry out an additional step after completing the installation process, creating the database, installing the Application Server, and installing the Pure Internet Architecture. Sign into the PeopleSoft system and navigate to the Installation table on the Products tab. The location of this table will vary depending upon the application you installed. In the Installation table, uncheck the products for which you have not purchased support.

---

**Note.** PeopleSoft does not support CDs that you burn at your own site from E-Delivery files.

---

### See Also

“Setting Up the PeopleSoft Pure Internet Architecture,” Testing the PeopleSoft Pure Internet Architecture Installation

*Application-specific installation instructions*, PeopleSoft Customer Connection (Site Index, installation guides and notes)

---

## Task 4-2: Mounting and Unmounting CD-ROMs (UNIX Only)

This section discusses:

- Understanding CD-ROM Mounting and Unmounting
- Mounting a CD-ROM on HP-UX
- Unmounting a CD-ROM

## Understanding CD-ROM Mounting and Unmounting

This task includes sample commands to mount and unmount CDs for various UNIX platforms. We do not support automounting of CDs; automounting sometimes puts the volume label as part of the mount point, in which case the PeopleSoft Installer will not recognize the second PeopleTools CD.

**Note.** Most, if not all, of these platforms require root access to mount and unmount CDs. You cannot be in the mount point or any of the subdirectories when unmounting the CD. Your devices and your mount point might be different than the examples below.

UNIX Platform	Mounting a CD to /mnt/cdrom	Unmounting the CD
AIX	<code>mount -o ro -v cdrfs /dev/cd0 /mnt/cdrom</code>	<code>umount /mnt/cdrom</code>
HP-UX	<code>mount -r /dev/dsk/c2t1d2 /mnt/cdrom</code>	<code>umount /mnt/cdrom</code>
Linux	<code>mount -t iso9660 -r /dev/cdrom /mnt/cdrom</code>	<code>umount /mnt/cdrom</code>
Solaris	<code>mount -F hsfs -o ro /dev/dsk/c0t6d0s2 /mnt/cdrom</code>	<code>umount /mnt/cdrom</code>
Tru64	<code>mount -r /dev/disk/cdrom0c /mnt/cdrom</code>	<code>umount /mnt/cdrom</code>

### Task 4-2-1: Mounting a CD-ROM on HP-UX

To mount a CD-ROM on HP-UX:

1. Log on as root.
2. Determine the device address for the CD-ROM by entering the following command:

```
# ioscscan -C disk -f -n
```

You will see output similar to the following. This output example indicates that the CD-ROM device file is `/dev/dsk/c1t2d0`:

```
Class I H/W Path      Driver  S/W State  H/W Type  Description
=====
disk  0  8/0/19/0.6.0  sdisk   CLAIMED   DEVICE    IBM       DD RS-39130WS
              /dev/dsk/c0t6d0  /dev/rdisk/c0t6d0
disk  1  8/16/5.2.0     sdisk   CLAIMED   DEVICE    TOSHIBA   CD-ROM XM-6201TA
              /dev/dsk/c1t2d0  /dev/rdisk/c1t2d0
```

3. Create a new directory called `/cdrom` at the root of the file system. This directory becomes the CD-ROM mount point; all CD-ROM files appear under this directory.
4. Determine whether the pfs daemon is running by entering the following command:

```
# ps -ef | grep pfs
```

If the pfs daemon is running, output similar to the following is displayed:

```
root  1681  1651  0 11:39:20 pts/ta    0:00 /usr/sbin/pfs_mountd
root  1682  1681  0 11:39:20 pts/ta    0:00 pfs_mountd.rpc
```

If the pfs daemon is running proceed to step 5. If the pfs daemon is *not* running:

- a. Edit the file `/etc/pfs_fstab` by adding a line similar to the one below to indicate the hardware path for the CD-ROM:

```
/dev/dsk/c0t6d0 /cdrom pfs-rrip xlat=unix 0 0
```

- b. Enter the following commands:

```
# nohup /usr/sbin/pfs_mountd &
# nohup /usr/sbin/pfsd &
```

You must reenter these commands every time you restart your system.

5. To physically mount the CD-ROM, place the CD-ROM in the machine and enter the following command:

```
# /usr/sbin/pfs_mount /cdrom
```

## Task 4-2-2: Unmounting a CD-ROM

To unmount a CD-ROM:

1. After you finish using the CD-ROM, enter the following command:

```
# /usr/sbin/pfs_umount /cdrom
```

2. Eject the CD-ROM.

---

## Task 4-3: Running the PeopleSoft Installer with a Single CD-ROM Drive (Optional)

The following information is provided for mounting PeopleTools 8.4x CDs for a single CD-ROM drive or mounting multiple CDs for easier access.

To run the PeopleSoft Installer on a machine with a single CD:

1. Open two telnet sessions (such as telnet1 and telnet2).
2. In telnet1, mount the first PeopleTools CD to a directory (for example, `/cdrom`).
3. In telnet2, go to any directory *except* `/cdrom` (for example, `/tmp`).

Run the PeopleSoft Installer, pointing to the executable in `/cdrom`—for example:

```
/cdrom/setup.aix -is:javaconsole -console -is:tempdir $HOME/tmp
```

4. Go through the install prompts in telnet2.
5. When prompted in telnet2 to swap media (to change to media 2), go back to telnet1.  
Unmount and eject the CD, then mount the second PeopleTools CD as `/cdrom`.
6. In telnet2, press ENTER to continue the install.

7. Repeat steps 5 and 6 for all the CDs.

---

**Note.** A common problem is that in one of the telnet sessions, the user changes the directory to /cdrom (or any of its subdirectories). As a result, the OS will not allow you to unmount and eject the CD.

---

## Task 4-4: Running the PeopleSoft Installer Without Swapping CDs (Optional)

To avoid swapping CDs, you can either copy the contents of all CDs to a network share, or mount the eight CDs as <anydirectory>/disk1, <anydirectory>/disk2, <anydirectory>/disk3, <anydirectory>/disk4, and so on. You can mount the PeopleTools CD through a CD-ROM shared machine, a Jukebox or an NFS server. For example, on machine A (a CD-ROM drive with PeopleTools 8.4x disk1 share):

```
share /cdrom/pt84cd1r0
```

On machine B (a CD-ROM drive with PeopleTools 8.4x disk2 share):

```
share /cdrom/pt84cd2r0
```

On machine C (a CD-ROM drive with PeopleTools 8.4x disk3 share):

```
share /cdrom/pt84cd3r0
```

On machine D (a CD-ROM drive with PeopleTools 8.4x disk4 share):

```
share /cdrom/pt84cd4r0
```

On machine E (a CD-ROM drive with PeopleTools 8.4x disk5 share):

```
share /cdrom/pt84cd5r0
```

On machine F (a CD-ROM drive with PeopleTools 8.4x disk6 share):

```
share /cdrom/pt84cd6r0
```

On machine G (a CD-ROM drive with PeopleTools 8.4x disk7 share):

```
share /cdrom/pt84cd7r0
```

On machine H (a CD-ROM drive with PeopleTools 8.4x disk8 share):

```
share /cdrom/pt84cd8r0
```

On machine I (the machine where you want to install PeopleTools 8.4x):

```
mkdir -p /pt84/disk1
```

```
mkdir -p /pt84/disk2
```

```
mkdir -p /pt84/disk3
```

```
:
```

```
mkdir -p /pt84/disk8
```

```
mount A: /cdrom/pt84cd1r0 /pt84/disk1
```

```
mount B: /cdrom/pt84cd2r0 /pt84/disk2
```

```
mount C: /cdrom/pt84cd3r0 /pt84/disk3
```

```
:
```

```
mount H: /cdrom/pt84cd7r0 /pt84/disk8
```

---

## Task 4-5: Running the PeopleSoft Installer

This section discusses:

- Understanding the PeopleSoft Installer
- Starting the PeopleSoft Installer
- Running the PeopleSoft Installer in GUI Mode
- Running the PeopleSoft Installer in Console Mode

### Understanding the PeopleSoft Installer

The PeopleSoft Installer guides you through the process of installing files to your various servers. You must run the PeopleSoft Installer on each machine that you use for one or more PeopleSoft server.

The files will be installed into a high-level PeopleSoft directory. This directory, which is referred to in this documentation as <PS\_HOME>, is the location for PeopleTools, application, and multilanguage files. It is a good idea to use a directory name that indicates the application you are installing and the version number, such as HRMS881 for the 8.8 SP1 version of Human Resources.

The following error may appear during your installation:

```
.....The wizard cannot continue because of the following error: could not
load wizard specified in /wizard.inf (104)
```

If you see this error message during the installation of PeopleTools, your application CDs, PeopleSoft Pure Internet Architecture, or when using the Database Configuration Wizard, run <PS\_HOME>/setup/uninstall\_endorsed.sh (for UNIX) or <PS\_HOME>\setup\uninstall\_endorsed.bat (Windows) to uninstall the xerces.jar file that is located in the <PS\_HOME>\jre\lib\endorsed directory. Run <PS\_HOME>/setup/install\_endorsed.sh or <PS\_HOME>\setup\install\_endorsed.bat again to install this xerces.jar back after your installation is complete. This problem happens only when the xerces.jar is installed in <PS\_HOME>\jre\lib\endorsed and when this JRE is used for the installation.

---

**Note.** For HP-UX 11.11 machines, the values of maxfiles and maxfiles\_lim must be at least 2048 in order for the installation to be successful.

---

You can run the installer in GUI mode or in console (text) mode. Running the installer on UNIX in GUI mode requires an X-Windows interface.

---

**Note.** The machine that you use to perform your PeopleTools installation must be running in *256-color mode* or higher when running the CD install, PeopleSoft Pure Internet Architecture install, and Database configuration in Windows. This is not necessary for UNIX or console mode.

---

The PeopleSoft Installer asks whether you want to install supporting features such as Enterprise Resource Planning Connectors, Unicode support, or Environment Management Hub. Before you run the PeopleSoft Installer, you may want to consult supporting documentation to help you in choosing these options. To confirm that Enterprise Resource Planning Connectors will run on the operating systems and database platforms you are using, consult the Hardware and Software Requirements book.

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Integration Broker*

*Enterprise PeopleTools 8.48 PeopleBook: Global Technology*

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

*Enterprise PeopleTools 8.48 Hardware and Software Requirements*, “Server Requirements”

## Task 4-5-1: Starting the PeopleSoft Installer

To start the PeopleSoft Installer in GUI mode, type:

```
[path]setup.<OS> [additional flags]
```

To start the PeopleSoft Installer in console mode, type:

```
[path]setup.<OS> [additional flags] -is:javaconsole -console
```

These are the additional flags:

Flag	Description
-is:tempdir <<specify the temp dir>>	Use this flag to specify the temporary directory to extract temporary files and the bundled JRE if Java is not found. This is needed if you have less than 1.5 GB of free disk space in your temp directory.
-is:log <<specify the log file>>	Use this flag to create a log file if you encountered problems with the native launcher.
-is:javahome <<specify the java home directory>> For example, -is:javahome c:\myjdk1.4.0	Use this flag to specify where you installed the Java home directory, if your installation is different than the vendor-defined JRE Search Path.

The following table lists the native launchers and the platforms to run them:

Operating System Platform	Native Launcher to Use
HP-UX (PA-RISC)	setup.hp
HP-UX (IPF)	setup.hp-ia64
Linux (SuSE or Red Hat)	setup.linux
z/Linux	setup.zlinux <b>Note.</b> See the information below for the correct process to use when running the installer on z/Linux.
Solaris	setup.solaris
Tru64	setup.tru64
Windows	setup.exe

If you are running on z/Linux:

1. Verify the location of the temporary directory for the installation (<TEMPDIR>), or create a temporary directory if necessary. You must have at least 1.5 GB of free temporary disk space. For example,

```
mkdir $HOME/tmp
```

2. Verify that JDK or JRE 1.4.x is installed on the system.
3. Set the JAVA\_HOME environment variable to the directory where the JRE 1.4.x or JDK is installed. For example:

```
export JAVA_HOME=<JAVA_HOME>
```

4. Use this command to start the installer:

```
setup.zlinux -console -is:tempdir <TEMPDIR> -is:nospacecheck -is:javahome <JAVA_⇒  
⇒  
HOME>
```

The JRE installation directory for z/Linux systems is usually /opt/IBMJava2-s390x-142/jre. If your installation is different, substitute the correct directory for <JAVA\_HOME> in the command line.

Note that the PeopleTools installation spans two or more CDs. During the installation process, if you are running the installer with a single CD-ROM drive, you will be prompted to swap to the next CD before you can proceed. To avoid swapping CDs during the installation process, you need to copy the contents of all CDs to a network share (in a very specific way) before launching the PeopleSoft Installer. For example, copy the contents of the first CD to n:\ps\tools\disk1, the contents of the second CD to n:\ps\tools\disk2, and so on. Then launch the setup.xxx that is located at n:\ps\tools\disk1. You can use the same concept to avoid mounting and unmounting CDs on UNIX boxes during the install.

If you mounted your CDs as described in the task “Running the PeopleSoft Installer Without Swapping CDs,” you will not be prompted to swap CDs during the installation.

## Task 4-5-2: Running the PeopleSoft Installer in GUI Mode

To run the PeopleSoft Installer in GUI mode:

1. Launch the installer. Click Next when you see the Welcome screen.
2. Click the radio button to accept the license agreement and click Next.
3. Enter your license code and click Next.
4. Choose a Unicode or non-Unicode database and click Next.

---

**Note.** Unicode databases are beneficial if you intend to deploy your applications globally and would otherwise have to implement multiple databases to handle different languages. However, Unicode databases require much more disk space than non-Unicode databases.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*.

5. Select the servers you want to install and click *Next*.

---

**Note.** If you do not have admin privileges, you will not be able to install PeopleSoft web server. You will have to either acquire admin privileges or deselect the Web Server option to continue.

---



---

**Note.** You can install multiple servers at the same time, but they will all be installed on the same machine. If you want to install servers on separate machines, you need to run the PeopleSoft Installer on each server machine.

---



---

**Note.** You *must* install the PeopleSoft software on your database server in order to run the PeopleSoft Database Configuration Wizard.

---



---

**Note.** You must select the web server if you want to install Enterprise Resource Planning Connectors.

---

See “Creating a Database.”

6. Specify the directory where you want to install PeopleTools and click *Next*.

---

**Note.** Please substitute your network drive and the directory name of your choice for the default selection. The installation directory name cannot contain a space. Note that directory names containing periods or non-US-ASCII characters may not work with some additional component software.

---



---

**Note.** If you are installing on UNIX, do not use Symbolic Links. Use the actual directory.

---

7. *UNIX only:* If you have checked Application Server, Batch Server, or Database Server, you are prompted to enter the TUXEDO directory.
8. Choose whether to install Enterprise Resource Planning Connectors. If you choose Yes, specify the installation directory. Note that this directory must not be the location in which PeopleTools is installed, or a subdirectory of that directory.

---

**Note.** The Enterprise Resource Planning Connectors feature is supported on Windows, Solaris, AIX, HP-UX, and Linux. (If you are on another platform, you will not see this screen.) PeopleSoft provides access to an additional software product, iWay SOAPswitch, which provides ERP adaptors, or connectors, that generate Web Service Description Language (WSDL) for bridging to SAP, Oracle, and Siebel development environments. You can then easily import the WSDL into PeopleSoft to create the desired integration points. For information on configuring iWay SOAPswitch consult the PeopleSoft Integration Broker PeopleBook.

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Integration Broker*

---

**Note.** If you need to refer to the ERP installation log files, they will either be in your user home directory or in the directory in which ERP is installed.

---

9. Specify the location of your Connectivity Program Directory and click *Next*.

The default location for the connectivity software for your platform (as set by the vendor) is listed in the following table. If the database connectivity software was installed to a different directory, enter that path instead.

Platform Name	Default Location of Database Connectivity Libraries
Oracle	C:\oracle\ora81\bin or C:\oracle\ora91\bin

10. Depending on the PeopleSoft servers you selected, choose whether to install the PeopleTools icons and click Next.

11. If you elected to install PeopleTools icons, choose a valid group folder in which to create them and click Next.

12. At this point, enter the configuration information for Environment Management.

Select the machine name of the web server running the Environment Manager Hub. (This will very likely be the machine on which you run PIA). Select the hub port number (the default is 80). This needs to match the PIA port. If you change the port number for the PIA configuration, you must also change the web server listener port number for all the agents in the configuration.properties file.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Using Environment Management Component.”

13. The next screen lists the PeopleTools components (features) for which you are licensed. Accept the defaults for the PeopleTools features and click Next.

- Select *PeopleTools* to install PeopleTools and the PeopleSoft Pure Internet Architecture. This component contains the core PeopleTools files and is required for the proper operation of the PeopleSoft system and the PeopleSoft Pure Internet Architecture.
- Select *PeopleTools System Database* to allow your developers to create custom PeopleTools applications outside of the delivered PeopleSoft Application.
- The *PeopleTools Language Pack* and *PeopleTools Language Development Kit* contain the translated PeopleTools DLLs and the resource files and headers needed to build them.

Select *PeopleTools Language Pack* if you plan on running the Windows components of the installation in languages other than English. This component contains the compiled PeopleSoft translations for the Windows client. If you are not using multiple languages throughout your implementation, you do not need this component.

Select *PeopleTools Language Development Kit* if you plan on modifying or creating your own new translations for the PeopleTools Windows client components. It contains the source and header files required to modify and compile new versions of these translations. Again, you do not need this component if you are not using multiple languages.

14. You will see an installation confirmation window. If the information is correct, choose Next. If you need to modify any of the information, choose the Back button and make your changes.

15. If prompted, change your CD during the installation process.

16. After the files have been installed, click *Finish* to complete the setup.

---

**Note.** If you have chosen to install ERP connectors, you see an informational message indicating that they are being installed.

---

## Task 4-5-3: Running the PeopleSoft Installer in Console Mode

To run the PeopleSoft Installer in console mode:

---

**Note.** The console mode installation is typically used on UNIX platforms.

---

1. Launch the PeopleSoft Installer in console mode. At the Welcome screen, press ENTER to continue.  
See Starting the PeopleSoft Installer.

---

**Note.** If you are running the installer with a single CD-ROM drive, you should always follow the instruction in the task “Running the PeopleSoft Installer with a Single CD.”

---



---

**Note.** If you mounted your CDs (as described in the task “Running the PeopleSoft Installer Without Swapping CDs”), we recommend that you launch the installer from an existing directory on the box, and not the directory that links to the CD, in the following two cases: *for HP-UX*, if the CDs are mounted on Jukebox; *for TRU64*, if the CDs are mounted on a NFS server.

---

2. *Windows only:* Accept the license agreement by selecting 1. Select 0 when you are finished.
3. Enter your license code, and press ENTER to continue.
4. Choose a non-Unicode or Unicode database by selecting the appropriate number, and then 0 to continue.

---

**Note.** You will probably choose to create a non-Unicode database. Unicode databases are beneficial if you intend to deploy your applications globally and would otherwise have to implement multiple databases to handle different languages. However, Unicode databases require much more disk space than non-Unicode databases.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*

5. Select the PeopleSoft servers you want to install.

By default, all of the servers supported for your database platform are selected.

---

**Note.** If you are installing on UNIX, do not use Symbolic Links. Use the actual directory.

---

After your selection, press ENTER; you will be prompted for the destination (for example, <PS\_HOME>). Specify the directory and press ENTER to continue.

---

**Note.** In console mode, the browse option for specifying a different install directory is unavailable.

---



---

**Note.** You must select the web server if you want to install Enterprise Resource Planning Connectors.

---

6. Choose whether to install Enterprise Resource Planning Connectors.

If you choose Yes, specify the installation directory. Note that this directory must not be the location in which PeopleTools is installed, or a subdirectory of that directory.

---

**Note.** For the current release, the Enterprise Resource Planning Connectors feature is supported only on Windows, Solaris, AIX, HP-UX, and Linux. (If you are on another platform, you will not see this screen.) PeopleSoft provides access to a third-party software product, iWay SOAPswitch, which provides ERP adaptors, or connectors, that generate Web Service Description Language (WSDL) for touchpoints in SAP, Oracle, and Siebel systems. You can then easily import the WSDL into PeopleSoft to create the desired integration points.

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Integration Broker*

7. *UNIX only:* If you checked Application Server, Batch Server, or Database Server, you are prompted to enter the TUXEDO directory.
8. At this point, enter the configuration for Environment Management. Select the machine name and port number.

Select the machine name of the web server running the Environment Manager Hub. (This will very likely be the machine on which you run PIA). Select the hub port number (the default is 80). This needs to match the PIA port. If you change the port number for the PIA configuration, you must also change the web server listener port number for all the agents in the configuration.properties file.

See *Enterprise PeopleTools 8.48 PeopleBook: Software Updates*, “Configuring and Running Environment Management Components.”

9. *Windows only:* Specify the database connectivity directory.

The default location for the connectivity software for your platform (as set by the vendor) is listed in the following table. If the database connectivity software was installed to a different directory, enter that path instead.

Platform Name	Default Location of Database Connectivity Libraries
Oracle	C:\oracle\ora81\bin or C:\oracle\ora91\bin

10. *Windows only:* Indicate whether you want icons to be created.
11. Choose the products that you wish to install:

To select/deselect a feature or to view its children, type its number

1. [X] PeopleTools
2. [X] PeopleTools System Database
3. [X] PeopleTools Language Pack
4. [X] PeopleTools Language Development Kit

12. At this point, you can toggle the install status of each product. Press 0 and then ENTER to continue and the PeopleSoft Installer will give you a summary of your selection. This summary will depend on your earlier selections.

PeopleTools 8.48 will be installed in the following location:

c:\temp\ptest

with the following features:

PeopleTools

PeopleTools System Database

PeopleTools Language Pack

PeopleTools Language Development Kit

The following PeopleSoft Servers were selected by you:

PeopleSoft Application Server

PeopleSoft Batch Server

```

PeopleSoft Database Server
PeopleSoft File Server
PeopleSoft Web Server

```

```

Database Type:
<Database Name>

```

```

ERP Connectors Installation:
Not selected

```

```

Environment Hub Configuration:
Hub machine name: PSEMHUB
Hub port number: 80

```

```

Press 1 for Next, 2 for Previous, 3 to Cancel, or 4 to Redisplay [1]

```

13. Press ENTER to start the installation. You may be prompted to insert the next CD.
14. The PeopleSoft Installer will create a text-based progress bar to indicate the progress of the install.
15. Please press ENTER to exit.

---

**Note.** For UNIX platforms, if you chose PeopleSoft servers that require a JRE, you see the “Unpacking JRE” message after the progress bar.

---



---

**Note.** If you chose to install ERP connectors, you see an informational message indicating that they are being installed.

---

## Task 4-6: Installing the Application CD

After installing the PeopleTools CD, install the application CD to the same <PS\_HOME> directory. The screens may look slightly different depending upon which application you install.

---

**Note.** If you are installing more than one application, it is a good idea to create an application-specific <PS\_HOME> and carry out an installation of PeopleTools for each application. This helps you to maintain your applications more efficiently, since you can easily match each application version to the correct version of PeopleTools.

---



---

**Note.** To properly install a Demo database, you must select both the System Database and the Demo Database options during the installation of your PeopleSoft applications.

---



---

**Note.** The next chapter discusses the installation of the application database component to the database server.

---

To install the application CD:

1. Insert the application CD into the CD-ROM drive and run the setup application from the root directory of the CD.

See Running the PeopleSoft Installer.

2. After reading the Welcome information, click Next.
3. Click Yes to agree to the Software License Agreement.
4. Enter the PeopleSoft license code and click Next.

---

**Note.** All modules for the product line you are installing exist on the PeopleSoft Application and Database CDs regardless of the modules purchased. Your unique license code will “unlock” the combination of modules you purchased. A master license key no longer exists.

---

5. Choose a *Unicode* or a *non-Unicode* database and click Next.
6. Select the servers you want to install and click Next.
7. Specify the directory where you want to install the application. You must specify the <PS\_HOME> directory; that is the directory where you installed PeopleTools for a given server. Click Next.
8. A feature selection screen appears. (What you see depends on what product you are installing.) Select the features that you wish to install and click Next.
9. In the confirmation dialog box, click Next to begin the installation. A message box appears that indicates the progress of the installation.
10. Click Finish to exit the PeopleSoft installation program.

---

## Task 4-7: Loading the Multilanguage CD

If you have licensed and selected to install languages other than English, you need to load the application-specific PeopleSoft Multilanguage CD. Each application CD has a corresponding Multilanguage CD that contains all the non-English translations.

---

**Warning!** The release numbers for the application CD and the Multilanguage CD must be in sync. For example, if you are installing HRMS 8.3, you can only use the Multilanguage CD HRMS 8.3 ML; you cannot use HRMS 8 SP1.

---



---

**Note.** Load the Multilanguage CD after you install the PeopleTools CD and the Application CD. Install the Multilanguage CD to the same <PS\_HOME> as you used for the PeopleTools and Application CD.

---

To load the Multilanguage CD:

1. Insert the Multilanguage CD into the CD-ROM drive and run the setup application from the root directory of the CD.
2. After reading the Welcome message, click Next.
3. Click Yes to agree to the Software License Agreement.
4. Enter the PeopleSoft license code and click Next.
5. Choose to create a *Unicode* or a *non-Unicode* database and click Next.
6. You will be asked to select the components you want to install.

(What you see depends upon what product you are installing.) Select the applications you want to install and click Next.

7. From the confirmation dialog box, click Next to begin the installation.  
A message box appears indicating the progress of the installation.
8. Click Finish to exit the PeopleSoft installation program.





## CHAPTER 5

# Setting Up the Windows File Server

This chapter discusses:

- Understanding the File Server
- Mapping a Drive on the Install Workstation
- Installing the PeopleTools CD to the File Server
- Installing the Application CD
- Loading the Multilanguage CD

---

## Understanding the File Server

The file server is the environment (or file) repository for the PeopleTools Development Environment, which is required for the Database Configuration Wizard to run. The file server is also used for the files necessary to perform an upgrade. This includes Upgrade Assistant or Change Assistant and all of the executables and scripts necessary to perform an upgrade. You will apply patches and updates from PeopleSoft Customer Connection directly to the file server and then copy the updated files to your other servers. In addition, the file server is a source repository for COBOL and SQR.

See “Preparing for Installation,” Installing Supporting Applications.

---

**Note.** *The information in this chapter applies to installations on both UNIX and Windows.* If you are doing an installation only for UNIX boxes, you need a Windows file server. If you are working only on Windows, and you set up your file server in the previous chapter, you can skip this chapter.

---

---

**Note.** If you have used the PeopleSoft Server Transfer program in the past, it is no longer needed, because the PeopleSoft Installer lets you install files directly to the designated server.

---

In some cases you may choose to set up local copies of the PeopleSoft executables on the PeopleTools Development Environment and Windows batch servers, rather than mapping to a shared directory on the file server. You can use the instructions in this chapter to perform such local installations.

---

**Warning!** The PeopleSoft Installer installs COBOL source code from the CD to your Windows file server and to all UNIX servers, but not to the rest of your Windows servers.

*If you are running Windows and your application requires COBOL, we require that you maintain a central repository of your COBOL source code on the file server.* If you apply a patch or make customizations, apply them to the file server first, and then disseminate them across your servers as described here. *If you have Windows file, application, and batch servers,* you should compile the COBOL on the file server and copy the cblbina, cblbinu, or cblbine directory (depending on whether you have an ASCII, Unicode or EBCDIC database) to all the application and batch servers. The COBOL compiler itself does not have to be on the file server—as long as the workstation on which it is installed has full access to the shared drives.

For every type of UNIX operating system, we recommend that you designate a single server (either application or batch) as the compile server, so that you can compile COBOL from a central location and then distribute the cblbin directory to the rest of your application and batch servers. If you use this approach, you need only copy patches or customizations from the file server to the compile server. In this case, you would install a COBOL compiler on the master (or compile) server and either the COBOL compiler or runtime on the rest. If you prefer, you can copy patches or customizations from the file server to all of your UNIX servers and compile the COBOL on each machine.

---

**Note.** If you want to copy compiled COBOL programs from one UNIX server to another, both servers must be on the same operating system.

For example, if you compile on Solaris 8 for the application server and the Process Scheduler is on AIX, you cannot copy the compiled program (you will also need to compile on the AIX computer).

---

**Note.** The format of COBOL source file names of patches or customizations on the file server should always be UPPERCASE.cbl. to ensure compatibility with your UNIX servers.

---

## Task 5-1: Mapping a Drive on the Install Workstation

If you need to install the CDs to the file server from a networked install workstation, map a drive letter to the top-level PeopleSoft directory (<PS\_HOME>) from the install workstation. The <PS\_HOME> directory must be shared, and you must have write permission from the install workstation to the file server. The <PS\_HOME> directory was discussed in the previous chapter.

See “Using the PeopleSoft Installer.”

---

**Note.** If you install the CDs directly from the file server's CD-ROM drive, you can skip this task. Installing directly from the file server is preferable for installation because you do not need a drive to be mapped. It also provides faster performance, as there is no need for a network connection between the workstation and the server.

---

From the install workstation, create a logical drive that points to the <PS\_HOME> directory.

On a Windows network, use Windows Explorer to map to the drive on the file server to which you are installing; or use the NET USE command, for example:

```
NET USE N: \\SERVER1\<PS_HOME>
```

On a Novell network, use the MAP command:

```
MAP ROOT N:=SERVER1/SYS:<PS_HOME>
```

In this example, *SERVER1* is the name of the file server.

---

## Task 5-2: Installing the PeopleTools CD to the File Server

To install the PeopleTools CD-ROM to the file server:

1. Insert the PeopleTools CD into the CD-ROM drive and run the setup application from the root directory of the CD.  
A welcome screen appears.
2. Click Next.  
The licensing agreement appears.
3. Click Yes and enter your 31-digit license code from the license code sheet.
4. Click Next and choose whether to use a Unicode or a non-Unicode database.

See "Preparing for Installation," Planning Multilingual Strategy.

---

**Note.** Unicode databases are beneficial to customers who intend to deploy their applications globally and would otherwise have to implement multiple databases to handle different languages. However, Unicode databases require much more disk space than non-Unicode databases.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*.

5. Select *PeopleSoft File Server* and click Next.
6. Click the Browse button, choose the path of the <PS\_HOME> directory on the file server, and click OK.  
Click Next.
7. Choose whether to install the Enterprise Resource Planning connectors.

If you choose Yes, specify the installation directory. Note that this directory must not be the location in which PeopleTools is installed, or a subdirectory of that directory.

---

**Note.** The Enterprise Resource Planning Connectors feature is supported on Windows, Solaris, AIX, HP-UX, and Linux. (If you are on another platform, you will not see this screen.) PeopleSoft provides access to an additional software product, iWay SOAPswitch, which provides ERP adaptors, or connectors, that generate Web Service Description Language (WSDL) for bridging to SAP, Oracle, and Siebel development environments. You can then easily import the WSDL into PeopleSoft to create the desired integration points. For information on configuring iWay SOAPswitch consult the PeopleSoft Integration Broker PeopleBook.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Integration Broker*.

8. Select the location of your connectivity software.

The default location for your connectivity software (as set by the vendor) is listed in the following table. If the database connectivity software was installed to a different directory, enter that path instead.

Platform Name	Location of Database Connectivity Libraries
Oracle	C:\oracle\ora81\bin or C:\oracle\ora91\bin

9. In the next dialog box, choose Yes to install an Installation icon group on the install workstation. Then click Next.
10. Then specify the desired program group folder (the default is PeopleTools 8.4 Installation) and click Next (a program folder name cannot contain any of the following characters: \ / : \* ? " < > |). This step creates an icon group on the installing machine that supplies shortcuts to every program needed throughout the installation process.
11. Enter the configuration information for Environment Management.  
Select the machine name of the web server running the Environment Manager Hub. (This will very likely be the machine on which you run PIA). Select the hub port number (the default is 80). This needs to match the PIA port. If you change the port number for the PIA configuration, you must also change the web server listener port number for all the agents in the configuration.properties file.  
  
See *Enterprise PeopleTools 8.48 PeopleBook: Software Updates*, “Configuring and Running Environment Management Components.”
12. A component selection window appears. This screen lists the PeopleTools components for which you are licensed. Select the products to install from the Components list.

---

**Note.** The components PeopleTools Language Pack and PeopleTools Language Development Kit contain the translated PeopleTools DLLs and the resource files and headers needed to build them. If you do not need translated files, you may choose to not install these two components.

---

- Select *PeopleTools* to install PeopleTools Development Environment and the Upgrade Environment. This component contains the core PeopleTools files and is required for the proper operation of your PeopleSoft Development and Upgrade environment.
  - Select *PeopleTools Language Pack* if you plan on running the Windows components of your installation in languages other than English. This component contains the compiled PeopleSoft translations for the Windows client. If you are not using multiple languages throughout your implementation, you don't need this component.
  - Select *PeopleTools Language Development Kit* if you plan on modifying or creating your own new translations for the PeopleTools Windows client components. It contains the source and header files required to modify and compile new versions of these translations. Again, you do not need this component if you are not using multiple languages.
  - Select *PeopleTools System Database* to allow your developers to create custom PeopleTools applications outside of the delivered PeopleSoft Application.
13. Click Next. You should see the Confirm Products dialog box.
  14. Click Next to verify that you want to install to the specified directory. You'll see a progress indicator so you can monitor the progress of your installation.
  15. When the setup program successfully completes the installation of PeopleTools, click Finish to exit the installation program.

---

## Task 5-3: Installing the Application CD

After installing the PeopleTools CD, install the application CD to the same <PS\_HOME> directory. The screens may look slightly different depending upon which application you install.

---

**Note.** If you are installing more than one application, it is a good idea to create an application-specific <PS\_HOME> and carry out an installation of PeopleTools for each application. This helps you to maintain your applications more efficiently, since you can easily match each application version to the correct version of PeopleTools.

---

---

**Note.** To properly install a Demo database, you must select both the System Database and the Demo Database options during the installation of your PeopleSoft applications.

---

---

**Note.** The next chapter discusses the installation of the application database component to the database server.

---

To install the application CD:

1. Insert the application CD into the CD-ROM drive and run the setup application from the root directory of the CD.

See Running the PeopleSoft Installer.

2. After reading the Welcome information, click Next.
3. Click Yes to agree to the Software License Agreement.
4. Enter the PeopleSoft license code and click Next.

---

**Note.** All modules for the product line you are installing exist on the PeopleSoft Application and Database CDs regardless of the modules purchased. Your unique license code will “unlock” the combination of modules you purchased. A master license key no longer exists.

---

5. Choose a *Unicode* or a *non-Unicode* database and click Next.
6. Select the servers you want to install and click Next.
7. Specify the directory where you want to install the application. You must specify the <PS\_HOME> directory; that is the directory where you installed PeopleTools for a given server. Click Next.
8. A feature selection screen appears. (What you see depends on what product you are installing.) Select the features that you wish to install and click Next.
9. In the confirmation dialog box, click Next to begin the installation. A message box appears that indicates the progress of the installation.
10. Click Finish to exit the PeopleSoft installation program.

---

## Task 5-4: Loading the Multilanguage CD

If you have licensed and selected to install languages other than English, you need to load the application-specific PeopleSoft Multilanguage CD. Each application CD has a corresponding Multilanguage CD that contains all the non-English translations.

---

**Warning!** The release numbers for the application CD and the Multilanguage CD must be in sync. For example, if you are installing HRMS 8.3, you can only use the Multilanguage CD HRMS 8.3 ML; you cannot use HRMS 8 SP1.

---

---

**Note.** Load the Multilanguage CD after you install the PeopleTools CD and the Application CD. Install the Multilanguage CD to the same <PS\_HOME> as you used for the PeopleTools and Application CD.

---

To load the Multilanguage CD:

1. Insert the Multilanguage CD into the CD-ROM drive and run the setup application from the root directory of the CD.
2. After reading the Welcome message, click Next.
3. Click Yes to agree to the Software License Agreement.
4. Enter the PeopleSoft license code and click Next.
5. Choose to create a *Unicode* or a *non-Unicode* database and click Next.
6. You will be asked to select the components you want to install.  
(What you see depends upon what product you are installing.) Select the applications you want to install and click Next.
7. From the confirmation dialog box, click Next to begin the installation.  
A message box appears indicating the progress of the installation.
8. Click Finish to exit the PeopleSoft installation program.

## CHAPTER 6

# Setting Up the Install Workstation

This chapter discusses:

- Understanding the Install Workstation
- Prerequisites
- Starting Configuration Manager
- Setting Startup Options
- Editing the Default Profile
- Running Client Setup

---

## Understanding the Install Workstation

This chapter describes how to set up a PeopleSoft Windows-based client for connecting to the database server in two-tier mode, specifically for the purpose of performing install-related tasks from the workstation. You must configure at least one two-tier Windows-based client for running the Server Transfer, Data Mover and SQR processes required for setting up the batch server and for creating the PeopleSoft database. For some installations you may wish to set up multiple install workstations, so that you can perform asynchronous tasks at the same time; for example, you could create and populate multiple databases simultaneously. You can quickly configure multiple workstations by exporting a configuration file from one workstation and importing it to another workstation.

### See Also

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

---

## Prerequisites

The following tasks are prerequisites for setting up the install workstation:

- The workstation must have database connectivity software installed.
- You must have planned your database creation strategy. You should know the precise names of the databases that you intend to create.
- Make sure that you have created your connect strategy. You must use a Connect ID. You should know both the Connect ID and Connect password.
- The workstation must have a logical drive mapped to <PS\_HOME> on the file server (or, if the file server and install workstation are one and the same, <PS\_HOME> can be installed on a local drive).

- The person performing the installation must have read access to the <PS\_HOME> directory.

If this is the same workstation on which the CD installation was performed, it should have a PeopleTools 8.4 Installation program group, which was created when you loaded the PeopleTools CD-ROM. This isn't a requirement, but it does make it more convenient to run the PeopleTools install applications.

### See Also

“Preparing for Installation”

“Setting Up the File Server”

---

## Task 6-1: Starting Configuration Manager

Configuration Manager is a utility for configuring workstations being used as the PeopleTools Development Environment. These are its principal functions:

- Sets up and make changes to PeopleSoft configuration settings.
- Creates a program group containing Windows shortcuts to PeopleSoft applications.
- Installs local DLLs.
- Installs the PeopleSoft ODBC driver, which is used for PeopleSoft Open Query and for Crystal Reports, and sets up an ODBC user data source name (DSN).

The first time you run Configuration Manager on the client, it will populate certain fields with default values specified in a configuration file stored on the file server, specifically: <PS\_HOME>\setup\pstools.cfg. This configuration file was set up when you ran the CD installation. Once you set up and run Configuration Manager, it will populate fields using values that are stored in the Windows system registry.

To start Configuration Manager, do one of the following:

- Select *Start, Programs, PeopleTools 8.4 Installation, Configuration Manager*. (This program group will be available if you installed the PeopleSoft CDs from this workstation.)
- If the *PeopleSoft 8.4* program group was not installed on this workstation, run pscfg.exe directly from the <PS\_HOME>\bin\client\winx86 directory on the file server.

---

## Task 6-2: Setting Startup Options

The Startup tab of Configuration Manager sets the default options for the PeopleSoft sign-on screen that is used for connecting to a PeopleSoft database. It also contains a setting that specifies the local directory for storing cached PeopleSoft data.

To set Startup options:

1. Make sure you are viewing the Configuration Manager Startup tab (this tab is what you see if you started Configuration Manager as described in the previous task).

Set the following options:

- *Database type* — Verify the type of RDBMS. This should already be set to Oracle.



- *Application Server Name* — This option appears if you select a database type of Application Server. It is where you enter your application server name if you are setting up a three-tier connection.
  - *Database name* — The name of the default database to connect to. Enter the name of one of the databases that you intend to create.
  - *User ID* — The name of the default user that will appear in the sign-on screen. This can be any valid user name, although for installation setup it normally matches the name of one of the built-in PeopleSoft users (typically PS or VP1) that will be installed in the database.
  - *Connect ID and Connect Password* — Type your connect ID and password into these fields. Connect ID is required for PeopleSoft 8.
2. Select the Crystal/Bus. Interlink/JDeveloper tab and set the following options:
    - *Crystal EXEs Path* — Set this to the location of your Crystal Reports executables.
    - *Default Crystal Reports* — Set this to the path on the file server where the Crystal reports reside. Note that the specified path should not contain reports run in production. This option is used when running from PSQuery to Crystal.
    - *Use trace during execution* — This option is used when running Crystal Reports from Process Scheduler on the client.
    - *Business Interlink Directory* — You can leave this option blank. If you do so, the system uses its default directory <PS\_HOME>\bin\<client>|<server>\winx86\interfacedrivers.
    - *JDeveloper Directory* — See the appendix “Using the XSLT Mapper with Oracle BPEL Process Manager” for information on using this option.


---

## Task 6-3: Editing the Default Profile

Begin by editing the default profile for the workstation. Among other things, this will verify that the paths to <PS\_HOME> and its subdirectories are correctly set, which is required for subsequent tasks.

To edit the default profile:

1. Select the Profile tab in Configuration Manager. Only one profile, the Default Profile, has been defined.
2. Select Edit to display the Edit Profile dialog box, and then select the Process Scheduler tab.
3. In the Process Scheduler tab, verify the following options; these should have been set correctly by the CD installation program:
  - Verify that the PeopleSoft Home Directory (PS\_HOME) field is set to the path to <PS\_HOME> on the file server.
  - Set the SQR Executables (SQRBIN) field to the file server directory where SQR for Windows was installed when you ran the PeopleSoft Installer.
  - Set the SQR Flags (PSSQRFLAGS) field to `-ZIF<PS_HOME>\sqr\pssqr.ini`.
  - Set the SQR Report Search 1 (PSSQR1) field to `<PS_HOME>\sqr`. The remaining SQR Report Search fields can be left blank, because no additional SQR report directories have been created yet.
4. Select the Common tab of the Edit Profile dialog box.



Edit Profile dialog box

The following fields are used to set Data Mover default input, output, and log directories.

- Verify that the Input Directory and Output Directory fields are set to `<PS_HOME>\data`. This directory will store the Data Mover scripts required to populate the PeopleSoft database.
- Set the Log Directory to a local workstation directory to store the Data Mover log files. The default is `C:\TEMP`.

5. Select OK to close the Edit Profile dialog box.

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Using PeopleSoft Configuration Manager”

## Task 6-4: Running Client Setup

The Client Setup tab does the following:

- Installs a PeopleSoft program group on the workstation.
- Installs the PeopleSoft ODBC driver required for Open Query and Crystal Reports.
- Installs system DLLs on the workstation.

These Client Setup functions are performed when you click OK or Apply from Configuration Manager only if the Install Workstation option on the Client Setup tab is selected.

---

**Note.** Any files installed by Client Setup on the workstation from the file server, including ODBC driver files, use the paths specified in the default profile.

---

To run Client Setup:

1. Select the Client Setup tab in Configuration Manager.
2. In the Group Title text box enter the name of the program group for the icons you want on the client workstation. (A program group name cannot contain any of the following characters: \ / : \* ? " < > |)

You can call the program group anything you want, but this documentation uses the default name, *PeopleTools 8.4*.

3. If you do not have a PeopleTools 8.4 program group set up on the workstation, be sure to check the following two options for installing shortcuts to applications essential for installation:

---

**Note.** When you run Client Setup, it will uninstall any existing shortcuts in the PeopleTools 8.4 program group, and install shortcuts for the applications you have selected. If you subsequently want to install or uninstall shortcuts, you can always re-run Client Setup.

---

- *Data Mover*
- *Configuration Manager*

4. If applicable, select the option Install PeopleSoft ODBC Driver. This installs the ODBC driver, and sets up a user ODBC data source name required by PeopleSoft Query and by Crystal Reports.
5. Select the option Install Workstation.

This check box determines whether Client Setup runs when you click Apply or OK in Configuration Manager. If this option is not selected, Client Setup will create or update settings in the registry, but it won't set up the PeopleTools 8.4 program group or install local DLLs.

6. Click OK to run Client Setup and close Configuration Manager.

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Query*

*Enterprise PeopleTools 8.48 PeopleBook: Crystal Reports for PeopleSoft*



## CHAPTER 7A

# Creating a Database on Windows

This chapter discusses:

- Understanding the Database Configuration Wizard
- Fulfilling PeopleSoft Database Configuration Wizard Prerequisites
- Running the Database Configuration Wizard
- Checking the Log Files and Troubleshooting
- Updating Database to Latest PeopleTools Release
- Running Additional Data Mover Scripts
- Installing a Multilingual PeopleTools System Database
- Running VERSION Application Engine Program
- Running SQR Reports
- Checking the Database
- Running SETSPACE.SQR
- Running Alter Audit

---

## Understanding the Database Configuration Wizard

The Database Configuration Wizard is a tool designed to simplify your PeopleSoft database installation. When you run the Database Configuration Wizard, Data Mover is also running silently.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*.

---

**Important!** Do not forget that application-specific installation steps are provided in a separate document specific to the application. For instance, if you are performing PeopleSoft CRM installation, you need both this PeopleTools installation guide and you also need any additional instructions provided by CRM. PeopleSoft Customer Connection provides installation guides that are specific to your application.

---

See PeopleSoft Customer Connection (Site Index, installation guides and notes).

You can still use the manual process for creating a PeopleSoft database instead of using the Database Configuration Wizard. The manual process is mandatory for some configurations.

---

**Important!** The Database Configuration Wizard cannot be used for Windows 2003 64 bit. To create a database on that platform, you must use the manual method of creating a database on Windows, as documented in the appendix “Creating a Database Manually.”

---

---

**Important!** The Database Configuration Wizard cannot be used with Oracle 10g RAC. To create a database with this database platform, you must use the manual method of creating a database, as documented in the appendix “Creating a Database Manually on Windows.”

---

See “Creating a Database Manually on Windows.”

See “Setting Up the PeopleSoft Installation with Oracle 10g RAC.”

---

## Task 7A-1: Fulfilling PeopleSoft Database Configuration Wizard Prerequisites

This section discusses:

- Installing the PeopleSoft Database Server Components on the Database Server
- Obtaining Windows Administrator Authority
- Meeting the Minimum Memory Requirements
- Installing the Oracle RDBMS Software
- Creating an INIT<SID>.ORA File
- Creating Target Directory Paths
- Setting Up Target Database Connectivity
- Update Connection Information on the Server
- Unsetting the ORACLE\_SID Environment Variable

### Task 7A-1-1: Installing the PeopleSoft Database Server Components on the Database Server

To run the PeopleSoft Database Configuration Wizard, your setup *must* fulfill these requirements:

- You must have installed the PeopleTools software on your database server by running the PeopleSoft Installer.
- You must have chosen the Database Server option during the PeopleTools software installation.
- You must have installed the Database component of your application CD to your database server.
- You must have the PeopleTools Development Environment set up to create your database.
- You must run the Database Configuration Wizard at the database server.

#### See Also

“Using the PeopleSoft Installer”

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Using PeopleSoft Configuration Manager”

## Task 7A-1-2: Obtaining Windows Administrator Authority

To run the Database Configuration Wizard, you must be a Windows administrator of the target server. This is necessary because the Database Configuration Wizard executes the Oracle 'ORADIM' command to add a Windows service. On UNIX, an Oracle SID is comprised of many different processes. On Windows, an Oracle SID is run as a single Windows service, and you need to be an administrator to create that service.

## Task 7A-1-3: Meeting the Minimum Memory Requirements

When the Database Configuration Wizard is invoked, you are running Oracle, Java, the installer engine, and Data Mover in addition to all other running processes, which tends to use a lot of virtual memory.

You need a minimum of 384 MB of virtual memory on Windows server machines to execute the Database Configuration Wizard successfully.

To set these options on Windows machines, select Start, Settings, Control Panel, System. Double-click *System*, select the Performance tab, and on the virtual memory block, enter 384 MB or more for both initial and maximum paging size.

Assuming you've started with a clean environment (Windows service and old files deleted), you may encounter the following Oracle errors if insufficient memory is available:

- Value not allowed.
- Insufficient privileges.
- Oracle not available.
- Shared realm memory already exists.
- Internal error code arguments.

## Task 7A-1-4: Installing the Oracle RDBMS Software

The Oracle RDBMS software must be installed before you run the Database Configuration Wizard. The following discussion assumes that you are familiar with Oracle administration tasks. During the execution of the Wizard, references are made to an existing Oracle RDBMS installation:

\$ORACLE\_HOME and \$ORACLE\_HOME\bin

---

**Note.** Beginning with PeopleTools PT8.46, the PeopleSoft Database Configuration Wizard supports either Oracle 9i or Oracle 10g.

---

## Task 7A-1-5: Creating an INIT<SID>.ORA File

You must create an init.ora with the naming convention of init<SID>.ora in the ORACLE\_HOME\database directory of your Oracle installation.

Please add or modify the following init.ora parameters:

```
DB_NAME = <SID>
```

```
DB_FILES = specify max allowed per your OS, typically 1021
```

```
CONTROL_FILES = (/filesystem1/cntrl1<SID>, /filesystem2/cntrl2<SID>)
```

```
OPEN_CURSORS = 255 <This is a minimum value. You may choose to set this higher>
```

```
db_block_size = 8192
```

---

**Note.** The default DB\_BLOCK\_SIZE in the init.ora file is 8192 or 8K. For PeopleSoft ANSI databases this is more than adequate. For PeopleSoft Unicode databases (for example, CHARACTER\_SET UTF8), a DB\_BLOCK\_SIZE value of 8K is required.

---

Beginning with PeopleTools PT8.46, PeopleTools supports Oracle 9i and 10g. The PeopleSoft scripts are delivered to work across all versions of the Oracle RDBMS that PeopleSoft will support for this release of PeopleTools.

Because Oracle 9i is now the minimum Oracle RDBMS version supported, the PeopleSoft database creation scripts are delivered to support Automatic Undo. That is, the scripts PeopleSoft delivers assume an init.ora with UNDO\_MANAGEMENT parm set to AUTO.

If you want to use Manual Undo (for example, rollback segments), then install the database manually as described in the appendix, “Creating a Database Manually.” Installing the database manually will allow you to modify the scripts as necessary to implement Manual Undo.

The Database Configuration Wizard will prompt you for a SID name. This init<SID>.ora will be referenced in the CREATEDB.SQL script, which is executed by the Database Configuration Wizard.

If you choose to use an Oracle Password file, you must create one using the ORAPWD utility, as illustrated in this example:

```
Set ORACLE_SID=FDMO
orapwd file=c:\ora9i\database\pwdtemp2.ora password=manager entries=5
```

If you choose not to use an Oracle Password file, make one of the following changes to the init.ora file. You must make one of these changes *before* running the Database Configuration Wizard:

- Comment out or remove this line:

```
#remote_login_passwordfile=EXCLUSIVE
```

- Set the parameter to *NONE*:

```
remote_login_passwordfile=NONE
```

---

**Note.** The init<SID>.ora will reference “target” directories to write control files, log files, and system files, as well as target locations for Oracle Logs, User Trace Files, and so on. These “target” directory paths must exist or the Database Configuration Wizard will fail. See the following section for details.

---

## See Also

“Required Operating System, RDBMS & Additional Component Patches Required for Installation,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise, your database platform)

## Task 7A-1-6: Creating Target Directory Paths

As mentioned, you must create the directory path structure for the target directories referenced in the scripts executed by the Database Configuration Wizard. The Database Configuration Wizard will not create directories on the fly; it expects the directories to exist.



The <SID> variable for which the Database Configuration Wizard prompts you is automatically prepended to the directory path structure referenced in the various database creation scripts executed by the Database Configuration Wizard.

---

**Note.** If you want to use something other than the delivered directory paths, you need to modify the CREATEDB.SQL, CREATEDB10.SQL, UTLSPACE.SQL, and xxDDL.SQL scripts in the scripts directory under <PS\_HOME>, replacing the delivered paths with paths appropriate for your site installation prior to running the Database Configuration Wizard.

---

You are also asked for several mount points. On Windows you just specify the drive. An example is C. Note that no other notation is necessary; you *do not* need to specify C: or C:\.

Here are some examples of directory path structure references.

The delivered CREATEDB.SQL script makes the following directory path structure references:

---

**Note.** Portions of the script have been omitted for clarity.

---

```
startup nomount pfile=%ORACLE_HOME%\database\init<SID>.ora
DATAFILE      '<drive>:\oradata\<SID>\system01.dbf'      SIZE    400M
LOGFILE       '<drive>:\oradata\<SID>\log01.dbf'          SIZE    70M,
              '<drive>:\oradata\<SID>\log02.dbf'          SIZE    70M;
```

The init<SID>.ora parameter file that is referenced in the CREATEDB.SQL script makes the following directory path structure references:

---

**Note.** Portions of the init<SID>.ora parameter file have been omitted for clarity. These paths are hardcoded by the user creating the init<SID>.ora parameter file. The Data Configuration Wizard will not make any substitutions for mount point, target directory path, or <SID> in the init<SID>.ora file.

---

*Control file references:*

```
control_files = ("c:\apps\db\oracle9i\oradata\ORCL\control01.ctl", "c:\apps\db⇒
\oracle9i\oradata\ORCL\control02.ctl", "c:\apps\db\oracle9i\oradata\ORCL⇒
\control03.ctl")
background_dump_dest = c:\apps\db\Oracle9i\admin\ORCL\bdump
core_dump_dest = c:\apps\db\Oracle9i\admin\ORCL\cdump
user_dump_dest = c:\apps\db\Oracle9i\admin\ORCL\udump
```

The delivered UTLSPACE.SQL script makes the following directory path structure references:

---

**Note.** Portions of the script have been omitted for clarity.

---

```
CREATE TABLESPACE      PSRBS
DATAFILE                '<drive>:\oradata\<SID>\psrbs01.dbf'      SIZE 300M
DEFAULT STORAGE (
    INITIAL              4M
    NEXT                 4M
    PCTINCREASE          0 );

CREATE TEMPORARY TABLESPACE      PSTEMP
TEMPFILE                        '<drive>:\oradata\<SID>\pstemp01.dbf'      SIZE 300M
EXTENT MANAGEMENT LOCAL UNIFORM SIZE 128K
```

```
CREATE TABLESPACE      PSDEFAULT
DATAFILE                '<drive>:\oradata\<SID>\psdefault.dbf'      SIZE 10M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
```

The delivered XXDDL.SQL scripts make the following directory path structure references:

---

**Note.** This is a sample of the first several Create Tablespace SQL statements in the xxDDL.SQL script. The rest of the script has been omitted here for clarity.

---

```
CREATE TABLESPACE PSIMAGE DATAFILE '<drive>:\oradata\<SID>\psimage.dbf' SIZE 8M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
/
CREATE TABLESPACE PSINDEX DATAFILE '<drive>:\oradata\<SID>\psindex.dbf' SIZE 64M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
/
CREATE TABLESPACE PTAPP DATAFILE '<drive>:\oradata\<SID>\ptapp.dbf' SIZE 4M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
/
```

## Task 7A-1-7: Setting Up Target Database Connectivity

You must add a TNS entry to \$ORACLE\_HOME\network\admin\tnsnames.ora, because during the Data Mover Load phase, the Database Configuration Wizard will try to connect to the newly created SID via a remote connection string—for example:

```
ACCESSID/ACCESSPWD@TNS_ALIAS
```

Update the connection information in TNSNAMES.ORA on your server to reflect your Database Name, Oracle SID, and Server Name.

---

**Note.** Make sure that you stop and start (or reload) the Oracle Net listener.

---


## Task 7A-1-8: Update Connection Information on the Server

Make sure that you add the new SID name or existing SID name to the \$ORACLE\_HOME\network\admin\LISTENER.ORA on the database server.

Stop and start (or reload) the Oracle Net listener.

## Task 7A-1-9: Unsetting the ORACLE\_SID Environment Variable

Make sure that you *do not* have the ORACLE\_SID parameter set in your user or system environment variables. The ORACLE\_SID is set by the Database Configuration Wizard during execution.



System Environment Variables

## Task 7A-2: Running the Database Configuration Wizard


When you run the Database Configuration Wizard, Data Mover typically does the following:

1. IMPORT \* Create all the PeopleTools and application tables with their indexes.
2. ENCRYPT\_PASSWORD \* Encrypt security information for the database.
3. CREATE\_TRIGGER \* Create application required triggers.
4. REPLACE\_VIEW \* Create PeopleSoft views.
5. CREATE\_TEMP\_TABLE \* Create PeopleSoft temporary tables.

If Data Mover fails at any of the above steps, it will complete the rest of the step, but will not start the next step—instead the Wizard aborts and tells the user what file to review for the detailed error message. There is a separate log file for each step, saved in the log directory. If Data Mover fails at step 1 or 2, it is fatal. If Data Mover fails at step 3 or 4, it is not necessarily fatal. You may continue the next steps manually.


To run the Database Configuration Wizard:

1. From the directory <PS\_HOME>\setup\DatabaseInstall, double click setup.exe.
2. In the Welcome window, click Next to continue.



PeopleSoft Database Configuration Wizard Welcome window

3. When prompted for the location of PS\_HOME, modify the directory name to reflect your <PS\_HOME> installation (the high level directory where you installed the PeopleTools and application software) and click Next to continue.




Entering the PS\_HOME directory on the Database Configuration Wizard window

4. Select Unicode or Non-Unicode, based upon the language strategy you defined in chapter 1, under "Planning Multilingual Strategy."

5. If you select Non-Unicode, select the appropriate character set and database type.

**Note.** The Wizard detects which database files are available for loading based on your specific installation; you will only see the database types that are valid based on the PeopleSoft application features you have installed.

This character set selection is substituted and used in the CREATEDB.SQL script.



Choosing the character set and database create type


6. If you select Unicode, just select the database type.
7. Click Next.
8. Select which PeopleSoft application database to load and click Next.

(The available selections will depend upon which application CDs you have licensed and installed.)

If you installed the Multilanguage CD, each application will be listed several times, once for each language. If you are installing languages other than English, make sure to select the appropriate language data files for each application you select in English. This will load the translated database objects.


See "Preparing for Installation," Planning Multilingual Strategy.

If you are installing an application in any language other than English, you must also select the English component of the application. For example, for HRMS if you select HR-French, you must also select HR-English. This ensures that you install the necessary base-language components.



Choosing the application database on the Database configuration wizard


9. When prompted for the location of \$ORACLE\_HOME\bin and \$ORACLE\_HOME, modify the locations as necessary and click Next.



Specifying the location for sqlplus and ORACLE\_HOME in the Database Configuration Wizard window


10. The PeopleSoft Database Configuration Wizard now supports both Oracle9i and Oracle 10g.

Select the appropriate Oracle version. Then either create an Oracle SID and load a PeopleSoft database or use an existing Oracle SID to load the PeopleSoft database. These instructions assume you use an existing SID. Click Next to continue.



Choosing an Oracle version and SID on the Database Configuration Wizard window

11. Otherwise, select Create database on existing server.
12. Enter the appropriate server information for your database, clicking Next when you are done.



Entering the server information on the Database Configuration Wizard window

Make sure that you scroll down to all parameters if needed. Whichever option you choose, the following prompts will remain the same. The Database Configuration Wizard will use just the information it needs to complete the tasks necessary based on whether you chose to create a new SID or use an existing one.

13. Again enter the appropriate values.

Scroll down to make sure you review all of the parameters. Click Next to continue.

Entering Oracle server connection information in the Database Configuration Wizard window

---

**Note.** You must limit the owner ID (access ID) and connect ID to eight characters or less.

---



---

**Note.** The PSADMIN.SQL script is run by the Database Configuration Wizard for every PeopleSoft database that you are going to create. When prompted for a default tablespace name, select PSDEFAULT if you are using PeopleSoft naming conventions, or your site equivalent if you are not using PeopleSoft naming conventions.

---



---

**Note.** The path in the preceding prompt for init<SID>.ora must match the path of the init<SID>.ora file you created under the task “Fulfilling the PeopleSoft Database Configuration Wizard Prerequisites” earlier in this chapter.

---

14. Select the base language (the default is US English) and click Next.


The Select base language selection is used to determine what primary base language the customer wants to run their PeopleSoft application on. If you choose a language other than English, the base language will be swapped during the database creation script.

See “Planning for Installation,” Planning Multilingual Strategy.



This step applies only if your users will be operating PeopleSoft applications primarily in one particular language other than English. This step gives a performance boost to the language you designate as the base language, but would require more administrative overhead than leaving English as the base language does.


See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*.



Selecting the base language on the Database Configuration Wizard window

15. At the confirmation dialog box, check the database configuration you selected, and if it is correct, click Next.

If you need to change any settings, click Back.



Confirmation message on the Database Configuration Wizard window


16. Various messages appear indicating that the Database Configuration Wizard is creating the uninstaller, executing psadmin.sql for Oracle, and executing dbsetup.dms for Oracle.

When Data Mover is invoked you get a new message dialog box indicating the status of the Data Mover run.

---

**Note.** It is always a good idea to let the installation run through even if you encounter a problem. If for any reason you manually abort the installation, you will need to delete the file vpd.properties in order for the Database Configuration Wizard to successfully update SID when you run the Wizard again. The file vpd.properties is located under the WINNT directory.

---



Data Mover dialog box

17. When you see a message that the PeopleSoft Database Configuration has been successfully installed, click Finish.

## Task 7A-3: Checking the Log Files and Troubleshooting

This section discusses:

- Checking the Log Files
- Troubleshooting
- Optimizing for Performance

### Task 7A-3-1: Checking the Log Files

After the Database Configuration Wizard finishes its execution, look for all log output in the <PS\_HOME>/log directory. Open all the log files. There is a log file for each of the steps that the Database Configuration Wizard carries out—importing, encrypting passwords, creating triggers, replacing views, and creating temp tables. *None should contain error messages.*

### Task 7A-3-2: Troubleshooting

If the Database Configuration Wizard did not complete successfully, please read this troubleshooting information. If your script has stopped midway (this can happen for a number of reasons) you need to edit the Data Mover script generated automatically by the Database Configuration Wizard and restart Data Mover manually. The Data Mover script files have the extension .dms and are sometimes referred to as “DMS scripts.”

The generated Data Mover import script is saved in the <PS\_HOME>/scripts directory. The script conforms to the following naming convention:

<dbname>ora.dms

To edit and restart the DMS script:

1. Determine the record that was being imported (that is, which IMPORT command was running) when the script stopped.

(See the note below for additional information on determining where the script stopped.)

---

**Note.** When building a DMO database or a multilingual database, adding the 'SET START' statement can be tricky because the Data Mover script used to load the database will include more than one IMPORT statement. The key is to view the LOG files and determine which IMPORT section of the script Data Mover failed on. If the failure occurred during the first IMPORT, add the 'SET START' statement before the first 'IMPORT \*;' statement. If the failure occurred during a subsequent IMPORT, comment out all statements preceding the 'IMPORT \*;' statement where the failure occurred and add the 'SET START' statement before the 'IMPORT \*;' statement of the section in which the failure occurred. *This is very important.* If you see any 'unique index constraint' error messages in the 'building required indexes' section, your IMPORT script failed during a subsequent IMPORT but the 'SET START' statement was added to the first IMPORT. In this situation, you can run the Data Mover script in its originally generated form, with only one modification. In the first IMPORT section, change the statement 'IMPORT \*;' to 'REPLACE\_DATA \*;'. This will delete all the data in the tables, and re-import it. This process will take some time to run, and you will need to separately create each of the indexes that failed.

---

2. Invoke Data Mover outside of the Database Configuration Wizard by selecting Start, Programs, PeopleTools 8.4x, Data Mover (or going to <PS\_HOME>\bin\client\winx86 and running psdmt.exe).

The PeopleSoft Logon window appears.

3. Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.

This starts Data Mover in *bootstrap mode*.

The input window should display the DMS import script for the database. The script has the format <dbname>ora.dms.

4. If necessary, select File, Open, and browse to the <PS\_HOME>/scripts directory to find the appropriate DMS script.
5. Add the following line before the offending IMPORT command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The 'SET START' will begin the Data Mover import at the specified record name.

---

**Note.** It is a good idea to change the name of the log file in the script before each attempt at running it. This ensures that you have a separate log file for each attempt, if you run the import more than once.

---

*Example:*

If the script stops and the table is partially inserted with a message similar to this one:

```
Importing PSPNLFIELD
Rows inserted into PSPNLFIELD
```

3000

First drop the partially inserted table (for example, record) by using the DROP TABLE command, and then restart Data Mover at the record that failed using the SET START command and continue the Data Mover import. With PeopleTools 8.4, this can be done in a single pass.

Add the following lines before the offending 'IMPORT \*;' command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
DROP TABLE <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The 'SET START' will begin the Data Mover import at the specified record name.

*Example of the original script:*

```
REM - PeopleTools System Database - US English
/
SET LOG ptengs.log;
SET INPUT ptengs.db;
SET COMMIT 30000;
SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE OFF;
IMPORT *;
```

*Example of script after modification, with changes in bold font:*

```
REM - PeopleTools System Database - US English
/
SET LOG ptengs2.log;
SET INPUT ptengs.db;
SET COMMIT 30000;
SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE OFF;
SET START PSPNLFIELD;
DROP TABLE PSPNLFIELD;
IMPORT *;
```

For the DROP Statement, for records with a non-leading PS recname, add PS\_ to the beginning of the recname; otherwise the table will not be found.

6. Restart the script (File, Run Script).

## Task 7A-3-3: Optimizing for Performance

The following tips can help you save time when running the Data Mover scripts:

- Run Data Mover from the fastest workstation available.
- Run only a single instance of Data Mover, and do not have any other applications running during the import.

- In the PeopleSoft Configuration Manager, turn off all trace options.  
Tracing during a DMS load will add considerable time to the process.
- Copy the database file over to the workstation so that Data Mover can access it locally instead of over the network.
- Run Data Mover on the database server with the .db or .dat file located locally.

If you are comfortable changing the options available for an Oracle instance, you might consider “tuning” the instance used for the import. Some of these options are appropriate only during the import, so you may not want to keep them in effect after the import is complete.

For best performance during a Data Mover import, set these options as follows:

- Increase the number of database blocks.
- Increase the shared\_pool.
- Use an 8K Oracle block size.
- Use very large rollback segments.
- Increase the size of the redo log files when you create the database.
- Use asynchronous read and write.
- Use multiple db\_writers.

---

## Task 7A-4: Updating Database to Latest PeopleTools Release

This section discusses:

- Understanding Database Updates
- Cleaning Up Data
- Updating PeopleTools System Tables
- Updating PeopleTools Database Objects
- Updating PeopleTools Multilingual Objects
- Deleting Obsolete PeopleTools Database Objects
- Altering PeopleTools Tables
- Migrating Records to New Tablespaces
- Updating PeopleTools System Data
- Running PeopleTools Conversions
- Converting Integration Broker
- Changing the User Interface

## Understanding Database Updates

Your PeopleSoft application database may be on a PeopleTools release prior to the version that you are currently running. For you to be able to sign on to your database after running the Data Mover script to load your database, the PeopleTools versions for your database and your file server must match. The steps in this task ensure that your PeopleSoft database is in sync with the PeopleTools version that you are running.

---

**Note.** You will use Application Designer for several steps in this portion of the installation. Consult the Application Designer documentation if you have questions.

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Application Designer*

---

**Note.** If you are installing a PeopleTools System Database or if your database is delivered on PeopleTools 8.48, the delivered database already contains the updated PeopleTools objects. Skip this task and continue with the install at the task “Running Additional Data Mover Scripts.”

---

Here is a list of applications for which this task must be run because the version of the database that was shipped is different than the version of PeopleTools that you are running. If your application release is earlier than the release listed in the table, you must run this task:

Application Release	Application Database Version	Requires Update to 8.48?
CRM 8.9	8.45	Yes
CRM 9.0	8.48	No
ELS 8.8 SP1	8.43	Yes
ELS 9.0	8.47	Yes
EPM 8.9	8.46	Yes
EPM 9.0	8.48	No
Fin/SCM 8.9	8.46	Yes
Fin/SCM 9.0	8.48	No
HRMS 8.8 SP1	8.43	Yes
HRMS 8.9	8.45	Yes
Portal 8.8	8.42	Yes
Portal 8.9	8.46	Yes
RMS 8.9	8.45	Yes
RMS 8.95	8.46	Yes
SIM 8.9	8.45	Yes

If your application is not listed above, look for your application and PeopleTools release information on Customer Connection. Navigate to Site Index, product releases (roadmaps and schedules), Release Definitions, select your product line, and then select the product you are installing. If the Tools version is not 8.48, you must run this task. Otherwise, continue to the task “Running Additional Data Mover Scripts.”

## Task 7A-4-1: Cleaning Up Data

If your database is delivered on PeopleTools 8.48 or higher, do *not* run this step, and instead, proceed to Updating PeopleTools System Tables. If your database is delivered on PeopleTools 8.47 or earlier, perform this step to clean out obsolete message data.

---

**Warning!** Performing this task when updating from PeopleTools 8.48 or later will wipe out current valid data that is needed for your system to function properly.

---

Message functionality and structure changed as of PeopleTools 8.48 and the old data is obsolete. Edit <PS\_HOME>\scripts\ptupgibdel.sql to delete data from the tables that only exist in the old PeopleTools release. Open the script and make the following modifications, and then run the modified script using your SQL query tool:

1. Search for the string “--- End of PT8.<xx> ---” where <xx> represents the last two digits of the PeopleTools release you are upgrading from.
2. Delete the entire portion of the script below this string.
3. Save the script as <PS\_HOME>\scripts\ptupgibdel8<xx>.sql where <xx> represents the last two digits of the PeopleTools release you are upgrading from, as determined in Step 1.

---

**Note.** Save the script using the naming convention shown above! This will preserve the original script for use in updating other databases at different PeopleTools releases.

---

4. Using a SQL query tool, run the ptupgibdel8<xx>.sql script against your PeopleSoft database.

## Task 7A-4-2: Updating PeopleTools System Tables

Run SQL scripts to update your PeopleTools system tables to the latest PeopleTools release (currently 8.48).

Use a query tool, such as Query SQL\*Plus, to run SQL scripts while in the PeopleSoft database.

1. Run the appropriate SQL scripts for your application version.

The following scripts are found in the <PS\_HOME>\scripts directory.

Use the scripts in the following table for non-Unicode databases:

Application Database Version	Required Scripts for Non-Unicode Databases
8.40	rel841, rel842, rel843, rel844, rel845, rel846, rel847, and rel848
8.41	rel842, rel843, rel844, rel845, rel846, rel847, and rel848
8.42	rel843, rel844, rel845, rel846, rel847, and rel848
8.43	rel844, rel845, rel846, rel847, and rel848
8.44	rel845, rel846, rel847, and rel848



Application Database Version	Required Scripts for Non-Unicode Databases
8.45	rel846, rel847, and rel848
8.46	rel847 and rel848
8.47	rel848 <b>Note.</b> If you are installing ELM 9.0, run rel848n.sql instead.
8.48	None

Use the scripts in the following table for Unicode databases:

Application Database Version	Required Scripts for Unicode Databases
8.40	rel841u, rel842u, rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.41	rel842u, rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.42	rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.43	rel844u, rel845u, rel846u, rel847u, and rel848u
8.44	rel845u, rel846u, rel847u, and rel848u
8.45	rel846u, rel847u, and rel848u
8.46	rel847u and rel848u
8.47	rel848u <b>Note.</b> If you are installing ELM 9.0, run rel848un.sql instead.
8.48	None

- If the application database version you are installing is either 8.42 or 8.43, run the following SQL command:

```
DROP TABLE PS_PSMCFQUEUESLANG
```

---

**Note.** PS\_PSMCFQUEUESLANG may not exist in some 8.43 application databases. Do *not* drop the table PSMCFQUEUESLANG.

---

- If the application database you are installing is 8.45 or lower, run the following SQL command:

```
DROP TABLE PSOPTSTATUS
```

- Edit and run the grant.sql script in the <PS\_HOME>\scripts directory. This will grant permissions to the Connect ID.
- Invoke Data Mover by running <PS\_HOME>\bin\client\winx86\psdmt.exe.

The PeopleSoft Logon window appears.

Log on using a valid PeopleSoft Operator ID, such as PS for HRMS or VP1 for FDM.

6. Run the storedddl.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update your platform-specific DDL model statements.  
Log out of Data Mover for the next step.
7. Invoke Data Mover by running <PS\_HOME>\bin\client\winx86\psdmt.exe.  
The PeopleSoft Logon window appears.  
Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.  
This will start Data Mover in bootstrap mode.
8. Run the msgtlsupg.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update the PeopleTools messages in your database.

### Task 7A-4-3: Updating PeopleTools Database Objects

To update PeopleTools database objects to the current release you must be in Application Designer. The Copy from File functionality lets you update your PeopleTools database objects from a file. You must perform this step to bring the database objects in sync with the PeopleTools release. Failure to run this step will introduce problems to your environment.


To update PeopleTools database objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PPLTLS84CUR from the list of projects and click the Select button.

---

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.


---



Selecting PPLTLS84CUR in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and then click the Copy button. When the progress window disappears, the project has been copied.



The Copy From File dialog box showing that PPLTLS84CUR will be copied

If you see the following types of messages in the output window do not worry; they are acceptable because the field label properties were copied with the object definition:

- Definition Name: OPERPSWD.OPERPSWD not copied, entire definition already copied (62,32).
- Definition Name: OPRID.NEW not copied, entire definition already copied (62,32).

## Task 7A-4-4: Updating PeopleTools Multilingual Objects

If you are currently updating a PeopleSoft Multilingual Database, you must also apply the project PPLTLS84CURML, which contains the translations of the PeopleTools Objects.


**Note.** If you have licensed and installed French into this database, copy the PPLTLSML project instead of the PPLTLS84CURML project for French *only*. Substitute the project name PPLTLSML instead of PPLTLS84CURML in the instructions below. Copy the PPLTLS84CURML project to update any non-French languages that are installed in the database.

To update PeopleTools database objects to the current release you must be in Application Designer. The Copy from File functionality lets you update your PeopleTools database objects from a file.

To apply the translation project for PeopleTools 8.48:


1. Bring up the Configuration Manager and select the Display tab.  
Ensure that the language matches the base language of your database. Always run upgrade copy as a base language user.
2. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
3. Select Tools, Copy Project, From File.
4. In the resulting dialog box, change the import directory to <PS\_HOME>\projects.
5. Select PPLTLS84CURML from the list of projects and click the Select button.

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.



Selecting PPLTLS84CURML in the Copy From File dialog box

6. The Upgrade Copy dialog box appears.  
Make sure that all object types are selected.
7. Click the Options button, select the Copy Options tab, and ensure that only the non-English languages you have installed are selected.  
Please note that English and Common should *not* be selected.
8. Select the languages that you are currently installing from the Copy Options dialog box.
9. Click the Copy button.



The Copy From File dialog box showing that PPLTLS84CURML will be copied

When the progress dialog box disappears, the project has been copied.

## Task 7A-4-5: Deleting Obsolete PeopleTools Database Objects

This process removes obsolete PeopleTools objects from your database. To update PeopleTools database objects to the current release you must be in Application Designer. You will use the Copy from File functionality to delete the obsolete objects from the database.


To delete obsolete PeopleTools database objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PPLTLS84CURDEL from the list of projects and click Select.

---

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.


---



Selecting PPLTLS84CURDEL in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and click the Copy button. When the progress dialog box disappears, the project has been copied.



The Copy From File dialog box showing that PPLTLS84CURDEL will be copied

**Note.** If you are applying a required for install PeopleTools patch *and if a database project is included*, apply the database projects now. Make sure to read the patch release notes to find out if database changes are in the patch.

## Task 7A-4-6: Altering PeopleTools Tables


ALTER AUDIT is an online utility used to check whether the PeopleTools tables are synchronized with the underlying SQL data tables in your database. This process compares the data structures of your database tables with the PeopleTools tables to uncover inconsistencies. ALTER AUDIT then reports its findings. In this release, we expect to see differences between the database structure and the tools tables. You will generate and run a SQL script to synchronize the PeopleTools table definitions with the underlying tables in your database.

To alter PeopleTools tables:

1. Launch PeopleTools and sign on to the installed database.
2. From the Application Designer, select File, Open.
3. Select *Project*, enter *PPLTLS84CUR* in the name dialog box, and click OK.
4. Select Build, Project.

The Build dialog box appears:






The Build dialog box

5. Select Create Tables and Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
6. Select Build script file in the Build Execute Options region.
7. Click Settings.

The Build Settings dialog box appears:




Build Settings dialog box: Scripts tab

8. Select the Scripts tab.
9. Select Write Alter comments to script.
10. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region.


Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.

Make sure that the option Alter by Table Rename is selected in the Alter Table Options region.



Build Settings dialog box: Alter tab

11. Select the Create tab and ensure that the Skip table if it already exists, Recreate view if it already exists, and Recreate index only if modified options are selected.



Build Settings dialog box: Create tab

12. Click OK.

The Build dialog box reappears.

13. Click Build.

14. Click Close when the process is completed.

15. Edit the generated SQL script for the correct tablespace names and sizing parameters if you are not using delivered PeopleSoft Tablespace names.

16. Run the generated SQL script in your platform-specific query tool to bring your database structure in sync with the PeopleTools tables.

## Task 7A-4-7: Migrating Records to New Tablespaces

This section discusses:

- Copying the Tablespace Record Project
- Running Alter Tools Tables


### Copying the Tablespace Record Project

PeopleSoft has moved some delivered tables to different Tablespaces in 8.44 and above. You must run this step to move the tables.

To copy the Tablespace Record project:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PT84TBLSPC from the list of projects, and click Select.

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.




Selecting PT84TBLSPC in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and click the Options button. Navigate to General Options and make sure that the Take DDL from Source option is selected.


Click OK.



Upgrade Options dialog box: General Options tab

5. Click the Copy button.

When the progress dialog box disappears, the project has been copied.




The Copy From File dialog box showing that PT84TBLSPC will be copied

## Running Alter Tools Tables

To run Alter Tools tables:

1. Launch PeopleTools and sign on to Installed database.
2. From the Application Designer, select File, Open.
3. Select Project, enter PT84TBLSPC in the name dialog box, and click OK.
4. Select Build, Project.


The Build dialog box appears:



The Build dialog box

5. Select Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
6. Select Build script file in the Build Execute Options region.
7. Click Settings.

The Build Settings dialog box appears:




Build Settings dialog box: Scripts tab

8. Select the Scripts tab.
9. Select Write Alter comments to script.
10. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region, and that the Alter even if no changes check box has been selected.

Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.





Build Settings dialog box: Alter tab

11. Click OK.

The Build dialog box reappears.

12. Click Build.
13. Click Close when the process is completed.
14. Edit the generated SQL script for the correct Tablespace names and sizing parameters if you are not using delivered PeopleSoft Tablespace names.
15. Run the generated SQL script in your platform-specific query tool move the tables to the correct Tablespaces.

## Task 7A-4-8: Updating PeopleTools System Data

Data Mover scripts that update PeopleTools system data are run to enable new features and load new messages for the PeopleTools 8.48 release. Several of the scripts that you need to run are dependent upon the version of the application you are running.

See Understanding Database Updates.

To update PeopleTools system data:

1. Invoke Data Mover by running `<PS_HOME>\bin\client\winx86\psdmt.exe`.

The PeopleSoft Logon window appears.

2. Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.

This will start Data Mover in bootstrap mode.

3. Run the appropriate Data Mover scripts for your application database version.

The application database version refers to the version before you started this step. Be sure to run the scripts in the order listed. The scripts are found in the <PS\_HOME>\scripts directory:

Application Database Version	Scripts to Run
8.40	pt841tls, pt842tls, pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.41	pt842tls, pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.42	pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.43	pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.44	pt845tls, pt846tls, pt847tls, and pt848tls
8.45	pt846tls, pt847tls, and pt848tls
8.46	pt847tls and pt848tls
8.47	pt848tls
8.48	None

4. Run the pslanguages.dms Data Mover script in the <PS\_HOME>\scripts directory.

This script loads language-specific seed data.

5. Run the tlsupgnoncomp.dms Data Mover script in the <PS\_HOME>\scripts directory.

This will import the updated PeopleTools Trees, Roles, and Access Groups into your database.

6. If you are a Multilingual customer, from the Data Mover script that was created for your PeopleSoft database installation, find the UPDATE to PSLANGUAGES.

The statement should look similar to the following:

```
UPDATE PSLANGUAGES SET INSTALLED=1 WHERE LANGUAGE_CD = 'xxx' ;
```

where xxx is one of the PeopleSoft three-letter language code identifiers, as described earlier.

See “Preparing for Installation,” Planning Multilingual Strategy.

Run the SQL command identified above using your SQL tool.

7. Open Data Mover using a valid PeopleSoft Operator ID, such as PS for HRMS or VP1 for FDM.
8. If you are a Multilingual customer and have licensed non-English languages, run the pt848tlsxxx.dms scripts in the <PS\_HOME>\scripts directory.

This will update the language-specific PeopleTools system data in your database.

---

**Note.** The portion of the script name *xxx* is equivalent to the language code (that is, FRA, CFR, GER, JPN, and so on) of the non-English languages you have installed. There will be a Data Mover script for each non-English language.

---

9. Run the msgtleng.dms Data Mover Script in the <PS\_HOME>\scripts directory.  
Non-English message data was loaded in the pt848tlsx.dms scripts. This will update the messages in your database.
10. Run the ptstreng.dms Data Mover script in the <PS\_HOME>\scripts directory.  
Non-English system data was loaded in the pt848tlsx.dms scripts. This will update the SQR strings in your database.
11. Run the storept.dms Data Mover script in the <PS\_HOME>\src\cb\base directory.  
This will update your PeopleTools COBOL stored statements.
12. Run the ptdefnsec.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update the PeopleTools Definition Security group.
13. Run the createvw.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will recreate all the views in your database.

## Task 7A-4-9: Running PeopleTools Conversions

This section discusses:

- Convert Portal Objects
- Convert Query Headings
- Convert Setup Manager
- Convert Navigation Collection and Pagelet Wizard Data
- Convert Additional Pagelet Wizard Data

### Convert Portal Objects

The Application Engine program UPG844PORTAL splits PSPRSMDEFN.PORTAL\_URLTEXT into segments. This is performed for PeopleSoft Components URLs to extract Menu, Component, and Market information. Record, Field, Event, and Function Names are extracted from Iscript URLs. This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role. The following SQL will identify which users have the PeopleSoft Administrator or Portal Administrator roles:

```
select ROLEUSER, ROLENAME from PSROLEUSER where ROLENAME in ('PeopleSoft⇒
Administrator','Portal Administrator')
```

Run the UPG844PORTAL Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R⇒
INSTALL -AI UPG844PORTAL
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <oprid>, respectively. However, be aware that <pswd> is not the same as the connect password that you entered on the Configuration Manager startup tab. Enter a value for <pswd> that is the password you want to be associated with the <oprid>.

See “Setting Up the Install Workstation.”

See Running the Database Configuration Wizard.

You may see some of the following errors when running this Application Engine program:

- Not authorized CRef: <Portal Object Name> (95,5032).

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

- Security synchronization failed for Portal Object: <Portal Object Name> (96,61).

This is not a fatal error. It may be caused by a content reference that contains invalid URL text and indicates that there was an internal error writing to the security table. The invalid URL text may be pointing to a component or script that does not exist in the database. If you receive this error, please check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database.

- Cref <Portal Object Name> points to Menu: <Menu Name>, Component <Component Name> which doesn't exist. (96,80).

The content reference is pointing to an invalid Menu/Component combination. If you receive this error, please check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

## Convert Query Headings

Crystal 9 when run through Process Scheduler will not handle queries with two or more prompts that have the same heading. These duplicates are also not legal in Query. Any old queries that have this condition need to be altered to work with Crystal. This Application Engine program searches for duplicate prompt headings in the table PSQRYBIND and appends numbers onto the text. For example "Item ID" would become "Item ID 2".

Run the UPGQRYDUPHED Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R⇒
INSTALL -AI UPGQRYDUPHED
```

---

**Note.** If a duplicate heading is found that will exceed the length of the field HEADING, the heading will need to be manually changed. The following error will be written to the log file in these cases :

The prompt heading <HEADING> for Query <QUERY> is duplicated.  
Please manually correct. (108, 1108)

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Query*.

## Convert Setup Manager

The application engine program UPGPTSMDAT upgrades Setup Manager Version 1 (shipped with Fin SCM 8.8, CRM 8.9, and with HCM 8.9) to Setup Manager Version 2 (shipped with PeopleTools 8.46 and above). The program moves all data from Setup Manager Version 1 tables to Version 2 tables.

The application engine program was designed so that it can be run in any database, and can be rerun in the same database. In either case, it will determine if there is data to convert and run as appropriate. For detailed information, see comments attached to the Steps and Actions in this Application Engine Program within Application Designer. This program must be run by a PeopleSoft User with PeopleSoft Administrator role.

Run the UPGPTSMDAT Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
INSTALL -AI UPGPTSMDAT
```

## Convert Navigation Collection and Pagelet Wizard Data

The application engine program UPGPT846PP adds Navigation Collection and Pagelet Wizard data from the Common Components and Enterprise Portal storage tables into PeopleTools tables.

The application engine program performs the following conversions:

1. Moves data from Common Components tables to PeopleTools tables.
2. Moves data from Enterprise Portal tables to PeopleTools tables.
3. Updates the registry definitions to enable displaying Navigation pages.
4. Adds, updates, and deletes the Navigation Collections folders and content references in the portal registry to the new structures.
5. Converts Pagelet Wizard definitions to the PeopleTools Pagelet Wizard version.
6. Renames Navigation Collection and Pagelet Wizard portal registry attributes to the PeopleTools attribute names.

This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role.

Run the UPGPT846PP Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -=>
R INSTALL -AI UPGPT846PP
```

You may see the following error when running this Application Engine program:

```
You are not authorized for the <objecttype>...
```

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

You can ignore any other errors encountered on PeopleSoft delivered objects at this time. Check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database. You can safely rerun UPGPT846PP to check for any remaining errors after applying patches.

## Convert Additional Pagelet Wizard Data

The application engine program UPGPT848PP adds the following Pagelet Wizard data sources from Enterprise Portal to PeopleTools: IB Connector, Integration Broker, SOAP, and URL. In addition, the application program transforms the WSRP Portlets created in PeopleTools 8.46 or 8.47 versions of Pagelet Wizard. The process includes the following:

- Move data from Enterprise Portal tables to PeopleTools tables.
- Convert WSRP Portlets created by Pagelet Wizard to the new version.

This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role.

Run the UPGPT848PP Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>  
INSTALL -AI UPGPT848PP
```

You may see the following error when running this Application Engine program:

```
You are not authorized for the <objecttype>...
```

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

You can ignore any other errors encountered on PeopleSoft delivered objects at this time. Check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database. You can safely rerun UPGPT848PP to check for any remaining errors after applying patches.

## Task 7A-4-10: Converting Integration Broker

This section discusses:

- Updating Integration Broker Defaults
- Creating Integration Broker Objects
- Saving Application Messaging Objects
- Exporting Node Transactions
- Deleting Application Messaging Objects
- Deleting Node Transactions

If your database is delivered with PeopleTools 8.48 or higher, do *not* run this task since the database is already delivered with the new Integration Broker objects as of PeopleTools 8.48. Instead, proceed to Changing the User Interface.

### Updating Integration Broker Defaults

User-level node security and transactional security have been added as of PeopleTools 8.48. Service namespace information, a low-level user on the node, and a low-level permission list for service operations, need to be specified. Edit <PS\_HOME>\scripts\ptibupgrade.dms and make the necessary modifications as documented in the script. Consult with your Integration Broker specialist for assistance.

Open Data Mover using a valid PeopleSoft Operator ID and run this script.

### Creating Integration Broker Objects

The application engine program UPGPT848IBUG converts Application Package metadata into Integration Broker metadata. It also creates the projects PTUPGIBCLONE and PTUPGIBDELETE, and the script ptupg\_trx.dms.

---

**Note.** Conversion errors in the Application Engine log file will be resolved by applying application-specific Required for Install patches.

---

Run the UPGPT848IBUG Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>  
INSTALL -AI UPGPT848IBUG
```

## Saving Application Messaging Objects

The PTUPGIBCLONE project was created by the UPGPT848IBUG Application Engine program and contains objects that were successfully converted. Copy this project to a directory of your choice where it will not be overwritten. The objects are copied to file as a precautionary measure since you will delete them from the database in a subsequent step.

To save Application Messaging Objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. From the Application Designer, select File, Open.
3. Select Project, enter *PTUPGIBCLONE* in the name dialog box, and click OK.
4. Select Tools, Copy Project, To File.
5. In the resulting dialog box, change the export directory to one of your choice, and click Copy.

When the progress dialog box disappears, the project has been copied to the specified location.

## Exporting Node Transactions

Open Data Mover using a valid PeopleSoft Operator ID and run the script <PS\_HOME>\scripts\ptupg\_trx\_export.dms to save the old pre-conversion node transaction data.

## Deleting Application Messaging Objects

Delete the obsolete pre-conversion object definitions from the database by first copying the PTUPGIBDELETE project to file, and then copying the same project from file. This project was created by the UPGPT848IBUG Application Engine program and contains the same objects as PTUPGIBCLONE.

To delete Application Messaging Objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. From the Application Designer, select File, Open.
3. Select Project, enter *PTUPGIBDELETE* in the name dialog box, and click OK.
4. Select Tools, Copy Project, To File.
5. In the resulting dialog box, change the export directory to the same one you used for PTUPGIBCLONE, and click Copy.

When the progress dialog box disappears, the project has been copied to the specified location.

6. Select Tools, Copy Project, From File.
7. In the resulting dialog box, change the import directory to the previously specified directory, select PTUPGIBDELETE from the list of projects, and click Select.

---

**Note.** Because the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.

---

8. Select all object types and click the Copy button.

When the progress dialog box disappears, the project has been copied. The actions in the project are set to Delete, so this will delete the obsolete pre-conversion object definitions from the database.

## Deleting Node Transactions

The script ptupg\_trx.dms is generated by the UPGPT848IBUG Application Engine program. This script can be found in the location specified in the OUTPUT variable set in Configuration Manager.

To view the OUTPUT variable:

1. Open Configuration Manager.
2. Select the Profile tab.
3. Click Edit to open the Default profile.
4. Select the Process Scheduler tab.
5. Examine the Output Directory value.

Open Data Mover using a valid PeopleSoft Operator ID and run this script to remove obsolete node transaction data associated with the obsolete objects in the PTUPGIBDELETE project.

## Task 7A-4-11: Changing the User Interface

PeopleTools has updated the styles that define the user interface. This PeopleTools release delivers the classic (old) style as well as two new styles: a dark blue style and a light blue style. PeopleTools System Databases and PeopleSoft 8.4 applications use the classic style, but all other applications use the new dark blue style. The classic style is set as the default. To use one of the new user interfaces, you have to delete the substyle sheets associated with the classic style and replace them with either the light or dark blue substyle sheet.

---

**Note.** The new user interface is supported by Internet Explorer release 5 and above and Netscape Navigator release 6 and above. If you are using a browser and release other than these, the system defaults to the classic style.

---

To enable a new user interface:

1. In Application Designer, select File, Open.
2. On the Open Definition dialog box, select *Style Sheet* from the Definition drop-down list.
3. Enter the name *PSSTYLEDEF* in the Selection Criteria Name field, and select Open.
4. Highlight *PSSTYLEDEF* in the list, and select Open.
5. Click the *PSALTERNATE* Sub Style Sheet and press DELETE.
6. Select Insert, Insert Sub Style Sheet.
7. Select *PSALTERNATE\_LIGHTBLUE* or *PSALTERNATE\_DARKBLUE*.
8. Repeat steps 5 through 7 for the *PTSTYLEDEF* Sub Style Sheet, making sure to use the same extension (*\_LIGHTBLUE* or *\_DARKBLUE*) you used for *PSALTERNATE*.
9. Select File, Save.
10. Open the style sheet *PSQUERYSTYLEDEF* as in steps 1 through 4.
11. Click the *PTQUERYSTYLESUB* Sub Style Sheet and press DELETE.
12. Select Insert, Insert Sub Style Sheet.
13. Select *PTQUERYSTYLESUB\_LIGHTBLUE* or *PTQUERYSTYLESUB\_DARKBLUE*.



- Use the same extension that you used in step 8.
14. Select File, Save.

---

## Task 7A-5: Running Additional Data Mover Scripts

To import additional data for your specific PeopleSoft database, or to make other required changes, you may need to run additional Data Mover scripts. These script files have the extension .dms and are sometimes referred to as “DMS scripts.” They are located in the <PS\_HOME>\scripts directory of your file server, and need to be run from the file server by means of Data Mover.

For the details on which additional application-specific Data Mover scripts to run, consult your application-specific installation instructions.

If you have installed a language other than English, you may need additional instructions on language-specific Data Mover scripts.

See Installing a Multilingual PeopleTools System Database.

---

## Task 7A-6: Installing a Multilingual PeopleTools System Database

This section discusses:

- Understanding the Multilingual Database Project
- Applying the Multilingual Database Project
- Populating the Translated System Data

### Understanding the Multilingual Database Project

The information in this section applies if you are installing a multilingual PeopleTools System database. If not, skip this task and go on to the task “Running VERSION Application Engine Program.” If you are installing an application database (for example, HRMS, FSCM, EPM, and so on), you do not need to run this task.

If you are adding a new (PeopleSoft-delivered) language to the PTSYS database, you must execute this step for that language. For example, if you want to add Polish to your current multilingual database, you should install Polish from PPLTLSML so you will get all objects. If you only “upgrade” your database to have Polish using PPLTLS84CURML, you will only get the objects that changed between 8.40 and the current release.

If you are installing a PeopleTools System database and you want it to be multilingual, you need to perform the steps in the following section after the database has been loaded with Data Mover.

See Applying the Multilingual Database Project.

---

**Note.** When you log onto the multilingual database, be sure to select the base language of the database.

---

## Task 7A-6-1: Applying the Multilingual Database Project

This procedure describes how to apply the multilingual database project that contains translations of the PeopleTools objects.

To apply the multilingual database project:

1. Launch Application Designer.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects.
4. Select *PPLTSLML* from the list of projects and click the Open button.
5. In the Upgrade Copy dialog box, make sure that all object types are selected.
6. Click the Options button, select the Copy Options tab, and ensure that only the non-English languages you have installed are selected.

Please note that English and Common should *not be selected*.

7. Select the languages that you are currently installing from the Copy Options dialog box.
8. Click the Copy button.

(The Reset Done Flags check box will be selected; accept this default.)

## Task 7A-6-2: Populating the Translated System Data

To populate the translated system data:

---

**Note.** You need to run the following script in User mode.

---

1. Launch Data Mover.
2. Open the pt848tlsx.dms script using File, Open.
3. Select File, Run

---

**Note.** The portion of the script name xxx is equivalent to the language code (that is, FRA, CFR, GER, JPN, and so on) of the languages you have installed. There will be a Data Mover script for each language.

---

## Task 7A-7: Running VERSION Application Engine Program

Run the VERSION Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <userid> -CP=>
<userpswd> -R INSTALL -AI VERSION
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <userid> respectively. However, be aware that <userpswd> is not the same as the connect password you entered on the Configuration Manager startup tab. Enter a value for <userpswd> that is the password you want to be associated with the <userid>.

See “Setting Up the Install Workstation.”

See Running the Database Configuration Wizard.

## Task 7A-8: Running SQR Reports

This section discusses:

- Running SQRs on the Client Workstation
- Creating a Shortcut to Run SQRs


**Note.** The following instructions describe how to run Structured Query Reports (SQRs) from the client workstation. On the Windows client, you may prefer to create a shortcut to allow you to run the reports repeatedly. You can use these instructions to run SQRs required in the upcoming task “Checking the Database.” You can also choose to run SQRs from the command line in console mode.

### Task 7A-8-1: Running SQRs on the Client Workstation

To run an SQR on the client workstation:

1. Select Start, Run, click Browse, and navigate to <PS\_HOME>\bin\sqr\ORA\binw.  
Select sqrw.exe and click Open.
2. Add any needed flags at the end of the command line.

Refer to the table that follows. For those flags that require attributes, append the attributes to the flags with no intervening spaces (for example, `-fd:\psbase\psenv\cr881dmo\`).



Running an SQR report on the client


The following table summarizes the SQR report arguments used by PeopleSoft. (For a full listing of report arguments, press the Help button to view the SQR help topic for this dialog box.)

Flag	Description
-I	Specifies the directories that SQR will search for the #INCLUDE files. (A trailing slash is required.)
-f	Specifies the directory where the report output will be sent.  If you use the <code>-keep</code> flag, specify a directory with an ending slash.  If you use the <code>-printer</code> flag, specify a full pathname with a filename for the HTML file.
-ZIF	Sets the full path and name of the SQR initialization file. The <code>-ZIF</code> flag should point to your <PS_HOME>\sqr\pssqr.ini file.

Flag	Description
-keep	Keeps the .SPF file after the program runs. This enables you to view the report with the SQR viewer.
-printer:ht	Generates the output file in HTML format. Specify the filename, with path location, with the -f flag.

- Click OK.

The resulting dialog box should look something like this:



SQR for PeopleSoft dialog box

- Enter the following values:
  - Enter the report name.  
You must specify the full path.
  - Enter the access ID in the Username field.
  - Enter the access password in the Password field.
  - Enter the database name.
- Click OK to run the SQR report.

---

**Note.** In the Properties dialog box for your SQR icon, make sure that the Start in path points to your Oracle connectivity on the Shortcut tab. If you take the default, you may see a misleading error message about TNS packet writer failure.

---

## Task 7A-8-2: Creating a Shortcut to Run SQRs

If you think you may need to run the SQR reports more than once, you may want to create a shortcut on the Windows client workstation. To save the report arguments:

- Open Windows Explorer on the machine on which you want to run SQR.
- Navigate to <PS\_HOME>\bin\sqr\ORA\binw.
- Right-click sqrw.exe and click Create Shortcut.
- Right-click the shortcut that you just created and select Properties.

5. On the Shortcut tab, add the same sqw flags that you used in the previous task after sqw.exe in the Target entry box.
6. Click OK.
7. To run the report, double-click the shortcut and specify the following information in the dialog box:
  - Report Name: Enter the full path and the name.
  - Database name
  - Username: Enter the access ID.
  - Password: Enter the access password.
  - Report arguments: Make any necessary modifications to the saved arguments.
8. Click OK.

---

## Task 7A-9: Checking the Database

Run and examine two SQW reports to verify that your database is complete.

See Preparing to Run SQW.

To verify that the database is complete, run the following SQW reports from the <PS\_HOME>\sqw directory:

- dddaudit.sqw
- sysaudit.sqw.

For further information about the dddaudit and sysaudit reports, consult PeopleBooks. This documentation includes specific information on how to interpret the reports and how to fix any errors found there.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*, “Ensuring Data Integrity.”

You can greatly improve the performance and run time of sysaudit.sqw run by making the following configuration changes to the Oracle init.ora for your SID:

```
db_file_multiblock_read_count = 16
db_block_buffers = 2000 or greater
log_checkpoint_interval = 9999999
log_buffer = 102400
```

If you are using rollback segments, you may also want to increase the size of the RBSBIG rollback segment to 500 MB.

Alter all other rollback segments but RBSBIG offline.

---

**Note.** If any records show up in the VIEWS-2 or TABLE-3 section of dddaudit and are contained within the PPLTLS84CURDEL project, you may safely drop these records using the SQL query tool for your platform.

---

### See Also

*Enterprise PeopleTools 8.48 PeopleBook: Data Management*


*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

## Task 7A-10: Running SETSPACE.SQR

Run the SETSPACE.SQR script to populate or synchronize Tablespace information with the system catalog. To run SETSPACE.SQR:

1. Using the instructions provided in the earlier task "Preparing to Run SQR," run SETSPACE.SQR from the <PS\_HOME>\SQR directory.

**Note.** Your results will vary depending on the application you are loading.



Running SETSPACE.SQR on the SQR for PeopleSoft dialog box

2. Click OK.
3. As SETSPACE.SQR runs you see a progress indicator similar to the following.

```
Set Table Space Name in PSRECTBLSPC
```

```
Table PSRECTBLSPC column DDLSPACEName have been updated
with the tablespace found in the system catalog table.
The total number of records updated appears at the bottom of this report.
```

```
Recname           New DDLSpaceName   Old DDLSpaceName
-----
```

```
This phase of SETSPACE will sync up the PSRECTBLSPC and
PSTBLSPCCAT tables
```

```
PSRECTBLSPC Records Updated:      0
```

```
PSTBLSPCCAT Records Inserted:    0
```

```
Ending SQR.
```

---

## Task 7A-11: Running Alter Audit

ALTER AUDIT is an online utility used to check whether the PeopleTools tables are synchronized with the underlying SQL data tables in your database. This process compares the data structures of your database tables with the PeopleTools tables to uncover inconsistencies. ALTER AUDIT then reports its findings. At this point of time in the install, we do not expect to see differences between the database structure and the tools tables.

---

**Note.** If your application database was delivered on the PeopleTools release you are installing (see chart at the beginning of the task “Updating PeopleTools System Tables”), this task is optional.

---

---


**Note.** Triggers are always dropped and re-created during the alter process and will always show up in the generated Alter Audit script. You can ignore the generated script for triggers.

---

To alter PeopleTools tables:

1. Launch PeopleTools and sign on to the installed database.
2. From the Application Designer select File, New.
3. Select Project and click OK.
4. Select Insert, Definitions into Project.
5. Select *Records* from the Definition Type drop-down list box.
6. Select *Table* from the Type drop-down list box.
7. Click Insert, and then click Select All.
8. Click Insert, and then click Close.
9. Select Build, Project.

The Build dialog box appears:




The Build dialog box

10. Select Create Tables and Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
11. Select Build script file in the Build Execute Options region.
12. Click Settings.

The Build Settings dialog box appears:






Build Settings dialog box: Scripts tab

13. Select the Scripts tab.
14. Select Write Alter comments to script.
15. Enter a unique output file name for each type.
16. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region.


Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.

Make sure that Alter by Table Rename is selected in the Alter Table Options region.



Build Settings dialog box: Alter tab

17. Select the Create tab, and ensure that the options Skip table if it already exists, Recreate view if it already exists, and Recreate index only if modified are selected.



Build Setting dialog box: Create tab

18. Click OK.

The Build dialog box reappears.

19. Click Build.

20. Click Close when the process is completed.

21. Edit the generated SQL script for the correct tablespace names and sizing parameters if you are not using delivered PeopleSoft tablespace names.

22. Run the generated SQL scripts in your platform-specific query tool to bring your database structure in sync with the PeopleTools tables.



## CHAPTER 7B

# Creating a Database on UNIX

This chapter discusses:

- Understanding the Database Configuration Wizard
- Fulfilling PeopleSoft Database Configuration Wizard Prerequisites
- Running the Database Configuration Wizard
- Checking the Log Files and Troubleshooting
- Updating Database to Latest PeopleTools Release
- Running Additional Data Mover Scripts
- Installing a Multilingual PeopleTools System Database
- Running VERSION Application Engine Program
- Running SQR Reports
- Checking the Database
- Running SETSPACE.SQR
- Running Alter Audit

---

## Understanding the Database Configuration Wizard

The Database Configuration Wizard is a tool designed to simplify your PeopleSoft database installation. When you run the Database Configuration Wizard, Data Mover is also running silently.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*.

---

**Important!** Do not forget that application-specific installation steps are provided in a separate document specific to the application. For instance, if you are performing PeopleSoft CRM installation, you need both this PeopleTools installation guide and you also need any additional instructions provided by CRM. PeopleSoft Customer Connection provides installation guides that are specific to your application.

---

See PeopleSoft Customer Connection (Site Index, installation guides and notes).

You can still use the manual process for creating a PeopleSoft database instead of using the Database Configuration Wizard. The manual process is mandatory for some configurations.

---

**Important!** The Database Configuration Wizard cannot be used for RedHat Linux 64 bit. To create a database on that platform, you must use the manual method of creating a database on UNIX, as documented in the appendix “Creating a Database Manually.”

---

---

**Important!** The Database Configuration Wizard cannot be used with Oracle 10g RAC. To create a database with this database platform, you must use the manual method of creating a database, as documented in the appendix “Creating a Database Manually on UNIX.”

---

See “Creating a Database Manually on UNIX.”

See “Setting Up the PeopleSoft Installation with Oracle 10g RAC.”

---

## Task 7B-1: Fulfilling PeopleSoft Database Configuration Wizard Prerequisites

This section discusses:

- Installing the PeopleSoft Database Server Components on the Database Server
- Installing the Oracle RDBMS Software
- Creating an INIT<SID>.ORA File
- Creating Target Directory Paths
- Setting Up Target Database Connectivity
- Update Connection Information on the Server
- Running the Shell Script psconfig.sh
- Setting the ORACLE\_SID Environment Variable

### Task 7B-1-1: Installing the PeopleSoft Database Server Components on the Database Server

To run the PeopleSoft Database Configuration Wizard, your setup *must* fulfill these requirements:

- You must have installed the PeopleTools software on your database server by running the PeopleSoft Installer.
- You must have chosen the Database Server option during the PeopleTools software installation.
- You must have installed the Database component of your application CD to your database server.
- You must have the PeopleTools Development Environment set up to create your database.
- You must have the BEA Tuxedo software installed before you run the Database Configuration Wizard.

The Database Configuration Wizard invokes the PeopleSoft Data Mover utility. Data Mover on the UNIX platform has a dependency on the BEA Tuxedo software.

- You must run the Database Configuration Wizard at the database server.

Be sure the UNIX login ID executing the Database Configuration Wizard has sufficient read and write permissions on this server. Ideally the UNIX login ID executing the Database Configuration Wizard is part of the same UNIX group that the Oracle owner is part of, usually the DBA group.

## See Also

“Using the PeopleSoft Installer”

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Using PeopleSoft Configuration Manager”

## Task 7B-1-2: Installing the Oracle RDBMS Software

The Oracle RDBMS software must be installed before you run the Database Configuration Wizard. The following discussion assumes that you are familiar with Oracle administration tasks. During the execution of the Wizard, references are made to an existing Oracle RDBMS installation:

\$ORACLE\_HOME and \$ORACLE\_HOME/bin

---

**Note.** Beginning with PeopleTools PT8.46, the PeopleSoft Database Configuration Wizard supports either Oracle 9i or Oracle 10g.

---

## Task 7B-1-3: Creating an INIT<SID>.ORA File

You must create an init.ora with the naming convention of init<SID>.ora in the ORACLE\_HOME/dbs directory of your Oracle installation.

Please add or modify the following init.ora parameters:

```
DB_NAME = <SID>

DB_FILES = specify max allowed per your OS, typically 1021

CONTROL_FILES = (/filesystem1/cntrl1<SID>,/filesystem2/cntrl2<SID>)

OPEN_CURSORS = 255 <This is a minimum value. You may choose to set this higher>

db_block_size = 8192
```

---

**Note.** For UNIX the default DB\_BLOCK\_SIZE in the int.ora file is operating system dependent. On most operating systems the default is 8192 or 8K. For PeopleSoft ANSI databases this is more than adequate. For PeopleSoft Unicode databases (for example, CHARACTER\_SET UTF8), a DB\_BLOCK\_SIZE value of 8K is required.

---

Beginning with PeopleTools PT8.46, PeopleTools supports Oracle 9i and 10g. The PeopleSoft scripts are delivered to work across all versions of the Oracle RDBMS that PeopleSoft will support for this release of PeopleTools.

Because Oracle 9i is now the minimum Oracle RDBMS version supported, the PeopleSoft database creation scripts are delivered to support Automatic Undo. That is, the scripts PeopleSoft delivers assume an init.ora with UNDO\_MANAGEMENT parm set to AUTO.

If you want to use Manual Undo (for example, rollback segments), then install the database manually as described in the appendix, “Creating a Database Manually.” Installing the database manually will allow you to modify the scripts as necessary to implement Manual Undo.

The Database Configuration Wizard will prompt you for a SID name. This init<SID>.ora will be referenced in the CREATEDB.SQL script, which is executed by the Database Configuration Wizard.

If you choose to use an Oracle Password file, you must create one using the ORAPWD utility, as illustrated in this example:

```
Set ORACLE_SID=FDMO
orapwd file=$ORACLE_HOME/dbs/pwdtemp2.ora password=manager entries=5
```

If you choose not to use an Oracle Password file, make one of the following changes to the init.ora file. This must be done *before* running the running the CREATEDB.SQL or CREATEDB10.SQL script.

- Comment out or remove this line:

```
#remote_login_passwordfile=EXCLUSIVE
```

- Set the parameter to *NONE*:

```
remote_login_passwordfile=NONE
```

---

**Note.** The init<SID>.ora will reference “target” directories to write control files, log files, and system files, as well as target locations for Oracle Logs, User Trace Files, and so on. These “target” directory paths must exist or the Database Configuration Wizard will fail. See the following section for details.

---

## See Also

“Required Operating System, RDBMS & Additional Component Patches Required for Installation,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise, your database platform)

## Task 7B-1-4: Creating Target Directory Paths

As mentioned, you must create the directory path structure for the target directories referenced in the scripts executed by the Database Configuration Wizard. The Database Configuration Wizard will not create directories on the fly; it expects the directories to exist.

The <SID> variable for which the Database Configuration Wizard prompts you is automatically prepended to the directory path structure referenced in the various database creation scripts executed by the Database Configuration Wizard.

---

**Note.** If you want to use something other than the delivered directory paths, you need to modify the CREATEDB.SQL, CREATEDB10.SQL, UTLSPACE.SQL, and xxDDL.SQL scripts in the scripts directory under <PS\_HOME>, replacing the delivered paths with paths appropriate for your site installation prior to running the Database Configuration Wizard.

---

You are also asked for several mount points. On UNIX you just specify the File System mount point. An example is *data1*. (Note that no preceding slash is required.)

Here are some examples of directory path structure references.

The delivered CREATEDB.SQL script makes the following directory path structure references:

---

**Note.** Portions of the script have been omitted for clarity.

---

```
startup nomount pfile=$ORACLE_HOME/dbs/init<SID>.ora
datafile
    '/u01/oradata/<SID>/system01.dbf'          size 400M
logfile
```



```

'/u01/oradata/<SID>/log01.dbf'          size 70M,
'/u01/oradata/<SID>/log02.dbf'          size 70M,
'/u01/oradata/<SID>/log03.dbf'          size 70M;

```

The init<SID>.ora parameter file that is referenced in the CREATEDB.SQL script makes the following directory path structure references:

---

**Note.** Portions of the init<SID>.ora parameter file have been omitted for clarity. These paths are hardcoded by the user creating the init<SID>.ora parameter file. The Data Configuration Wizard will not make any substitutions for mount point, target directory path, or <SID> in the init<SID>.ora file.

---

*Control file references:*

```

control_files = ('/u01/oradata/test920/control01.ctl', '/u01/oradata/test920⇒
/control02.ctl', '/u01/oradata/test920/control03.ctl')

```

*Trace and Alert Log file references:*

```

# define directories to store trace and alert files
background_dump_dest = /products/oracle/admin/test920/bdump
core_dump_dest = /products/oracle/admin/test920/cdump
user_dump_dest = /products/oracle/admin/test920/udump

```

The delivered UTLSPACE.SQL script makes the following directory path structure references:

---

**Note.** Portions of the script have been omitted for clarity.

---

```

CREATE TABLESPACE PSRBS
DATAFILE '/u02/oradata/<SID>/psrbs01.dbf'      SIZE      300M
DEFAULT STORAGE (
    initial          4M
    next             4M
    pctincrease      0
);

CREATE TEMPORARY TABLESPACE      PSTEMP
TEMPFILE          'u03/oradata/<SID>/pstemp01.dbf'      SIZE 300M
EXTENT MANAGEMENT LOCAL UNIFORM SIZE 128K;

CREATE TABLESPACE      PSDEFAULT
DATAFILE          'u03/oradata/<SID>/psdefault.dbf'      SIZE 10M

EXTENT MANAGEMENT LOCAL AUTOALLOCATE;
    INITIAL          100K
    NEXT             100K
    PCTINCREASE      0 );

```

The delivered XXDDL.SQL scripts make the following directory path structure references:

---

**Note.** This is a sample of the first several Create Tablespace SQL statements in the xxDDL.SQL script. The rest of the script has been omitted here for clarity.

---

```

CREATE TABLESPACE PSIMAGE DATAFILE '/u01/oradata/<SID>/psimage.dbf' SIZE 8M

```

```

EXTENT MANAGEMENT LOCAL AUTOALLOCATE
/
CREATE TABLESPACE PSINDEX DATAFILE '/u01/oradata/<SID>/psindex.dbf' SIZE 64M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
/
CREATE TABLESPACE PTAPP DATAFILE '/u01/oradata/<SID>/ptapp.dbf' SIZE 4M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
/

```

## Task 7B-1-5: Setting Up Target Database Connectivity

You must add a TNS entry to \$ORACLE\_HOME/network/admin/tnsnames.ora, because during the Data Mover Load phase, the Database Configuration Wizard will try to connect to the newly created SID by means of a remote connection string—for example:

```
ACCESSID/ACCESSPWD@TNS_ALIAS
```

Update the connection information in TNSNAMES.ORA on your server to reflect your Database Name, Oracle SID, and Server Name.

---

**Note.** Make sure that you stop and start (or reload) the Oracle Net listener.

---

## Task 7B-1-6: Update Connection Information on the Server

Make sure that you add the new SID name or existing SID name to the \$ORACLE\_HOME/network/admin/LISTENER.ORA on the database server.

Stop and start (or reload) the Oracle Net listener.

## Task 7B-1-7: Running the Shell Script psconfig.sh

The shell script psconfig.sh sets up the environment for Data Mover to run. The PeopleSoft Data Mover utility is used to load the database.

To run psconfig.sh:

1. Change the directory to <PS\_HOME>.
2. Run psconfig.sh (. ./psconfig.sh)

---

**Note.** The PeopleSoft UNIX user ID executing the Database Configuration Wizard has to be part of the Oracle DBA group or the PeopleSoft UNIX user ID must grant the UNIX Oracle Administration ID write permission to the following directories: \$PS\_HOME/ (log, modifiedscripts, scripts ).

---

## Task 7B-1-8: Setting the ORACLE\_SID Environment Variable

For Oracle on Tru64, you must set the \$ORACLE\_SID environment variable to the SID you are going to use or create before you run Database Configuration Wizard.

---

## Task 7B-2: Running the Database Configuration Wizard

When you run the Database Configuration Wizard, Data Mover typically does the following:

1. **IMPORT \***  
Create all the PeopleTools and application tables with their indexes.
2. **ENCRYPT\_PASSWORD \***  
Encrypt security information for the database.
3. **CREATE\_TRIGGER \***  
Create application-required triggers.
4. **REPLACE\_VIEW \***  
Create PeopleSoft views.
5. **CREATE\_TEMP\_TABLE \***  
Create PeopleSoft temporary tables.

If Data Mover fails at any of the above steps, it will complete the rest of the steps but will not start the next step—instead the Wizard aborts and tells the user what file to review for the detailed error message. If Data Mover fails at step 1 or 2, it is fatal. If Data Mover fails at step 3 or 4, it is not necessarily fatal. You may continue the next step(s) manually.

---

**Note.** If you want to run Data Mover on the same machine as the application server or Process Scheduler, you need to start a new telnet session without running PSADMIN and make sure the PS\_SERVER\_CFG environment variable is not set. PS\_SERVER\_CFG is only set when you run PSADMIN, so if you have not run it before this should not be a concern. When running Data Mover, you do not need to run PSADMIN. Consult the PeopleBooks documentation for the details on using PS\_SERVER\_CFG to set up tracing in Data Mover.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*.

---

**Note.** During UNIX console mode installation, you can go back to the previous steps whenever you see the instruction: “Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1].” Choose 2 for Previous.

---



---

**Note.** Remember, for Oracle on Tru64, you must set the \$ORACLE\_SID environment variable to the SID you are going to use or create before you run the Database Configuration Wizard.

---

To run the Database Configuration Wizard:

1. Go to <PS\_HOME>/setup/databaseinstall.
2. Launch the installation using the following command:

```
setup.xxx -is:javaconsole -console
```

where xxx is the operating system platform. See the chapter “Using the PeopleSoft Installer” for additional flags, or for details about running in GUI mode.

---

**Note.** PeopleSoft delivers operating-system-specific native launchers designed to work with your specific operating system.

---

See “Using the PeopleSoft Installer,” Running the PeopleSoft Installer.

3. You see the following prompt:

```
Welcome to the PeopleSoft Database Configuration Wizard
This Wizard will assist you in configuring and loading a PeopleSoft database.
                To continue, click Next.
Press 1 for Next, 3 to Cancel or 4 to Redisplay [1]
```

4. Press ENTER to continue.
5. Specify the location of <PS\_HOME>—the high level directory where the PeopleSoft software is installed—and press ENTER.

```
Peoplesoft Database Configuration Install Location
Please specify a directory or press Enter to accept the default directory.
Directory Name: [/ds1/<platform name>/PT848]
```

```
Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]
```

6. Press ENTER to continue
7. Select whether you want to create a Unicode or non-Unicode database, and press ENTER.

```
For a database platform of Oracle, are you installing:
Database Create Type:
[ ] 1 - Unicode
[X] 2 - Non-Unicode
```

```
To select a choice enter its number, or 0 when you are finished [0]: 0
```

8. Select the desired character set and press ENTER.

This Character Set selection is substituted and used in the CREATEDB.SQL script.

```
Select Character Set:
[ ] 1 - Western European ISO 8859-1
[X] 2 - Western European ISO 8859-15 (with Euro sign)
[ ] 3 - Microsoft Windows Latin-1 CP1252
[ ] 4 - US 7-bit ASCII
[ ] 5 - Japanese Shift-JIS
```

```
To select a choice enter its number, or 0 when you are finished [0]: 0
```

9. The Database Configuration Wizard detects what database files are available for loading. Select the appropriate PeopleSoft database type to load and press ENTER to continue. You will only see the database types that are valid based on the PeopleSoft Application Modules that you have installed.

```
Database Create Type:
[ ] 1 - Demo
[X] 2 - System
[ ] 3 - PeopleTools System
```

To select a choice enter its number, or 0 when you are finished [0]: 0

Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]

---

**Note.** See the manual database creation appendix for further details about PeopleSoft database types.

---

10. Select the PeopleSoft application database you want to load, pressing ENTER when you are done. (The available selections will depend upon which application CDs you have installed.)

Select PeopleSoft Application:

[ ] 1 - PeopleSoft Fin/SCM Database Objects - US English

To select a choice enter its number, or 0 when you are finished [0]: 0

Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]

If you installed the Multilanguage CD, each application will be listed several times, once for each language. If you are installing languages other than English, make sure to select the appropriate language data files for each application you select in English. This will load the translated database objects.

See “Preparing for Installation,” Planning Multilingual Strategy.

If you are installing an application in any language other than English, you must also select the English component of the application. For example, for HRMS if you select HR-French, you must also select HR-English. This ensures that you install the necessary base-language components.

11. When prompted for the location of \$ORACLE\_HOME/bin and \$ORACLE\_HOME, modify the locations as necessary.

Specify the directory path for 'sqlplus'

Please specify a directory name or press Enter

[/products/oracle/9.2.0-64bit/bin] /products/oracle/9.2.0-64bit/bin

Specify the location for ORACLE\_HOME

Please specify a directory name or press Enter

[/products/oracle/9.2.0-64bit] /products/oracle/9.2.0-64bit

12. You see the following informational prompt:

Location of modified scripts:

/dsl/certora/PT848/modifiedscripts

Please press Enter to Continue

13. At this point, indicate your Oracle version. In addition, choose to either create an Oracle SID and load a PeopleSoft database, or use an existing Oracle SID to load the PeopleSoft database. For a new installation you must create a new Oracle SID.

Please select the Oracle version that you are building this database on?

[X] 1 - Oracle 9i

[ ] 2 - Oracle 10g

To select a choice enter its number, or 0 when you are finished [0]: 1

Please press Enter to Continue

Do you want to create a new SID or use the existing one?

[ ] 1 - Use existing SID

[X] 2 - Create new SID

To select a choice enter its number, or 0 when you are finished [0]: 1

Please press Enter to Continue

The PeopleSoft Database Configuration Wizard now supports both Oracle 9i and Oracle 10g. Select the appropriate Oracle version. Then either create an Oracle SID and load a PeopleSoft database or use an existing Oracle SID to load the PeopleSoft database. These instructions assume you use an existing SID.

14. The following dialog requests Oracle server and SID information. Whichever option you chose in the previous step, the following prompts will remain the same. The Database Configuration Wizard will use just the information it needs to complete the tasks necessary based on whether you chose to create a new SID or use an existing one.

---

**Note.** You must use all uppercase text for the Oracle SID and the database name.

---

Please enter oracle server information

Oracle SID [PTSYS] TEST920

Database Name [PTSYS] PT848

Mount Point 1( for SYSTEM and REDO LOGS file in createdb.sql, ex: NT 'C', UNIX⇒  
'u01') [c] ds1

Mount Point 2 ( for PSRBS file in utlspace.sql, ex: NT 'C' , UNIX 'u01') [c]⇒  
ds2

Mount Point 3 ( for PSTEMP file in utlspace.sql, ex: NT 'C' , UNIX 'u01') [c]⇒  
ds1

Mount Point 4 ( for all files in xdd1.sql, ex: NT 'C' , UNIX 'u01') [c] ds2

---

**Note.** No preceding slash is required for the mount points.

---

Enable AutoExtend for Peoplesoft Tablespaces?

[X] 1 - Yes

[ ] 2 - No

To select a choice enter its number, or 0 when you are finished [0]: 0

Please press Enter to Continue

15. Next you are asked for additional Oracle server information.

Please enter oracle server information

Peoplesoft owner ID (ex: 'sysadm')

[sysadm] PT848

Peoplesoft owner password (ex: 'sysadm')

(Type in your password here.)

[] PT848

---

**Note.** Whatever you type as your password will not be displayed. This is true for the connect ID password and the internal password.

---

---

**Note.** You must limit the owner ID (access ID) and connect ID to eight characters or less.

---

Peoplesoft connect ID

[people]

Peoplesoft connect password

(Type in your password here.)

[]

Peoplesoft default tablespace (ex: 'PSTEMP')

[PSTEMP]

---

**Note.** The PSADMIN.SQL script is run by the Database Configuration Wizard for every PeopleSoft database that you are going to create. When prompted for a default tablespace name, select PSDEFAULT if you are using PeopleSoft naming conventions, or your site equivalent if you are not using PeopleSoft naming conventions.

---

Oracle Internal password

(Type in your password here.)

[password] password

---

**Note.** For the UNIX platform, an Oracle internal password is not necessary.

---

init.ora file complete path

Please specify a directory name or press Enter

```
[/ds29/products2/oracle/9.2.0/dbs/inittest920.ora] /products/oracle/9.2.0->
64bit/dbs/inittest920.ora
```

Please press Enter to Continue

---

**Note.** The path in the preceding prompt for init<SID>.ora must match the path of the init<SID>.ora file you created under the task "Fulfilling PeopleSoft Database Configuration Wizard Prerequisites" earlier in this chapter.

---

16. Select the base language (the default is US English) and press ENTER.

```
Select Base Language:
[X] 1 - ENG - US English
```

To select a choice enter its number, or 0 when you are finished [0]: 0

Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]

The Select base language selection is used to determine what primary base language the customer wants to run their PeopleSoft application on. If you choose a language other than English, the base language will be swapped during the database creation script.

See "Planning for Installation," Planning Multilingual Strategy.

This step applies only if your users will be operating PeopleSoft applications primarily in one particular language other than English. This step gives a performance boost to the language you designate as the base language, but would require more administrative overhead than leaving English as the base language does.

See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*.

17. You see a confirmation dialog indicating the selected database configuration.

Peoplesoft Database Configuration will be installed in the following location:

```
/dsl/certora/pt848
```

```
PeopleToolsOraUnixFeature
Database Platform:
```

```
Oracle - Non-Unicode
```

```
Oracle SID: test920
```

```
Application:
```

```
PeopleTools System Database - US English
```

```
Database Name:
```

```
PT848
```



Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]

18. Press ENTER. You see a number of messages indicating the progress of the processes being run.

```
Installing Peoplesoft Database Configuration... Please wait.
The ORACLE_SID Environment Variable has been updated to "test920"
Up to this point the message(s) indicating progress will be identical.
Beyond this point they will differ based on which option you chose above,=>
  Create a New Sid or Use an Existing SID.
```

---

**Note.** It is always a good idea to let the installation run through even if you encounter a problem. If for any reason you manually abort the installation, you will need to delete the file vpd.properties in order for the Database Configuration Wizard to successfully update SID when you run the Wizard again. The file vpd.properties is located under your home directory.

---

19. If you chose to use an existing SID, you see Database Configuration Wizard messages like this:

---

**Note.** The messages are displayed on the console to indicate real time progress of the Database Configuration Wizard. All messages are also written to log files contained in the <PS\_HOME>/log directory.

---

You see a message for every SQL script the Wizard executes, regardless of which option you have chosen.

---

```
Installing Peoplesoft Database Configuration... Please wait.
The ORACLE_SID Environment Variable has been updated to 'test920'

Executing psadmin.sql for oracle(UNIX)...

Executing connect.sql for oracle(UNIX).....
```

---

**Note.** At this step, DBSetup is invoked via Data Mover to generate the input Data Mover script. This script can be found in the <PS\_HOME>/SCRIPTS directory.

---

```
Initializing Data Mover ... please wait

PeopleTools 8.48 - Data Mover
Copyright (c) 2003 PeopleSoft, Inc.
All Rights Reserved
Started: Thu Jan 3 19:39:02 2003
Data Mover Release: 8.48
Database: PT848
Creating Database setup script /PT848/scripts/PT848.dms
Ended: Thu Jan 3 19:39:02 2003
Successful completion
Initializing Data Mover ... please wait
```

---

**Note.** At this step, Data Mover is invoked to execute the input Data Mover script.

If Data Mover attempts to run and fails, you can edit and rerun the script and restart Data Mover. This procedure is covered in the next section. If the process fails before Data Mover begins, run the script DBSetup.dms.

---

See Checking the Log Files and Troubleshooting.

```

PeopleTools 8.48 - Data Mover
Copyright (c) 2003 PeopleSoft, Inc.
All Rights Reserved
Started: Thu Jan 3 19:39:40 2003
Data Mover Release: 8.48
Database: PT848
Importing ACCESS_GRP_LANG
Creating Table ACCESS_GRP_LANG
Import ACCESS_GRP_LANG 0
Building required indexes for ACCESS_GRP_LANG
Updating statistics for ACCESS_GRP_LANG
Records remaining: 1098
Importing ACCESS_GRP_TBL
Creating Table ACCESS_GRP_TBL
Import ACCESS_GRP_TBL 47
Building required indexes for ACCESS_GRP_TBL
Updating statistics for ACCESS_GRP_TBL
Records remaining: 1097

```

---

**Note.** A portion of the messages generated at this step have been omitted for clarity.

---

```

Importing XMLSERVICEINFO
Creating Table XMLSERVICEINFO
Import XMLSERVICEINFO 0
Building required indexes for XMLSERVICEINFO
Updating statistics for XMLSERVICEINFO
Records remaining: 1
Importing PSSTATUS
Creating Table PSSTATUS
Import PSSTATUS 1
Building required indexes for PSSTATUS
Updating statistics for PSSTATUS
SQL Spaces: 0 Tables: 1099 Triggers: 0 Indexes: 1399 Views: 0
SQL Successful - INSERT INTO PS.PSDBOWNER VALUES('PT848', 'PT848')
SQL Successful - UPDATE PSSTATUS SET OWNERID = 'PT848'
SQL Successful - UPDATE PSOPRDEFN SET SYMBOLICID = 'test920', OPERPSWD =>
OPRID, ENCRYPTED = 0
SQL Successful - UPDATE PSACCESSPRFL SET ACCESSID = 'PT848', SYMBOLICID =>
'test920', ACCESSPSWD = 'PT848', VERSION = 0, ENCRYPTED = 0
SQL Successful - UPDATE PSOPTIONS SET LICENSE_CODE = 'fffffffffffffffff2', LICENSE_GROUP = '06'

```

```

SQL Successful - GRANT    SELECT ON PSSTATUS TO people
SQL Successful - GRANT    SELECT ON PSOPRDEFN TO people
SQL Successful - GRANT    SELECT ON PSACCESSPRFL TO people
SQL Successful - CREATE  VIEW SYSKEYS (IXCREATOR, IXNAME, COLNAME, COLNO,⇒
COLSEQ, ORDERING, FUNCTION) AS SELECT A.OWNERID, B.INDEX_
NAME, B.COLUMN_NAME, B.COLUMN_POSITION, B.COLUMN_POSITION, 'a', ' ' FROM P⇒
SSTATUS A, USER_IND_COLUMNS B
SQL Successful - CREATE  VIEW SYSINDEXES (TBCREATOR, NAME, TBNAME, CREATO R,⇒
UNIQUERULE, COLCOUNT, IXTYPE, CLUSTERRULE, IXSIZE, PERC
ENTFREE) AS SELECT TABLE_OWNER, INDEX_NAME, TABLE_NAME, TABLE_OWNER, SUBST R⇒
(UNIQUENESS,1,1), 1, 'b', 'n', 1, PCT_FREE FROM USER_INDEXES
Ended:  Thu Jan  3 20:00:32 2003
Successful completion

```

---

**Note.** At this step, the Data Mover import is complete and additional Data Mover commands and scripts are being executed. The first of these commands is ENCRYPT PASSWORD\*.

---

```

Started:  Thu Jan  3 20:00:32 2003
Data Mover Release: 8.48
Database: PT848
Password encrypted for APPENV
Password encrypted for PSADMIN
Password encrypted for PT8
Password encrypted for PTADMIN
Password encrypted for PTAE
Password encrypted for PTAPPMMSG
Password encrypted for PTDMO
Password encrypted for PTEMPL
Password encrypted for PTEND
Password encrypted for PTGBL
Password encrypted for PTHVAP
Password encrypted for PTIDE
Password encrypted for PTOLAP
Password encrypted for PTOPT
Password encrypted for PTPORTAL
Password encrypted for PTPRD
Password encrypted for PTQETST
Password encrypted for PTRPT
Password encrypted for PTSECADM
Password encrypted for PTSVR
Password encrypted for PTTOOLS
Password encrypted for PTUPG
Password encrypted for PTWEB
Access Profiles successfully encrypted.
Ended:  Thu Jan  3 20:00:35 2003
Successful completion

```

---

**Note.** At this step, Data Mover is executing the CREATE\_TRIGGER \* command.

---

```
Started: Thu Jan 3 20:00:35 2003
Data Mover Release: 8.48
Database: PT848
Creating Trigger for CURRENCY_CD_TBL
Records remaining: 2
Creating Trigger for PSMPTREF
Records remaining: 1
Creating Trigger for PSWORKLIST
SQL Triggers: 3
Ended: Thu Jan 3 20:00:41 2003
Successful completion
```

---

**Note.** At this step, Data Mover is executing the REPLACE\_VIEW command.

---

```
Started: Thu Jan 3 20:00:41 2003
Data Mover Release: 8.48
Database: PT848
View PRCSOUTTYPE_VW
Views remaining: 666
View PRCSSRVROPSLANG
Views remaining: 665
View PRCSSRVROPSYS
Views remaining: 664
```

---

**Note.** A portion of the messages generated at this step have been omitted for clarity.

---

```
View PSTREEFLDDTLVW
Views remaining: 3
View PSTREEFLDNODVW
Views remaining: 2
View PSTREESTRCTDFVW
Views remaining: 1
View PSTREESTRCTNFVW
SQL Views: 667
Ended: Thu Jan 3 20:02:52 2003
Successful completion
```

---

**Note.** At this step, Data Mover is executing the CREATE\_TEMP\_TABLE \* command.

---

```
Started: Thu Jan 3 20:02:52 2003
Data Mover Release: 8.48
Database: PT848
Creating Table MENU_LANG_TMP
```

```

Building required indexes for MENU_LANG_TMP
SQL Tables: 1   Indexes: 1
Ended: Thu Jan  3 20:02:57 2003
Successful completion

```

---

**Note.** At this step, Data Mover is complete and the Database Configuration Wizard is checking the log file for errors.

---

```

Checking Data Mover log ... please wait

```

```

Checking ... /ds1/home/certora/PT848/log/ptengs.log           OK
Checking ... /ds1/home/certora/PT848/log/encrypt.log         OK
Checking ... /ds1/home/certora/PT848/log/triggers.log        OK
Checking ... /ds1/home/certora/PT848/log/views.log           OK
Checking ... /ds1/home/certora/PT848/log/temptbls.log        OK

```

---

**Note.** If the Wizard executed successfully, you see the message below.

---

```

The InstallShield Wizard has successfully installed Peoplesoft Database
Configuration. Click Finish to exit the wizard.

```

```

Press 3 to Finish or 4 to Redisplay [3]

```

---

**Note.** If the Wizard detected an error, you get a message similar to the one below, depending on the error encountered:

---

```

Checking Data Mover log ... please wait

```

```

Checking ... ptengs.log

```

```

Error Information

```

```

The installation failed to load PeopleSoft data with the following error: Error
in ptengs.log Please look into the log file(s) located under log directory for
details.

```

```

Click next to exit the installation.

```

```

Please press Enter to Exit

```

20. If you chose to create a new SID, you see Database Configuration Wizard messages like this:

```

Installing Peoplesoft Database Configuration... Please wait.
The ORACLE_SID Environment Variable has been updated to 'test920'

```

---

**Note.** You see a message for every SQL script the Wizard executes, regardless of which option you have chosen.

---

```

Executing createdb.sql for Oracle(UNIX).....
Executing utlspace.sql for Oracle(UNIX).....
Executing ptddl.sql for Oracle(UNIX).....
Executing dbowner.sql for Oracle(UNIX).....
Executing psroles.sql for Oracle(UNIX).....
Executing psadmin.sql for Oracle(UNIX).....
Executing connect.sql for Oracle(UNIX).....

```

---

**Note.** At this step, DBSetup is invoked via Data Mover to generate the input Data Mover script. This script can be found in the <PS\_HOME>/SCRIPTS directory.

---

```

Initializing Data Mover ... please wait

PeopleTools 8.48 - Data Mover
Copyright (c) 2003 PeopleSoft, Inc.
All Rights Reserved
Started:  Fri Jan  4 06:24:55 2003
Data Mover Release: 8.48
Database: PT848
Creating Database setup script /dsl/home/certora/PT848/scripts/PT848ora.dms
Ended:    Fri Jan  4 06:24:55 2003
Successful completion

```

---

**Note.** At this step, Data Mover is invoked to execute the input Data Mover script.

---

```

Initializing Data Mover ... please wait

Started:  Fri Jan  4 06:25:27 2003
Data Mover Release: 8.48
Database: PT848
Importing  ACCESS_GRP_LANG
Creating Table  ACCESS_GRP_LANG
Import  ACCESS_GRP_LANG  0
Building required indexes for ACCESS_GRP_LANG
Updating statistics for ACCESS_GRP_LANG
Records remaining: 1098
Importing  ACCESS_GRP_TBL

```

---

**Note.** A portion of the messages generated at this step have been omitted for clarity.

---

```

Records remaining: 2
Importing  XMLSERVICEINFO
Creating Table  XMLSERVICEINFO
Import  XMLSERVICEINFO  0

```

```

Building required indexes for XMLSERVICEINFO
Updating statistics for XMLSERVICEINFO
Records remaining: 1
Importing PSSTATUS
Creating Table PSSTATUS
Import PSSTATUS 1
Building required indexes for PSSTATUS
Updating statistics for PSSTATUS
SQL Spaces: 0 Tables: 1099 Triggers: 0 Indexes: 1399 Views: 0
SQL Successful - INSERT INTO PS.PSDBOWNER VALUES('PT848', 'PT848')
SQL Successful - UPDATE PSSTATUS SET OWNERID = 'PT848'
SQL Successful - UPDATE PSOPRDEFN SET SYMBOLICID = 'prod817', OPERPSWD = OPRI0
SQL Successful - UPDATE PSACCESSPRFL SET ACCESSID = 'PT848', SYMBOLICID = 0
SQL Successful - UPDATE PSOPTIONS SET LICENSE_CODE = 'ffffffffffffffffffff'
SQL Successful - GRANT SELECT ON PSSTATUS TO people
SQL Successful - GRANT SELECT ON PSOPRDEFN TO people
SQL Successful - GRANT SELECT ON PSACCESSPRFL TO people
SQL Successful - CREATE VIEW SYSKEYS (IXCREATOR, IXNAME, COLNAME, COLNO, COLSB
SQL Successful - CREATE VIEW SYSINDEXES (TBCREATOR, NAME, TBNAME, CREATOR, UNS
Ended: Fri Jan 4 06:38:10 2003
Successful completion

```

---

**Note.** At this step, The Data Mover import is complete and additional Data Mover commands and scripts are being executed. The first of these commands is ENCRYPT PASSWORD\*.

---

```

Started: Fri Jan 4 06:38:11 2003
Data Mover Release: 8.48
Database: PT848
Password encrypted for APPENV
Password encrypted for PSADMIN
Password encrypted for PT8
Password encrypted for PTADMIN
Password encrypted for PTAE
Password encrypted for PTAPPMMSG
Password encrypted for PTDMO
Password encrypted for PTEMPL
Password encrypted for PTEND
Password encrypted for PTGBL
Password encrypted for PTHVAP
Password encrypted for PTIDE
Password encrypted for PTOLAP
Password encrypted for PTOPT
Password encrypted for PTPORTAL
Password encrypted for PTPRD
Password encrypted for PTQETST
Password encrypted for PTRPT
Password encrypted for PTSECADM
Password encrypted for PTSVR
Password encrypted for PTTOOLS

```

```
Password encrypted for PTUPG
Password encrypted for PTWEB
Access Profiles successfully encrypted.
Ended:  Fri Jan  4 06:38:13 2003
Successful completion
```

---

**Note.** At this step, Data Mover is executing the CREATE\_TRIGGER \* command.

---

```
Started:  Fri Jan  4 06:38:13 2003
Data Mover Release: 8.48
Database: PT848
Creating Trigger for CURRENCY_CD_TBL
Records remaining: 2
Creating Trigger for PSMPTREF
Records remaining: 1
Creating Trigger for PSWORKLIST
SQL Triggers: 3
Ended:  Fri Jan  4 06:38:18 2003
Successful completion
```

---

**Note.** At this step, Data Mover is executing the REPLACE\_VIEWS \* command.

---

```
Started:  Fri Jan  4 06:38:18 2003
Data Mover Release: 8.48
Database: PT848
View  PRCSOUTTYPE_VW
Views remaining: 666
View  PRCSSRVROPSLANG
Views remaining: 665
View  PRCSSRVROPSYS
```

---

**Note.** A portion of the messages generated at this step have been omitted for clarity.

---

```
Views remaining: 3
View  PSTREEFLDNODVW
Views remaining: 2
View  PSTREESTRCTDFVW
Views remaining: 1
View  PSTREESTRCTNFVW
SQL Views: 667
Ended:  Fri Jan  4 06:40:19 2003
Successful completion
```

---

**Note.** At this step, Data Mover is executing the CREATE\_TEMP\_TABLE \* command.

---



```

Started:  Fri Jan  4 06:40:19 2003
Data Mover Release: 8.48
Database: PT848
Creating Table  MENU_LANG_TMP
Building required indexes for MENU_LANG_TMP

```

```

SQL Tables: 1  Indexes: 1
Ended:  Fri Jan  4 06:40:20 2003
Successful completion

```

---

**Note.** At this step, Data Mover is complete and the Wizard is checking the log file for errors.

---

Checking Data Mover log ... please wait

```

Checking ... /ds1/home/certora/PT848/log/ptengs.log      OK
Checking ... /ds1/home/certora/PT848/log/encrypt.log     OK
Checking ... /ds1/home/certora/PT848/log/triggers.log    OK
Checking ... /ds1/home/certora/PT848/log/views.log       OK
Checking ... /ds1/home/certora/PT848/log/temptbls.log    OK

```

21. If the Wizard executed successfully, you see the following message, and you can press ENTER to exit the Database Configuration Wizard.

```

The InstallShield Wizard has successfully installed Peoplesoft Database
Configuration. Click Finish to exit the wizard.
Press 3 to Finish or 4 to Redisplay [3]

```

22. If the Wizard detected an error, you get a message similar to the one below, depending on the error encountered:

```

Checking Data Mover log ... please wait
Checking ... /ds1/home/certora/pt848/log/ptengs.log      Error
Information
The installation failed to load PeopleSoft data with the following error: Error
in /ds1/home/certora/pt848/log/ptengs.log Please look into the log file(s)
located under log directory for details.
Execute a Unix tail command on the log will show you the last record you were⇒
processing when the error occurred.

```

Example:

```

pt-sun20:$ tail ptengs.log
Updating statistics for CURRCD_TBL_LANG
Records remaining: 982
Importing  CURRENCY_CD_TBL
Creating Table  CURRENCY_CD_TBL
SQL Error. Error Position: 230  Return: 1722 - ORA-01722: invalid number
INSERT INTO PS_CURRENCY_CD_TBL  (CURRENCY_CD, EFFDT, EFF_STATUS, DESCR, DESCRSH)
Error: SQL execute error for CURRENCY_CD_TBL

```

```
SQL Spaces: 0 Tables: 118 Triggers: 0 Indexes: 122 Views: 0
Ended: Mon Jan 28 15:59:43 2003
Unsuccessful completion
```

---

## Task 7B-3: Checking the Log Files and Troubleshooting

This section discusses:

- Checking the Log Files
- Troubleshooting
- Optimizing for Performance

### Task 7B-3-1: Checking the Log Files

After the Database Configuration Wizard finishes its execution, look for all log output in the <PS\_HOME>/log directory. Open all the log files. There is a log file for each of the steps that the Database Configuration Wizard carries out—importing, encrypting passwords, creating triggers, replacing views, and creating temp tables. *None should contain error messages.*

### Task 7B-3-2: Troubleshooting

If the Database Configuration Wizard did not complete successfully, please read this troubleshooting information. If your script has stopped midway (this can happen for a number of reasons) you need to edit the Data Mover script generated automatically by the Database Configuration Wizard and restart Data Mover manually. The Data Mover script files have the extension .dms and are sometimes referred to as “DMS scripts.”

The generated Data Mover import script is saved in the <PS\_HOME>/scripts directory. The script conforms to the following naming convention:

<dbname>ora.dms

To edit and restart the DMS script:

1. Determine the record that was being imported (that is, which IMPORT command was running) when the script stopped.  
(See the note below for additional information on determining where the script stopped.)

---

**Note.** When building a DMO database or a multilingual database, adding the 'SET START' statement can be tricky because the Data Mover script used to load the database will include more than one IMPORT statement. The key is to view the LOG files and determine which IMPORT section of the script Data Mover failed on. If the failure occurred during the first IMPORT, add the 'SET START' statement before the first 'IMPORT \*;' statement. If the failure occurred during a subsequent IMPORT, comment out all statements preceding the 'IMPORT \*;' statement where the failure occurred and add the 'SET START' statement before the 'IMPORT \*;' statement of the section in which the failure occurred. *This is very important.* If you see any 'unique index constraint' error messages in the 'building required indexes' section, your IMPORT script failed during a subsequent IMPORT but the 'SET START' statement was added to the first IMPORT. In this situation, you can run the Data Mover script in its originally generated form, with only one modification. In the first IMPORT section, change the statement 'IMPORT \*;' to 'REPLACE\_DATA \*;'. This will delete all the data in the tables, and re-import it. This process will take some time to run, and you will need to separately create each of the indexes that failed.

---

2. Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.

This starts Data Mover in *bootstrap mode*.

The input window should display the DMS import script for the database. The script has the format <dbname>ora.dms.

3. If necessary, select File, Open, and browse to the <PS\_HOME>/scripts directory to find the appropriate DMS script.
4. Add the following line before the offending IMPORT command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The 'SET START' will begin the Data Mover import at the specified record name.

---

**Note.** It is a good idea to change the name of the log file in the script before each attempt at running it. This ensures that you have a separate log file for each attempt, if you run the import more than once.

---

*Example:*

If the script stops and the table is partially inserted with a message similar to this one:

```
Importing PSPNLFIELD
Rows inserted into PSPNLFIELD
3000
```

First drop the partially inserted table (for example, record) by using the DROP TABLE command, and then restart Data Mover at the record that failed using the SET START command and continue the Data Mover import. With PeopleTools 8.4, this can be done in a single pass.

Add the following lines before the offending 'IMPORT \*;' command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
DROP TABLE <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The 'SET START' will begin the Data Mover import at the specified record name.

*Example of the original script:*

```

REM - PeopleTools System Database - US English
/
SET LOG ptengs.log;
SET INPUT ptengs.db;
SET COMMIT 30000;
SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE OFF;
IMPORT *;

```

*Example of script after modification, with changes in bold font:*

```

REM - PeopleTools System Database - US English
/
SET LOG ptengs2.log;
SET INPUT ptengs.db;
SET COMMIT 30000;
SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE OFF;
SET START PSPNLFIELD;
DROP TABLE PSPNLFIELD;
IMPORT *;

```

For the DROP Statement, for records with a non-leading PS rename, add PS\_ to the beginning of the rename; otherwise the table will not be found.

5. To restart the script, use the `psdmtx` command to execute Data Mover on the command line. First, change the directory.

```
cd $PS_HOME/bin
```

---

**Note.** You can run `psdmtx` by supplying arguments on the command line, or by passing the arguments from a text file. You will use a text file in this procedure.

---

6. Use the following command to view the help for `psdmtx`:

```

pt-sun20:$ psdmtx /help
Usage:  psdmtx  [-CT DB2|DB2ODBC|DB2UNIX|INFORMIX|MICROSFT|ORACLE|SYBASE]
              [-CS server name]
              [-CD database name]
              [-CO user id]
              [-CP user pswd]
              [-CI connect id]
              [-CW connect id pswd]
              [-I  process instance]
              [-FP filename]

or

```

```
psdmtx [parmfile]
```

To capture the output in a file, use a “pipe” symbol (>) followed by a filename. For example:

```
psdmtx [arguments] > filename.txt
```

Use the following information for the `psdmtx` arguments:

Command Argument	Description
-CT <DB type>	The type of database to connect to. The valid values are: ORACLE and APPSRV. (The APPSRV value allows you to start tools in 3-tier.)
-CD <DBNAME>	Your selected Database Name.
-CO <ACCESSID>	Use the <DBNAME> Access ID to run Data Mover in bootstrap mode.
-CP <ACCESSPWD>	The password for <DBNAME> Access ID.
-CI <CONN ID>	The ID used to connect to the database server.
-CW <CONN PSWD>	The password for the specified connection ID.
-FP <filename>	The filename for the Data Mover import script (DMS) to run.

7. To set up Data Mover to rerun the Data Mover import script in bootstrap mode, do the following:
  - a. Change directory to <PS\_HOME>/setup.
  - b. Copy parmfile to parm<DBNAME>. For example, *parmPT848*.
  - c. Edit parm<DBNAME>.

Use the information in the table above to edit the file for your configuration.

Use ORACLE for <DB type>.

For example:

*Before*

```
-CT <DB type> -CD <DBNAME> -CO <ACCESSID> -CP <ACCESSPWD> -CI <CONN ID> -CW=>
<CONN PSWD> -FP <filename>
```

*After*

```
-CT ORACLE -CD PT848 -CO PT848 -CP PT848 -CI people -CW people -FP $PS_HOME=>
/scripts/pt848ora.dbs
```

8. To launch Data Mover to rerun the Data Mover import script in bootstrap mode, do the following:
  - Change directory (cd) to <PS\_HOME>/bin
  - Run the psdmtx command with the edited parm<DBNAME> file.

```
pt-sun20:$ psdmtx ../setup/parmPT848
```

At this point you see Data Mover log messages tracking Data Mover progress.

## Task 7B-3-3: Optimizing for Performance

The following tips can help you save time when running the Data Mover scripts:

- Run Data Mover from the fastest workstation available.
- Run Data Mover on the database server.
- Run only a single instance of Data Mover, and do not have any other applications running during the import.
- In the PeopleSoft Configuration Manager, turn off all trace options.  
Tracing during a DMS load will add considerable time to the process.
- Copy the database file over to the workstation so that Data Mover can access it locally instead of over the network.
- Run Data Mover on the database server with the .db or .dat file located locally.

If you are comfortable changing the options available for an Oracle instance, you might consider “tuning” the instance used for the import. Some of these options are appropriate only during the import, so you may not want to keep them in effect after the import is complete.

For best performance during a Data Mover import, set these options as follows:

- Increase the number of database blocks.
- Increase the shared\_pool.
- Use an 8K Oracle block size.
- Use very large rollback segments.
- Increase the size of the redo log files when you create the database.
- Use asynchronous read and write.
- Use multiple db\_writers.

---

## Task 7B-4: Updating Database to Latest PeopleTools Release

This section discusses:

- Understanding Database Updates
- Cleaning Up Data
- Updating PeopleTools System Tables
- Updating PeopleTools Database Objects
- Updating PeopleTools Multilingual Objects
- Deleting Obsolete PeopleTools Database Objects
- Altering PeopleTools Tables
- Migrating Records to New Tablespaces
- Updating PeopleTools System Data
- Running PeopleTools Conversions

- Converting Integration Broker
- Changing the User Interface

## Understanding Database Updates

Your PeopleSoft application database may be on a PeopleTools release prior to the version that you are currently running. For you to be able to sign on to your database after running the Data Mover script to load your database, the PeopleTools versions for your database and your file server must match. The steps in this task ensure that your PeopleSoft database is in sync with the PeopleTools version that you are running.

---

**Note.** You will use Application Designer for several steps in this portion of the installation. Consult the Application Designer documentation if you have questions.

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Application Designer*

---

**Note.** If you are installing a PeopleTools System Database or if your database is delivered on PeopleTools 8.48, the delivered database already contains the updated PeopleTools objects. Skip this task and continue with the install at the task “Running Additional Data Mover Scripts.”

---

Here is a list of applications for which this task must be run because the version of the database that was shipped is different than the version of PeopleTools that you are running. If your application release is earlier than the release listed in the table, you must run this task:

Application Release	Application Database Version	Requires Update to 8.48?
CRM 8.9	8.45	Yes
CRM 9.0	8.48	No
ELS 8.8 SP1	8.43	Yes
ELS 9.0	8.47	Yes
EPM 8.9	8.46	Yes
EPM 9.0	8.48	No
Fin/SCM 8.9	8.46	Yes
Fin/SCM 9.0	8.48	No
HRMS 8.8 SP1	8.43	Yes
HRMS 8.9	8.45	Yes
Portal 8.8	8.42	Yes
Portal 8.9	8.46	Yes
RMS 8.9	8.45	Yes

Application Release	Application Database Version	Requires Update to 8.48?
RMS 8.95	8.46	Yes
SIM 8.9	8.45	Yes

If your application is not listed above, look for your application and PeopleTools release information on Customer Connection. Navigate to Site Index, product releases (roadmaps and schedules), Release Definitions, select your product line, and then select the product you are installing. If the Tools version is not 8.48, you must run this task. Otherwise, continue to the task “Running Additional Data Mover Scripts.”

## Task 7B-4-1: Cleaning Up Data

If your database is delivered on PeopleTools 8.48 or higher, do *not* run this step, and instead, proceed to Updating PeopleTools System Tables. If your database is delivered on PeopleTools 8.47 or earlier, perform this step to clean out obsolete message data.

---

**Warning!** Performing this task when updating from PeopleTools 8.48 or later will wipe out current valid data that is needed for your system to function properly.

---

Message functionality and structure changed as of PeopleTools 8.48 and the old data is obsolete. Edit <PS\_HOME>\scripts\ptupgibdel.sql to delete data from the tables that only exist in the old PeopleTools release. Open the script and make the following modifications, and then run the modified script using your SQL query tool:

1. Search for the string “--- End of PT8.<xx> ---” where <xx> represents the last two digits of the PeopleTools release you are upgrading from.
2. Delete the entire portion of the script below this string.
3. Save the script as <PS\_HOME>\scripts\ptupgibdel8<xx>.sql where <xx> represents the last two digits of the PeopleTools release you are upgrading from, as determined in Step 1.

---

**Note.** Save the script using the naming convention shown above! This will preserve the original script for use in updating other databases at different PeopleTools releases.

---

4. Using a SQL query tool, run the ptupgibdel8<xx>.sql script against your PeopleSoft database.

## Task 7B-4-2: Updating PeopleTools System Tables

Run SQL scripts to update your PeopleTools system tables to the latest PeopleTools release (currently 8.48).

Use a query tool, such as Query SQL\*Plus, to run SQL scripts while in the PeopleSoft database.

1. Run the appropriate SQL scripts for your application version.  
The following scripts are found in the <PS\_HOME>\scripts directory.  
Use the scripts in the following table for non-Unicode databases:



Application Database Version	Required Scripts for Non-Unicode Databases
8.40	rel841, rel842, rel843, rel844, rel845, rel846, rel847, and rel848
8.41	rel842, rel843, rel844, rel845, rel846, rel847, and rel848
8.42	rel843, rel844, rel845, rel846, rel847, and rel848
8.43	rel844, rel845, rel846, rel847, and rel848
8.44	rel845, rel846, rel847, and rel848
8.45	rel846, rel847, and rel848
8.46	rel847 and rel848
8.47	rel848 <b>Note.</b> If you are installing ELM 9.0, run rel848n.sql instead.
8.48	None

Use the scripts in the following table for Unicode databases:

Application Database Version	Required Scripts for Unicode Databases
8.40	rel841u, rel842u, rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.41	rel842u, rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.42	rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.43	rel844u, rel845u, rel846u, rel847u, and rel848u
8.44	rel845u, rel846u, rel847u, and rel848u
8.45	rel846u, rel847u, and rel848u
8.46	rel847u and rel848u
8.47	rel848u <b>Note.</b> If you are installing ELM 9.0, run rel848un.sql instead.
8.48	None

- If the application database version you are installing is either 8.42 or 8.43, run the following SQL command:

```
DROP TABLE PS_PSMCFQUEUESLANG
```

---

**Note.** PS\_PSMCFQUEUESLANG may not exist in some 8.43 application databases. Do *not* drop the table PSMCFQUEUESLANG.

---

- If the application database you are installing is 8.45 or lower, run the following SQL command:

```
DROP TABLE PSOPTSTATUS
```

4. Edit and run the grant.sql script in the <PS\_HOME>\scripts directory. This will grant permissions to the Connect ID.
5. Invoke Data Mover by running <PS\_HOME>\bin\client\winx86\psdmt.exe.  
The PeopleSoft Logon window appears.  
Log on using a valid PeopleSoft Operator ID, such as PS for HRMS or VP1 for FDM.
6. Run the storedddl.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update your platform-specific DDL model statements.  
Log out of Data Mover for the next step.
7. Invoke Data Mover by running <PS\_HOME>\bin\client\winx86\psdmt.exe.  
The PeopleSoft Logon window appears.  
Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.  
This will start Data Mover in bootstrap mode.
8. Run the msgtlsupg.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update the PeopleTools messages in your database.

## Task 7B-4-3: Updating PeopleTools Database Objects

To update PeopleTools database objects to the current release you must be in Application Designer. The Copy from File functionality lets you update your PeopleTools database objects from a file. You must perform this step to bring the database objects in sync with the PeopleTools release. Failure to run this step will introduce problems to your environment.


To update PeopleTools database objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PPLTLS84CUR from the list of projects and click the Select button.

---

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.


---



Selecting PPLTLS84CUR in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and then click the Copy button. When the progress window disappears, the project has been copied.



The Copy From File dialog box showing that PPLTLS84CUR will be copied

If you see the following types of messages in the output window do not worry; they are acceptable because the field label properties were copied with the object definition:

- Definition Name: OPERPSWD.OPERPSWD not copied, entire definition already copied (62,32).
- Definition Name: OPRID.NEW not copied, entire definition already copied (62,32).

## Task 7B-4-4: Updating PeopleTools Multilingual Objects

If you are currently updating a PeopleSoft Multilingual Database, you must also apply the project PPLTLS84CURML, which contains the translations of the PeopleTools Objects.


**Note.** If you have licensed and installed French into this database, copy the PPLTLSML project instead of the PPLTLS84CURML project for French *only*. Substitute the project name PPLTLSML instead of PPLTLS84CURML in the instructions below. Copy the PPLTLS84CURML project to update any non-French languages that are installed in the database.

To update PeopleTools database objects to the current release you must be in Application Designer. The Copy from File functionality lets you update your PeopleTools database objects from a file.

To apply the translation project for PeopleTools 8.48:


1. Bring up the Configuration Manager and select the Display tab.  
Ensure that the language matches the base language of your database. Always run upgrade copy as a base language user.
2. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
3. Select Tools, Copy Project, From File.
4. In the resulting dialog box, change the import directory to <PS\_HOME>\projects.
5. Select PPLTLS84CURML from the list of projects and click the Select button.

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.



Selecting PPLTLS84CURML in the Copy From File dialog box

6. The Upgrade Copy dialog box appears.  
Make sure that all object types are selected.
7. Click the Options button, select the Copy Options tab, and ensure that only the non-English languages you have installed are selected.  
Please note that English and Common should *not* be selected.
8. Select the languages that you are currently installing from the Copy Options dialog box.
9. Click the Copy button.



The Copy From File dialog box showing that PPLTLS84CURML will be copied

When the progress dialog box disappears, the project has been copied.

## Task 7B-4-5: Deleting Obsolete PeopleTools Database Objects

This process removes obsolete PeopleTools objects from your database. To update PeopleTools database objects to the current release you must be in Application Designer. You will use the Copy from File functionality to delete the obsolete objects from the database.


To delete obsolete PeopleTools database objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PPLTLS84CURDEL from the list of projects and click Select.

---

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.


---



Selecting PPLTLS84CURDEL in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and click the Copy button. When the progress dialog box disappears, the project has been copied.



The Copy From File dialog box showing that PPLTLS84CURDEL will be copied

**Note.** If you are applying a required for install PeopleTools patch *and if a database project is included*, apply the database projects now. Make sure to read the patch release notes to find out if database changes are in the patch.

## Task 7B-4-6: Altering PeopleTools Tables


ALTER AUDIT is an online utility used to check whether the PeopleTools tables are synchronized with the underlying SQL data tables in your database. This process compares the data structures of your database tables with the PeopleTools tables to uncover inconsistencies. ALTER AUDIT then reports its findings. In this release, we expect to see differences between the database structure and the tools tables. You will generate and run a SQL script to synchronize the PeopleTools table definitions with the underlying tables in your database.

To alter PeopleTools tables:

1. Launch PeopleTools and sign on to the installed database.
2. From the Application Designer, select File, Open.
3. Select *Project*, enter *PPLTLS84CUR* in the name dialog box, and click OK.
4. Select Build, Project.

The Build dialog box appears:






The Build dialog box

5. Select Create Tables and Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
6. Select Build script file in the Build Execute Options region.
7. Click Settings.

The Build Settings dialog box appears:




Build Settings dialog box: Scripts tab

8. Select the Scripts tab.
9. Select Write Alter comments to script.
10. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region.


Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.

Make sure that the option Alter by Table Rename is selected in the Alter Table Options region.



Build Settings dialog box: Alter tab

11. Select the Create tab and ensure that the Skip table if it already exists, Recreate view if it already exists, and Recreate index only if modified options are selected.



Build Settings dialog box: Create tab

12. Click OK.

The Build dialog box reappears.

13. Click Build.

14. Click Close when the process is completed.

15. Edit the generated SQL script for the correct tablespace names and sizing parameters if you are not using delivered PeopleSoft Tablespace names.

16. Run the generated SQL script in your platform-specific query tool to bring your database structure in sync with the PeopleTools tables.

## Task 7B-4-7: Migrating Records to New Tablespaces

This section discusses:

- Copying the Tablespace Record Project
- Running Alter Tools Tables


### Copying the Tablespace Record Project

PeopleSoft has moved some delivered tables to different Tablespaces in 8.44 and above. You must run this step to move the tables.

To copy the Tablespace Record project:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PT84TBLSPC from the list of projects, and click Select.

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.




Selecting PT84TBLSPC in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and click the Options button. Navigate to General Options and make sure that the Take DDL from Source option is selected.


Click OK.



Upgrade Options dialog box: General Options tab

5. Click the Copy button.

When the progress dialog box disappears, the project has been copied.




The Copy From File dialog box showing that PT84TBLSPC will be copied

## Running Alter Tools Tables

To run Alter Tools tables:

1. Launch PeopleTools and sign on to Installed database.
2. From the Application Designer, select File, Open.
3. Select Project, enter PT84TBLSPC in the name dialog box, and click OK.
4. Select Build, Project.


The Build dialog box appears:



The Build dialog box

5. Select Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
6. Select Build script file in the Build Execute Options region.
7. Click Settings.

The Build Settings dialog box appears:




Build Settings dialog box: Scripts tab

8. Select the Scripts tab.
9. Select Write Alter comments to script.
10. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region, and that the Alter even if no changes check box has been selected.

Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.





Build Settings dialog box: Alter tab

11. Click OK.

The Build dialog box reappears.

12. Click Build.
13. Click Close when the process is completed.
14. Edit the generated SQL script for the correct Tablespace names and sizing parameters if you are not using delivered PeopleSoft Tablespace names.
15. Run the generated SQL script in your platform-specific query tool move the tables to the correct Tablespaces.

## Task 7B-4-8: Updating PeopleTools System Data

Data Mover scripts that update PeopleTools system data are run to enable new features and load new messages for the PeopleTools 8.48 release. Several of the scripts that you need to run are dependent upon the version of the application you are running.

See Understanding Database Updates.

To update PeopleTools system data:

1. Invoke Data Mover by running `<PS_HOME>\bin\client\winx86\psdmt.exe`.

The PeopleSoft Logon window appears.

2. Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.

This will start Data Mover in bootstrap mode.

3. Run the appropriate Data Mover scripts for your application database version.

The application database version refers to the version before you started this step. Be sure to run the scripts in the order listed. The scripts are found in the <PS\_HOME>\scripts directory:

Application Database Version	Scripts to Run
8.40	pt841tls, pt842tls, pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.41	pt842tls, pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.42	pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.43	pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.44	pt845tls, pt846tls, pt847tls, and pt848tls
8.45	pt846tls, pt847tls, and pt848tls
8.46	pt847tls and pt848tls
8.47	pt848tls
8.48	None

4. Run the pslanguages.dms Data Mover script in the <PS\_HOME>\scripts directory.

This script loads language-specific seed data.

5. Run the tlsupgnoncomp.dms Data Mover script in the <PS\_HOME>\scripts directory.

This will import the updated PeopleTools Trees, Roles, and Access Groups into your database.

6. If you are a Multilingual customer, from the Data Mover script that was created for your PeopleSoft database installation, find the UPDATE to PSLANGUAGES.

The statement should look similar to the following:

```
UPDATE PSLANGUAGES SET INSTALLED=1 WHERE LANGUAGE_CD = 'xxx' ;
```

where xxx is one of the PeopleSoft three-letter language code identifiers, as described earlier.

See “Preparing for Installation,” Planning Multilingual Strategy.

Run the SQL command identified above using your SQL tool.

7. Open Data Mover using a valid PeopleSoft Operator ID, such as PS for HRMS or VP1 for FDM.
8. If you are a Multilingual customer and have licensed non-English languages, run the pt848tlsxxx.dms scripts in the <PS\_HOME>\scripts directory.

This will update the language-specific PeopleTools system data in your database.

---

**Note.** The portion of the script name *xxx* is equivalent to the language code (that is, FRA, CFR, GER, JPN, and so on) of the non-English languages you have installed. There will be a Data Mover script for each non-English language.

---

9. Run the msgtleng.dms Data Mover Script in the <PS\_HOME>\scripts directory.  
Non-English message data was loaded in the pt848tlsx.dms scripts. This will update the messages in your database.
10. Run the ptstreng.dms Data Mover script in the <PS\_HOME>\scripts directory.  
Non-English system data was loaded in the pt848tlsx.dms scripts. This will update the SQR strings in your database.
11. Run the storept.dms Data Mover script in the <PS\_HOME>\src\cbl\base directory.  
This will update your PeopleTools COBOL stored statements.
12. Run the ptdefnsec.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update the PeopleTools Definition Security group.
13. Run the createvw.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will recreate all the views in your database.

## Task 7B-4-9: Running PeopleTools Conversions

This section discusses:

- Convert Portal Objects
- Convert Query Headings
- Convert Setup Manager
- Convert Navigation Collection and Pagelet Wizard Data
- Convert Additional Pagelet Wizard Data

### Convert Portal Objects

The Application Engine program UPG844PORTAL splits PSPRSMDEFN.PORTAL\_URLTEXT into segments. This is performed for PeopleSoft Components URLs to extract Menu, Component, and Market information. Record, Field, Event, and Function Names are extracted from Iscript URLs. This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role. The following SQL will identify which users have the PeopleSoft Administrator or Portal Administrator roles:

```
select ROLEUSER, ROLENAME from PSROLEUSER where ROLENAME in ('PeopleSoft⇒
Administrator','Portal Administrator')
```

Run the UPG844PORTAL Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R⇒
INSTALL -AI UPG844PORTAL
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <oprid>, respectively. However, be aware that <pswd> is not the same as the connect password that you entered on the Configuration Manager startup tab. Enter a value for <pswd> that is the password you want to be associated with the <oprid>.

See “Setting Up the Install Workstation.”

See Running the Database Configuration Wizard.

You may see some of the following errors when running this Application Engine program:

- Not authorized CRef: <Portal Object Name> (95,5032).

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

- Security synchronization failed for Portal Object: <Portal Object Name> (96,61).

This is not a fatal error. It may be caused by a content reference that contains invalid URL text and indicates that there was an internal error writing to the security table. The invalid URL text may be pointing to a component or script that does not exist in the database. If you receive this error, please check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database.

- Cref <Portal Object Name> points to Menu: <Menu Name>, Component <Component Name> which doesn't exist. (96,80).

The content reference is pointing to an invalid Menu/Component combination. If you receive this error, please check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

## Convert Query Headings

Crystal 9 when run through Process Scheduler will not handle queries with two or more prompts that have the same heading. These duplicates are also not legal in Query. Any old queries that have this condition need to be altered to work with Crystal. This Application Engine program searches for duplicate prompt headings in the table PSQRYBIND and appends numbers onto the text. For example "Item ID" would become "Item ID 2".

Run the UPGQRYDUPHED Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R⇒
INSTALL -AI UPGQRYDUPHED
```

---

**Note.** If a duplicate heading is found that will exceed the length of the field HEADING, the heading will need to be manually changed. The following error will be written to the log file in these cases :

The prompt heading <HEADING> for Query <QUERY> is duplicated.  
Please manually correct. (108, 1108)

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Query*.

## Convert Setup Manager

The application engine program UPGTSMDAT upgrades Setup Manager Version 1 (shipped with Fin SCM 8.8, CRM 8.9, and with HCM 8.9) to Setup Manager Version 2 (shipped with PeopleTools 8.46 and above). The program moves all data from Setup Manager Version 1 tables to Version 2 tables.

The application engine program was designed so that it can be run in any database, and can be rerun in the same database. In either case, it will determine if there is data to convert and run as appropriate. For detailed information, see comments attached to the Steps and Actions in this Application Engine Program within Application Designer. This program must be run by a PeopleSoft User with PeopleSoft Administrator role.

Run the UPGPTSMDAT Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
INSTALL -AI UPGPTSMDAT
```

## Convert Navigation Collection and Pagelet Wizard Data

The application engine program UPGPT846PP adds Navigation Collection and Pagelet Wizard data from the Common Components and Enterprise Portal storage tables into PeopleTools tables.

The application engine program performs the following conversions:

1. Moves data from Common Components tables to PeopleTools tables.
2. Moves data from Enterprise Portal tables to PeopleTools tables.
3. Updates the registry definitions to enable displaying Navigation pages.
4. Adds, updates, and deletes the Navigation Collections folders and content references in the portal registry to the new structures.
5. Converts Pagelet Wizard definitions to the PeopleTools Pagelet Wizard version.
6. Renames Navigation Collection and Pagelet Wizard portal registry attributes to the PeopleTools attribute names.

This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role.

Run the UPGPT846PP Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -=>
R INSTALL -AI UPGPT846PP
```

You may see the following error when running this Application Engine program:

```
You are not authorized for the <objecttype>...
```

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

You can ignore any other errors encountered on PeopleSoft delivered objects at this time. Check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database. You can safely rerun UPGPT846PP to check for any remaining errors after applying patches.

## Convert Additional Pagelet Wizard Data

The application engine program UPGPT848PP adds the following Pagelet Wizard data sources from Enterprise Portal to PeopleTools: IB Connector, Integration Broker, SOAP, and URL. In addition, the application program transforms the WSRP Portlets created in PeopleTools 8.46 or 8.47 versions of Pagelet Wizard. The process includes the following:

- Move data from Enterprise Portal tables to PeopleTools tables.
- Convert WSRP Portlets created by Pagelet Wizard to the new version.

This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role.

Run the UPGPT848PP Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>  
INSTALL -AI UPGPT848PP
```

You may see the following error when running this Application Engine program:

```
You are not authorized for the <objecttype>...
```

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

You can ignore any other errors encountered on PeopleSoft delivered objects at this time. Check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database. You can safely rerun UPGPT848PP to check for any remaining errors after applying patches.

## Task 7B-4-10: Converting Integration Broker

This section discusses:

- Updating Integration Broker Defaults
- Creating Integration Broker Objects
- Saving Application Messaging Objects
- Exporting Node Transactions
- Deleting Application Messaging Objects
- Deleting Node Transactions

If your database is delivered with PeopleTools 8.48 or higher, do *not* run this task since the database is already delivered with the new Integration Broker objects as of PeopleTools 8.48. Instead, proceed to Changing the User Interface.

### Updating Integration Broker Defaults

User-level node security and transactional security have been added as of PeopleTools 8.48. Service namespace information, a low-level user on the node, and a low-level permission list for service operations, need to be specified. Edit <PS\_HOME>\scripts\ptibupgrade.dms and make the necessary modifications as documented in the script. Consult with your Integration Broker specialist for assistance.

Open Data Mover using a valid PeopleSoft Operator ID and run this script.

### Creating Integration Broker Objects

The application engine program UPGPT848IBUG converts Application Package metadata into Integration Broker metadata. It also creates the projects PTUPGIBCLONE and PTUPGIBDELETE, and the script ptupg\_trx.dms.

---

**Note.** Conversion errors in the Application Engine log file will be resolved by applying application-specific Required for Install patches.

---

Run the UPGPT848IBUG Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>  
INSTALL -AI UPGPT848IBUG
```

## Saving Application Messaging Objects

The PTUPGIBCLONE project was created by the UPGPT848IBUG Application Engine program and contains objects that were successfully converted. Copy this project to a directory of your choice where it will not be overwritten. The objects are copied to file as a precautionary measure since you will delete them from the database in a subsequent step.

To save Application Messaging Objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. From the Application Designer, select File, Open.
3. Select Project, enter *PTUPGIBCLONE* in the name dialog box, and click OK.
4. Select Tools, Copy Project, To File.
5. In the resulting dialog box, change the export directory to one of your choice, and click Copy.

When the progress dialog box disappears, the project has been copied to the specified location.

## Exporting Node Transactions

Open Data Mover using a valid PeopleSoft Operator ID and run the script <PS\_HOME>\scripts\ptupg\_trx\_export.dms to save the old pre-conversion node transaction data.

## Deleting Application Messaging Objects

Delete the obsolete pre-conversion object definitions from the database by first copying the PTUPGIBDELETE project to file, and then copying the same project from file. This project was created by the UPGPT848IBUG Application Engine program and contains the same objects as PTUPGIBCLONE.

To delete Application Messaging Objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. From the Application Designer, select File, Open.
3. Select Project, enter *PTUPGIBDELETE* in the name dialog box, and click OK.
4. Select Tools, Copy Project, To File.
5. In the resulting dialog box, change the export directory to the same one you used for PTUPGIBCLONE, and click Copy.

When the progress dialog box disappears, the project has been copied to the specified location.

6. Select Tools, Copy Project, From File.
7. In the resulting dialog box, change the import directory to the previously specified directory, select PTUPGIBDELETE from the list of projects, and click Select.

---

**Note.** Because the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.

---

8. Select all object types and click the Copy button.

When the progress dialog box disappears, the project has been copied. The actions in the project are set to Delete, so this will delete the obsolete pre-conversion object definitions from the database.

## Deleting Node Transactions

The script ptupg\_trx.dms is generated by the UPGPT848IBUG Application Engine program. This script can be found in the location specified in the OUTPUT variable set in Configuration Manager.

To view the OUTPUT variable:

1. Open Configuration Manager.
2. Select the Profile tab.
3. Click Edit to open the Default profile.
4. Select the Process Scheduler tab.
5. Examine the Output Directory value.

Open Data Mover using a valid PeopleSoft Operator ID and run this script to remove obsolete node transaction data associated with the obsolete objects in the PTUPGIBDELETE project.

## Task 7B-4-11: Changing the User Interface

PeopleTools has updated the styles that define the user interface. This PeopleTools release delivers the classic (old) style as well as two new styles: a dark blue style and a light blue style. PeopleTools System Databases and PeopleSoft 8.4 applications use the classic style, but all other applications use the new dark blue style. The classic style is set as the default. To use one of the new user interfaces, you have to delete the substyle sheets associated with the classic style and replace them with either the light or dark blue substyle sheet.

---

**Note.** The new user interface is supported by Internet Explorer release 5 and above and Netscape Navigator release 6 and above. If you are using a browser and release other than these, the system defaults to the classic style.

---

To enable a new user interface:

1. In Application Designer, select File, Open.
2. On the Open Definition dialog box, select *Style Sheet* from the Definition drop-down list.
3. Enter the name *PSSTYLEDEF* in the Selection Criteria Name field, and select Open.
4. Highlight *PSSTYLEDEF* in the list, and select Open.
5. Click the *PSALTERNATE* Sub Style Sheet and press DELETE.
6. Select Insert, Insert Sub Style Sheet.
7. Select *PSALTERNATE\_LIGHTBLUE* or *PSALTERNATE\_DARKBLUE*.
8. Repeat steps 5 through 7 for the *PTSTYLEDEF* Sub Style Sheet, making sure to use the same extension (*\_LIGHTBLUE* or *\_DARKBLUE*) you used for *PSALTERNATE*.
9. Select File, Save.
10. Open the style sheet *PSQUERYSTYLEDEF* as in steps 1 through 4.
11. Click the *PTQUERYSTYLESUB* Sub Style Sheet and press DELETE.
12. Select Insert, Insert Sub Style Sheet.
13. Select *PTQUERYSTYLESUB\_LIGHTBLUE* or *PTQUERYSTYLESUB\_DARKBLUE*.



- Use the same extension that you used in step 8.
14. Select File, Save.

---

## Task 7B-5: Running Additional Data Mover Scripts

To import additional data for your specific PeopleSoft database, or to make other required changes, you may need to run additional Data Mover scripts. These script files have the extension .dms and are sometimes referred to as “DMS scripts.” They are located in the <PS\_HOME>\scripts directory of your file server, and need to be run from the file server by means of Data Mover.

For the details on which additional application-specific Data Mover scripts to run, consult your application-specific installation instructions.

If you have installed a language other than English, you may need additional instructions on language-specific Data Mover scripts.

See Installing a Multilingual PeopleTools System Database.

---

## Task 7B-6: Installing a Multilingual PeopleTools System Database

This section discusses:

- Understanding the Multilingual Database Project
- Applying the Multilingual Database Project
- Populating the Translated System Data

### Understanding the Multilingual Database Project

The information in this section applies if you are installing a multilingual PeopleTools System database. If not, skip this task and go on to the task “Running VERSION Application Engine Program.” If you are installing an application database (for example, HRMS, FSCM, EPM, and so on), you do not need to run this task.

If you are adding a new (PeopleSoft-delivered) language to the PTSYS database, you must execute this step for that language. For example, if you want to add Polish to your current multilingual database, you should install Polish from PPLTLSML so you will get all objects. If you only “upgrade” your database to have Polish using PPLTLS84CURML, you will only get the objects that changed between 8.40 and the current release.

If you are installing a PeopleTools System database and you want it to be multilingual, you need to perform the steps in the following section after the database has been loaded with Data Mover.

See Applying the Multilingual Database Project.

---

**Note.** When you log onto the multilingual database, be sure to select the base language of the database.

---

## Task 7B-6-1: Applying the Multilingual Database Project

This procedure describes how to apply the multilingual database project that contains translations of the PeopleTools objects.

To apply the multilingual database project:

1. Launch Application Designer.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects.
4. Select *PPLTSLML* from the list of projects and click the Open button.
5. In the Upgrade Copy dialog box, make sure that all object types are selected.
6. Click the Options button, select the Copy Options tab, and ensure that only the non-English languages you have installed are selected.

Please note that English and Common should *not be selected*.

7. Select the languages that you are currently installing from the Copy Options dialog box.
8. Click the Copy button.

(The Reset Done Flags check box will be selected; accept this default.)

## Task 7B-6-2: Populating the Translated System Data

To populate the translated system data:

---

**Note.** You need to run the following script in User mode.

---

1. Launch Data Mover.
2. Open the pt848tlsx.dms script using File, Open.
3. Select File, Run

---

**Note.** The portion of the script name xxx is equivalent to the language code (that is, FRA, CFR, GER, JPN, and so on) of the languages you have installed. There will be a Data Mover script for each language.

---

## Task 7B-7: Running VERSION Application Engine Program

Run the VERSION Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <userid> -CP=>
<userpswd> -R INSTALL -AI VERSION
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <userid> respectively. However, be aware that <userpswd> is not the same as the connect password you entered on the Configuration Manager startup tab. Enter a value for <userpswd> that is the password you want to be associated with the <userid>.

See “Setting Up the Install Workstation.”

See Running the Database Configuration Wizard.

## Task 7B-8: Running SQR Reports

This section discusses:

- Running SQRs on the Client Workstation
- Creating a Shortcut to Run SQRs


**Note.** The following instructions describe how to run SQR reports from the client workstation. On the Windows client, you may prefer to create a shortcut to allow you to run the reports repeatedly. You can use these instructions to run SQRs required in the upcoming task “Checking the Database.” You can also choose to run SQR reports from the command line in console mode.

### Task 7B-8-1: Running SQRs on the Client Workstation

To run an SQR on the client workstation:

1. Select Start, Run, click Browse, and navigate to <PS\_HOME>\bin\sqr\ORA\binw.  
Select sqrw.exe and click Open.
2. Add any needed flags at the end of the command line.

Refer to the table that follows. For those flags that require attributes, append the attributes to the flags with no intervening spaces (for example, `-fd:\psbase\psenv\cr881dmo\`).



Running an SQR report on the client


The following table summarizes the SQR report arguments used by PeopleSoft. (For a full listing of report arguments, press the Help button to view the SQR help topic for this dialog box.)

Flag	Description
-I	Specifies the directories that SQR will search for the #INCLUDE files. (A trailing slash is required.)
-f	Specifies the directory where the report output will be sent.  If you use the <code>-keep</code> flag, specify a directory with an ending slash.  If you use the <code>-printer</code> flag, specify a full pathname with a filename for the HTML file.
-ZIF	Sets the full path and name of the SQR initialization file. The <code>-ZIF</code> flag should point to your <PS_HOME>\sqr\pssqr.ini file.

Flag	Description
-keep	Keeps the .SPF file after the program runs. This enables you to view the report with the SQR viewer.
-printer:ht	Generates the output file in HTML format. Specify the filename, with path location, with the -f flag.

- Click OK.

The resulting dialog box should look something like this:



SQR for PeopleSoft dialog box

- Enter the following values:
  - Enter the report name.  
You must specify the full path.
  - Enter the access ID in the Username field.
  - Enter the access password in the Password field.
  - Enter the database name.
- Click OK to run the SQR report.

---

**Note.** In the Properties dialog box for your SQR icon, make sure that the Start in path points to your Oracle connectivity on the Shortcut tab. If you take the default, you may see a misleading error message about TNS packet writer failure.

---

## Task 7B-8-2: Creating a Shortcut to Run SQRs

If you think you may need to run the SQR reports more than once, you may want to create a shortcut on the Windows client workstation. To save the report arguments:

- Open Windows Explorer on the machine on which you want to run SQR.
- Navigate to <PS\_HOME>\bin\sqr\ORA\binw.
- Right-click sqrw.exe and click Create Shortcut.
- Right-click the shortcut that you just created and select Properties.

5. On the Shortcut tab, add the same sqw flags that you used in the previous task after sqw.exe in the Target entry box.
6. Click OK.
7. To run the report, double-click the shortcut and specify the following information in the dialog box:
  - Report Name: Enter the full path and the name.
  - Database name
  - Username: Enter the access ID.
  - Password: Enter the access password.
  - Report arguments: Make any necessary modifications to the saved arguments.
8. Click OK.

---

## Task 7B-9: Checking the Database

Run and examine two SQW reports to verify that your database is complete.

See Preparing to Run SQW.

To verify that the database is complete, run the following SQW reports from the <PS\_HOME>\sqw directory:

- dddaudit.sqw
- sysaudit.sqw.

For further information about the dddaudit and sysaudit reports, consult PeopleBooks. This documentation includes specific information on how to interpret the reports and how to fix any errors found there.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*, “Ensuring Data Integrity.”

You can greatly improve the performance and run time of sysaudit.sqw run by making the following configuration changes to the Oracle init.ora for your SID:

```
db_file_multiblock_read_count = 16
db_block_buffers = 2000 or greater
log_checkpoint_interval = 9999999
log_buffer = 102400
```

If you are using rollback segments, you may also want to increase the size of the RBSBIG rollback segment to 500 MB.

---

**Note.** If any records show up in the VIEWS-2 or TABLE-3 section of dddaudit and are contained within the PPLTSLS84CURDEL project, you may safely drop these records using the SQL query tool for your platform.

---

### See Also

*Enterprise PeopleTools 8.48 PeopleBook: Data Management*


*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

## Task 7B-10: Running SETSPACE.SQR

Run the SETSPACE.SQR script to populate or synchronize Tablespace information with the system catalog. To run SETSPACE.SQR:

1. Using the instructions provided in the earlier task "Preparing to Run SQR," run SETSPACE.SQR from the <PS\_HOME>\SQR directory.

**Note.** Your results will vary depending on the application you are loading.



Running SETSPACE.SQR on the SQR for PeopleSoft dialog box

2. Click OK.
3. As SETSPACE.SQR runs you see a progress indicator similar to the following.

```
Set Table Space Name in PSRECTBLSPC
```

```
Table PSRECTBLSPC column DDLSPACEName have been updated
with the tablespace found in the system catalog table.
The total number of records updated appears at the bottom of this report.
```

```
Recname           New DDLSpaceName   Old DDLSpaceName
-----
```

```
This phase of SETSPACE will sync up the PSRECTBLSPC and
PSTBLSPCCAT tables
```

```
PSRECTBLSPC Records Updated:      0
```

```
PSTBLSPCCAT Records Inserted:    0
```

```
Ending SQR.
```

---

## Task 7B-11: Running Alter Audit

ALTER AUDIT is an online utility used to check whether the PeopleTools tables are synchronized with the underlying SQL data tables in your database. This process compares the data structures of your database tables with the PeopleTools tables to uncover inconsistencies. ALTER AUDIT then reports its findings. At this point of time in the install, we do not expect to see differences between the database structure and the tools tables.

---

**Note.** If your application database was delivered on the PeopleTools release you are installing (see chart at the beginning of the task “Updating PeopleTools System Tables”), this task is optional.

---

---


**Note.** Triggers are always dropped and re-created during the alter process and will always show up in the generated Alter Audit script. You can ignore the generated script for triggers.

---

To alter PeopleTools tables:

1. Launch PeopleTools and sign on to the installed database.
2. From the Application Designer select File, New.
3. Select Project and click OK.
4. Select Insert, Definitions into Project.
5. Select *Records* from the Definition Type drop-down list box.
6. Select *Table* from the Type drop-down list box.
7. Click Insert, and then click Select All.
8. Click Insert, and then click Close.
9. Select Build, Project.

The Build dialog box appears:




The Build dialog box

10. Select Create Tables and Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
11. Select Build script file in the Build Execute Options region.
12. Click Settings.

The Build Settings dialog box appears:






Build Settings dialog box: Scripts tab

13. Select the Scripts tab.
14. Select Write Alter comments to script.
15. Enter a unique output file name for each type.
16. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region.


Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.

Make sure that Alter by Table Rename is selected in the Alter Table Options region.



Build Settings dialog box: Alter tab

17. Select the Create tab, and ensure that the options Skip table if it already exists, Recreate view if it already exists, and Recreate index only if modified are selected.



Build Setting dialog box: Create tab

18. Click OK.

The Build dialog box reappears.

19. Click Build.

20. Click Close when the process is completed.

21. Edit the generated SQL script for the correct tablespace names and sizing parameters if you are not using delivered PeopleSoft tablespace names.

22. Run the generated SQL scripts in your platform-specific query tool to bring your database structure in sync with the PeopleTools tables.



## CHAPTER 8A

# Configuring the Application Server on Windows

This chapter discusses:

- Understanding the Application Server
- Prerequisites
- Setting Up COBOL for Remote Call
- Verifying Database Connectivity
- Creating, Configuring, and Starting an Initial Application Server Domain
- Configuring Fonts for Languages

---

## Understanding the Application Server

The information in this chapter is provided to help you configure your PeopleSoft application server.

---

**Note.** COBOL is not needed for PeopleTools or for applications that contain no COBOL programs. Check the information on PeopleSoft Customer Connection, and your application-specific documentation for the details on whether your application requires COBOL.

---

PeopleSoft supports a Windows application server to use with any of our supported databases.

You can install the application server using either a “logical” or “physical” three-tier configuration.

- Installing the application server on the same machine as the database server is known as a logical three-tier configuration. For your initial installation, PeopleSoft suggests that you install a logical configuration to simplify setup.
- Installing the application server on a machine separate from the database server machine is known as a physical three-tier configuration.

---

**Note.** You can start application servers as a Windows service, which means that administrators no longer need to manually start each application server that runs on a Windows machine.

---

---

**Note.** To test a three-tier connection from the PeopleTools Development Environment (the Windows-based client), sign on to PeopleSoft using Application Server as the Connection Type, and enter <Machine name or IP Address>:<WSL port number> for the application server name—for example, 224.160.192.128:7000. (As another alternative, you can use the Configuration Manager Startup tab to insert signon defaults and use the Profiles, Database/Application Server tab to specify connect information regarding your application server.)

---

## See Also

“Using the PeopleSoft Installer,” Understanding PeopleSoft Servers

“Setting Up Process Scheduler on Windows,” Starting Process Scheduler as a Windows Service

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Using PSADMIN Menus”

*Enterprise PeopleTools 8.48 PeopleBook: Data Management*

PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise)

“Compiling COBOL on Windows”

---

## Prerequisites

Before beginning this procedure, you should have completed the following tasks:

- Installed your application server.

See “Using the PeopleSoft Installer,” Understanding PeopleSoft Servers.

- Installed Tuxedo 8.1.

See “Installing Additional Components.”

- Granted authorization to a PeopleSoft user ID to start the application server. User ID: VP1 for Enterprise Performance Management and Financials/Supply Chain Management, and PS for HRMS, should be delivered with authorization to start the application server.
- Run the following SQL statements on your database server to review and if needed, update the PSCLASSDEFN table:

```
SELECT CLASSID, STARTAPPSERVER FROM PSCLASSDEFN
WHERE CLASSID IN (SELECT OPRCLASS FROM PSOPRCLS WHERE OPRID='<OPRID>')
UPDATE PSCLASSDEFN SET STARTAPPSERVER=1 WHERE CLASSID='<CLASSID>'
```

---

**Note.** Installers typically use VP1 or PS to test the application server, and the password for these users is stored in a fairly accessible text file. If these users are deleted or their passwords are changed, the application server will no longer be available. To avoid this problem, you can set up a new operator (called PSADMIN or PSASID, for instance) with privileges to start the application server. If you do this, you can use the new operator for your application servers and you won't need to change the password each time VP1 or PS is changed.

---

## Task 8A-1: Setting Up COBOL for Remote Call

Remote Call is a PeopleCode feature that launches a COBOL program from an application server, PeopleCode program or a batch Application Engine PeopleCode program and waits for it to complete execution before continuing. The execution of a COBOL program via Remote Call is completely independent of the Process Scheduler. You need to set up a COBOL runtime environment and COBOL executables on the application server to support Remote Call.

See “Compiling COBOL on Windows.”

If your application does not contain COBOL programs, you do not need to purchase or compile COBOL.

See *Enterprise PeopleTools 8.48 Hardware and Software Requirements*.

---

## Task 8A-2: Verifying Database Connectivity

Before continuing, it is critical to verify connectivity to the database that the application server domain will use. To verify connectivity, connect to the database server from the application server using the native SQL tool on the application server.

For Oracle use SQL\*Plus.

---

## Task 8A-3: Creating, Configuring, and Starting an Initial Application Server Domain

This section discusses:

- Creating, Configuring, and Starting the Application Server Domain
- Testing the Three-Tier Connection
- Importing an Existing Application Server Domain Configuration
- Setting Up a Custom Application Server Domain Configuration
- Troubleshooting Common Errors

### Task 8A-3-1: Creating, Configuring, and Starting the Application Server Domain

To create, configure, and start the application server domain:

1. To run PSADMIN, enter the following command:

```
cd <PS_HOME>\appserv
psadmin
```

---

**Note.** Make sure you change the directory from the <PS\_HOME> on the file server to the <PS\_HOME>, or high-level directory, on the application server.

---

2. When the menu appears, specify *1* for Application Server and press ENTER.
3. Specify *2* to Create a domain and press ENTER.
4. Specify the domain name. For example:

```
Please enter name of domain to create :HR84
```

Domain names are case sensitive and must be eight US-ASCII characters or less. The domain name is used to create a directory name under the <PS\_HOME>\appserv directory.

5. Specify 4 for small if this is your initial domain installation, press ENTER.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*.

6. After the system creates the domain, this prompt appears:

Would you like to configure this domain now? (y/n) [y] :

Enter y. The PeopleSoft Application Server Administration menu appears with a Quick-configure menu similar to this:

-----  
Quick-configure menu -- domain: HR84  
-----

Features =====	Settings =====
1) Pub/Sub Servers : No	15) DBNAME : [HR84]
2) Quick Server : No	16) DBTYPE : [ORACLE]
3) Query Servers : No	17) UserId : [QEDMO]
4) Jolt : Yes	18) UserPswd : [QEDMO]
5) Jolt Relay : No	19) DomainID : [TESTSERV]
6) WSL : No	20) AddToPATH : [c:\Program Files⇒
\Microsoft SQL Server\80\Tools\Binn]	
7) PC Debugger : No	21) ConnectID : [people]
8) Event Notification : Yes	22) ConnectPswd : [people]
9) MCF Servers : No	23) ServerName : []
10) Perf Collator : No	24) WSL Port : [7000]
11) Analytic Servers : Yes	25) JSL Port : [9000]
12) Domains Gateway : No	26) JRAD Port : [9100]
 Actions =====	
13) Load config as shown	
14) Custom configuration	
h) Help for this menu	
q) Return to previous menu	

HINT: Enter 15 to edit DBNAME, then 13 to load

Enter selection (1-26, h, or q):

---

**Note.** If you intend to use the PeopleSoft Report Distribution system, you must select *Yes* for feature 8, Event Notification. This enables the REN server, which is used by the “run to window” functionality of the Report Distribution system. *The Report Distribution system, MultiChannel Framework, and Optimization Framework use REN servers.* You must also remember to enter an Authentication Token Domain when installing the PeopleSoft Pure Internet Architecture (PIA).

---



---

**Note.** If your installation includes more than one application server domain on a given machine, read the troubleshooting section for more information.

---

See Troubleshooting Common Errors.

---

**Note.** If you are configuring an application server domain to support applications based on the PeopleSoft MultiChannel Framework (such as PeopleSoft CRM ERMS), select feature 9, MCF Servers.

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft MultiChannel Framework*, “Configuring REN Servers.”

7. If you need to modify any of the values for these settings, enter the number next to the parameter name, type the new value, and press ENTER.
8. Configure the WSL to boot by changing option 6 to Yes.  
Enter 6, and press ENTER.
9. If you are not installing a REN server, after you update the settings you can load the configuration by entering 13, for Load config as shown, from the Quick-configure menu.

10. If you are installing a REN server:

- a. Enter 14 for Custom configuration.
- b. Reply *y*, and press ENTER, at this prompt:

Do you want to change any config values <y/n> [n]?

- c. Reply *n*, and press ENTER, at this prompt:

Do you want to change any values <y/n> [n]?

Continue to enter *n*, for No, for all sections until you see the PSRENSRV section, and then answer *y*. (Be aware that there are several sections.)

- d. Leave the defaults for all settings except for default\_auth\_token, which you should set to the domain name for your web server.

---

**Note.** The default\_auth\_token setting should be identical to the Authentication Token Domain that you set during PIA installation.

---

See “Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode.”

- e. Accept the defaults for the next series of questions until asked if you want Event Notification configured. In this case, answer *y*.
- f. Accept the default for the remaining questions; the configuration will load automatically.
11. To start the application server (whether you installed a REN server or not), select 1, Boot this domain, from the PeopleSoft Domain administration menu.
12. Select 1, Boot (Serial Boot) or 2, Parallel Boot, from the PeopleSoft Domain Boot Menu.

---

**Note.** The messages you see and the number of processes started will depend on the options you chose during configuration.

---

13. If you plan to continue with PIA installation and testing, do not shut down the application server at this time.

14. If you want to shut down your PeopleSoft application server domain later, follow these simple steps:

- a. From the PeopleSoft Domain Administration menu, enter 2 for Domain shutdown menu.
- b. From the PeopleTools Domain Shutdown Menu, enter 1 for Normal shutdown.

You see messages about the application server processes being shut down. The number of processes stopped will vary depending on the number of processes that started when you booted the domain.

- c. Enter *q* to quit the PeopleSoft Domain Administration Menu.

## Task 8A-3-2: Testing the Three-Tier Connection

If you get an error message when you try to start the application server, it may be due to an incorrect server name or port number, or because the server was not booted. To test a three-tier connection from the PeopleTools Development Environment (the Windows-based client):

1. Select Start, Programs, PeopleTools 8.4, Configuration Manager to start Configuration Manager.
2. Select the Profile Tab. Highlight Default and select Edit.
3. On the Edit Profile dialog box, select *Application Server* as the Connection Type.
4. Enter values for these parameters:
  - Application Server Name
  - Machine Name or IP Address
  - Port Number (WSL)
5. Select Set to add the definition to the list and select OK to close the dialog box.
6. On the Configuration Manager dialog box, select the Startup tab.
7. Select *Application Server* from the Database Type list. Your application server name should be displayed.
8. Enter the values for User ID, Connect ID, and password.
9. Click OK.

---

**Note.** Confirm that the application server is running by booting it. Select 1, Boot this domain, from the PeopleSoft Domain administration menu. Select option 1, Boot (Serial Boot) or 2, Parallel Boot, from the PeopleSoft Domain Boot menu.

---

10. Select Start, Programs, PeopleTools 8.4, Application Designer.
11. In the PeopleSoft Signon dialog box, select *Application Server* as the Connection Type, and confirm that the Application Server Name is correct. Enter values for User ID and password.
12. Select OK to open Application Designer.

## Task 8A-3-3: Importing an Existing Application Server Domain Configuration

If you have an existing application server configuration for a previous PeopleTools release, you can import it to create a new domain. You can import an existing domain configuration by specifying a file or by specifying the path to an existing domain. To import from a file, you must use the `psappsrv.cfg` file found inside an existing application server domain folder (you must specify the full path to `psappsrv.cfg`). This file can be located anywhere in the file system, but must be named `psappsrv.cfg`. To import from an existing domain configuration, you must specify `<PS_HOME>` and the name of an existing application server domain.

To import an existing application server domain configuration:

1. Run PSADMIN:

```
cd <PS_HOME>\appserv
psadmin
```

---

**Note.** Make sure you change the directory from the <PS\_HOME> on the file server to the <PS\_HOME> on the application server.

---

2. Specify *1* for Application Server:

```
-----
PeopleSoft Server Administration
-----
```

```
1) Application Server
2) Process Scheduler
3) Search Server
4) Service Setup
q) Quit
```

Command to execute (1-4, q): 1

3. Specify *4* for *Import domain configuration*.

```
-----
PeopleSoft Application Server Administration
-----
```

```
1) Administer a domain
2) Create a domain
3) Delete a domain
4) Import domain configuration
q) Quit
```

Command to execute (1-4, q): 4

4. Specify whether to import the domain configuration from a file (1) or from an existing application domain configuration (2).

```
-----
PeopleSoft Import Application Server Configuration
-----
```

```
1) Import from file
2) Import from application domain
q) Quit
```

Command to execute (1-2, q) :

5. If you selected *1*, provide the full path to the file psappsrv.cfg, and then specify the name of the domain you want to create. If you selected *2*, go to the next step.

```
Enter full path to configuration file
:C:\temp\oldconfig\psappsrv.cfg
```

```
Enter domain name to create
:HR84
```

6. If you selected 2, provide the full path to the <PS\_HOME> of the existing domain.

```
Enter PS_HOME of domain you wish to import
:C:\HR84
```

If applicable, choose among the existing application server domains in the specified <PS\_HOME>:

Tuxedo domain list:

- 1) HR84A
- 2) HR84B

```
Select domain number to import: 1
```

```
Enter a name for new domain: HR84
```

---

**Note.** Once you create the domain, continue to the next task to verify that the imported configuration parameters are appropriate for the newly created domain. You may need to change the following values: DBName, DBType, UserId, UserPswd, Workstation Listener Port, Jolt Listener Port, Jolt Relay Adapter Listener Port. DBName can be the same or different, depending on which database the application server needs to point to. DBType depends on the database type of DBName. UserId and UserPswd are the user's choice. Workstation Listener Port will need to be modified if the old domain will be up and running in the same machine. Jolt Listener Port will also need a different number if the old domain will be up and running in the same machine. Jolt Relay Adapter Listener Port will need a different number if the old domain will be up and running in the same machine, and will be using Jolt Relay Adapter.

---

## Task 8A-3-4: Setting Up a Custom Application Server Domain Configuration

The Quick-configure menu is initially displayed when you choose to configure your domain. This menu is intended for the commonly adjusted parameters—those most likely to change from domain to domain. However, there are additional configuration parameters that are not available through the Quick-configure menu. For such configuration parameters, you must use the Custom Configuration option, which you can access from the Quick-configure menu. Feel free to skip this procedure if you have already created and configured your Application Server using the Quick-configure menu and want to move forward.

The following steps assume you will be using PSADMIN to specify parameter settings.

To reconfigure an application server domain:

1. Start PSADMIN by entering:

```
cd <PS_HOME>\appserv
psadmin
```

2. Specify *1* for Application Server and press ENTER.
3. Specify *1* for Administer a domain and press ENTER.
4. Select the domain to administer and press ENTER.
5. Specify *4* for Configure this domain and press ENTER.

The option Configure this domain performs the following tasks:

- Shuts down the application server, if it is running. (Shutdown is required since the binary file PSTUXCFG must be deleted and re-created to enable new configuration values. If there are no processes running when shutdown is attempted, an error will be displayed but the script continues on. This is normal.)
  - Initiates an interactive dialog, prompting for configuration parameters.
  - Updates psappsrv.cfg, generates psappsrv.ubb, and internally invokes Tuxedo's tmloadcf executable to create binary file PSTUXCFG used during the domain boot process.
6. Specify *14* for Custom Configuration and press ENTER.
  7. Respond to this prompt:

```
Do you want to change any config values (y/n):
```

- Specify *y* to start an interactive dialog to change or examine parameter values, as described in the next step.  
PeopleSoft recommends this option for more experienced users.
  - Specify *n* if you have already edited psappsrv.cfg, skip the next step, and continue with step 9.
8. Complete the interactive dialog to specify configuration parameters.

Configuration parameters are grouped into sections. For each section, you are asked whether you want to change any parameters in that section, as in the following example:

```
Values for config section - Startup
      DBName=
      DBType=
      UserId=
      UserPswd=
      ConnectId=
      ConnectPswd=
      ServerName=
Do you want to change any values (y/n)? [n]:  y
```

---

**Note.** Enter the user ID and user password that has security to start the application server. All application databases are delivered with one or more application server security users, usually PS or VP1.

---

- Specify *y* to change any parameter values for the current configuration section displayed.

You are prompted for each parameter value. Either specify a new value, or press ENTER to accept the default if applicable. After pressing ENTER, you are positioned at the next parameter in that section. When you are done with that section, you are again asked whether you want to re-edit any of the values you changed.

- If you do not wish to change any values, specify *n* and you will be prompted for the next configuration section.

---

**Note.** The WSL, JSL, and JRAD port numbers have default values of 7000, 9000, and 9100, respectively. These values must be unique for each application server domain. You may alter the port values if necessary to ensure that they are unique.

---



---

**Note.** When setting up your application server, make a note of the values you use for Database Name, Application Server Name (the machine name), and JSL Port. You will need to use these same values when installing the PeopleSoft Pure Internet Architecture.

---

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*.

#### 9. Select server process options.

At this point, you will be prompted to select server process options. If this is your initial installation, we suggest you accept the defaults. A message similar to this appears:

```
Setting Log Directory to the default... [PS_SERVDIR\LOGS]
Configuration file successfully created.
Loading new configuration...
```

“Loading new configuration” indicates that PSADMIN is generating a binary file named PSTUXCFG, which is used to boot the application server. At this point, your application server should be properly configured.

## Task 8A-3-5: Troubleshooting Common Errors

For troubleshooting help, you can access a log file through the PeopleSoft Domain Administration menu. The following information is a list of possible errors you may encounter.

- Use PSADMIN menu option 6 for Edit configuration/log files menu to check for errors in <PS\_HOME>\appserv\<domain>\LOGS\APPSRV\_mmdd.log and <PS\_HOME>\appserv\<domain>\LOGS\TUXLOG.mmddyy.
- If a PeopleSoft server such as PSAPPSRV fails, examine your configuration parameters. The failure of the PSAPPSRV process is often signalled by the message “Assume started”—which is usually misleading, because the process has often failed to start. Check the SIGNON section for misspelled or invalid database name, an invalid or unauthorized OprId, or ConnectId or ServerName is missing or invalid. Finally, make sure the database connectivity is set correctly.
- If a WSL (or JSL) fails to start, try specifying another port number (it may be in use already by another application server domain process).
- If you are unable to start the BBL, check that your Tuxedo is installed fully and that the directory really exists.
- If the installation includes more than one application server domain on a single machine, before booting the second domain, adjust the REN server configuration to avoid conflict in one of these ways:
  - Use PSADMIN to disable Event Notification (option 8 on the Quick-configure menu) for the second and subsequent app server domains.
  - Change default\_http\_port to a value other than 7180.

**See Also**

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft MultiChannel Framework*

---

## Task 8A-4: Configuring Fonts for Languages

This section discusses:

- Configuring Asian Language Fonts

### Task 8A-4-1: Configuring Asian Language Fonts

For text that is rendered by the Java Virtual Machine on the application server (for example, charting) the appropriate fonts must be available on the system. If characters are missing or fail to display after installation, additional configuration may be needed. Fonts are defined with a logical name (such as 'psjvm.1') in the database, and a system font name (such as HGGothic) on the application server. Mappings between the logical name and the system font name are defined on the application server in `<PSHOME>\class\PSOFTFonts.properties`. These mappings generally do not need to be specified for non-Asian languages.

For the correct display of Asian characters on HP-UX (IPF), specify the `JAVA_FONTS` configuration with this command:

```
JAVA_FONTS=$PS_HOME/jre/lib/fonts:/usr/lib/X11/fonts/TrueType/japanese.st⇒
/typefaces:/usr/lib/X11/fonts/TrueType/chinese_t.st/typefaces:/usr/lib/X11/fonts⇒
/TrueType/korean.st/typefaces:/usr/lib/X11/fonts/TrueType/chinese_s.st/typefaces
```

---

**Note.** `psjvm.1` is used by default.

---

The information that follows is an example of the Japanese entries on Windows:

```
ps.lang.1=JPN
JPN.psjvm.1=MS Mincho
JPN.psjvm.2=MS Gothic
```

In the example above, 'psjvm.1' and 'psjvm.2' can be used in charting style classes.

**See Also**

*Enterprise PeopleTools 8.48 PeopleBook: PeopleCode Language Reference*, “Chart Class”





## CHAPTER 8B

# Configuring the Application Server on UNIX

This chapter discusses:

- Understanding the Application Server
- Understanding the Application Server Domain Processes
- Prerequisites
- Setting Environment Variables
- Setting Up COBOL for Remote Call
- Verifying Database Connectivity
- Creating, Configuring, and Starting an Initial Application Server Domain
- Configuring Fonts for Languages

---

## Understanding the Application Server

The information in this chapter is provided to help you configure your PeopleSoft application server.

---

**Note.** COBOL is not needed for PeopleTools or for applications that contain no COBOL programs. Check the information on PeopleSoft Customer Connection, and your application-specific documentation for the details on whether your application requires COBOL.

---

PeopleSoft supports UNIX application servers on the following platforms:

- Hewlett-Packard HP-UX
- IBM AIX
- Tru64
- SUN Solaris
- Linux

You can install the application server using either a “logical” or “physical” three-tier configuration.

- Installing the application server on the same machine as the database server is known as a logical three-tier configuration. For your initial installation, PeopleSoft suggests that you install a logical configuration to simplify setup.
- Installing the application server on a machine separate from the database server machine is known as a physical three-tier configuration.

---

**Note.** To test a three-tier connection from the PeopleTools Development Environment (the Windows-based client), sign on to PeopleSoft using Application Server as the Connection Type, and enter <Machine name or IP Address>:<WSL port number> for the application server name—for example, 224.160.192.128:7000. (As another alternative, you can use the Configuration Manager Startup tab to insert signon defaults and use the Profiles, Database/Application Server tab to specify connect information regarding your application server.)

---

## See Also

“Using the PeopleSoft Installer,” Understanding PeopleSoft Servers

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Using PSADMIN Menus”

*Enterprise PeopleTools 8.48 PeopleBook: Data Management*

PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise)

“Compiling COBOL on UNIX”

---

## Understanding the Application Server Domain Processes

On most platforms (AIX, Solaris, Tru64, Linux, and HP-UX 11.23, also known as 11i V2, and higher, for IPF and PA-RISC) no changes are required from the system defaults, in order to allow the “small” and “development” domains that are shipped with PeopleTools to boot successfully.

Refer to the performance Red Paper for guidance in configuring your system to run larger domains. That document will describe the suggested minimum kernel settings for running PeopleTools in a real-world environment.

See PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Optimization Guide, Optimization Documentation and Software, Red Paper Library. Select the link “Online Performance Configuration Guidelines for PeopleTools” for your PeopleTools version under the heading “PeopleTools, PeopleSoft Enterprise Portal, and Other Technology.”)

Permanently changing system-wide parameters generally requires root privileges, and any changes to the kernel configuration of your operating system should be done with care.

On HP-UX 11.11, also known as 11i V1 (for PA-RISC), the following kernel parameters, at a minimum, need to be changed to allow a small domain to boot successfully:

- increase maxfiles from 60 to 1024
- increase maxuprc from 75 to 256
- increase max\_thread\_proc from 75 to 256

These can be changed with the kernel parameter command, `kmtune (1)`, or with the system administration manager, SAM, with root access. Some examples are:

Query a parameter value: `kmtune -q maxfiles`

Change a parameter value: `kmtune -s maxfiles=1024`

## Prerequisites

Before beginning this procedure, you should have completed the following tasks:

- Installed your application server.  
See “Using the PeopleSoft Installer,” Understanding PeopleSoft Servers.
- Installed Tuxedo 8.1.  
See “Installing Additional Components.”
- Granted authorization to a PeopleSoft user ID to start the application server. User ID: VP1 for Enterprise Performance Management and Financials/Supply Chain Management, and PS for HRMS, should be delivered with authorization to start the application server.
- Run the following SQL statements on your database server to review and if needed, update the PSCLASSDEFN table:

```
SELECT CLASSID, STARTAPPSERVER FROM PSCLASSDEFN
WHERE CLASSID IN (SELECT OPRCLASS FROM PSOPRCLS WHERE OPRID='<OPRID>')
UPDATE PSCLASSDEFN SET STARTAPPSERVER=1 WHERE CLASSID='<CLASSID>'
```

---

**Note.** Installers typically use VP1 or PS to test the application server, and the password for these users is stored in a fairly accessible text file. If these users are deleted or their passwords are changed, the application server will no longer be available. To avoid this problem, you can set up a new operator (called PSADMIN or PSASID, for instance) with privileges to start the application server. If you do this, you can use the new operator for your application servers and you won't need to change the password each time VP1 or PS is changed.

---

## Task 8B-1: Setting Environment Variables

Telnet to your UNIX system. Log in and ensure the following environment variables are set appropriately.

One method to ensure the required PeopleSoft environment variables are set is to source psconfig.sh. Enter the following command:

```
cd <PS_HOME>
. ./psconfig.sh
```

Alternatively you can make sure the following environment variables are set in the .profile file in the user's home directory:

- \$ORACLE\_HOME must point to the correct Oracle installation for example:

```
ORACLE_HOME=/products/oracle/9.2.0;export ORACLE_HOME
```

- \$ORACLE\_HOME/bin must be added to PATH; for example:

```
PATH=$PATH:$ORACLE_HOME/bin;export PATH
```

- \$ORACLE\_HOME/lib must be appended to LD\_LIBRARY\_PATH, LIBPATH, or SHLIB\_PATH, whichever is appropriate for your platform.
- \$ORACLE\_SID must be set to the correct Oracle instance for example:

```
ORACLE_SID=hdmo;export ORACLE_SID
```

- \$COBDIR must be set to the Server Express installation directory; for example:

```
COBDIR=/cobol/prod/svrexpr-4.0.SP1;export COBDIR
```

- \$COBDIR/bin must be appended to the PATH; for example:

```
PATH=$PATH:$COBDIR/bin;export PATH
```

- \$COBDIR/lib must be appended to LD\_LIBRARY\_PATH, LIBPATH, or SHLIB\_PATH, whichever is appropriate for your platform.

```
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$COBDIR/lib;export LD_LIBRARY_PATH
```

```
LIBPATH=$LIBPATH:$COBDIR/lib;export LIBPATH
```

```
SHLIB_PATH=$SHLIB_PATH:$COBDIR/lib;export SHLIB_PATH
```

---

## Task 8B-2: Setting Up COBOL for Remote Call

Remote Call is a PeopleCode feature that launches a COBOL program from an application server, PeopleCode program or a batch Application Engine PeopleCode program and waits for it to complete execution before continuing. The execution of a COBOL program via Remote Call is completely independent of the Process Scheduler. You need to set up a COBOL runtime environment and COBOL executables on the application server to support Remote Call.

See “Compiling COBOL on UNIX.”

If your application does not contain COBOL programs, you do not need to purchase or compile COBOL.

See *Enterprise PeopleTools 8.48 Hardware and Software Requirements*.

---

## Task 8B-3: Verifying Database Connectivity

Before continuing, it is critical to verify connectivity to the database that the application server domain will use. To verify connectivity, connect to the database server from the application server using the native SQL tool on the application server.

For Oracle use SQL\*Plus.

---

## Task 8B-4: Creating, Configuring, and Starting an Initial Application Server Domain

This section discusses:

- Creating, Configuring, and Starting the Application Server Domain
- Testing the Three-Tier Connection

- Importing an Existing Application Server Domain Configuration
- Setting Up a Custom Application Server Domain Configuration
- Troubleshooting Common Errors

## Task 8B-4-1: Creating, Configuring, and Starting the Application Server Domain

To create, configure, and start the application server domain:

1. To run PSADMIN, enter the following command:

```
cd <PS_HOME>/appserv
psadmin
```

---

**Note.** Make sure you change the directory from the <PS\_HOME> on the file server to the <PS\_HOME>, or high-level directory, on the application server.

---

2. When the menu appears, specify *1* for Application Server and press ENTER.
3. Specify *2* to Create a domain and press ENTER.
4. Specify the domain name. For example:

```
Please enter name of domain to create :HR84
```

Domain names are case sensitive and must be eight characters or less. The domain name is used to create a directory name under the <PS\_HOME>/appserv directory.

5. Specify *4* for small if this is your initial domain installation, press ENTER.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*.

6. After the system creates the domain, this prompt appears:

```
Would you like to configure this domain now? (y/n) [y] :
```

Enter *y*. The PeopleSoft Application Server Administration menu appears with a Quick-configure menu similar to this:

```
-----
Quick-configure menu -- domain: HR84
-----
```

Features		Settings	
=====		=====	
1) Pub/Sub Servers	: No	15) DBNAME	: [HR84]
2) Quick Server	: No	16) DBTYPE	: [ORACLE]
3) Query Servers	: No	17) UserId	: [VP1]
4) Jolt	: Yes	18) UserPswd	: [VP1]
5) Jolt Relay	: No	19) DomainID	: [TESTSERV]
6) WSL	: No	20) AddToPATH	: [.]
7) PC Debugger	: No	21) ConnectID	: [people]
8) Event Notification	: Yes	22) ConnectPswd	: [people]
9) MCF Servers	: No	23) ServerName	: []
10) Perf Collator	: No	24) WSL Port	: [7000]

```

11) Analytic Servers      : Yes      25) JSL Port      :[9000]
12) Domains Gateway     : No       26) JRAD Port     :[9100]

```

```

      Actions
      =====
13) Load config as shown
14) Custom configuration
   h) Help for this menu
   q) Return to previous menu

```

HINT: Enter 15 to edit DBNAME, then 13 to load

Enter selection (1-26, h, or q):

---

**Note.** If you intend to use the PeopleSoft Report Distribution system, you must select *Yes* for feature 8, Event Notification. This enables the REN server, which is used by the “run to window” functionality of the Report Distribution system. *The Report Distribution system, MultiChannel Framework, and Optimization Framework use REN servers.* You must also remember to enter an Authentication Token Domain when installing the PeopleSoft Pure Internet Architecture (PIA).

---



---

**Note.** If your installation includes more than one application server domain on a given machine, read the troubleshooting section for more information.

---

See Troubleshooting Common Errors.

---

**Note.** If you are configuring an application server domain to support applications based on the PeopleSoft MultiChannel Framework (such as PeopleSoft CRM ERMS), select feature 9, MCF Servers.

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft MultiChannel Framework*, “Configuring REN Servers.”

7. If you need to modify any of the values for these settings, enter the number next to the parameter name, type the new value, and press ENTER.
8. Configure the WSL to boot by changing option 6 to Yes.  
Enter 6, and press ENTER.
9. If you are not installing a REN server, after you update the settings you can load the configuration by entering 13, for Load config as shown, from the Quick-configure menu.
10. If you are installing a REN server:

- a. Enter 14 for Custom configuration.
- b. Reply *y*, and press ENTER, at this prompt:

```
Do you want to change any config values <y/n> [n]?
```

- c. Reply *n*, and press ENTER, at this prompt:

```
Do you want to change any values <y/n> [n]?
```

Continue to enter *n*, for No, for all sections until you see the PSRENSRV section, and then answer *y*. (Be aware that there are several sections.)

- d. Leave the defaults for all settings except for `default_auth_token`, which you should set to the domain name for your web server.

---

**Note.** The `default_auth_token` setting should be identical to the Authentication Token Domain that you set during PIA installation.

---

See “Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode.”

- e. Accept the defaults for the next series of questions until asked if you want Event Notification configured. In this case, answer *y*.
  - f. Accept the default for the remaining questions; the configuration will load automatically.
11. To start the application server (whether you installed a REN server or not), select *1*, Boot this domain, from the PeopleSoft Domain administration menu.
  12. Select *1*, Boot (Serial Boot) or *2*, Parallel Boot, from the PeopleSoft Domain Boot Menu.

---

**Note.** The messages you see and the number of processes started will depend on the options you chose during configuration.

---

13. If you plan to continue with PIA installation and testing, do not shut down the application server at this time.
14. If you want to shut down your PeopleSoft application server domain later, follow these simple steps:
  - a. From the PeopleSoft Domain Administration menu, enter *2* for Domain shutdown menu.
  - b. From the PeopleTools Domain Shutdown Menu, enter *1* for Normal shutdown.  
 You see messages about the application server processes being shut down. The number of processes stopped will vary depending on the number of processes that started when you booted the domain.
  - c. Enter *q* to quit the PeopleSoft Domain Administration Menu.

## Task 8B-4-2: Testing the Three-Tier Connection

If you get an error message when you try to start the application server, it may be due to an incorrect server name or port number, or because the server was not booted. To test a three-tier connection from the PeopleTools Development Environment (the Windows-based client):

1. Select Start, Programs, PeopleTools 8.4, Configuration Manager to start Configuration Manager.
2. Select the Profile Tab. Highlight Default and select Edit.
3. On the Edit Profile dialog box, select *Application Server* as the Connection Type.
4. Enter values for these parameters:
  - Application Server Name
  - Machine Name or IP Address
  - Port Number (WSL)
5. Select Set to add the definition to the list and select OK to close the dialog box.
6. On the Configuration Manager dialog box, select the Startup tab.
7. Select *Application Server* from the Database Type list. Your application server name should be displayed.
8. Enter the values for User ID, Connect ID, and password.
9. Click OK.

---

**Note.** Confirm that the application server is running by booting it. Select *1*, Boot this domain, from the PeopleSoft Domain administration menu. Select option *1*, Boot (Serial Boot) or *2*, Parellel Boot, from the PeopleSoft Domain Boot menu.

---

10. Select Start, Programs, PeopleTools 8.4, Application Designer.
11. In the PeopleSoft Signon dialog box, select *Application Server* as the Connection Type, and confirm that the Application Server Name is correct. Enter values for User ID and password.
12. Select OK to open Application Designer.

## Task 8B-4-3: Importing an Existing Application Server Domain Configuration

If you have an existing application server configuration for a previous PeopleTools release, you can import it to create a new domain. You can import an existing domain configuration by specifying a file or by specifying the path to an existing domain. To import from a file, you must use the `psappsrv.cfg` file found inside an existing application server domain folder (you must specify the full path to `psappsrv.cfg`). This file can be located anywhere in the file system, but must be named `psappsrv.cfg`. To import from an existing domain configuration, you must specify `<PS_HOME>` and the name of an existing application server domain.

To import an existing application server domain configuration:

1. Run PSADMIN:

```
cd <PS_HOME>/appserv
psadmin
```

---

**Note.** Make sure you change the directory from the `<PS_HOME>` on the file server to the `<PS_HOME>` on the application server.

---

2. Specify *1* for Application Server:

```
-----
PeopleSoft Server Administration
-----
```

```
1) Application Server
2) Process Scheduler
3) Search Server
q) Quit
```

```
Command to execute (1-3, q): 1
```

3. Specify *4* for *Import domain configuration*.

```
-----
PeopleSoft Application Server Administration
-----
```

```
1) Administer a domain
2) Create a domain
3) Delete a domain
4) Import domain configuration
```



q) Quit

Command to execute (1-4, q): 4

4. Specify whether to import the domain configuration from a file (1) or from an existing application domain configuration (2).

```
-----
PeopleSoft Import Application Server Configuration
-----
```

```
1) Import from file
2) Import from application domain
q) Quit
```

Command to execute (1-2, q) :

5. If you selected 1, provide the full path to the file psappsrv.cfg, and then specify the name of the domain you want to create. If you selected 2, go to the next step.

```
Enter full path to configuration file
:/home/oldconfig/psappsrv.cfg
```

```
Enter domain name to create
:HR84
```

6. If you selected 2, provide the full path to the <PS\_HOME> of the existing domain.

```
Enter PS_HOME of domain you wish to import
:/home/HR84
```

If applicable, choose among the existing application server domains in the specified <PS\_HOME>:

Tuxedo domain list:

```
1) HR84A
2) HR84B
```

Select domain number to import: 1

Enter a name for new domain: HR84

---

**Note.** Once you create the domain, continue to the next task to verify that the imported configuration parameters are appropriate for the newly created domain. You may need to change the following values: DBName, DBType, UserId, UserPswd, Workstation Listener Port, Jolt Listener Port, Jolt Relay Adapter Listener Port. DBName can be the same or different, depending on which database the application server needs to point to. DBType depends on the database type of DBName. UserId and UserPswd are the user's choice. Workstation Listener Port will need to be modified if the old domain will be up and running in the same machine. Jolt Listener Port will also need a different number if the old domain will be up and running in the same machine. Jolt Relay Adapter Listener Port will need a different number if the old domain will be up and running in the same machine, and will be using Jolt Relay Adapter.

---

## Task 8B-4-4: Setting Up a Custom Application Server Domain Configuration

The Quick-configure menu is initially displayed when you choose to configure your domain. This menu is intended for the commonly adjusted parameters—those most likely to change from domain to domain. However, there are additional configuration parameters that are not available through the Quick-configure menu. For such configuration parameters, you must use the Custom Configuration option, which you can access from the Quick-configure menu. Feel free to skip this procedure if you have already created and configured your Application Server using the Quick-configure menu and want to move forward.

The following steps assume you will be using PSADMIN to specify parameter settings.

To reconfigure an application server domain:

1. Start PSADMIN by entering:

```
cd <PS_HOME>/appserv
psadmin
```

2. Specify *1* for Application Server and press ENTER.
3. Specify *1* for Administer a domain and press ENTER.
4. Select the domain to administer and press ENTER.
5. Specify *4* for Configure this domain and press ENTER.

The option Configure this domain performs the following tasks:

- Shuts down the application server, if it is running. (Shutdown is required since the binary file PSTUXCFG must be deleted and re-created to enable new configuration values. If there are no processes running when shutdown is attempted, an error will be displayed but the script continues on. This is normal.)
  - Initiates an interactive dialog, prompting for configuration parameters.
  - Updates psappsrv.cfg, generates psappsrv.ubb, and internally invokes Tuxedo's tmloadcf executable to create binary file PSTUXCFG used during the domain boot process.
6. Specify *14* for Custom Configuration and press ENTER.
  7. Respond to this prompt:

```
Do you want to change any config values (y/n):
```

- Specify *y* to start an interactive dialog to change or examine parameter values, as described in the next step.  
PeopleSoft recommends this option for more experienced users.
  - Specify *n* if you have already edited psappsrv.cfg, skip the next step, and continue with step 9.
8. Complete the interactive dialog to specify configuration parameters.

Configuration parameters are grouped into sections. For each section, you are asked whether you want to change any parameters in that section, as in the following example:

```
Values for config section - Startup
      DBName=
      DBType=
      UserId=
      UserPswd=
```

```

ConnectId=
ConnectPswd=
ServerName=
Do you want to change any values (y/n)? [n]:  y

```

---

**Note.** Enter the user ID and user password that has security to start the application server. All application databases are delivered with one or more application server security users, usually PS or VP1.

---

- Specify *y* to change any parameter values for the current configuration section displayed.  
You are prompted for each parameter value. Either specify a new value, or press ENTER to accept the default if applicable. After pressing ENTER, you are positioned at the next parameter in that section. When you are done with that section, you are again asked whether you want to re-edit any of the values you changed.
- If you do not wish to change any values, specify *n* and you will be prompted for the next configuration section.

---

**Note.** The WSL, JSL, and JRAD port numbers have default values of 7000, 9000, and 9100, respectively. These values must be unique for each application server domain. You may alter the port values if necessary to ensure that they are unique.

---



---

**Note.** When setting up your application server, make a note of the values you use for Database Name, Application Server Name (the machine name), and JSL Port. You will need to use these same values when installing the PeopleSoft Pure Internet Architecture.

---

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*.

#### 9. Select server process options.

At this point, you will be prompted to select server process options. If this is your initial installation, we suggest you accept the defaults. A message similar to this appears:

```

Setting Log Directory to the default... [PS_SERVDIR/LOGS]
Configuration file successfully created.
Loading new configuration...

```

“Loading new configuration” indicates that PSADMIN is generating a binary file named PSTUXCFG, which is used to boot the application server. At this point, your application server should be properly configured.

## Task 8B-4-5: Troubleshooting Common Errors

For troubleshooting help, you can access a log file through the PeopleSoft Domain Administration menu. The following information is a list of possible errors you may encounter.

- Use the PSADMIN PeopleSoft Domain Administration menu option 6 for Edit configuration/log files menu to check for errors in <PS\_HOME>/appserv/<domain>/LOGS/APPSRV\_mmdd.LOG and <PS\_HOME>/appserv/<domain>/LOGS/TUXLOG.mmddyy.
- If a PeopleSoft server such as PSAPPSRV fails, examine your configuration parameters. The failure of the PSAPPSRV process is often signalled by the message “Assume started”—which is usually misleading, because the process has often failed to start. Check the SIGNON section for misspelled or invalid database

name, an invalid or unauthorized OprId, or ConnectId or ServerName is missing or invalid. Finally, make sure the database connectivity is set correctly.

- If a WSL (or JSL) fails to start, try specifying another port number (it may be in use already by another application server domain process).
- If you are unable to start the BBL, check that your Tuxedo is installed fully and that the directory really exists.
- If the installation includes more than one application server domain on a single machine, before booting the second domain, adjust the REN server configuration to avoid conflict in one of these ways:
  - Use PSADMIN to disable Event Notification (option 8 on the Quick-configure menu) for the second and subsequent app server domains.
  - Change default\_http\_port to a value other than 7180.

Also check that you do not have older Tuxedo releases (such as Tuxedo 6.4) prepended in your PATH or runtime library (LIBPATH, SHLIB\_PATH or LD\_LIBRARY\_PATH, depending on UNIX platform).

### See Also

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft MultiChannel Framework*

---

## Task 8B-5: Configuring Fonts for Languages

This section discusses:

- Configuring Asian Language Fonts
- Installing TrueType Fonts for Tru64 UNIX

### Task 8B-5-1: Configuring Asian Language Fonts

For text that is rendered by the Java Virtual Machine on the application server (for example, charting) the appropriate fonts must be available on the system. If characters are missing or fail to display after installation, additional configuration may be needed. Fonts are defined with a logical name (such as *psjvm.1*) in the database, and a system font name (such as *HGGothic*) on the application server. Mappings between the logical name and the system font name are defined on the application server in `<PSHOME>/appserver/classes/PSOFTFonts.properties`. These mappings generally do not need to be specified for non-Asian languages.

For the correct display of Asian characters on HP-UX (IPF), specify the `JAVA_FONTS` configuration with this command:

```
JAVA_FONTS=$PS_HOME/jre/lib/fonts:/usr/lib/X11/fonts/TrueType/japanese.st⇒
/typefaces:/usr/lib/X11/fonts/TrueType/chinese_t.st/typefaces:/usr/lib/X11/fonts⇒
/TrueType/korean.st/typefaces:/usr/lib/X11/fonts/TrueType/chinese_s.st/typefaces
```

---

**Note.** On UNIX, the X11 font packages must be installed.

---

---

**Note.** `psjvm.1` is used by default.

---

The information that follows is an example of the Japanese entries on HP-UX:

```
ps.lang.1=JPN
JPN.psjvm.1=HG Gothic B
JPN.psjvm.2=HG Mincho L
```

In the example above, 'psjvm.1' and 'psjvm.2' can be used in charting style classes. Extra fonts and languages can be added if needed.

---

**Note.** *On all UNIX platforms*, the `<PS_HOME>/jre/lib/fonts.propertiesXXX` file (where XXX represents the locale that the machine is operating under) must contain the mappings for all the fonts that will be used by the application server to generate charts. On most platforms, the default `font.propertiesXXX` files contain mappings only for those fonts most commonly used by each locale. If you wish to generate charts using fonts that are not by default mapped into the `font.propertiesXXX` file for your locale, you must manually modify the default file to include this information. Find the `font.propertiesXXX` files containing the appropriate mapping information, and append that mapping information to the end of the `font.propertiesXXX` file that matches your machine's locale.

---



---

**Note.** *On HP-UX*, the path to the fonts must be entered in the JVM's `font.propertiesXXX` file (where XXX is the locale that the machine is operating under). Each full path must be separated by colons under the setting `hp.fontpath`. This file is located in `<PSHOME>/jre/lib`. Following is an example:

```
hp.fontpath=/usr/lib/X11/fonts/ms.st/typefaces:/usr/lib
/X11/fonts/TrueType/japanese.st/typefaces:
```

---

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: PeopleCode Language Reference*, “Chart Class”

## Task 8B-5-2: Installing TrueType Fonts for Tru64 UNIX

Because the fonts that come with the Tru64 UNIX do not include European characters, you must obtain and install TrueType fonts to display European and Asian characters on Tru64. You can purchase these fonts from vendors such as Founder, Dynalab Inc., and Ricoh. Once you obtain a suitable font you must install it for use by the Application Server's JVM, as described here.

To install the TrueType fonts:

1. Copy the TrueType font to the `<PS_HOME>/jre/lib/fonts` directory.
2. The font should come with an example `fonts.scale.*` file. Find this file and append the entries (not including the number at the top) to the `fonts.scale` file in `<PS_HOME>/jre/lib/fonts`.
3. Edit the number at the top of the new `fonts.scale` file to reflect the number of entries (the old number plus the number at the top of the example file).
4. Run `mkfontdir` in this directory.
5. Edit `PSOFTFont.properties` to point to this file for the language you are configuring (see above).

## **See Also**

Founder: [www.foundertype.com](http://www.foundertype.com)

Dynalab Inc.: [www.dynalab.com](http://www.dynalab.com)

Ricoh: [www.ricoh.com](http://www.ricoh.com)

## CHAPTER 9A

# Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode

This chapter discusses:

- Understanding PeopleSoft Pure Internet Architecture
- Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation
- Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server in GUI Mode
- Installing the PeopleSoft Pure Internet Architecture on WebLogic in GUI Mode
- Installing the PeopleSoft Pure Internet Architecture on WebSphere
- Encrypting the Password (AIX Only)
- Testing the PeopleSoft Pure Internet Architecture Installation

---

## Understanding PeopleSoft Pure Internet Architecture

This chapter explains how to install and configure the components of the PeopleSoft Pure Internet Architecture (PIA) in GUI mode. It includes instructions for installing the PeopleSoft files on Oracle Application Server (OAS), WebLogic, and WebSphere. Only complete the instructions for the web server product that you installed.

See “Installing Web Server Products.”

The setup program for the PeopleSoft Pure Internet Architecture is installed to the web server machine when you run the PeopleSoft Installer and select the PeopleSoft Web Server option.

See “Using the PeopleSoft Installer.”

PeopleSoft only supports customer installations that use the version of the web servers packaged with PeopleTools. *You must install the web server before you install the PeopleSoft Pure Internet Architecture.* Before you install the PeopleSoft Pure Internet Architecture, you must also have configured an application server, as described in the previous chapter.

If your web server is on a different machine than your application server, you need to make sure you have JRE installed on your web server to run the PIA installation.

The initial PIA setup automatically creates the default PeopleSoft site named *ps*. In subsequent PIA setups, change the site name from *ps* to a unique value. We recommend using the database name. This is handy for easy identification and ensures that the database web server files are installed in a unique web site.

The URL that you use to invoke PIA must conform to ASN.1 specifications. That is, it may contain only alphanumeric characters, dots ("."), or dashes ("-"). The URL must not begin or end with a dot or dash, or contain consecutive dots (".."). If the URL includes more than one portion, separated by dots, do not use a number to begin a segment if the other segments contain letters. For example, "mycompany.second.country.com" is correct, but "mycompany.2nd.country.com" is wrong.

---

**Note.** If you want to connect between multiple application databases, you need to implement single signon.

---

---

**Note.** If the PeopleSoft Pure Internet Architecture installation encounters an error, it will indicate which log files to refer to.

---

See "Installing Web Server Products."

---

**Warning!** Do not use GUI mode to install the PeopleSoft Pure Internet Architecture if you want to install on a WebSphere server *and* you are running on a UNIX platform. In this situation, use console mode to set up the PeopleSoft Pure Internet Architecture.

---

---

**Note.** The machine on which you run the PeopleSoft Pure Internet Architecture install must be running in 256 *color mode*. This is not necessary for UNIX or console mode.

---

The PeopleSoft Pure Internet Architecture installation includes the following products:

- *PeopleSoft Pure Internet Architecture.* This product is the centerpiece of the PeopleSoft architecture that enables users to work on a machine with only a supported browser installed. This option installs the servlets required for deploying PeopleSoft Applications and for the PeopleSoft Portal. The portal packs and Enterprise Portal have their own installation instructions, which are available on Customer Connection. For an overview of the various types of portals, consult the following.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

- *PeopleSoft Report Repository.* This product works in conjunction with Process Scheduler to allow report distribution over the web.
- *PeopleSoft Integration Gateway.* This product is the entry and exit point for all messages to and from the Integration Broker. Its Java-based Connector architecture allows asynchronous and synchronous messages to be sent over a variety of standard protocols, many that are delivered at install, or through custom connectors.
- *PeopleSoft CTI Console.* This product works in conjunction with CTI vendor software to enable call center agents to take advantage of browser based teleset management and automatic population of application pages with relevant data associated with incoming calls, such as customer or case details.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft MultiChannel Framework*.

- *PeopleSoft Sync Server Gateway.* The Sync Server is a specialized application server optimized for concurrent multi-user synchronization processing in support of PeopleTools Mobile Agent. The web server-based Sync Gateway routes synchronization requests and messages to and from the appropriate Sync Server.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Mobile Agent*.

- *Environment Management Hub.* The Environment Management hub is a web application that is installed with the PeopleSoft Pure Internet Architecture and portal. It is started along with the rest of the web applications when the user boots the web server. You cannot start the Environment Management Hub on a



server that is configured to run HTTPS; in other words, if you plan to run Environment Management, your PIA server needs to be configured in HTTP mode.

See *Enterprise PeopleTools 8.48 PeopleBook: Software Updates*.

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: Security Administration*

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

---

# Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation

You have the option to specify an authentication domain when you install the PeopleSoft Pure Internet Architecture on OAS, WebLogic, or WebSphere.

---

**Note.** The authentication domain was referred to as the Authentication Token Domain in previous releases, and that term is still seen in the software.

---

When an authentication domain is specified during the PeopleSoft Pure Internet Architecture install, that value gets used as the Cookie domain in the web server configuration. The main requirements when setting a cookie domain are:

- The host must have a fully qualified domain name (FQDN). The requirement that you must have a domain name does not imply that you must have a DNS, but you do need some type of naming service such as DNS or some managed `..etc\hosts` file that contains a list of the servers with their domain name.
- The cookie domain value being set must begin with a dot (.ps.com is valid, ps.com is NOT valid).
- The cookie domain value being set must contain at least 1 embedded dot (.ps.com is valid, .corp.ps.com is valid, .com is NOT valid).
- The cookie domain value can only be a single domain name. It cannot be a delimiter-separated list of domains.

By default, the browser only sends cookies back to the machine that set the cookie. So if web server `crm.yourdomain.com` sets a cookie, the browser will only send it back there. You can make the browser send the single signon cookie to all servers at `yourdomain.com` by typing your domain name in the Authentication Token Domain list box of web server `crm`.

Specifying the authentication domain may be necessary in certain cases. For example, if you plan to use the PeopleSoft portal technology, be sure to read the supporting documentation to determine whether setting the authentication domain is required for correct operation.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*, “Configuring the Portal Environment.”

Specify an authentication domain if you plan to run a REN Server. REN Servers are required for PeopleSoft MultiChannel Framework, Reporting, and some PeopleSoft CRM applications supported by PeopleSoft MultiChannel Framework.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft MultiChannel Framework*.

Specify an authentication domain if you plan to use Business Objects Enterprise.

See “Installing and Configuring Software for Crystal Reports,” Installing BusinessObjects Enterprise XI.

---

## Task 9A-1: Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server in GUI Mode

This section discusses:

- Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server
- Uninstalling the PeopleSoft Pure Internet Architecture from Oracle Application Server

---

**Note.** The installation of the PeopleSoft Pure Internet Architecture on Oracle Application Server includes the PeopleSoft Provider. Use this to configure PeopleSoft portlets on Oracle Portal pages.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*, “Deploying PeopleSoft Portlets on Oracle Portal Pages.”

### Task 9A-1-1: Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server

Before installing the PeopleSoft Pure Internet Architecture (PIA) on Oracle Application Server (OAS), you must have installed the OAS software.

See “Installing Web Server Products,” Installing Oracle Application Server.

When installing PIA on OAS, you must work with a local copy of the PIA installation software; you cannot install remotely. If you are doing the installation on a machine other than the one on which you installed PeopleTools, copy the <PS\_HOME>\setup\mpinternet directory to the local machine.

1. Start opmn process if necessary.

To check the status of the opmn process run this command:

```
<OAS_HOME>\opmn\bin\opmnctl status
```

If you get the response, “Unable to connect to opmn”, start it by running this command:

```
<OAS_HOME>\opmn\bin\opmnctl start
```

See “Installing Web Server Products,” Installing Oracle Application Server.

2. Start dcm-daemon process if necessary.

To check the status of dcm-daemon run this command:

```
<OAS_HOME>\opmn\bin\opmnctl status
```

If the dcm-daemon’s status is not “Alive”, start it by running this command:


```
<OAS_HOME>\opmn\bin\opmnctl startproc ias-component=dcm-daemon
```

3. Navigate to <PS\_HOME>\setup\mpinternet.
4. Run setup.<OS>.

Alternatively, at the command prompt, type `<JAVA_HOME>\bin\java -cp setup.jar run`, where `<JAVA_HOME>` is the directory where the JRE software is installed. The default is `<PS_HOME>\jre`.


See “Using the PeopleSoft Installer,” Prerequisites.

5. Click Next on the welcome screen.




PeopleSoft Internet Architecture Welcome window

6. Enter the location of `<PS_HOME>`, the home directory where you installed PeopleTools.



Specifying the PeopleSoft home directory


7. Accept Oracle Application Server as the setup type.



Choosing Oracle Application Server

Click Next.

8. Specify the OAS home directory; that is, the directory where you installed the OAS software.  
Click Next.



Specifying the OAS home directory

9. Enter an application name for this web server (for example, PeopleSoft) and select the type of server you want to install.

The *Single Component Server* option creates one OC4J component to hold all the PeopleSoft web applications. The installer uses the Application Name you enter for the new component's name.


The *Multi Component Server* option splits the PeopleSoft web application into three OC4J components—PIA\_<application\_name>, PSOL\_<application\_name> (for the PeopleSoft Online Library), and PSEMHUB\_<application\_name> (for the PeopleSoft Environment Management Framework). Each OC4J component has its own JVM, so the multicomponent option will be better suited for installations needing higher performance or reliability. If you are not sure which to pick choose Single.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with Oracle Application Server 10g.”

See “Installing PeopleBooks.”


See *Enterprise PeopleTools 8.48 PeopleBook: Software Updates*, “Configuring and Running Environment Management Components.”

10. If you entered a new (unused) name, click Next and skip the next two steps. Continue with step 13.



Specifying the application name and server type

11. If the name you enter belongs to an OAS web server application that already exists, select Single Component Server or Multi Component Server and click Next.
12. Select one of the following options for the type of installation:




Selecting the installation options for an existing OAS application

- *Create an additional site in the existing application:* Select this option to install only the necessary files for defining an additional PeopleSoft site onto the existing OAS web server configuration.
- *Deploy additional PeopleSoft application extensions:* This option is solely for use with PeopleSoft product applications. PeopleSoft application extensions are provided with certain PeopleSoft applications, and this option allows you to deploy those extensions. Consult the installation documentation for your PeopleSoft application to see whether this option is appropriate. PeopleTools does not use application extensions.
- *Go back to enter a new application name:* Select this option to return to the previous window.


**Note.** To redeploy PIA on OAS, you must remove the OC4J component(s) and perform a fresh PIA installation. Use Application Server Control or `dcmtl` commands to remove the OC4J component(s). Note that any customizations done after the PIA install must be done again.

13. If you select the option Deploy additional PeopleSoft application extensions, a window appears listing the available application packages. Select the check boxes for those applications you want to deploy:




Selecting application packages to deploy

14. Enter a web site name; the default is ps.



Entering the web site name

15. Specify the application server name, its JSL (Jolt Station Listener) port number, its HTTP and HTTPS port numbers, the Authentication Token Domain (optional), and click Next.



Specifying the app server name, port numbers, and authentication token domain for the OAS installation.

**AppServer name**

Enter the name of your application server machine.



**JSL Port**

Enter the JSL port number you specified when setting up the application server (the default is 9000).

**HTTP/HTTPS**

The default HTTP/HTTPS ports of the Oracle HTTP Server (OHS) are 80/443 for Windows and 7777/4443 for UNIX/Linux. However, you should enter different HTTP/HTTPS port values at this point for the PIA installation. Please use any unused port other than 80/443 for Windows and 7777/4443 for UNIX/Linux. The PIA installation may fail or may not work properly if you enter the same HTTP/HTTPS ports for the PIA installation as the default OHS ports.

To access PIA, specify a URL with either the default OHS port values, or the port values you enter here for PIA. For example, `http://<machine_name>:<port_number>/<site_name>/signon.html`.

For Multi Component Server, the HTTP/HTTPS ports that you enter here correspond to the OC4J component `PIA_<application_name>`.

**Authentication Token Domain**

The value you enter for Authentication Token Domain must match the value you specify for the authentication domain when configuring your application server. In addition, certain installation configurations require that you specify an authentication domain.

See Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation.

16. Enter the name of the web profile in the database that will be used to configure this PeopleSoft web site.


This can be either a predelivered name as shown on the page, or one you intend to create yourself using PeopleTools, Web Profile Configuration, after logging in. Each site is configured according to the profile you specify here when it is first accessed after the web server is booted. The user ID and password will be used by the PIA servlets themselves at runtime to log in to the application server to retrieve the profile. For applications on PeopleTools 8.44 and above, PeopleSoft predelivers the PTWEBSEVER user ID for the purpose of configuring PIA servlets at runtime and running the Performance Monitor Agents. You may have to unlock that user profile in certain application databases. If you have any problems logging in after starting the web server, refer to the application server domain logs.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

---

**Note.** If you are upgrading your application database to PeopleTools 8.44 and above, you must set up the PTWEBSEVER user ID. Go to PeopleTools, Security, User Profiles, User Profiles. Click Add a New Value, enter PTWEBSEVER for User ID, and click Add. Enter and confirm a password, and enter a description. Enter the role *PeopleTools Web Server* and then click Save.

---



Specifying the web profile, user ID, and password


17. Specify the root directory for the Report Repository (c:\psreports by default), and click Next. You can install to any location.

---

**Note.** For the Report Repository directory, specify the same directory that you specify as the Home Directory. Make sure that this directory is shared.


---

See “Setting Up Process Scheduler on Windows,” Setting Up the Process Scheduler to Transfer Reports and Logs to Report Repository.



Specifying the Report Repository location

18. Verify your selections on the summary window (click Back if you need to make any changes).  
Click Install to start the installation. An indicator appears showing the progress of the installation.



Verifying the installation information

19. Click Finish.

The default installation directory is <OAS\_HOME>\j2ee\<component>\application\<application>.

## Task 9A-1-2: Uninstalling the PeopleSoft Pure Internet Architecture from Oracle Application Server

To uninstall using the distributed configuration management control (dcmctl):

1. Change directory to <OAS\_HOME>\dcm\bin.
2. Run this command to view a list of component names:

```
dcmctl listcomponents
```

The component name is the name you entered when asked for Application Name in the task “Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server.” The documentation used *PeopleSoft* as an example.

3. Run the following command, substituting your application name for <PIA\_COMPONENT>:

```
dcmctl removecomponent -component <PIA_COMPONENT>
```

4. Run the following command:

```
dcmctl updateconfig
```

It is also possible to uninstall using the Application Server Control pages.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with Oracle Application Server 10g.”

---

## Task 9A-2: Installing the PeopleSoft Pure Internet Architecture on WebLogic in GUI Mode

This section describes how to install the PeopleSoft Pure Internet Architecture on WebLogic.

See “Installing Web Server Products,” Installing WebLogic.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with BEA WebLogic.”


---

**Note.** The installation will not proceed with an incorrect version of the WebLogic Server Service Pack. Make sure the correct service pack version (at least SP5) for WebLogic Server is properly installed prior to running this PeopleSoft Pure Internet Architecture install.

---

To install the PeopleSoft Pure Internet Architecture on WebLogic:


1. Go to <PS\_HOME>\setup\mpinternet.
2. Run setup.<OS>.
3. Click Next in the Welcome screen.
4. Enter the same <PS\_HOME> directory that you specified when running the PeopleTools Installer.
5. Choose BEA WebLogic Server and click Next.



Choosing the BEA WebLogic Server in the PeopleSoft Internet Architecture window

6. Specify the root directory where WebLogic is installed, and click Next.

**Note.** If you enter an incorrect path for WebLogic, you receive an error message “Detected web server version: no choices available.” Check that you have WebLogic installed, and in the designated directory.




Specifying the root directory in the PeopleSoft Internet Architecture window

7. Enter the login ID and password for the new domain to be created.

Click Next to continue. The next window asks you to choose whether to create a new WebLogic domain or to use an existing domain

8. If you select Create New WebLogic Domain, the installation process automatically generates a valid domain name in the domain name field.

If you attempt to enter an invalid domain name, you see a prompt asking you to enter a new domain name or choose an existing domain.



Specifying a new WebLogic domain

9. If you select Existing WebLogic Domain, specify the domain name and select one of these options:

---

**Note.** You see the option Existing WebLogic Domain only if there is already a domain in <PS\_HOME>.

---

#### **Install additional PeopleSoft site**

This option is relevant only to the PeopleSoft PORTAL web application, and does not modify or revert any other configuration settings. Select this option to install only the necessary files for defining an additional PeopleSoft site onto an existing WebLogic configuration. The new site will be accessed using its name in the URL. A site named “CRM” would be accessed using a URL similar to `http://mywebserver_machine/CRM`. To reset or re-create an existing PeopleSoft site, simply enter that site's name as the site to create. On your web server, a PeopleSoft site is comprised of the following directories within the PORTAL web application:

`<WEBLOGIC_DOMAIN>\applications\peoplesoft\PORTAL\<site>.*`

`<WEBLOGIC_DOMAIN>\applications\peoplesoft\PORTAL\WEB-INF\psftdocs\<site>.*`

#### **Redeploy PeopleSoft Internet Architecture**

This selection affects all of the PeopleSoft Pure Internet Architecture web applications installed to the local WebLogic domain. Select this

option to redeploy all of the class files and jar files that comprise web components of PeopleSoft Pure Internet Architecture. WebLogic Server configuration files, scripts and any existing PeopleSoft (PORTAL) sites are not overwritten, unless you specify an existing PeopleSoft site during this setup.

**Re-create WebLogic domain and redeploy PeopleSoft Internet Architecture**

This option affects WebLogic Server configuration and all of the PeopleSoft Pure Internet Architecture web applications installed to the local WebLogic domain. Select this option to completely remove an existing WebLogic domain and create the newly specified PeopleSoft site.

**Deploy additional PeopleSoft application extensions**


This option is solely for use with PeopleSoft applications. PeopleSoft application extensions are provided with certain PeopleSoft applications, and this option allows you to deploy those extensions. Consult the installation documentation for your PeopleSoft application to see if this option is appropriate. PeopleTools does not use application extensions.

---

**Warning!** Re-creating an existing domain will delete everything previously installed into that domain, including PeopleBooks. If you choose to re-create—instead of redeploying—a domain, you may first want to back up your PeopleBooks <docroot> directory (typically, htmldoc) at the top level of the PeopleSoft Online Library (PSOL) web site. You can then restore it after the PeopleSoft Pure Internet Architecture installation.


---

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.



Selecting an existing WebLogic domain


10. If there are application packages in the archives directory, you'll be asked whether you want to deploy them. (If you are using an existing domain, you'll only be prompted if you selected Deploy additional PeopleSoft extensions.)



Sample application package selection screen

11. Select the type of domain to create—single server, multi server, or distributed managed server.

**Note.** You must select "Multi Server Domain" if you plan to host PeopleBooks on the web server on which you are installing the PeopleSoft Pure Internet Architecture.



Choosing your domain type




There are three domain configuration options:

- *Single Server Domain*: This domain configuration contains one server named PIA, and the entire PeopleSoft enterprise application is deployed to it. This configuration is intended for single user or very small scale, nonproduction environments. This configuration is very similar to the WebLogic domain provided in PeopleTools 8.40 through 8.43.
- *Multi Server Domain*: This domain configuration contains seven unique server definitions, a WebLogic cluster, and the PeopleSoft Enterprise Application split across multiple servers. This configuration is intended for a production environment.
- *Distributed Managed Server*: This option is an extension of the *Multi Server Domain* selection and installs the necessary files to boot a managed server. This option requires a Multi Server installation to be performed to some other location, which will contain the configuration for this managed server.

12. Enter a PeopleSoft web site name; the default is ps.

**Warning!** The site name can include underscores ( \_ ), but an underscore cannot be followed by a numeric character or the string “newwin” (for example, my\_site\_3 or my\_newwin\_site).



Entering the PeopleSoft web site name

13. Specify your application server name, its JSL (Jolt Station Listener) port number, its HTTP and HTTPS port numbers, the Authentication Token Domain (optional), and click Next.

**Note.** For the AppServer name setting, enter the name of your application server. For the JSL port setting, enter the JSL port number you specified when setting up your application server. (The default value is 9000.)

See “Configuring the Application Server on <Windows or UNIX>.”

Specifying your application server name, your port numbers, and the authentication token domain

---

**Note.** The value you enter for Authentication Token Domain must match the value you specify when configuring your application server, as described earlier in this book. In addition, certain installation configurations require that you specify an authentication domain.

---

See Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation.

---

**Note.** If you enter a value for Authentication Token Domain, the URL to invoke PeopleSoft Pure Internet Architecture must include the network domain name in the URL. For example, if you do not enter an authentication domain, the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName/ps/signon.html`. If you do enter a value for the authentication domain (for example, `.myCompany.com`), the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName.myCompany.com/ps/signon.html`. In addition, if the web server for the database is using an http port other than the default port of 80, the URL must include the port number, for example `http://MachineName:8080/ps/signon.html` if there is no authentication domain, or `http://MachineName.myCompany.com:8080/ps/signon.html` if there is an authentication domain. The URL must also comply with the naming rules given earlier in this chapter.

---

See Understanding the PeopleSoft Pure Internet Architecture.

14. Enter the name of the web profile name in the database that will be used to configure this PeopleSoft web site.

This can be the name of either a predelivered one shown on the page, or one you intend to create yourself using PeopleTools, Web Profile Configuration, after logging in. Each site is configured according to the profile you specify here when it is first accessed after the web server is booted. The user ID and password will be used by the PIA servlets themselves at runtime to log in to the application server to retrieve the profile. For applications on PeopleTools 8.44 and above, PeopleSoft predelivers the PTWEBSERVER user ID for the purpose of configuring PIA servlets at runtime and running the Performance Monitor Agents.

You may have to unlock that user profile in certain application databases. If you have any problems logging in after starting the web server, refer to the application server domain logs.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

**Note.** If you are upgrading your application database to PeopleTools 8.44 and above, you must set up the PTWEBSEVER user ID. Go to PeopleTools, Security, User Profiles, User Profiles. Click Add a New Value, enter PTWEBSEVER for User ID, and click Add. Enter and confirm a password, and enter a description. Enter the role *PeopleTools Web Server* and then click Save.

Entering a web profile name

15. Specify the root directory for the Report Repository (c:\psreports by default), and click Next. You can install to any location.

**Note.** For the Report Repository directory, specify the same directory that you specify as the Home Directory. Make sure that this directory is shared.

See "Setting Up Process Scheduler on Windows," Setting Up the Process Scheduler to Transfer Reports and Logs to Report Repository.

16. Verify all of your selections (click Back if you need to make any changes), and click Install to begin the installation.

An indicator appears showing the progress of your installation.

17. Click Finish to complete the installation.

The default installation directory is <PS\_HOME>\webserv\<domain>\.

**Note.** If you are installing into an existing domain, you need to restart that domain.

---

## Task 9A-3: Installing the PeopleSoft Pure Internet Architecture on WebSphere

This section discusses:

- Prerequisites
- Installing the PeopleSoft Pure Internet Architecture on WebSphere
- Uninstalling the PeopleSoft Pure Internet Architecture from WebSphere

### Prerequisites

The information in this section applies to the installation of PeopleSoft Pure Internet Architecture on a WebSphere server.

---

**Important!** For more detailed WebSphere installation topics and Frequently Asked Questions (FAQs) refer to the PeopleSoft Customer Connection link <ftp://ftp.peoplesoft.com/outgoing/PTools/websphere/51/docs>.

---

Each WebSphere server runs one PeopleSoft Pure Internet Architecture application. If you need to install more than one PeopleSoft Pure Internet Architecture application on your WebSphere server, you must create a new server from the WebSphere Administration console and then deploy the PeopleSoft Pure Internet Architecture application to the new WebSphere server. Deploy PeopleSoft Pure Internet Architecture to WebSphere Base before clustering using Network Deployment.

You must select a unique name for each PeopleSoft Pure Internet Architecture application that you install on a WebSphere node. You cannot install two PeopleSoft Pure Internet Architecture applications with the same name to one WebSphere node.

---

**Note.** *On UNIX, install the PeopleSoft Pure Internet Architecture with a user who owns WebSphere, and who owns <PS\_HOME>.* Here are two examples: If WebSphere is owned by user “root” and group “system,” PeopleSoft Pure Internet Architecture must be installed with “root” and group “system.” If WebSphere is owned by user “wsadmin” and group “wsadmin,” then PeopleSoft Pure Internet Architecture must be installed with wsadmin/wsadmin as the user and group.

---

If PeopleSoft Pure Internet Architecture needs to be installed through WebSphere Network Deployment as an EAR file, refer to the Red Paper section of Customer Connection for instructions.

See “Clustering and High Availability for PeopleSoft 8.4” (PeopleSoft Customer Connection, Site Index, Red Papers).

Be sure the Default Application is uninstalled through the Admin console before installing PeopleSoft Pure Internet Architecture.

---

**Note.** You do not need to uninstall previous WebSphere PeopleSoft Pure Internet Architecture installs before continuing. However, if you do decide to uninstall any previous PeopleSoft Pure Internet Architecture installs, you cannot just delete <PS\_HOME>. Instead you need to follow the officially sanctioned uninstall procedure described in a later section.

---

## See Also

“Installing Web Server Products,” Installing WebSphere

Uninstalling the PeopleSoft Pure Internet Architecture from WebSphere

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with IBM WebSphere”

## Task 9A-3-1: Installing the PeopleSoft Pure Internet Architecture on WebSphere

Before installing the PeopleSoft Pure Internet Architecture on WebSphere, be sure you complete the requirements discussed previously.


See Prerequisites.

To install the PeopleSoft Pure Internet Architecture on WebSphere:

1. Start WebSphere on the server on which you plan to deploy PeopleSoft Pure Internet Architecture. From the bin directory under the WebSphere home directory, enter:

```
startServer.bat <server_name>
```


2. Go to <PS\_HOME>\setup\mpinternet.
3. Double-click on setup.<OS>.
4. Click Next in the Welcome screen.
5. Choose IBM WebSphere Application Server and click Next.



Choosing the IBM WebSphere Server in the PeopleSoft Internet Architecture window

6. Specify the WebSphere application server directory, and the cell name, node name, and server name of the WebSphere server. Then click Next.

**Note.** If the web server on which you're installing PeopleSoft Pure Internet Architecture is not up and running, you'll receive an error message that you need to start your web server.



Specifying the WebSphere application server directory

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*.


7. Choose whether to create a new WebSphere application (domain) or to use an existing application, and specify the name of the application.

**Note.** The name you specify for each PeopleSoft Enterprise Application must be unique for each WebSphere Node.


**Note.** You only see the option Existing WebSphere Application if there is already an application in <PS\_HOME>.

If you select Create New WebSphere Application, the install automatically generates a valid application name in the application name field. If you attempt to enter an invalid application name, you'll be prompted to enter a new application name or choose an existing application.

If you select Existing WebSphere Application, you can choose from a drop-down list of existing applications, and can select whether to install an additional PeopleSoft site, redeploy PeopleSoft Pure Internet Architecture, or deploy additional PeopleSoft application extensions.



Specifying a new WebSphere domain




Selecting an existing WebSphere domain

8. If there are application packages in the archives directory, you'll be asked whether you want to deploy them. (If you're using an existing domain, you'll only be prompted if you selected Deploy additional PeopleSoft extensions.)
9. Enter a PeopleSoft web site name; the default is ps.

---

**Warning!** The site name can include underscores ( \_ ), but an underscore cannot be followed by a numeric character or the string “newwin” (for example, my\_site\_3 or my\_newwin\_site).

---



Entering the PeopleSoft web site name

10. Specify your application server name, its JSL (Jolt Station Listener) port number, its HTTP and HTTPS port numbers, the authentication token domain, and click Next.

---

**Note.** For the AppServer name setting, enter the name of your application server. For the JSL port setting, enter the JSL port number you specified when setting up your application server. (The default value is 9000.)

---

See “Configuring the Application Server on Windows.”

---

**Note.** The HTTP/HTTPS port numbers are reset to those that you just specified when you restart your WebSphere server.

---



Specifying your application server name, your port numbers, and the authentication token domain

**Note.** The value you enter for Authentication Token Domain must match the value you specify for the authentication domain when configuring your application server, as described earlier in this book. In addition, certain installation configurations require that you specify an authentication domain.

See Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation.

**Note.** If you enter a value for the Authentication Token Domain, the URL to invoke PeopleSoft Pure Internet Architecture must include the network domain name in the URL. For example, if you do not enter an authentication domain, the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName/ps/signon.html`. If you do enter a value for the authentication domain (for example, `.myCompany.com`), the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName.myCompany.com/ps/signon.html`. In addition, if the web server for the database is using an HTTP port other than the default port of 9080, the URL must include the port number, for example `http://MachineName:8080/ps/signon.html` if there is no authentication domain, or `http://MachineName.myCompany.com:8080/ps/signon.html` if there is an authentication domain. The URL must also comply with the naming rules given earlier in this chapter.

See “Understanding the PeopleSoft Pure Internet Architecture.”

11. Enter the name of the web profile name in the database that will be used to configure this PeopleSoft web site.

This can be the name of either a predelivered one shown on the page, or one you intend to create yourself using PeopleTools, Web Profile Configuration, after logging in. Each site is configured according to the profile you specify here when it is first accessed after the web server is booted. The user ID and password will be used by the PIA servlets themselves at runtime to log in to the application server to retrieve the profile. For applications on PeopleTools 8.44 and above, PeopleSoft predelivers the PTWEBSEVER user ID for the purpose of configuring PIA servlets at runtime and running the Performance Monitor Agents. You may have to unlock that user profile in certain application databases. If you have any problems logging in after starting the web server, refer to the application server domain logs.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

**Note.** If you are upgrading your application database to PeopleTools 8.47 or later, you will need to set up the PTWEBSEVER user ID. Go to PeopleTools, Security, User Profiles, User Profiles, click Add a New Value, enter PTWEBSEVER for User ID, and click Add. Enter and confirm a password, and enter a description. Enter the role *PeopleTools Web Server* and then click Save.

Entering a web profile name

12. Specify the root directory for the Report Repository (c:\psreports by default), and click Next. You can install to any location.

**Note.** For the Report Repository directory, specify the same directory that you specify as the Home Directory. Make sure that this directory is shared.

See "Setting Up Process Scheduler on Windows," Setting Up the Process Scheduler to Transfer Reports and Logs to Report Repository.

13. Verify all of your selections (click Back if you need to make any changes), and click Next to begin the installation. An indicator shows the progress of your installation.
14. Click Finish to complete the installation.

The default installation directory is <PS\_HOME>\webserv\<cellname\_nodename\_servername>\<domain>

15. Stop the WebSphere server. From the bin directory under the WebSphere home directory, enter:

```
stopServer.bat <server_name>
```

where <server\_name> indicates where you have deployed PeopleSoft Pure Internet Architecture.

## Task 9A-3-2: Uninstalling the PeopleSoft Pure Internet Architecture from WebSphere

You cannot uninstall PeopleSoft Pure Internet Architecture simply by deleting <PS\_HOME>, without uninstalling it from WebSphere Administration Console. If you do so, the WebSphere registry becomes corrupt, and subsequent attempts to install PeopleSoft Pure Internet Architecture will fail. Instead, if necessary, you must uninstall PeopleSoft Pure Internet Architecture on WebSphere as described here:

To uninstall PeopleSoft Pure Internet Architecture on WebSphere:

1. Open WebSphere Administration Console at `http://<machine-name>:9090/admin`.

To invoke PeopleSoft Pure Internet Architecture on a non-default admin port, consult the section on WebSphere in PeopleBooks.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with IBM WebSphere.”

2. Log in as any user.
3. Choose Applications, Enterprise Applications.
4. Select the check boxes for the PeopleSoft Pure Internet Architecture applications you want to uninstall, and click Stop.
5. Select the check boxes for the PeopleSoft Pure Internet Architecture applications you want to uninstall, and click Uninstall.
6. Save your configuration.
7. Stop WebSphere server.
8. Delete the directory `<PS_HOME>\WebServ\<cellname>_<nodename>_<servername>`.

---

## Task 9A-4: Encrypting the Password (AIX Only)

If you installed either the WebLogic or WebSphere web server on an AIX operating system, you must encrypt the password manually.

1. Navigate to `<PS_HOME>/websrv/<domain_name>`, where the default value for `<domain_name>` is `peoplesoft`.
2. Run the following commands, substituting your User ID and its password for `<userid>` and `<password>`:

```
PSCipher.sh <userid>
PSCipher.sh <password>
```

The commands return encrypted values. Save these values.

3. Navigate to `<PS_HOME>/websrv/<domain_name>/applications/peoplesoft/PORTAL/WEB-INF/psftdocs/<site_name>`.

The default values for `<domain_name>` and `<site_name>`, respectively, are `peoplesoft` and `ps`. If you used other values when setting up the PeopleSoft Pure Internet Architecture, use those values here.

4. Open the file `configuration.properties` in a text editor.
5. Replace the values of `WebUserId` and `WebPassword` in this file with the encrypted values for `<userid>` and `<password>`, respectively, from step 2.

## Task 9A-5: Testing the PeopleSoft Pure Internet Architecture Installation

This section discusses:

- Starting and Stopping Oracle Application Server
- Starting and Stopping WebLogic
- Starting WebSphere
- Accessing the PeopleSoft Signon
- Updating Database Information
- Updating PeopleTools Options

**Note.** After installing the PeopleSoft Pure Internet Architecture, you should make sure that your configuration is functional. You can test this by signing on to PeopleSoft, navigating within the menu structure, and accessing pages. (Make sure the application server is configured and booted.)

### Task 9A-5-1: Starting and Stopping Oracle Application Server

There are several commands you can use to start and stop OAS and PIA, either separately or together.

Action	Command (full path)
Start PIA and other related processes	<OAS_HOME>\opmn\bin\opmnctl startall
Stop PIA and other related processes	<OAS_HOME>\opmn\bin\opmnctl stopall
View the status of the PIA installation on OAS	<OAS_HOME>\opmn\bin\opmnctl status
Start the OAS admin console	<OAS_HOME>\bin\emctl start em
Stop the OAS admin console	<OAS_HOME>\bin\emctl stop em
Start only PIA. In a single-component installation, <i>PIA_component</i> is the same as the application name entered during the installation of PIA on OAS.  In a multi-component installation, <i>PIA_component</i> is a combination of the application name entered during the installation and the specific OC4J component type. The default name for the PIA component in a multi-component installation is <i>PIA_PeopleSoft</i> .	<OAS_HOME>\opmn\bin\opmnctl.exe⇒ startproc ias-component=OC4J process⇒ type= <i>PIA_component</i>
Stop only PIA.	<OAS_HOME>\opmn\bin\opmnctl.exe⇒ stopproc ias-component=OC4J process⇒ type= <i>PIA_component</i>

## Task 9A-5-2: Starting and Stopping WebLogic

If you are using the WebLogic web server, you need to sign on to WebLogic. If you are using WebSphere instead, go on to the next procedure.

To start WebLogic:

1. To start BEA WebLogic Server as a Windows service, install the server as a windows service using the following command in your WebLogic domain directory:

*Single Server:*

```
installNTservicePIA.cmd
```

*Multi Server or Distributed Server:*

```
installNTservice.cmd <ServerName>
```

The Windows service name will be *WebLogicDomain-WebLogicServer*. For example, to install server PIA as an NT service in a domain named peoplesoft, run `installNTservice.cmd PIA` and you will see "peoplesoft-PIA" as a service.

2. To start BEA WebLogic Server as a foreground process, execute the following command in your WebLogic domain directory (the default directory is `<PS_HOME>\webserve\<domain_name>`):

*Single Server:*

```
startPIS.cmd (on Windows)
```

```
startPIA.sh (on UNIX)
```

*Multi Server or Distributed Server:*

```
startWebLogicAdmin.cmd (on Windows)
```

```
startWebLogicAdmin.sh (on UNIX)
```

and then

```
startManagedWebLogic.cmd <ManagedServerName> (on Windows)
```

```
startManagedWebLogic.sh <ManagedServerName> (on UNIX)
```

3. To stop the server, execute the following command in your WebLogic domain directory:

*Single Server:*

```
stopPIA.cmd (on Windows)
```

```
stopPIA.sh (on UNIX)
```

*Multi Server or Distributed Server:*

```
stopWebLogic.cmd [-url t3://ServerHostName:port | <ManagedServerName>] (on⇒  
Windows)
```

```
stopWebLogic.sh [-url t3://ServerHostName:port | <ManagedServerName>] (on UNIX)
```

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

## Task 9A-5-3: Starting WebSphere

If you are using the WebSphere web server, you need to sign on to WebSphere. If you are using WebLogic instead, you should have used the previous procedure.

To start WebSphere:

1. Change directories to the folder in which WebSphere is installed—the bin directory under the WebSphere home directory.

2. Enter the command

```
startServer.bat <server_name>
```

where <server\_name> indicates where you have deployed PeopleSoft Pure Internet Architecture.

3. To stop the server, change directories to the folder in which WebSphere is installed and enter the command

```
stopserver <server_name>
```

where <server\_name> indicates where you have deployed PeopleSoft Pure Internet Architecture.

## Task 9A-5-4: Accessing the PeopleSoft Signon

To access the PeopleSoft signon:

1. Open your web browser.
2. Enter the name of the site you want to access—for example (the default value for <site\_name> is *ps*):


```
http://<machine_name>:<http_port>/<site_name>/signon.html
```

---

**Note.** PeopleSoft Pure Internet Architecture installed on WebSphere server listens at the HTTP/HTTPS ports specified during the PeopleSoft Pure Internet Architecture install. Invoke PeopleSoft Pure Internet Architecture through a browser by using the specified HTTP or HTTPS ports—that is, `http://<WebSphere_machine_name>:<server_port>/<site_name>/signon.html` (if AuthTokenDomain is not specified ) or `http://<WebSphere_machine_name.mycompany.com>:<server_port>/<site_name>/signon.html` (if you specified .mycompany.com as the AuthTokenDomain).

---

This will take you to the signon screen corresponding to your browser's language preference.



Oracle PeopleSoft Enterprise Sign in window

**Note.** If you do not see the signon screen, check that you supplied all the correct variables and that your application server and the database server are running.

3. Sign in to the PeopleSoft system by entering a valid user ID and password.

Different applications use different default user IDs and passwords. For instance, for HRMS applications you enter PS for the user ID and the password. For Financials applications, you enter VP1 for the user ID and the password. Your application-specific install instructions contain any custom/delivered user IDs that you should use for the demonstration environment.

**Note.** The user ID and password are case sensitive. You need to enter the user ID and password using UPPERCASE.

## Task 9A-5-5: Updating Database Information

The database information updated in this procedure is used by the PeopleSoft software update tools to identify your PeopleSoft database when searching for updates. These steps should be followed for all additional databases that you create to enable the accurate identification of your databases.

1. Sign on to your PeopleSoft database.
2. Navigate to PeopleTools, Utilities, Administration, PeopleTools Options.
3. Specify long and short names for your environment. For example:
  - Environment Long Name — Customer HR Demo Database

- Environment Short Name — HR Demo DB
4. Select a system type from the drop-down list. For example, Demo Database.
  5. Save your changes.

## Task 9A-5-6: Updating PeopleTools Options

You can set the following options on the PeopleTools Options page:

- Multi-Currency — Check this box if you plan to use currency conversion.  
*See Enterprise PeopleTools 8.48 PeopleBook: Global Technology, “Controlling Currency Display Format.”*
- Base Time Zone — Check this box to set the base time zone for your PeopleTools database.  
*See Enterprise PeopleTools 8.48 PeopleBook: Global Technology “Setting and Maintaining Time Zones.”*
- Data Field Length Checking Flag — Check this box if you are using a Japanese EBCDIC (DB2 MBCS) or Japanese Shift-JIS (MBCS) database.  
*See Enterprise PeopleTools 8.48 PeopleBook: Global Technology, “Selecting and Configuring Character Sets and Language Input and Output.”*
- Sort Order Option — If you specified a non-binary sort order for your database, choose the Sort Order Option that most closely approximates your database sort order.  
*See Enterprise PeopleTools 8.48 PeopleBook: Global Technology, “Sorting in PeopleTools.”*



## CHAPTER 9B

# Setting Up the PeopleSoft Pure Internet Architecture in Console Mode

This chapter discusses:

- Understanding PeopleSoft Pure Internet Architecture
- Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation
- Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server in Console Mode
- Installing the PeopleSoft Pure Internet Architecture on WebLogic in Console Mode
- Installing the PeopleSoft Pure Internet Architecture on WebSphere in Console Mode
- Encrypting the Password (AIX Only)
- Testing the PeopleSoft Pure Internet Architecture Installation

---

## Understanding PeopleSoft Pure Internet Architecture

This chapter explains how to install and configure the components of the PeopleSoft Pure Internet Architecture in console mode. It includes instructions for installing the PeopleSoft files on Oracle Application Server (OAS), WebLogic, and WebSphere. Only complete the instructions for the web server product that you installed.

---

**Note.** The console mode installation is typically used on UNIX platforms.

---

See “Installing Web Server Products.”

The setup program for the PeopleSoft Pure Internet Architecture is installed to the web server machine when you run the PeopleSoft Installer and select the PeopleSoft Web Server option.

See “Using the PeopleSoft Installer.”

PeopleSoft only supports customer installations that use the version of the web servers packaged with PeopleTools. *You must install the web server before you install the PeopleSoft Pure Internet Architecture.* Before you install the PeopleSoft Pure Internet Architecture, you must also have configured an application server, as described in the previous chapter.

Before performing the steps in this chapter, verify that Sun’s international version of JRE version 1.4.1 or higher is properly installed on the system and its path is in the system’s environment variable PATH.

If your web server is on a different machine than your application server, you need to make sure you have JRE installed on your web server to run the PIA installation.

The initial PIA setup automatically creates the default PeopleSoft site named *ps*. In subsequent PIA setups, change the site name from *ps* to a unique value. We recommend using the database name. This is handy for easy identification and ensures that the database web server files are installed in a unique web site.

The URL that you use to invoke PIA must conform to ASN.1 specifications. That is, it may contain only alphanumeric characters, dots ("."), or dashes ("-"). The URL must not begin or end with a dot or dash, or contain consecutive dots (".."). If the URL includes more than one portion, separated by dots, do not use a number to begin a segment if the other segments contain letters. For example, "mycompany.second.country.com" is correct, but "mycompany.2nd.country.com" is wrong.

---

**Note.** If you want to connect between multiple application databases, you need to implement single signon.

---



---

**Note.** If the PeopleSoft Pure Internet Architecture installation encounters an error, it will indicate which log files to refer to.

---

See “Installing Web Server Products.”

---

**Note.** The machine on which you run the PeopleSoft Pure Internet Architecture install must be running in 256 *color mode*. This is not necessary for UNIX or console mode.

---



---

**Note.** If you encounter the error message “No Matching JVM,” you need to specify the location of the Java Runtime Environment (JRE) to the installer using the `-is:javahome` command line parameter; for example: `/PA84206/setup.<OS> -is:javaconsole -console -is:tempdir<tempdir> -is:javahome <jredir>`.

---

The PeopleSoft Pure Internet Architecture installation includes the following products:

- *PeopleSoft Pure Internet Architecture*. This product is the centerpiece of the PeopleSoft architecture that enables users to work on a machine with only a supported browser installed. This option installs the servlets required for deploying PeopleSoft Applications and for the PeopleSoft Portal. The portal packs and Enterprise Portal have their own installation instructions, which are available on Customer Connection. For an overview of the various types of portals, consult the following.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

- *PeopleSoft Report Repository*. This product works in conjunction with Process Scheduler to allow report distribution over the web.
- *PeopleSoft Integration Gateway*. This product is the entry and exit point for all messages to and from the Integration Broker. Its Java-based Connector architecture allows asynchronous and synchronous messages to be sent over a variety of standard protocols, many that are delivered at install, or through custom connectors.
- *PeopleSoft CTI Console*. This product works in conjunction with CTI vendor software to enable call center agents to take advantage of browser based teleset management and automatic population of application pages with relevant data associated with incoming calls, such as customer or case details.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft MultiChannel Framework*.

- *PeopleSoft Sync Server Gateway*. The Sync Server is a specialized application server optimized for concurrent multi-user synchronization processing in support of PeopleTools Mobile Agent. The web server-based Sync Gateway routes synchronization requests and messages to and from the appropriate Sync Server.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Mobile Agent*.

- *Environment Management Hub*. The Environment Management hub is a web application that is installed with the PeopleSoft Pure Internet Architecture and portal. It is started along with the rest of the web applications when the user boots the web server. You cannot start the Environment Management Hub on a server that is configured to run HTTPS; in other words, if you plan to run Environment Management, your PIA server needs to be configured in HTTP mode.

See *Enterprise PeopleTools 8.48 PeopleBook: Software Updates*.

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: Security Administration*

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

---

# Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation

You have the option to specify an authentication domain when you install the PeopleSoft Pure Internet Architecture on OAS, WebLogic, or WebSphere.

---

**Note.** The authentication domain was referred to as the Authentication Token Domain in previous releases, and that term is still seen in the software.

---

When an authentication domain is specified during the PeopleSoft Pure Internet Architecture install, that value gets used as the Cookie domain in the web server configuration. The main requirements when setting a cookie domain are:

- The host must have a fully qualified domain name (FQDN). The requirement that you must have a domain name does not imply that you must have a DNS, but you do need some type of naming service such as DNS or some managed `../etc/hosts` file that contains a list of the servers with their domain name.
- The cookie domain value being set must begin with a dot (`.ps.com` is valid, `ps.com` is NOT valid).
- The cookie domain value being set must contain at least 1 embedded dot (`.ps.com` is valid, `.corp.ps.com` is valid, `.com` is NOT valid).
- The cookie domain value can only be a single domain name. It cannot be a delimiter-separated list of domains.

By default, the browser only sends cookies back to the machine that set the cookie. So if web server `crm.yourdomain.com` sets a cookie, the browser will only send it back there. You can make the browser send the single signon cookie to all servers at `yourdomain.com` by typing your domain name in the Authentication Token Domain list box of web server `crm`.

Specifying the authentication domain may be necessary in certain cases. For example, if you plan to use the PeopleSoft portal technology, be sure to read the supporting documentation to determine whether setting the authentication domain is required for correct operation.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*, “Configuring the Portal Environment.”

Specify an authentication domain if you plan to run a REN Server. REN Servers are required for PeopleSoft MultiChannel Framework, Reporting, and some PeopleSoft CRM applications supported by PeopleSoft MultiChannel Framework.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft MultiChannel Framework*.

Specify an authentication domain if you plan to use Business Objects Enterprise.

See “Installing and Configuring Software for Crystal Reports,” Installing BusinessObjects Enterprise XI.

---

## Task 9B-1: Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server in Console Mode

This section discusses:

- Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server
- Uninstalling the PeopleSoft Pure Internet Architecture from Oracle Application Server

---

**Note.** The installation of the PeopleSoft Pure Internet Architecture on Oracle Application Server includes the PeopleSoft Provider. Use this to configure PeopleSoft portlets on Oracle Portal pages.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*, “Deploying PeopleSoft Portlets on Oracle Portal Pages.”

### Task 9B-1-1: Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server

Before you begin the installation of the PeopleSoft Pure Internet Architecture (PIA) on Oracle Application Server (OAS), you must have installed the OAS software as described previously.

See “Installing Web Server Products,” Installing Oracle Application Server.

When installing PIA on OAS, you must work with a local copy of the PIA installation software; you cannot install remotely. If you are doing the installation on a machine other than the one on which you installed PeopleTools, copy the <PS\_HOME>/setup/mpinternet directory to the local machine.

To install the PeopleSoft Pure Internet Architecture on Oracle Application Server:

1. Start opmn process if necessary.

To check the status of the opmn process run this command:

```
<OAS_HOME>/opmn/bin/opmnctl status
```

If you get the response, “Unable to connect to opmn”, start it by running this command:

```
<OAS_HOME>/opmn/bin/opmnctl start
```

See “Installing Web Server Products,” Installing Oracle Application Server.

2. Start dcm-daemon process if necessary.

To check the status of dcm-daemon run this command:

```
<OAS_HOME>/opmn/bin/opmnctl status
```

If the dcm-daemon’s status is not “Alive”, start it by running this command:

```
<OAS_HOME>/opmn/bin/opmnctl startproc ias-component=dcm-daemon
```

3. Change directory to `<PS_HOME>/setup/mpinternet` and run one of these commands:

```
setup.<OS> -console
```

or

```
<JAVA_HOME>/bin/java -cp setup.jar run -console
```

where `<JAVA_HOME>` is the directory where the JRE software is installed. The default is `<PS_HOME>/jre`.

See “Using the PeopleSoft Installer,” Prerequisites.

A welcome message appears.

4. Select Enter to continue.
5. Enter the `<PS_HOME>` directory, where you installed the PeopleSoft software.
6. At the prompt:

```
[X] 1 - Oracle Application Server
[ ] 2 - BEA WebLogic Server
[ ] 3 - IBM WebSphere Application Server
```

Press ENTER to select the default selection *1*, for the Oracle Application Server.

7. At the prompt:

```
Select an Oracle Application Server home:
Directory Name: [/opt/OraHome_1]
```

Enter the directory where you installed OAS, or press ENTER to accept the default.

8. Enter an application name for this web server.
9. Select the type of server you want to install, and press ENTER to continue:

```
Select the server install type:
```

```
[X] 1 - Single Component Server
[ ] 2 - Multi Component Server
```

The *Single Component Server* option creates one OC4J component to hold all the PeopleSoft web applications. The Application Name you enter in the next step is used for the new component’s name.

The *Multi Component Server* option splits the PeopleSoft web application into three OC4J components—`PIA_<application_name>`, `PSOL_<application_name>`, and `PSEMFHUB_<application_name>`. Each OC4J component has its own JVM so the multi component option is better suited for installations needing higher performance or reliability. If you are not sure which to pick, choose Single.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with Oracle Application Server 10g.”

10. If you enter a new name, for example, `peoplesoft`, press ENTER.  
Skip the next two steps, and continue with step 13.
11. If the name you enter belongs to an OAS web application that already exists, for example, `jwong_single`, select one of the options below and press ENTER to continue:

```
The PeopleSoft application "jwong_single" already exists.
```

Select from the following:

- [X] 1 - Create an additional site in the existing application
- [ ] 2 - Deploy additional PeopleSoft application extensions
- [ ] 3 - Go back to enter a new application name

---

**Note.** To redeploy PIA on OAS, you must remove the OC4J component(s) and perform a fresh installation of PIA. Use Application Server Control or `demctl` commands to remove the OC4J component(s). Note that any customizations done after the PIA install needs to be done again.

---

- *Create an additional site in the existing application:* Select this option to install only the necessary files for defining an additional PeopleSoft site on the existing OAS web server configuration.
  - *Deploy additional PeopleSoft application extensions:* This option is solely for use with PeopleSoft product applications. PeopleSoft application extensions are provided with certain PeopleSoft applications, and this option allow you to deploy those extensions. Consult the installation documentation for your PeopleSoft application to see whether this option is appropriate. PeopleTools does not use application extensions.
  - *Go back to enter a new application name:* Select this option to return to the previous screen.
12. If you select the option Deploy additional PeopleSoft application extension, select the application packages you want to deploy:

```
[X] 1 -EMP PeopleSoft Activity Based Mgmt
```

13. Enter a web site name; the default is ps.
14. Specify the application server name, its JSL (Jolt Station Listener) port number, its HTTP and HTTPS port numbers, and the authentication token domain (optional):

Enter port numbers and summaries.

```
AppServer name: [<App Server Machine Name>]
JSL Port: [9000]
HTTP Port: [8000]
HTTPS Port: [4430]
Authentication Token Domain: (optional) []
```

**AppServer name** Enter the name of your application server machine.

**JSL Port** Enter the JSL port number you specified when setting up the application server (the default is 9000).

**HTTP/HTTPS** The default HTTP/HTTPS ports of the Oracle HTTP Server (OHS) are 80/443 for Windows and 7777/4443 for UNIX/Linux. However, you should enter different HTTP/HTTPS port values at this point for the PIA installation. Please use any unused port other than 80/443 for Windows and 7777/4443 for UNIX/Linux. The PIA installation may fail or may not work properly if you enter the same HTTP/HTTPS ports for the PIA installation as the default OHS ports.

To access PIA, specify a URL with either the default OHS port values, or the port values you enter here for PIA. For example, `http://<machine_name>:<port_number>/<site_name>/signon.html`.

For Multi Component Server, the HTTP/HTTPS ports that you enter here correspond to the OC4J component `PIA_<application_name>`.

**Authentication Token Domain**

The value you enter for Authentication Token Domain must match the value you specify for the authentication domain when configuring your application server. In addition, certain installation configurations require that you specify an authentication domain.

See Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation.

---

**Note.** If you enter a value for the Authentication Token Domain, the URL to invoke PeopleSoft Pure Internet Architecture must include the network domain name in the URL. For example, if you do not enter an authentication domain, the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName/ps/signon.html`. If you do enter a value for authentication domain (for example, `.myCompany.com`), the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName.myCompany.com/ps/signon.html`. In addition, if the web server for the database is using an http port other than the default port of 80, the URL must include the port number, for example `http://MachineName:8080/ps/signon.html` if there is no authentication domain, or `http://MachineName.myCompany.com:8080/ps/signon.html` if there is an authentication domain. The URL must also comply with the naming rules given earlier in this chapter.

---

See Understanding the PeopleSoft Pure Internet Architecture

15. Enter the name of the web profile in the database that will be used to configure this PeopleSoft web site. This can either be the predelivered name as shown on the page, or one that you intend to create yourself using PeopleTools, Web Profile Configuration after logging in. Each site is configured according to the profile you specify here when it is first accessed after the web server is booted. The user ID and password will be used by the PIA servlets themselves at runtime to log in to the application server to retrieve the profile. For applications on PeopleTools 8.44 and above, PeopleSoft predelivers the PTWEBSEVER user ID for the purpose of configuring PIA servlets at runtime and running the Performance Monitor Agents. You may have to unlock that user profile in certain application databases. If you have any problems logging in after starting the web server, refer to the application server domain logs.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

---

**Note.** If you are upgrading your application database to PeopleTools 8.44 and above, you must set up the PTWEBSEVER user ID. Go to PeopleTools, Security, User Profiles, User Profiles. Click Add a New Value, enter PTWEBSEVER for User ID, and click Add. Enter and confirm a password, and enter a description. Enter the role PeopleTools Web Server and then click Save.

---

16. Specify the root directory for the Report Repository (`c:\psreports` by default). You can install to any location.

---

**Note.** For the Report Repository directory, specify the same directory that you specify as the Home Directory. Make sure that this directory is shared. See "Setting Up Process Scheduler," Setting Up the Process Scheduler to Transfer Reports and Logs to Report Repository.

---

17. Verify your selection and press ENTER to start the installation.  
You see an indicator showing the progress of the installation.
18. When the installation is complete, exit from the console window.

The default installation directory is `<OAS_HOME>/j2ee/<component>/applications/<application>`.

## Task 9B-1-2: Uninstalling the PeopleSoft Pure Internet Architecture from Oracle Application Server

To uninstall using the distributed configuration management control (dcmctl):

1. Change directory to <OAS\_HOME>/dcm/bin.
2. Run this command to view a list of component names:

```
dcmctl listcomponents
```

The component name is the name you entered when asked for Application Name in the task “Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server.” The documentation used *PeopleSoft* as an example.

3. Run the following command, substituting your application name for <PIA\_COMPONENT>:

```
dcmctl removecomponent -component <PIA_COMPONENT>
```

4. Run the following command:

```
dcmctl updateconfig
```

It is also possible to uninstall using the Application Server Control pages.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with Oracle Application Server 10g.”

---

## Task 9B-2: Installing the PeopleSoft Pure Internet Architecture on WebLogic in Console Mode

This section describes how to install the PeopleSoft Pure Internet Architecture on WebLogic.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with BEA WebLogic.”

---

**Note.** The installation will not proceed with an incorrect version of the WebLogic Server Service Pack. Make sure the correct service pack version (at least SP5) for WebLogic Server is properly installed prior to running this PeopleSoft Pure Internet Architecture installation.

---

To install the PeopleSoft Pure Internet Architecture on WebLogic:

1. Change directory to <PS\_HOME>/setup/mpinternet and run one of these commands:

```
setup.<OS> -console
```

or

```
<JAVA_HOME>/bin/java -cp setup.jar run -console
```

where <JAVA\_HOME> is the directory where the JRE software is installed. The default is <PS\_HOME>/jre.

See “Using the PeopleSoft Installer,” Prerequisites.

A welcome message appears.

```
Welcome to the InstallShield Wizard for PeopleSoft Internet Architecture.
```



Using the InstallShield Wizard you will install PeopleSoft Internet⇒  
Architecture on your computer.

Version: 8.48

If installing onto a BEA WebLogic Server, make sure to shutdown any running⇒  
web servers to avoid web server configuration.

2. Select Enter to continue.
3. Choose the directory where you installed PeopleSoft, or <PS\_HOME>.
4. At the prompt

```
[X] 1 - Oracle Application Server
[ ] 2 - BEA WebLogic Server
[ ] 3 - IBM WebSphere Application Server
```

Enter 2 to select the BEA WebLogic Server.

5. At the prompt

Select the web server root directory:

Please specify a directory name or press Enter [/opt/bea] /data4/syb/bea

Enter the top-level directory where WebLogic is installed. Press ENTER to continue.

---

**Note.** You will get an error message if you specify a directory that does not contain WebLogic, or that contains an incorrect WebLogic version.

---

6. Enter the administrator login and password for your WebLogic domain. Press ENTER to continue.

Please enter the administrator login and password for WebLogic domain.

Login ID:

[system]

Password:

[password]

Re-type Password:

[password]

At the next prompt you must choose whether to create a new WebLogic domain or to use an existing domain.

7. If you select Create New WebLogic domain, the installation process automatically generates a valid domain name in the domain name field.  
  
If you attempt to enter an invalid domain name, you see a prompt asking you to enter a new domain name or choose an existing domain.
8. If you select Existing WebLogic Domain, specify the domain name and select one of these options:

---

**Note.** You only see the option Existing WebLogic Domain if there is already a domain in <PS\_HOME>.

---

**Install additional  
PeopleSoft site**

This option is relevant only to the PeopleSoft PORTAL web application, and does not modify or revert any other configuration settings. Select this option to install only the necessary files for defining an additional PeopleSoft site onto an existing WebLogic configuration. The new site will be accessed using its name in the URL. A site named “CRM” would be accessed using a URL similar to `http://<mywebserver_machine>/CRM`. To reset or re-create an existing PeopleSoft site, simply enter that site's name as the site to create. On your web server, a PeopleSoft site is comprised of the following directories within the PORTAL web application:

`<WEBLOGIC_DOMAIN>/applications/peoplesoft/PORTAL/site/*`

`<WEBLOGIC_DOMAIN>/applications/peoplesoft/PORTAL/WEB-INF/psftdocs/site/*`

**Redeploy PeopleSoft  
Internet Architecture**

This selection affects all of the PeopleSoft Pure Internet Architecture web applications installed to the local WebLogic domain. Select this option to redeploy all of the class files and jar files that comprise web components of PeopleSoft Pure Internet Architecture. WebLogic Server configuration files, scripts and any existing PeopleSoft (PORTAL) sites are not overwritten, unless you specify an existing PeopleSoft site during this setup.

**Re-create WebLogic  
domain and redeploy  
PeopleSoft Internet  
Architecture**

This option affects WebLogic Server configuration and all of the PeopleSoft Pure Internet Architecture web applications installed to the local WebLogic domain. Select this option to completely remove an existing WebLogic domain and create the newly specified PeopleSoft site.

**Deploy additional  
PeopleSoft application  
extensions**

This option is solely for use with PeopleSoft applications. PeopleSoft application extensions are provided with certain PeopleSoft applications, and this option allows you to deploy those extensions. Consult the installation documentation for your PeopleSoft application to see if this option is appropriate. PeopleTools does not use application extensions.

---

**Warning!** Re-creating an existing domain will delete everything previously installed into that domain, including PeopleBooks. If you choose to re-create—instead of redeploying—a domain, you may first want to back up your PeopleBooks *docroot* directory (typically, *html*doc) below the PSOL directory. You can then restore it after the PeopleSoft Pure Internet Architecture installation.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

9. Specify the name of the domain.
10. If there are application packages in the archives directory, select whether you want to deploy them. (If you are using an existing domain, you see a prompt for this only if you elected to Deploy Additional PeopleSoft Extensions.)
11. Select the type of domain to create—single server, multi server, or distributed managed server.

---

**Note.** You must select "Multi Server Domain" if you plan to host PeopleBooks on the web server on which you are installing the PeopleSoft Pure Internet Architecture.

---

Please select the configuration to install.

```
[X] 1 - Single Server Domain
[ ] 2 - Multi Server Domain
[ ] 3 - Distributed Managed Server
```

There are three domain configuration options:

- *Single Server Domain*: This domain configuration contains one server, named PeopleSoft Pure Internet Architecture and the entire PeopleSoft enterprise application is deployed to it. This configuration is intended for single user or very small scale, nonproduction environments. This configuration is very similar to the WebLogic domain provided in PeopleTools 8.40 through 8.43.
- *Multi Server Domain*: This domain configuration is contains seven unique server definitions, a WebLogic cluster, and the PeopleSoft Enterprise Application split across multiple servers. This configuration is the intended for a production environment.
- *Distributed Managed Server*: This option is an extension of the *Multi Server Domain* selection and installs the necessary files to boot a managed server. This option requires a Multi Server installation to be performed to some other location, which will contain the configuration for this managed server.

12. Enter a PeopleSoft web site name; the default is ps.

---

**Warning!** The site name can include underscores ( \_ ), but an underscore cannot be followed by a numeric character or the string “newwin” (for example, my\_site\_3 or my\_newwin\_site).

---

13. Specify your application server name, its JSL (Jolt Station Listener) port number, its HTTP and HTTPS port numbers, the Authentication Token Domain (optional).

Enter port numbers and summaries.

AppServer name:

[APPSRVNAME]

JSL Port:

[9000]

HTTP Port:

[80]

HTTPS Port:

[443]

Authentication Token Domain:(optional)

---

**Note.** For the AppServer name setting, enter the name of your application server. For the JSL port setting, enter the JSL port number you specified when setting up your application server. (The default value is 9000.)

---

See “Configuring the Application Server on <Windows or UNIX>.”

---

**Note.** The value you enter for the Authentication Token Domain must match the value you specify when configuring your application server, as described earlier in this book. In addition, certain installation configurations require that you specify an authentication domain.

---

See Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation.

---

**Note.** If you enter a value for the Authentication Token Domain, the URL to invoke PeopleSoft Pure Internet Architecture must include the network domain name in the URL. For example, if you do not enter an authentication domain, the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName/ps/signon.html`. If you do enter a value for authentication domain (for example, `.myCompany.com`), the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName.myCompany.com/ps/signon.html`. In addition, if the web server for the database is using an http port other than the default port of 80, the URL must include the port number, for example `http://MachineName:8080/ps/signon.html` if there is no authentication domain, or `http://MachineName.myCompany.com:8080/ps/signon.html` if there is an authentication domain. The URL must also comply with the naming rules given earlier in this chapter.

---

See “Understanding the PeopleSoft Pure Internet Architecture.”

14. Enter the name of the web profile name in the database that will be used to configure this PeopleSoft web site.

This can be the name of either a predelivered one shown on the page, or one you intend to create yourself using PeopleTools, Web Profile Configuration after logging in. Each site is configured according to the profile you specify here when it is first accessed after the web server is booted. The user ID and password will be used by the PIA servlets themselves at runtime to log in to the application server to retrieve the profile. For applications on PeopleTools 8.44 and above, PeopleSoft predelivers the PTWEBSEVER user ID for the purpose of configuring PIA servlets at runtime and running the Performance Monitor Agents. You may have to unlock that user profile in certain application databases. If you have any problems logging in after starting the web server, refer to the application server domain logs.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

---

**Note.** If you are upgrading your application database to PeopleTools 8.44 and above, you must set up the PTWEBSEVER user ID. Go to PeopleTools, Security, User Profiles, User Profiles. Click Add a New Value, enter PTWEBSEVER for User ID, and click Add. Enter and confirm a password, and enter a description. Enter the role *PeopleTools Web Server* and then click Save.

---

15. Specify the root directory for the Report Repository (`/opt/psreports` by default). You can install to any location.

---

**Note.** For the Report Repository directory, specify the same directory that you specify as the Home Directory. Make sure that this directory is shared.

---

See "Setting Up Process Scheduler," Setting Up the Process Scheduler to Transfer Reports and Logs to Report Repository.

16. Verify all of your selections and press Enter to begin the installation.

You see a progress indicator showing the progress of your installation.

17. When the installation is complete, exit from the console window.

The default installation directory is `<PS_HOME>/webserv/<domain>/`, where *<domain>* is the web server domain (peoplesoft by default).

---

## Task 9B-3: Installing the PeopleSoft Pure Internet Architecture on WebSphere in Console Mode

This section discusses:

- Prerequisites
- Installing the PeopleSoft Pure Internet Architecture on WebSphere
- Uninstalling the PeopleSoft Pure Internet Architecture from WebSphere

### Prerequisites

The information in this section applies to the installation of PeopleSoft Pure Internet Architecture on a WebSphere server.

---

**Important!** For more detailed WebSphere installation topics and Frequently Asked Questions (FAQs) refer to the PeopleSoft Customer Connection link <ftp://ftp.peoplesoft.com/outgoing/PTools/websphere/51/docs>.

---

Each WebSphere server runs one PeopleSoft Pure Internet Architecture application. If you need to install more than one PeopleSoft Pure Internet Architecture application on your WebSphere server, you must create a new server from the WebSphere Administration console and then deploy the PeopleSoft Pure Internet Architecture application to the new WebSphere server. Deploy PeopleSoft Pure Internet Architecture to WebSphere Base before clustering using Network Deployment.

You must select a unique name for each PeopleSoft Pure Internet Architecture application that you install on a WebSphere node. You cannot install two PeopleSoft Pure Internet Architecture applications with the same name to one WebSphere node.

---

**Note.** *On UNIX, install the PeopleSoft Pure Internet Architecture with a user who owns WebSphere, and who owns <PS\_HOME>.* Here are two examples: If WebSphere is owned by user “root” and group “system,” PeopleSoft Pure Internet Architecture must be installed with “root” and group “system.” If WebSphere is owned by user “wsadmin” and group “wsadmin,” then PeopleSoft Pure Internet Architecture must be installed with wsadmin/wsadmin as the user and group.

---

If PeopleSoft Pure Internet Architecture needs to be installed through WebSphere Network Deployment as an EAR file, refer to the Red Paper section of Customer Connection for instructions.

See “Clustering and High Availability for PeopleSoft 8.4” (PeopleSoft Customer Connection, Site Index, Red Papers).

Be sure the Default Application is uninstalled through the Admin console before installing PeopleSoft Pure Internet Architecture.

---

**Note.** You do not need to uninstall previous WebSphere PeopleSoft Pure Internet Architecture installs before continuing. However, if you do decide to uninstall any previous PeopleSoft Pure Internet Architecture installs, you cannot just delete <PS\_HOME>. Instead you need to follow the officially sanctioned uninstall procedure described in a later section.

---

## See Also

“Installing Web Server Products,” Installing WebSphere

Uninstalling the PeopleSoft Pure Internet Architecture from WebSphere

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with IBM WebSphere”

## Task 9B-3-1: Installing the PeopleSoft Pure Internet Architecture on WebSphere

Before installing the PeopleSoft Pure Internet Architecture on WebSphere, be sure you complete the requirements discussed previously.

See Prerequisites.

To install the PeopleSoft Pure Internet Architecture on WebSphere:

1. Start WebSphere on the server on which you plan to deploy PeopleSoft Pure Internet Architecture. From the bin directory under the WebSphere home directory, enter:

```
startServer.sh <server_name>
```

2. In your shell prompt under the <PS\_HOME>/setup/mpinternet directory, type

```
java -cp setup.jar run -console
```

or

```
setup.<OS>
```

You see the following:

```
Welcome to the InstallShield Wizard for PeopleSoft Internet Architecture.
```

```
Using the InstallShield Wizard you will install PeopleSoft Internet⇒
```

```
Architecture on your computer.
```

```
Please be sure to shutdown any running web servers at this time to avoid data⇒  
corruption.
```

3. Select Enter to continue.
4. Choose the directory where you installed PeopleSoft, or <PS\_HOME>.
5. At the prompt

```
[X] 1 - Oracle Application Server
```

```
[ ] 2 - BEA WebLogic Server
```

```
[ ] 3 - IBM WebSphere Application Server
```

Enter 3, to select the IBM WebSphere Application Server.

6. At the following prompt

```
Select the WebSphere Application Server directory:
```

```
Directory Name:
```

```
Please specify a directory name or press Enter [C:\WebSphere\AppServer] c:\we
```

bsphere5\WebSphere\AppServer

Enter the directory where WebSphere is installed. Press Enter to continue.

---

**Note.** You will get an error message if you specify a directory that does not contain WebSphere, or that contains an incorrect WebSphere version.

---

7. Enter a cell name.
8. Enter a node name.
9. Enter a server name.

---

**Note.** If the web server on which you are installing PeopleSoft Pure Internet Architecture is not up and running, you'll receive an error message that you need to start your web server.

---

10. Choose whether to create a new WebSphere application (domain) or to use an existing domain.

---

**Note.** You only see the option Existing WebSphere Application if there is already a domain in <PS\_HOME>.

---

If you select Create New WebSphere application, the install automatically generates a valid domain name in the domain name field. If you attempt to enter an invalid domain name, you'll be prompted to enter a new domain name or choose an existing domain.

11. Select an application name.

---

**Note.** The PeopleSoft Enterprise Application name you specify must be unique for each WebSphere node.

---

12. If you selected Existing WebSphere application, you can choose from a drop-down list of existing domains, and can select whether to install an additional PeopleSoft site, redeploy PeopleSoft Pure Internet Architecture, or deploy additional PeopleSoft application extensions.
13. Enter a PeopleSoft web site name; the default is ps.

---

**Warning!** The site name can include underscores ( \_ ), but an underscore cannot be followed by a numeric character or the string “newwin” (for example, my\_site\_3 or my\_newwin\_site).

---

14. Specify your application server name, its JSL (Jolt Station Listener) port number, its HTTP and HTTPS port numbers, the authentication token domain (optional).

Enter port numbers and summaries.

AppServer name:

[ <MACHINENAME > ]

JSL Port:

[ 9000 ]

HTTP Port:

[ 80 ]

HTTPS Port:

[ 443 ]

Authentication Token Domain:(optional)

---

**Note.** For the AppServer name setting, enter the name of your application server. For the JSL port setting, enter the JSL port number you specified when setting up your application server. (The default value is 9000.)

---

See “Configuring the Application Server on UNIX.”

---

**Note.** The HTTP/HTTPS port numbers are reset to those that you just specified when you restart your WebSphere server.

---



---

**Note.** The value you enter for the Authentication Token Domain must match the value you specific when configuring your application server, as described earlier in this book. In addition, certain installation configurations require that you specify an authentication domain.

---

See Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation.

---

**Note.** If you enter a value for the Authentication Token Domain, the URL to invoke PeopleSoft Pure Internet Architecture must include the network domain name in the URL. For example, if you do not enter an authentication domain, the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName/ps/signon.html`. If you do enter a value for the authentication domain (for example, `.myCompany.com`), the URL to invoke PeopleSoft Pure Internet Architecture is `http://MachineName.myCompany.com/ps/signon.html`. In addition, if the web server for the database is using an HTTP port other than the default port of 9080, the URL must include the port number, for example `http://MachineName:8080/ps/signon.html` if there is no authentication domain, or `http://MachineName.myCompany.com:8080/ps/signon.html` if there is an authentication domain. The URL must also comply with the naming rules given earlier in this chapter.

---

See “Understanding the PeopleSoft Pure Internet Architecture.”

15. Enter the name of the web profile name in the database that will be used to configure this PeopleSoft web site.

This can be the name of either a predelivered one shown on the page, or one you intend to create yourself using PeopleTools, Web Profile Configuration after logging in. Each site is configured according to the profile you specify here when it is first accessed after the web server is booted. The user ID and password will be used by the PIA servlets themselves at runtime to log in to the application server to retrieve the profile. For applications on PeopleTools 8.44 and above, PeopleSoft predelivers the PTWEBSEVER user ID for the purpose of configuring PIA servlets at runtime and running the Performance Monitor Agents. You may have to unlock that user profile in certain application databases. If you have any problems logging in after starting the web server, refer to the application server domain logs.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.



---

**Note.** If you are upgrading your application database to PeopleTools 8.44 and above, you must set up the PTWEBSEVER user ID. Go to PeopleTools, Security, User Profiles, User Profiles, click Add a New Value, enter PTWEBSEVER for User ID, and click Add. Enter and confirm a password, and enter a description. Enter the role *PeopleTools Web Server* and then click Save.

---

16. Specify the root directory for the Report Repository (c:\psreports by default). You can install to any location.

---

**Note.** For the Report Repository directory, specify the same directory that you specify as the Home Directory. Make sure that this directory is shared.

---

See "Setting Up Process Scheduler," Setting Up the Process Scheduler to Transfer Reports and Logs to Report Repository.

17. Verify all of your selections and press Enter to kick off the installation. You see a progress indicator showing the progress of your installation.
18. Click Finish to complete the installation.

The default installation directory is <PS\_HOME>\webserv\<cellname\_nodename\_servername>\<domain>.

19. Stop the WebSphere server. From the bin directory under the WebSphere home directory, enter:

```
stopServer.sh <server_name>
```

where <server\_name> indicates where you have deployed PeopleSoft Pure Internet Architecture.

## Task 9B-3-2: Uninstalling the PeopleSoft Pure Internet Architecture from WebSphere

You cannot uninstall PeopleSoft Pure Internet Architecture simply by deleting <PS\_HOME>, without uninstalling it from WebSphere Administration Console. If you do so, the WebSphere registry becomes corrupt, and subsequent attempts to install PeopleSoft Pure Internet Architecture will fail. Instead, if necessary, you must uninstall PeopleSoft Pure Internet Architecture on WebSphere as described here:

To uninstall PeopleSoft Pure Internet Architecture on WebSphere:

1. Open WebSphere Administration Console at <http://<machine-name>:9090/admin>.

To invoke PeopleSoft Pure Internet Architecture on a non-default admin port, consult the section on WebSphere in PeopleBooks.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, "Working with IBM WebSphere."

2. Log in as any user.
3. Choose Applications, Enterprise Applications.
4. Select the check boxes for the PeopleSoft Pure Internet Architecture applications you want to uninstall, and click Stop.
5. Select the check boxes for the PeopleSoft Pure Internet Architecture applications you want to uninstall, and click Uninstall.
6. Save your configuration.
7. Stop WebSphere server.

8. Delete the directory <PS\_HOME>/WebServ/<cellname>\_<nodename>\_<servername>.

---

## Task 9B-4: Encrypting the Password (AIX Only)

If you installed either the WebLogic or WebSphere web server on an AIX operating system, you must encrypt the password manually.

1. Navigate to <PS\_HOME>/webserv/<domain\_name>, where the default value for <domain\_name> is peoplesoft.
2. Run the following commands, substituting your User ID and its password for <userid> and <password>:

```
PSCipher.sh <userid>
PSCipher.sh <password>
```

The commands return encrypted values. Save these values.

3. Navigate to <PS\_HOME>/webserv/<domain\_name>/applications/peoplesoft/PORTAL/WEB-INF/psftdocs/<site\_name>.

The default values for <domain\_name> and <site\_name>, respectively, are *peoplesoft* and *ps*. If you used other values when setting up the PeopleSoft Pure Internet Architecture, use those values here.

4. Open the file configuration.properties in a text editor.
5. Replace the values of *WebUserId* and *WebPassword* in this file with the encrypted values for <userid> and <password>, respectively, from step 2.

---

## Task 9B-5: Testing the PeopleSoft Pure Internet Architecture Installation

This section discusses:

- Starting and Stopping Oracle Application Server
- Starting and Stopping WebLogic
- Starting WebSphere
- Accessing the PeopleSoft Signon
- Updating Database Information
- Updating PeopleTools Options

---

**Note.** After installing the PeopleSoft Pure Internet Architecture, you should make sure that your configuration is functional. You can test this by signing on to PeopleSoft, navigating within the menu structure, and accessing pages. (Make sure the application server is configured and booted.)

---

### Task 9B-5-1: Starting and Stopping Oracle Application Server

There are several commands you can use to start and stop OAS and PIA, either separately or together.

Action	Command (full path)
Start PIA and other related processes	<OAS_HOME>/opmn/bin/opmnctl startall
Stop PIA and other related processes	<OAS_HOME>/opmn/bin/opmnctl stopall
View the status of the PIA installation on OAS	<OAS_HOME>/opmn/bin/opmnctl status
Start the OAS admin console	<OAS_HOME>/bin/emctl start em
Stop the OAS admin console	<OAS_HOME>/bin/emctl stop em
Start only PIA.  In a single-component installation, <i>PIA_component</i> is the same as the application name entered during the installation of PIA on OAS.  In a multi-component installation, <i>PIA_component</i> is a combination of the application name entered during the installation and the specific OC4J component type. The default name for the PIA component in a multi-component installation is <i>PIA_PeopleSoft</i> .	<OAS_HOME>/opmn/bin/opmnctl.exe⇒ startproc ias-component=OC4J process⇒ type=PIA_component
Stop only PIA.	<OAS_HOME>/opmn/bin/opmnctl.exe⇒ stopproc ias-component=OC4J process⇒ type=PIA_component

## Task 9B-5-2: Starting and Stopping WebLogic

If you are using the WebLogic web server, you need to sign on to WebLogic. If you are using WebSphere instead, go on to the next procedure.

To start WebLogic:

1. To start BEA WebLogic Server as a foreground process, execute the following command in your WebLogic domain directory (the default directory is <PS\_HOME>\webserv\<domain\_name>):

*Single Server:*

```
startPIS.cmd (on Windows)
startPIA.sh (on UNIX)
```

*Multi Server or Distributed Server:*

```
startWebLogicAdmin.cmd (on Windows)
startWebLogicAdmin.sh (on UNIX)
```

and then

```
startManagedWebLogic.cmd <ManagedServerName> (on Windows)
startManagedWebLogic.sh <ManagedServerName> (on UNIX)
```

2. To stop the server, execute the following command in your WebLogic domain directory:

*Single Server:*

```
stopPIA.cmd (on Windows)
stopPIA.sh (on UNIX)
```

*Multi Server or Distributed Server:*

```
stopWebLogic.cmd [-url t3://ServerHostName:port | <ManagedServerName>] (on⇒
Windows)
stopWebLogic.sh [-url t3://ServerHostName:port | <ManagedServerName>] (on UNIX)
```

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

## Task 9B-5-3: Starting WebSphere

If you are using the WebSphere web server, you need to sign on to WebSphere. If you are using WebLogic instead, you should have used the previous procedure.

To start WebSphere:

1. Change directories to the folder in which WebSphere is installed—the bin directory under the WebSphere home directory.
2. Enter the command

```
./startServer.sh <server_name>
```

where <server\_name> indicates where you have deployed PeopleSoft Pure Internet Architecture.

3. To stop the server, change directories to the folder in which WebSphere is installed and enter the command

```
./stopServer <server_name>
```

where <server\_name> indicates where you have deployed PeopleSoft Pure Internet Architecture.

## Task 9B-5-4: Accessing the PeopleSoft Signon

To access the PeopleSoft signon:

1. Open your web browser.
2. Enter the name of the site you want to access—for example (the default value for <site\_name> is *ps*):


```
http://<machine_name>:<http_port>/<site_name>/signon.html
```

---

**Note.** PeopleSoft Pure Internet Architecture installed on WebSphere server listens at the HTTP/HTTPS ports specified during the PeopleSoft Pure Internet Architecture install. Invoke PeopleSoft Pure Internet Architecture through a browser by using the specified HTTP or HTTPS ports—that is, `http://<WebSphere_machine_name>:<server_port>/<site_name>/signon.html` (if AuthTokenDomain is not specified ) or `http://<WebSphere_machine_name.mycompany.com>:<server_port>/<site_name>/signon.html` (if you specified .mycompany.com as the AuthTokenDomain).

---

This will take you to the signon screen corresponding to your browser's language preference.



Oracle PeopleSoft Enterprise Sign in window

**Note.** If you do not see the signon screen, check that you supplied all the correct variables and that your application server and the database server are running.

3. Sign in to the PeopleSoft system by entering a valid user ID and password.

Different applications use different default user IDs and passwords. For instance, for HRMS applications you enter PS for the user ID and the password. For Financials applications, you enter VP1 for the user ID and the password. Your application-specific install instructions contain any custom/delivered user IDs that you should use for the demonstration environment.

**Note.** The user ID and password are case sensitive. You need to enter the user ID and password using UPPERCASE.

## Task 9B-5-5: Updating Database Information

The database information updated in this procedure is used by the PeopleSoft software update tools to identify your PeopleSoft database when searching for updates. These steps should be followed for all additional databases that you create to enable the accurate identification of your databases.

1. Sign on to your PeopleSoft database.
2. Navigate to PeopleTools, Utilities, Administration, PeopleTools Options.
3. Specify long and short names for your environment. For example:
  - Environment Long Name — Customer HR Demo Database

- Environment Short Name — HR Demo DB
4. Select a system type from the drop-down list. For example, Demo Database.
  5. Save your changes.

## Task 9B-5-6: Updating PeopleTools Options

You can set the following options on the PeopleTools Options page:

- Multi-Currency — Check this box if you plan to use currency conversion.  
*See Enterprise PeopleTools 8.48 PeopleBook: Global Technology, “Controlling Currency Display Format.”*
- Base Time Zone — Check this box to set the base time zone for your PeopleTools database.  
*See Enterprise PeopleTools 8.48 PeopleBook: Global Technology “Setting and Maintaining Time Zones.”*
- Data Field Length Checking Flag — Check this box if you are using a Japanese EBCDIC (DB2 MBCS) or Japanese Shift-JIS (MBCS) database.  
*See Enterprise PeopleTools 8.48 PeopleBook: Global Technology, “Selecting and Configuring Character Sets and Language Input and Output.”*
- Sort Order Option — If you specified a non-binary sort order for your database, choose the Sort Order Option that most closely approximates your database sort order.  
*See Enterprise PeopleTools 8.48 PeopleBook: Global Technology, “Sorting in PeopleTools.”*

## CHAPTER 10A

# Setting Up Process Scheduler on Windows

This chapter discusses:

- Prerequisites
- Setting Up Process Scheduler Security
- Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository
- Setting Environment Variables
- Setting Up Process Scheduler Server Agent
- Starting Process Scheduler as a Windows Service (Optional)
- Configuring the Process Scheduler for Word for Windows (Optional)
- Configuring Setup Manager

### See Also

*Enterprise PeopleTools 8.48 Hardware and Software Requirements*

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler*

PeopleSoft Customer Connection, Supported Platforms (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise)

---

## Prerequisites

Before setting up your Process Scheduler, you must:

- Install Tuxedo (except for z/Linux).  
See “Installing Additional Components.”
- Install database connectivity to be able to communicate with your database server (Process Scheduler requires a direct connection to the database).  
See “Preparing for Installation.”
- Set up the web server with the PeopleSoft Pure Internet Architecture, as described in the previous chapter. This is required to set up the Process Scheduler to transfer reports or log files to the Report Repository.
- Set up your COBOL batch environment if you need to run COBOL processes through Process Scheduler. COBOL is no longer required to start a Process Scheduler Server Agent because the program for Process Scheduler has been rewritten in C++. If the PeopleSoft modules purchased do not contain any COBOL modules, the COBOL run time libraries are not required. Also, COBOL is not required for applications

that contain no COBOL programs. Consult Customer Connection for the details on whether your application requires COBOL.

See “PeopleSoft Application COBOL Requirements,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise, By PeopleTools release, Platform Communications by Topic, Batch)

- Install the Microsoft Office products Microsoft Word and Microsoft Excel.
- Have both your application server and the PeopleSoft Pure Internet Architecture started. In this chapter, you must modify security options of the designated PeopleSoft user ID that will be used to boot up Process Scheduler. This requires that the user ID's profile be modified through the User Security component. Please refer to earlier chapters for the details on starting the application server and the PeopleSoft Pure Internet Architecture.

---

## Task 10A-1: Setting Up Process Scheduler Security

This section discusses:

- Understanding Process Scheduler Security
- Changing User Account to Start BEA ProcMGR V8.1
- Granting Process Scheduler Administrative Rights

### Understanding Process Scheduler Security

This task—in which you set up the PeopleSoft User ID that will be used to boot Process Scheduler server so it has administrative rights to both Process Scheduler and Report Manager—guarantees that security is set up properly both in Windows and within your PeopleSoft database.

You must carry out this task to start Process Scheduler successfully.

Set up BEA ProcMGR V8.1 with a network user ID.

When you install BEA Tuxedo, the BEA ProcMGR V8.1 service is set up by default to be started by local system account—a user account that does not have access to the Windows network. If the Process Scheduler server or processes initiated through Process Scheduler will be using a network printer, accessing files from a network drive, or using Windows utilities such as XCOPY that may access UNC paths, you need to change the user account used to start BEA ProcMGR with a network user account.


### Task 10A-1-1: Changing User Account to Start BEA ProcMGR V8.1

To change User Account to start BEA ProcMGR V8.1:

1. Select Start, Settings, Control Panel. Double-click Administrative Tools, and double-click the Services icon.


In the Services dialog box, find the service labeled *BEA ProcMGR V8.1*. This service is installed automatically when you install Tuxedo.





Services dialog box

2. If the Stop button is enabled, click on it to stop the current BEA ProcMGR V8.1 process. Click Yes when a message informs you of the status change. Then, click BEA ProcMGR V8.1 and click Startup to modify its settings. You see this Service dialog box.



BEA ProcMGR Properties dialog box

3. Choose This Account.

---

**Note.** When you configure your Tuxedo server as outlined in the chapter, "Configuring the Application Server," the user ID designated to be the Application Server Administrator must have read/write permissions to the PeopleSoft file directory and read permission to the %TUXDIR% directory, such as c:\tuxedo.

---

4. Make sure that Startup Type is set to Automatic, and click OK.
5. Click Start. A message in the Services dialog box will indicate the "Started" status. Click Close to return to Control Panel.

## Task 10A-1-2: Granting Process Scheduler Administrative Rights

To grant Process Scheduler administrative rights:

1. Log onto your PeopleSoft database through the PeopleSoft Pure Internet Architecture.
2. Select PeopleTools, Security, User Profiles.

3. Select the User Profiles component. Use the Search dialog to select the PeopleSoft User ID you plan to use to boot the Process Scheduler server.
4. Click the Roles tab, click the plus icon to insert a new row, and there enter the *ProcessSchedulerAdmin* role to grant the user ID with administrative rights in the Process Scheduler components.

The screenshot shows the 'Roles' tab in the Process Scheduler window. At the top, there are tabs for 'General', 'ID', 'Roles', 'Workflow', 'Audit', 'Links', and 'User ID Queries'. Below the tabs, the 'User ID' is set to 'VP1' and the 'Description' is 'VP of Corporate Planning'. The main area displays a table of roles with columns for 'Role Name', 'Description', 'Dynamic', 'Route Control', and 'View Definition'. The table lists several roles, including 'Coordinator', 'PAPP\_USER', 'Packaging', 'PeopleSoft Administrator', 'PeopleSoft User', 'PeopleTools', 'ProcessSchedulerAdmin', 'ReportDistAdmin', 'UPG\_ALLPANLS', and 'UPG\_APPSRVR'. Each role has a search icon, a description, a 'Dynamic' checkbox, and links for 'Route Control' and 'View Definition'. At the bottom right of the table, there are '+' and '-' icons for adding or removing roles.

Role Name	Description	Dynamic	Route Control	View Definition
Coordinator	Coordinator	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>
PAPP_USER	Enterprise Portal User	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>
Packaging	Env. Mgmt. Packaging	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>
PeopleSoft Administrator	PeopleSoft Admin Privileges	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>
PeopleSoft User	PeopleSoft User	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>
PeopleTools	PeopleTools	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>
ProcessSchedulerAdmin	Process Scheduler Admin	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>
ReportDistAdmin	Report Distribution Admin	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>
UPG_ALLPANLS	ALLPANLS	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>
UPG_APPSRVR	Can start application server	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>

Process Scheduler window: Roles tab

5. Repeat the instructions in step 4 to add the role *ReportDistAdmin*. This will grant the user ID administrative rights to the Report Manager component.
6. Click Save to save your changes.
7. Select the General tab and jot down the Permission List name assigned to the Process Profile field.
8. From the Portal menu, choose PeopleTools, Security, Permissions & Roles, Permission Lists.
9. In the Search dialog, enter the Permission List you noted in step 7.
10. Select the Can Start Application Server check box.
11. Click Save to save your changes.

## Task 10A-2: Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository

This section discusses:

- Understanding Report Distribution
- Setting Up Single Signon to Navigate from PIA to Report Repository

- Determining the Transfer Protocol
- Starting the Distribution Agent
- Setting Up the Report Repository
- Setting Up the Distribution for Your Process Scheduler Server
- Setting Up Sending and Receiving of Report Folders in the Report Manager

## Understanding Report Distribution

The PeopleTools Report Distribution lets you access reports and log files generated from process requests run by a Process Scheduler Server Agent. Using the PeopleSoft Pure Internet Architecture, you can view reports and log files from the web browser through the Report Manager or Process Monitor Detail page. Report Distribution enables you to restrict access to these reports to authorized users based either on user ID or role ID.

This product also includes the Distribution Agent component, which runs on the same server as the Process Scheduler Server Agent. The Distribution Agent, a process that runs concurrently with the Process Scheduler Server Agent, transfers to the Report Repository files generated by process requests initiated by the Process Scheduler Server Agent.


The Distribution Agent transfers files to the Report Repository when one of these criteria is true:

- The Process Scheduler Server Agent is set up in the *Server Definition* to transfer all log files to the Report Repository.
- The process request output destination type is *Web/Window*.

In either case, the Process Scheduler Server Agent inserts a row in the Report List table (PS\_CDM\_LIST). The server agent then updates the distribution status for a process request to *Posting* upon completion of the program associated with the process request. The distribution status of *Posting* signals the Distribution Status that the files for the process request are ready for transfer to the Report Repository. The Distribution Agent is notified by Process Scheduler for any process requests that are ready for transferring. As part of the process to transfer files to the Report Repository, the Distribution Agent performs the following steps:

- *Transfer files to the Report Repository.* All the report and log files are transferred to the Report Repository. For each process request transferred, a directory is created in the Report Repository using the following format: \<database name>\<date yyymmdd>\<report id>. All the files for a process request are stored in this directory.
- *Delete the directory from the Process Scheduler Agent's Log/Output directory.* When the output destination type specified for a process request is *Web/Window*, all the files and directory associated with the process request are deleted from the Process Scheduler Log/Output directory after the files are transferred to the Report Repository.

The following diagram illustrates the Process Scheduler and Report Repository architecture.



Process Scheduler and Report Repository Architecture

**Note.** The PeopleSoft Pure Internet Architecture must be installed for Process Scheduler to be able to transfer reports to the Repository.

**Note.** Before users can view a report, they are authenticated against the PeopleSoft database.

**Note.** You should set up single signon if you do not want users to have to log on an additional time to view reports in the Report Repository. For the details on setting up single signon, consult the security PeopleBook.

See *Enterprise PeopleTools 8.48 PeopleBook: Security Administration*.

## Task 10A-2-1: Setting Up Single Signon to Navigate from PIA to Report Repository

To view reports (log files or system files) from Report Repository, you need to pass the authentication. Report Repository should be treated as a separate PeopleSoft application. To navigate from PeopleSoft Pure Internet Architecture (PIA) to Report Repository, you need to set up single signon to avoid getting a prompt for a second signon. Here are some considerations for setting up single signon to navigate from PIA to Report Repository:

If Report Repository resides on the same web server as the PeopleSoft Pure Internet Architecture, make sure your Local Message Node is set up to be a "trusted" node for single signon for your system.

If Report Repository resides on a different web server than PeopleSoft Pure Internet Architecture, do the following:

- Make sure your Local Message Node is set up to be a "trusted" node for single signon for your system.
- Use a fully qualified domain name when addressing the web server for both PIA and Report Repository. For example, enter `http://<machineName>.peoplesoft.com/<site_name>/signon.html` instead of `http://<machineName>/<site_name>/signon.html`.

- Specify the Authentication Domain for your application during installation. If you have multiple applications, and you want them to employ single signon, it is important to specify the same Authentication Domain for all applications.

See *Enterprise PeopleTools 8.48 PeopleBook: Security Administration*, “Implementing Single Signon.”

- Set up single signon with a password, like this:
  - Choose PeopleTools, Integration Broker, Integration Setup, Nodes.
  - Click Search and then select the node marked as Default Local Node.
  - Select *Password* for the Authentication Option.
  - Enter a password of your choice.
  - Enter the password again in the Confirm Password field.
  - Enter the user ID for which you are setting up single signon in the Default User ID field.
  - Save the Node Definition.
  - Sign off of PIA.
  - Reboot your application server.

### See Also

*Enterprise PeopleTools 8.48 PeopleBook: Security Administration*

## Task 10A-2-2: Determining the Transfer Protocol

*We recommend using HTTP as your transfer protocol.*

Before transferring the files to the Report Repository, you need to determine which transfer protocol to use. If you have a Windows Process Scheduler and a Windows web server, you can use either an XCOPY, FTP, or HTTP/HTTPS. (If FTP information is not specified, Process Scheduler will perform an XCOPY.) If you have any other combination of servers (such as a Windows or z/OS Process Scheduler and a UNIX web server), you must use FTP or HTTP/HTTPS.

---

**Note.** If you are using FTP, the FTP service must be set up in your web server.

---

---

**Note.** JRE is installed automatically on your Process Scheduler server.

---

## Task 10A-2-3: Starting the Distribution Agent

The Distribution Agent is automatically started as another Tuxedo server when a Process Scheduler Server is booted. If a Process Scheduler Server was set up without specifying a Distribution Node in the *Server Definition* page, the Process Scheduler server will have a status in Process Monitor of “Running with No Report Node.” Once a node is defined for the Process Scheduler server and in the next cycle the Process Scheduler server checks the state of the system, the Distribution Agent dynamically sets up its environment.

## Task 10A-2-4: Setting Up the Report Repository

This section discusses:

- Defining ReportRepositoryPath

- Defining the Report Node to Use HTTP/HTTPS
- Defining the Report Node to Use XCOPY
- Defining the Report Node to Use FTP

### Defining ReportRepositoryPath

The ReportRepositoryPath specifies the location of a directory for the Report Repository. You can specify the location for the Report Repository Path on the General page of the Web Profile during installation. If you do not set the location in the Web Profile, the location given by ReportRepositoryPath in the configuration.properties file is used for the default location. Note that the value entered for Report Repository Path in the Web Profile overrides any entry in the configuration.properties file.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*, “Configuring the Portal Environment.”

Use the following formats to enter the name for the directory that you want to use for the ReportRepositoryPath. The examples below give the default values. Note that you must use a forward slash ("/") in both cases:

- *Windows*: ReportRepositoryPath=c:/psreports
- *UNIX*: ReportRepositoryPath=/opt/psreports

### Defining the Report Node to Use HTTP/HTTPS

To define the report node to use HTTP/HTTPS:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select the Add a New Value link and enter the Report node name.

The Report Node Definition page appears. You are on the Http Distribution Node page.

3. Verify that the Http Information option is selected.

**Report Node Definition**

Node Name: HTTP

☐ Ftp/XCopy ☒ Http Information

**Distribution Node Details**

URL: http://<machine name>/psreports/<site name>

Description:

Operating System: NT/Win2000

**Connection Information**

☒ http ☐ https

URI Host: <machine name> URI Port: 80

URI Resource: SchedulerTransfer/<site name>

Login ID:

Password:

Confirm Password:

Save Notify Add Update/Display

[Http Distribution Node](#) | [FTP/XCopy Distribution Node](#)

Report Node Definition page for HTTP

- Enter the *URL* of the web server using the following format:

http://<machine name>:<port number>/psreports/<site name>

Replace <machine name> with the name of your machine. Use the fully qualified host name for your web server. If you are using an http port other than 80, you need to specify the port number.

**Note.** If you specify the Authentication Token Domain name during the PeopleSoft Pure Internet Architecture installation, you must include a fully qualified domain name for the URL instead of the IP address.

- *Description:* Enter a description of the server (optional).
  - *Operating System:* Select the web server operating system.
- Enter the following Connection Information:
    - *http/https:* Select the http option if you are *not* using SSL (default). Select the https option if you are using SSL. Note that if you are using SSL you need to have Client Certificates installed on your web server.
    - *URI Host:* Enter the machine name for the report repository.

**Note.** In a basic setup, the machine name for the report repository will match the machine name of the web server URL. However, under certain circumstances—for example, if you are using a reverse proxy server—the URL and URI Host may have different machine names.

- *URI Port:* Enter the port number, which must match the port number of your web server (defaults are http = 80, https = 443). If you change a port number you will lose the default values for both protocols.



- *URI Resource*: Enter SchedulerTransfer/<site name>.

---

**Note.** The setup of basic authentication is optional, but is recommended for security of the Report Repository when using the HTTP to transfer files. For detailed instructions on setting up basic authentication on the web server where the Report Repository resides, refer to the appendix “Securing the Report Repository for HTTP.”

---

- *Login ID*: Enter the Login ID. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.
  - *Password*: Enter the password for the user ID specified in the Login ID field. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.
  - *Confirm Password*: Enter the password a second time as a confirmation. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.
6. Click Save to save your entries.
  7. To add additional report nodes, select Add to return to the Search page.

The following fields are shared between the FTP/XCOPY Distribution Node page and the Http Distribution page:

- URL
- Description
- Operating System
- Login ID
- Password
- Confirm Password.

When you enter the information on one page, the information is also displayed on the shared fields of the other page but the fields are grayed out.

---

**Note.** If you complete the information for one protocol and then change your selection to another protocol, the shared fields will become active on the other page and grayed out on the original page. When you save, the system automatically clears the fields that are not shared.

---

## Defining the Report Node to Use XCOPY

To define the report node to use XCOPY:

---

**Note.** If you use XCOPY the following parameters must be configured: URL, Operating System (must be Windows Server), Network Path (must be DOS or UNC paths and should be a shared directory with write permissions for the account running the Process Scheduler). Both the Process Scheduler machine and the Report Repository machine must be Windows for XCOPY to be used.

---

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.
3. Select the FTP/XCopy option.

The FTP/XCopy Distribution page appears.

**Report Node Definition**

**Node Name:** XCOPY

☒ Ftp/XCopy ☐ Http Information

**Distribution Node Details**

**URL:** http://<machine name>/psreports/<site name>

**Home Directory:**

**Description:**

**Operating System:** NT/Win2000

**Connection Information**

**FTP Address:** **Password:**

**FTP ID:** **Confirm Password:**

**Network Path:** \\<machine name>\psreports

[Save](#) [Notify](#) [Add](#) [Update/Display](#)

[Http Distribution Node](#) | [FTP/XCopy Distribution Node](#)

Report Node Definition page for XCOPY

- Enter the URL of the web server using this format:

http://<machine name>:<port number>/psreports/<site name>

Replace <machine name> with the name of your web server.

If you are using an http port other than 80, you need to specify the port number. <site name> refers to the directory where you installed the PIA files.

**Note.** If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

- Under Network Path replace <machine name> with the name of your machine.  
Make sure that this directory is shared with the login or logins used to start Process Scheduler. Enter the UNC path that points to your Report Repository share.
- Select NT/Win2000 as the operating system.
- Select Save to save your entries.
- To add additional report nodes, select Add to return to the Search page.

## Defining the Report Node to Use FTP

If you use FTP the following parameters must be configured: URL, Home Directory, Operating System, FTP Address, FTP ID, Password, Confirm Password. In addition, if your FTP server is a Windows server, you may have to set up the FTP service.

**Note.** The Distribution Agent will perform a validation after FTP has transferred files into the Report Repository by sending a query request to the web server. For this task to be accomplished, it is critical that the following setup is done:

JRE must be properly installed from the Process Scheduler server.

The value entered in the URL must be accurate. Verify that the machine name, port number, and site number are correct.

If either of these tasks are not done, the process request will get a status of NOT POSTED in the Process Monitor Detail page and will log the message "Unable to verify files posted."

To define the report node to use FTP:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.
3. Select the FTP/XCopy option.

The FTP/XCopy Distribution node page appears.

The screenshot shows the 'Report Node Definition' page for an 'FTP/XCopy Distribution Node'. The page has two tabs: 'Http Distribution Node' and 'FTP/XCopy Distribution Node', with the latter being selected. The main title is 'Report Node Definition'. Below the title, there are two radio buttons: 'Ftp/XCopy' (selected) and 'Http Information'. The 'Distribution Node Details' section contains the following fields: 'URL:' with a text box containing 'http://<machine name>/psreports/<site name>', 'Home Directory:' with a text box containing '\\<machine name>\psreports', 'Description:' with a text box containing 'FTP Sample', and 'Operating System:' with a dropdown menu showing 'NT/Win2000'. The 'Connection Information' section contains the following fields: 'FTP Address:' with a text box containing '<machine name>', 'Password:' with a text box containing '\*', 'FTP ID:' with a text box containing '<user id>', 'Confirm Password:' with a text box containing '\*', and 'Network Path:' with an empty text box. At the bottom of the page, there are four buttons: 'Save', 'Notify', 'Add', and 'Update/Display'. Below the buttons, there is a link: 'Http Distribution Node | FTP/XCopy Distribution Node'.

Report Node Definition page for FTP

4. Enter the URL of the web server using this format:

`http://<machine name>:<port number>/psreports/<site name>`

Replace *<machine name>* with the name of your web server. If you are using an http port other than 80, you need to specify the port number. The variable *<site name>* refers to the directory where you installed the PIA files; this will default to ps for the first installation.

---

**Note.** If you specify the Authentication Token Domain name during the PeopleSoft Pure Internet Architecture installation, you must include a fully qualified domain name for the URL instead of the IP address.

---

---

**Note.** If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

---

5. Enter the following additional parameters:
  - *Home Directory:* Specify the directory specified during the installation of PeopleSoft Pure Internet Architecture as the Report Repository. The FTP user ID must have write access to this directory. Note that this is not a required field for HTTP transfer, as the system uses the Report Repository directory specified at install time or the current directory assigned to ReportRepositoryPath in configuration.properties. Note that the value you enter for the Report Repository Path in the Web Profile at install time overrides any entry for ReportRepositoryPath in configuration.properties.  
  
For Windows, the directory needs to match the Report Repository path. Make sure that you do not include any drive information—as in c:\psreports\—because you are using the FTP protocol to interpret this parameter.
  - *Description:* Enter a description of the server (optional).
  - *Operating System:* Select the operating system of the Report Repository.
  - *FTP Address:* Enter the machine name or the IP address of the Report Repository. If the name of the machine is used, it must be included on a DNS server.
  - *FTP ID:* FTP user ID.
  - *Password:* Enter the password for the user ID specified in the FTP ID field.
  - *Confirm Password:* Enter the password a second time as a confirmation.
6. Select Save to save your entries.
7. To add additional report nodes, select Add to return to the Search page.

## Task 10A-2-5: Setting Up the Distribution for Your Process Scheduler Server

To set up the Distribution Settings for your Process Scheduler Server:

1. Choose PeopleTools, Process Scheduler, Servers.
2. Enter the Server Name (such as PSNT). The Server Definition page appears.
3. Select the Distribution tab.

Server Definition | **Distribution** | Operation | Notification | Daemon

Server Name: PSNT

**Server Distribution Details**

Distribution Node Name:

Maximum Transfer Retries:

Interval for Transfer Attempt:  seconds

Transfer System Files to Report Repository ☐

Save Return to Search Notify Add Update/Display

[Server Definition](#) | [Distribution](#) | [Operation](#) | [Notification](#) | [Daemon](#)

Server Definition page: Distribution tab

4. Click the lookup button to display the report node names and select the name of the required report node.
5. Enter a number for the Maximum Transfer Retries. This is the maximum number of times the server can try to send a report before it errors out.
6. Enter the number of seconds for the Interval for Transfer Attempt field. This is the interval between attempts to send the report.
7. Select the check box Transfer Log Files to Report Repository if you want to transfer all log and trace files from processes that do not generate reports.
8. Click Save to save your entries.
9. If Process Scheduler is running, you must reboot for any new settings to take effect.

To view reports (log files or system files) from Report Repository, you need to pass the authentication. Report Repository should be treated as a separate PeopleSoft Application. To navigate from PIA to Report Repository, you need to setup single signon in order to avoid getting prompt for second signon.

## Task 10A-2-6: Setting Up Sending and Receiving of Report Folders in the Report Manager

To be able to view reports in the Report Manager Explorer and List pages, you need to set up the sending and receiving of report folders in the Report Manager by activating the domain on which a sending and receiving server resides. Consult the documentation covering the PeopleSoft Integration Broker to learn how to activate the sending and receiving server domain.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Integration Broker*, “Using the Service Operations Monitor.”

## Task 10A-3: Setting Environment Variables

To set the appropriate Tuxedo environment variables, carry out these steps. (If you have already set these variables on the machine you are using as your Process Scheduler Server, you can skip this task.)

See “Installing Additional Components,” Installing Tuxedo on Windows.

To set the variables:

1. Choose Start, Settings, Control Panel.
2. Double-click the System icon.
3. Make sure that the NLSPATH environment variable is set.

NLSPATH does not need to be explicitly set since BEA/Tuxedo sets NLSPATH in its own registry tree. This value can be displayed using Control Panel, BEA/Tuxedo, on the Environment tab. However, the installation of certain products, such as IBM DB2 connectivity (DB2 UDB for z/OS and DB2 for Linux, UNIX, and Windows) sets NLSPATH to a value that causes Tuxedo to fail. The solution is to either set NLSPATH=c:\tuxedo\locale\c, or to delete it entirely and let Tuxedo pick up the value from its registry tree. If you are running DB2 for Linux, UNIX, and Windows, the solution instead is to append the c:\tuxedo\locale\c directory in the NLSPATH directory.

## Task 10A-4: Setting Up Process Scheduler Server Agent

This section discusses:

- Understanding Process Scheduler Server Agent
- Creating and Configuring a Process Scheduler Server
- Reconfiguring a Process Scheduler Server
- Verifying the Process Scheduler Server Status

### Understanding Process Scheduler Server Agent

For installation purposes, you can use predefined server names and other definitions. The predefined name that you might use is as follows:

Server Name	Operating System
PSNT	Windows

To test this, use processes already defined in your PeopleSoft database. To set up a new server definition in your PeopleSoft database, refer to the Process Scheduler PeopleBook.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler*

**Note.** When creating multiple Process Scheduler Servers for the same database, each server must have a unique server name. For example, two Process Scheduler Servers, both named PSNT, cannot run against the same database.

## Task 10A-4-1: Creating and Configuring a Process Scheduler Server

This section describes how to create and configure a Process Scheduler server.

---

**Note.** You can set Process Scheduler configuration parameters either by using PSADMIN, which provides an interactive dialog, or by editing the configuration file `psprcs.cfg` located in the `<PS_HOME>\appserv\prcs\database name` directory. The following steps assume you are using PSADMIN to specify parameter settings.

---

To create and configure a Process Scheduler Server:

1. From `<PS_HOME>\appserv` on the batch server, type `psadmin` and press ENTER to access the PeopleSoft Server Administration menu.
2. Select 2 to access the Process Scheduler submenus.

```
-----
PeopleSoft Server Administration
-----
1) Application Server
2) Process Scheduler
3) Search Server
4) Service Setup
q) Quit
```

Command to execute (1-4 q): 2

3. Select 4 from the PeopleSoft Process Scheduler Administration menu.

```
-----
PeopleSoft Process Scheduler Administration
-----
1) Start a Process Scheduler Server
2) Stop a Process Scheduler Server
3) Configure a Process Scheduler Server
4) Create a Process Scheduler Server Configuration
5) Delete a Process Scheduler Server Configuration
6) Edit a Process Scheduler Configuration File
7) Import an existing Process Scheduler Configuration
8) Show Status of a Process Scheduler Server
9) Kill a Process Scheduler Server
10) Clean IPC resources of a Process Scheduler Domain
q) Quit
```

Command to execute (1-9, q) : 4

4. When prompted for the name of the database that your server will access

Please enter name of Database that server will access :

enter the name of the database and press ENTER.

## 5. After the system creates the domain, you see the prompt

Would you like to configure this Process Scheduler Server now? (y/n) [y] :

Choose y; you'll see a Quick-configure menu something like this:

-----  
Quick-configure menu -- Scheduler for Database: HRDMO  
-----

Features =====	Settings =====
1) Master Schdlr : Yes	5) DBNAME : [HRDMO]
2) App Eng Server : Yes	6) DBTYPE : [ORACLE]
	7) PrcsServer : [PSNT]
	8) UserId : [PS]
	9) UserPswd : [PS]
	10) ConnectID : [people]
	11) ConnectPswd: [people]
	12) ServerName : []
	13) Log/Output Dir: [%PS_SERVDIR%\log_output]
	14) SQRBIN : [%PS_HOME%\bin\sqr\ORA\binw]
3) Load config as shown	15) AddToPATH : [%WINDIR%;%WINDIR%\SYSTEM32]
4) Custom configuration	16) DBBIN : [C:\<connectivity directory>]
h) Help for this menu	
q) Return to previous menu	

HINT: Enter 5 to edit DBNAME, then 3 to load

Enter selection (1-16, h, or q):

---

**Note.** Cognos/Cube Manager Installs: Make sure to specify the proper path for Cognos in the *Add to Path* parameter. By default, that path is C:\Program Files\Cognos\cer2\bin;C:\ODI\OStore\bin. The Cognos and ODI are the important top level directories, and could change depending on the install.

---

6. If you need to modify any of these settings, enter the number next to the parameter name, type the new value, and press ENTER.

Parameter	Description
Master Schdlr	Flag to enable the Master Scheduler Server (PSMSTPRC). Default is to enable the server.  See Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler.
App Eng Server	Flag to initiate Application Engine programs through the AE Tuxedo Server (PSAESRV). Default is set to run AE using PSAESRV.  See Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler.



Parameter	Description
Load config as shown	Load the selections you made in the Quick Configure menu.
Custom configuration	Make custom selections in PSADMIN, using options that are not available in the Quick Configure menu.
DBNAME	Specify the database name that is associated with a PeopleSoft Process Scheduler Server Agent, such as HRDMO, FSDMO, SADMO, and so on.
DBTYPE	Specify the database type: ORACLE.
PrsServer	Specify the process server name. This must match the name defined in the Server Definition table, such as <i>PSNT</i> or <i>PSUNX</i> .
UserId	Enter the user ID. For Enterprise Resource Planning (ERP), this is typically <i>VPI</i> , and for Human Resources (HR) it's <i>PS</i> .
UserPswd	Enter the user password. For Enterprise Resource Planning, this is typically <i>VPI</i> , and for Human Resources it's <i>PS</i> .
ConnectID	Enter the connect ID. This value is required.
ConnectPswd	Enter the connect password. This value is required.
ServerName	This value is required for Sybase users.
Log/Output Dir	Specify the directory in which files that are generated by the program are written. When PeopleSoft Process Scheduler initiates a process request, it creates a subdirectory in the format <Process Type ID> <Program Name> <Process Instance> that contains the generated files. For instance, the SQR program XRFWIN that ran with process instance 20 has all reports, trace, and log files in the subdirectory SQR_XRFWIN_20. It is also the optional directory used with the Output Destination field when scheduling a request. This variable (%%OutputDirectory%%) can be used in the File/Printer field of the Process Scheduler Request dialog box.
SQRBIN	Enter the path to the SQR executables.
AddToPATH	(Optional for Tuxedo) Specify an additional directory that is appended to the PATH environment variable.
DBBIN	Enter the path to the database drivers; that is, your connectivity software.

For descriptions of the PSADMIN options that do not appear in the Quick-configure menu, consult the following. For a basic install, in most cases you can accept the defaults.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler*.

7. When you have updated the settings as needed, choose *3, Load config as shown*, from the Quick-Configure menu to save your settings to the Process Scheduler configuration file, `pstuxcfg`.
8. To start Process Scheduler, choose *1* and select the item number corresponding to your database to start.

---

**Note.** The correct Crystal and nVision libraries and components are automatically configured when Process Scheduler is booted.

---



---

**Note.** To stop Process Scheduler Server, choose *2, Stop a Process Scheduler Server*, from the PeopleSoft Process Scheduler Administration menu, and then enter the number corresponding to the name of the appropriate database.

---



---

**Note.** If you see the following message, then the server is already down:

```
Command to execute (1-2, q) [q]: 1
Loading command line administration utility ...
tmadmin - Copyright (c) 1996 BEA Systems, Inc.
Portions * Copyright 1986-1997 RSA Data Security, Inc.
All Rights Reserved.
Distributed under license by BEA Systems, Inc.
Tuxedo is a registered trademark.
No bulletin board exists. Entering boot mode.
> TMADMIN_CAT:111: ERROR: No such command.
```

---

## Task 10A-4-2: Reconfiguring a Process Scheduler Server

If you create and then immediately configure a Process Scheduler server, you can use the Quick-configure menu. However, if you want to update the configuration of an existing domain, or carry out a number of other administrative tasks, this handy shortcut is not available. Instead you can use PSADMIN as follows. Feel free to skip this procedure if you have already created and configured your Process Scheduler Server using the Quick-configure menu and want to move forward with your installation.

---

**Note.** If you want to configure the Process Scheduler Server while it is running, you need to stop and restart the server to load the new settings.

---

To reconfigure a Process Scheduler Server:

1. Start PSADMIN by entering:

```
cd <PS_HOME>\appserv
psadmin
```

2. Select *2* for Process Scheduler in the PeopleSoft Server Administration menu.
3. In the PeopleSoft Process Scheduler Administration menu, select *3* for Configure a Process Scheduler.

4. Select the database for which the Process Scheduler needs to be configured.
5. At the prompt

Do you want to change any config values (y/n)? [n]:

Specify *y* to start an interactive dialog that lets you examine or change parameter values.

6. Now you specify configuration parameters one by one. Configuration parameters are grouped into sections. At each section, you are asked whether to change any parameters—for example:

Values for config section - Startup

```
DBName=
DBType=
UserId=
UserPswd=
ConnectId=
ConnectPswd=
ServerName=
```

Do you want to change any values (y/n)? [n]:

- Specify *y* to change any parameter values for the current section. You are prompted for each parameter value. Either specify a new value or press ENTER to accept the default. After you press ENTER, you are positioned at the next parameter in that section. When you are done with that section, you are again asked whether you want to re-edit any of the values you changed.
- If you do not want to change any values, specify *n* and you are prompted for the next configuration section.

7. Once you have selected all your parameters, you see this message

You will need to shut down and start up the server to read the new settings.

For descriptions of the Process Scheduler options in the PSADMIN, consult the following. In most cases you can accept the defaults.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler*.

## Task 10A-4-3: Verifying the Process Scheduler Server Status

At this stage it is a good idea to verify the Process Scheduler Server status.

To verify the Process Scheduler Server status:

1. From the PeopleSoft Process Scheduler Administration menu, select option 8.

```
-----
PeopleSoft Process Scheduler Administration
-----

1) Start a Process Scheduler Server
2) Stop a Process Scheduler Server
3) Configure a Process Scheduler Server
4) Create a Process Scheduler Server Configuration
5) Delete a Process Scheduler Server Configuration
6) Edit a Process Scheduler Configuration File
```

- 7) Import an existing Process Scheduler Configuration
- 8) Show Status of a Process Scheduler Server
- 9) Kill a Process Scheduler Server
- 10) Clean IPC resources of a Process Scheduler Domain

q) Quit

Command to execute (1-10, q) : 8

2. To verify the status of the Process Scheduler Server for a specific database, type the number corresponding to the appropriate database.

For example:

Database list:

- 1) HRDMO

Select item number to start: 1

will verify the status of the Process Scheduler Server for the database HRDMO.

```

Loading command line administration utility ...
tmadmin - Copyright (c) 1996-1999 BEA Systems, Inc.
Portions * Copyright 1986-1997 RSA Data Security, Inc.
All Rights Reserved.
Distributed under license by BEA Systems, Inc.
Tuxedo is a registered trademark.

> Prog Name      Queue Name  Grp Name      ID RqDone Load Done Current Service
-----
BBL.exe          33728      PSSERVER+     0    2    100 ( IDLE )
PSMONITORSRV.e  MONITOR    MONITOR       1    0    0 ( IDLE )
PSAESRV.exe      00101.00001 AESRV         1    0    0 ( IDLE )
PSAESRV.exe      00101.00002 AESRV         2    0    0 ( IDLE )
PSAESRV.exe      00101.00003 AESRV         3    0    0 ( IDLE )
PSPRCSRV.exe     SCHEDQ     BASE          101   0    0 ( IDLE )
PSMSTPRC.exe     MSTRSCHQ   BASE          102   0    0 ( IDLE )
PSDSTSRV.exe     DSTQ       BASE          103   0    0 ( IDLE )

> Prog Name      Queue Name  # Serve Wk Queued # Queued Ave. Len Machine
-----
PSDSTSRV.exe     DSTQ       1          -          0          - PSSERVER1+

>

```

#### Verifying Status

You can also verify the status of the Process Scheduler Server from Process Monitor in PIA. To verify the Process Scheduler Server status from the Process Monitor page, go to PeopleTools, Process Scheduler, Process Monitor, and select *Server List*.

If the user has the process security rights to update the server status, the *Refresh* button can be used to refresh the screen, too.

See Setting Up Process Scheduler Security.

Process List

Server List

Refresh

Server	Hostname	Last Update Date/Time	Dist Node	Master	CPU (%)	Memory (%)	Active	Status	Details
<a href="#">PSNT</a>	PTLAB95	10/28/2003 9:53:33AM	https	N	1	29	0	Down	<a href="#">Details</a>
<a href="#">QE PSNT2</a>	PTLAB95	10/28/2003 9:53:45AM	https	N	1	29	0	Down	<a href="#">Details</a>
<a href="#">QE HPX1</a>	pt-hp07	10/28/2003 10:05:47AM	https	Y	21	34	1	Running	<a href="#">Details</a>

```

PeopleSoft Server Administration
-----
1) Application Server
2) Process Scheduler
3) Search Server
4) Service Setup
q) Quit

```

Command to execute (1-4, q): 4

5. Select 1 from the PeopleSoft Services Administration menu.

```

-----
PeopleSoft Services Administration
-----
1) Configure a Service
2) Install a Service
3) Delete a Service
4) Edit a Service Configuration File
q) Quit

```

Command to execute (1-4, q) : 1

When asked if you want to change configuration values, enter y.

6. Enter the name of the Process Scheduler databases that you intend to include as part of the Windows service.

```

Values for config section - NT Services
Service Start Delay=60
Application Server Domains=HR840
Process Scheduler Databases=HR840

```

Do you want to change any values (y/n)? [n]:

If you specify more than one Process Scheduler database, separate each entry with a comma.

---

**Note.** You can take advantage of a new setting when using PSADMIN to set up Process Scheduler Servers or application servers as a Windows service. The Windows Service psntrsv.exe automatically starts application servers and Process Scheduler Servers that reside on the same Windows machine. Occasionally, psntrsv.exe would attempt to initiate a connection between an application server or Process Scheduler Server and a database on the same machine that was not ready to receive requests. As a result the connection would fail. Now when you set up Process Scheduler or an application server as a Windows Service, the Service Start Delay setting lets you specify a delay, in seconds, that elapses before a service attempts to start any application server domains or Process Scheduler Servers. This allows the RDBMS to boot and become available to accept requests. The default setting for the Service Start Delay parameter is 60 seconds.

---

---

**Note.** The NT Services section of the PSADMIN modifies the psntsrv.cfg file located in the <PS\_HOME>\appserv directory. You can edit this file manually by selecting 4, *Edit a Service Configuration File* from the PeopleSoft Services Administration menu. If you edit it, you need to delete and then install the service again.

---

7. Select option 2 from the PeopleSoft Services Administration menu.

```

-----
PeopleSoft Services Administration
-----
1) Configure a Service
2) Install a Service
3) Delete a Service
4) Edit a Service Configuration File
q) Quit

Command to execute (1-4, q) : 2

```

8. Return to the Control Panel, choose *Administrative Tools*, and launch the *Services* utility.
9. On the Services dialog, scroll to find the entry that adheres to the following naming convention, and select it:

```
PeopleSoft <PS_HOME>
```

---

**Note.** The default Startup mode is Manual.

---

10. Click *Startup*.
11. On the Service dialog in the Startup Type group, select *Automatic*, and in the Log On As group, select *System Account*. Then click OK.

---

**Note.** The *Log On As* setting needs to reflect that which you set for your BEA ProcMGR V8.1 and Tlisten processes. PeopleSoft recommends that you set these services to *System Account* when you install Tuxedo. The *Log On As* value only affects the application server because Process Scheduler runs independently from Tuxedo. See the chapter “Installing Additional Components” for more information on installing Tuxedo, and refer to the chapter “Configuring the Application Server” for the details on configuring the application server.

---

12. On the Services dialog, make sure the PeopleSoft service is selected, and click Start.
13. Use the Process Monitor to verify that the Process Scheduler Server is running. You can also use Task Manager to verify that the executables involved with the service are running.

For the Process Scheduler, make sure that the psprcsrv.exe is running. If you have customized the name of psprcsrv.exe, make sure the appropriate executable is running.

---

## Task 10A-6: Configuring the Process Scheduler for Word for Windows (Optional)

Some applications process documents using Word for Windows. Here is how to configure Word to work with the Process Scheduler.

---

**Note.** Microsoft Word must already be installed on the server; it is not included with the PeopleTools install.

---

**Note.** If spaces exist in the WINWORD path in the Process Scheduler configuration file (psprcs.cfg), WinWord reports will fail. You will need to modify the Process Type Definition and add quotes around the entry in the Command Line field, for example "%%WINWORD%%\winword.exe".

---

To configure Process Scheduler for Word for Windows:

1. Edit the Process Scheduler configuration file. In the [Process Scheduler] section, edit the WINWORD entry so that it points to the directory where winword.exe is installed—for example, WINWORD=C:\Apps\Office2000\Office.

---

**Note.** The Process Scheduler configuration file psprcs.cfg is located in <PS\_HOME>\appserv\prcs\database name directory.

---

2. Change the Microsoft Word macro security to allow macros to be run. Start Microsoft Word and select *Tools, Macro, Security*. Select the *Low* security setting and click *OK*.

---


## Task 10A-7: Configuring Setup Manager

Before you can use PeopleTools Setup Manager, you must fulfill these requirements:

- To use the Excel to CI template-generation feature of Setup manager, the Process Scheduler must be PSNT. That is, Process Scheduler must be installed on a Windows machine.
- Process Scheduler must be running.
- Any Process Scheduler environment variables (especially %PS\_FILEDIR%) must be specified.
- Microsoft Office 2000 must be present on the process scheduler server, and Microsoft Excel must be installed.
- The MSXML COM object for Excel, msxml4.dll, must be present on the system.

For confirmation, navigate to %SystemRoot%\system32\msxml4.dll. Right-click and select Properties, Versions, Product Version. The version number must be 4.20 or above.





msxml4.dll Properties dialog box

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: Setup Manager*

Microsoft support, [support.microsoft.com](http://support.microsoft.com)



## CHAPTER 10B

# Setting Up Process Scheduler on UNIX

This chapter discusses:

- Prerequisites
- Setting Up Process Scheduler Security
- Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository
- Setting Up Process Scheduler Server Agent

---

**Note.** If your database runs on UNIX, you need to set up a Windows batch environment on a Windows application server or on a dedicated Windows workstation for Windows-specific batch processes, such as Crystal Reports, nVision reports, Microsoft Word, or Cube Manager. These processes are Windows-specific applications that cannot be executed by the Process Scheduler on UNIX or z/OS.

---

### See Also

*Enterprise PeopleTools 8.48 Hardware and Software Requirements*

*Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler*

PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise)

---

## Prerequisites

Before setting up your Process Scheduler, you must:

- Install Tuxedo (except for z/Linux).  
See “Installing Additional Components.”
- Install database connectivity to be able to communicate with your database server (Process Scheduler requires a direct connection to the database).  
See “Preparing for Installation.”
- Set up the web server with the PeopleSoft Pure Internet Architecture, as described in the previous chapter. This is required to set up the Process Scheduler to transfer reports or log files to the Report Repository.
- Set up your COBOL batch environment if you need to run COBOL processes through Process Scheduler. COBOL is no longer required to start a Process Scheduler Server Agent because the program for Process Scheduler has been rewritten in C++. If the PeopleSoft modules purchased do not contain any COBOL modules, the COBOL run time libraries are not required. Also, COBOL is not required for applications that contain no COBOL programs. Consult Customer Connection for the details on whether your application requires COBOL.

See “PeopleSoft Application COBOL Requirements,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise, By PeopleTools release, Platform Communications by Topic, Batch)

- Have both your application server and the PeopleSoft Pure Internet Architecture started. In this chapter, you must modify security options of the designated PeopleSoft user ID that will be used to boot up Process Scheduler. This requires that the user ID's profile be modified through the User Security component. Please refer to earlier chapters for the details on starting the application server and the PeopleSoft Pure Internet Architecture.

---

## Task 10B-1: Setting Up Process Scheduler Security

This section discusses:

- Understanding Process Scheduler Security
- Granting Process Scheduler Administrative Rights

### Understanding Process Scheduler Security

This task—in which you set up the PeopleSoft User ID that will be used to boot Process Scheduler server so it has administrative rights to both Process Scheduler and Report Manager—guarantees that security is set up properly within your PeopleSoft database.

You must carry out this task to start Process Scheduler successfully.

### Task 10B-1-1: Granting Process Scheduler Administrative Rights

To grant Process Scheduler administrative rights:

1. Log onto your PeopleSoft database through the PeopleSoft Pure Internet Architecture.
2. Select PeopleTools, Security, User Profiles.
3. Select the User Profiles component. Use the Search dialog to select the PeopleSoft User ID you plan to use to boot the Process Scheduler server.
4. Click the Roles tab, click the plus icon to insert a new row, and there enter the *ProcessSchedulerAdmin* role to grant the user ID with administrative rights in the Process Scheduler components.

General ID **Roles** Workflow Audit Links User ID Queries

User ID: VP1

Description: VP of Corporate Planning

Role Name	Description	Dynamic	Route Control	View Definition		
Coordinator	Coordinator	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-
PAPP_USER	Enterprise Portal User	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-
Packaging	Env. Mgmt. Packaging	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-
PeopleSoft Administra	PeopleSoft Admin Privileges	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-
PeopleSoft User	PeopleSoft User	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-
PeopleTools	PeopleTools	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-
ProcessSchedulerAdm	Process Scheduler Admin	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-
ReportDistAdmin	Report Distribution Admin	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-
UPG_ALLPANLS	ALLPANLS	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-
UPG_APPSRVR	Can start application server	<input type="checkbox"/>	<a href="#">Route Control</a>	<a href="#">View Definition</a>	+	-

Process Scheduler window: Roles tab

- Repeat the instructions in step 4 to add the role *ReportDistAdmin*. This will grant the user ID administrative rights to the Report Manager component.
- Click Save to save your changes.
- Select the General tab and jot down the Permission List name assigned to the Process Profile field.
- From the Portal menu, choose PeopleTools, Security, Permissions & Roles, Permission Lists.
- In the Search dialog, enter the Permission List you noted in step 7.
- Select the Can Start Application Server check box.
- Click Save to save your changes.

## Task 10B-2: Setting Up Process Scheduler to Transfer Reports and Logs to the Report Repository

This section discusses:

- Understanding Report Distribution
- Setting Up Single Signon to Navigate from PIA to Report Repository
- Determining the Transfer Protocol
- Starting the Distribution Agent
- Setting Up the Report Repository
- Setting Up the Distribution for Your Process Scheduler Server

- Setting Up Sending and Receiving of Report Folders in the Report Manager

## Understanding Report Distribution

The PeopleTools Report Distribution lets you access reports and log files generated from process requests run by a Process Scheduler Server Agent. Using the PeopleSoft Pure Internet Architecture, you can view reports and log files from the web browser through the Report Manager or Process Monitor Detail page. Report Distribution enables you to restrict access to these reports to authorized users based either on user ID or role ID.

This product also includes the Distribution Agent component, which runs on the same server as the Process Scheduler Server Agent. The Distribution Agent, a process that runs concurrently with the Process Scheduler Server Agent, transfers to the Report Repository files generated by process requests initiated by the Process Scheduler Server Agent.


The Distribution Agent transfers files to the Report Repository when one of these criteria is true:

- The Process Scheduler Server Agent is set up in the *Server Definition* to transfer all log files to the Report Repository.
- The process request output destination type is *Web/Window*.

In either case, the Process Scheduler Server Agent inserts a row in the Report List table (PS\_CDM\_LIST). The server agent then updates the distribution status for a process request to *Posting* upon completion of the program associated with the process request. The distribution status of Posting signals the Distribution Status that the files for the process request are ready for transfer to the Report Repository. The Distribution Agent is notified by Process Scheduler for any process requests that are ready for transferring. As part of the process to transfer files to the Report Repository, the Distribution Agent performs the following steps:

- *Transfer files to the Report Repository.* All the report and log files are transferred to the Report Repository. For each process request transferred, a directory is created in the Report Repository using the following format: \<database name>\<date yyymmdd>\<report id>. All the files for a process request are stored in this directory.
- *Delete the directory from the Process Scheduler Agent's Log/Output directory.* When the output destination type specified for a process request is Web/Window, all the files and directory associated with the process request are deleted from the Process Scheduler Log/Output directory after the files are transferred to the Report Repository.

The following diagram illustrates the Process Scheduler and Report Repository architecture.



Process Scheduler and Report Repository Architecture

**Note.** The PeopleSoft Pure Internet Architecture must be installed for Process Scheduler to be able to transfer reports to the Repository.

**Note.** Before users can view a report, they are authenticated against the PeopleSoft database.

**Note.** You should set up single signon if you do not want users to have to log on an additional time to view reports in the Report Repository. For the details on setting up single signon, consult the security PeopleBook.

See *Enterprise PeopleTools 8.48 PeopleBook: Security Administration*.

## Task 10B-2-1: Setting Up Single Signon to Navigate from PIA to Report Repository

To view reports (log files or system files) from Report Repository, you need to pass the authentication. Report Repository should be treated as a separate PeopleSoft application. To navigate from PeopleSoft Pure Internet Architecture (PIA) to Report Repository, you need to set up single signon to avoid getting a prompt for a second signon. Here are some considerations for setting up single signon to navigate from PIA to Report Repository:

If Report Repository resides on the same web server as the PeopleSoft Pure Internet Architecture, make sure your Local Message Node is set up to be a "trusted" node for single signon for your system.

If Report Repository resides on a different web server than PeopleSoft Pure Internet Architecture, do the following:

- Make sure your Local Message Node is set up to be a "trusted" node for single signon for your system.
- Use a fully qualified domain name when addressing the web server for both PIA and Report Repository. For example, enter `http://<machineName>.peoplesoft.com/<site_name>/signon.html` instead of `http://<machineName>/<site_name>/signon.html`.

- Specify the Authentication Domain for your application during installation. If you have multiple applications, and you want them to employ single signon, it is important to specify the same Authentication Domain for all applications.

See *Enterprise PeopleTools 8.48 PeopleBook: Security Administration*, “Implementing Single Signon.”

- Set up single signon with a password, like this:
  - Choose PeopleTools, Integration Broker, Integration Setup, Nodes.
  - Click Search and then select the node marked as Default Local Node.
  - Select *Password* for the Authentication Option.
  - Enter a password of your choice.
  - Enter the password again in the Confirm Password field.
  - Enter the user ID for which you are setting up single signon in the Default User ID field.
  - Save the Node Definition.
  - Sign off of PIA.
  - Reboot your application server.

### See Also

*Enterprise PeopleTools 8.48 PeopleBook: Security Administration*

## Task 10B-2-2: Determining the Transfer Protocol

*We recommend using HTTP as your transfer protocol.*

Before transferring the files to the Report Repository, you need to determine which transfer protocol to use. If you have a Windows Process Scheduler and a Windows web server, you can use either an XCOPY, FTP, or HTTP/HTTPS. (If FTP information is not specified, Process Scheduler will perform an XCOPY.) If you have any other combination of servers (such as a Windows or z/OS Process Scheduler and a UNIX web server), you must use FTP or HTTP/HTTPS.

---

**Note.** If you are using FTP, the FTP daemon must be set up in your web server.

---

---

**Note.** JRE is installed automatically on your Process Scheduler server.

---

## Task 10B-2-3: Starting the Distribution Agent

The Distribution Agent is automatically started as another Tuxedo server when a Process Scheduler Server is booted. If a Process Scheduler Server was set up without specifying a Distribution Node in the *Server Definition* page, the Process Scheduler server will have a status in Process Monitor of “Running with No Report Node.” Once a node is defined for the Process Scheduler server and in the next cycle the Process Scheduler server checks the state of the system, the Distribution Agent dynamically sets up its environment.

## Task 10B-2-4: Setting Up the Report Repository

This section discusses:

- Defining ReportRepositoryPath



- Defining the Report Node to Use HTTP/HTTPS
- Defining the Report Node to Use FTP

## Defining ReportRepositoryPath

The ReportRepositoryPath specifies the location of a directory for the Report Repository. You can specify the location for the Report Repository Path on the General page of the Web Profile during installation. If you do not set the location in the Web Profile, the location given by ReportRepositoryPath in the configuration.properties file is used for the default location. Note that the value entered for Report Repository Path in the Web Profile overrides any entry in the configuration.properties file.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*, “Configuring the Portal Environment.”

Use the following formats to enter the name for the directory that you want to use for the ReportRepositoryPath. The examples below give the default values. Note that you must use a forward slash (/) in both cases:

- *Windows*: ReportRepositoryPath=c:/psreports
- *UNIX*: ReportRepositoryPath=/opt/psreports

## Defining the Report Node to Use HTTP/HTTPS

To define the report node to use HTTP/HTTPS:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select the Add a New Value link and enter the Report node name.

The Report Node Definition page appears. You are on the Http Distribution Node page.

3. Verify that the Http Information option is selected.

**Http Distribution Node** **FTP/XCopy Distribution Node**

### Report Node Definition

**Node Name:** HTTP

☐ Ftp/XCopy ☒ **Http Information**

**Distribution Node Details**

**URL:**

**Description:**

**Operating System:**

**Connection Information**

☒ **http** ☐ https

**URI Host:**  **URI Port:**

**URI Resource:**

**Login ID:**

**Password:**  **Confirm Password:**

[Http Distribution Node](#) | [FTP/XCopy Distribution Node](#)

Report Node Definition page for HTTP

4. Enter the *URL* of the web server using the following format:

```
http://<machine name>:<port number>/psreports/<site name>
```

Replace <machine name> with the name of your machine. Use the fully qualified host name for your web server. If you are using an http port other than 80, you need to specify the port number.

---

**Note.** If you specify the Authentication Token Domain name during the PeopleSoft Pure Internet Architecture installation, you must include a fully qualified domain name for the URL instead of the IP address.

---

- *Description:* Enter a description of the server (optional).
  - *Operating System:* Select the web server operating system.
5. Enter the following Connection Information:
    - *http/https:* Select the http option if you are *not* using SSL (default). Select the https option if you are using SSL. Note that if you are using SSL you need to have Client Certificates installed on your web server.
    - *URI Host:* Enter the machine name for the report repository.

---

**Note.** In a basic setup, the machine name for the report repository will match the machine name of the web server URL. However, under certain circumstances—for example, if you are using a reverse proxy server—the URL and URI Host may have different machine names.

---

- *URI Port:* Enter the port number, which must match the port number of your web server (defaults are http = 80, https = 443). If you change a port number you will lose the default values for both protocols.
- *URI Resource:* Enter SchedulerTransfer/<site name>.

---

**Note.** The setup of basic authentication is optional, but is recommended for security of the Report Repository when using the HTTP to transfer files. For detailed instructions on setting up basic authentication on the web server where the Report Repository resides, refer to the appendix “Securing the Report Repository for HTTP.”

---

- *Login ID:* Enter the Login ID. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.
  - *Password:* Enter the password for the user ID specified in the Login ID field. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.
  - *Confirm Password:* Enter the password a second time as a confirmation. This is not required, unless basic authentication has been set up on the web server by the Web Administrator.
6. Click Save to save your entries.
  7. To add additional report nodes, select Add to return to the Search page.

The following fields are shared between the FTP/XCOPY Distribution Node page and the Http Distribution page:

- URL
- Description
- Operating System
- Login ID

- Password
- Confirm Password.

When you enter the information on one page, the information is also displayed on the shared fields of the other page but the fields are grayed out.

---

**Note.** If you complete the information for one protocol and then change your selection to another protocol, the shared fields will become active on the other page and grayed out on the original page. When you save, the system automatically clears the fields that are not shared.

---

## Defining the Report Node to Use FTP

If you use FTP the following parameters must be configured: URL, Home Directory, Operating System, FTP Address, FTP ID, Password, Confirm Password. In addition, if your FTP server is a Windows server, you may have to set up the FTP service.

---

**Note.** The Distribution Agent will perform a validation after FTP has transferred files into the Report Repository by sending a query request to the web server. For this task to be accomplished, it is critical that the following setup is done:

JRE must be properly installed from the Process Scheduler server.

The value entered in the URL must be accurate. Verify that the machine name, port number, and site number are correct.

If either of these tasks are not done, the process request will get a status of NOT POSTED in the Process Monitor Detail page and will log the message "Unable to verify files posted."

---

To define the report node to use FTP:

1. Select PeopleTools, Process Scheduler, Report Nodes.
2. Select Add a New Value, enter the Report node name, and click Add.
3. Select the FTP/XCopy option.

The FTP/XCopy Distribution node page appears.

**Report Node Definition**

Node Name: FTP

☒ Ftp/XCopy ☐ Http Information

**Distribution Node Details**

URL: http://<machine name>/psreports/<site name>

Home Directory: /home/psreports

Description: FTP Sample

Operating System: UNIX

**Connection Information**

FTP Address: <machine name> Password: \*

FTP ID: <user id> Confirm Password: \*

[Http Distribution Node](#) | [FTP/XCopy Distribution Node](#)

Report Node Definition page for FTP

- Enter the URL of the web server using this format:

http://<machine name>:<port number>/psreports/<site name>

Replace *<machine name>* with the name of your web server. If you are using an http port other than 80, you need to specify the port number. The variable *<site name>* refers to the directory where you installed the PIA files; this will default to ps for the first installation.

**Note.** If you specify the Authentication Token Domain name during the PeopleSoft Pure Internet Architecture installation, you must include a fully qualified domain name for the URL instead of the IP address.

**Note.** If you installed the web server software with the default TCP port of 80, you do not need to specify the port number in the URL path. However, if you installed the web server to some other port, you must specify the port number in the URL path.

- Enter the following additional parameters:
  - Home Directory:* Specify the directory specified during the installation of PeopleSoft Pure Internet Architecture as the Report Repository. The FTP user ID must have write access to this directory. Note that this is not a required field for HTTP transfer, as the system uses the Report Repository directory specified at install time or the current directory assigned to ReportRepositoryPath in configuration.properties. Note that the value you enter for the Report Repository Path in the Web Profile at install time overrides any entry for ReportRepositoryPath in configuration.properties.

For UNIX, the directory will look like \$PS\_HOME/psreports/.

- *Description*: Enter a description of the server (optional).
  - *Operating System*: Select the operating system of the Report Repository.
  - *FTP Address*: Enter the machine name or the IP address of the Report Repository. If the name of the machine is used, it must be included on a DNS server.
  - *FTP ID*: FTP user ID.
  - *Password*: Enter the password for the user ID specified in the FTP ID field.
  - *Confirm Password*: Enter the password a second time as a confirmation.
6. Select Save to save your entries.
  7. To add additional report nodes, select Add to return to the Search page.

## Task 10B-2-5: Setting Up the Distribution for Your Process Scheduler Server

To set up the Distribution Settings for your Process Scheduler Server:

1. Choose PeopleTools, Process Scheduler, Servers.
2. Enter the Server Name (such as PSUNIX). The Server Definition page appears.
3. Select the Distribution tab.

The screenshot shows the 'Server Definition' page with the 'Distribution' tab selected. The 'Server Name' is set to 'PSUNIX'. Below this is a section titled 'Server Distribution Details' containing several input fields: 'Distribution Node Name' with a search icon, 'Maximum Transfer Retries', 'Interval for Transfer Attempt' with a unit of 'seconds', and 'Transfer System Files to Report Repository' with an unchecked checkbox. At the bottom of the form are five buttons: 'Save', 'Return to Search', 'Notify', 'Add', and 'Update/Display'. Below the buttons is a navigation bar with links for 'Server Definition', 'Distribution', 'Operation', 'Notification', and 'Daemon'.

Server Definition page: Distribution tab

4. Click the lookup button to display the report node names and select the name of the required report node.
5. Enter a number for the Maximum Transfer Retries. This is the maximum number of times the server can try to send a report before it errors out.

6. Enter the number of seconds for the Interval for Transfer Attempt field. This is the interval between attempts to send the report.
7. Select the check box Transfer Log Files to Report Repository if you want to transfer all log and trace files from processes that do not generate reports.
8. Click Save to save your entries.
9. If Process Scheduler is running, you must reboot for any new settings to take effect.

To view reports (log files or system files) from Report Repository, you need to pass the authentication. Report Repository should be treated as a separate PeopleSoft Application. To navigate from PIA to Report Repository, you need to setup single signon in order to avoid getting prompt for second signon.

## Task 10B-2-6: Setting Up Sending and Receiving of Report Folders in the Report Manager

To be able to view reports in the Report Manager Explorer and List pages, you need to set up the sending and receiving of report folders in the Report Manager by activating the domain on which a sending and receiving server resides. Consult the documentation covering the PeopleSoft Integration Broker to learn how to activate the sending and receiving server domain.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Integration Broker*, “Using the Service Operations Monitor.”

---

## Task 10B-3: Setting Up Process Scheduler Server Agent

This section discusses:

- Understanding Process Scheduler Server Agent
- Changing the Default Operating System
- Setting Up Your Environment
- Creating and Configuring a Process Scheduler Server
- Reconfiguring a Process Scheduler Server
- Verifying the Process Scheduler Server Status

## Understanding Process Scheduler Server Agent

For installation purposes, you can use predefined server names and other definitions. The predefined name that you might use is as follows:

Server Name	Operating System
PSUNIX	UNIX

To test this, use processes already defined in your PeopleSoft database. To set up a new server definition in your PeopleSoft database, refer to the Process Scheduler PeopleBook.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler*

---

**Note.** When creating multiple Process Scheduler Servers for the same database, each server must have a unique server name. For example, two Process Scheduler Servers, both named PSNT, cannot run against the same database.

---

## Task 10B-3-1: Changing the Default Operating System

By default, Process Scheduler is set up to run a process request from a Process Scheduler Server Agent started in a Windows server when the value of the *ServerName* field in the Process Request Dialog page is left blank. If you plan to run all processes other than Windows-based programs (that is, nVision or Crystal Reports) from UNIX, you must change the default operating system.

---

**Note.** If you do not change the default operating system from Windows to UNIX and you do not plan to set up a Process Scheduler Server Agent in Windows, process requests that are created will be directed to a Windows-based operating system and will remain in the "Queued" status.

---

To change the default operating system for process requests that were not assigned a Process Scheduler Server Name:

1. Navigate to PeopleTools, Process Scheduler, System Settings.
2. Under *Primary Operating System*, choose *UNIX* from the drop-down list.
3. Click on the *System Purge Options* tab. Enter the date for the next purge of process requests in the *Next Purge Date* field.
4. Enter the time for the next purge of process requests in the *Next Purge Time* field. The default time is 12:00:00AM.
5. Enter a *Recurrence* if you want to set a regular purging basis.
6. Choose *Save*.

## Task 10B-3-2: Setting Up Your Environment

Telnet to your UNIX system. Log in and ensure the following environment variables are set appropriately. Alternatively, make sure the following environment variables are set in the profile file in the user's home directory:

Remember, you only need COBOL if your application requires COBOL.

See *Enterprise PeopleTools 8.48 Hardware and Software Requirements*.

- \$ORACLE\_HOME must point to the correct Oracle installation; for example:

```
ORACLE_HOME=/products/oracle/8.1.7;export ORACLE_HOME
```

- \$ORACLE\_HOME/bin must be added to PATH; for example:

```
PATH=$PATH:$ORACLE_HOME/bin;export PATH
```

- \$ORACLE\_HOME/lib must be appended to LD\_LIBRARY\_PATH, LIBPATH, or SHLIB\_PATH, whichever is appropriate for your platform.
- \$ORACLE\_SID must be set to the correct Oracle instance; for example:

```
ORACLE_SID=hdmo;export ORACLE_SID
```

- \$COBDIR must be set to the Server Express installation; for example:

```
COBDIR=/cobol/prod/svrex-2.2.SP1;export COBDIR
```

- \$COBDIR/lib must be appended to LD\_LIBRARY\_PATH, LIBPATH, or SHLIB\_PATH, whichever is appropriate for your platform.

```
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$COBDIR/lib;export LD_LIBRARY_PATH
```

```
LIBPATH=$LIBPATH:$COBDIR/lib;export LIBPATH
```

```
SHLIB_PATH=$SHLIB_PATH:$COBDIR/lib;export SHLIB_PATH
```

- \$COBDIR/bin must be appended to the PATH; for example:

```
PATH=$PATH:$COBDIR/bin;export PATH
```

To set the required PeopleSoft environment variables, run psconfig.sh. Enter the following command:

```
cd <PS_HOME>
. ./psconfig.sh
```

## Task 10B-3-3: Creating and Configuring a Process Scheduler Server

This section describes how to create and configure a Process Scheduler server.

---

**Note.** You can set Process Scheduler configuration parameters either by using PSADMIN, which provides an interactive dialog, or by editing the configuration file psprcs.cfg located in the <PS\_HOME>/appserv/prcs/database name directory. The following steps assume you are using PSADMIN to specify parameter settings.

---

To create and configure a Process Scheduler Server:

1. From <PS\_HOME>/appserv on the batch server, type psadmin and press ENTER to access the PeopleSoft Server Administration menu.
2. Select 2 to access the Process Scheduler submenus.

```
-----
PeopleSoft Server Administration
-----
1) Application Server
2) Process Scheduler
3) Search Server
q) Quit
```

```
Command to execute (1-3 q): 2
```

3. Select 4 from the PeopleSoft Process Scheduler Administration menu.

```
-----
PeopleSoft Process Scheduler Administration
-----
1) Start a Process Scheduler Server
2) Stop a Process Scheduler Server
3) Configure a Process Scheduler Server
4) Create a Process Scheduler Server Configuration
5) Delete a Process Scheduler Server Configuration
```



- 6) Edit a Process Scheduler Configuration File
- 7) Import an existing Process Scheduler Configuration
- 8) Show Status of a Process Scheduler Server
- 9) Kill a Process Scheduler Server
- 10) Clean IPC resources of a Process Scheduler Domain
- q) Quit

Command to execute (1-9, q) : 4

4. When prompted for the name of the database that your server will access

Please enter name of Database that server will access :

enter the name of the database and press ENTER.

5. After the system creates the domain, you see the prompt

Would you like to configure this Process Scheduler Server now? (y/n) [y] :

Choose y; you'll see a Quick-configure menu something like this:

-----  
Quick-configure menu -- Scheduler for Database: HRDMO  
-----

Features =====	Settings =====
1) Master Schdlr : Yes	5) DBNAME : [HRDMO]
2) App Eng Server : Yes	6) DBTYPE : [ORACLE]
	7) PrcsServer : [PSUNX]
	8) UserId : [QEDMO]
	9) UserPswd : [QEDMO]
	10) ConnectID : [people]
	11) ConnectPswd: [people]
	12) ServerName : []
	13) Log/Output Dir: [%PS_SERVDIR%/log_output]
	14) SQRBIN : [%PS_HOME%/bin/sqr/ORA/bin]
	15) AddToPATH : [%PS_HOME%/cblbin]
Actions =====	
3) Load config as shown	
4) Custom configuration	
h) Help for this menu	
q) Return to previous menu	

HINT: Enter 5 to edit DBNAME, then 3 to load

Enter selection (1-15, h, or q):

6. If you need to modify any of these settings, enter the number next to the parameter name, type the new value, and press ENTER.

Parameter	Description
Master Schdlr	Flag to enable the Master Scheduler Server (PSMSTPRC). Default is to enable the server.  See Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler.
App Eng Server	Flag to initiate Application Engine programs through the AE Tuxedo Server (PSAESRV). Default is set to run AE using PSAESRV.  See Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler.
Load config as shown	Load the selections you made in the Quick Configure menu.
Custom configuration	Make custom selections in PSADMIN, using options that are not available in the Quick Configure menu.
DBNAME	Specify the database name that is associated with a PeopleSoft Process Scheduler Server Agent, such as HRDMO, FSDMO, SADMO, and so on.
DBTYPE	Specify the database type: ORACLE.
PrsServer	Specify the process server name. This must match the name defined in the Server Definition table, such as <i>PSNT</i> or <i>PSUNX</i> .
UserId	Enter the user ID. For Enterprise Resource Planning (ERP), this is typically <i>VPI</i> , and for Human Resources (HR) it's <i>PS</i> .
UserPswd	Enter the user password. For Enterprise Resource Planning, this is typically <i>VPI</i> , and for Human Resources it's <i>PS</i> .
ConnectID	Enter the connect ID. This value is required.
ConnectPswd	Enter the connect password. This value is required.
ServerName	This value is required for Sybase users.

Parameter	Description
Log/Output Dir	Specify the directory in which files that are generated by the program are written. When PeopleSoft Process Scheduler initiates a process request, it creates a subdirectory in the format <Process Type ID>_<Program Name>_<Process Instance> that contains the generated files. For instance, the SQR program XRFWIN that ran with process instance 20 has all reports, trace, and log files in the subdirectory SQR_XRFWIN_20. It is also the optional directory used with the Output Destination field when scheduling a request. This variable (%%OutputDirectory%%) can be used in the File/Printer field of the Process Scheduler Request dialog box.
SQRBIN	Enter the path to the SQR executables.
AddToPATH	(Optional for Tuxedo) Specify an additional directory that is appended to the PATH environment variable.
DBBIN	Enter the path to the database drivers; that is, your connectivity software.

For descriptions of the PSADMIN options that do not appear in the Quick-configure menu, consult the following. For a basic install, in most cases you can accept the defaults.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler*.

7. When you have updated the settings as needed, choose 3, *Load config as shown*, from the Quick-Configure menu to save your settings to the Process Scheduler configuration file, pstuxcfg.
8. To start Process Scheduler, choose 1 and select the item number corresponding to your database to start.

---

**Note.** To stop Process Scheduler Server, choose 2, *Stop a Process Scheduler Server*, from the PeopleSoft Process Scheduler Administration menu, and then enter the number corresponding to the name of the appropriate database.

---



---

**Note.** If you see the following message, then the server is already down:

Command to execute (1-2, q) [q]: 1

Loading command line administration utility ...

tadmin - Copyright (c) 1996 BEA Systems, Inc.

Portions \* Copyright 1986-1997 RSA Data Security, Inc.

All Rights Reserved.

Distributed under license by BEA Systems, Inc.

Tuxedo is a registered trademark.

No bulletin board exists. Entering boot mode.

> TMADMIN\_CAT:111: ERROR: No such command.

---

## Task 10B-3-4: Reconfiguring a Process Scheduler Server

If you create and then immediately configure a Process Scheduler server, you can use the Quick-configure menu. However, if you want to update the configuration of an existing domain, or carry out a number of other administrative tasks, this handy shortcut is not available. Instead you can use PSADMIN as follows. Feel free to skip this procedure if you have already created and configured your Process Scheduler Server using the Quick-configure menu and want to move forward with your installation.

---

**Note.** If you want to configure the Process Scheduler Server while it is running, you need to stop and restart the server to load the new settings.

---

To reconfigure a Process Scheduler Server:

1. Start PSADMIN by entering:

```
cd <PS_HOME>/appserv
psadmin
```

2. Select 2 for Process Scheduler in the PeopleSoft Server Administration menu.
3. In the PeopleSoft Process Scheduler Administration menu, select 3 for Configure a Process Scheduler.
4. Select the database for which the Process Scheduler needs to be configured.
5. At the prompt

```
Do you want to change any config values (y/n)? [n]:
```

Specify *y* to start an interactive dialog that lets you examine or change parameter values.

6. Now you specify configuration parameters one by one. Configuration parameters are grouped into sections. At each section, you are asked whether to change any parameters—for example:

```
Values for config section - Startup
```

```
DBName=
DBType=
UserId=
UserPswd=
ConnectId=
ConnectPswd=
ServerName=
```

```
Do you want to change any values (y/n)? [n]:
```

- Specify *y* to change any parameter values for the current section. You are prompted for each parameter value. Either specify a new value or press ENTER to accept the default. After you press ENTER, you are positioned at the next parameter in that section. When you are done with that section, you are again asked whether you want to re-edit any of the values you changed.
  - If you do not want to change any values, specify *n* and you are prompted for the next configuration section.
7. Once you have selected all your parameters, you see this message

```
You will need to shut down and start up the server to read the new settings.
```

For descriptions of the Process Scheduler options in the PSADMIN, consult the following. In most cases you can accept the defaults.

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Process Scheduler*.

## Task 10B-3-5: Verifying the Process Scheduler Server Status

At this stage it is a good idea to verify the Process Scheduler Server status.

To verify the Process Scheduler Server status:

1. From the PeopleSoft Process Scheduler Administration menu, select option 8.

```
-----
PeopleSoft Process Scheduler Administration
-----

1) Start a Process Scheduler Server
2) Stop a Process Scheduler Server
3) Configure a Process Scheduler Server
4) Create a Process Scheduler Server Configuration
5) Delete a Process Scheduler Server Configuration
6) Edit a Process Scheduler Configuration File
7) Import an existing Process Scheduler Configuration
8) Show Status of a Process Scheduler Server
9) Kill a Process Scheduler Server
10) Clean IPC resources of a Process Scheduler Domain

q) Quit

Command to execute (1-10, q) : 8
```

2. To verify the status of the Process Scheduler Server for a specific database, type the number corresponding to the appropriate database.

For example:

Database list:

```
1) HRDMO
```

Select item number to start: 1

will verify the status of the Process Scheduler Server for the database HRDMO.

```

Loading command line administration utility ...
tmadmin - Copyright (c) 1996-1999 BEA Systems, Inc.
Portions * Copyright 1986-1997 RSA Data Security, Inc.
All Rights Reserved.
Distributed under license by BEA Systems, Inc.
Tuxedo is a registered trademark.

> Prog Name      Queue Name  Grp Name      ID RqDone Load Done Current Service
-----
BBL              59013      pt-ibm20      0      1      50 ( IDLE )
PSMONITORSRV    MONITOR    MONITOR      1      0      0 ( IDLE )
PSAESRV         00101.00001 AESRV        1      0      0 ( IDLE )
PSAESRV         00101.00002 AESRV        2      0      0 ( IDLE )
PSAESRV         00101.00003 AESRV        3      0      0 ( IDLE )
PSPRCSRV        SCHEDQ     BASE        101     0      0 ( IDLE )
PSMSTPRC        MSTRSCHQ   BASE        102     0      0 ( IDLE )
PSDSTSRV        DSTQ       BASE        103     0      0 ( IDLE )

> Prog Name      Queue Name  # Serve Wk Queued # Queued Ave. Len Machine
-----
PSDSTSRV        DSTQ              1      -      0      -      pt-ibm20

>

```

Verifying Status

---

**Note.** You can also do this using the following command line argument:

```
psadmin -p status -d <DBNAME>
```

---



---

**Note.** You can also verify the status of the Process Scheduler Server from Process Monitor in PIA. To verify the Process Scheduler Server status from the Process Monitor page, go to PeopleTools, Process Scheduler, Process Monitor, and select *Server List*.

---

## CHAPTER 11

# Installing and Configuring Software for Crystal Reports

This chapter discusses:

- Understanding Crystal Reports Software Installation and Configuration
- Determining the Crystal Reports Runtime Environment
- Installing Crystal Reports 9
- Installing BusinessObjects Enterprise XI
- Migrating your BusinessObjects Enterprise XI Installation to a New Version of PeopleTools
- Installing Crystal Reports XI
- Removing Crystal Reports XI
- Administering and Using BusinessObjects Enterprise XI
- Converting Crystal Reports


---

## Understanding Crystal Reports Software Installation and Configuration

This chapter addresses the installation and administration of your Crystal Reports environment. Depending on the type of installation that you have some parts of the chapter will not be relevant to you.

The chapter is divided into sections. Within each section are parts that provide informative background information or describe installation and administration tasks.

The following flowchart describes how to use the information in this chapter to install and configure the software that you need to run Crystal Reports on your PeopleSoft system:



Chapter navigation

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: Crystal Reports for PeopleSoft*

PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise)



---

## Task 11-1: Determining the Crystal Reports Runtime Environment

PeopleSoft applications are delivered to work with the Crystal Reports 9 runtime environment. Process scheduler report definitions are configured to use the Crystal Reports 9 print engine, and the Crystal report definition files delivered by PeopleSoft are in the Crystal 9 format. You use the Crystal Reports 9 product to create and edit report definitions.

If you are using PeopleTools 8.48 *and* are using PeopleSoft applications at Release 9 or higher, you can optionally use the BusinessObjects Enterprise XI runtime environment to run and view your reports. You use the Crystal Reports XI product to create and edit report definitions.

For any particular PeopleSoft application you must use either Crystal 9 or BusinessObjects Enterprise XI—you cannot run a “mixed” environment where some reports are run using Crystal 9 and some reports are run using BusinessObjects Enterprise XI.

If you decide to use BusinessObjects Enterprise XI, you can run a PeopleSoft supplied conversion program to convert report definitions from Crystal 9 format to Crystal XI format. There is no conversion program to convert from Crystal XI format to Crystal 9 format.

The advantages of BusinessObjects Enterprise XI (compared to Crystal Reports 9) are:

- Runs on other operating systems (Solaris, AIX, Linux) besides Windows
- Runs on a scalable server platform; that is, you can scale across machines
- Users can view interaction reports over the web (such as search, filter, or table of contents).

The restrictions of the PeopleSoft Integration with BusinessObjects Enterprise XI are:

- The PeopleSoft Process Scheduler that you use to run reports on the BusinessObjects Enterprise XI server can run only on one of the operating systems that BusinessObjects Enterprise XI runs on.
- You need to convert all your reports from Crystal 9 format to Crystal XI format to run them using BusinessObjects Enterprise XI.
- The PeopleSoft Integration does not support some platforms that a standalone BusinessObjects Enterprise XI installation supports.

That is, not all platforms that BusinessObjects Enterprise XI runs on were tested in the integrated BusinessObjects Enterprise XI/PeopleSoft solution. For example, while standalone BusinessObjects Enterprise XI support Tomcat as a web server, the integrated BusinessObjects Enterprise XI/PeopleSoft solution does not.

The advantages of using Crystal Reports 9 are:

- Works the same as previous releases of PeopleTools
- Requires little configuration and administration
- Run to Crystal Reports 9 from Windows Query Designer is available
- Does not require a database management system for report management
- Report output is smaller in size compared to BusinessObjects Enterprise XI, as the latter contains more internal information about the report.

The observed difference in tests indicates that report output generated from BusinessObjects Enterprise XI will be 30 to 40% larger. This may vary by report and by the amount of business data in the report.

One restriction on Crystal Reports 9 is that it runs only on Windows.

---

## Task 11-2: Installing Crystal Reports 9

This section discusses:

- Understanding the Crystal Reports 9 Installation
- Installing Crystal Reports 9

### Understanding the Crystal Reports 9 Installation

Crystal Reports 9 is packaged with PeopleSoft. The Crystal Reports installation is required for Windows-based workstations (also referred to as the PeopleTools Development Environment) where reports will be designed. Workstations that will only run existing reports via Process Scheduler do not need Crystal Reports. The functionality for running these reports on the client is provided in DLLs that are installed when you run Client Setup in Configuration Manager.

---

**Note.** Depending upon the languages you licensed from PeopleSoft, you may receive more than one Crystal Reports CD-ROM. You should repeat the following installation instructions for each language of Crystal Reports that you plan to use in the PeopleTools Development Environment.

---

---

**Note.** Although some versions of Crystal Reports include web server applications such as Web Component Server, they are not tested, certified, or supported by PeopleSoft.

---

You can install Crystal Reports 9 locally on a workstation where reports will be designed, or on a Windows batch server where Crystal Reports will be executed by Process Scheduler. You can also install Crystal Reports to a network file server; typically it would be installed to a subdirectory of the <PS\_HOME> directory. If you install Crystal Reports to a network file server, you need to run a Crystal Reports setup on each Windows-based workstation or batch server where Crystal Reports will be run. To do so, make sure to select the Complete installation when running the CD setup program.

---

**Note.** When installing Crystal Reports to a Netware file server, the ideal solution is to use Windows as the installation workstation environment. If, however, you are installing Crystal under Windows 95 to a Novell file server, install Crystal on a local drive and then copy the Crystal directory to the Novell server from an MS-DOS command prompt.

---

### See Also

*Enterprise PeopleTools 8.48 PeopleBook: Crystal Reports for PeopleSoft*, “Using Crystal Reports 9”

### Task 11-2-1: Installing Crystal Reports 9

To install Crystal Reports 9:

1. Insert the Crystal CD into your CD-ROM drive and run the setup program from the root of the drive.

---

**Note.** If you are installing to a network, you must run `setup.exe` from the command prompt with the `/a` option, as in `<path>setup.exe /a`.

---

- The install program will search for any previous version of Crystal and then present a Welcome message.
2. Click Next.  
A license dialog box appears.
  3. Select the I accept the License Agreement radio button and click Next.  
A window appears with the possible installation types.
  4. Select the Typical radio button. If necessary, use the Browse button to set your destination folder.
  5. Click Next.  
A screen appears displaying the features you have selected. Review and modify your selections if necessary.
  6. Click Next.  
You are prompted to start the installation or go back to modify any of the information added.
  7. Select Next to begin the installation.  
A progress screen appears.
  8. Select Finish to complete the installation.

---

**Note.** For additional instructions on installing the Crystal Reports CD-ROM, see the Crystal installation documentation, which is delivered in the \DOCS directory of the Crystal Reports CD as install.rtf.

---

---

**Note.** To install Crystal on a local machine but run it from the network, consult the Crystal documentation.

---

---

**Note.** If you are upgrading your system to PeopleTools 8.48 from a version of PeopleTools earlier than an 8.x version, you may have to convert your custom Crystal report definitions to Crystal 9. Please see the section Converting Crystal Reports for additional information and tasks.

If this is not the case, at this point if you are using Crystal 9 you are finished. Ignore the rest of the chapter as it addresses BusinessObjects Enterprise XI exclusively.

---

## Task 11-3: Installing BusinessObjects Enterprise XI


This section discusses:

- Understanding the BusinessObjects Enterprise XI Installation
- Understanding Integration Between BusinessObjects Enterprise XI and PeopleSoft Enterprise
- Understanding Query Access Services
- Reviewing Key BusinessObjects Enterprise XI Components
- Planning your BusinessObjects Enterprise XI Integration
- Installing the PeopleSoft Application Environment
- Installing BusinessObjects Enterprise XI on Windows
- Installing BusinessObjects Enterprise XI Integration on Windows
- Installing Patches Required at Installation Time


- Creating a Web Server for BusinessObjects Enterprise XI on Windows
- Installing BusinessObjects Enterprise XI on UNIX or Linux
- Installing PeopleSoft BusinessObjects Enterprise XI Integration on UNIX or Linux
- Installing Patches Required at Installation
- Creating a Web Server for BusinessObjects Enterprise on UNIX or Linux
- Confirming Access to the BusinessObjects Enterprise XI Administration and User Launchpad Applications
- Configuring the PeopleSoft Application for BusinessObjects Enterprise XI Integration
- Configuring the BusinessObjects Enterprise XI Server
- Verifying the PeopleSoft to BusinessObjects Enterprise XI Integration

## **Understanding the BusinessObjects Enterprise XI Installation**


Use the following flowcharts to understand which parts of this section are relevant to your particular circumstances.



Navigating the BOE XI installation and configuration - Figure 1




Navigating the BOE XI installation and configuration - Figure 2



Navigating the BOE XI installation and configuration - Figure 3


## Understanding Integration Between BusinessObjects Enterprise XI and PeopleSoft Enterprise

PeopleSoft Enterprise, together with Business Objects, provides a robust suite of reporting tools to be used with PeopleSoft products. The diagrams below illustrates how BusinessObjects Enterprise XI integrates with PeopleSoft Enterprise.




Design a report





Run a report



View a report stored in the BusinessObjects Enterprise XI Repository

Implementation of this integration requires:

- installation of BusinessObjects Enterprise XI server
- installation of PeopleSoft-specific components on the BusinessObjects Enterprise server
- configuration tasks in your PeopleSoft database
- configuration tasks in your BusinessObjects Enterprise XI server
- conversion of Crystal report definitions from Crystal 9 format to Crystal XI format.

BusinessObjects Enterprise XI for PeopleSoft Enterprise interacts with PeopleSoft Enterprise security server using a plug-in. This integration provides single signon and ensures the synchronization of users and roles between PeopleSoft Enterprise and BusinessObjects Enterprise XI. Using a data driver that calls the Query Access Services, BusinessObjects Enterprise receives data from PS Query and builds a report using Report Application Server (RAS) API.


## Understanding Query Access Services

The primary goal of Query Access Services (QAS) is to provide streaming PeopleSoft query results to BusinessObjects Enterprise over the web to create Crystal reports.

QAS plays the following roles in BusinessObjects Enterprise XI for PeopleSoft Enterprise:

- Provides a mechanism for the BusinessObjects Enterprise XI to access Query metadata so that users can design Crystal Reports based on the queries.
- Provides a mechanism for the BusinessObjects Enterprise XI to obtain results for a query to be used in report definitions.

The following diagram illustrates the QAS architecture:



Query Access Services architecture

The following sections describe the components in the Query Access Services architecture:

- **Integration Gateway**

The Integration Gateway receives every Simple Object Access Protocol (SOAP) request coming from BusinessObjects Enterprise XI. The Gateway forwards the request to the integration engine running on the web server.

- **Web Server**

The Integration Gateway resides on a PeopleSoft web server that generates the URL to navigate inside BusinessObjects Enterprise. The Integration Gateway receives every SOAP request coming from BusinessObjects Enterprise over HTTP/HTTPS. Using the QueryListening Connector class, results are received directly from the report repository.

- **Application Server**

PeopleCode running on the application server implements most of the QAS services and generates the required response. The integration engine is installed on an application server as part of the PeopleSoft application.

- **Analytic Server**

The Analytic server provides asynchronous query execution. The query engine is embedded in the analytic server. When a query execution request arrives, the PeopleCode delegates the request to one of the available analytic servers running within the same application server domain. The query engine starts executing the query based on the input parameters.

- Result Repository

Once the query engine fetches the first block of results, it encapsulates the results in a well-defined XML format and posts the XML data in the Result Repository.

- BusinessObjects Enterprise XI

When BusinessObjects Enterprise XI makes a request to obtain the XML data from the Report Repository, the request is authenticated and the data is sent directly from the report repository.

## Reviewing Key BusinessObjects Enterprise XI Components

BusinessObjects Enterprise involves the interaction of the following components:

- Central Management Console (CMC)

The Central Management Console (CMC) enables you to perform administrative tasks. Administrative tasks include authenticating users, granting rights to groups, adding domains, mapping PeopleSoft roles with BusinessObjects Enterprise roles, and adding users.

- Security Plugin

The Central Management Server uses the BusinessObjects Enterprise XI security plug-in to verify the user name and password against the system database. In the context of BusinessObjects Enterprise for PeopleSoft Enterprise, the security plug-in enables you to map user accounts and groups from PeopleSoft into BusinessObjects Enterprise XI. The user names and passwords are authenticated against the BusinessObjects Enterprise XI user list that is synchronized with the users and roles in the PeopleSoft database.

## Task 11-3-1: Planning your BusinessObjects Enterprise XI Integration

This section discusses:

- Installing Prerequisite Software
- Configuring UNIX Environment Variables

---

**Note.** These are steps that should be done prior to starting the installation and configuration of PeopleTools and BusinessObjects Enterprise XI. Completing these tasks will make the installation and configuration process proceed smoothly.

---

### Installing Prerequisite Software

Several different alternative software packages are supported for BusinessObjects Enterprise XI. These alternatives are listed in the PeopleTools 8.48 Hardware and Software guide. Additional detailed information on specific release levels supported is available online on Customer Connection.

See *Enterprise PeopleTools 8.48 Hardware and Software Requirements*.

- Operating System

Before you begin to install BusinessObjects Enterprise XI on UNIX or Linux operating systems using terminal emulation, make sure that you are using an X-Windows terminal emulation program.

---

**Note.** You can install BusinessObjects Enterprise XI from the server console or with X-Windows terminal emulation software such as Cygwin. Telnet and ssh clients, such as Putty, will not allow you to install the software properly.

---

- Database Software

BusinessObjects Enterprise XI requires a relational database, which stores report definitions as well as report output. Oracle, DB2 LUW, Microsoft SQL Server, and Sybase are all supported database platforms.

The database server software can run on a different machine in the same network as your installation of BusinessObjects Enterprise XI

Before you begin to install BusinessObjects Enterprise XI, you should identify the database server that you want to use. Make note of the database or schema name, user account name, and password for the database, as you will need this information to complete the BusinessObjects Enterprise XI installation. A database must exist, which will become the Central Management Server database.

---

**Note.** MySQL is not a supported database platform for the integration between PeopleTools and BusinessObjects Enterprise XI.

---

- Database Connectivity Software

BusinessObjects Enterprise XI runs under a web server and requires a database, which stores report definitions as well as report output. In order for BusinessObjects Enterprise XI to communicate with the database software, the appropriate database client connectivity software must be installed on the server running BusinessObjects Enterprise XI.

Before you begin to install BusinessObjects Enterprise XI, install the appropriate database connectivity software on the server where BusinessObjects Enterprise XI will reside.

- Java SDK

If your web application server software does not automatically install the Java SDK as part of its installation process, you must install the J2SE SDK first. Ensure that your machine's PATH environment variable includes the Java SDK bin directory.

- Web Application Server Software

BusinessObjects Enterprise XI runs under a web application server, either Oracle Application Server (OAS), BEA WebLogic, or IBM WebSphere. Before you begin to install BusinessObjects Enterprise XI, install the appropriate web server software on the server where BusinessObjects Enterprise XI will reside.

---

**Note.** You must install BusinessObjects Enterprise XI with the same user account as that used to install the web server software.

---

See “Installing Web Server Products.”

The instructions in this section assume BusinessObjects Enterprise XI is installed on one server machine that is separate from the machine on which you have installed (or will install) the PeopleSoft software.

## Configuring UNIX Environment Variables

To configure environment variables for UNIX platforms:

1. Set the JAVA\_HOME environment variable:

```
JAVA_HOME= java_installDirectory; export JAVA_HOME
```

2. Set LC\_ALL and LANG environment variable to your preferred locale in your login environment. For example:

```
LANG=en_US.UTF-8
LC_ALL=en_US.UTF-8
```

3. Run the `locale` command to verify that all of the related locale environment variables were properly set by LC\_ALL. For example:

```
st-sun17:$ locale
LANG=en_US.UTF-8
LC_CTYPE="en_US.UTF-8"
LC_NUMERIC="en_US.UTF-8"
LC_TIME="en_US.UTF-8"
LC_COLLATE="en_US.UTF-8"
LC_MONETARY="en_US.UTF-8"
LC_MESSAGES="en_US.UTF-8"
LC_ALL=en_US.UTF-8
```

---

**Note.** If the `locale` command does not return values exactly like this, contact your system administrator to set the values properly.

---

## Task 11-3-2: Installing the PeopleSoft Application Environment

Install your PeopleSoft application environment as you normally would. There are special configuration steps that you will have to perform later in order to complete the integration of PeopleSoft with BusinessObjects Enterprise XI.

---

**Note.** In order for the integration between PeopleSoft and BusinessObjects Enterprise XI to work, the PeopleSoft Process Scheduler must be installed on an operating system that BusinessObjects Enterprise XI supports. This is because PSBOERUN.EXE, the PeopleSoft process that calls BusinessObjects Enterprise XI, uses Business Objects-supplied APIs.

---

## Task 11-3-3: Installing BusinessObjects Enterprise XI on Windows

You must log on to the Windows machine as a user included in the Administrator group.

To install BusinessObjects Enterprise XI from the CD:

1. Insert the BusinessObjects Enterprise XI CD into the server machine's CD-ROM drive.
2. Navigate to the CD-ROM's root directory and run `setup.exe`.

---


**Note.** If you are installing from a network, you must run `setup.exe` from the network location.

---

The install program will search for any previous version of BusinessObjects Enterprise XI and then present a Welcome message.

3. Click Next.  
A license dialog box appears.
4. Accept the license agreement.

5. Select Perform Server Installation.




Select Client or Server Installation window

6. Accept the default location for the installation directory or use the Browse button to select another location.

---

**Note.** The folder that you enter here is referred to as the <BOE\_DIR> later in this document.

---



Directory Selection window

7. On the Install Type dialog, select *New* as the installation type.

If you are using the MS SQL Server *and* it is located on the same machine on which you are installing BusinessObjects Enterprise XI, select the Install MSDE or use existing local SQL Server check box.

---

**Note.** MSDE is not supported in the PeopleSoft integration with BusinessObjects Enterprise XI, although SQL Server is supported.


---

---

**Note.** This database will become the BusinessObjects Server database. If Microsoft SQL Server is to be used, the installation wizard creates the BusinessObjects Server database automatically. If you are using another database management system, you must create the database manually prior to installing BusinessObjects Enterprise.

---





Install type window

8. Select Use preinstalled Java application server

---

**Note.** You may see a warning message if the installer is unable to detect a web application server. If you get this message, you should cancel the installation, configure the web server, and then re-start the installation.

---

---


**Note.** The Tomcat application server is *not* supported in the PeopleSoft integration with BusinessObjects Enterprise XI.

---

---

**Note.** The IIS server is not supported in the PeopleSoft integration with BusinessObjects Enterprise XI.


---



Choose Web Component Adapter Type window

9. If you chose as your database a local SQL Server database, you will be prompted for SQL Server Authentication information. Enter the SQL Server Login ID and password.

If a RDBMS other than MS SQL Server is used, proceed to the next step.



Specifying MS SQL Server Authentication

10. If a database other than a local SQL Server database is used, select the appropriate database connection radio button and provide connection information.

The screenshot shows the 'BusinessObjects Enterprise XI Setup' window with the 'CMS Database Information' tab selected. The window prompts the user to 'Please specify the CMS database information'. It features two main sections: 'ODBC Database' and 'Database connection'. In the 'ODBC Database' section, the 'SQL Server (ODBC)' radio button is selected, with fields for 'ODBC DSN' and 'Database', and a 'Select DSN' button. In the 'Database connection' section, the 'Oracle' radio button is selected, and the user is prompted to 'Please enter the logon information for CMS database.' with fields for 'Server' (WSMITH-PC.peoplesoft.com), 'Login ID' (QEDMO), and 'Password' (masked with dots). Navigation buttons at the bottom include '< Back', 'Next >', and 'Cancel'.

CMS Database Information window

11. Click Next on the Start Installation dialog box.


The screenshot shows the 'BusinessObjects Enterprise XI Setup' window with the 'Start Installation' tab selected. The window asks, 'Are you ready to have the Wise Installation Wizard?begin the install?'. Below this, it instructs the user: 'Press the Next button to begin or the Back button to reenter the installation information.' At the bottom, there are three buttons: '< Back', 'Next >', and 'Cancel'. The 'Next >' button is highlighted with a dashed border, indicating it is the recommended action.

BusinessObject Enterprise XI Start Installation window

12. If you are installing BusinessObjects Enterprise XI from CDs, you will be prompted to insert additional CDs to proceed.


If you are installing from a network location, you will not receive these prompts.

The installation proceeds for several minutes.



Installation window

13. When the dialog box appears saying the installation is complete, deselect the check box Launch BusinessObjects Administration Console and click Finish.



Installation complete window

14. Select Start, Programs, Business Objects XI, Business Objects Enterprise, Central Configuration Manager.
15. Highlight Central Management Server and ensure that it is started.

If it is not started, start the server by clicking the start arrow.

After each machine reboot, you may have to start the Central Management Server in the Central Configuration Manager manually.

16. Set the following environment system variables after the BusinessObjects Enterprise XI installation is complete:

---

**Important!** If these system variables are not set, the deployment of the BusinessObjects Enterprise web applications will fail as they are dependent on these environment settings.

---



---

**Note.** <BOE\_DIR> refers to the folder in which you installed BusinessObjects Enterprise XI (for example, C:\Program Files\BusinessObjects\). Substitute your path in the following.

---

- The PATH environment system variable should include:  
     <BOE\_DIR>\BusinessObjects Enterprise 11\win32\_x86
- The CLASSPATH environment system variable should include:  
     <BOE\_DIR>\BusinessObjects Enterprise 11\java\applications\cewcanative.jar

17. Reboot your machine.

## Task 11-3-4: Installing BusinessObjects Enterprise XI Integration on Windows

This task installs the PeopleSoft Security Plugin, Data Driver, and four web application files:


- psadmin.war
- psdesktop.war
- psadhoc.war
- pswebcompadapter.war

This installation takes place on the machine on which you have installed BusinessObjects Enterprise XI.

To install PeopleSoft BusinessObjects Enterprise XI Integration:

1. Log on to your machine as an administrator.
2. Navigate to <PS\_HOME>\setup\PSCrystal and double-click setup.exe.


A welcome window appears:



BusinessObjects Enterprise XI for PeopleSoft Enterprise Integration Installer window

3. Click Next.


If the installer finds Crystal Report or BusinessObjects Enterprise XI installed on your system, it displays the name and version number:



Confirming BusinessObjects Products

**Note.** If the installer cannot find Crystal Reports or BusinessObjects Enterprise XI on your system, it displays an error message. You must exit and install one of these products to continue.


4. Accept the default installation directory on the next window, or click Browse to find another installation directory:



Selecting installation directory for BusinessObjects Enterprise XI Integration


Click Next to continue.

5. Select Typical for the setup type, and click Next to continue:



Selecting setup type on the BusinessObjects Enterprise XI for PeopleSoft Enterprise Integration Installer


6. Confirm that the installation summary is correct, and click Next to continue:



Summary information on the BusinessObjects Enterprise XI for PeopleSoft Enterprise Integration Installer



7. Click Next.  
An indicator shows the progress of your installation.
8. Click Finish to complete the installation:



Completion message on the BusinessObjects Enterprise XI for PeopleSoft Enterprise Integration Installer window

### Task 11-3-5: Installing Patches Required at Installation Time

There may be patches for BusinessObjects Enterprise XI as well as the PeopleSoft Integration for BusinessObjects Enterprise XI that must be installed at installation.

Log onto Customer Connection to check using the Required for Install or Upgrade search page. You can search using the following criteria:

<b>Product Line</b>	PeopleTools
<b>Product</b>	PeopleTools
<b>Release</b>	the release of PeopleTools that you are using

### Task 11-3-6: Creating a Web Server for BusinessObjects Enterprise XI on Windows

This section discusses:

- Creating an Oracle Application Server (OAS) Server on Windows
- Deploying the BusinessObjects Enterprise XI Launchpad Applications for OAS on Windows
- Creating a WebLogic Server on Windows
- Deploying the BusinessObjects Enterprise XI Launchpad Applications for WebLogic on Windows

- Creating a WebSphere Server on Windows
- Deploying the BusinessObjects Enterprise XI Launchpad Applications for WebSphere on Windows

## Creating an Oracle Application Server (OAS) Server on Windows

Before beginning this procedure you must have installed OAS on the server where BusinessObjects Enterprise XI is installed.

1. Change the deployment values for the Java WCA, if you are using Oracle 10g server.
  - a. Stop java application server.

---

**Note.** To stop OAS, use the command `<OAS_HOME>\opmn\bin\opmnctl stopall`.

---

- b. Extract web.xml from pswebcompadapter.war using a tool such as WinZip.

The default location for pswebcompadapter.war is C:\Program Files\Business Objects\BusinessObjects Enterprise 11\java\applications.

- c. Open web.xml with a text editor.
- d. Change “false” to “true” in the following entry:

```
<!-- if you are using oracle10g, turn this flag to true -->
<context-param>
  <param-name>was.oracle</param-name>
  <param-value>false</param-value>
  <description>Reserved.</description>
</context-param>
```

- e. Save web.xml and reinsert into WEB-INF in pswebcompadapter.war.

---

**Note.** Tip: To insert web.xml to WEB-INF using WinZip. Open WinZip. From the Option menu, select Configuration. In the View tab of the Configuration dialog box, ensure that the “Allow all upper case file names” check box is selected. Return to your file directory, right-click the WEB-INF directory that contains your edited web.xml file and select Add to Zip File. Adding the file in this way ensures that it is placed in the correct directory inside the archive.

---

2. Open a browser window and enter the following URL to verify that the OAS server is running correctly:

`http://<machine_name>:<port>`


where <machine name> is the name of the machine on which OAS is installed and <port> is the OAS port number (1810 is the default).

Enter the administrator user name (ias\_admin is the default) and the password that was set during the install.




OAS login dialog box

3. Click on the Start button to launch the server “home”.
4. Click OK after you receive a message that server has been started.
5. Select the Administration tab.



Administration tab

6. Configure the class path:



Class Paths page

- a. Click Global Web Module.
- b. Click the General link under Properties.
- c. Click Add Another Row in the Class Paths section.

- d. Enter the full path, including the filename, for the `cewcanative.jar` file in the path field.  
For example, `<BOE_DIR>\BusinessObjects Enterprise 11\java\applications\cewcanative.jar`, where is the location where you installed BusinessObjects Enterprise XI.
7. Click the Apply button at the bottom of the page, and click OK.
8. On the Administration tab, click the Server Properties link.
9. In the Environment Variables section, click the Add Environment Variable button.
10. To configure the PATH:

Select Name	Value	Append
PATH	E:\Program Files\Business Objects\	<input checked="" type="checkbox"/>

Environment Variables page

- a. Enter `PATH` in the Name field.
  - b. Enter the absolute path to the BusinessObjects Enterprise XI `win32_86` directory in the Value field.  
If you have not changed the default directory for Business Objects, the setting for this field would be `"C:\Program Files\Business Objects\BusinessObjects Enterprise 11\win32_x86"`. If the default path was changed for your installation of BusinessObjects Enterprise XI, modify the path accordingly.
  - c. Select the Append check box.
  - d. Click Apply.
  - e. Click No when you receive the message that the application server must be restarted before the changes take affect. You can restart the server later.
11. On the Administration tab, click the Server Properties link.
  12. To change the memory allocation:

Command Line Options	
Java Executable	
QC4J Options	
Java Options	/config/java2.policy -Djava.awt.headless=true -Xms128m -Xmx512m


Command Line Options page

- a. In the Java Options box, add a space, then append `-Xms128m -Xmx512m` to the existing entry.
- b. Click Apply.
- c. Click Yes when you receive the message that the application server must be restarted before the changes take affect.

## Deploying the BusinessObjects Enterprise XI Launchpad Applications for OAS on Windows


To deploy the Launchpad applications for OAS on Windows:

1. Click the Applications tab from the server home.



Deployed Applications page

2. Click the Deploy WAR file button.
3. Click the Browse button and locate the file <BOE\_DIR>\Enterprise 11\java\applications\pswebcompadapter.war, where <BOE\_DIR> is the location where you installed BusinessObjects Enterprise XI.



Deploy Web Application page

4. Enter *pswebcompadapter* in the Application Name field.
5. Enter */businessobjects* as context root in the Map to URL field.
6. Click Deploy.
7. Repeat steps 1 through 6, but use the following values:
 

<b>File</b>	<BOE_DIR>\Enterprise 11\java\applications\jsfadmin.war
<b>Application name</b>	jsfadmin
<b>Context root (Map to URL)</b>	/jsfadmin
8. Repeat steps 1 through 6, but use the following values:
 

<b>File</b>	<BOE_DIR>\Enterprise 11\java\applications\psadmin.war
<b>Application name</b>	psadmin
<b>Context root (Map to URL)</b>	/businessobjects/enterprise11/adminlaunch
9. Repeat steps 1 through 6, but use the following values:
 

<b>File</b>	<BOE_DIR>\Enterprise 11\java\applications\psdesktop.war
<b>Application name</b>	psdesktop
<b>Context root (Map to URL)</b>	/businessobjects/enterprise11/desktoplaunch

10. Repeat steps 1 through 6, but use the following values:

**File** <BOE\_DIR>\Enterprise 11\java\applications\ psadhoc.war  
**Application name** psadhoc  
**Context root (Map to URL)** /businessobjects/enterprise11/adhoc


**Note.** The file pswebcompadapter.war has to be deployed first, followed by jsfadmin.war and then psadmin.war. The files psdesktop.war and psadhoc.war don't depend on other war files, so they can be deployed at any time.

11. To verify the OAS configuration:

- a. Open a new browser window.
- b. Enter the following URL:

http://<machine\_name>:<port>/businessobjects/enterprise11/adminlaunch

For <machine\_name> and <port> substitute the name of your machine and port.



BusinessObjects Enterprise Administration Launchpad window

- c. Select Central Management Console and log on as administrator (no password) to confirm that you can log in.


## Creating a WebLogic Server on Windows

Before beginning this procedure, you must have installed BEA WebLogic on the server where BusinessObjects Enterprise XI is installed.

**Note.** The web server that you create in this section is not the same as the PeopleSoft Pure Internet Architecture web server. If you want to run both web servers on the same machine, be sure to assign a non-default port number to the BusinessObjects Enterprise XI web server as described below.

1. Select Start, Programs, BEA WebLogic Platform 8.1, Configuration Wizard.


2. Verify that Create a new Weblogic configuration is selected and click Next.  
The Select a Configuration Template window appears.
3. Verify that Basic WebLogic Server Domain is highlighted and click Next.
4. Verify that the Express radio button is selected and click Next.
5. Accept the default user name, enter a password, confirm the password, and click Next.  
For testing, “password” is often used as the password.



Configure Administrative Username and Password window

The Configure Server Start Mode and Java SDK window appears.

6. Accept the defaults and click Next.
7. Enter a meaningful Configuration Name, such as BOE, and click Create.  
A progress indicator appears.



BEA WebLogic Configuration Wizard window

8. Select Done to complete the wizard.

You have now created a web server at the default port 7001. If you want to use a port other than the default port 7001, perform the following steps. This may be useful if you want to run both a PeopleSoft Pure Internet Architecture web server and the BusinessObjects Enterprise XI web server on the same machine.

- a. Open the file C:\BEA\user\_projects\domains\*<mydomain>*\config.xml in Notepad.  
For *<mydomain>*, use the value for Configuration Name in step 7 above.
  - b. Find the text 7001 and replace it with the desired port number.
  - c. Save and exit.
  - d. *<BEA\_port>* will be used to refer to the port number that you are now using. Substitute your specific port number for the default port number 7001 in the following steps.
9. Select Start, Programs, BEA Weblogic Platform 8.1, User Projects, *<mydomain>* (BOE in this example), Start Server.

An MS-DOS window opens. Wait until a message containing the phrase “listening on port *<BEA\_port>*” appears, indicating that the web server is active.

---


**Note.** You perform this step to start the web server. You will need to perform this step after you reboot the machine or close down the WebLogic web server.

---

10. To confirm that you can log in to the web server, enter the URL *http://localhost:<BEA\_port>/console* in a browser.
11. Enter the user name and password for the WebLogic Admin that you entered during your installation of WebLogic.



Click the Sign In button.




WebLogic Server sign in

## Deploying the BusinessObjects Enterprise XI Launchpad Applications for WebLogic on Windows


This procedure assumes that you have logged into the WebLogic web server in a browser.

1. Select the Web Application Modules link.



BEA WebLogic Server home


2. Select Deploy a new Web Application.



Web Applications window

3. Navigate to <BOE\_DIR>\Enterprise 11\java\applications, where <BOE\_DIR> is the location where you installed BusinessObjects Enterprise XI.
4. Select the psadmin.war radio button and click the Target Module button.


This deploys the Administrator Launchpad application.



Deploy a Web Application Module window

5. Accept the defaults on the confirmation window and click Deploy.

The process is complete when the status is shown as “Success.”



Deploy tab on the Web Applications window

6. Select Home to return to the WebLogic web server home page.
7. Repeat steps 1 through 6, but in step 3, select the psdesktop.war radio button to deploy the User Launchpad application.
8. Repeat steps 1 through 6, but in step 3, select the pswebcompadapter.war radio button to deploy the pswebcompadapter.war application.
9. Repeat steps 1 through 6, but in step 3, select the psadhoc.war radio button to deploy the Crystal Reports Explorer application.
10. Repeat steps 1 through 6, but in step 3, select the jfsadmin.war radio button to deploy the Crystal Reports Explorer application.
11. Select Home to return to the WebLogic web server home page.
12. To test the installation, stop and start the web server:
  - a. To stop the server, navigate to C:\BEA\user\_projects\domains\<mydomain>, where <mydomain> is the name you entered in the task Creating a WebLogic Server, and double-click stopWebLogic.cmd.
  - b. To start the server, navigate to C:\BEA\user\_projects\domains\<mydomain>, and double-click startWebLogic.cmd.
13. In a new browser window, enter the following URL:  
 http://<machine\_name>:<port>/businessobjects/enterprise11/adminlaunch/.




BusinessObjects Enterprise Administration Launchpad window

## Creating a WebSphere Server on Windows


Before beginning this procedure, you must have installed IBM WebSphere on the server where BusinessObjects Enterprise XI is installed.

1. Select Start, Programs, IBM WebSphere, Application Server 5.1, Start the Server.  
Wait until the server finishes starting.
2. Select Start, Programs, IBM WebSphere, Application Server 5.1, Administrative Console.
3. Enter *admin* as the User ID and select OK.



WebSphere Application Server login window


4. Expand the Environment node and select the Shared Libraries link:



Selecting Shared Libraries

5. Select New to add a new library.

Enter values for the Name, Classpath and Native Library Path as shown. Then click OK.



Setting up shared libraries for WebSphere web server

**Note.** Remember that before you can use BusinessObjects Enterprise XI, you must complete additional installation and configuration procedures.

## Deploying the BusinessObjects Enterprise XI Launchpad Applications for WebSphere on Windows

This procedure assumes that you have logged into the WebSphere Administrative Console.

1. From the menu on the left, select Applications, Install New Application.
2. Browse to find the file `<BOE_DIR>\Enterprise\java\applications\pswebcompadapter.war`; where `<BOE_DIR>` is the location where you installed BusinessObjects Enterprise XI.
3. Enter `/businessobjects` in the Context Root area.

**Preparing for the application installation**

Specify the EAR/WAR/JAR module to upload and install.

Path: Browse the local machine or a remote server:

☒ Local path:  

☐ Server path:

Context Root: Used only for standalone Web modules (\*.war)

Preparing for the application installation for pswebcompadapter.war


Click Next.

4. Accept all defaults on the next several windows and continue until you see a window with a Finish button.
5. Click the Finish button.

A confirmation window appears with a message similar to the following: “Application pswebcompadapter\_war installed successfully.”

6. Select Manage Applications to see the list of applications.
7. Select the link pswebcompadapter\_war to open its configuration page.
8. Near the bottom, select Libraries.
9. Select Add to add a new library.

WCA should appear automatically. Just select OK to save it.



Adding a new shared library

10. Repeat steps 2 through 9, but use these parameters:

**File** <BOE\_DIR>\Enterprise\java\applications\psadmin.war

**Context Root** /businessobjects/enterprise11/adminlaunch

11. Repeat steps 2 through 9 with these parameters:

**File** <BOE\_DIR>\Enterprise\java\applications\psdesktop.war

**Context Root** /businessobjects/enterprise11/desktoplaunch

12. Repeat steps 2 through 9 with these parameters:

**File** <BOE\_DIR>\Enterprise\java\applications\psadhoc.war


**Context Root** /adhoc

13. Repeat steps 2 through 9 with these parameters:

**File** <BOE\_DIR>\Enterprise\java\applications\jfsadmin.war


**Context Root** /jfsadmin

14. Select the link Save to permanently save all changes.



Saving changes on WebSphere Administrative Console

15. Click the Save button on the confirmation window and wait for the changes to be saved.




Saving changes on the Master Configuration window

To stop the server, select Start, Programs, IBM WebSphere, Application Server 5.1, Stop the Server.

16. To restart the server, select Start, Programs, IBM WebSphere, Application Server 5.1, Start the Server.

17. In a new browser window, enter the following URL for the admin launchpad (where *<machine\_name>* is the computer name):


[http://<machine\\_name>:9080/businessobjects/enterprise11/adminlaunch/](http://<machine_name>:9080/businessobjects/enterprise11/adminlaunch/)



BusinessObjects Enterprise Administration Launchpad window


18. Select the Central Management Console link and enter *administrator* (no password) to confirm that you can log in.





BusinessObject Enterprise Central Management Console Log on window

19. Enter the following URL for the user launchpad (where *<machine\_name>* is the computer name):  
[http://<machine\\_name>:9080/businessobjects/enterprise11/desktoplaunch/](http://<machine_name>:9080/businessobjects/enterprise11/desktoplaunch/)



BusinessObjects Enterprise XI log on window

20. Select the link BusinessObjects Enterprise XI and enter *Administrator* (no password) to confirm that you can log in.

## Task 11-3-7: Installing BusinessObjects Enterprise XI on UNIX or Linux

To install BusinessObjects Enterprise XI on UNIX or Linux:

**Note.** You can perform this installation from the server console or with X Windows terminal emulation software such as Cygwin. Telnet and ssh clients, such as putty, will not allow you to install the software properly.

1. Insert the BusinessObjects Enterprise XI CD into the server machine's CD-ROM drive and run the setup program, *winstall*, from the root of the drive.
2. The install program checks for all required components and displays the missing ones.

\*\*\*\*\*

SunOS: Your system is missing required components:

```
*****
```

```
Missing package: SUNWeu8os (American English/UTF-8 L10N For OS Environment User⇒
Files)
```

```
Missing package: SUNWeuluf (UTF-8 L10N For Language Environment User Files)
```

```
If you continue your installation may not work correctly.
Please press Enter to continue...
```

Ensure all missing components are installed before proceeding.

3. Select the language that you want to install.

```
BusinessObjects Enterprise XI Setup
Please select the current language for the installation
1   -   Dutch
2   -   English
3   -   French
4   -   German
5   -   Italian
6   -   Japanese
7   -   Korean
8   -   Simplified Chinese
9   -   Spanish
10  -   Traditional Chinese
```

4. Select New Installation.

5. Read and accept the license agreement.

6. At the Installation Directory prompt, enter your own path for the installation directory, or press Enter to accept the default one, which is your current directory.

7. Choose User Install at the Install Option prompt.

8. Select New for the Installation Type.

9. The next page prompts you to choose between using an existing database as CMS repository, or installing MySQL as the default repository. Select Use an existing database and press Enter.

---

**Note.** MySQL is not supported in the PeopleSoft integration with BusinessObjects Enterprise XI.

---

10. Choose the type of database (Oracle, DB2 or Sybase) from the list and press Enter.

If prompted, provide the location and connection information for the database, and press Enter.

If prompted “Overwrite existing configuration?”, reply *Y*.

If prompted “Re-initialize database?”, reply *Y*.

11. Select Use an existing Java application server and press Enter.

You will need to configure your web application server after the installation is complete.

12. The final page of the setup program displays the installation directory. Press Enter to complete the installation.

## BusinessObjects Enterprise XI Setup

```

Operation CompletePress [Enter] to go to the⇒
next screen

```

Business Objects products have been successfully installed :

```
/ds2/home/bobje/install
```

```

Please read installation guide for information on how to manually configure⇒
your java application server

```

13. You must manually set the following environment variables after BusinessObjects Enterprise XI is installed. Then run `env.sh`, so that the updated environment variables take effect

```
export CLASSPATH=$CLASSPATH:/$bobje_home/bobje/enterprisell/java/applications⇒
/cewcanative.jar
```

```
export PATH= /$bobje_home /bobje/enterprisell/solaris_sparc:$PATH
```

```
cd /$bobje_home /bobje/setup
. ./env.sh
```

---

**Important!** If these system variables are not set, the deployment of BusinessObjects Enterprise XI web applications will fail as they are dependent on these environment settings.

---

The `ccm.sh` script provides you with a command-line interface to the various BusinessObjects Enterprise XI server components. The installation setup program starts and enables servers automatically. The following information is included for reference.

Action	Command
Go to bobje directory that was created by the installation	<pre>cd &lt;BOE_DIR&gt;/bobje</pre> <p><b>Note.</b> The commands below are run from this directory.</p>
Start all BusinessObjects Enterprise XI servers as daemons	<pre>./ccm.sh --start all</pre>
Enable all BusinessObjects Enterprise XI servers using default ports	<pre>./ccm.sh --enable all</pre>
Stop all BusinessObjects Enterprise XI servers	<pre>./ccm.sh --stop all</pre>
View the help on <code>ccm.sh</code>	<pre>./ccm.sh --help   more</pre>

This completes the installation of BusinessObjects Enterprise XI on UNIX or Linux.

## Task 11-3-8: Installing PeopleSoft BusinessObjects Enterprise XI Integration on UNIX or Linux

This task installs the PeopleSoft Security Plugin, Data Driver, and four web application files:

- `psadmin.war`

- psdesktop.war
- psadhoc.war
- pswebcompadapter.war

To install BusinessObjects Enterprise XI Integration in console mode:

---

**Note.** The console mode installation is typically used on UNIX platforms.

---

1. Enter the following commands, where `<PS_HOME>` is the main PeopleSoft directory, and `<OS>` is the UNIX operating system:

---

**Note.** The notation at the beginning of the second line is “dot-space-dot,” not “dot-dot.”

---

```
cd <PS_HOME>
. ./psconfig.sh
cd setup/PSCrystal
setup.<OS> -console
```

See “Using the PeopleSoft Installer,” Starting the PeopleSoft Installer.

You see the following message:

```
Welcome to the InstallShield Wizard for BusinessObjects Enterprise for People⇒
Soft Enterprise Integration
```

```
The InstallShield Wizard will install BusinessObjects Enterprise for PeopleSoft⇒
Enterprise Integration on your computer.
To continue, choose Next.
```

```
BusinessObjects Enterprise for PeopleSoft Enterprise Integration
PeopleSoft, Inc
http://www.peoplesoft.com
Press 1 for Next, 3 to Cancel or 4 to Redisplay [1]
```

2. Enter `1` for Next to continue.
3. At the prompt:

```
Please enter the BusinessObjects Enterprise XI installation directory [/opt⇒
/crystal] /home/jwong/BOE_AIX/enterprise
```

```
Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]
```

Enter the directory where BusinessObjects Enterprise is installed and then enter `1`.

4. At the prompt:

```
BusinessObjects Enterprise for PeopleSoft Enterprise Integration Install⇒
Location
```

```
Please specify a directory or press Enter to accept the default directory.
```

```
Directory Name: [/home/BusinessObjects/enterprise/PeopleSoft_BOE]
```

Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]

Accept the default location for the BusinessObjects Enterprise Integration installation by pressing ENTER, or enter a new location, then enter */* to continue.

5. At the prompt, choose the Typical setup type:

Choose the setup type that best suits your needs.

[X] 1 - Typical

The program will be installed with the suggested configuration.  
Recommended for most users.

[ ] 2 - Custom

The program will be installed with the features you choose.  
Recommended for advanced users.

To select an item enter its number, or 0 when you are finished: [0]

Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]

Press ENTER twice to accept the default, Typical installation, and continue.

6. Confirm that the installation summary is correct:

BusinessObjects Enterprise for PeopleSoft Enterprise Integration will be⇒  
installed in  
the following location:

/home/BusinessObjects/enterprise/PeopleSoft\_BOE

with the following features:

Native Drivers  
Security Plug-in (Server Side)  
Security Plug-in (Web Content)  
Security Plug-in (Client Side Java Version)

for a total size:

15.8 MB

Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]

Enter */* to continue and begin the installation.

7. You see a message showing the progress of the installation.

8. When the installation is complete, you see the following message:

The InstallShield Wizard has successfully installed BusinessObjects Enterprise⇒  
for  
PeopleSoft Enterprise Integration. Choose Finish to exit the wizard.

Press 3 to Finish or 4 to Redisplay [3]

Enter 3 to finish and exit the installation.

## Task 11-3-9: Installing Patches Required at Installation

There may be patches for BusinessObjects Enterprise XI as well as the PeopleSoft Integration for BusinessObjects Enterprise XI that must be installed at installation.

Log onto Customer Connection to check using the Required for Install or Upgrade search page. You can search using the following criteria:

<b>Product Line</b>	PeopleTools
<b>Product</b>	PeopleTools
<b>Release</b>	the release of PeopleTools that you are using

## Task 11-3-10: Creating a Web Server for BusinessObjects Enterprise on UNIX or Linux

This section discusses:

- Creating an Oracle Application Server on UNIX or Linux
- Deploying the BusinessObjects Enterprise XI Launchpad Applications for OAS on UNIX or Linux
- Creating a WebLogic Server on UNIX or Linux
- Deploying the BusinessObjects Enterprise XI Launchpad Applications for WebLogic on UNIX or Linux
- Creating a WebSphere Server on UNIX or Linux
- Deploying the BusinessObjects Enterprise XI Launchpad Applications on WebSphere

### Creating an Oracle Application Server on UNIX or Linux

Before beginning this procedure you must have installed OAS on the server where BusinessObjects Enterprise XI is installed. You must use the same user account to install OAS and BusinessObjects Enterprise XI.

To create an Oracle Application Server on UNIX or Linux:

1. Change the deployment values for the Java WCA, if you are using Oracle 10g server.
  - a. Stop the java application server if it is running.

---

**Note.** To stop OAS, use the command `<OAS_HOME>/opmn/bin/opmnctl stopall`.

---

- b. Extract web.xml from pswebcomadapter.war with the following command:

```
jar -xf pswebcomadapter.war WEB-INF/web.xml
```

The default location for pswebcomadapter.war is `$bobje_home/bobje/enterprise11/java/applications`.

- c. Open web.xml with a text editor.
- d. Change “false” to “true” in the following entry:

```
<!-- if you are using oracle10g, turn this flag to true -->
<context-param>
```

```

<param-name>was.oracle</param-name>
<param-value>false</param-value>
<description>Reserved.</description>
</context-param>

```

- e. Save web.xml and reinsert it into WEB-INF in pswebcomadapter.war.

To reinsert the updated web.xml, use the following command:


```
jar -uf pswebcomadapter.war WEB-INF/web.xml
```

2. Open a browser window and enter the following URL to verify that the OAS server is running correctly:

`http://<machine_name>:<port>`


where <machine\_name> is the name of the machine on which OAS is installed and <port> is the OAS port number (1810 is the default).

Enter the administrator user name (ias\_admin is the default) and the password that was set during the installation.




OAS login dialog box

3. Click on the Start button to launch the server “home”:
4. Click OK after you receive a message that the server has been started.
5. Select the Administration tab.




Administration tab

6. Configure the class path:



Class Paths page

- a. Click Global Web Module.
  - b. Click the General link under Properties.
  - c. Click Add Another Row in the Class Paths section.
  - d. Enter the full path, including the filename, for the cewcanative.jar file in the path field.  
For example, *\$bobje\_home/bobje/enterprise11/java/applications/cewcanative.jar*, where *\$bobje\_home* is the directory where you installed BusinessObjects Enterprise XI.
7. Click the Apply button at the bottom of the page, and click OK.
  8. On the Administration tab, click the Server Properties link.
  9. In the Environment Variables section, click the Add Environment Variable button.
  10. To configure the PATH:



Environment Variables page

- a. Enter *PATH* in the Name field.



- b. Enter the absolute path to the BusinessObjects Enterprise XI win32\_86 directory in the Value field.  
If you have not changed the default directory for Business Objects, the setting for this field would be "\$bobje\_home/bobje/enterprise11/<OS>". If the default path was changed for your installation of BusinessObjects Enterprise XI, modify the path accordingly.
  - c. Select the Append check box.
  - d. Click Apply.
  - e. Click No when you receive the message that the application server must be restarted before the changes take affect. You can restart the server later.
11. On the Administration tab, click the Server Properties link.
  12. To change the memory allocation:

Command Line Options	
Java Executable	
OC4J Options	
Java Options	/config/java2.policy -Djava.awt.headless=true -Xms128m -Xmx512m

Command Line Options page

- a. In the Java Options box, add a space, then append *-Xms128m -Xmx512m* to the existing entry.
- b. Click Apply.
- c. Click Yes when you receive the message that the application server must be restarted before the changes take affect.

## Deploying the BusinessObjects Enterprise XI Launchpad Applications for OAS on UNIX or Linux

To deploy the Launchpad applications for OAS on UNIX or Linux:

1. Click the Applications tab from the server home.

OC4J: Home

Home Applications Administration

Page Refreshed Mar 3, 2006 2:54:58 PM

Default Application Name [default](#)  
Default Application Path [application.xml](#)

Deployed Applications

[Edit](#) [Undeploy](#) [Redeploy](#) [Deploy EAR file](#) [Deploy WAR file](#)

Select	Name	Path	Parent Application	Active Requests	Request Processing Time (seconds)	Active EJB Methods
<input checked="" type="radio"/>	ADFBCManager	../applications/ADFBCManager.ear	default	0	0.00	0
<input type="radio"/>	BC4J	../applications/BC4J.ear	default	0	0.00	0
<input type="radio"/>	IsWebCacheWorking	../applications/IsWebCacheWorking.ear	default	0	0.00	0

Deployed Applications page

2. Click Deploy WAR file.
3. Click the Browse button and locate the file *\$bobje\_home/bobje/enterprise11/java/applications/pswebcompadapter.war*, where *\$bobje\_home* is the location where you installed BusinessObjects Enterprise XI.

### Deploy Web Application

Select the Web Application (.war file) you wish to deploy. This web application will be wrapped into a J2EE

Web Application

Specify the name you would like this application to be called and the URL to map this web application to.

Application Name

Map to URL

Deploy Web Application page

4. Enter *pswebcompadapter* in the Application Name field.
5. Enter */businessobjects* as context root in the Map to URL field.
6. Click Deploy.
7. Repeat steps 1 through 6, but use the following values:
 

<b>File</b>	<i>\$bobje_home/bobje/enterprise11/java/applications/jsfadmin.war</i>
<b>Application name</b>	jsfadmin
<b>Context root (Map to URL)</b>	/jsfadmin
8. Repeat steps 1 through 6, but use the following values:
 

<b>File</b>	<i>\$bobje_home/bobje/enterprise11/java/applications/psadmin.war</i>
<b>Application name</b>	psadmin
<b>Context root (Map to URL)</b>	/businessobjects/enterprise11/adminlaunch
9. Repeat steps 1 through 6, but use the following values:
 

<b>File</b>	<i>\$bobje_home/bobje/enterprise11/java/applications/psdesktop.war</i>
<b>Application name</b>	psdesktop
<b>Context root (Map to URL)</b>	/businessobjects/enterprise11/desktoplaunch
10. Repeat steps 1 through 6, but use the following values:
 

<b>File</b>	<i>\$bobje_home/bobje/enterprise11/java/applications/psad hoc.war</i>
<b>Application name</b>	psad hoc
<b>Context root (Map to URL)</b>	/businessobjects/enterprise11/ad hoc

---

**Note.** pswebcompadapter.war has to be deployed first, followed by jsfadmin.war and then psadmin.war. psdesktop.war and psad hoc.war don't depend on other war files, so they can be deployed at any time.

---

11. To verify the OAS configuration:
  - a. Open a new browser window.
  - b. Enter the following URL:  
 http://<machine\_name>:<port>/businessobjects/enterprise11/adminlaunch  
 For <machine\_name> and <port> substitute the name of your machine and port.



BusinessObjects Enterprise XI Admin Launchpad window

- c. Click Central Management Console and log on as administrator (no password) to confirm that you can log in.

## Creating a WebLogic Server on UNIX or Linux

Before beginning this procedure, you must have installed BEA WebLogic 8.1 on the server where BusinessObjects Enterprise XI is installed. You must use the same user account to install WebLogic and BusinessObjects Enterprise XI.

1. On the machine where BEA Weblogic 8.1 is installed, run `config.sh` from the `<WEBLOGIC_HOME>/weblogic81/common/bin` directory.
2. Select Create a new WebLogic configuration and press Enter.
3. Select Basic WebLogic Server Domain and press Enter.
4. Run the wizard in express mode.
5. Enter User name and User password on the next page.  
The default value is `weblogic/password`. Press Enter.
6. Select Development mode on Domain Mode Configuration page.
7. Select the Java SDK you installed.
8. Accept the default Target Location and press Enter.
9. Specify the domain name on the final page.

The web server has been created at the default port 7001.

---

**Note.** If you want to use a port other than the default port of 7001, follow the step below. This may be useful if you want to run both a PIA web server and the BusinessObjects Enterprise XI web server on the same machine.

---

- a. Edit the file: `<WEBLOGIC_HOME> /user_projects/domains/<mydomain>/config.xml`
- b. Find the text 7001 and replace it with the port number you want.


- c. Then save the config.xml file and exit.
 

<BEA\_port> will be used to refer to the port number that you are now using. Substitute your specific port number as needed in the following steps.
10. Start the web server by running `startWebLogic.sh` from <WEBLOGIC\_HOME>/user\_projects/domains/<mydomain>
 

Wait until a message containing “listening on port <BEA\_port>” appears. The web server is now started.
11. Confirm that you can log in to the web server. In a browser, enter the URL:
 

`http://<machine_name>:<BEA_port>/console`
12. At the login page, enter the user name and password for the WebLogic admin that you entered during the WebLogic installation, for example, weblogic and password.

Click the Sign In button.




BEA WebLogic Administration Console window for UNIX

If you are logged in this verifies your WebLogic server set up was successful.

## Deploying the BusinessObjects Enterprise XI Launchpad Applications for WebLogic on UNIX or Linux


To deploy the BusinessObjects Enterprise XI Launchpad applications:

1. Click the Web Application Modules link on the BEA WebLogic Server home page:




BEA WebLogic Server Home window for UNIX

2. On the Configuration tab, click the Deploy a new Web Application link:



Web Applications window for UNIX: Configuration tab

3. Navigate to `<BOE_DIR>/enterprise/java/applications`, where `<BOE_DIR>` is the location where you installed BusinessObjects Enterprise XI.



Deploy a Web Application Module window for UNIX


A confirmation window appears.

4. Select the psadmin.war radio button and click the Target Module button.

This deploys the Administrator Launchpad application.

5. Accept the defaults and click Deploy.

The deployment is complete when *Success* is displayed in the Status of Last Action field on the Deploy tab:



Verifying the status on the Web Applications window for UNIX


6. Click the Home button (the house icon at the top).
7. From the BEA WebLogic Server home page repeat steps 1 through 6, but in step 4, select the psdesktop.war radio button to deploy that application.
8. Repeat steps 1 through 6, but in step 4, select the pswebcompadapter.war radio button to deploy that application.

9. Repeat steps 1 through 6, but in step 4, select the `psadmin.war` radio button to deploy that application.
10. Repeat steps 1 through 6, but in step 4, select the `psadhoc.war` radio button to deploy that application.
11. Repeat steps 1 through 6, but in step 4, select the `jfsadmin.war` radio button to deploy that application.
12. Select the Home button.
13. To test the BusinessObjects Enterprise installation, stop and start the web server as follows:
  - a. Navigate to `<BEA_HOME>/user_projects/domain/<mydomain>`, where `<mydomain>` is the name you entered in Creating a WebLogic Server, and run `stopWebLogic.sh`.
  - b. Navigate to `<BEA_HOME>/user_projects/domain/<mydomain>` and run `startWebLogic.sh`.

## Creating a WebSphere Server on UNIX or Linux


Before beginning this procedure, you must have installed IBM WebSphere on the server where BusinessObjects Enterprise XI is installed. You must use the same user account to install WebSphere and BusinessObjects Enterprise XI.

1. Start the WebSphere server by running the command `./startServer.sh server_name`
2. Enter this URL in a browser to invoke the WebSphere Administrative Console:  
`http://<machine_name>:9090/admin/`
3. In the WebSphere Administrative Console window, enter *admin* (or another User ID) and press OK.



WebSphere Application Server login window for UNIX

4. Expand the Environment node and select the Shared Libraries link:



Selecting shared libraries for UNIX

5. Click the New button to add a new library


Enter values for Name, Classpath, and Native Library Path, and click OK. The values for Classpath and Native Library Path will vary depending upon your platform.

<b>Name</b>	WCA
<b>Classpath</b>	<i>\$bobje_home/bobje/enterprise11/java/applications/cewcanative.jar</i>
<b>Native Library Path</b>	<i>\$bobje_home/bobje/enterprise11/solaris_sparc</i>

## Deploying the BusinessObjects Enterprise XI Launchpad Applications on WebSphere

This task assumes that you have logged into the WebSphere Administrative Console as described in the previous section.

1. From the menu on the left, select the Applications, Install New Applications link.



WebSphere Administrative Console



2. Select Server path, and specify the war file to install:  
\$bobje\_home/bobje/enterprise11/java/applications/webcompadapter.war
3. Enter `/businessobjects` in the context root area, and click Next.

Path: Browse the local machine or a remote server:

☐ Local path:  Browse...

☒ Server path:

Context Root: Used only for standalone Web modules (\*.war)

Next Cancel

Preparing for the application installation for webcompadapter.war

4. Accept all defaults on the next several windows and continue until you see a window with a Finish button.
  5. Click the Finish button.
- A confirmation window appears with a message similar to the following: "Application webcompadapter\_war installed successfully."
6. Click Manage Applications to see the list of applications.
  7. Select the webcompadapter\_war link to open its configuration page.
  8. Near the bottom, select the Libraries link.

Additional Properties	
<a href="#">Target Mappings</a>	The mapping of this deployed object (Application or Module) into a target er
<a href="#">Libraries</a>	A list of library references which specify the usage of global libraries.

Additional Properties page

9. Click the Add button to add a new library.
- WCA* should appear automatically. Just click OK to save it.

**New**

Library References specify one or more shared libraries used by this application. [?](#)

Configuration

General Properties

Library Name:

Apply OK Reset Cancel

Adding a new shared library for UNIX

10. Repeat steps 2 through 9, but use these parameters:

**File** *\$bobje\_home/bobje/enterprise11/java/applications/psadmin.war*

**Context Root** */businessobjects/enterprise11/adminlaunch*

11. Repeat steps 2 through 9 with these parameters:

**File** *\$bobje\_home/bobje/enterprise11/java/applications/psdesktop.war*

**Context Root** */businessobjects/enterprise11/desktoplaunch*

12. Repeat steps 2 through 9 with these parameters:

**File** *\$bobje\_home/bobje/enterprise11/java/applications/psadhoc.war*


**Context Root** */adhoc*

13. Repeat steps 2 through 9 with these parameters:

**File** *\$bobje\_home/bobje/enterprise11/java/applications/jfsadmin.war*


**Context Root** */jfsadmin*

14. Select the Save link to permanently save all changes.



Saving changes on WebSphere Administrative Console for UNIX

15. Click the Save button on the confirmation window and wait for the changes to be saved.



Saving changes on the Master Configuration window for UNIX

16. Stop and start the WebSphere server.


## Task 11-3-11: Confirming Access to the BusinessObjects Enterprise XI Administration and User Launchpad Applications

After you have completed the installations, you should confirm that you can access the administration console and User Launchpad. Use this procedure for both the Windows and UNIX/Linux installations.

Before beginning this task, start the web server software under which you installed BusinessObjects Enterprise XI.

1. In a new browser window, enter the following URL for the admin launchpad (where *<machine\_name>* is the computer name and *<port>* is the web server port):

`http://<machine_name>:<port>/businessobjects/enterprise11/adminlaunch/`



BusinessObjects Enterprise XI Admin Launchpad window

2. Select the Central Management Console link and enter *administrator* (no password) to confirm that you can log in.
3. To confirm that you can access the user launch, enter the following URL in the browser address line for the user launchpad (where *<machine\_name>* is the computer name and *<port>* is the web server port):

`http://<machine_name>:<port>/businessobjects/enterprise11/desktoplaunch`


4. Select the link BusinessObjects Enterprise XI and enter the following to confirm that you can log in:

**System** `<machine_name>:6400`

**Username** `administrator`

**Password** `(none)`

**Authentication** `Enterprise`



BusinessObjects Enterprise XI logon window

---

**Note.** Remember that before you can use BusinessObjects Enterprise XI, you must complete additional installation and configuration procedures

---

## Task 11-3-12: Configuring the PeopleSoft Application for BusinessObjects Enterprise XI Integration

This section discusses:

- Preparing the PeopleSoft Application to Integrate with BusinessObjects Enterprise XI
- Running the Data Mover Script and Database Project
- Configuring the PeopleSoft Application Server
- Configuring the PeopleSoft Pure Internet Architecture
- Adding PeopleSoft Users for Integration
- Identifying the Local Default Node in your System
- Adding the Local Default Node as a Message Node to your Gateway
- Configuring Query Access Services
- Configuring Query Access Services Node Security

### Preparing the PeopleSoft Application to Integrate with BusinessObjects Enterprise XI

In the PeopleSoft application that you wish to integrate with BusinessObjects Enterprise XI, you will have to configure settings in the following areas:

- PeopleSoft Application Server
- PeopleSoft Web Server
- PeopleSoft Integration Broker
- Query Access Services (QAS)

## Running the Data Mover Script and Database Project

The PeopleSoft database as delivered is configured to run reports using Crystal 9. In order to use BusinessObjects Enterprise XI you need to run a data mover script and a project.

This will add pertinent roles and change the Crystal process types to use the BusinessObjects Enterprise XI executable.

1. Run Data Mover script CRTOBOE.
2. Run Project CRTOBOE.

## Configuring the PeopleSoft Application Server

To configure the application server:

1. Make sure that your PeopleSoft application server is down.
2. Access the PSADMIN Quick-Configure menu by launching `psadmin.exe` from the `<PS_HOME>\appserv` directory.

Select the domain to configure.

See “Configuring the Application Server on Windows.”

3. Set Analytic Servers (Feature 11) to Yes.

```
-----
Quick-configure menu -- domain: HR84
-----
```

Features =====	Settings =====
1) Pub/Sub Servers : No	15) DBNAME : [HR84]
2) Quick Server : No	16) DBTYPE : [MICROSFT]
3) Query Servers : No	17) UserId : [QEDMO]
4) Jolt : Yes	18) UserPswd : [QEDMO]
5) Jolt Relay : No	19) DomainId : [TESTSERV]
6) WSL : No	20) AddToPATH : [c:\Program Files\Microsoft⇒ SQL Server\80\Tools\Binn]
7) PC Debugger : No	21) ConnectID : [people]
8) Event Notification : Yes	22) ConnectPswd : [people]
9) MCF Servers : No	23) ServerName : []
10) Perf Collator : No	24) WSL Port : [7000]
11) Analytic Servers : Yes	25) JSL Port : [9000]
12) Domains Gateway : No	26) JRAD Port : [9100]

```

Actions
=====
13) Load config as shown
14) Custom configuration
    h) Help for this menu
    q) Return to previous menu

```

Enter selection (1-26, h, or q):

4. Open psappsrv.cfg, the PeopleSoft Application Server configuration file, from the <PS\_HOME>\appsrv\<DOMAIN> directory.
5. Change the MIN Instances and MAX Instances for the Application Server and Analytic Server to be greater than 1. (Of course, the MAX setting should be no less than the MIN setting.)

```
[PSAPPSRV]
;=====
; Settings for PSAPPSRV
;=====

;-----
; UBBGEN settings
Min Instances=2
Max Instances=4
```


6. Re-start the application server.

## Configuring the PeopleSoft Pure Internet Architecture

To ensure that single sign-on works properly in the integration between PeopleSoft and BusinessObjects Enterprise XI the Authentication Token Domain in the PIA architecture must be configured and the PeopleSoft Integration Gateway properties must be set.

1. Run <PS\_HOME>\setup\mpinternet\setup.exe.
2. Enter a value for the Authentication Token Domain.

See “Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode,” Using Authentication Domains in the PeopleSoft Pure Internet Architecture Installation.



Specifying the Authentication Token Domain

## Adding PeopleSoft Users for Integration

To add User QAS\_Admin:

1. Navigate to PeopleTools, Security, User Profiles, User Profiles.
2. Select the Add a New Value tab.
3. Enter QAS\_Admin, and click the Add button.
4. Choose a symbolic id from the drop-down list.
5. Enter QAS\_Admin for password.
6. Select the ID tab.
7. Select *none* for the ID Type.  
Enter “QAS administrative user” for description.
8. Select the Roles tab.
9. Enter QAS Admin, and click the Save button.

To add User BOE\_Admin:

1. Return to the Add a New User page.
2. Select the Add a New Value tab.
3. Enter BOE\_Admin, and click the Add button.
4. Choose a symbolic id from the drop-down list.
5. Enter BOE\_Admin for password.
6. Select the ID tab.
7. Select *none* for ID Type.  
Enter “BOE administrative user” for description.
8. Select the Roles tab.
9. Enter BOE Admin, and QAS Admin, and click the Save button.

To add User BOE\_Viewing:

1. Return to the Add a New User page.
2. Select the Add a New Value tab.
3. Enter BOE\_Viewing, and click the Add button.
4. Choose a symbolic id from the drop-down list.
5. Enter BOE\_Viewing for password.
6. Select the ID tab.
7. Select *none* for ID Type.  
Enter “BOE viewing user” for description.
8. Select the Roles tab.
9. Enter BOE Viewing, and click the Save button.

## Identifying the Local Default Node in your System

After you identify the Local default node, use it in the next procedure.

1. Select PeopleTools, Integration Broker, Integration Setup, Nodes.
2. Click the Search button to display a list of all nodes defined in the system.

There should be one (and only one) node designated as the Default Local Node. You can sort on the Default Local Node column header to quickly find the proper node. Look for the node that has a “Y” in the Default Local Node column in the search results.

The screenshot shows the PeopleTools interface. On the left, the 'Nodes' menu item under 'Integration Broker' is selected. The main area displays 'Search Results' for 'Nodes'. The table below shows the search results:

Node Name	Description	Local Node	Default Local Node	Node Type
H900R23B	PS HRMS - Local Node	1	Y	PIA
HC801EI2	HC801EI2 EIP remote node	0	N	PIA
HC801EIP	HC801EIP EIP remote node	0	N	PIA
HC801SRC	HC801SRC EIP remote node	0	N	PIA
HC831EI2	HC831EI2 EIP remote node	0	N	PIA
HC831EIP	HC831EIP EIP remote node	0	N	PIA
HC831SRC	HC831SRC EIP remote node	0	N	PIA
HC881EI2	HC881EI2 EIP remote node	0	N	PIA
HC881EIP	HC881EIP EIP remote node	0	N	PIA
HC881SRC	HC881SRC EIP remote node	0	N	PIA
HC890EI2	HC890EI2 EIP remote node	0	N	PIA
HC890EIP	HC890EIP EIP remote node	0	N	PIA
HRMS	Portal Node - HRMS	1	N	PIA

Finding the Default Local Node

3. Copy the node name to a text editor, as you will use it in a later step.

See Adding the Local Default Node as a Message Node to your Gateway.

## Adding the Local Default Node as a Message Node to your Gateway

You must update the PeopleSoft Integration Broker Gateway to recognize your PeopleSoft application server.

To add the Local default node:

1. Log onto your PeopleSoft system with a user ID that has rights to access PeopleTools.
2. Select PeopleTools, Integration Broker, Configuration, Gateways.
3. Search and select the Gateway that is designated as the Local Gateway (that is, the Local Gateway check box is selected).
4. In the URL field, enter the following value, where <machine\_name> is the machine where the Integration Broker is installed, and <port> is the port number where the PeopleSoft web server is listening:

http://<machine\_name>:<port>/PSIGW/PeopleSoftListeningConnector

5. Click Save.

You should get a “Loading Process was successful” message.



**Note.** If you are configuring the Gateway for the first time, you get a message prompting you to load connectors. Click OK. You get a confirmation message. click OK again.

## Gateways

**Gateway ID:** LOCAL

☒ **Local Gateway**
☐ **Load Balancer**

**URL:**

[Gateway Setup Properties](#)

Load Gateway Connectors

Connectors		
	*Connector ID	*Connector Class
1	AS2TARGET	AS2TargetConne
2	FILEOUTPUT	SimpleFileTarget
3	FTPTARGET	FTPTargetConne
4	GETMAILTARGET	GetMailTargetCor
5	HTTPTARGET	HttpTargetConne
6	JMSTARGET	JMSTargetConne
7	LDAPTARGET	LDAPTTargetConn

Gateways page

6. Select the Gateway Setup Properties link on this page.

This will take you to a page where you must enter the administrator userid and password.

**Gateways**  
**Gateway Properties**

Sign on to access integrationGateway.properties file.

The default user ID is 'administrator' and the default password is 'password'.

User ID

Password

☐ Change Password

OK Cancel

Gateway Properties sign on window

7. Add a new node in the PeopleSoft Node Configuration page and save.

**PeopleSoft Node Configuration**

URL: http://asp0215.peoplesoft.com:80/PSIGW/PeopleSoftListeningConnector

Gateway Default App. Server

App Server URL	User ID	Password	Tools Release
ASP0215:9000	VP1	***	8.48-801-R1

PeopleSoft Nodes

Message Node Name	Web Server URL	User ID	Password	Tools Release	
BOE_FMS	http://FMSURL:80	BOE_Admin	*****	8.48-801-R1	Ping Node + -

Advanced Properties Page

OK Cancel Save

PeopleSoft Node Configuration page

**Note.** If the proper message node name already exists, you do not have to add it.

Enter the following values:

<b>Message Node Name</b>	The name of the Default Local Node that you had copied to your text editor earlier.
<b>Web Server URL</b>	Enter the URL of the web server that is connected (through Jolt) to your PeopleSoft database's application server
<b>User ID</b>	Enter user BOE_Admin and its password
<b>Password</b>	Enter the password for user BOE_Admin
<b>Tools Release</b>	Provide the precise PeopleTools release that your application server is using.

8. Click Save.  
Click the Ping Node button beside the message node name that you added to confirm success.
9. Click OK.
10. Restart the PeopleSoft web server in order for the configuration file changes to take effect.

## Configuring Query Access Services

To configure Query Access Services (QAS):

1. Select PeopleTools, Query Access Services, Configure.
2. All of the information on the screen is automatically pre-populated.
3. Click the Save button to save the information.

**Query Access Services** | BusinessObjects Enterprise

**Query Access Services Integration Gateway URL**

External Applications use this URL to interface with PeopleSoft Query Access Services (QAS). The URL is derived from the local Integration Gateway URL.

http://<machine name>:<port>/PSIGW/QueryListeningConnector

**QAS URL** http://rh-sun07.peoplesoft.com:7001/PSIGW/QueryListeningConnector/H900F **Ping**

[Edit Integration Gateway URL](#)

**Query Access Services Result Repository URL**

This is where the results of a PeopleSoft Query are placed. The machine name is the same as in the Integration Gateway URL above.

http://<machine name>:<port>/PSIGW/QASRepository/Writer

**URL** http://rh-sun07.peoplesoft.com:7001/PSIGW/QASRepository/Writer/H900R70A **Ping**

**Max Query Size (megabytes)** 500

**Save**

[Query Access Services](#) | [BusinessObjects Enterprise](#)

Query Access Services page

4. Copy the QAS URL entry into a text editor.  
Later when you configure the BusinessObjects Enterprise XI server, you will need to paste this text.
5. Select the BusinessObjects Enterprise tab.
6. Enter the user BOE\_Admin as the Administrative User, and enter its password.

Query Access Services
BusinessObjects Enterprise

BusinessObjects Enterprise

Administrative User
BOE\_Admin

Password
\*\*\*\*\*

Viewing User
BOE\_Viewing

Password
\*\*\*\*\*

BusinessObjects Web Server

This is the location of the BusinessObjects Enterprise (BOE) web server. Enter http:// followed by the machine name and port.

http://<machine name>:<port>

BOE Web Server URL
http://ss-intel12.peoplesoft.com:7001

<http://ss-intel12.peoplesoft.com:7001/businessobjects/enterprise11/admin>
Ping

BusinessObjects Database

This is the location of the BusinessObjects Enterprise (BOE) - Central Management Server (CMS) database. Enter the machine name and port. The BOE Domain Name is optional.

<machine name>:<port>

CMS Machine Name
ss-intel12.peoplesoft.com:6400

BOE Domain Name
BOAPPDB

Specifying Administrative and Viewing users

- Enter the user BOE\_Viewing as the Viewing User, and enter its password.

**Note.** The Administrative User is used by BusinessObjects Enterprise XI to schedule reports. The Viewing User is used to view reports.

- Enter the URL for the BOE web server.
- Enter the <machine\_name>:<port> for the CMS machine name.
- Enter a meaningful name for the BOE Domain Name. Use UPPERCASE and do not use spaces.

Copy this to a text editor as you will use this value in the BOE server setup.

- Click Save to save your settings.

## Configuring Query Access Services Node Security

To configure QAS node security:

1. Navigate to PeopleTools, Integration Setup, Node Definition. Search for node QAS\_REMOTE.
2. Enter user QAS\_Admin and save.
3. Navigate to PeopleTools, Integration Setup, Node Definition. Search for the default local node.
4. Enter user QAS\_Admin and save.

## Task 11-3-13: Configuring the BusinessObjects Enterprise XI Server

To enter PeopleSoft authentication information in BusinessObjects Enterprise XI:

1. In a browser, enter the following URL, substituting the name of your BusinessObjects Enterprise XI server for <machine\_name>, and the BusinessObjects Enterprise XI port number for <BOE\_port>:

`http://<machine_name>:<BOE_port>/businessobjects/enterprise11/adminlaunch/`

---


**Note.** You can also click the Webserver Ping button on the QAS admin page to open the Central Manager Console.

---

2. Log on with *administrator* and no password.

Central Management Console log on

3. On the CMC Home page, click Authentication.



CMC Home page

4. Click the PeopleSoft Enterprise tab.

---

**Note.** If this tab is not present, it means the PeopleSoft Data Driver and Security Plugin have not been installed.

---

See Installing BusinessObjects Enterprise XI Integration on Windows.

See Installing BusinessObjects Enterprise XI Integration on UNIX or Linux.



Authentication page

5. Enter information on this page, then press the Update button at the bottom.

PeopleSoft Enterprise page

Query Access Services Integration Gateway URL page

- Select the check box Enable PeopleSoft Enterprise Authentication.
- In the PeopleSoft Enterprise System User field, enter BOE\_Admin as the user, and enter its password.
- Enter PeopleSoft Enterprise Domain information.

You can have up to one PeopleSoft Enterprise domain listed in the Current PeopleSoft Enterprise Domain box. To add a domain to this box enter the information into the New PeopleSoft Enterprise Domain box and click the Add button.

The value you enter here has two components separated by an equal (“=”) sign. The left-hand side is the name of the domain. This must be the same as the BOE Domain Name that you entered on the QAS configuration page, and that you copied to a text editor.

See Configuring the PeopleSoft Application for BusinessObjects Enterprise XI Integration, Configuring Query Access Services.

The right-hand side is the Query Access Services Integration Gateway URL that you copied into a text editor earlier when you configured the PeopleSoft application (see the second screen immediately above).

- Enter a value in the Default PeopleSoft Enterprise Domain Name field.

This value should match the Domain name specified in the Current PeopleSoft Enterprise Domain (that is, the characters that appear before the equal sign).

---

**Note.** The following three values must be exactly the same for proper configuration:

The BOE Domain Name on the PeopleSoft QAS Configuration page.

The domain portion of the Current PeopleSoft Enterprise Domain in the BOE XI CMC PeopleSoft Enterprise Authentication page.

The Default PeopleSoft Enterprise Domain Name in the BOE XI CMC PeopleSoft Enterprise Authentication page.

---

6. Use the information in the table to fill out these screens:

Mapped PeopleSoft Enterprise Roles page

Options for PeopleSoft Users



PeopleSoft Role	New Alias Options	Update Options	New User Options
BOE Admin	(Choice 1) Assign each added PeopleSoft Enterprise alias to an account with the same name	(Choice 1) New aliases will be added and new users will be created	(Choice 1) New users are created as named users
BOE Viewing	(Choice 1) Assign each added PeopleSoft Enterprise alias to an account with the same name	(Choice 1) New aliases will be added and new users will be created	(Choice 2) New users are created as <i>concurrent</i> users

For each PeopleSoft role in the table:

- a. Enter the role name.


---

**Note.** Enter the role name only. The remaining information (for example, secpsenterprise:R=PSIGW\)) will be pre-pended after you click the Update button at the bottom of the page.

---

- b. Click the Add button.
- c. Select the options indicated in the table.
- d. Click the Update button.

After you add the PeopleSoft roles and update, you will see PeopleSoft Enterprise as a new Authentication Type when you log into the BusinessObjects Enterprise XI Central Management Console:



Authentication Type list

Also, User IDs from the PeopleSoft database with the given roles have been automatically added into BusinessObjects Enterprise XI.

You have completed the installation and configuration. Proceed to run the verification tests in the next section.

## Task 11-3-14: Verifying the PeopleSoft to BusinessObjects Enterprise XI Integration

Use these tests to ensure that the various features of BusinessObjects Enterprise XI are functional:

---

**Note.** Prior to running your verification tests, you need to convert your Crystal Reports from Crystal 9 format to Crystal 11 format. See Converting Crystal Reports for details.

---

1. Schedule and run a Crystal Report
  - a. Login to PeopleSoft as a user who has the authority to run report XRFWIN.
  - b. Select PeopleTools, Process Scheduler, System Process Request.

- c. Select the Add New Value tab.
  - d. Enter a new run control ID of BOETEST, and click the Add button.  
Click the Run button in the Process Request dialog box.
  - e. Select an active process scheduler server.
  - f. Select the check box next to the crystal report XRFWIN.
  - g. Select *Web* for the type and *CE RPT* for the format.
  - h. Click OK to run the report. It should generate a process instance id.
2. View Report output in InfoViewer
    - a. Using the Process Instance ID, ensure the process runs to completion in process monitor.
    - b. Select Reporting Tools, Report Manager, and select the Administration Tab.
    - c. Search for the report using the process instance id generated from step 2.
    - d. Click the Details link next to the report, then the .RPT link to view the report in the BusinessObjects Enterprise XI report viewer.

---

## Task 11-4: Migrating your BusinessObjects Enterprise XI Installation to a New Version of PeopleTools

You must complete several steps in order to ensure that your new version of PeopleTools integrates properly with your BusinessObjects Enterprise XI installation.

---

**Important!** If you fail to perform these steps in the correct order, you could compromise the installation.

---

1. Delete all PeopleSoft Users from the BusinessObjects Enterprise XI server as follows:
  - a. Login to the Central Management Console.
  - b. Select USERS from the navigation drop-down list and click the GO button.
  - c. Click the check box next to all PeopleSoft Users (not administrator or guest) and delete them.
2. Delete Roles in the BusinessObjects Enterprise XI server:
  - a. Login to the Central Management Console.
  - b. Click on the PeopleSoft Authentication tab.
  - c. Delete All the roles. Click Update.
3. Delete the Domains:
  - a. Delete All the Domains. Click Update.
  - b. Click LOGOFF.
  - c. Log back in to the Central Management Console and verify all that the roles and domains are gone.
4. Stop the BusinessObjects Enterprise XI Web Server and all the BusinessObjects Enterprise XI services.
5. Uninstall the PeopleSoft Integration for BusinessObjects Enterprise XI from the server.  
This is the integration that was installed for the old version of PeopleTools.

6. Install the PeopleSoft Integration for BusinessObjects Enterprise XI for the new version of PeopleTools.
7. Run the PeopleSoft Integration installer from the PeopleTools build you installed.
8. Run the verification steps in the task Installing BusinessObjects Enterprise XI, Verifying the PeopleSoft to BusinessObjects Enterprise XI Integration

---

## Task 11-5: Installing Crystal Reports XI

Install Crystal Reports XI only on workstations of those people who:


- will be creating or modifying report definitions
- will be running the conversion program to convert reports from Crystal 9 format to Crystal XI format

Simply running reports does not require installation of Crystal Reports XI.

Before beginning this task, verify that the target workstation meets the minimum system requirements as detailed in the Enterprise PeopleTools 8.48 Hardware and Software Requirements guide.


To install Crystal Reports XI:

1. Insert Crystal Reports XI for PeopleSoft Disk 1.  
It should start automatically. If it does not, run `CRXI_Autorun.exe` from the CD directory.
2. Select your language and click Install.



Crystal Reports XI dialog box

3. Accept the defaults on the following windows.
4. Select Typical installation and, if necessary change the destination folder and common files folder (it is recommended that you accept the defaults).




Select Installation Type dialog box

5. Click Next.


The installation begins. This takes several minutes.

6. Insert Disk 2 and click Next when this message box appears:



Crystal Reports XI Setup dialog box - insert disk

7. The installation proceeds. The installation is complete when this window appears:




Crystal Reports XI Setup dialog box - successful installation

---

**Note.** If there are any product updates, you should install them.

---

8. Click the Finish button. If the following dialog box appears, click Continue.



Wrong volume dialog box

9. Set the PATH environment system variable after the Crystal Reports installation is complete to include:  
`<CR_DIR>\BusinessObjects Enterprise 11\win32_x86`

---

**Note.** <CR\_DIR> refers to the folder in which you installed Crystal Reports XI (for example, C:\Program Files\Business Objects\). Substitute your path.

---

## Task 11-6: Removing Crystal Reports XI

To remove Crystal Reports XI:

1. On the workstation where you installed Crystal Reports XI, select Start, Settings, Add/Remove Programs.
2. Highlight Crystal Reports XI.
3. Select Remove.

It will take several minutes for the removal to finish.

---

## Task 11-7: Administering and Using BusinessObjects Enterprise XI

This section discusses:

- Understanding PeopleSoft Permission Lists, Roles, and Users Involved in PeopleSoft Integration with BusinessObjects Enterprise XI
- Installing Patches
- Changing the Data Source of the BusinessObjects Enterprise XI Report Repository
- Uninstalling BusinessObjects Enterprise XI Integration
- Switching to Crystal 9 from BusinessObjects Enterprise XI
- Using Logging in BusinessObjects Enterprise XI
- Understanding BusinessObjects Enterprise XI License Codes

### Understanding PeopleSoft Permission Lists, Roles, and Users Involved in PeopleSoft Integration with BusinessObjects Enterprise XI

Certain PeopleSoft permission lists, roles, and users are necessary in order to have your PeopleSoft application integrate with BusinessObjects Enterprise XI. To run BusinessObjects Enterprise XI the following need to be present in the PeopleSoft database and then referenced in the appropriate places (described in the installation instructions) in both the PeopleSoft application and BusinessObjects Enterprise XI:

- PeopleSoft Permission Lists
- PeopleSoft Roles
- PeopleSoft Users IDs

The Permission Lists and Roles are added to the PeopleSoft database when you run the CRTOBOE project and CRTOBOE Data Mover script. The PeopleSoft users must be created manually.

---

**Note.** You should use the objects (that is, permission list and roles) as delivered. Do not rename them, delete them or otherwise alter them. This will only complicate and possibly compromise your installation.

---

#### *PeopleSoft Permission Lists:*

The following Permission Lists are inserted into the PeopleSoft database when you run the project CRTOBOE:

- PTPT2200

This is the “QAS Access” permission list. It provides permission to a number of web services related to Query Access Services (QAS).

This permission list is used only by the “QAS Admin” role. When the role is created, this association is already defined.

- PTPT2300

This is the “BOE Viewing” permission list.

### *PeopleSoft Roles*

The three roles listed here work hand-in-hand with the three PeopleSoft users that you need to create. The following Roles are inserted into the PeopleSoft database when you run the project CRTOBOE:

- “QAS Admin”

This role is associated with the QAS\_Admin and BOE\_Admin user IDs. This role (through the permission list associated with it) allows users associated with the role to make QAS web-service calls. Note that the name of this role CANNOT be changed, as it is hardcoded into the QAS web service implementation.

- “BOE Admin”

This role is associated with the BOE\_Admin user ID (which is configured in the PeopleSoft BusinessObjects Enterprise PIA page).

- “BOE Viewing”

This role is associated with the BOE\_Viewing user ID (which is configured in the PeopleSoft BusinessObjects Enterprise PIA page).

### *PeopleSoft Users*

You will have to create 3 PeopleSoft users in the PeopleSoft database. They work hand-in-hand with the three PeopleSoft roles described above. For ease of supportability we strongly suggest that you create the users with exactly the names specified. The users are:

- QAS\_Admin

This user makes QAS web service calls to PeopleSoft from BusinessObjects Enterprise. It is known only within the PeopleSoft application. BusinessObjects Enterprise XI is not aware of this user.

When user BOE\_Admin calls the PeopleSoft application from BusinessObjects Enterprise XI with a request to run a query through QAS, the user is switched programmatically from BOE\_Admin to QAS\_Admin to run the query.

- BOE\_Admin

This user is used:

- to run the Crystal 9 to Crystal XI report convert/publish utility
- by Process Scheduler to run reports in BusinessObjects Enterprise XI

This user is specified in the PeopleSoft BusinessObjects Enterprise PIA configuration page. The user will be created in BusinessObjects Enterprise XI automatically by specifying its corresponding role (that is, “BOE Admin”) in that application. This user is considered a named user in BusinessObjects Enterprise. Additionally, this user must also be in the BusinessObjects Enterprise XI administrators group.

- BOE\_Viewing

PeopleSoft Report Manager logs in to BusinessObjects Enterprise XI Interactive Viewer as this user in order to permit viewing dynamic report output. This user is specified in the PeopleSoft BusinessObjects Enterprise XI PIA configuration page.

The user will be created automatically in BusinessObjects Enterprise XI by specifying its corresponding role (that is, “BOE Viewing”) in that application.

This user id is a concurrent user in BusinessObjects Enterprise XI, which means that each time it logs into BusinessObjects Enterprise XI it will use a BOE concurrent access license.



Please note that multiple end-users (that is, real people) accessing reports concurrently in the BusinessObjects Enterprise XI Interactive Viewer via the PeopleSoft Report Manager will appear from the perspective of the BusinessObjects XI Interactive Viewer to be concurrent logins from the same user – BOE\_Viewing.

## **Task 11-7-1: Installing Patches**

While you may have installed patches for both BusinessObject Enterprise XI and the PeopleSoft Integration for BusinessObject Enterprise XI that were required at installation time, there may be other patches that you need to install after installation.

Check PeopleSoft Customer Connection to see whether there are patches you must install.

Installation instruction for each patch will be included with the patch.

## **Task 11-7-2: Changing the Data Source of the BusinessObjects Enterprise XI Report Repository**


This section discusses:

- Changing the Data Source on Windows
- Changing the Data Source on UNIX or Linux

### **Changing the Data Source on Windows**


Use the steps in this section if you want to change the data source after you have completed the installation and integration.

1. Select Start, Programs, Business Objects XI, Business Objects Enterprise, Central Configuration Manager.
2. Right-click the Central Management Server and choose the Stop option.
3. Right-click the Central Management Server and select Properties.
4. Select the Configuration tab.
5. Click the Specify button in the CMS Data Source area.




Central Management Server Properties dialog box: Configuration tab

6. Select the radio button Select a Data Source and click OK.



CMC Database Setup window

7. Specify whether you want to connect to the production CMS database through ODBC or through one of the native drivers, and then click OK.



Select Database Driver dialog box

- If you select ODBC, the Windows “Select Data Source” dialog box appears.  
Select the ODBC data source that corresponds to your CMS database; then click OK. If prompted, provide your database credentials and click OK.
  - If you select a native driver, you are prompted for your database server name, user id and password.
8. Click OK.  
The SvcMgr dialog box notifies you when the CMS database setup is complete.
  9. Start the Central Management Server.

### Changing the Data Source on UNIX or Linux

Use the steps in this section if you want to change the data source after you have completed the installation and integration.

1. Use the script `ccm.sh` to stop the Central Management Server.
2. Run `cmsdbsetup.sh`.  
When prompted, enter the CMS name or press Enter to select the default one.
3. Type 6 in order to specify source CMS.
4. Select the type of database connection.
5. Enter the database server name, user ID and password.
6. The script notifies you when the setup is complete.

## Task 11-7-3: Uninstalling BusinessObjects Enterprise XI Integration

This section discusses:

- Uninstalling PeopleSoft for BusinessObjects Enterprise XI on Windows
- Uninstalling BusinessObjects Enterprise XI on Windows
- Uninstalling PeopleSoft for BusinessObjects Enterprise XI on UNIX or Linux
- Uninstalling BusinessObjects Enterprise XI on UNIX or Linux

## Uninstalling PeopleSoft for BusinessObjects Enterprise XI on Windows

To remove the BusinessObjects Enterprise XI integration to PeopleSoft Enterprise, you must first uninstall the PeopleSoft for BusinessObjects Enterprise XI integration, then uninstall BusinessObjects Enterprise XI.

1. Select Start, Settings, Control Panel.
2. Select Add/Remove Programs.
3. Select BusinessObjects Enterprise XI for PeopleSoft Integration.
4. Click Remove.

## Uninstalling BusinessObjects Enterprise XI on Windows

After removing the BusinessObjects Enterprise XI integration to PeopleSoft, use these steps to uninstall BusinessObjects Enterprise XI:

---

**Note.** These instructions assume that Crystal Reports XI is not installed on the same machine as BusinessObjects Enterprise XI.

---

1. Select Start, Settings, Control Panel, Add or Remove Programs.
2. Remove Business Objects XI.
3. Remove the following directories:
  - <BOE\_DIR>\Business Objects, where <BOE\_DIR> is the directory where you installed BusinessObjects Enterprise XI. If you accepted the defaults during installation, this is C:\Program Files\Business Objects.
  - <BOE\_DIR>\Common Files\Business Objects
4. Find and delete the following registry keys.

---

**Warning!** Using the Registry Editor incorrectly can cause serious problems that may require you to reinstall the Windows operating system. Use Registry Editor at your own risk. It is strongly advised that you make a backup copy of the registry files (System.dat and User.dat on Win9x computers) before you edit the registry.

---

- HKEY\_LOCAL\_MACHINE\SOFTWARE\Business Objects
  - HKEY\_LOCAL\_MACHINE\Software\Business Objects
  - HKEY\_USERS\S-#-#-##...-####\Software\Business Objects
- The number signs (#) represent a series of numbers that are different on each computer.
- HKEY\_USERS\DEFAULT\Software\Business Objects
5. If you have both Business Objects and Crystal Reports installed on your system, you must also delete the Crystal Reports folders, and delete the Crystal Reports registry key, as described above.
  6. Reboot your system.

## Uninstalling PeopleSoft for BusinessObjects Enterprise XI on UNIX or Linux

To uninstall the BusinessObjects Enterprise XI integration to PeopleSoft on UNIX or Linux, you must first uninstall the PeopleSoft for BusinessObjects Enterprise XI integration, then uninstall BusinessObjects Enterprise XI.

1. Enter the following command, where <BOE\_INTEG\_HOME> is the directory where you installed BusinessObjects Enterprise XI Integration, and <OS> is your database platform:

```
<BOE_INTEG_HOME>/_uninst/uninstallaer.<OS> -console
```

2. At the following prompt, enter *1* for Next to continue:

```
InstallShield Wizard
```

```
Initializing InstallShield Wizard...
```

```
-----
Welcome to the InstallShield Wizard for Integration Kit for PeopleSoft
Enterprise 11.0
```

```
The InstallShield Wizard will uninstall Integration Kit for PeopleSoft
Enterprise 11.0 from your computer.
To continue, choose Next.
```

```
Integration Kit for PeopleSoft Enterprise 11.0
Oracle
http://www.oracle.com
```

```
Press 1 for Next, 3 to Cancel or 4 to Redisplay [1] 1
InstallShield Wizard
```

```
Initializing InstallShield Wizard...
```

```
-----
Welcome to the InstallShield Wizard for Integration Kit for PeopleSoft
Enterprise 11.0
```

```
The InstallShield Wizard will uninstall Integration Kit for PeopleSoft
Enterprise 11.0 from your computer.
To continue, choose Next.
```

```
Integration Kit for PeopleSoft Enterprise 11.0
Oracle
http://www.oracle.com
```

```
Press 1 for Next, 3 to Cancel or 4 to Redisplay [1] 1
```

3. At the following prompt, enter *1* for Next to continue:

```
Select the features for "Integration Kit for PeopleSoft Enterprise 11.0" you
would like to uninstall:
```

```
[x] Integration Kit for PeopleSoft Enterprise 11.0
```

```
To select/deselect a feature or to view its children, type its number:
```

```
1. [x] Native Drivers
```

- 2. [x] Security Plug-in (Server Side)
- 3. [x] Security Plug-in (Web Content)
- 4. [x] Security Plug-in (Client Side Java Version)

Other options:

- 1. Deselect 'Integration Kit for PeopleSoft Enterprise 11.0'
- 0. Continue uninstalling

Enter command [0]

Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1] 1

4. At the following prompt, confirm the directory where BusinessObjects Enterprise is installed and then enter */* for Next to continue:

Integration Kit for PeopleSoft Enterprise 11.0 will be uninstalled from the following location:

/dsl/home/bobje/installation/peoplesoft

with the following features:

Native Drivers  
 Security Plug-in (Server Side)  
 Security Plug-in (Web Content)  
 Security Plug-in (Client Side Java Version)

Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]

5. Confirm the uninstallation is correct and enter 3 to finish:

Uninstalling Integration Kit for PeopleSoft Enterprise 11.0...

-----  
 The InstallShield Wizard has successfully uninstalled Integration Kit for PeopleSoft Enterprise 11.0. Choose Finish to exit the wizard.

Press 3 to Finish or 4 to Redisplay [3]

## Uninstalling BusinessObjects Enterprise XI on UNIX or Linux

After removing the BusinessObjects Enterprise XI integration to PeopleSoft, use these steps to uninstall BusinessObjects Enterprise IX:

1. Disable and stop all of the BusinessObjects Enterprise XI servers.
2. Run the script `$bobje/uninstallBOBJE.sh`.

This script deletes all of the files installed during your original installation of BusinessObjects Enterprise XI.

---

**Note.** You may also notice scripts in the %bobje/uninstall directory. Do not run the scripts in the %bobje/uninstall directory manually. Each of these scripts removes only the files associated with a single BusinessObjects Enterprise XI component, which may leave your BusinessObjects Enterprise XI system in an indeterminate state.

---

3. Remove all of the files in the \$bobje directory by running the command `rm -rf`.  
This removes files that are created during the installation process, or files created by the system or by users after installation, that are not removed by the `uninstallBOBJE.sh` script.
4. If you performed the “system” installation type, you will also need to delete the run control scripts from the appropriate `/etc/rc#` directories.

## Task 11-7-4: Switching to Crystal 9 from BusinessObjects Enterprise XI

Use the instructions in this section if you need to switch your environment back to run Crystal Reports using the Crystal Reports 9 runtime instead of the BusinessObjects Enterprise XI server.

To switch from using BusinessObjects Enterprise XI to Crystal Reports:

1. Run the DMS script `boetocr.dms`
2. Run the project `BOEtoCR`.

Running this script and project will change your delivered Crystal process type back to use Crystal 9.

---

**Note.** This will not change any process types that you created.

---

You cannot run any reports converted to BusinessObjects Enterprise XI format using Crystal Reports. You have to run your original Crystal reports.

## Task 11-7-5: Using Logging in BusinessObjects Enterprise XI

This section discusses:

- Enabling Web Component Adapter Logging
- Enabling BusinessObjects Enterprise XI Server Logging
- Enabling Security Plug-in Logging
- Enabling BusinessObjects Enterprise XI Services Tracing

### Enabling Web Component Adapter Logging

The integration between PeopleSoft and BusinessObjects Enterprise XI requires a special version of the Web Component Adapter. It is delivered as a war file called `pswebcompadapter.war`.

To enable logging:

1. Stop the application server running BusinessObjects Enterprise XI.
2. Extract the `web.xml` file from the `pswebcompadapter.war` archive.
3. Edit the file using a text editor. The relevant entries to edit are:

Context Parameter	Description
Log.file	Filename of the log file including full real path to file, including extension. The default is WCA, with no path.
Log.ext	File extension of log file; the default is .log
Log.isRolling	Determines whether or not the logs will be rotated; the default value is true.
Log.size	If log rolling is turned on, this will govern the maximum size allowed before the log file is rotated. Accepted suffixes: MB, KB, and GB
Log.level	The default log level is “ERROR”  Possible values are: ALL, DEBUG, INFO, WARN, FATAL, ERROR, OFF
Log.entryPattern	This is the log4j Pattern Layout. Log4j is a standard for logging in XML files for Java application servers. It formats logging events according to the pattern specified.  If no value is specified, the entry in the log will display the date, thread, level or priority of the logging event, and the message.  Conversion patterns are composed of literal text and conversion specifiers. Literal text is output as is. Conversion specifiers consist of the % character followed by an optional format modifier and a mandatory conversion character.  For example: %-5p [%t]: %m%n  Please refer to log4j documentation for accepted log patterns.
Log.Flags	Possible values are:  -trace -reqtrace -noassert -stackdump -nativeassert -nonativeassert -notraceoutput -filelogFilter

4. Reinsert the file into the WEB-INF directory in pswebcompadapter.war.

---

**Note.** To reinsert web.xml into WEB-INF using WinZip, right-click on the WEB-INF directory that contains your edited web.xml file and select “Add to Zip File...”. Adding the file in this way ensures that it is placed in the correct directory inside the archive.

---

5. Restart your application server.



When you install more than one WCA, each `pswebcompadapter.war` file contains its own `web.xml` file containing configuration parameters for that WCA.

For more information on configuring the Web Component Adapter please refer to the section in the BusinessObjects Administration Guide, “Configuring the Web Component Adapter.”

## Enabling BusinessObjects Enterprise XI Server Logging

Each of the BusinessObjects Enterprise XI servers is designed to log messages to your operating system’s standard system log.

On Windows, BusinessObjects Enterprise XI logs to the Event Log service. You can view the results with the Event Viewer (in the Application Log).

On UNIX, BusinessObjects Enterprise XI logs to the syslog daemon as a User application. Each server prepends its name and PID to any messages that it logs.

Each server also logs assert messages to the logging directory of your product installation. The programmatic information logged to these files is typically useful only to Business Objects support staff for advanced debugging purposes. The location of these log files depends upon your operating system:

- On Windows, the default logging directory is `C:\Program Files\Business Objects\BusinessObjects Enterprise 11\Logging`.
- On UNIX, the default logging directory is the `<INSTALL_ROOT>/bobje/logging` directory of your installation.

It is important to note that these log files are cleaned up automatically, so there will never be more than approximately 1 MB of logged data per server.

For more information on Logging BusinessObjects Enterprise XI server activity please refer to the BusinessObjects Enterprise Admin Guide Section “Logging Server Activity.”

## Enabling Security Plug-in Logging

The procedure to turn on security plug-in logging varies by operating system.

---

**Note.** Return the log mode to a value of 0 when you do not need logging. Performance will be impacted otherwise.

---

- Windows:

To turn on logging, edit the Windows registry.

```
HKLM\SOFTWARE\Business Objects\Suite 11.0\Integration Kit for PeopleSoft⇒
Enterprise
Log Mode
```

1. Change the Log Mode value from 0 to 1.
2. Restart the services CMS.

This will then generate log files in the directory specified in Path Log. You may want to clean up that directory first, if logging had been turned on before.

- UNIX and Linux:

To turn on logging you need to update the Log Mode setting in the registry file.

The registry file is located at: `<BOE_DIR>/bobje/data/.bobj/registry`

1. Open the file in a text editor and set the value of "Log Mode" to "1".
2. Restart the services (CMS, Job Server, Page Server, Report Application Server). This will turn on the driver/security plug-in tracing.

## Enabling BusinessObjects Enterprise XI Services Tracing

It is also possible to turn on tracing for the BusinessObjects Enterprise XI services. This involves updating the command line for each of the services and adding *-trace* at the end. Depending on the Operating System on which you are running BusinessObjects Enterprise XI the procedure to do this varies.

Remove the *-trace* from the command line after your testing is complete as it can cause performance issues with the servers because of the large number of log files created.

### *Windows:*

1. Log on to the Crystal Configuration Manager with an account with administrative privileges.
2. Highlight the server you would like to enable tracing on and click the Stop button.
3. Double-click the server, add *-trace* to the command line, and click the Start button.

Completing the steps will enable advanced logging on a Crystal Enterprise, Crystal Reports Server, or BusinessObjects Enterprise XI server for Windows.

To review the logs open Windows Explorer and navigate to the logging directory:

*X:\Program Files\Business Objects\BusinessObjects Enterprise 11\Logging*

where X is the drive letter where software was installed.

### *UNIX or Linux:*

1. Go to the \$bobje\$\bobje folder.
2. Edit ccm.config file. Add "-trace" at the end of services that you want to logging.
3. Restart all servers.

The log files write to the \$bobje\$\bobje\logging folder.

## Task 11-7-6: Understanding BusinessObjects Enterprise XI License Codes

Access to BusinessObjects Enterprise XI is based on license codes. There are two types of license codes relevant to BusinessObjects Enterprise XI:

- Named Users licences
- Concurrent Access licences

Named users licenses allow a specific user access to BusinessObjects Enterprise XI. If you are a named user, you have access to BusinessObjects Enterprise XI regardless of how many other users are connected to the system.

Concurrent access licenses allow a certain number of unspecified users access to BusinessObjects Enterprise XI from a pool of users. If you are a concurrent user, you have access to BusinessObjects Enterprise XI only if there are Concurrent Access Licenses that are not being used by other concurrent users.

The OEM license codes delivered by Oracle for the integration between PeopleSoft and BusinessObjects Enterprise allow for:

- 1 Named User license
- 5 Concurrent Access licences

In the context of PeopleSoft applications integrated with BusinessObjects Enterprise XI, the one Named User License is reserved for use by Process Scheduler to schedule reports to be run by BusinessObjects Enterprise XI.

In the context of PeopleSoft applications integrated with BusinessObjects Enterprise XI, Concurrent Access Licenses are used in these ways:

- when a user views a report using the BusinessObjects Enterprise XI Interactive Viewer
- when a user logs into the BusinessObjects Enterprise XI Central Management Console (CMC) directly using a user id set up as a concurrent user

After a user is done viewing the report in either scenario, the Concurrent Access license is then free to be used by another user.

---

**Note.** Viewing a report in Acrobat (pdf) format or in viewers other than the BusinessObjects Enterprise XI Interactive Viewer does not use a Concurrent Access License.

---

A relatively small number of concurrent access licenses can support a large number of users. The number of users that it will support depends on how many reports users view and how long they view them.

It is likely that you will want to purchase additional Concurrent Access licenses to provide greater access for more users. You can do so by contacting your Oracle sales representative.

When you purchase more Concurrent Access Licenses, you will be provided a License Code. You will need to add this License Code to your BusinessObjects Enterprise XI installation.

To enter license codes:

1. In a browser, enter the following URL, substituting the name of your BusinessObjects Enterprise XI server for <machine\_name>, and the BusinessObjects Enterprise XI port number for <BOE\_port>:

`http://<machine_name>:<BOE_port>/businessobjects/enterprise11/adminlaunch/`

---

**Note.** You can also click the Webserver Ping button on the QAS admin page to open the Central Manager Console.

---

2. Log on with *administrator* and no password.



**BusinessObjects Enterprise Central Management Console**

**BusinessObjects Enterprise Central Management Console Log On**

Enter your user name and password, then click Log On.  
(If you are unsure of your account information, contact your system administrator.)

System: PLE-KK0:6400

User Name: administrator


Password:

Authentication Type: Enterprise

Log On Cancel

Central Management Console log on

3. Click License Keys.



**Home**

**Organize**

- Folders
- Objects
- Groups
- Users
- Server Groups
- Servers
- Categories
- Personal Categories
- Inboxes
- Universe Connections
- Universes

**Define**

- Calendars
- Events

**Manage**

- Settings
- BusinessObjects Enterprise Applications
- License Keys
- Authentication

CMC Home page

4. Enter the following license keys:

B1W60 080084G 3SM5U40 0J51 (1 Named User)  
 B1W60 G81084G 3S4PD20 0YD1 (5 User Concurrent Access)

**Note.** As concurrent users access the system to view reports, you may find that the five user concurrent access license is insufficient. If you need more concurrent access licenses, please contact the Oracle Global Support Center for assistance in securing additional licenses.

**BusinessObjects Enterprise Professional Version**

Currently held license keys (Select a key to see its licensing information)

Add Key	<input type="text"/>	<b>Add</b>
B1W60-G81084G-3S4PD20-0YD1 (Product code)		<b>Delete</b>

(Changes take effect immediately - on click of Add or Delete)

**'BusinessObjects Enterprise Professional Version' License Key Information**

	Selected Key	Total Licenses
Named Users:	<input type="text" value="-"/>	<input type="text" value="0"/>
Concurrent Users:	<input type="text" value="5"/>	<input type="text" value="5"/>
Processors:	<input type="text" value="-"/>	<input type="text" value="0"/>
Expires:	<input type="text" value="-"/>	

Entering license keys

- Click Go to return to the home page.

## Task 11-8: Converting Crystal Reports

This section discusses:

- Selecting the Crystal Reports Conversion Method
- Converting pre-PeopleTools 8 Crystal Reports to PeopleTools 8 Crystal Reports
- Converting Reports from Crystal Reports 9 Format to Crystal Reports XI Format

### Selecting the Crystal Reports Conversion Method

This section includes information on converting from Crystal Reports to various formats. You will fall into one of the following scenarios:

- *Scenario 1:*

You are upgrading your PeopleSoft installation to run on PeopleTools 8 and you do not plan to use BusinessObjects Enterprise XI. You will use the Windows-based Crystal Report Print Engine packaged with PeopleTools instead.

You will have to run a conversion program to convert your Crystal reports so that they can run on PeopleTools 8.

See *Converting pre-PeopleTools 8 Crystal Reports to PeopleTools 8 Crystal Reports*.

- *Scenario 2:*

Your PeopleSoft installation is already running on PeopleTools 8 and you want to run your Crystal reports using BusinessObjects Enterprise XI.

You will have to convert your reports from Crystal 9 format to Crystal XI format.

See *Converting Reports from Crystal Reports 9 Format to Crystal Reports XI Format*.

- *Scenario 3:*

You are upgrading your PeopleSoft installation to run on PeopleTools 8.48 from a pre-PeopleTools 8 environment and plan to use BusinessObjects Enterprise XI.

You will have to:

- first run a conversion program to convert your Crystal reports so that they can run on PeopleTools 8;
- then run the conversion program that will convert them from Crystal 9 format to Crystal 11 format.

See the section *Converting pre-PeopleTools 8 Crystal Reports to PeopleTools 8 Crystal Reports*.

Then see the section *Converting Reports from Crystal Reports 9 format to Crystal Reports XI format*.

- *Scenario 4:*

You are upgrading your PeopleSoft installation and are already running your reports on BusinessObjects Enterprise XI.

No report conversion is necessary.

## **Task 11-8-1: Converting pre-PeopleTools 8 Crystal Reports to PeopleTools 8 Crystal Reports**

This section discusses:

- Understanding the PeopleTools RPT Conversion Utility
- Converting RPT Files
- Repairing RPT Files

### **Understanding the PeopleTools RPT Conversion Utility**

The PeopleTools RPT Conversion utility is a standalone program that converts your .rpt files from the format PeopleSoft used in previous releases to the PeopleTools 8 format. You only need to run this program if you are upgrading from previous versions of PeopleTools. This section discusses how to:

- Convert .rpt files
- Repair .rpt files

See the PeopleSoft upgrade guide for your platform.

### **Converting RPT Files**

Before you run the PeopleSoft RPT Conversion utility, you should move your report files to a specific directory. You can then point the conversion utility to that directory.

---

**Note.** You should also back up your report files. If any problem occurs while you run this program, your report files may become corrupted.

---

To run the conversion:

1. Select Start, Programs, PeopleSoft 8, PeopleTools RPT Converter.  
Alternatively, run `pscvtrpt.exe` from `<PS_HOME>\bin\client\winx86`.
2. Accept the default directory or browse to select a new directory.  
The Selected Report directory default is the location of your Crystal Reports as specified in the Configuration Manager. If you wish to convert files in a different location, select the new directory.
3. Select the check box Convert RPT files in subdirectories.  
The database information is automatically removed from older reports that are converted. After the conversion, reports that were successfully converted appear in the Files Converted list box.
4. Select Convert.  
If you have not signed into the PeopleSoft database, you are prompted to do so. After you successfully sign into a database, you can see a progress window.
5. At the prompt “Successful conversion of *x* files. Skipped *x* files,” click OK.  
When the conversion is complete, a Close button is enabled.
6. Select Close.  
Before closing, take note of any .rpt files that failed to convert. This is usually due to read only access.

## Repairing RPT Files

You can use the RPT Conversion utility when you are experiencing problems with a report that has already been converted as part of the upgrade procedure.

---

**Note.** Select the Run Verify Database option first. If the problem is still not resolved, select the Remove database info from current Crystal reports option.

---

To repair RPT files:

1. Select Start, Programs, PeopleSoft 8, PeopleTools RPT Converter.
2. Accept the default directory or browse to select a different directory.  
The Selected Report directory default is the location of your Crystal Reports as specified in the Configuration Manager. If you wish to repair files in a different location, select the new directory.
3. Select either the Run Verify Database or the Remove database info from current Crystal reports check box.  
The Run Verify Database option verifies whether the query information saved in the report is in sync with the query definition.  
When it is complete, reports that were current and had the database information removed appear in the Files Converted list box, with a \* to the left of the report name.
4. Select Convert.  
A progress window appears.
5. At the prompt “Successful conversion of *x* files. Skipped *x* files,” click OK.

When the conversion is complete, a Close button is enabled.

6. Select Close.

Before closing, take note of any .rpt files that failed. This is usually due to read-only access.

## Task 11-8-2: Converting Reports from Crystal Reports 9 Format to Crystal Reports XI Format

This section discusses:

- Understanding the Conversion from Crystal Reports 9 to Crystal Reports XI
- Preparing for Conversion of Crystal 9 Reports
- Running the Conversion
- Verifying the Conversion and Publish
- Reviewing Common Conversion Errors and Warning Messages

### Understanding the Conversion from Crystal Reports 9 to Crystal Reports XI

The PeopleTools RPT Conversion utility pscrconv.exe is a program that converts your Crystal Reports .rpt files from the format that PeopleSoft used in previous PeopleTools 8.x releases to the PeopleTools 8.48 format for use with Crystal Reports XI. This utility also publishes the converted Crystal Reports files by moving them into the BusinessObjects Enterprise Repository so that they can run in the PeopleSoft database.

---

**Note.** The PeopleTools RPT Conversion Utility is not intended to be run on reports with non-PeopleSoft data sources.

---

#### *Overview of the Conversion and Publish Processes*

There are two key processes:

- Converting report definition files from Crystal 9 format to Crystal XI format
- Publishing Crystal XI report definition files into the BusinessObjects Enterprise XI Report Repository


In order to run reports using BusinessObjects Enterprise XI through PeopleSoft, the Crystal Reports XI report definitions must reside in the BusinessObjects Enterprise XI Report Repository.

You can perform each process individually or both together. Here are some examples that might make this clear:

- In a development environment you might run convert and publish together to populate your development environment.
- In a test environment you may want to run the conversion by itself, and then run the publish process multiple times in order to publish the same reports to different test environments.

Here is a diagram that illustrates conversion and publishing:





PeopleTools conversion or publish process

### *Understanding Report Conversion*

The conversion process performs the following:

- Prompts the user for inputs:
  - PeopleSoft sign-on information
  - The action that they would like to take
  - Source folder with Crystal Reports 9 report definition files
  - Destination folder for Crystal Reports XI report definition files
- For each report to be converted in the source folder the program:
  - Reads a Crystal 9 report from a folder
  - Runs a Verify Database on that report
  - Removes database information from the report definition and verifies whether the query information saved in the reports is in sync with their query definitions.

- For every field on the report the program determines the name by which QAS recognizes it.

The program identifies all the possible field names that could be used in a report (as either a selected field, parameter field, expression field) and then provides the name QAS will use for those same fields.

- Calls a Business Objects-supplied conversion routine to convert report definition contents from Crystal 9 format to Crystal XI format
- Runs a Verify Database on the converted report definition

### *Understanding Report Publishing*

Report publishing can be accomplished by:

- Publishing reports automatically after converting them
- Publishing reports in a separate execution of the program

If you are publishing Crystal XI report files for the first time to the BusinessObjects Enterprise XI Report Repository for a PeopleSoft database, folders are created in the BusinessObjects Enterprise XI Repository under the database name. Report definitions must be published for each PeopleSoft database for which you plan to run reports. Published report definitions cannot be shared across databases. BusinessObjects Enterprise XI security on these folders is set with full access granted to the BusinessObject Enterprise Administrative User (BOE\_Admin) identified on the PeopleTools, Query Access Services, Configure, BusinessObject Enterprise page. Read access is granted to individual users.

The publish process:

- Requires login information for the administrative PeopleSoft user (user BOE\_Admin)
- Requires as input the user for the source folder with Crystal XI reports
- Stores (publishes) the converted report in the BusinessObjects Enterprise XI Report Repository
- Updates information in the PeopleSoft Report Manager so that the Report Manager is aware of the report definitions in the BusinessObjects Enterprise XI Report Repository

---

**Note.** If you publish a report that has been previously published to the BusinessObjects Enterprise XI Repository for a PeopleSoft database, the earlier version will be overwritten.

---

In order to successfully convert and publish you must have the following environment in place:

- A properly installed BusinessObjects Enterprise XI server
- A properly installed PeopleSoft application (database and application server)
- Integration between the PeopleSoft application and the BusinessObjects Enterprise XI server properly installed and configured
- A designated machine on which you will run the conversion program

See the PeopleSoft upgrade guide for your platform.

## **Preparing for Conversion of Crystal 9 Reports**

Before running the conversion, there are several steps you must complete.

To prepare the conversion workstation:

1. Confirm the Operating System of the workstation.

The conversion program must be run on a machine that is running Windows 2000, Windows Server 2003, or Windows XP.

2. Confirm access to the PeopleSoft application.

The workstation must have connectivity to the PeopleSoft application (that is, you can log on to the application through the PeopleSoft logon page).

3. Confirm access to the BusinessObjects Enterprise XI application.

The workstation must have connectivity to the BusinessObjects Enterprise XI application. Users can verify connectivity by bringing up the BusinessObjects Enterprise XI server CMC (management console) on the workstation.

4. Install PeopleTools on the workstation.

The way to install the conversion program on the conversion workstation is to simply install PeopleTools on the workstation. PSCRCONV.EXE is one of the files installed on the machine.

5. Install Crystal Reports XI on the workstation.

Install the latest version of Crystal Reports XI and any hotfixes. Crystal Reports XI will install certain dynamic link libraries that are required for the installation program.

6. Perform a PeopleTools Workstation Installation on the workstation.


The conversion program (specifically, the portion of the conversion program supplied by Business Objects), performs a “Verify Database” on each Crystal 9 report definition to be converted. “Verify Database” requires the PeopleSoft ODBC driver. PeopleSoft ODBC driver requires the PeopleTools workstation installation in order to remove the pipe character ‘|’ which would otherwise cause the Crystal Report XI report resulting from conversion to fail creation within BusinessObjects Enterprise XI environment.

Do this by navigating to Start, Programs, PeopleSoft 8, Configuration Manager and selecting the Client Setup tab. Alternatively, run `pscfg.exe` from `<PS_HOME>\bin\client\winx86`.

7. Install PSODBC on the Workstation.

PSODBC provides connectivity between Crystal 9 reports and the PeopleSoft application database.

The PSODBC ODBC driver can be installed by navigating to Start, Programs, PeopleSoft 8, Configuration Manager and selecting the Client Setup tab. Alternatively, run `pscfg.exe` from `<PS_HOME>\bin\client\winx86`.



PeopleSoft Configuration Manager Client Setup tab

To confirm the PeopleSoft Application environment:

1. Confirm the application version of the database and application version of the Crystal 9 Reports.

The PeopleSoft database that you have must be associated with the Crystal 9 reports that you want to convert. That is, the database must have the queries that the Crystal 9 reports access. And the application version of the database must match the application version of the reports that you plan to convert.

2. Verify that the user that will convert the reports has Query access for all the reports that you are planning to convert.

The simplest way to do this is to assign user BOE\_Admin the “PeopleSoft Administrator” role. That role allows the user access to run all queries. To assign this role to BOE\_Admin:

- a. Log onto PIA and navigate to PeopleTools, Security, User Profiles.
- b. Open the User Profile for BOE\_Admin and go to the “Roles” tab.
- c. If not already present in the list of Roles, add Role “PeopleSoft Administrator” to the roles assigned to BOE\_Admin and save the page.


---

**Note.** The PeopleSoft Administrator Role should be removed from BOE\_Admin as soon as you are done converting reports to minimize security concerns.

---

- d. Run the process to update the Query Access List Cache.

Select PeopleTools, Security, Query Security, Query Access List Cache. On the Query Access List Cache page, verify that the radio button Enable Access List Cache is selected, and click the Run button to run the process.



Query Access List Cache page

- e. If you do not want to assign the PeopleSoft Administrator Role to user BOE\_Admin, there are two options:

Run the conversion by running the conversion program logged on as a PeopleSoft user who does have the “PeopleSoft Administrator” role assigned to it.

or

Manually assign query security to user BOE\_Admin such that BOE\_Admin has security access to all queries used in Crystal reports. This can be time consuming and error prone, however.

3. Confirm the integrity of the PeopleSoft application database.

Verify the integrity of the PeopleSoft application database by running SYSAUDIT.SQR on the database. In particular, there should be no anomalies in the database as regards Query definitions (SysQuery-01 through SysQuery-26). For more information on SYSAUDIT.SQR refer to *Enterprise PeopleTools 8.48 PeopleBook: Data Management*.

4. Turn logging levels to low.

Excessive logging will slow the conversion process. Make sure that you have logging for the application server, PeopleCode, SQL, and Integration Broker set to Low levels. If you experience problems while executing the conversion process, you can selectively increase logging to get better diagnostic information.

5. Confirm your BusinessObjects Enterprise XI environment and integration with PeopleSoft.


The conversion program relies on having a properly installed and configured BusinessObjects Enterprise XI so that the converted report definitions can be inserted in the BusinessObjects Enterprise XI repository. There are no special steps in this section that are not part of the basic installation steps covered elsewhere in this installation guide.

## Running the Conversion

To run the conversion:


1. Run `pscrconv.exe` from `<PS_HOME>\bin\client\winx86` directory.
2. Sign into the PeopleSoft database, if you have not already done so. Log in as user BOE\_Admin.

Ensure that log into the correct database for the reports that you are converting. For example, do not sign into a Human Resources database if the reports were created against a Financials database.



PeopleSoft database signon dialog box

3. Choose the action that you wish to perform.



Crystal 9 to Crystal 11 Conversion window

- Converting reports without publishing them to the BusinessObjects Enterprise XI report repository allows you to go from running Crystal Reports 9 report definitions to running Crystal Reports XI report definitions using Crystal Reports XI on a client machine. The converted reports will be stored in a directory that you specify a little later. Converting without publishing is useful in a demonstration environment where you wish to publish reports to a production or development environment at a later time.
- Converting reports and publishing them to the BusinessObjects Enterprise XI report repository allows you to go from running Crystal Reports 9 report definitions to running Crystal Reports XI report definitions using BusinessObjects Enterprise XI via the PeopleSoft Process Scheduler.
- If you choose to Publish Reports to the repository, you are publishing to the Report Repository report definitions that have already been converted to Crystal Reports XI format.

4. Select a report input directory and click OK.


The report input directory must contain a subdirectory that is identified by a language code; the reports to be converted reside in this subdirectory.

---

**Note.** If you chose the Publish Converted Reports to Repository process option in the previous step, you do not see this dialog box.


---

For example, select C:\PT848\CRW if the reports to be converted are located in C:\PT848\CRW\ENG.



Directory selection for the Crystal 9 to Crystal 11 Conversion

5. Select a report output directory for the converted reports and click OK.



Output directory for Crystal 9 to Crystal 11 Conversion


This can be any writable folder, however it cannot be a subfolder of the report input directory. For example, if the reports to be converted are located in C:\\PT848\\CRW\\ENG, the report output directory cannot be C:\\PT848\\CRW\\NEW.

The conversion program will create an appropriate language subdirectory in which the converted reports will be placed. Therefore, if you want your converted reports to be placed in C:\\PT848\\Converted\\ENG, enter C:\\PT848\\Converted as the report output directory.

6. Review the information on the summary screen.


If all looks good, click the Start button to begin the process. Clicking Cancel will cause you to exit from the program.





Summary information for Crystal 9 to Crystal 11 Conversion

A window appears indicating that the conversion is processing. Once the process is complete, a summary details information about the execution. This information is also written to the <PS\_HOME>\bin\client\winx86\pscrconvsum.log file.



Progress indicator for Crystal 9 to Crystal 11 Conversion

7. Click the Finish button.

## Verifying the Conversion and Publish

Use these steps to verify that your reports converted properly are:

1. Review the conversion logs.

Two log files are generated every time the conversion is run.

**PSCRCONVSUM.LOG** the summary log

**PSCRCONV.LOG** the detailed log

These files will be found in the working folder (generally this will be your \client\bin folder).

---

**Note.** These files will be overwritten each time you run the conversion program. If you want to save the logs from a previous run, rename them before you run the process.

---

The log files will contain information about the conversion for all reports that you submitted for conversion in that execution of the conversion program.

- a. Review the Summary conversion log, PSCRCONVSUM.LOG.

The fastest way is to search the summary log for “Error” and “Warn”. If no reports had error or warnings then the conversion was successful. If an error or warning condition is indicated on the summary log, proceed to the next step to check the detailed log.

Here is a sample summary conversion log:

```
Completed conversions -----
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): ----- =>
Completed conversions -----
-----
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): -----=>
=>
-----
A total of 13 reports are converted.
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): A total of 13 reports=>
are converted.

Fri Jan 20 13:24:31 2006 - --- INFO --- (convert):
13 reports converted successfully:
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): 13 reports converted=>
successfully:
C:\pt848801i1\CRW\ENG\XRFAPFL.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG=>
\XRFAPFL.RPT
C:\pt848801i1\CRW\ENG\XRFFLPC.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG=>
\XRFFLPC.RPT
C:\pt848801i1\CRW\ENG\XRFFLPN.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG=>
\XRFFLPN.RPT
C:\pt848801i1\CRW\ENG\XRFFLRC.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG=>
\XRFFLRC.RPT
```

```

C:\pt848801i1\CRW\ENG\XRFIELDS.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG⇒
\XRFIELDS.RPT
C:\pt848801i1\CRW\ENG\XRFMENU.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG⇒
\XRFMENU.RPT
C:\pt848801i1\CRW\ENG\XRFPANEL.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG⇒
\XRFPANEL.RPT
C:\pt848801i1\CRW\ENG\XRFPCFL.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG⇒
\XRFPCFL.RPT
C:\pt848801i1\CRW\ENG\XRFPNPC.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG⇒
\XRFPNPC.RPT
C:\pt848801i1\CRW\ENG\XRFRFCFL.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG⇒
\XRFRFCFL.RPT
C:\pt848801i1\CRW\ENG\XRFRCPN.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG⇒
\XRFRCPN.RPT
C:\pt848801i1\CRW\ENG\XRFWIN.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG⇒
\XRFWIN.RPT
C:\pt848801i1\CRW\ENG\XRFWNFL.RPT
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): C:\pt848801i1\CRW\ENG⇒
\XRFWNFL.RPT
0 reports converted with warnings:
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): 0 reports converted with⇒
warnings:
0 reports failed to convert:
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): 0 reports failed to⇒
convert:

Fri Jan 20 13:24:31 2006 - --- INFO --- (convert):
-----
Fri Jan 20 13:24:31 2006 - --- INFO --- (convert): -----⇒
⇒
-----

```

b. If necessary review the detailed conversion log, PSCRCONV.LOG

It is not necessary to perform this step if the summary conversion log indicates that all reports converted successfully.

The detailed log contains three types of messages:

```

INFO
WARN
ERROR

```

You need to eliminate all ERROR messages. The best policy is to understand why all WARN messages are generated and eliminate them if you can.

Here's a portion of the detailed log that illustrates a successfully converted report:

```
...
...
Converting the report "C:\pt848801i1\CRW\ENG\XRFAPFL.RPT".
Fri Jan 20 13:29:46 2006 - --- INFO --- (convert): Converting the report "C:⇒
⇒
\pt848801i1\CRW\ENG\XRFAPFL.RPT".
Fri Jan 20 13:29:46 2006 - --- INFO --- (verify ): Verifying the report⇒
before conversion.
Fri Jan 20 13:29:46 2006 - --- INFO --- (verify ): Successfully verified⇒
the report.
Fri Jan 20 13:29:50 2006 - --- INFO --- (convert): Successfully converted⇒
report "C:\pt848801i1\CRW\ENG\XRFAPFL.RPT" to target "c:\cnew\ENG⇒
\XRFAPFL.RPT".
...
...
```

If a report has one or more ERROR messages associated with it, it failed conversion. If a report has only WARN and INFO messages associated with it, it passed conversion and will run. The WARN messages may indicate some changes you may want to make to the report definition.

See [Reviewing Common Conversion Errors and Warning Messages](#).

## 2. Re-run the conversion on the altered reports

After you have made changes to address the ERRORS and WARNs, re-run the conversion program. You should exclude from this execution of the conversion program any reports that were successfully converted in prior executions.

## 3. Verify report publishing.

To verify that the reports published properly, launch the BusinessObjects Enterprise XI Admin Console (on Infoview) and locate the shared folder with the database name you used to publish. Ensure that the number of reports with the datetime of the Publish process matches the number of Crystal Reports XI report definition files that you wanted to publish.

## 4. Run the converted reports.

For final verification that the reports you converted are correct, you should run the converted reports and compare their output to their unconverted (that is, Crystal 9) counterparts. You should compare them for equivalent layouts and equivalent data.

To run the report in BusinessObjects Enterprise XI InfoView:

- a. Log onto BusinessObjects Enterprise XI Infoview with user BOE\_Admin.
- b. Use search edit box at top to find the report that you want to run.
- c. In the search results choose the report.
- d. Enter report parameters, if any, and the report displays.

## Reviewing Common Conversion Errors and Warning Messages

Here are some conversion errors that you may encounter as you convert your reports. For each we suggest possible ways to address the problem.

- **ERROR** — Failed to update the data source of table *[datasource(table name)]* to QUERY.*[query name]*

For example:

```
Converting the report "C:\M\CRWFDM\ENG\FORA003-.RPT".
Fri Jan 13 18:10:00 2006 - --- INFO --- (convert): Converting the report "C:\M\
\CRWFDM\ENG\FORA003-.RPT".
Fri Jan 13 18:10:00 2006 - --- INFO --- (verify ): Verifying the report before⇒
conversion.
Fri Jan 13 18:10:00 2006 - --- INFO --- (verify ): Successfully verified the⇒
report.
Fri Jan 13 18:10:01 2006 - --- ERROR --- (convert): Failed to update the data⇒
source of table EB_EAB(EB_EAB_GEN0) to QUERY.EB_EAB.
```

Things to check:

- Does the offending query exist in the database?
- Does the PeopleSoft user doing the conversion (that is, the PeopleSoft user that you provided to the conversion program) have security in the PeopleSoft database to access the query?
- **WARN** — Encountered a duplicate table *[table name]*. Skipping element.

**WARN** — Encountered an element "field" within an invalid "table" element. Skipping element.

For example:

```
Thu Jan 19 11:07:29 2006 - --- INFO --- ( parse ): -----⇒
⇒
-----
Thu Jan 19 11:07:29 2006 - --- INFO --- ( parse ): ----- Reading⇒
command file -----
Thu Jan 19 11:07:29 2006 - --- INFO --- ( parse ): -----⇒
⇒
-----
Thu Jan 19 11:07:29 2006 - --- INFO --- ( parse ): Parse commands from file⇒
pscrconv.xml
Thu Jan 19 11:07:29 2006 - --- WARN --- ( parse ): Encountered a duplicate⇒
table WFA0001_AVERAGES_BY_BP_WL. Skipping element.
Thu Jan 19 11:07:29 2006 - --- WARN --- ( parse ): Encountered an element⇒
"field" within an invalid "table" element. Skipping element.
Thu Jan 19 11:07:29 2006 - --- WARN --- ( parse ): Encountered an element⇒
"field" within an invalid "table" element. Skipping element.
Thu Jan 19 11:07:29 2006 - --- WARN --- ( parse ): Encountered an element⇒
"field" within an invalid "table" element. Skipping element
```

These two warnings are often seen together. They can be generated when two reports being converted in the same execution of the conversion program use the same query.

There is no need to take action on these warnings.



## CHAPTER 12A

# Compiling COBOL on Windows

This chapter discusses:

- Understanding COBOL
- Prerequisites
- Compiling COBOL Source Files
- Distributing COBOL Binaries

---

## Understanding COBOL

This chapter describes how to compile and link PeopleSoft COBOL batch programs, if necessary.

COBOL is not needed for PeopleTools because the Process Scheduler has been re-written in C++. In addition, COBOL is not required for applications that contain no COBOL programs. See Supported Platforms on Customer Connection for the details on whether your application requires COBOL.

See “PeopleSoft Application COBOL Requirements,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise, By PeopleTools release, Platform Communications by Topic, Batch).

For more details about running COBOL in Unicode, consult the following.

See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*, “Running COBOL in a Unicode Environment.”

---

## Prerequisites

Before you attempt to run COBOL from the command line you should do the following:

- For UNIX and Windows systems, make sure the variable PS\_SERVER\_CFG points to a valid pspres.cfg file.
- For Windows systems, make sure %PS\_HOME%\bin\server\winx86 is in your path. It should appear before %PS\_HOME%\bin\client\winx86 if that also appears in the path.

## Task 12A-1: Compiling COBOL Source Files

This section discusses:

- Understanding COBOL Compilation
- Compiling COBOL with CBLBLD.BAT
- Compiling COBOL with CBLMAKE.BAT
- Defining the GNT and INT Files

### Understanding COBOL Compilation

With PeopleTools 8.4, your COBOL always needs to be compiled on Windows. (This is a change from previous versions of PeopleTools, which delivered compiled COBOL for Windows.) This chapter assumes that you are carrying out the compile from your file server. (The COBOL compiler itself doesn't need to be on the file server, as long as the user can write to the file server and can link to the src and bin directories.) PeopleSoft's recommended approach is to use CBLBLD.BAT to compile all your COBOL at once. Another alternative is CBLMAKE.BAT, which you can use to compile selected COBOL files.

Make certain to check whether you need to apply any late-breaking patches.

See PeopleSoft Customer Connection, Updates and Fixes.

### Task 12A-1-1: Compiling COBOL with CBLBLD.BAT

To compile COBOL with CBLBLD.BAT:

1. Set up two environment variables, PS\_HOME and COBROOT, on the machine from which you'll compile COBOL. (This should be either your file server or a machine that has access to your file server.) You can do this from a DOS command prompt window.

Environment Variable	Purpose
PS_HOME	PeopleSoft home directory—that is, the drive letter and high-level PeopleSoft directory where you installed PeopleTools and the application.
COBROOT	Drive letter and root directory of the COBOL compiler.

For example, you could enter the following at the DOS command prompt:

```
set PS_HOME=C:\hr840
set COBROOT=c:\netexpress\base
```

2. Open a DOS command prompt window if you do not have one open already, and change directories to <PS\_HOME>\setup.
3. Execute CBLBLD.BAT as follows

```
cblbld <compile drive> <compile directory>
```

where <compile drive> is the drive where the compile takes place, <compile directory> is the temp directory where the compile takes place

The CBLBLD.BAT file will create the compile directory for you if it does not already exist.



---

**Note.** *Make sure* to include a space between the <compile drive> and <compile directory> parameters; they are treated as two different parameters within the CBLBLD.BAT batch program. Also ensure that you have write permission to <compile drive> and <compile directory> as the compile process will take place there.

---

For example, the following command will take the COBOL source from <PS\_HOME>\src\cbl and do the compile process under c:\temp\compile:

```
cblbld c: \temp\compile
```

Make note of the information that is displayed on the screen while the process is running; it provides the locations of important files that you will need to examine.

4. After you have successfully compiled your source code, all of the executables should have been placed in your <PS\_HOME>\CBLBINX directory (this directory will be named CBLBINA, CBLBINU, or CBLBINE, depending on whether you are using ANSI, Unicode or EBCDIC). Make sure that all of the files were copied correctly to this directory.
5. If the files were copied correctly, you can delete the entire temporary compile directory to free space on your disk drive.

---

**Note.** You may want to keep the files in the compile directory for testing purposes. Make sure that you have enough space on the drive where <compile directory> is located. Estimate about three times the amount in the <PS\_HOME>\CBLBINX directory.

---



---

**Note.** If you chose the Unicode option while running the PeopleSoft Installer, the file UNICODE.CFG was created in the setup directory. UNICODE.CFG automatically triggers the batch file CBL2UNI.BAT when you run CBLBLD.BAT. Another batch file, CBLRTCPY.BAT, copies four DLLs (CBLINTS.DLL, CBLRTSS.DLL, CBLVIOS.DLL, COB32API.DLL) from the Microfocus compiler directory (identified by %COBROOT% setting) into the appropriate CBLBIN directory (CBLBINA, CBLBINU, or CBLBINE) when you run CBLBLD. These files are needed for COBOL to run; they can reside anywhere as long as they are in the path. You can run either of these BAT files independently from the DOS command line (they reside in <PS\_HOME>\setup). For CBLRTCPY.BAT you need to specify a target directory.

---

## Task 12A-1-2: Compiling COBOL with CBLMAKE.BAT

CBLBLD.BAT compiles all your COBOL at once, which can take a lot of time. CBLMAKE.BAT, in contrast, lets you employ one or more parameters to compile a specific COBOL file or a selected group of COBOL files. Unlike CBLBLD.BAT, however, CBLMAKE.BAT does not automatically trigger the batch file CBL2UNI.BAT or CBLRTCPY.BAT.

Here is the basic syntax for CBLMAKE.BAT:

```
CBLMAKE.BAT [] [ALL] [wildcard filename[ALL]] [wildcard filename | wildcard⇒
filename without extension[INT | GNT | EXE]] [EBCDIC] [LIST]
```

---

**Note.** The switches are well documented in the CBLMAKE.BAT file in the form of comments.

---



---

**Note.** If the change in the COBOL source is a copy member, you must compile all of the COBOL programs using CBLBLD.BAT. You know it is a copy member when the third letter in the file name is a C, as in PTCSQLRT.CBL.

---

The following table describes the various options for CBLMAKE.BAT.

Option	Purpose
Cblmake	Compiles all source
Cblmake all	Compiles all source
Cblmake EBCDIC	Compiles all source files for DB2 UDB for z/OS
Cblmake PT*	Compiles all source files that start with PT
Cblmake PT* ALL	Compiles all source files that start with PT
Cblmake PT* INT	Generates INT files for all source files that start with PT
Cblmake PT* GNT	Generates GNT files for all source files that start with PT
Cblmake PT* EXE	Generates EXE files for all source files that start with PT
Cblmake PTPDBTST INT	Generates PTPDBTST.INT file
Cblmake PTPDBTST INT LIST	Generates PTPDBTST.INT and source listing file
Cblmake PTPDBTST GNT	Generates PTPDBTST.GNT file
Cblmake PTPDBTST EXE	Generates PTPDBTST.EXE file

The LIST option creates a source listing file under <compile directory>\<filename>.lis. The LIST option is useful when the compile fails during the debugging phase. The source listing files show exactly where an error occurred. This option is not recommended when the program compiles successfully because the .LIS files can grow to be quite large.

---

**Note.** By default, when the program fails to compile, the system will generate a .LIS file.

---

To compile with CBLMAKE.BAT:

1. Verify that the PS\_HOME and COBROOT environment variables are set up correctly.
2. Open a DOS command prompt window.
3. Make sure the compile directory exists; it may already if you've run CBLBLD.BAT. If it does exist, remove any files residing there—just as a safeguard. If it does not exist, you need to create it.

---

**Note.** Make sure you have write permission to <compile directory> as the compile process will take place there.

---

4. Change to the <PS\_HOME>\setup directory.
5. If the installation is Unicode, run CBL2UNI (with no parameters).
6. Execute the following command to copy all the COBOL source files from the <PS\_HOME> directory to the compile directory:

```
cblsrc <source directory> <compile directory>
```

where <source directory> is the drive and directory where the source resides (it should be the same as <PS\_HOME>), and <compile directory> is the drive and directory to which the source files will be copied.

For example, the following command will take the COBOL source from <PS\_HOME> and copy all the necessary files to the location where the compile process will take place.

```
cblsrc <PS_HOME> c:\temp\compile
```

If the COBOL source that will be compiled is different from the one under <PS\_HOME>, copy that COBOL source to <compile directory>.

---

**Note.** The compile in the next step will generate a GNT file unless the exception file, CBLINT.XX already exists (the XX represents the Product ID). CBLINT.XX contains the list of files that need to be compiled to the INT file. Make sure the intended CBLINT.XX is located under <compile directory> before executing CBLMAKE.

---

7. After CBLSRC completes, change directories to the compile directory, and run CBLMAKE.BAT, using the basic syntax as well as the CBLMAKE table shown earlier as your guide.
8. After CBLMAKE.BAT completes, copy the EXE, GNT, or INT files to the appropriate <PS\_HOME>\CBLBINX directory (CBLBINA, CBLBINU, or CBLBINE).

```
copy *.exe <PS_HOME>\cblbina
copy *.gnt <PS_HOME>\cblbina
copy *.int <PS_HOME>\cblbina
```

---

**Note.** You have to copy these files to the appropriate cblbin directory manually when you use CBLMAKE; they are not copied automatically, as when you use CBLBLD.

---

## Task 12A-1-3: Defining the GNT and INT Files

By default, the compile generates a GNT file unless the exception file, CBLINT.XX already exists. CBLINT.XX contains the list of files that need to be compiled to the INT file.

---

**Note.** The INT exception file is sometimes needed to overcome MicroFocus execution error with GNT files.

---

For example, the exception file, CBLINT.PT, where *PT* represents PeopleTools, would contain the following information:

```
Call cblcrnt <file name without file extension>
```

or:

```
Call cblcrnt PTPDBTST
```

---

## Task 12A-2: Distributing COBOL Binaries

Once you've compiled your COBOL, you must transfer it to the needed locations. Copy the contents of <PS\_HOME>\CBLBINX (CBLBINA, CBLBINU, or CBLBINE) directory into <PS\_HOME>\CBLBINX (CBLBINA, CBLBINU, or CBLBINE) on your batch and application server machines.



## CHAPTER 12B

# Compiling COBOL on UNIX

This chapter discusses:

- Understanding COBOL
- Prerequisites
- Setting Environment Variables
- Modifying the Liblist (IBM AIX 5.1, IBM AIX 5.2, and HP-UX Only)
- Compiling COBOL Programs
- Linking COBOL
- Recompiling COBOL on UNIX

---

## Understanding COBOL

This chapter describes how to compile and link PeopleSoft COBOL batch programs, if necessary.

COBOL is not needed for PeopleTools because the Process Scheduler has been re-written in C++. In addition, COBOL is not required for applications that contain no COBOL programs. See Supported Platforms on Customer Connection for the details on whether your application requires COBOL.

See “PeopleSoft Application COBOL Requirements,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise, By PeopleTools release, Platform Communications by Topic, Batch).

For more details about running COBOL in Unicode, consult the following.

See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*, “Running COBOL in a Unicode Environment.”

---

## Prerequisites

Before you attempt to run COBOL from the command line you should do the following:

- For UNIX and Windows systems, make sure the variable PS\_SERVER\_CFG points to a valid pspres.cfg file.
- For Windows systems, make sure %PS\_HOME%\bin\server\winx86 is in your path. It should appear before %PS\_HOME%\bin\client\winx86 if that also appears in the path.

---

## Task 12B-1: Setting Environment Variables

On your UNIX system, you need to log in and ensure the following environment variables are set appropriately. Alternatively, make sure the following environment variables are set in the *.profile* file in the user's home directory:

- \$ORACLE\_HOME must point to the correct Oracle installation; for example:

```
ORACLE_HOME=/products/oracle/8.1.7;export ORACLE_HOME
```

- \$ORACLE\_HOME/bin must be added to PATH; for example:

```
PATH=$PATH:$ORACLE_HOME/bin;export PATH
```

- \$ORACLE\_HOME/lib must be appended to LD\_LIBRARY\_PATH, LIBPATH, or SHLIB\_PATH, whichever is appropriate for your platform.
- \$ORACLE\_SID must be set to the correct Oracle instance; for example:

```
ORACLE_SID=hdmo;export ORACLE_SID
```

- \$COBDIR must be set to the Server Express installation; for example:

```
COBDIR=/cobol/prod/svrexpress-2.2.SP1;export COBDIR
```

- \$COBDIR/lib must be appended to LD\_LIBRARY\_PATH, LIBPATH, or SHLIB\_PATH, whichever is appropriate for your platform.

```
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$COBDIR/lib;export LD_LIBRARY_PATH
```

```
LIBPATH=$LIBPATH:$COBDIR/lib;export LIBPATH
```

```
SHLIB_PATH=$SHLIB_PATH:$COBDIR/lib;export SHLIB_PATH
```

- \$COBDIR/bin must be appended to the PATH; for example:

```
PATH=$PATH:$COBDIR/bin;export PATH
```

To set the required PeopleSoft environment variables, run psconfig.sh. Enter the following command:

```
cd <PS_HOME>
```

```
. ./psconfig.sh
```

---

## Task 12B-2: Modifying the Liblist (IBM AIX 5.1, IBM AIX 5.2, and HP-UX Only)

This section discusses:

- Understanding Liblist Modifications
- Modifying the Liblist File

## Understanding Liblist Modifications

If you are compiling COBOL on AIX 5.1 or 5.2, or HP-UX, modify the liblist or liblist64 file as described here. See the document “COBOL: Installation, versions, fixpacks, etc. PT8.44+” on Customer Connection for additional information about modifications that need to be made in the liblist or liblist64 file.

See “COBOL: Installation, versions, fixpacks, etc. PT8.44+,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise, By PeopleTools Release, Platform Communications by Topic, Batch).

### Task 12B-2-1: Modifying the Liblist File

This section discusses:

- Modifying the Liblist File for AIX
- Modifying the Liblist64 File for HP-UX

#### Modifying the Liblist File for AIX

To modify the liblist file for AIX 5.1 and 5.2:

1. cd to \$COBDIR/lib.
2. Add the following line to the liblist file:

```
x:*:s!t:-lC
```

The following listing shows where to make the changes:

```
# More emulation of cc (MUST be after MF/user libraries):
x:*:sg:-lg
x:*:sg:-bE:/usr/lib/libg.exp
x:*:st:-L/usr/lib/threads
x:*:st:-lpthreads
x:*:s!t:-lC          <=== Add this line
x:*:s:-lC
```

#### Modifying the Liblist64 File for HP-UX

You must modify \$COBDIR/lib/liblist64 if *both* of the following conditions exist:

---

**Note.** This modification is for the liblist64 (sixty-four) file, not the liblist file.

---

- You get this error message when running psrun.mak:

```
$ ./psrun.mak
./psrun.mak - linking PSRUN ...
./psrun.mak - Error(s) encountered creating PSRUN!
./psrun.mak - See psrun.err for messages
```

- The psrun.err error file contains the following error:

```
ld: Can't open /opt/langtools/lib/pa20_64/crt0.o
ld: No such file or directory
```

To modify the liblist64 file for HP-UX PA RISC:

1. Login into the system as user root.
2. cd to \$COBDIR/lib and find the liblist64 file.
3. Edit \$COBDIR/lib/liblist64 with vi, emacs or your favorite editor, and change the crt0.o specification as depicted below.

From this:

```
x:*:s:/opt/langtools/lib/pa20_64/crt0.o
```

To this:

```
x:*:s:/usr/ccs/lib/ps20_64/crt0.o
```

---

## Task 12B-3: Compiling COBOL Programs

This section discusses:

- Understanding COBOL Compilation
- Compiling COBOL on UNIX

### Understanding COBOL Compilation

Under UNIX, you always need to compile your COBOL at installation time. After you run the PeopleSoft Installer to set up your application or batch server, carry out the following steps.

---

**Note.** You have two options for compiling. You can treat one application or batch server as your compile server, compile all your COBOL there, and then distribute cblbin from there to all other relevant servers. In this case, only that one server would require a COBOL compiler, and you would copy any patches and customizations from your file server to this designated server before carrying out the compile. The second option is to compile on all servers. In this situation, all servers would need a COBOL compiler, and you would need to copy any patches and customizations from the file server to all of these servers before carrying out the compile.

---

---

**Note.** To copy a compiled COBOL program from one UNIX server to another, they must be on the same OS that the compile took place on. For example, if you compile on Solaris 8 and/or 9 for the Application Server and the Process Scheduler is on AIX you cannot copy the compiled program (you will also need to compile on the AIX box).

---

### Task 12B-3-1: Compiling COBOL on UNIX

To compile COBOL on UNIX:

1. If you haven't already done so, download all required patches to your file server, and from there to FTP the contents of src\cbl\base and src\cbl\unix over to src/cbl on the relevant application or batch server.

---

**Note.** When you bring patches up from the file server, the files need to have a lowercase cbl extension and an uppercase program name, as in PATCH.cbl.

---

2. Run psconfig.sh from <PS\_HOME> to set up environment variables correctly on your application or batch server.



3. Change to the <PS\_HOME>/setup directory:

```
cd $PS_HOME/setup
```

4. To compile all the COBOL source dynamically, issue the command:

```
./pscbl.mak
```

The dynamic compile creates INT, LST, and GNT files, which are copied to these locations:

File	Location
INT	<PS_HOME>/src/cbl/int
LST	<PS_HOME>/src/cbl/lst
GNT	<PS_HOME>/cblbin

---

**Warning!** Proposed ISO 2000 COBOL features are enabled. Please refer to documentation for details, and do not rely on these features being supported in future products from Micro Focus due to changes in the proposed COBOL standard.

---



---

**Note.** For Server Express, PeopleSoft sets the COBOL directive INTLEVEL to 4. Setting this directive to this value enables you to raise the significant digits of numeric fields from 18 to 31. This is in accordance with the ISO 2000 COBOL standard. During the compilation of each program, the vendor of Server Express will display a warning. This should not be considered a compilation error.

---

## Task 12B-4: Linking COBOL

This section discusses:

- Understanding COBOL Linking
- Linking COBOL Components on UNIX

### Understanding COBOL Linking

PSRUN is the PeopleSoft procedure that connects the COBOL batch programs with the RDBMS API. It is compiled uniquely for each platform and consists of modules from PeopleSoft, the RDBMS vendor, and the operating system.

You need to create the PSRUN program in the following situations:

- You are installing PeopleSoft for the first time.
- Any COBOL programs have changed.
- The version of the RDBMS running PeopleSoft has changed.
- The COBOL compiler has changed.
- One of the C programs supplied by PeopleSoft has changed.

---

**Note.** PeopleSoft only supports dynamic linking of COBOL. Static linking is not an option.

---

## Task 12B-4-1: Linking COBOL Components on UNIX

To link COBOL components on UNIX:

1. Change to the <PS\_HOME>/setup directory:

```
cd $PS_HOME/setup
```

2. For dynamic linking, run:

```
./psrun.mak
```

The PSRUN.MAK script should return the UNIX prompt when done. If the compile completes without errors, the file PSRUN will now exist in the <PS\_HOME>/bin directory. If you encounter errors, check <PS\_HOME>/setup/psrun.err.

---

## Task 12B-5: Recompiling COBOL on UNIX

You always need to compile at installation, so you will only need to recompile COBOL in the following situations:

- Any COBOL programs change
- The supported COBOL compiler changes
- You change the version of your RDBMS
- You change your version of your operating system
- You apply a patch or a fix

---

**Note.** Remember, you must always use your file server as the source repository for your COBOL. You should download any patches and apply any customizations to the file server, and disseminate them from there.

---

You can compile a *single* COBOL program dynamically by using this command syntax:

```
./pscb1.mak <PROGRAM NAME WITHOUT "cbl" EXTENSION>
```

For example,

```
./pscb1.mak PTPDBTST
```

compiles the lone file PTPDBTST.

---

**Note.** If you want to recompile all your COBOL, you can follow the procedure described earlier.

See “Compiling COBOL Programs.”

---

The compile should run without errors until it completes. After the script is complete, check the destination directories for the newly created files in <PS\_HOME>/src/cbl/int, <PS\_HOME>/src/cbl/lst, and <PS\_HOME>/cblbin. They should have a length greater than zero as well as a current date and time stamp.

---

**Note.** You can also use `pscbl.mak PTP` or `pscbl.mak PTP*` to compile all source files that start with PTP.

---



## CHAPTER 13

# Installing PeopleSoft Change Assistant

This chapter discusses:

- Understanding PeopleSoft Change Assistant
- Installing and Configuring PeopleSoft Change Assistant
- Specifying Options
- Exporting Jobs to XML, HTML, or Microsoft Excel Format
- Validating Change Assistant Settings

---

## Understanding PeopleSoft Change Assistant

Oracle's PeopleSoft Change Assistant is a standalone application that enables you to assemble and organize the steps necessary to apply patches and fixes for maintenance updates. You also use PeopleSoft Change Assistant for software upgrades, that is, the process of moving from one PeopleTools release to another PeopleTools release.

---

**Note.** If you are upgrading to PeopleTools 8.44 or below, you must use PeopleSoft Upgrade Assistant.

---

In order to perform reliable and accurate updates, PeopleSoft Change Assistant gathers all the necessary information including the change log from the Environment Management hub and uploads it to PeopleSoft Customer Connection. With the environment data available, PeopleSoft Customer Connection can determine what updates apply to your environment.

When you access PeopleSoft Customer Connection, you can obtain a list of all unapplied updates for a given application environment including all prerequisites. You can then download a set of change packages associated with the update IDs and install the patches and fixes with minimal effort.

---

## Task 13-1: Installing and Configuring PeopleSoft Change Assistant

This section discusses:

- Installing PeopleSoft Change Assistant
- Setting Up Security for Change Assistant
- Scanning the Workstation

## Task 13-1-1: Installing PeopleSoft Change Assistant

At the end of the installation, you have the option of installing PeopleSoft Change Impact Analyzer. For more information on that installation, see the following chapter.

See “Installing PeopleSoft Change Impact Analyzer.”


To install PeopleSoft Change Assistant:

---

**Note.** A Windows-based operating system is required to use Change Assistant.

---

1. From the <PS\_HOME>/setup/PsCA directory, run `Setup.exe`.
2. If there is an existing installation of PeopleSoft Change Assistant the following screen appears:




Change Assistant Setup Maintenance

Select the Remove radio button, then click Next to remove the previous installation and close the screen. Run <PS\_HOME>/setup/PsCA/setup.exe again.

3. On the Welcome screen, select Next.  
The Change Assistant screen appears.
4. Accept the default Destination Folder or specify another Destination Folder.
5. Select Next.  
The Start Copying Files screen appears.
6. Click Back to review or change any settings.  
If you are satisfied with your settings, click Next to begin copying files. Change Assistant copies files to the designated directory.
7. On the screen asking whether you want to install Change Impact Analyzer, select No, and click Next.

If you select Yes, the PeopleSoft Change Impact Analyzer installation begins. You will do this installation in the next chapter. Instead, continue with the tasks in this chapter to finish setting up PeopleSoft Change Assistant.



Choosing not to install Change Impact Analyzer

8. Click Finish to complete the installation process.
9. Reboot your machine after the installation process is complete.

## Task 13-1-2: Setting Up Security for Change Assistant

To use PeopleSoft Enterprise Change Assistant, you must configure your firewall settings so that the firewall does not filter PeopleSoft domain and IP names.

---

**Note.** When setting trust rules or bypass rules on your proxy server, or in browser security, it is easier to maintain rules by domain or IP subnet.

---

The following features must be set to allow access for PeopleSoft Enterprise Change Assistant:

- *Domains:* Allow access for the domains `www.peoplesoft.com` and `update.peoplesoft.com`.  
We recommend that you set domain rules to allow access to `*.peoplesoft.com`.
- *IP addresses:* Allow access for the IP addresses `192.206.43.114` and `192.206.43.105`.  
We recommend that you set IP rules at the subnet `192.206.43.0`.
- *FTP sites:* Configure your firewall to allow inbound ftp when the request is not initiated on the same port.  
Software update requests go to PeopleSoft Customer Connection on one port number, and the actual download comes back on a different ftp port number.

Change Assistant uses SSL to connect at all times, but when you log in to PeopleSoft Customer Connection or Update Gateway through a browser only the login page is SSL.

## Task 13-1-3: Scanning the Workstation

The first time you use Change Assistant, it automatically scans your workstation for applications that it will use in order to automate the steps. For example, it automatically finds the SQL Query tool and uses it to run SQL commands or scripts.

If you add a new application or update an existing application, Change Assistant must perform a scan of the system in order to discover the changes. To perform this scan, select Tools, Scan Configuration.

---


## Task 13-2: Specifying Options

This section discusses:

- Specifying Change Assistant Options
- Setting Email Options
- Setting Up Web Services Options
- Setting Environment Management Options

### Task 13-2-1: Specifying Change Assistant Options

This section describes options to set in Change Assistant. Select Tools, Options, Change Assistant.



Change Assistant Options window



<b>Change Assistant Mode</b>	<p>Select one of the following radio buttons; the window changes depending upon the mode you choose:</p> <ul style="list-style-type: none"> <li>• Apply Application Update</li> <li>• Perform PeopleTools Only Upgrade</li> <li>• Perform Application Upgrade</li> <li>• Enable Server Processing</li> </ul> <p>Select this check box to enable Change Assistant to run Application Engine, Data Mover User, Data Mover Bootstrap, and SQL Scripts on Remote Agents as configured through Environment Management Framework as part of the Application upgrade.</p> <ul style="list-style-type: none"> <li>• Create or Modify Templates</li> </ul>
<b>Maximum Concurrent Processes</b>	Specify the maximum number of processes that can be executed concurrently on the local machine. The default at installation time is one.
<b>Download Directory</b>	Enter the full path of the location to which you want to download your change packages.
<b>*PS_HOME</b>	Enter the full path of the directory in which you installed PeopleTools.
<b>*Staging Directory</b>	Enter the directory in which you would like to stage all the Change Assistant update files. This is the location that Change Assistant will store files to be used during the apply update process.
<b>*Output Directory</b>	Enter the directory in which you want the log files generated by the update process to reside.


## Task 13-2-2: Setting Email Options

Select Tools, Options, Email.

<b>Send email notifications</b>	Select this check box to receive email notifications if there are errors in the update process. Change Assistant also sends you a completion message when it encounters a <i>Stop</i> in the update process.
<b>SMTP Server</b>	Enter the SMTP mail server from which you receive the error or completion messages.
<b>Port</b>	Enter the port from which you want to access the email.
<b>Send To</b>	Enter the address to which you want the email sent.
<b>Return Address</b>	Enter the email address of the sender. Use this to identify who sent the notification.
<b>Test</b>	Use to validate that email is sent to the designated recipients and is working correctly

## Task 13-2-3: Setting Up Web Services Options

Select Tools, Options, Web Services.



Change Assistant Options: Web Services tab

<b>Host</b>	(Optional) Enter the name of the proxy server if you want to run Change Assistant behind the firewall using a proxy server.
<b>Port</b>	(Optional) Enter the port number for the proxy server.
<b>Anonymous Proxy</b>	Indicates that you are using a proxy server that does not require authenticated connections.
<b>Microsoft Proxy Server</b>	Indicates that you are using a proxy server with Windows NT authentication.
<b>Windows Domain</b>	The domain to which you belong.
<b>Other Proxy Servers</b>	Indicates you are using non-Microsoft proxy servers.

## Task 13-2-4: Setting Environment Management Options

Select Tools, Options, Environment Management.

<b>Server Hostname</b>	The hostname of the server in which the Environment Management components reside.
<b>Server Port</b>	Indicates the port in which to connect to the Environment Management hub.
<b>Ping (button)</b>	Click to verify a valid server URL. If you see "Service is off" to the right of this button, then you must correct the server URL and ping again until you see "Service is on."
<b>Chunk Size</b>	Used for deploying files during a software update. Default is 1024 * 1024 bytes. Typically this does not need to be changed unless there are a significant number of files greater than 1024 KB in a software update.
<b>Ping Interval</b>	Ping interval is in milliseconds for Change Assistant to contact the hub for new messages.
<b>Drives to Crawl</b>	Setting of drives to crawl to identify the configuration of the Change Assistant machine. Windows directories need to use the forward slash (/) character. Include your local drive in this setting so that Change Assistant can locate the SQL Query tool used for automating steps. Also include the path of the SQL Query tool.

---

## Task 13-3: Exporting Jobs to XML, HTML, or Microsoft Excel Format

Change Assistant allows users to export jobs to XML, HTML, or Microsoft Excel file formats. Do this by selecting File, Export Job in Change Assistant. Then, enter the desired exported filename and select the desired file type format.

---

## Task 13-4: Validating Change Assistant Settings

After you have set up and configured Change Assistant and the Environment Management components, you should validate your Change Assistant and environment settings.


Change Assistant validates settings by:

- Locating valid SQL query tools required to run SQL scripts.
- Testing the Environment Management hub and ensuring that Change Assistant can communicate with it.
- Testing Customer Connection and ensuring that Change Assistant can communicate with it.

You can also print a summary of your environment, which can facilitate the diagnosis of problems by PeopleSoft Global Support.

To validate your environment, select Tools, Options, Validate. Click Start Validation.


If any of the steps were unable to complete successfully, open the log file to determine the cause.



Validating Change Assistant Settings in Your Environment

**Note.** If you use proxy servers, the system will ping those and prompt for proxy server user ID and password. In this case, the validation step numbers would be different from the example.

To review the log file, click the View Log button at the bottom of the screen:



```

validate_2004_12_22_12_38 - Notepad
File Edit Format Help
Assistant\commons-httpclient-2.0-rc1.jar;C:\Program Files\PeopleSoft\Change
Assistant\commons-codec-1.1.jar;C:\Program Files\PeopleSoft\Change
Assistant\xml-db-api-20021118.jar;C:\Program Files\PeopleSoft\Change
Assistant\xml-db-common.jar;C:\Program Files\PeopleSoft\Change
Assistant\xindice-1.1b.jar;C:\Program Files\PeopleSoft\Change Assistant\psemf.jar;C:\Program
Files\PeopleSoft\Change Assistant\AbsoluteLayout.jar;C:\Program Files\PeopleSoft\Change
Assistant\log4j-1.2.8.jar;C:\Program Files\PeopleSoft\Change Assistant\jxl.jar;C:\Program
Files\PeopleSoft\Change Assistant\j2ee.jar
Current working Directory: C:\Program Files\PeopleSoft\Change Assistant
Done.
(Step 2) Validating your SQL Query Tools
Found Microsoft SQL Query Tool at c:\Program Files\Microsoft SQL
Server\80\Tools\Binn\OSQL.exe
Found Oracle SQL Query Tool at c:\Apps\DB\Oracle7\bin\sqlplus.exe
Done. 2 SQL Query Tools found.
(Step 3) Pinging DELLARD7100 (EM Hub)
Done.
(Step 4) Connecting to Hub: http://DELLARD7100:80/PSEMHUB/hub
Error Connecting to EMHub: Unable to connect to Environment Management Hub
(Step 5) Pinging www.peoplesoft.com (Customer Connection)
Done.
(Step 6) Validating connection to logon site: https://www.peoplesoft.com/sm/login.fcc
No proxy servers defined in configuration settings. Connecting directly to
https://www.peoplesoft.com/sm/login.fcc
Done.
(Step 7) Pinging update.peoplesoft.com (Update Gateway upload/download)
Done.
(Step 8) Validating connection to update Gateway:
https://update.peoplesoft.com/PSIGW/HttpListeningConnector
No proxy servers defined in configuration settings. Connecting directly to
https://update.peoplesoft.com/PSIGW/HttpListeningConnector
Done.
[Wed Dec 22 12:38:38 PST 2004] End Validation
Unsuccessful completion (1 Step Failed). Click on view Log to see additional messages.

```

Validation log



## CHAPTER 14

# Installing PeopleSoft Change Impact Analyzer

This chapter discusses:

- Prerequisites
- Installing Change Impact Analyzer

---

## Prerequisites

Oracle's PeopleSoft Change Impact Analyzer (PsCIA) is a tool you can use to evaluate the effect of changes you make on your installation. CIA can help you monitor the impact a Change Package has on your system, as well as monitor the impact from other changes such as customizations.

Ensure that your system meets the following requirements before you begin this installation:

- The PsCIA runs on Windows. For database platforms that do not run on Windows, install PsCIA on the Windows client.
- You can install PsCIA from downloaded files as a standalone application, or as a part of your PeopleTools installation. You can also install PsCIA as a part of the PeopleSoft Change Assistant installation, as mentioned in the previous chapter. These instructions assume you have installed PeopleTools on the machine on which you want to run PsCIA, and have completed the PeopleSoft Change Assistant installation.
- PsCIA uses Type 4 JDBC drivers by default. These drivers are automatically installed for you.

### See Also


*Enterprise PeopleTools 8.48 PeopleBook: Software Updates*

---

## Task 14-1: Installing Change Impact Analyzer

To install Change Impact Analyzer and Rules Editor:


1. From the <PS\_HOME>\setup\PsCIA directory, run `setup.exe`.  
A Welcome screen appears.
2. If there is an existing installation of PsCIA on your machine, a screen appears asking whether you want to Modify, Update, or Remove the existing installation.



PeopleSoft Change Impact Analyzer Setup Maintenance window

Select the Remove radio button, then click Next to remove the previous installation and close the screen. Run <PS\_HOME>/setup/PsCIA/setup.exe again.


3. Click Next.



PeopleSoft Change Impact Analyzer welcome window


4. Select the JDBC drivers for your database platform.






Selecting JDBC drivers type

5. Browse to select the directory where PsCIA will be installed, or accept the default directory.



Selecting the destination folder

6. Click Back to review or change any settings.  
If you are satisfied with your settings, click Next to begin copying files to the designated directory.
7. Click Finish to exit when the installation is complete:



Installation complete

8. To start PsCIA, select Start, Programs, PeopleTools 8, Change Impact Analyzer.

## APPENDIX A

# Adding New Product Modules

This appendix discusses:

- Adding New Module(s) to PeopleSoft 8.4 Installations

---

### Task A-1: Adding New Module(s) to PeopleSoft 8.4 Installations

This task explains how to add new application modules to an existing PeopleSoft installation. Follow this procedure if, for example, you already installed HRMS and now you need to install Time and Labor.

When you add new application modules to an existing installation, you may overwrite files that were included as part of a patch or fixes, or customizations that you applied. For example, suppose you customize a report that PeopleSoft then redelivers. If you install the update into your current working directory, your customized report will be overwritten with the newly installed, updated report.

PeopleSoft does not currently provide an automated way to notify you before overwriting customized modules or patch files. You can make preparations to protect important files from being overwritten. For your customized modules, you need to maintain a backup of any customizations. It is also a good idea to make a copy of your <PS\_HOME> directory before beginning this process, so that you can find and restore necessary patch files. Check PeopleSoft Customer Connection to identify any patches or fixes required for your installation.

See PeopleSoft Customer Connection, Updates and Fixes.

To add new module(s) to PeopleSoft 8.4 installations:

1. Back up the database, file server, application server, Process Scheduler Server, and web server components of your current system.
2. Make sure you have the new license code that includes the new module(s). The new license code allows you to load the batch components for the new module(s).
3. Install the Application CD on the file server.
4. When prompted, enter the new license code for your applications.

Initially, all installation options will be selected. You must deselect those programs you do not wish to install.

5. Launch Data Mover in bootstrap mode (sign in as the accessid and password).

Data Mover is located in <PS\_HOME>\bin\client\winx86\psdmt.exe.

6. Select File, Database Setup and choose your database type in the resulting dialog.
7. Select Next and select add new product.
8. Select Finish and a Data Mover script that updates the license code will be generated in Data Mover.

9. Select File, Run script and your database updates are complete.
10. Install software to your batch server.

See “Setting Up Process Scheduler.”

11. Reapply all code customizations if needed.

---

**Note.** Remember to maintain back-up copies of your customizations.

---

12. Compile and link COBOL.

See Compiling COBOL.

13. Verify that the appropriate Installation Records are selected.

If they are not checked, check them and save the page. To open the page, select Setup <apptype>, Install, Installation Options, where <apptype> is HRMS, CRM, Financials/Supply, and so on. (For HRMS the navigation is Setup <apptype>, Install, Installation Table.)

14. Run the DDDAUDIT and SYSAUDIT SQRs.

See “Creating a Database.”

15. Shut down all application servers.

16. Install software to your application server.

See “Configuring the Application Server.”

17. Restart all required application servers.

18. Shut down all web servers.

19. Install software to your web server.

See “Setting Up the PeopleSoft Pure Internet Architecture.”

## APPENDIX B

# Installing PeopleBooks

This appendix discusses:

- Understanding PeopleBooks
- Installing PeopleBooks
- Implementing the PSOL Server for PeopleBooks
- Setting up a Reverse Proxy Server
- Configuring Context-Sensitive Help
- Administering PeopleBooks

---

## Understanding PeopleBooks

PeopleBooks are the documentation delivered with PeopleTools and every PeopleSoft application. This appendix describes how to install and configure PeopleBooks so that you can deploy the PeopleSoft documentation at your site.

There are three options for configuring PeopleBooks. Most sites will want to take advantage of all three.

- *Browse*: Browse the PeopleBooks from a file server or web server.
- *Full-text Search*: Requires installation of the PeopleSoft Pure Internet Architecture and hosting PeopleBooks on a web server.
- *Context-sensitive help*: Configure PeopleTools to call PeopleBooks as context-sensitive help from both internet applications and Windows-based programs. For instance, when a user clicks the Help link in a browser or presses F1 in Windows, the appropriate documentation appears.

---

**Note.** The F1 button calls PeopleBooks Help only for the PeopleTools Development Environment (the Windows-based client). If you press F1 while using the portal, you invoke the help for your current browser. For context-sensitive help in the portal, end users need to click the Help link to call PeopleBooks Help.

---

---

## Task B-1: Installing PeopleBooks

This section discusses:

- Prerequisites
- Installing the PeopleBooks CD

## Prerequisites

You can install PeopleBooks to your PeopleTools 8.48 dedicated web server machine or to a separate web server machine. Either way, the web server software must be installed before you install PeopleBooks. You can also install PeopleBooks on a file server, but you will not be able to search or to use PeopleBooks as context-sensitive help for your PeopleSoft applications.

Before you begin the installation, make sure you are installing to a supported web server and operating system platform. PeopleBooks 8.48 is supported on the same web server platforms as the PeopleSoft Pure Internet Architecture (PIA) for PeopleTools 8.48, and on the same operating systems as the PeopleTools 8.48 application server.

---

**Note.** PeopleBooks must be installed on a system other than HP-UX Itanium if full-text search is required. Asian language full-text search is not available on HP-UX systems.

---

### See Also

*Enterprise PeopleTools 8.48 Hardware and Software Requirements*

PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise)

## Task B-1-1: Installing the PeopleBooks CD

Unlike in past releases, PeopleBooks can now be installed directly to a UNIX machine. In addition, PeopleBooks can be installed over an existing PeopleBooks site, effectively upgrading the site and merging in new content. (Duplicate book titles will be overwritten.)

---

**Note.** The PeopleSoft Pure Internet Architecture file structure has changed for PeopleTools 8.44 and above, so you cannot install PeopleBooks 8.48 into a pre-8.44 PIA site. However, after installing PIA 8.48, you can move your old PeopleBooks structure into the PSOL web module directory created during the PIA installation, and then install PeopleBooks 8.48 on top of it.

---

---

**Note.** The following instructions are based on using the GUI InstallShield program. If you run the installation in console mode, follow the instructions on your command line to make selections and progress through the installation prompts.

---

To install the PeopleBooks CD:

1. If your server does not have a built-in CD-ROM drive, share a CD-ROM drive elsewhere on the network and mount that drive on your server. You also have the option of copying the CDs to the network.
2. On UNIX, if you have not run `psconfig.sh` in the current shell, run it now at the command line:  

```
. ./psconfig.sh
```
3. Insert the PeopleBooks CD into the CD-ROM drive.
4. If your Windows CD-ROM drive is set to autorun, the PeopleBook Installer welcome screen appears. Otherwise, at the command line launch the setup program for your operating system platform:

Platform	Launch Program
AIX	setup.aix
HP-UX (PA RISC)	setup.hp
HP-UX Itanium	setup.hp-ia64
Linux	setup.linux
Solaris	setup.solaris
Tru64	setup.tru64
Windows	setup.exe

---

**Note.** If you are installing to a UNIX machine and do not have a GUI interface tool, use the command `setup.<OS> -is:javaconsole -console`.

---

5. Enter your application license code and click Next.
6. Accept the license terms and click Next.
7. Select one of the following options, and click Next:
  - Option 1: Generate search collection on this product only
  - Option 2: Generate search collection on entire site

---

**Note.** The collection generation can take up to 20 minutes to complete per PeopleBooks CD. If you are installing multiple PeopleBooks CDs, you might want to install all but the last without building the collections, and then generate them for the entire site (option 2) when installing the last CD. You should also choose option 2 if you are installing over an older version of PeopleBooks.

You can generate or regenerate the search collections at any time after installation using the PSOL Manager utility.

---

See *About These PeopleBooks*, “Managing PeopleBooks and the PeopleSoft Online Library.”

- Option 3: Do not generate search collection

---

**Note.** If you do not plan to use the Full-Text Search functionality, select this option.

---

8. Select which PeopleTools web server you are installing to and whether PIA is installed on the machine and click Next.

---

**Note.** This information is used to build the default install path for PeopleBooks. If you are not using one of these web servers, it does not matter which you choose.

---

9. Enter the paths to the PeopleTools home directory (<PS\_HOME>) and to the directory where you installed the Oracle Application Server (OAS), WebLogic, or WebSphere web server software (for example, specify your <OAS\_HOME> for OAS, <WebLogic\_Home> for WebLogic, and <WAS\_HOME> for WebSphere). Then click Next.

---

**Note.** This information is used to build the default install path for PeopleBooks. If you are installing to a non-PeopleTools machine, enter any valid directory. If you are installing to a web server other than OAS, WebLogic, or WebSphere, enter any valid directory.

---



---

**Warning!** After clicking Next, you may be warned that you have a non-standard PSOL path. If so, this is either because you are not using the PIA default domain/node name, or because PIA is not installed and you selected the “PIA” option on the previous panel. If you have a custom domain/node name, continue to the next step and be sure to edit the default path to reflect your PIA installation. If PIA is not installed, you must either cancel the PeopleBooks installation and install it first, or go back the previous panel and deselect the “PIA” option.

---

10. Enter the install location and click Next.

If you plan to use the Full-Text Search feature, you *must* specify a subdirectory *immediately* below the PSOL module directory in your PIA installation. *Edit the default path as necessary to reflect your PIA installation.*

---

**Note.** You can opt to use an install directory other than the default, 'htmldoc'. It will be created automatically.

---



---

**Note.** If you do not plan to use PeopleBooks Full-Text Search, you can enter any valid path you like—for instance, to the docroot of your alternate web server.

---

For OAS the path should be:

```
<OAS_HOME>\j2ee\PSOL_<domain_name>\applications\<domain_name>\PSOL\htmldoc
```

For WebLogic, the path should be:

```
<PS_HOME>\webserver\<PIA_domain_name>\applications\peoplesoft\PSOL\htmldoc
```

For WebSphere, the path should be:

```
<PS_HOME>\webserver\<CellName_NodeName_ServerName>\peoplesoft.ear\PSOL\htmldoc
```

11. The screen now lists the PeopleBooks that you are entitled to install. If you do not want to install a particular book, deselect the check box next to that book title. Click Next.

---

**Note.** If you are running the installation to apply a maintenance patch, just click Next.

---

12. Specify whether you want to install the selected titles (default) or install just the PeopleBooks infrastructure (for applying maintenance patches only) and click Next.
13. Confirm your selections and click Next to install PeopleBooks.
14. After the CD content has been installed (and collections generated, if applicable), click Finish to end the setup program.

---

## Task B-2: Implementing the PSOL Server for PeopleBooks

This section discusses:



- Understanding PeopleBooks in the PeopleSoft Pure Internet Architecture
- Starting Oracle Application Server Components
- Creating the PSOL Server on WebSphere with Existing 8.4x PeopleSoft Pure Internet Architecture
- Managing the PSOL Server on WebLogic or WebSphere

## Understanding PeopleBooks in the PeopleSoft Pure Internet Architecture

If you are hosting PeopleBooks in a PIA installation that also hosts your PeopleSoft applications, you must run PeopleBooks, the PeopleSoft Online Library (PSOL) web module, as a separate server instance. The setup of the separate server differs slightly depending on the web server you are using:

- For Oracle Application Server (OAS), the PSOL server was created during the PIA installation. The commands to start all PeopleSoft services on OAS are given in the next section.  
See Starting Oracle Application Server Components.
- For WebLogic, you were instructed to install PIA as a “Multiple Server Domain” if installing PeopleBooks on the same machine as PeopleTools. This means that PSOL is now configured to be run as a separate server (on port 6001).
- For WebSphere, because there is no such option during the PeopleSoft Pure Internet Architecture install, you will now need to create a new server to run PSOL.

See “Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode,” Installing the PeopleSoft Pure Internet Architecture in GUI Mode.

If you are hosting PeopleBooks in a PIA installation that is independent of the PeopleSoft applications, there is no need to create or configure a new server instance, and you can skip this task.

You also do not need to carry out the steps in this task if you installed PeopleBooks on another web server that is independent of a PeopleSoft Pure Internet Architecture installation (Full-Text Searching disabled).

### Task B-2-1: Starting Oracle Application Server Components

On a Windows-based server, NT services are automatically created for the Oracle Application Server-based components. The services default to startup type Automatic. If the services have never been started or are set to type Manual, you may start up the web server by following the instructions below.

To manually start the Oracle Application Server, change to the opmn\bin directory under the OAS home directory and execute the appropriate opmnctl command as follows. The default port for the PeopleBooks (PSOL) server is 7777, unless the installer changed the port number at PIA creation time.

Action	Windows command	UNIX command
To start services	C:\<OAS_HOME>\opmn\bin⇒ \opmctl.exe startall	\$OAS_HOME/opmn/bin/opmctl⇒ startall
To stop services	C:\<OAS_HOME>\opmn\bin⇒ \opmctl.exe stopall	\$OAS_HOME/opmn/bin/opmctl⇒ stopall

The resulting default URL for access to the PeopleBooks website is:

[http://<machine\\_name>:7777/PSOL/htmldoc/index.htm](http://<machine_name>:7777/PSOL/htmldoc/index.htm)

## Task B-2-2: Creating the PSOL Server on WebSphere with Existing 8.4x PeopleSoft Pure Internet Architecture

These instructions explain how to install a new server instance via the WebSphere administration console. This task is only required if running PeopleBooks on the same PeopleSoft Pure Internet Architecture installation that hosts your PeopleSoft applications.

---

**Warning!** These steps will cause the PIA application to be redeployed, which will remove directories created during the PIA installation. It is imperative that you back up your webserv folder as instructed below.

---

To create a new PSOL server:

1. Stop the WebSphere server, if it is running.

At the command line, navigate to `<WAS_HOME>\AppServer\bin` and enter the following command:

```
stopServer server1
```

2. Make a copy of your `<PS_HOME>\websrv` folder.
3. Start the WebSphere server.

At the command line, navigate to `<WAS_HOME>\AppServer\bin` and enter the following command:

```
startServer server1
```

4. In a web browser, launch the WebSphere Administrative Console.  
The URL address is `http://<machine_name>:<port>/admin/`, with `<machine_name>` and `<port>` replaced by your onsite values. By default, the port number is 9090.
5. Log in with your user name. (For change tracking purposes only.)
6. In the left-hand frame, click Servers, Application Servers.
7. In the right-hand frame, add a new application server by clicking the New button.
8. In the form in the right-hand frame, enter PSOL as the Server name, select Generate Unique Http Ports, and select Existing application server as the server template. Then click Next.
9. Confirm your selections and click Finish to install the server.
10. In the upper left-hand corner of the browser window, click Save to save your changes. Then click the Save button in the right-hand frame.
11. In the left-hand frame, click Applications, Enterprise Applications.
12. In the right-hand frame click the link peoplesoft.
13. In the new page in the right-hand frame, scroll to the bottom and click Map modules to application servers.
14. The new page in the right-hand frame lists the available Clusters and Servers, including the PSOL server you just created. Select the PSOL server entry in that list.
15. Select the PSOL module check box and click Apply.  
After the screen refreshes, re-select the PSOL module check box, and then click OK.
16. Save your changes a final time. In the upper left-hand corner of the browser window, click Save, and then click the Save button in the right-hand frame.
17. Navigate to the Application Servers page again and click PSOL.

In the new page in the right-hand frame, click Web Container. In the new page, click Http transports. The new page shows the port numbers assigned to the PSOL server. Make a note of these values.

18. Stop server1, as described in step 1.

19. Copy the contents of your backed up webserv folder into the real webserv folder, overwriting any duplicate files.

See the next task for instructions on starting the PSOL server.

See Managing the PSOL Server on WebLogic or WebSphere.

---

**Note.** In the future, you may see warnings that the peoplesoft application could not be launched on PSOL. You can ignore these warnings.

---

## Task B-2-3: Managing the PSOL Server on WebLogic or WebSphere

This section discusses:

- Modifying the PSOL Admin Scripts
- Using the PSOL Admin Scripts

During the PeopleBooks installation, two script files were generated in the admin directory below your installation directory. You can use these scripts to manage your PSOL server.

---

**Note.** The PSOL script files will have a .bat extension on Windows machines and a .sh extension on UNIX machines. The following discussion omits the file extensions.

---

The two PSOL script files are:

- psolAdmin. The command script used to start the PSOL server, stop the PSOL server, etc.
- set\_psol\_env. A configuration script used to store information about your PSOL environment.

### Modifying the PSOL Admin Scripts

For convenience, you may want to copy the scripts from the admin directory to the location where your other web server scripts and commands are located. This is not required, however. The scripts will run properly no matter where they are located or where they are run from.

If you want to copy the scripts to the same directory where your other web server scripts are located:

- On WebLogic, copy the scripts to `<PS_HOME>\webserv\<domain>`
- On WebSphere, copy the scripts to `<WAS_HOME>\AppServer\bin`

---

**Note.** The two script files *must* reside in the same directory.

---

Before you use the psolAdmin script, you should check the configuration in the set\_psol\_env script and compare it against the variable descriptions below. Make any necessary changes according to your system environment, depending upon whether your domain is WebLogic, WebSphere, Single Server or Multi Server. This script was created during the PeopleBooks installation and contains directory paths and other information required for launching the PSOL server properly. There are eight PSOL environment variables that you can verify and set accordingly:

Variable	Description
PSOL_SERVERNAME	This is the name of the server instance that runs PSOL. For WebLogic Multi Server Domain and WebSphere, this value is set to <i>PSOL</i> . For WebLogic Single Server Domain, it is set to <i>PIA</i> . You should only have to modify this value if you installed a PeopleTools-independent PIA for WebSphere (and so did not create a new PSOL server). In that case, you should change this value to <i>server1</i> .
PSOL_SERVERURL	This stores the URL of your WebLogic administration server domain and port. In some Multi Server Domain environments, it may be necessary to pass this value as an argument when starting the PSOL server. It is also necessary if the IP address of the PSOL server machine resolves to multiple values. In that case the URL should specify the proper IP address—for example: <code>http://55.234.667.91:9999</code> .
PSOL_SVC_NAME	This is the name that will be used when creating a Windows service for PSOL.  <b>Note.</b> On WebLogic, this name will be prepended with “peoplesoft -”. On WebSphere, the name will be prepended with “IBM WebSphere Application Server V5 -”.
PSOL_PSHOME	The location of your PeopleTools home directory.
PSOL_WEBSERVER_HOME	The location of your WebLogic or WebSphere installation.
PSOL_WEBSERVER_CMD_PATH	The directory where your web server command scripts are stored. On WebLogic, this is <code>&lt;PS_HOME&gt;\webserver\&lt;domain&gt;</code> . On WebSphere this is <code>PSOL_WEBSERVER_HOME\bin</code> .
PSOL_ENV_SCRIPT	The path to the <code>set_psol_env</code> script (the file you are currently editing). If you moved your scripts in the previous step, be sure to update this path accordingly.
PSOL_WEBSERVER_TYPE	The web server you are running on.

**Important!** If you make any changes to `set_env_psol`, save your changes and then also save a backup copy of the `set_psol_env` script under another name, as the script will be recreated with any subsequent PeopleBooks installation.

## Using the PSOL Admin Scripts

Once your scripts are edited and in the desired location, you can use `psolAdmin` to start and stop the PSOL server, as well as to install or uninstall a Windows service for PSOL.

**Note.** The following instructions assume that the script files are in the current working directory.

Enter each command at the command line. The command arguments must be in UPPERCASE. If you launch the script without an argument, explanatory text will be displayed.

Action	Command	Comment
Start the PSOL server	<code>psolAdmin START</code>	On WebLogic in a multi server domain, you must launch the administration server before starting PSOL. To do this, use the <code>startWebLogicAdmin</code> command.
Stop the PSOL server	<code>psolAdmin STOP</code>	none
Create a Windows service for PSOL	<code>psolAdmin INST_SVC</code>	none
Remove the PSOL Windows service	<code>psolAdmin RMV_SVC</code>	Stop the PSOL service before attempting to remove it.

---

## Task B-3: Setting up a Reverse Proxy Server

A reverse proxy server (RPS) is a web server that acts as a front-end gateway to user requests, usually forwarding transaction requests to a back-end server and hosting the static HTML pages itself. WebLogic and WebSphere both support various popular web servers (Apache, Microsoft IIS, Sun ONE) as RPS platforms. If you would like to use WebLogic or WebSphere as a back-end server to an RPS, you can configure the RPS to host static PeopleBooks requests and forward PeopleBooks Full-Text Search (servlet) requests to the back-end server. More information on setting up an RPS can be found in the PeopleTools documentation. And instructions on configuring PeopleBooks on an RPS can be found in *About These PeopleBooks*.

### See Also

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with BEA WebLogic”

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with IBM WebSphere”

*About These PeopleBooks*, “Managing PeopleBooks and the PeopleSoft Online Library”

---

## Task B-4: Configuring Context-Sensitive Help

This section discusses:

- Enabling the Help Link from the Application Pages
- Enabling F1 Help

### Task B-4-1: Enabling the Help Link from the Application Pages

Each page in your PeopleSoft applications includes a Help icon that, when clicked, opens a new browser window displaying help topics that discuss that page.

To enable the Help link from application pages:

1. In your PeopleSoft application, navigate to the PeopleTools, Web Profile, Web Profile Configuration page.

2. Click Search and select the Profile Name you specified during your PeopleSoft Pure Internet Architecture installation.
3. Change the value for the Help URL field by replacing the "helpweb server" string with the domain name and port number of your web server. Also, if you installed to a directory other than "htmldoc" (the default), replace "htmldoc" accordingly.

*Example:*

If your PSOL server is named "mywebserver" and listens to port 5080, you would modify the default Help URL from:

```
http://helpweb server/htmldoc/flsearch.htm?ContextID=%CONTEXT_ID%&LangCD=%LANG_⇒
CD%
```

to:

```
http://mywebserver:5080/PSOL/htmldoc/flsearch.htm?ContextID=%CONTEXT_ID%&LangCD=⇒
⇒
%LANG_CD%
```

---

**Note.** The system resolves %CONTEXT\_ID% to the page name from which you called help. The system resolves %LANG\_CD% to the signon language of the user.

---



---

**Note.** If you do not want the Help icon to display in your applications, clear the Help URL field value.

---



---

**Note.** The default port for PSOL in a WebLogic multi-server domain installation is 6001.

---

4. Save and exit the Web Profile Configuration page.
5. Before testing help functionality, purge the browser cache on the client and close all web browsers. Restart the application server and web server for PIA.
6. Test the help functionality by clicking the *Help* icon on a PeopleSoft application page.

## Task B-4-2: Enabling F1 Help

This procedure describes how to enable F1 help for Application Designer, PeopleCode Editor, and other Windows-based PeopleSoft programs.

To enable F1 help:

1. Sign on to your PeopleSoft application using your browser.
2. Navigate to the PeopleTools, Utilities, Administration, PeopleTools Options page.
3. Enter the same URL as in the previous procedure (where <web\_server>/<directory>/ reflects your installation) into the F1 Help URL field:

```
http://<web_server>/<directory>/flsearch.htm?ContextID=%CONTEXT_ID%&LangCD=⇒
%LANG_CD%
```

4. Save the page.

---

## Task B-5: Administering PeopleBooks

A special browser-based tool, `psolmanager.htm`, may assist you in administering your PeopleBooks web site.

For security purposes, this tool is disabled by default on installation. When enabled, you may use it to recreate collections upon demand, and view system parameters.

See *About These PeopleBooks*, “Managing PeopleBooks and the PeopleSoft Online Library”





## APPENDIX C

# Installing PeopleTools Mobile Agent

This appendix discusses:

- Understanding PeopleTools Mobile Agent
- Finding the Installation Program
- Installing PeopleTools Mobile Agent on a Laptop
- Installing PeopleTools Mobile Agent on a PDA
- Modifying, Repairing, or Removing PeopleTools Mobile Agent
- Expediting the Initialization of a PDA
- Troubleshooting Installation Issues

---

## Understanding PeopleTools Mobile Agent

This chapter describes how to install the PeopleTools Mobile Agent software to a laptop computer or personal digital assistant (PDA).

The PeopleTools Mobile Agent is a product that is licensed separately from the PeopleTools product, and only those customers who have a license for PeopleTools Mobile Agent may install and use this product. Use of the Mobile Agent functionality described herein is subject to the licensing conditions for the PeopleTools Mobile Agent product. Please refer to the applicable contract to determine restrictions regarding this product.

---

## Task C-1: Finding the Installation Program

The installation program for PeopleTools Mobile Agent can be delivered in several ways:

- From a web site established by your administrator.
- From an FTP site established by your administrator.
- As an attachment to an email.
- As a link to a web or FTP site in an email.
- In the mobile portal web site directory of your web server:

---


**Note.** PeopleSoft delivers a sample index.html file to be used to deploy the PeopleSoft Mobile Agent from a web site. This is only a sample and needs to be modified if it is to support web server configurations other than the delivered defaults and provide option of customer branding.

---

- On an Oracle Application Server web server the location of index.html is  
c:\<OAS\_HOME>\j2ee\PeopleSoft\applications\PeopleSoft\PORTAL\ps\mobile
- On a BEA WebLogic web server the location of index.html is  
c:\<PS\_HOME>\websrv\peoplesoft\applications\peoplesoft\PORTAL\ps\mobile\
- On an IBM WebSphere web server the location of index.html is  
c:\<PS\_HOME>\websrv\<cellname\_nodename\_servername>\peoplesoft.ear\PORTAL\ps\mobile\

## Task C-2: Installing PeopleTools Mobile Agent on a Laptop

Use a web page like the following to distribute PeopleTools Mobile Agent installation files.



PeopleSoft 8 window

To install PeopleTools Mobile Agent on a laptop:

1. Locate and run setup.exe:  
The PeopleTools Mobile Agent Setup window appears.
2. Click Next.

3. Specify the directory in which PeopleTools Mobile Agent will be installed, or accept the default.
4. Click Next.
5. Select whether to automatically start PeopleTools Mobile Agent on login.
6. Click Next.
7. Select the preferred language.  
After installation, you cannot change this selection except by reinstalling PeopleTools Mobile Agent.
8. Click Next.
9. Enter the address of your Sync Server in the URL text box.  
This address will usually be the same as that of your PIA web server. For example, if you access PeopleSoft applications at <http://mywebserver/ps/signon.html>, your Sync Server address is <http://mywebserver:80/SyncServer>. Contact your system administrator to confirm this information.
10. Click Next.  
A summary page appears, listing your installation selections.
11. Click Back to change a selection, or click Next to proceed with installation.
12. Click Finish when the installation completion window appears.

---

## Task C-3: Installing PeopleTools Mobile Agent on a PDA

Installing PeopleTools Mobile Agent to a PDA requires:

- Installing the appropriate version of PeopleTools Mobile Agent to the computer that connects to your PDA.
- Installing PeopleTools Mobile Agent to your PDA.

---

**Note.** The following procedure assumes that you have already established connectivity between the computer and PDA, including applicable synchronization software.

---

To install PeopleTools Mobile Agent on a PDA:

1. Locate and run `setup_<processor_type>.exe`:  
The `<processor_type>` is the type of processor present in the PDA to which PeopleTools Mobile Agent is being installed.  
The PeopleTools Mobile Agent Welcome window appears.
2. Click Next.
3. Specify the directory in which PeopleTools Mobile Agent will be installed on the computer, or accept the default.
4. Click Next.
5. Select the preferred language.  
The only way you can change the preferred language on the PDA is by reinstalling PeopleTools Mobile Agent.
6. Click Next.

7. Enter the address of your Sync Server in the URL text box and click Next.

This address will usually be the same as that of your PIA web server. For example, if you access PeopleSoft applications at <http://mywebserver/ps/signon.html>, your Sync Server address is <http://mywebserver:80/SyncServer>. Contact your system administrator to confirm this information.

8. Click Next.

A summary page appears, listing your installation selections.

9. Click Back to change a selection, or click Next to proceed with installation.

The ActiveSync Add/Remove Programs dialog box appears.

10. Confirm the installation.

The installation proceeds. A completion message appears when installation to the PDA has finished.

11. Click Finish when the installation completion window appears.

---

## Task C-4: Modifying, Repairing, or Removing PeopleTools Mobile Agent

To modify, repair, or remove PeopleTools Mobile Agent:

1. Locate and run the appropriate program:

Installation	Program
Laptop	Setup.exe
PDA	Setup_<processor_type>.exe

The PeopleTools Mobile Agent Welcome window appears.

2. Select:
  - *Modify* to specify another preferred language
  - *Repair* to reinstall all program components
  - *Remove* to remove all installed components

You are asked to confirm any changes to the current installation.

---

## Task C-5: Expediting the Initialization of a PDA

If PeopleTools Mobile Agent is installed to a PDA, you have the option of using the processing power of the connected computer to expedite initialization (bootstrap synchronization) or update applications synchronization.

To expedite the initialization of a PDA:

1. From the Start menu of the computer connected to your PDA, select *Programs, PeopleTools Mobile Agent, PS Sync PDA*.

The PeopleTools Mobile Device Bootstrap page appears.

2. Enter your User ID and Password.

Your User ID and its associated roles determine the application metadata and business data that will be installed to your mobile device.

3. Click *Synchronize*.

The PeopleTools Mobile Synchronization Results page appears, showing the progress of your bootstrap synchronization.

4. After Update PDA Applications completes successfully, open the PeopleSoft program folder on the PDA.
5. Start PS Mobile Agent.
6. Start PS Mobile Application.
7. Select *Synchronization, Last Results* to view the synchronization results.

---

## Task C-6: Troubleshooting Installation Issues

This section discusses:

- Resolving Port Conflicts
- Configuring the Web Server

### Task C-6-1: Resolving Port Conflicts

The default HTTP listening port for PeopleTools Mobile Agent is port 8080, which is specified in the `psmobile.ini` file. If possible, ensure that port 8080 is not used by another application. If PeopleTools Mobile Agent encounters a port conflict because another process is already using port 8080, it reports an error in the log file (`\temp\psmobile.log`), and stops processing.

You can resolve the conflict by editing the `psmobile.ini` file. For example, change `Port=8080` to `Port=80` or `Port=8888`.

- For a laptop installation, edit the Port setting in the `psmobile.ini` file.  
Find the file in `C:\Windows` or `C:\WinNT`.
- For a PDA installation, copy the `psmobile.ini` file to the laptop or desktop computer using ActiveSync, edit it there, and then copy it back.

After changing the port assignment in `psmobile.ini`, start PeopleTools Mobile Agent to determine whether the new setting is acceptable.

---

**Note.** If you change the port assignment in `psmobile.ini`, update any shortcuts, bookmarks, or favorites that reference the changed setting. For example, if you changed `Port=8080` to `Port=8888`, change a browser favorite or bookmark from `http://localhost:8080` to `http://localhost:8888`. If you use PS Sync PDA to expedite PDA synchronization, change the port number in any shortcuts to the port number specified in `psmobile.ini` + 1. For example, if you change `psmobile.ini` to `Port=8888`, change the PS Sync PDA shortcut to `http://localhost:8889`.

---

### Task C-6-2: Configuring the Web Server

Configure the web server to identify the application server (Sync Server gateway) used for synchronization.

To configure the web server, edit the file SyncServerGatewayConfig.xml. The location of this file depends on the web server.

Web Server	Directory Path
Oracle Application Server	c:\<OAS_HOME>\j2ee\PeopleSoft\applications\PeopleSoft\PORTAL\WEB-INF\psftdocs\ps
BEA WebLogic	c:\<PS_HOME>\weberv\peoplesoft\applications\peoplesoft\PORTAL\WEB-INF\psftdocs\ps
IBM WebSphere	c:\<PS_HOME>\weberv\<cellname_nodename_servername>\peoplesoft.ear\PORTAL\WEB-INF\psftdocs\ps

Edit the file to reflect your environment, where:

- *Domain #1 Name Here* is an optional name for the gateway.
- *Domain #1 Description Here* is an optional description for the gateway.
- *Domain #1 Application Server Connect String Here* is the machine name and JSL port number for the gateway.
- *APP\_SRVRS* is the number of application servers configured for this gateway.

```
<?xml version='1.0'?>
<sync-gateway-config>
  <primary-domain>1</primary-domain>
    <trace-level>0</trace-level>
    <max-timeslice>10</max-timeslice>
  <domain-list>
    <domain id='1' version='1'>
      <name>Domain #1 Name Here</name>
      <description>Domain #1 Description Here</description>
      <connect>Domain #1 Application Server Connect String Here</connect>
      <thread-pool-size>APP_SRVRS</thread-pool-size>
    </domain>
  </domain-list>
</sync-gateway-config>
```

## APPENDIX D

# Installing Web Application Deployment Tools

This appendix discusses:

- Prerequisites
- Installing the Web Application Deployment Tools on Oracle Application Server in GUI Mode
- Installing the Web Application Deployment Tools on WebLogic in GUI Mode
- Installing the Web Application Deployment Tools on WebSphere in GUI Mode
- Installing the Web Application Deployment Tools on Oracle Application Server in Console Mode
- Installing the Web Application Deployment Tools on WebLogic in Console Mode
- Installing the Web Application Deployment Tools on WebSphere in Console Mode
- Testing and Troubleshooting the Web Application Deployment

---

## Prerequisites

This appendix includes instructions for installing the Web Application Deployment tools on Oracle Application Server (OAS), WebLogic, and WebSphere. Complete the instructions for the web server you selected when you carried out the PeopleTools installation. Typically, you would choose GUI mode for Windows platforms and console mode for UNIX or Linux platforms.

Before you install the Web Application Deployment tools, confirm that you have completed the following requirements.

If you use OAS as your web server, you must fulfill these requirements:

- You must install the PeopleSoft web server during the PeopleTools installation.
- The OAS 10g software must be installed.

If you use WebLogic as your web server, you must fulfill these requirements:

- JDK 1.4.x must be installed and working properly. Your PATH environment variable must include an entry for JDK 1.4.x (for example, <jdk14x>/bin). If you do not install JDK 1.4.x the deployment will fail due to the absence of a java compiler.
- You must install the PeopleSoft web server during the PeopleTools installation.
- WebLogic 8.x must be installed.

If you use WebSphere as your web server, you must fulfill these requirements:

- JRE 1.4.1 or above must be installed and working properly. You can use the JRE software that is supplied with the PeopleTools installation CD.

- You must install the PeopleSoft web server during the PeopleTools installation.
- The WebSphere 5.x software must be installed and the web server must be up and running when you carry out the Web Application Deployment tools installation.
- If you are running on UNIX or Linux, run the Web Application Deployment install with a user who owns WebSphere, and who owns <PS\_HOME>. Here are two examples: If WebSphere is owned by "root" and group "system", the Web Application Deployment install must be run with "root" and group "system." If WebSphere is owned by user "wsadmin" and group "wsadmin", then the Web Application Deployment install must be run with wsadmin/wsadmin as the user and group.

### See Also

“Installing Web Server Products”

“Using the PeopleSoft Installer”

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration.*


---

## Task D-1: Installing the Web Application Deployment Tools on Oracle Application Server in GUI Mode

To install the Web Application Deployment tools on Oracle Application Server (OAS):


1. Copy the required Web application (EAR) files to <PS\_HOME>/setup/mpwebappdeploy/archive.
2. Navigate to <PS\_HOME>/setup/mpwebappdeploy.
3. Double-click on setup.<OS>.
4. Click Next on the Welcome page.
5. Enter the same <PS\_HOME> that you specified when you ran the PeopleTools installer, and click Next.






Specifying directory on PeopleSoft Webapp Deploy window

6. Accept Oracle Application Server as the setup type, and click Next.



Selecting Oracle Application Server

7. Specify the OAS home directory, or accept the default, and click Next.  
This is the directory where you installed the OAS software.



Specifying OAS home on the PeopleSoft Webapp Deploy window


8. Enter an application name, and click Next.

---

**Note.** This is not a PeopleSoft Application package name.


---

A new OC4J component will be created using the user-specified application name.




Entering the Application Name for the PeopleSoft Webapp Deploy window

9. Select the application package to deploy, and click Next.



Selecting the application package on the PeopleSoft Webapp Deploy window


10. Specify Application Information:



Entering application information on PeopleSoft Webapp Deploy window


11. Enter port numbers, and click Next.

**Note.** Review the reserved port numbers for OAS in the file <OAS\_HOME>/install/portlist.ini and enter a different port number here.




Entering port numbers on PeopleSoft Webapp Deploy window

12. Verify that the information on the confirmation window is correct, and click Next.




Verifying information on PeopleSoft Webapp Deploy window

A progress window appears.



Progress window for PeopleSoft Webapp Deploy

13. A confirmation window appears when the installation is complete. Click Finish to exit.



Successful installation on the PeopleSoft Webapp Deploy window


## Task D-2: Installing the Web Application Deployment Tools on WebLogic in GUI Mode

Use these instructions to install the Web Application Deployment Tools on WebLogic in GUI mode.

1. Copy the required Web Applications (EAR) files to <PS\_HOME>/setup/mpwebappdeploy/archive.
2. Navigate to <PS\_HOME>/setup/mpwebappdeploy.
3. Double-click on setup.exe.


**Note.** If the setup executable fails, and an error message appears saying the JVM directory cannot be found, open a command prompt. Navigate to <PS\_HOME>\setup\mpwebappdeploy, and use the command `setup.exe -is:javahome <jre_dir>`, where <jre\_dir> is the location of the JRE files.

4. Click Next on the Welcome page.
5. Enter the same <PS\_HOME> directory that you specified when you ran the PeopleTools Installer.
6. Select BEA WebLogic Server and click Next.



Selecting BEA WebLogic on the PeopleSoft Webapp Deploy window

7. Specify the root directory where you installed WebLogic, and click Next.



Specifying the WebLogic root directory on the PeopleSoft Webapp Deploy window


8. Enter the login ID and password for the new domain that you are creating. Click Next to continue.
9. Enter a name for the Web Application Deploy domain, or accept the default name. Use a fully qualified domain name, and do not use an IP address. Click Next to continue.

---

**Important!** The domain that you create for the Web Application Deploy cannot be the same as any existing PeopleSoft Pure Internet Architecture domains. Be sure you do not enter a name that you used for a PeopleSoft Pure Internet Architecture domain.

---


10. The next window lists all of the available application packages (EAR files). Select the packages you want to install. *You must select at least one application package from this list.*



Selecting application packages from the PeopleSoft Webapp Deploy window

11. Select the type of domain to create from these options:


See “Setting Up the PeopleSoft Pure Internet Architecture in GUI Mode,” Installing the PeopleSoft Pure Internet Architecture in GUI Mode.



Selecting the domain type from the PeopleSoft Webapp Deploy window




- **Single Server Domain:** This configuration is intended for single users or very small scale, non-production environments.
  - **Multi-Server Domain:** This configuration is intended for a production environment.
  - **Distributed Managed Server:** This option is an extension of the Multi-Server Domain selection and installs the necessary files to boot a managed server. This option requires a Multi-Server installation to be performed to some other location, which will contain the configuration for this managed server.
12. If the application(s) you selected in step 10 requires additional information, a window appears with entry fields for the required information. For example:

The screenshot shows a window titled "PeopleSoft Webapp Deploy". On the left side, there is a vertical panel with the "PeopleSoft Enterprise" logo and the "ORACLE" logo below it, with the text "Copyright © 1988, 2006, Oracle." at the bottom. The main area of the window is titled "CRM OMK:" and contains several input fields: "Database Type" (with "MSSQL" entered), "Database Server Name", "Database Port Number" (with "0" entered), "Database Instance Name", "Database User Name" (with "Admin" entered), and "Database User Password". At the bottom of the window, there are three buttons: "< Back", "Next >", and "Cancel". The "Next >" button is highlighted with a dashed border.


Specifying application information on the PeopleSoft Webapp Deploy window

13. Enter HTTP and HTTPS port numbers. Click Next to continue.




Entering port numbers on the PeopleSoft Webapp Deploy window

14. Verify your installation information on the summary screen that appears. Click Deploy to begin the installation, Back to go back to make changes on an earlier window, or Cancel to exit the installation.



Verifying installation information on the PeopleSoft Webapp Deploy window

15. A confirmation screen appears when the installation completes. Click Finish to exit the install shield wizard.



Final confirmation on PeopleSoft Webapp Deploy window

---

## Task D-3: Installing the Web Application Deployment Tools on WebSphere in GUI Mode

Use these instructions to install the Web Application Deployment Tools on WebSphere in GUI mode.

1. Copy the required Web Applications (EAR) files to <PS\_HOME>\setup\mpwebappdeploy\archive.
2. Start WebSphere on the server on which you plan to deploy the Web Application Deployment tools. Open a command prompt, navigate to the \bin directory under the root directory where you installed WebSphere (<WAS\_HOME>\bin), and enter:

```
startServer.bat <server_name>
```


3. Navigate to <PS\_HOME>\setup\mpwebappdeploy.
4. Double-click on setup.exe.

---

**Note.** If the setup executable fails, and an error message appears saying the JVM directory cannot be found, open a command prompt. Navigate to <PS\_HOME>\setup\mpwebappdeploy, and use the command `setup.exe -is:javahome <jre_dir>`, where <jre\_dir> is the location of the JRE files.


---

5. Click Next on the Welcome page.
6. Enter the same <PS\_HOME> directory that you specified when you ran the PeopleTools Installer.
7. Select IBM WebSphere and click Next.



Selecting IBM WebSphere on the PeopleSoft Webapp Deploy window

8. Specify the root directory where you installed WebSphere, and the cell name, node name and server name of the WebSphere server.



Specifying the WebSphere directory on the PeopleSoft Webapp Deploy window

**Note.** If the web server on which you are installing the Web Application Deployment tools is not up and running, you receive an error message at this point instructing you to start your web server.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*


9. Enter a name for the Web Application Deploy domain, or accept the default name. Use a fully qualified domain name, and do not use an IP address. Click Next to continue.

---

**Important!** The domain that you create for the Web Application Deploy cannot be the same as any existing PeopleSoft Pure Internet Architecture domains. Be sure you do not enter a name that you used for a PeopleSoft Pure Internet Architecture domain.


---

10. The next window lists all of the available application packages (EAR files). Select the packages you want to install. *You must select at least one application package from this list.*



Selecting application packages on the PeopleSoft Webapp Deploy window


11. If the application(s) you selected in step 10 requires additional information, a window appears with entry fields for the required information. For example:



The screenshot shows the 'PeopleSoft Webapp Deploy' window. On the left is a logo for 'PeopleSoft Enterprise' with the 'ORACLE' logo below it and 'Copyright © 1988, 2006, Oracle.' at the bottom. The main area is titled 'CRM OMK:' and contains several input fields: 'Database Type' (MSSQL), 'Database Server Name' (empty), 'Database Port Number' (0), 'Database Instance Name' (empty), 'Database User Name' (Admin), and 'Database User Password' (empty). At the bottom right are three buttons: '< Back', 'Next >', and 'Cancel'. The 'InstallShield' logo is visible at the bottom left of the main area.

Specifying application information on the PeopleSoft Webapp Deploy window


12. Enter HTTP and HTTPS port numbers. Click Next to continue.



The screenshot shows the 'PeopleSoft Webapp Deploy' window with the title 'Enter port numbers.' The input fields are: 'HTTP Port:' (80) and 'HTTPS Port:' (443). The layout is identical to the previous screenshot, including the logo on the left and the buttons at the bottom right.


Entering port numbers on the PeopleSoft Webapp Deploy window for WebSphere

13. Verify your installation information on the summary screen that appears. Click Deploy to begin the installation, Back to go back to make changes on an earlier window, or Cancel to exit the installation.



Verifying installation information on the PeopleSoft Webapp Deploy

14. A window appears with a progress indicator. A confirmation screen appears when the installation completes. Click Finish to exit the install shield wizard.



Confirming installation on the PeopleSoft Webapp Deploy window

## Task D-4: Installing the Web Application Deployment Tools on Oracle Application Server in Console Mode

To install the Web Application Deployment Tools on OAS in console mode:

---

**Note.** The console mode installation is typically used on UNIX platforms.

---

1. Copy the required Web Applications (EAR) files to <PS\_HOME>/setup/mpwebappdeploy/archive.
2. Set up the PeopleSoft environment as follows:

```
cd <PS_HOME>
../psconfig.sh
```

3. To run the installer:

```
cd <PS_HOME>/setup/mpwebappdeploy
setup.<OS> -console [-is:javahome<jre14x>]
```

- Use the same platform-specific extension for the setup executable as you used for the PeopleSoft Installer.

See “Using the PeopleSoft Installer,” Running the PeopleSoft Installer.

- Use the optional flag `-is:javahome<jre14x>` if you installed the JRE/JDK files in a directory that is different than the vendor-defined JRE search path. For example, to run on a HP-UX platform and use the JRE that PeopleSoft supplies with PeopleTools, use the command `setup.hp -console -is:javahome <PS_HOME>/jre`.

4. You see a welcome message. Enter */* to continue.

```
Welcome to the InstallShield Wizard for PeopleSoft Webapp Deploy Tool.
```

```
Using the InstallShield Wizard you will deploy PeopleSoft Application(s) on⇒
your computer.
```

```
Note: If installing onto a BEA WebLogic Server, make sure to shutdown any⇒
running web servers to avoid web server corruption.
```

```
Select Next to continue or Cancel to exit.
```

```
Press 1 for Next, 3 to Cancel or 4 to Redisplay [1]
```

5. Choose the <PS\_HOME> directory that you specified when you installed PeopleTools. Enter */* to continue.

```
Choose the directory where you installed PeopleSoft, commonly known as "PS_⇒
HOME":
```

```
Please specify a directory name or press Enter [/opt/PS_HOME]
```

```
Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]
```

6. Press ENTER to select the default, Oracle Application Server, at the following prompt, and then enter */* to continue.

```
Choose the setup type that best suits your needs.
```

```
[X] 1 - Oracle Application Server
```



```
[ ] 2 - BEA WebLogic Server
[ ] 3 - IBM WebSphere Server
To select an item enter its number, or 0 when you are finished: [0]
Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]
```

7. Enter the directory where you installed the OAS software, and press ENTER to continue at the following prompt.

```
Select the web server root directory:
Please specify a directory name or press ENTER [/home/OraHome_1]
```

8. Enter a name for the web application, or accept the default name.

```
Enter application name or click Next to select default:
```

```
[CRMOLM]
```

A New OC4J component will be created using the user-specified application name.

9. The next prompt lists all of the available application packages (EAR files). Enter the numbers beside the packages you want to install. *You must select at least one application package from this list.*

```
Please select the application package to deploy:
```

```
[X] 1 - CRM Package
[ ] 2 - Financial Package
```

```
To select an item enter its number, or 0 when you are finished [0]:
```

10. If the application(s) you selected in step 9 requires additional information, supply the necessary information at the next prompt. For example:

```
CRM OMK :
```

```
Database Type
[MSSSQL]
```

```
Database Server Name
[ ]
```

```
Database Port Number
[0]
```

```
Database Instance Name
[ ]
```

```
Database User Name
[Admin]
```

```
Database User Password
[ ]
```

11. Enter HTTP and HTTPS port numbers.

---

**Note.** Review the reserved port numbers for OAS in the file <OAS\_HOME>/install/portlist.ini and enter a different port number here.

---

Enter port numbers.

HTTP Port : [80] 8091

HTTPS Port : [443] 4431

12. Verify your installation information on the next prompt and press ENTER to begin the installation. An indicator shows your installation progress.

Please verify the following information:

Setup Type : OAS

Web server root directory : /home/OraHome\_1

Web server version : 10.1.2

PeopleSoft App Name : CRMOLM

HTTP Port : 8091

HTTPS Port : 4431

Selected deploy package(s) : crm\_omk\_wl.ear

13. A confirmation screen appears when the installation completes. Click Finish to exit the install shield wizard.

---

## Task D-5: Installing the Web Application Deployment Tools on WebLogic in Console Mode

Use these instructions to install the Web Application Deployment Tools on WebLogic in console mode.

---

**Note.** The console mode installation is typically used on UNIX platforms.

---

1. Copy the required Web Applications (EAR) files to <PS\_HOME>/setup/pswebappdeploy/archive.
2. Set up the PeopleSoft environment as follows:

```
cd <PS_HOME>
../psconfig.sh
```

3. To run the installer:

```
cd <PS_HOME>/setup/pswebappdeploy
```

```
setup.<platform> -console [-is:javahome<jre14x>]
```

- Use the same platform-specific extension for the setup executable as you used for the PeopleSoft Installer.

See “Using the PeopleSoft Installer,” Running the PeopleSoft Installer.

- Use the optional flag `-is:javahome<jre14x>` if you installed the JRE/JDK files in a directory that is different than the vendor-defined JRE search path. For example, to run on a HP-UX platform and use the JRE that PeopleSoft supplies with PeopleTools, use the command `setup.hp -console -is:javahome <PS_HOME>/jre`.

4. You see a welcome message. Enter */* to continue.

```
Welcome to the InstallShield Wizard for PeopleSoft Webapp Deploy Tool.
```

```
Using the InstallShield Wizard you will deploy PeopleSoft Application(s) on⇒
your computer.
```

```
Note: If installing onto a BEA WebLogic Server, make sure to shutdown any⇒
running web servers to avoid web server corruption.
```

```
Select Next to continue or Cancel to exit.
```

```
Press 1 for Next, 3 to Cancel or 4 to Redisplay [1]
```

5. Choose the `<PS_HOME>` directory that you specified when you installed PeopleTools. Enter */* to continue.

```
Choose the directory where you installed PeopleSoft, commonly known as "PS_⇒
HOME":
```

```
Please specify a directory name or press Enter [/opt/PS_HOME]
```

```
Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]
```

6. Enter 2 to select BEA WebLogic Server, at the following prompt, and then enter */* to continue.

```
Choose the setup type that best suits your needs.
```

```
[X] 1 - Oracle Application Server
```

```
[ ] 2 - BEA WebLogic Server
```

```
[ ] 3 - IBM WebSphere Server
```

```
To select an item enter its number, or 0 when you are finished: [0]
```

```
Press 1 for Next, 2 for Previous, 3 to Cancel or 4 to Redisplay [1]
```

7. Enter the directory where you installed WebLogic, and press ENTER to continue at the following prompt.

```
Select the web server root directory:
```

```
Please specify a directory name or press ENTER [/opt/bea_ps]
```

---

**Note.** You receive an error message if the correct WebLogic version is not found in the directory you enter.

---

8. Enter a name for the Web Application Deploy domain, or accept the default name. Use a fully qualified domain name, and do not use an IP address.

```
Enter domain name or click Next to select default:
```

```
[PSWebApp]
```

---

**Important!** The domain that you create for the Web Application Deploy cannot be the same as any existing PeopleSoft Pure Internet Architecture domains. Be sure you do not enter a name that you used for a PeopleSoft Pure Internet Architecture domain.

---

9. Enter the administrator login and password for your WebLogic domain, and press ENTER to continue.

Please enter the administrator login and password for WebLogic domain.

Login ID:

[system]

Password:

[password]

Re-type Password:

[password]

10. The next prompt lists all of the available application packages (EAR files). Enter the numbers beside the packages you want to install. *You must select at least one application package from this list.*

Please select the application package to deploy:

[X] 1 - CRM Package  
[ ] 2 - Financial Package

To select an item enter its number, or 0 when you are finished [0]:

11. Select the type of domain to create—single server, multi server, or distributed managed server.

See “Setting Up the PeopleSoft Pure Internet Architecture in Console Mode,” Installing the PeopleSoft Pure Internet Architecture in Console Mode.

Please select the configuration to install.

[X] 1 - Single Server Domain  
[ ] 2 - Multi Server Domain  
[ ] 3 - Distributed Managed Server

To select an item enter its number, or 0 when you are finished: [0]

- **Single Server Domain:** This configuration is intended for single user or very small scale, non-production environments.
- **Multi-Server Domain:** This configuration is intended for a production environment.
- **Distributed Managed Server:** This option is an extension of the Multi-Server Domain selection and installs the necessary files to boot a managed server. This option requires a Multi Server installation to be performed to some other location, which will contain the configuration for this managed server.

12. If the application(s) you selected in step 10 requires additional information, supply the necessary information at the next prompt. For example:

CRM OMK :

Database Type

[MSSQL]

Database Server Name

[ ]

Database Port Number

[0]

Database Instance Name

[ ]

Database User Name

[Admin]

Database User Password

[ ]

13. Enter HTTP and HTTPS port numbers.

Enter port numbers.

HTTP Port : [80] 8091

HTTPS Port : [443] 4431

14. Verify your installation information on the next prompt and press ENTER to begin the installation. An indicator shows your installation progress.

Please verify the following information:

Setup Type : weblogic

Web server root directory : /opt/bea\_ps

Web server version : 8.1

Web server domain : PSWebApp

HTTP Port : 8091

HTTPS Port : 4431

Selected deploy package(s) : CRM Package.ear

Package(s) webserver directory : /opt/PS\_HOME/webserv

15. After the installation is complete, you must deploy the Web Application Deploy tools. Use the following commands:

```
cd <PS_HOME>/webserve/<domain_name>
startPSWEBAPPS.sh
```

For <domain\_name>, use the name you entered in step 8.

---

**Note.** You can choose to deploy at a later time using the same commands.

---

## Task D-6: Installing the Web Application Deployment Tools on WebSphere in Console Mode

Use these instructions to install the Web Application Deployment Tools on WebSphere in console mode.

---

**Note.** The console mode installation is typically used on UNIX platforms.

---

1. Copy the required Web Applications (EAR) files to <PS\_HOME>/setup/pswebappdeploy/archive.
2. Set up the PeopleSoft environment using the following commands:

```
cd <PS_HOME>
../psconfig.sh
```

3. Start WebSphere on the server on which you plan to deploy the Web Application Deployment tools. Navigate to the bin directory under the directory where you installed WebSphere, <WAS\_HOME>. Use the following commands:

```
cd <WAS_HOME>/bin
startServer.sh <server_name>
```

4. To run the installer:

```
cd <PS_HOME>/setup/pswebappdeploy
setup.<platform> -console [-is:javahome<jre14x>]
```

- Use the same platform-specific extension for the setup executable as you used for the PeopleSoft Installer. See “Using the PeopleSoft Installer,” Running the PeopleSoft Installer.
- Use the optional flag `-is:javahome<jre14x>` if you installed the JRE/JDK files in a directory that is different than the vendor-defined JRE search path. For example, to run on a HP-UX platform and use the JRE that PeopleSoft supplies with PeopleTools, use the command `setup.hp -console -is:javahome <PS_HOME>/jre`.

5. You see a Welcome message. Enter *I* to continue.

```
Welcome to the InstallShield Wizard for PeopleSoft Webapp Deploy Tool.
Using the InstallShield Wizard you will deploy PeopleSoft Application(s) onyour⇒
computer.
```

Note: If installing onto a BEA WebLogic Server, make sure to shutdown any⇒  
running web servers to avoid web server corruption.

Select Next to continue or Cancel to exit.

Press 1 for Next, 3 to Cancel or 4 to Redisplay [1]

6. Choose the same <PS\_HOME> directory that you specified when you ran the PeopleTools Installer.

Choose the directory where you installed PeopleSoft, commonly known as "PS\_⇒  
HOME":

Please specify a directory name or press Enter [/opt/PS\_HOME]

7. Enter 3, to select the IBM WebSphere Server, at the following prompt:

Choose the setup type that best suits your needs.

```
[X] 1 - Oracle Application Server
[ ] 2 - BEA WebLogic Server
[ ] 3 - IBM WebSphere Server
```

To select an item enter its number, or 0 when you are finished: [0]

8. Enter the root directory where you installed WebSphere at the following prompt, and press ENTER to continue:

Select the WebSphere Server directory:

Directory Name:

Please specify a directory name or press Enter [/opt/webserv]

---

**Note.** If the web server on which you are installing the Web Application Deployment tools is not up and running, you receive an error message at this point instructing you to start your web server.

---

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*.

9. At the next prompts, enter a cell name, node name, and server name.
10. Enter a name for the Web Application Deploy domain, or accept the default name. Use a fully qualified domain name, and do not use an IP address. Press / to continue.

Enter domain name or click Next to select default:

[PSWebApp]

---

**Important!** The domain that you create for the Web Application Deploy cannot be the same as any existing PeopleSoft Pure Internet Architecture domains. Be sure you do not enter a name that you used for a PeopleSoft Pure Internet Architecture domain.

---

11. The next prompt lists all of the available application packages (EAR files). Enter the number corresponding to the packages you want to install. *You must select at least one application package from this list.*

Please select the application package to deploy:

```
[X] 1 - CRM Package
[ ] 2 - Financial Package
```

To select an item enter its number, or 0 when you are finished [0]:

12. If the application(s) you selected in the previous step requires additional information, supply the necessary information at the next prompt. For example:

CRM OMK :

Database Type  
[MSSQL]

Database Server Name  
[ ]

Database Port Number  
[0]

Database Instance Name  
[ ]

Database User Name  
[Admin]

Database User Password  
[ ]

13. Enter HTTP and HTTPS port numbers at the following prompt. Press */* to continue.

Enter port numbers.

HTTP Port: [80] 8091

HTTPS Port: [443] 4431

14. Verify your installation information at the next prompt and press ENTER to begin the installation. An indicator shows your installation progress.
15. A confirmation screen appears when the installation completes. Click Finish to exit the install shield wizard.
16. After the installation is complete, you must stop and start the WebSphere server. Use the following commands:

```
cd <WAS_HOME>/bin
../stopServer.sh <server_name>
../startServer.sh <server_name>
```

For <server\_name>, use the name of the WebSphere server you used in step 3.



---

## Task D-7: Testing and Troubleshooting the Web Application Deployment

Check the log file for any problems encountered during installation. The log file is saved in the following locations:

- If you installed on OAS, the log files are found in <OAS\_HOME>/j2ee/home/webappdeploy\_install.log.
- If you installed on WebLogic, the log file is found in <PS\_HOME>/webserver/<domain\_name>logs/\*.log
- If you installed on WebSphere, look in <WAS\_HOME>/appserver/log/<server\_name>\*.log

If you need to start or stop OAS, WebLogic, or WebSphere, use the commands given in the chapter on installing the PeopleSoft Pure Internet Architecture.

See “Setting Up the PeopleSoft Pure Internet Architecture (in GUI Mode or Console Mode),” Testing the PeopleSoft Pure Internet Architecture Installation.



## APPENDIX E

# Creating a Database Manually on Windows

This appendix discusses:

- Understanding Database Creation
- PeopleSoft Database Installation Prerequisites
- Creating the Windows Service for the Database Instance
- Editing Database Scripts
- Using SQL Tools
- Creating an Oracle Instance
- Creating Catalog Views and Utility Tablespaces
- Creating PS.PSDBOWNER Table
- Creating Application-Specific Dbspaces and Tablespaces
- Creating PeopleSoft Database Roles
- Creating the PeopleSoft Database Owner ID
- Setting Up Connect ID
- Updating Connection Information
- Setting NLS\_LANG in the Windows Registry
- Creating Data Mover Import Scripts
- Running Data Mover Import Scripts
- Updating Database to Latest PeopleTools Release
- Running Additional Data Mover Scripts
- Installing a Multilingual PeopleTools System Database
- Running VERSION Application Engine Program
- Changing the Base Language
- Running SQR Reports
- Checking the Database
- Running SETSPACE.SQR

---

## Understanding Database Creation

This section describes the tasks required to create a PeopleSoft product database. During a standard PeopleSoft installation you will execute these tasks to create two distinct types of databases.

- *System*: The System database has no company specific data, and can be used to load your data and begin development of your production database.
- *Demo*: The Demo database contains data for a sample company, and can be used immediately for demonstration, for testing, and as a development reference.

The requirements for these databases vary, so not all of this section's tasks apply to each database. The instructions will note any distinctions between creating a Demo and a System database.

Remember, you need to have the PeopleTools Development Environment set up to create your database.

---

**Important!** Do not forget that application-specific installation steps are provided in a separate document specific to the application. For instance, if you are performing PeopleSoft CRM installation, you need both this PeopleTools installation guide and any additional instructions provided by CRM. To find the installation documentation specific to your application, go to PeopleSoft Customer Connection. Under the Site Index, find the category "Installation Guides and Notes," and then look under the subcategory for your particular application.

---

---

**Important!** If you are installing PeopleSoft on an Oracle 10g RAC database, there are additional configuration procedures that you must follow.

---

See "Setting Up the PeopleSoft Installation with Oracle 10g RAC."

---

## Task E-1: PeopleSoft Database Installation Prerequisites

This section discusses:

- Installing the PeopleSoft Database Server Components on the Database Server
- Installing the Oracle RDBMS Software
- Obtaining Windows Administrator Authority
- Creating an INIT<SID>.ORA File
- Creating Target Directory Paths
- Setting the ORACLE\_SID Environment Variable

### Task E-1-1: Installing the PeopleSoft Database Server Components on the Database Server

To create a PeopleSoft Database you *must have installed* the PeopleSoft software on your database server by running the PeopleSoft Installer and choosing the Database Server option, as described in a previous chapter. In addition, you need to install your application CD to your database server before loading the database.

See "Using the PeopleSoft Installer."

---

**Note.** Remember, you need to have the PeopleTools Development Environment set up to create your database.

---

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “PeopleSoft Configuration Manager.”

## Task E-1-2: Installing the Oracle RDBMS Software

The rest of this chapter assumes that the Oracle RDBMS software is installed on your database server. If you have not already done so, install the Oracle RDBMS software now. During the database creation process, we refer to an existing Oracle RDBMS installation. Specifically:

`$ORACLE_HOME` and `$ORACLE_HOME\bin`

## Task E-1-3: Obtaining Windows Administrator Authority

To create a database instance on Windows, you must be a Windows administrator of the target server. This is necessary because creating an instance on Windows requires creating a SERVICE using the Oracle 'ORADIM' command to add a Windows service. On UNIX, an Oracle SID is comprised of many different processes. On Windows, an Oracle SID is run as a single Windows service and you need to be an administrator to create that service.

---

**Note.** You must also be part of the ORA\_DBA group.

---

## Task E-1-4: Creating an INIT<SID>.ORA File

You must create an init.ora with the naming convention of init<SID>.ora in the ORACLE\_HOME\database directory of the Oracle installation. The init.ora file is referenced in two places during the database creation process.

- Using the ORADIM command to create the Windows Service
- Executing the CREATEDB.SQL script

Please add or modify the following init.ora parameters:

```
DB_NAME = <SID>
DB_FILES = specify max allowed per your OS, typically 1021
OPEN_CURSORS = 255 <This is a minimum value. You may choose to set this higher>
db_block_size = 8192
```

---

**Note.** Beginning with PeopleTools PT8.46, PeopleTools supports Oracle 9i and 10g. The PeopleSoft scripts are delivered to work across all versions of the Oracle RDBMS that PeopleSoft will support for this release of PeopleTools.

Because Oracle 9i is now the minimum Oracle RDBMS version supported, the PeopleSoft database creation scripts are delivered to support Automatic Undo. That is, the scripts that PeopleSoft delivers assume an init.ora with UNDO\_MANAGEMENT parm set to AUTO.

If you want to use Manual Undo (for example, for rollback segments), make sure you set your UNDO\_MANAGEMENT parm to MANUAL and modify the CREATEDB.SQL and UTLSPACE.SQL scripts as necessary to implement Manual Undo.

---

---

**Note.** The default DB\_BLOCK\_SIZE in the init.ora file is 8192 or 8K. For PeopleSoft ANSI databases this is more than adequate. For PeopleSoft Unicode databases (for example, CHARACTER\_SET UTF8), a DB\_BLOCK\_SIZE value of 8K is required.

---



---

**Note.** Search the Supported Platforms page on PeopleSoft Customer Connection for more parameters that may be required for the INIT<SID>.ora file.

---

See “Required Operating System, RDBMS & Additional Component Patches for Installation,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise. Select your database platform.)

## Task E-1-5: Creating Target Directory Paths

You must create the directory path structure for the target directories referenced in the scripts that are executed by the database creation process. The referenced directories are not created on the fly, so they need to exist when referenced.

---

**Note.** If you want to use something other than the delivered directory paths, you need to modify the CREATEDB.SQL, CREATEDB10.SQL, UTLSPACE.SQL, and xxDDL.SQL scripts in the <PS\_HOME>\scripts directory, replacing the delivered paths with paths that are appropriate for your site installation prior to creating the database.

---

Here are some examples of directory path structure references.

The delivered CREATEDB.SQL script makes the following directory path structure references:

---

**Note.** Portions of the script have been omitted for clarity.

---

```
startup nomount pfile=%ORACLE_HOME%\database\init<SID>.ora

DATAFILE      '<drive>:\oradata\<SID>\system01.dbf'    SIZE    400M
LOGFILE       '<drive>:\oradata\<SID>\log01.dbf'        SIZE     70M,
              '<drive>:\oradata\<SID>\log02.dbf'        SIZE     70M;
```

The init<SID>.ora parameter file that is referenced in the CREATEDB.SQL script makes the following directory path structure references:

---

**Note.** Portions of the init<SID>.ora parameter file have been omitted for clarity. These paths are hardcoded by the user creating the init<SID>.ora parameter file.

---

*Control file references:*

```
control_files = ("c:\apps\db\Oracle9i\oradata\ORCl\control01.ctl", "c:\apps\db⇒
\Oracle9i\oradata\ORCl\control02.ctl", "c:\apps\db\Oracle9i\oradata\ORCl⇒
\control03.ctl")
```

*Trace and Alert Log file references:*

```
background_dump_dest = c:\apps\db\Oracle9i\admin\ORCl\bdump
core_dump_dest = c:\apps\db\Oracle9i\admin\ORCl\cdump
user_dump_dest = c:\apps\db\Oracle9i\admin\ORCl\udump
```

The delivered UTLSPACE.SQL script makes the following directory path structure references:

---

**Note.** Portions of the script have been omitted for clarity.

---

```
CREATE TABLESPACE      PSRBS
DATAFILE                '<drive>:\oradata\<SID>\psrbs01.dbf'      SIZE 300M
DEFAULT STORAGE (      INITIAL          4M
                        NEXT             4M
                        PCTINCREASE     0  );

CREATE TEMPORARY TABLESPACE      PSTEMP
TEMPFILE                        '<drive>:\oradata\<SID>\pstemp01.dbf'      SIZE 300M
EXTENT MANAGEMENT LOCAL UNIFORM SIZE 128K;

CREATE TABLESPACE      PSDEFAULT
DATAFILE                '<drive>:\oradata\<SID>\psdefault.dbf'      SIZE 10M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE;
```

The delivered XXDDL.SQL scripts make the following directory path structure references:

---


**Note.** This is a sample of the first several Create Tablespace SQL statements in the xxDDL.SQL script. The rest of the script has been omitted here for clarity.

---

```
CREATE TABLESPACE PSIMAGE DATAFILE '<drive>:\oradata\<SID>\psimage.dbf' SIZE 8M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
/
CREATE TABLESPACE PSINDEX DATAFILE '<drive>:\oradata\<SID>\psindex.dbf' SIZE 64M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
/
CREATE TABLESPACE PTAPP DATAFILE '<drive>:\oradata\<SID>\ptapp.dbf' SIZE 4M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
/
```

## Task E-1-6: Setting the ORACLE\_SID Environment Variable

Make sure that you have the ORACLE\_SID parameter set in your user or system environment variables.



Setting the ORACLE\_SID environment variable

## Task E-2: Creating the Windows Service for the Database Instance

Before running the CREATEDB.SQL script and all other scripts needed to create a database, you must first create a Windows service. This is necessary because creating an instance on Windows requires creating a SERVICE using the Oracle 'ORADIM' command to add a Windows service. On UNIX, an Oracle SID is comprised of many different processes. On Windows, an Oracle SID is run as a single Windows service and you need to be an administrator to create that service. You must also be part of the ORA\_DBA group.

To create a Windows service:

1. Log on to your database server using an ID that is both a Server Administrator and part of the ORA\_DBA administrative group.
2. To create the Windows service, open up a windows command prompt window.
3. Set the ORACLE\_SID value to the Oracle database SID you're going to create:

```
Set ORACLE_SID=FDMO
```

4. If you choose to use an Oracle Password file, you need to create one using the ORAPWD utility, as illustrated in this example:

```
Set ORACLE_SID=FDMO
```

```
orapwd file=c:\ora9i\database\pwdtemp2.ora password=manager entries=5
```



---

**Note.** If you choose not to use an Oracle Password file, don't forget to comment out or remove the following parameter in the init.ora file:

remote\_login\_passwordfile=EXCLUSIVE

---

- Using the ORADIM utility as directed in the following example to create the Windows Oracle Service associated with the SID you are creating:

```
oradim -new -sid FDMO -intpwd manager -startmode auto -pfile c:\ora9i\admin⇒
\FDMO\pfile\init.ora
```

---

## Task E-3: Editing Database Scripts

This section discusses:

- Understanding Database Scripts
- Modifying Database Scripts

### Understanding Database Scripts

The scripts required for creating the database scripts reside in the <PS\_HOME>\scripts\nt directory on the file server. You need to edit a few of these scripts for your environment before you execute them and go on with the following procedures.

Typically, you need to modify the file system locations and the Oracle SID name.

### Task E-3-1: Modifying Database Scripts

To edit required database scripts:

- Go to the <PS\_HOME>\scripts\nt directory on the file server.
- Edit the scripts to conform to your environment.

The following list presents the necessary scripts:

- CREATEDB.SQL or CREATEDB10.SQL (for Oracle 10g installs)

---

**Note.** When editing CREATEDB.SQL or CREATEDB10.SQL, if you are creating a Unicode database, you need to choose an Oracle character set supported by PeopleSoft. Insure that the CHARACTER SET parameter in the CREATE DATABASE statement is set to UTF8.

---

- CONNECT.SQL.

Edit CONNECT.SQL only if you do not wish to use the default CONNECT\_ID.

- UTLSPACE.SQL.
- XXDDL.SQL, where XX is a two-letter code for your product line, as listed in the table below.

Code	Product Line
CR	Customer Relationship Management
EP	Financials / Supply Chain Management
FO	Staffing Front Office
HC	HRMS
IM	Incentive Management
LM	Enterprise Learning Management
PA	Enterprise Portal
PF	Enterprise Performance Management
SA	Student Administration/ Contributor Relations

**Note.** This is a complete list of available product lines for PeopleTools 8.4x. Note that not all products go out on all PeopleTools releases, so you may not see a script corresponding to every product line. In addition, some bolt-on products reference their own scripts within their application installation documentation. Check PeopleSoft Customer Connection to confirm that the product is supported for a specific release and database platform.

See PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise).

**Note.** For multilanguage installs, you need to increase the size of the PTTBL, PSIMAGE, and PSINDEX tablespaces. Refer to the comments in the DDL scripts for further details regarding the incremental increase for each additional language.

### See Also

“Using the PeopleSoft Installer”

*Enterprise PeopleTools 8.48 Hardware and Software Requirements*

## Task E-4: Using SQL Tools

When you execute PeopleSoft SQL scripts, use the appropriate tool included with your version of the RDBMS. You should use SQL\*Plus, which is available with each PeopleSoft supported version of the Oracle RDBMS.

## Task E-5: Creating an Oracle Instance

Run the CREATEDB.SQL or CREATEDB10.SQL script from SQL\*Plus to create an Oracle database.

To create an Oracle database:

1. Invoke SQL\*PLUS (sqlplus), connecting as sysdba.

```
$sqlplus '/as sysdba'
```

2. Run the CREATEDB.SQL or CREATEDB10.SQL script, using the following example as a guide:

```
sqlplus>@<PS_HOME>\scripts\nt\createdb.sql
```

---

**Note.** Beginning with PeopleTools PT8.46, PeopleTools supports Oracle 9i and 10g. The CREATE DATABASE parameters are distinctly different between an Oracle 9i and Oracle 10g install. To support both versions we have delivered a different script to use for Oracle 10g installs: CREATEDB10.SQL. The CREATEDB.SQL script can be used for any Oracle 9i supported release.

---

---

**Note.** When editing CREATEDB.SQL or CREATEDB10.SQL, if you are creating a Unicode database, you need to choose an Oracle character set that is supported by PeopleSoft. Insure that the CHARACTER SET parameter in the CREATE DATABASE statement is set to UTF8.

---

---

## Task E-6: Creating Catalog Views and Utility Tablespaces

Run the UTLSPACE.SQL script from SQL\*Plus to create catalog views and utility tablespaces.

To create catalog views and utility tablespaces:

1. Invoke SQL\*Plus (sqlplus), connecting as sysdba.
2. Run the UTLSPACE.SQL script:

```
sqlplus>@<PS_HOME>\scripts\nt\utlspace.sql
```

---

## Task E-7: Creating PS.PSDBOWNER Table

Run the DBOWNER.SQL script from SQL\*Plus to create the PS.PSDBOWNER table.

To create the PS.PSDBOWNER table:

1. Invoke SQL\*Plus (sqlplus), connecting as sysdba.
2. Run the DBOWNER.SQL script, using the following example as a guide:

```
sqlplus>@<PS_HOME>\scripts\nt\dbowner.sql
```

## Task E-8: Creating Application-Specific Dbspaces and Tablespaces

To create tablespaces for the product you are installing, run the appropriate *XXDDL.SQL* scripts, logged on as the system user, where *XX* stands for your product line, as spelled out in the table below.

Code	Product Line
CR	Customer Relationship Management
EP	Financials / Supply Chain Management
FO	Staffing Front Office
HC	HRMS
LM	Enterprise Learning Management
PA	Enterprise Portal
PF	Enterprise Performance Management
SA	Student Administration/ Contributor Relations

**Note.** This is a complete list of available product lines for PeopleTools 8.4x. Note that not all products go out on all PeopleTools releases, so you may not see a script corresponding to every product line. In addition, some bolt-on products reference their own scripts within their application installation documentation. Please see your application-specific installation documentation for details.

To create application-specific tablespaces:

1. Invoke SQL\*Plus (sqlplus), connecting as sysdba.
2. Run the appropriate DDL scripts.

For example:

```
sqlplus>@<PS_HOME>\scripts\nt\epddl.sql
```

## Task E-9: Creating PeopleSoft Database Roles

Run the PSROLES.SQL script from SQL\*Plus to create the PeopleSoft database roles.

To create the roles for your PeopleSoft database:

1. Log on to SQL\*Plus to as the System user.
2. Run the PSROLES.SQL script:

```
SQLPLUS>@<PS_HOME>\scripts\nt\psroles.sql
```

---

## Task E-10: Creating the PeopleSoft Database Owner ID

This task creates the PeopleSoft database owner ID that will be referenced in future tasks. It grants the roles, created in the previous step, to this owner ID.

---

**Note.** You must run the PSADMIN.SQL script for each PeopleSoft database that you are going to create. When prompted for a default tablespace name, select PSDEFAULT if you are using PeopleSoft naming conventions, or your site equivalent if you are not using PeopleSoft naming conventions.

---

To create the PeopleSoft database owner ID:

1. Log on to SQL\*Plus as the System user.
2. Run the PSADMIN.SQL script.

```
SQLPLUS>@<PS_HOME>\scripts\nt\psadmin.sql
```

---

## Task E-11: Setting Up Connect ID

This section discusses:

- Understanding Connect ID
- Defining the Connect ID
- Creating the Connect ID

### Understanding Connect ID

With PeopleTools 8.4, you establish connections to a database simply by using the connect ID, which allows you to associate multiple PeopleSoft operators to the same connect ID. The connect ID has the minimum privileges required to connect to the database—that is, it has only SELECT privileges on specific PeopleTools tables. After connection, PeopleSoft Security uses the operator ID to control access to objects in the database. The PeopleSoft sign-on process validates the connect ID on the server, rather than the operator ID. Connect ID simplifies database security maintenance. You don't have to maintain access for all PeopleSoft users, just for the connect ID.

The connect ID is granted access using the following script:

*Connect.sql:* Creates the connect ID and grants CREATE SESSION privilege to the connect ID. Access to the PeopleSoft database is then granted to the connect ID explicitly via the initial Data Mover load script generated by DBSETUP to include the following grants.

```
grant select on PSSTATUS to <CONNECT_ID>;  
grant select on PSOPRDEFN to <CONNECT_ID>;  
grant select on PSACCESSPRFL to <CONNECT_ID>;
```

In order to work, the connect ID and connect password must be specified at the client configuration manager or the configuration file of any two-tier client accessing the application.

## Task E-11-1: Defining the Connect ID

When logging into a PeopleSoft database in two-tier mode, the user enters a Database Name, User ID, and Password in the PeopleSoft Signon dialog box.

Log-in Processing Steps	Related Database SQL Operations
The access to the PeopleSoft Database is established with the Connect ID not the User ID.	Connect=PT84/people/people
Check PSSTATUS	SELECT OWNERID, TOOLSREL, LASTREFRESHDTM, LASTCHANGEDTTM FROM PSSTATUS
Validate the User ID and Password	SELECT VERSION, OPERPSWD, ENCRYPTED, SYMBOLICID, ACCTLOCK FROM PSOPRDEFN WHERE OPRID = :1
Get the Access ID and Password	SELECT ACCESSID, ACCESSPSWD, ENCRYPTED FROM PSACCESSPRFL WHERE SYMBOLICID = :1
Disconnect Connect ID	Disconnect
Login using the Access ID	Connect=PT84/ACCESSID/ACCESSPWD

At this point, access is governed by PeopleSoft security, which determines what applications a specific user ID has access to.

## Task E-11-2: Creating the Connect ID

To create connect ID:

1. Log on to SQL\*Plus as the System user.
2. Run the connect.sql script.

```
SQLPLUS>@<PS_HOME>\scripts\nt\connect.sql
```

3. The script will then create the connect ID and grant it CREATE Session privileges only.

---

## Task E-12: Updating Connection Information

This section discusses:

- Updating Connection Information on the Client
- Updating Connection Information on the Server

---

**Note.** You must update connection information on both the client and the server.

---

## Task E-12-1: Updating Connection Information on the Client

To update connection information on the client, update the connection information in TNSNAMES.ORA on your client to reflect your Database Name, Oracle SID, and Server Name.

## Task E-12-2: Updating Connection Information on the Server

To update connection information on the server:

1. Add the new SID name and \$ORACLE\_HOME location to the LISTENER.ORA on the database server.
2. Stop and start (or reload) the Oracle Net listener.

---

**Note.** For more information regarding optimum tnsnames.ora entry configuration for the DB server, see "Oracle Net" in the Data Management PeopleBook. Also check your Oracle documentation for further information.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*, "Administering PeopleSoft Databases on Oracle."

---

## Task E-13: Setting NLS\_LANG in the Windows Registry

You must set the NLS\_LANG Oracle registry key to indicate the Oracle language and character set. The PeopleSoft Internet Application Server and reporting tools run in Unicode regardless of the database character set or the NLS\_LANG character set component. However, the NLS\_LANG character set component does affect the transmission of data in non-PeopleTools connections, such as SQLPlus and direct COBOL. NLS\_LANG has three components, a language, a territory, and a character set in the form LANGUAGE\_TERRITORY.CHARACTERSET. For example, for American English, the correct NLS\_LANG setting for PeopleSoft would be AMERICAN\_AMERICA.UTF8. See the Oracle National Language Support guide for full details.


---

**Note.** When using SQL\*Plus to query data, set NLS\_LANG on the client side to match the OS character set rather than the database character set.

---


To set NLS\_LANG in the Windows registry:

1. The NLS\_LANG parameter should be set on each workstation you use to access PeopleSoft in two-tier mode, and on your application server machine.
2. Open the Windows Registry Editor by selecting *Run* from the Windows Start menu.
3. Type REGEDIT in the Run dialog.
4. Navigate to the key HKEY\_LOCAL\_MACHINE\Software\Oracle.



Navigating to NLS\_LANG

- Double-click on the NLS\_LANG key in the right hand side of the window.



Entering the Value data

- Enter <language>\_<territory>.UTF8 in the "Value Data" field, substituting <language> and <territory> for your preferred language and territory settings.

If unsure, use AMERICAN\_AMERICA.UTF8.

- Click *OK* and close the Registry Editor.

## Task E-14: Creating Data Mover Import Scripts

This task explains how to create the Data Mover Import script, which is used to populate the PeopleSoft database with data. The following procedure describes how to run Database Setup Wizard from Data Mover to generate the import scripts.

**Note.** This task and the next one ("Running Data Mover Import Scripts") should be executed from a Windows client machine. Before you can load PeopleSoft data from a Windows client machine, you need to install the PeopleTools CD and PeopleSoft Application CD to the Windows client machine and be sure to select File Server and Database Server.




**Note.** If you want to run Data Mover on the same machine as the application server or Process Scheduler, you need to start a new telnet session without running PSADMIN and make sure the PS\_SERVER\_CFG environment variable is not set. PS\_SERVER\_CFG is only set when you run PSADMIN, so if you have not run it before this should not be a concern. When running Data Mover, you do not need to run PSADMIN. Consult PeopleBooks documentation for the details on using PS\_SERVER\_CFG to set up tracing in Data Mover.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*

To create the Data Mover import script using Data Mover:

1. Verify that the same connect ID was used in the Database Setup and Configuration Manager panel displayed below.

If you accepted all defaults, the connect ID/password is: people/people (password contains the number “1”).



Configuration Manager dialog box

2. Run Data Mover in bootstrap mode, using as a user ID the access ID, which should be the user that creates the database.  
When connecting to Data Mover using your access ID, you automatically sign on in bootstrap mode.
3. To invoke the Database Setup wizard, choose File, Database Setup.
4. Select your database platform.

---

**Note.** Choose the Database Type—Unicode or Non-Unicode—that you selected in the section on multilingual strategy. If you choose Non-Unicode, select the character set you decided upon in that section.

---

See “Preparing for Installation,” Planning Multilingual Strategy.

---

**Note.** The character set you select here must match the character set you used to create your database in the task “Creating an Oracle Database.” If you choose to create a Unicode database, you must have created your instance using the UTF8 character set in the step “Creating an Oracle Instance.”

---

5. Select your character set and click Next.

---

**Note.** DB Setup does not actually modify the character set of your database. That is done by your DBA during database creation. DB Setup will create customized scripts based on your selections.

---




---

**Note.** When you select a non-Unicode character set, only the characters within that character set can be stored in your database. If you require characters from multiple character sets or scripts to be stored in a single database, PeopleSoft recommends that you create your database using Unicode.

---

6. Select your PeopleSoft Application and click Next.



Selecting a PeopleSoft application in the Database Setup dialog box

7. Select the Demo or System radio button, depending on which type of PeopleSoft database you are installing.
8. Select the Products for which you want to create a Data Mover script from the PeopleSoft Application list box, and move the items you have selected into the Data Mover Scripts to Create list box by clicking on the Add or Add All button.

Only the products and languages that you have licensed will be available.

If you installed the Multilanguage CD, each application will be listed several times, once for each language. If you are installing languages other than English, make sure to select the appropriate language data files for each application you select in English. This will load the translated database objects.

See “Preparing for Installation,” Planning Multilingual Strategy.

If you are installing an application in any language other than English, you must also select the English component of the application. For example, if you select PeopleSoft Fin/SCM - French, you must also select PeopleSoft Fin/SCM Database - US English. This ensures that you install the necessary base-language components.

9. Set the database parameters and click Next.

Selecting the database parameters in the Database Setup dialog box

- *Database Name:* The database name that users will enter on the PeopleSoft signon screen. This corresponds to the owner ID. It can be up to eight characters long and must be entered in uppercase.
- *Symbolic ID:* This is used as the key to retrieve ACCESSID and ACCESSPSWD from PSACCESSPRFL. For initial installation set it equal to the Database Name. The symbolic ID cannot be longer than eight characters.
- *Access ID:* This is the user you used to create the database.  
This value is case sensitive. You will use the access ID every time you want to sign on to Data Mover in bootstrap mode.

---

**Note.** You must limit access ID and connect ID to eight characters or less.

---

- *Access ID Password:* This is the PeopleSoft access ID password defined in chapter 1.
- *Connect ID:* For Oracle, this is the connect ID that is used for the initial connection to Oracle. This ID is used for connecting to the database.


10. Select your database's base language and click *Finish*.

---

**Note.** This screen appears only if you selected a database for a language other than English. If you see this screen it is critical to select the correct base language. When you select a base language other than ENG, DBSETUP generates the Data Mover import script with the SWAP\_BASE\_LANGUAGE command to swap the base language.

---

At this point you are in Data Mover, with the DMS script you just created ready to run.



Selecting a base language in the Database Setup dialog box

---

**Note.** If you have not already done so, read the first chapter before determining whether to install multiple languages and whether to change your base language.

---

---

**Note.** If you are creating a database and want to load PeopleSoft-provided translations for non-English languages, you must load English (ENG) in addition to the foreign language components.

---

---

**Note.** If you are creating a non-Unicode database, you must ensure that the languages you select are all supported by the character set you used to create your database.

---

See “Preparing for Installation,” Planning Multilingual Strategy

---

**Note.** All PeopleSoft releases are shipped with English as the database's base language. Therefore when selecting components for the Data Mover Import script, you must select the English components in addition to any other languages you have licensed. During the Database Setup wizard, you need to select the database's base language that you plan to use most frequently. If your database's base language is different than the Database Setup wizard generate the `SWAP_BASE_LANGUAGE` command in the Data Mover Import script to swap the language.

---

---

## Task E-15: Running Data Mover Import Scripts

This section discusses:

- Understanding Data Mover Import Scripts
- Populating Tables in the PeopleSoft Database
- Validating Files
- Troubleshooting
- Improving Performance

### Understanding Data Mover Import Scripts

Now you will run the Data Mover scripts (DMS) that you created in the preceding task to import the data for your PeopleSoft database. The Data Mover script creates either a system (SYS) or a demo (DMO) database.

When you initially logged onto Data Mover to create the DMS scripts, you logged in using bootstrap mode. *Bootstrap mode* means starting Data Mover with the database Access ID and password, rather than with a PeopleSoft user ID. You need to use bootstrap mode to run the Data Mover import script, because there are not yet any PeopleSoft security tables in the database.

---

**Note.** If you want to run Data Mover on the same machine as the application server or Process Scheduler, you need to start a new telnet session without running PSADMIN and make sure the `PS_SERVER_CFG` environment variable is not set. `PS_SERVER_CFG` is only set when you run PSADMIN, so if you have not run it before this should not be a concern. When running Data Mover, you do not need to run PSADMIN.

---

When you start Data Mover in bootstrap mode, the word “BootStrap” appears in the Data Mover status bar.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*.

### Task E-15-1: Populating Tables in the PeopleSoft Database

To populate tables in the PeopleSoft database:

1. The DMS import script for your application will contain hard-coded file names for log files and data files. Modify the DMS script if you have moved any files from the delivered directories or want to write log files to another location than that specified in the script.
2. Select File, Run to execute the script.

When you run the script, Data Mover typically does the following:

- `IMPORT *`  
Create all the PeopleTools and application tables with their indexes.

- **ENCRYPT\_PASSWORD \***  
Encrypt security information for the database.
- **CREATE\_TRIGGER \***  
Create application required triggers.
- **REPLACE\_VIEW \***  
Create PeopleSoft views.
- **CREATE\_TEMP\_TABLE \***  
Create PeopleSoft temporary tables.

## Task E-15-2: Validating Files

Each script will produce .LOG files. The log files are located in the directory you specified in the Data Mover Script.

Examine these files after each run to make sure that all the commands were executed successfully.

## Task E-15-3: Troubleshooting

If your script has stopped midway (this can happen for a number of reasons) you need to edit the script and start again.

To edit and restart the DMS script:

1. Determine the record that was being imported (that is, which IMPORT command was running) when the script stopped. (See the note below for additional information on determining where the script stopped.)

---

**Note.** When building a DMO database or a multilingual database, adding the SET START statement can be tricky because the Data Mover script used to load the database will include more than one IMPORT statement. The key is to view the LOG files and determine which IMPORT section of the script Data Mover failed on. If the failure occurred during the first IMPORT, add the SET START statement before the first IMPORT \*; statement (no problem with this one). If the failure occurred during a subsequent IMPORT, comment out all preceding IMPORT \*; statements and add the SET START statement before the IMPORT\*; statement of the section in which the failure occurred. This is very important. If you see any 'unique index constraint' error messages in the 'Create Indexes' step (found later in the chapter), your IMPORT script failed during a subsequent IMPORT but the SET START statement was added to the first IMPORT. In this situation, you can run the Data Mover script in its originally generated form, with only one modification. In the first IMPORT section, change the statement IMPORT \*; to REPLACE\_DATA \*;. This will delete all the data in the tables, and re-import it. This process will take some time to run, and you will need to separately create each of the indexes that failed.

---

2. Add the following line before the offending IMPORT command (the one being executed when the failure occurred):

```
Set start <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The 'SET START' will begin the Data Mover import at the <RECORD NAME> specified.

---

**Note.** It is a good idea to change the name of the log file in the script before each attempt at running it. This ensures that you have a separate log file for each attempt, if you run the import more than once.

---

*Example:*

If the script stops and the table is partially inserted with a message similar to this one:

```
Importing PSPNLFIELD
Rows inserted into PSPNLFIELD
```

```
3000
```

First drop the partially inserted table (for example, record) by using the DROP TABLE command, and then restart Data Mover at the record that failed using the SET START command and continue the Data Mover import. With PeopleTools 8.4, this can be done in a single pass.

Add the following lines before the offending IMPORT command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
```

```
DROP TABLE <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The 'SET START' will begin the Data Mover import at the <RECORD NAME> specified.

*Example:*

**Before:**

```
REM - PeopleTools System Database - US English
/
SET LOG ptengs.log;
SET INPUT ptengs.db;

SET COMMIT 30000;

SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE OFF;
IMPORT *;
```

**After:**

```
REM - PeopleTools System Database - US English
/
SET LOG ptengs.log;
SET INPUT ptengs.db;

SET COMMIT 30000;

SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
```

```
SET UNICODE OFF;  
SET START PSPNLFIELD;  
  
DROP TABLE PSPNLFIELD;  
  
IMPORT *;
```

For the DROP Statement, for records with a recname without a leading PS, add PS\_ to the beginning of the recname; otherwise the table will not be found.

*Example:*

```
PS_<RECNAME>
```

3. Re-start the script (File, Run Script).

## Task E-15-4: Improving Performance

The following tips can help you save time when running the Data Mover scripts:

- Run Data Mover on the database server.
- Run only a single instance of Data Mover, and do not have any other applications running during the import.
- In the PeopleSoft Configuration Manager, turn off all Trace options. Tracing during a DMS load will add considerable time to the process.
- Run Data Mover on the database server with the .db or .dat file located locally.

If you are comfortable changing the options available for an Oracle instance, you might consider tuning the instance used for the import. Some of these options are appropriate only during the import, so you may not want to keep them in effect after the import is complete.

For best performance during a Data Mover import, set these options as follows:

- Increase the number of database blocks.
- Increase the shared\_pool.
- Use an 8K Oracle block size.
- Use very large rollback segments.
- Increase the size of the redo log files when you create the database.
- Use asynchronous read and write.
- Use multiple db\_writers.

---

## Task E-16: Updating Database to Latest PeopleTools Release

This section discusses:

- Understanding Database Updates
- Cleaning Up Data



- Updating PeopleTools System Tables
- Updating PeopleTools Database Objects
- Updating PeopleTools Multilingual Objects
- Deleting Obsolete PeopleTools Database Objects
- Altering PeopleTools Tables
- Migrating Records to New Tablespaces
- Updating PeopleTools System Data
- Running PeopleTools Conversions
- Converting Integration Broker
- Changing the User Interface

## Understanding Database Updates

Your PeopleSoft application database may be on a PeopleTools release prior to the version that you are currently running. For you to be able to sign on to your database after running the Data Mover script to load your database, the PeopleTools versions for your database and your file server must match. The steps in this task ensure that your PeopleSoft database is in sync with the PeopleTools version that you are running.

---

**Note.** You will use Application Designer for several steps in this portion of the installation. Consult the Application Designer documentation if you have questions.

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Application Designer*

---

**Note.** If you are installing a PeopleTools System Database or if your database is delivered on PeopleTools 8.48, the delivered database already contains the updated PeopleTools objects. Skip this task and continue with the install at the task “Running Additional Data Mover Scripts.”

---

Here is a list of applications for which this task must be run because the version of the database that was shipped is different than the version of PeopleTools that you are running. If your application release is earlier than the release listed in the table, you must run this task:

Application Release	Application Database Version	Requires Update to 8.48?
CRM 8.9	8.45	Yes
CRM 9.0	8.48	No
ELS 8.8 SP1	8.43	Yes
ELS 9.0	8.47	Yes
EPM 8.9	8.46	Yes
EPM 9.0	8.48	No
Fin/SCM 8.9	8.46	Yes

Application Release	Application Database Version	Requires Update to 8.48?
Fin/SCM 9.0	8.48	No
HRMS 8.8 SP1	8.43	Yes
HRMS 8.9	8.45	Yes
Portal 8.8	8.42	Yes
Portal 8.9	8.46	Yes
RMS 8.9	8.45	Yes
RMS 8.95	8.46	Yes
SIM 8.9	8.45	Yes

If your application is not listed above, look for your application and PeopleTools release information on Customer Connection. Navigate to Site Index, product releases (roadmaps and schedules), Release Definitions, select your product line, and then select the product you are installing. If the Tools version is not 8.48, you must run this task. Otherwise, continue to the task “Running Additional Data Mover Scripts.”

## Task E-16-1: Cleaning Up Data

If your database is delivered on PeopleTools 8.48 or higher, do *not* run this step, and instead, proceed to Updating PeopleTools System Tables. If your database is delivered on PeopleTools 8.47 or earlier, perform this step to clean out obsolete message data.

---

**Warning!** Performing this task when updating from PeopleTools 8.48 or later will wipe out current valid data that is needed for your system to function properly.

---

Message functionality and structure changed as of PeopleTools 8.48 and the old data is obsolete. Edit <PS\_HOME>\scripts\ptupgibdel.sql to delete data from the tables that only exist in the old PeopleTools release. Open the script and make the following modifications, and then run the modified script using your SQL query tool:

1. Search for the string “--- End of PT8.<xx> ---” where <xx> represents the last two digits of the PeopleTools release you are upgrading from.
2. Delete the entire portion of the script below this string.
3. Save the script as <PS\_HOME>\scripts\ptupgibdel8<xx>.sql where <xx> represents the last two digits of the PeopleTools release you are upgrading from, as determined in Step 1.

---

**Note.** Save the script using the naming convention shown above! This will preserve the original script for use in updating other databases at different PeopleTools releases.

---

4. Using a SQL query tool, run the ptupgibdel8<xx>.sql script against your PeopleSoft database.

## Task E-16-2: Updating PeopleTools System Tables

Run SQL scripts to update your PeopleTools system tables to the latest PeopleTools release (currently 8.48).

Use a query tool, such as Query SQL\*Plus, to run SQL scripts while in the PeopleSoft database.

1. Run the appropriate SQL scripts for your application version.

The following scripts are found in the <PS\_HOME>\scripts directory.

Use the scripts in the following table for non-Unicode databases:

Application Database Version	Required Scripts for Non-Unicode Databases
8.40	rel841, rel842, rel843, rel844, rel845, rel846, rel847, and rel848
8.41	rel842, rel843, rel844, rel845, rel846, rel847, and rel848
8.42	rel843, rel844, rel845, rel846, rel847, and rel848
8.43	rel844, rel845, rel846, rel847, and rel848
8.44	rel845, rel846, rel847, and rel848
8.45	rel846, rel847, and rel848
8.46	rel847 and rel848
8.47	rel848 <b>Note.</b> If you are installing ELM 9.0, run rel848n.sql instead.
8.48	None

Use the scripts in the following table for Unicode databases:

Application Database Version	Required Scripts for Unicode Databases
8.40	rel841u, rel842u, rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.41	rel842u, rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.42	rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.43	rel844u, rel845u, rel846u, rel847u, and rel848u
8.44	rel845u, rel846u, rel847u, and rel848u
8.45	rel846u, rel847u, and rel848u
8.46	rel847u and rel848u
8.47	rel848u <b>Note.</b> If you are installing ELM 9.0, run rel848un.sql instead.
8.48	None

2. If the application database version you are installing is either 8.42 or 8.43, run the following SQL command:

```
DROP TABLE PS_PSMCFQUEUESLANG
```

---

**Note.** PS\_PSMCFQUEUESLANG may not exist in some 8.43 application databases. Do *not* drop the table PSMCFQUEUESLANG.

---

3. If the application database you are installing is 8.45 or lower, run the following SQL command:

```
DROP TABLE PSOPTSTATUS
```

4. Edit and run the grant.sql script in the <PS\_HOME>\scripts directory. This will grant permissions to the Connect ID.
5. Invoke Data Mover by running <PS\_HOME>\bin\client\winx86\psdmt.exe.  
The PeopleSoft Logon window appears.  
Log on using a valid PeopleSoft Operator ID, such as PS for HRMS or VP1 for FDM.
6. Run the storedddl.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update your platform-specific DDL model statements.  
Log out of Data Mover for the next step.
7. Invoke Data Mover by running <PS\_HOME>\bin\client\winx86\psdmt.exe.  
The PeopleSoft Logon window appears.  
Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.  
This will start Data Mover in bootstrap mode.
8. Run the msgtlsupg.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update the PeopleTools messages in your database.

## Task E-16-3: Updating PeopleTools Database Objects

To update PeopleTools database objects to the current release you must be in Application Designer. The Copy from File functionality lets you update your PeopleTools database objects from a file. You must perform this step to bring the database objects in sync with the PeopleTools release. Failure to run this step will introduce problems to your environment.


To update PeopleTools database objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PPLTLS84CUR from the list of projects and click the Select button.

---

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.


---



Selecting PPLTLS84CUR in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and then click the Copy button. When the progress window disappears, the project has been copied.



The Copy From File dialog box showing that PPLTLS84CUR will be copied

If you see the following types of messages in the output window do not worry; they are acceptable because the field label properties were copied with the object definition:

- Definition Name: OPERPSWD.OPERPSWD not copied, entire definition already copied (62,32).
- Definition Name: OPRID.NEW not copied, entire definition already copied (62,32).

## Task E-16-4: Updating PeopleTools Multilingual Objects

If you are currently updating a PeopleSoft Multilingual Database, you must also apply the project PPLTLS84CURML, which contains the translations of the PeopleTools Objects.


**Note.** If you have licensed and installed French into this database, copy the PPLTLSML project instead of the PPLTLS84CURML project for French *only*. Substitute the project name PPLTLSML instead of PPLTLS84CURML in the instructions below. Copy the PPLTLS84CURML project to update any non-French languages that are installed in the database.

To update PeopleTools database objects to the current release you must be in Application Designer. The Copy from File functionality lets you update your PeopleTools database objects from a file.

To apply the translation project for PeopleTools 8.48:


1. Bring up the Configuration Manager and select the Display tab.  
Ensure that the language matches the base language of your database. Always run upgrade copy as a base language user.
2. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
3. Select Tools, Copy Project, From File.
4. In the resulting dialog box, change the import directory to <PS\_HOME>\projects.
5. Select PPLTLS84CURML from the list of projects and click the Select button.

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.



Selecting PPLTLS84CURML in the Copy From File dialog box

6. The Upgrade Copy dialog box appears.  
Make sure that all object types are selected.
7. Click the Options button, select the Copy Options tab, and ensure that only the non-English languages you have installed are selected.  
Please note that English and Common should *not* be selected.
8. Select the languages that you are currently installing from the Copy Options dialog box.
9. Click the Copy button.



The Copy From File dialog box showing that PPLTLS84CURML will be copied

When the progress dialog box disappears, the project has been copied.

## Task E-16-5: Deleting Obsolete PeopleTools Database Objects

This process removes obsolete PeopleTools objects from your database. To update PeopleTools database objects to the current release you must be in Application Designer. You will use the Copy from File functionality to delete the obsolete objects from the database.

To delete obsolete PeopleTools database objects:


1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PPLTLS84CURDEL from the list of projects and click Select.

---

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.

---






Selecting PPLTLS84CURDEL in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and click the Copy button. When the progress dialog box disappears, the project has been copied.



The Copy From File dialog box showing that PPLTLS84CURDEL will be copied

**Note.** If you are applying a required for install PeopleTools patch *and if a database project is included*, apply the database projects now. Make sure to read the patch release notes to find out if database changes are in the patch.


## Task E-16-6: Altering PeopleTools Tables

ALTER AUDIT is an online utility used to check whether the PeopleTools tables are synchronized with the underlying SQL data tables in your database. This process compares the data structures of your database tables with the PeopleTools tables to uncover inconsistencies. ALTER AUDIT then reports its findings. In this release, we expect to see differences between the database structure and the tools tables. You will generate and run a SQL script to synchronize the PeopleTools table definitions with the underlying tables in your database.

To alter PeopleTools tables:

1. Launch PeopleTools and sign on to the installed database.
2. From the Application Designer, select File, Open.
3. Select *Project*, enter *PPLTLS84CUR* in the name dialog box, and click OK.
4. Select Build, Project.


The Build dialog box appears:



The Build dialog box

5. Select Create Tables and Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
6. Select Build script file in the Build Execute Options region.
7. Click Settings.

The Build Settings dialog box appears:




Build Settings dialog box: Scripts tab

8. Select the Scripts tab.
9. Select Write Alter comments to script.
10. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region.


Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.

Make sure that the option Alter by Table Rename is selected in the Alter Table Options region.



Build Settings dialog box: Alter tab

11. Select the Create tab and ensure that the Skip table if it already exists, Recreate view if it already exists, and Recreate index only if modified options are selected.



Build Settings dialog box: Create tab

12. Click OK.

The Build dialog box reappears.

13. Click Build.

14. Click Close when the process is completed.

15. Edit the generated SQL script for the correct tablespace names and sizing parameters if you are not using delivered PeopleSoft Tablespace names.

16. Run the generated SQL script in your platform-specific query tool to bring your database structure in sync with the PeopleTools tables.

## Task E-16-7: Migrating Records to New Tablespaces

This section discusses:

- Copying the Tablespace Record Project
- Running Alter Tools Tables


### Copying the Tablespace Record Project

PeopleSoft has moved some delivered tables to different Tablespaces in 8.44 and above. You must run this step to move the tables.

To copy the Tablespace Record project:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PT84TBLSPC from the list of projects, and click Select.

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.




Selecting PT84TBLSPC in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and click the Options button. Navigate to General Options and make sure that the Take DDL from Source option is selected.


Click OK.



Upgrade Options dialog box: General Options tab

5. Click the Copy button.

When the progress dialog box disappears, the project has been copied.



The Copy From File dialog box showing that PT84TBLSPC will be copied




## Running Alter Tools Tables

To run Alter Tools tables:

1. Launch PeopleTools and sign on to Installed database.
2. From the Application Designer, select File, Open.
3. Select Project, enter PT84TBLSPC in the name dialog box, and click OK.
4. Select Build, Project.


The Build dialog box appears:



The Build dialog box

5. Select Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
6. Select Build script file in the Build Execute Options region.
7. Click Settings.


The Build Settings dialog box appears:



Build Settings dialog box: Scripts tab

8. Select the Scripts tab.
9. Select Write Alter comments to script.
10. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region, and that the Alter even if no changes check box has been selected.

Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.



Build Settings dialog box: Alter tab

11. Click OK.

The Build dialog box reappears.

12. Click Build.

13. Click Close when the process is completed.

14. Edit the generated SQL script for the correct Tablespace names and sizing parameters if you are not using delivered PeopleSoft Tablespace names.

15. Run the generated SQL script in your platform-specific query tool move the tables to the correct Tablespaces.

## Task E-16-8: Updating PeopleTools System Data

Data Mover scripts that update PeopleTools system data are run to enable new features and load new messages for the PeopleTools 8.48 release. Several of the scripts that you need to run are dependent upon the version of the application you are running.

See Understanding Database Updates.

To update PeopleTools system data:

1. Invoke Data Mover by running `<PS_HOME>\bin\client\winx86\psdmt.exe`.

The PeopleSoft Logon window appears.

2. Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.

This will start Data Mover in bootstrap mode.

3. Run the appropriate Data Mover scripts for your application database version.

The application database version refers to the version before you started this step. Be sure to run the scripts in the order listed. The scripts are found in the <PS\_HOME>\scripts directory:

Application Database Version	Scripts to Run
8.40	pt841tls, pt842tls, pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.41	pt842tls, pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.42	pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.43	pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.44	pt845tls, pt846tls, pt847tls, and pt848tls
8.45	pt846tls, pt847tls, and pt848tls
8.46	pt847tls and pt848tls
8.47	pt848tls
8.48	None

4. Run the pslanguages.dms Data Mover script in the <PS\_HOME>\scripts directory.

This script loads language-specific seed data.

5. Run the tlsupgnoncomp.dms Data Mover script in the <PS\_HOME>\scripts directory.

This will import the updated PeopleTools Trees, Roles, and Access Groups into your database.

6. If you are a Multilingual customer, from the Data Mover script that was created for your PeopleSoft database installation, find the UPDATE to PSLANGUAGES.

The statement should look similar to the following:

```
UPDATE PSLANGUAGES SET INSTALLED=1 WHERE LANGUAGE_CD = 'xxx' ;
```

where xxx is one of the PeopleSoft three-letter language code identifiers, as described earlier.

See “Preparing for Installation,” Planning Multilingual Strategy.

Run the SQL command identified above using your SQL tool.

7. Open Data Mover using a valid PeopleSoft Operator ID, such as PS for HRMS or VP1 for FDM.
8. If you are a Multilingual customer and have licensed non-English languages, run the pt848tlsxxx.dms scripts in the <PS\_HOME>\scripts directory.

This will update the language-specific PeopleTools system data in your database.

---

**Note.** The portion of the script name *xxx* is equivalent to the language code (that is, FRA, CFR, GER, JPN, and so on) of the non-English languages you have installed. There will be a Data Mover script for each non-English language.

---

9. Run the msgtleng.dms Data Mover Script in the <PS\_HOME>\scripts directory.  
Non-English message data was loaded in the pt848tlsx.dms scripts. This will update the messages in your database.
10. Run the ptstreng.dms Data Mover script in the <PS\_HOME>\scripts directory.  
Non-English system data was loaded in the pt848tlsx.dms scripts. This will update the SQR strings in your database.
11. Run the storept.dms Data Mover script in the <PS\_HOME>\src\cb\base directory.  
This will update your PeopleTools COBOL stored statements.
12. Run the ptdefnsec.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update the PeopleTools Definition Security group.
13. Run the createvw.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will recreate all the views in your database.

## Task E-16-9: Running PeopleTools Conversions

This section discusses:

- Convert Portal Objects
- Convert Query Headings
- Convert Setup Manager
- Convert Navigation Collection and Pagelet Wizard Data
- Convert Additional Pagelet Wizard Data

### Convert Portal Objects

The Application Engine program UPG844PORTAL splits PSPRSMDEFN.PORTAL\_URLTEXT into segments. This is performed for PeopleSoft Components URLs to extract Menu, Component, and Market information. Record, Field, Event, and Function Names are extracted from Iscript URLs. This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role. The following SQL will identify which users have the PeopleSoft Administrator or Portal Administrator roles:

```
select ROLEUSER, ROLENAME from PSROLEUSER where ROLENAME in ('PeopleSoft⇒
Administrator','Portal Administrator')
```

Run the UPG844PORTAL Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R⇒
INSTALL -AI UPG844PORTAL
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <oprid>, respectively. However, be aware that <pswd> is not the same as the connect password that you entered on the Configuration Manager startup tab. Enter a value for <pswd> that is the password you want to be associated with the <oprid>.

See “Setting Up the Install Workstation.”

See Running the Database Configuration Wizard.

You may see some of the following errors when running this Application Engine program:

- Not authorized CRef: <Portal Object Name> (95,5032).

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

- Security synchronization failed for Portal Object: <Portal Object Name> (96,61).

This is not a fatal error. It may be caused by a content reference that contains invalid URL text and indicates that there was an internal error writing to the security table. The invalid URL text may be pointing to a component or script that does not exist in the database. If you receive this error, please check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database.

- Cref <Portal Object Name> points to Menu: <Menu Name>, Component <Component Name> which doesn't exist. (96,80).

The content reference is pointing to an invalid Menu/Component combination. If you receive this error, please check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

## Convert Query Headings

Crystal 9 when run through Process Scheduler will not handle queries with two or more prompts that have the same heading. These duplicates are also not legal in Query. Any old queries that have this condition need to be altered to work with Crystal. This Application Engine program searches for duplicate prompt headings in the table PSQRYBIND and appends numbers onto the text. For example "Item ID" would become "Item ID 2".

Run the UPGQRYDUPHED Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
INSTALL -AI UPGQRYDUPHED
```

---

**Note.** If a duplicate heading is found that will exceed the length of the field HEADING, the heading will need to be manually changed. The following error will be written to the log file in these cases :

The prompt heading <HEADING> for Query <QUERY> is duplicated.  
Please manually correct. (108, 1108)

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Query*.

## Convert Setup Manager

The application engine program UPGPTSMDAT upgrades Setup Manager Version 1 (shipped with Fin SCM 8.8, CRM 8.9, and with HCM 8.9) to Setup Manager Version 2 (shipped with PeopleTools 8.46 and above). The program moves all data from Setup Manager Version 1 tables to Version 2 tables.

The application engine program was designed so that it can be run in any database, and can be rerun in the same database. In either case, it will determine if there is data to convert and run as appropriate. For detailed information, see comments attached to the Steps and Actions in this Application Engine Program within Application Designer. This program must be run by a PeopleSoft User with PeopleSoft Administrator role.

Run the UPGPTSMDAT Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
INSTALL -AI UPGPTSMDAT
```

## Convert Navigation Collection and Pagelet Wizard Data

The application engine program UPGPT846PP adds Navigation Collection and Pagelet Wizard data from the Common Components and Enterprise Portal storage tables into PeopleTools tables.

The application engine program performs the following conversions:

1. Moves data from Common Components tables to PeopleTools tables.
2. Moves data from Enterprise Portal tables to PeopleTools tables.
3. Updates the registry definitions to enable displaying Navigation pages.
4. Adds, updates, and deletes the Navigation Collections folders and content references in the portal registry to the new structures.
5. Converts Pagelet Wizard definitions to the PeopleTools Pagelet Wizard version.
6. Renames Navigation Collection and Pagelet Wizard portal registry attributes to the PeopleTools attribute names.

This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role.

Run the UPGPT846PP Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -=>
R INSTALL -AI UPGPT846PP
```

You may see the following error when running this Application Engine program:

```
You are not authorized for the <objecttype>...
```

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

You can ignore any other errors encountered on PeopleSoft delivered objects at this time. Check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database. You can safely rerun UPGPT846PP to check for any remaining errors after applying patches.

## Convert Additional Pagelet Wizard Data

The application engine program UPGPT848PP adds the following Pagelet Wizard data sources from Enterprise Portal to PeopleTools: IB Connector, Integration Broker, SOAP, and URL. In addition, the application program transforms the WSRP Portlets created in PeopleTools 8.46 or 8.47 versions of Pagelet Wizard. The process includes the following:

- Move data from Enterprise Portal tables to PeopleTools tables.
- Convert WSRP Portlets created by Pagelet Wizard to the new version.

This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role.

Run the UPGPT848PP Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
INSTALL -AI UPGPT848PP
```

You may see the following error when running this Application Engine program:

```
You are not authorized for the <objecttype>...
```

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

You can ignore any other errors encountered on PeopleSoft delivered objects at this time. Check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database. You can safely rerun UPGPT848PP to check for any remaining errors after applying patches.

## Task E-16-10: Converting Integration Broker

This section discusses:

- Updating Integration Broker Defaults
- Creating Integration Broker Objects
- Saving Application Messaging Objects
- Exporting Node Transactions
- Deleting Application Messaging Objects
- Deleting Node Transactions

If your database is delivered with PeopleTools 8.48 or higher, do *not* run this task since the database is already delivered with the new Integration Broker objects as of PeopleTools 8.48. Instead, proceed to Changing the User Interface.

### Updating Integration Broker Defaults

User-level node security and transactional security have been added as of PeopleTools 8.48. Service namespace information, a low-level user on the node, and a low-level permission list for service operations, need to be specified. Edit <PS\_HOME>\scripts\ptibupgrade.dms and make the necessary modifications as documented in the script. Consult with your Integration Broker specialist for assistance.

Open Data Mover using a valid PeopleSoft Operator ID and run this script.

### Creating Integration Broker Objects

The application engine program UPGPT848IBUG converts Application Package metadata into Integration Broker metadata. It also creates the projects PTUPGIBCLONE and PTUPGIBDELETE, and the script ptupg\_trx.dms.

---

**Note.** Conversion errors in the Application Engine log file will be resolved by applying application-specific Required for Install patches.

---

Run the UPGPT848IBUG Application Engine program on your database. From the DOS command line, the syntax is:



```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
INSTALL -AI UPGPT848IBUG
```

## Saving Application Messaging Objects

The PTUPGIBCLONE project was created by the UPGPT848IBUG Application Engine program and contains objects that were successfully converted. Copy this project to a directory of your choice where it will not be overwritten. The objects are copied to file as a precautionary measure since you will delete them from the database in a subsequent step.

To save Application Messaging Objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. From the Application Designer, select File, Open.
3. Select Project, enter *PTUPGIBCLONE* in the name dialog box, and click OK.
4. Select Tools, Copy Project, To File.
5. In the resulting dialog box, change the export directory to one of your choice, and click Copy.

When the progress dialog box disappears, the project has been copied to the specified location.

## Exporting Node Transactions

Open Data Mover using a valid PeopleSoft Operator ID and run the script <PS\_HOME>\scripts\ptupg\_trx\_export.dms to save the old pre-conversion node transaction data.

## Deleting Application Messaging Objects

Delete the obsolete pre-conversion object definitions from the database by first copying the PTUPGIBDELETE project to file, and then copying the same project from file. This project was created by the UPGPT848IBUG Application Engine program and contains the same objects as PTUPGIBCLONE.

To delete Application Messaging Objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. From the Application Designer, select File, Open.
3. Select Project, enter *PTUPGIBDELETE* in the name dialog box, and click OK.
4. Select Tools, Copy Project, To File.
5. In the resulting dialog box, change the export directory to the same one you used for PTUPGIBCLONE, and click Copy.

When the progress dialog box disappears, the project has been copied to the specified location.

6. Select Tools, Copy Project, From File.
7. In the resulting dialog box, change the import directory to the previously specified directory, select PTUPGIBDELETE from the list of projects, and click Select.

---

**Note.** Because the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.

---

8. Select all object types and click the Copy button.

When the progress dialog box disappears, the project has been copied. The actions in the project are set to Delete, so this will delete the obsolete pre-conversion object definitions from the database.

## Deleting Node Transactions

The script ptupg\_trx.dms is generated by the UPGPT848IBUG Application Engine program. This script can be found in the location specified in the OUTPUT variable set in Configuration Manager.

To view the OUTPUT variable:

1. Open Configuration Manager.
2. Select the Profile tab.
3. Click Edit to open the Default profile.
4. Select the Process Scheduler tab.
5. Examine the Output Directory value.

Open Data Mover using a valid PeopleSoft Operator ID and run this script to remove obsolete node transaction data associated with the obsolete objects in the PTUPGIBDELETE project.

## Task E-16-11: Changing the User Interface

PeopleTools has updated the styles that define the user interface. This PeopleTools release delivers the classic (old) style as well as two new styles: a dark blue style and a light blue style. PeopleTools System Databases and PeopleSoft 8.4 applications use the classic style, but all other applications use the new dark blue style. The classic style is set as the default. To use one of the new user interfaces, you have to delete the substyle sheets associated with the classic style and replace them with either the light or dark blue substyle sheet.

---

**Note.** The new user interface is supported by Internet Explorer release 5 and above and Netscape Navigator release 6 and above. If you are using a browser and release other than these, the system defaults to the classic style.

---

To enable a new user interface:

1. In Application Designer, select File, Open.
2. On the Open Definition dialog box, select *Style Sheet* from the Definition drop-down list.
3. Enter the name *PSSTYLEDEF* in the Selection Criteria Name field, and select Open.
4. Highlight *PSSTYLEDEF* in the list, and select Open.
5. Click the *PSALTERNATE* Sub Style Sheet and press DELETE.
6. Select Insert, Insert Sub Style Sheet.
7. Select *PSALTERNATE\_LIGHTBLUE* or *PSALTERNATE\_DARKBLUE*.
8. Repeat steps 5 through 7 for the *PTSTYLEDEF* Sub Style Sheet, making sure to use the same extension (*\_LIGHTBLUE* or *\_DARKBLUE*) you used for *PSALTERNATE*.
9. Select File, Save.
10. Open the style sheet *PSQUERYSTYLEDEF* as in steps 1 through 4.
11. Click the *PTQUERYSTYLESUB* Sub Style Sheet and press DELETE.
12. Select Insert, Insert Sub Style Sheet.
13. Select *PTQUERYSTYLESUB\_LIGHTBLUE* or *PTQUERYSTYLESUB\_DARKBLUE*.

- Use the same extension that you used in step 8.
14. Select File, Save.

---

## Task E-17: Running Additional Data Mover Scripts

To import additional data for your specific PeopleSoft database, or to make other required changes, you may need to run additional Data Mover scripts. These script files have the extension .dms and are sometimes referred to as “DMS scripts.” They are located in the <PS\_HOME>\scripts directory of your file server, and need to be run from the file server by means of Data Mover.

For the details on which additional application-specific Data Mover scripts to run, consult your application-specific installation instructions.

If you have installed a language other than English, you may need additional instructions on language-specific Data Mover scripts.

See Installing a Multilingual PeopleTools System Database.

---

## Task E-18: Installing a Multilingual PeopleTools System Database

This section discusses:

- Understanding the Multilingual Database Project
- Applying the Multilingual Database Project
- Populating the Translated System Data

### Understanding the Multilingual Database Project

The information in this section applies if you are installing a multilingual PeopleTools System database. If not, skip this task and go on to the task “Running VERSION Application Engine Program.” If you are installing an application database (for example, HRMS, FSCM, EPM, and so on), you do not need to run this task.

If you are adding a new (PeopleSoft-delivered) language to the PTSYS database, you must execute this step for that language. For example, if you want to add Polish to your current multilingual database, you should install Polish from PPLTLSML so you will get all objects. If you only “upgrade” your database to have Polish using PPLTLS84CURML, you will only get the objects that changed between 8.40 and the current release.

If you are installing a PeopleTools System database and you want it to be multilingual, you need to perform the steps in the following section after the database has been loaded with Data Mover.

See Applying the Multilingual Database Project.

---

**Note.** When you log onto the multilingual database, be sure to select the base language of the database.

---

## Task E-18-1: Applying the Multilingual Database Project

This procedure describes how to apply the multilingual database project that contains translations of the PeopleTools objects.

To apply the multilingual database project:

1. Launch Application Designer.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects.
4. Select *PPLTSLML* from the list of projects and click the Open button.
5. In the Upgrade Copy dialog box, make sure that all object types are selected.
6. Click the Options button, select the Copy Options tab, and ensure that only the non-English languages you have installed are selected.

Please note that English and Common should *not be selected*.

7. Select the languages that you are currently installing from the Copy Options dialog box.
8. Click the Copy button.

(The Reset Done Flags check box will be selected; accept this default.)

## Task E-18-2: Populating the Translated System Data

To populate the translated system data:

---

**Note.** You need to run the following script in User mode.

---

1. Launch Data Mover.
2. Open the pt848tlsx.dms script using File, Open.
3. Select File, Run

---

**Note.** The portion of the script name xxx is equivalent to the language code (that is, FRA, CFR, GER, JPN, and so on) of the languages you have installed. There will be a Data Mover script for each language.

---

## Task E-19: Running VERSION Application Engine Program

Run the VERSION Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <userid> -CP=>
<userpswd> -R INSTALL -AI VERSION
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <userid> respectively. However, be aware that <userpswd> is not the same as the connect password you entered on the Configuration Manager startup tab. Enter a value for <userpswd> that is the password you want to be associated with the <userid>.

See “Setting Up the Install Workstation.”

See Running the Database Configuration Wizard.

## Task E-20: Changing the Base Language

Chapter 1 will help you determine whether you should change your base language, and lists the currently supported languages.

See “Preparing for Installation,” Planning Multilingual Strategy.

This task applies only if your users will be operating PeopleSoft applications *primarily* in one particular language other than English. It gives a performance boost to the language you designate as the base language, but requires more administrative overhead than leaving English as the base language. The details are spelled out in the following PeopleBook:

See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*.

## Task E-21: Running SQR Reports

This section discusses:

- Running SQRs on the Client Workstation
- Creating a Shortcut to Run SQRs


**Note.** The following instructions describe how to run SQR reports from the client workstation. On the Windows client, you may prefer to create a shortcut to allow you to run the reports repeatedly. You can use these instructions to run SQRs required in the upcoming task “Checking the Database.” You can also choose to run SQR reports from the command line in console mode.

### Task E-21-1: Running SQRs on the Client Workstation

To run an SQR on the client workstation:

1. Select Start, Run, click Browse, and navigate to <PS\_HOME>\bin\sqr\ORA\binw.  
Select sqrw.exe and click Open.
2. Add any needed flags at the end of the command line.

Refer to the table that follows. For those flags that require attributes, append the attributes to the flags with no intervening spaces (for example, `-fd:\psbase\psenv\cr881dmo\`).




Running an SQR report on the client

The following table summarizes the SQR report arguments used by PeopleSoft. (For a full listing of report arguments, press the Help button to view the SQR help topic for this dialog box.)

Flag	Description
-I	Specifies the directories that SQR will search for the #INCLUDE files. (A trailing slash is required.)
-f	Specifies the directory where the report output will be sent. If you use the <code>-keep</code> flag, specify a directory with an ending slash. If you use the <code>-printer</code> flag, specify a full pathname with a filename for the HTML file.
-ZIF	Sets the full path and name of the SQR initialization file. The <code>-ZIF</code> flag should point to your <code>&lt;PS_HOME&gt;\sqr\pssqr.ini</code> file.
-keep	Keeps the .SPF file after the program runs. This enables you to view the report with the SQR viewer.
-printer:ht	Generates the output file in HTML format. Specify the filename, with path location, with the <code>-f</code> flag.

- Click OK.

The resulting dialog box should look something like this:



SQR for PeopleSoft dialog box

- Enter the following values:
  - Enter the report name.  
You must specify the full path.
  - Enter the access ID in the Username field.
  - Enter the access password in the Password field.
  - Enter the database name.
- Click OK to run the SQR report.

---

**Note.** In the Properties dialog box for your SQR icon, make sure that the Start in path points to your Oracle connectivity on the Shortcut tab. If you take the default, you may see a misleading error message about TNS packet writer failure.

---

## Task E-21-2: Creating a Shortcut to Run SQRs

If you think you may need to run the SQR reports more than once, you may want to create a shortcut on the Windows client workstation. To save the report arguments:

1. Open Windows Explorer on the machine on which you want to run SQR.
2. Navigate to <PS\_HOME>\bin\sqr\ORA\binw.
3. Right-click sqrw.exe and click Create Shortcut.
4. Right-click the shortcut that you just created and select Properties.
5. On the Shortcut tab, add the same sqr flags that you used in the previous task after sqrw.exe in the Target entry box.
6. Click OK.
7. To run the report, double-click the shortcut and specify the following information in the dialog box:
  - Report Name: Enter the full path and the name.
  - Database name
  - Username: Enter the access ID.
  - Password: Enter the access password.
  - Report arguments: Make any necessary modifications to the saved arguments.
8. Click OK.

---

## Task E-22: Checking the Database

Run and examine two SQR reports to verify that your database is complete.

See Preparing to Run SQR.

To verify that the database is complete, run the following SQR reports from the <PS\_HOME>\sqr directory:

- dddaudit.sqr
- sysaudit.sqr.

For further information about the dddaudit and sysaudit reports, consult PeopleBooks. This documentation includes specific information on how to interpret the reports and how to fix any errors found there.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*, “Ensuring Data Integrity.”

You can greatly improve the performance and run time of sysaudit.sqr run by making the following configuration changes to the Oracle init.ora for your SID:

```
db_file_multiblock_read_count = 16
db_block_buffers = 2000 or greater
```

```
log_checkpoint_interval = 9999999
log_buffer = 102400
```

If you are using rollback segments, you may also want to increase the size of the RBSBIG rollback segment to 500 MB.

Alter all other rollback segments but RBSBIG offline.

---

**Note.** If any records show up in the VIEWS-2 or TABLE-3 section of dddaudit and are contained within the PPLTLS84CURDEL project, you may safely drop these records using the SQL query tool for your platform.

---

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: Data Management*

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

---

## Task E-23: Running SETSPACE.SQR


Run the SETSPACE.SQR script to populate or synchronize Tablespace information with the system catalog. To run SETSPACE.SQR:

1. Using the instructions provided in the earlier task "Preparing to Run SQR," run SETSPACE.SQR from the <PS\_HOME>\SQR directory.

---

**Note.** Your results will vary depending on the application you are loading.

---



Running SETSPACE.SQR on the SQR for PeopleSoft dialog box

2. Click OK.
3. As SETSPACE.SQR runs you see a progress indicator similar to the following.

```
Set Table Space Name in PSRECTBLSPC
```

```
Table PSRECTBLSPC column DDLSPACENAME have been updated
with the tablespace found in the system catalog table.
```



The total number of records updated appears at the bottom of this report.

Recname	New DDLSpaceName	Old DDLSpaceName
-----	-----	-----
This phase of SETSPACE will sync up the PSRECTBLSPC and PSTBLSPCCAT tables		
PSRECTBLSPC Records Updated:		0
PSTBLSPCCAT Records Inserted:		0
Ending SQR.		



## APPENDIX F

# Creating a Database Manually on UNIX

This appendix discusses:

- Understanding Database Creation
- Editing Database Scripts
- Creating an Oracle Instance
- Using SQL Tools
- Setting NLS\_LANG in the Windows Registry
- Creating an Oracle Database
- Creating Catalog Views and Utility Tablespaces
- Creating PS.PSDBOWNER Table
- Creating Application-Specific Dbspaces and Tablespaces
- Creating PeopleSoft Database Roles
- Creating the PeopleSoft Database Owner ID
- Setting Up Connect ID
- Updating Connection Information
- Creating Data Mover Import Scripts
- Running Data Mover Import Scripts
- Updating Database to Latest PeopleTools Release
- Running Additional Data Mover Scripts
- Installing a Multilingual PeopleTools System Database
- Running VERSION Application Engine Program
- Changing the Base Language
- Running SQR Reports
- Checking the Database
- Running SETSPACE.SQR

---

## Understanding Database Creation

This section describes the tasks required to create a PeopleSoft product database. During a standard PeopleSoft installation you will execute these tasks to create two distinct types of databases.

- *System*: The System database has no company specific data, and can be used to load your data and begin development of your production database.
- *Demo*: The Demo database contains data for a sample company, and can be used immediately for demonstration, for testing, and as a development reference.

The requirements for these databases vary, so not all of this section's tasks apply to each database. The instructions will note any distinctions between creating a Demo and a System database.

Remember, you need to have the PeopleTools Development Environment set up to create your database.

---

**Important!** Do not forget that application-specific installation steps are provided in a separate document specific to the application. For instance, if you are performing PeopleSoft CRM installation, you need both this PeopleTools installation guide and any additional instructions provided by CRM. To find the installation documentation specific to your application, go to PeopleSoft Customer Connection. Under the Site Index, find the category “Installation Guides and Notes,” and then look under the subcategory for your particular application.

---

---

**Important!** If you are installing PeopleSoft on an Oracle 10g RAC database, there are additional configuration procedures that you must follow.

---

See “Setting Up the PeopleSoft Installation with Oracle 10g RAC.”

---

## Task F-1: Editing Database Scripts

This section discusses:

- Understanding Database Scripts
- Modifying Database Scripts

### Understanding Database Scripts

The scripts required for creating the database were installed on the server using the PeopleSoft Installer described in the chapter “Using the PeopleSoft Installer.” These scripts reside in the <PS\_HOME>/scripts/unix directory on the UNIX database server. You need to edit a few of these scripts for your environment before you execute them and go on with the following procedures.

Typically, you need to modify the file system locations and the Oracle SID name.

### Task F-1-1: Modifying Database Scripts

To edit required database scripts:

1. Go to the <PS\_HOME>/scripts/unix directory on the database server.

2. Edit the scripts to conform to your environment.

The following list presents the necessary scripts:

- CREATEDB.SQL or CREATEDB10.SQL (for Oracle 10g installs)

---

**Note.** When editing CREATEDB.SQL or CREATEDB10.SQL, if you are creating a Unicode database, you need to choose an Oracle character set supported by PeopleSoft. Insure that the CHARACTER SET parameter in the CREATE DATABASE statement is set to UTF8.

---

- CONNECT.SQL.

Edit CONNECT.SQL only if you do not wish to use the default CONNECT\_ID.

- UTLSPACE.SQL.
- XXDDL.SQL, where XX is a two-letter code for your product line, as listed in the table below.

Code	Product Line
CR	Customer Relationship Management
EP	Financials / Supply Chain Management
FO	Staffing Front Office
HC	HRMS
IM	Incentive Management
LM	Enterprise Learning Management
PA	Enterprise Portal
PF	Enterprise Performance Management
SA	Student Administration/ Contributor Relations

---

**Note.** This is a complete list of available product lines for PeopleTools 8.4x. Note that not all products go out on all PeopleTools releases, so you may not see a script corresponding to every product line. In addition, some bolt-on products reference their own scripts within their application installation documentation. Check PeopleSoft Customer Connection to confirm that the product is supported for a specific release and database platform.

---

See PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise).

---

**Note.** For multilanguage installs, you need to increase the size of the PTTBL, PSIMAGE, and PSINDEX tablespaces. Refer to the comments in the DDL scripts for further details regarding the incremental increase for each additional language.

---

## See Also

“Using the PeopleSoft Installer”

*Enterprise PeopleTools 8.48 Hardware and Software Requirements*

## Task F-2: Creating an Oracle Instance

To create an Oracle instance:

1. Log on to the server as the Oracle owner.
2. Set the ORACLE\_SID value to point to the database you are going to set up, and then export the value. From the Bourne or Korn shell, enter the following:

```
$ ORACLE_SID=hdmo; export ORACLE_SID
```

3. Set the NLS\_LANG environment variable to indicate the Oracle language and character set.

The PeopleSoft Internet Application Server and reporting tools run in Unicode regardless of the database character set or the NLS\_LANG character set component. However, the NLS\_LANG character set component does affect the transmission of data in non-PeopleTools connections, such as SQLPlus and direct COBOL. NLS\_LANG has three components, a language, a territory and a character set in the form LANGUAGE\_TERRITORY.CHARACTERSET. For example, for American English, the correct NLS\_LANG setting for PeopleSoft would be AMERICAN\_AMERICA.UTF8. See the Oracle National Language Support guide for full details. These parameters need to be set each time you access your PeopleSoft system from the UNIX shell. Therefore, we suggest you edit your psconfig.sh file to make these changes take effect each time you configure your environment. From the Bourne or Korn shell, enter the following, substituting <language> and <territory> for the language and territory values you prefer to use. If unsure, use AMERICAN\_AMERICA.UTF8.

```
$ NLS_LANG=<language>_<territory>.UTF8; export NLS_LANG
```

Alternatively, from the C shell, enter the following:

```
$ setenv NLS_LANG <language>_<territory>
```

4. Create an initialization file by copying and editing the INIT.ORA file that is delivered with Oracle and typically resides in \$ORACLE\_HOME/dbs.

```
cd $ORACLE_HOME
```

```
cd dbs
```

```
cp init.ora init<sid>.ora
```

5. Add or modify the following parameters in the INIT<SID>.ora:

```
DB_NAME = <SID>
```

```
DB_FILES = specify max allowed per your OS, typically 1021
```

```
CONTROL_FILES = (/filesystem1/cntrl1<SID>,/filesystem2/cntrl2<SID>)
```

```
OPEN_CURSORS = 255 <This is a minimum value; you may choose to set it higher.>
```

```
db_block_size = 8192
```

---

**Note.** Beginning with PeopleTools PT8.46, PeopleTools supports Oracle 9i and 10g. The PeopleSoft scripts are delivered to work across all versions of the Oracle RDBMS that PeopleSoft will support for this release of PeopleTools.

Because Oracle 9i is now the minimum Oracle RDBMS version supported, the PeopleSoft database creation scripts are delivered to support Automatic Undo. That is, the scripts PeopleSoft delivers assume an init.ora with UNDO\_MANAGEMENT parm set to AUTO.

---



---

**Note.** If you want to use Manual Undo (for example, rollback segments), make sure you set your UNDO\_MANAGEMENT parm to MANUAL and modify the CREATEDB.SQL and UTLSPACE.SQL scripts as necessary to implement Manual Undo.

---



---

**Note.** For UNIX the default DB\_BLOCK\_SIZE in the init.ora file is operating system dependent. On most operating systems the default is 8192 or 8K. For PeopleSoft ANSI databases this is more than adequate. For PeopleSoft Unicode databases, (that is, CHARACTER\_SET UTF8), a DB\_BLOCK\_SIZE value of 8K is required.

---



---

**Note.** For more parameters that may be required for the INIT<SID>.ora file, consult PeopleSoft Customer Connection.

---

See “Required Operating System, RDBMS & Additional Component Patches for Installation,” PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Supported Platforms, PeopleSoft Enterprise. Select your database platform.)

If you choose to use an Oracle Password file, create one using the ORAPWD utility, as illustrated in this example:

```
Set ORACLE_SID=FDMO
orapwd file=$ORACLE_HOME/dbs/pwdtemp2.ora password=manager entries=5
```

If you choose not to use an Oracle Password file, you must make one of the following changes to the init.ora file before running the CREATEDB.SQL or CREATEDB10.SQL script.

- Comment out or remove the following line:

```
#remote_login_passwordfile=EXCLUSIVE
```

- Use the following setting:

```
remote_login_passwordfile=NONE
```

---

## Task F-3: Using SQL Tools

When you execute PeopleSoft SQL scripts, use the appropriate tool included with your version of the RDBMS. You should use SQL\*Plus, which is available with each PeopleSoft supported version of the Oracle RDBMS.


## Task F-4: Setting NLS\_LANG in the Windows Registry

You must set the NLS\_LANG Oracle registry key to indicate the Oracle language and character set. The PeopleSoft Internet Application Server and reporting tools run in Unicode regardless of the database character set or the NLS\_LANG character set component. However, the NLS\_LANG character set component does affect the transmission of data in non-PeopleTools connections, such as SQLPlus and direct COBOL. NLS\_LANG has three components, a language, a territory, and a character set in the form LANGUAGE\_TERRITORY.CHARACTERSET. For example, for American English, the correct NLS\_LANG setting for PeopleSoft would be AMERICAN\_AMERICA.UTF8. See the Oracle National Language Support guide for full details.

**Note.** When using SQL\*Plus to query data, set NLS\_LANG on the client side to match the OS character set rather than the database character set.

To set NLS\_LANG in the Windows registry:


1. The NLS\_LANG parameter should be set on each workstation you use to access PeopleSoft in two-tier mode, and on your application server machine.
2. Open the Windows Registry Editor by selecting *Run* from the Windows Start menu.
3. Type REGEDIT in the Run dialog.
4. Navigate to the key HKEY\_LOCAL\_MACHINE\Software\Oracle.



Navigating to NLS\_LANG

5. Double-click on the NLS\_LANG key in the right hand side of the window.





Entering the Value data

6. Enter <language>\_<territory>.UTF8 in the "Value Data" field, substituting <language> and <territory> for your preferred language and territory settings.  
If unsure, use AMERICAN\_AMERICA.UTF8.
7. Click *OK* and close the Registry Editor.

---

## Task F-5: Creating an Oracle Database

Run the CREATEDB.SQL or CREATEDB10.SQL script from SQL\*Plus to create an Oracle database.

To create an Oracle database:

1. Invoke SQL\*PLUS (sqlplus), connecting as sysdba.

```
$sqlplus '/as sysdba'
```

2. Run the CREATEDB.SQL or CREATEDB10.SQL script using the following example as a guide:

```
sqlplus>@<PS_HOME>/scripts/unix/createdb.sql
```

---

**Note.** Beginning with PeopleTools PT8.46, PeopleTools supports Oracle 9i and 10g. The CREATE DATABASE parameters are distinctly different between an Oracle 9i and Oracle 10g install. To support both versions we have delivered a different script to use for Oracle 10g installs: CREATEDB10.SQL. The CREATEDB.SQL script can be used for any Oracle 9i supported release.

---



---

**Note.** When editing CREATEDB.SQL or CREATEDB10.SQL, if you are creating a Unicode database, you need to choose an Oracle character set supported by PeopleSoft. Insure that the CHARACTER SET parameter in the CREATE DATABASE statement is set to UTF8.

---



---

## Task F-6: Creating Catalog Views and Utility Tablespaces

Run the UTLSPACE.SQL script from SQL\*Plus to create catalog views and utility tablespaces.

To create catalog views and utility tablespaces:

1. Invoke SQL\*Plus (sqlplus), connecting as sysdba.

2. Run the UTLSPACE.SQL script:

```
sqlplus>@<PS_HOME>/scripts/unix/utlspace.sql
```

---

## Task F-7: Creating PS.PSDBOWNER Table

Run the DBOWNER.SQL script from SQL\*Plus to create the PS.PSDBOWNER table.

To create the PS.PSDBOWNER table:

1. Invoke SQL\*Plus (sqlplus), connecting as sysdba.
2. Run the DBOWNER.SQL script, using the following example as a guide:

```
sqlplus>@<PS_HOME>/scripts/unix/dbowner.sql
```

---

## Task F-8: Creating Application-Specific Dbspaces and Tablespaces

To create tablespaces for the product you are installing, run the appropriate XXDDL.SQL scripts, logged on as the system user, where *XX* stands for your product line, as spelled out in the table below.

Code	Product Line
CR	Customer Relationship Management
EP	Financials / Supply Chain Management
FO	Staffing Front Office
HC	HRMS
LM	Enterprise Learning Management
PA	Enterprise Portal
PF	Enterprise Performance Management
SA	Student Administration/ Contributor Relations

---

**Note.** This is a complete list of available product lines for PeopleTools 8.4x. Note that not all products go out on all PeopleTools releases, so you may not see a script corresponding to every product line. In addition, some bolt-on products reference their own scripts within their application installation documentation. Please see your application-specific installation documentation for details.

---

To create application-specific tablespaces:

1. Invoke SQL\*Plus (sqlplus), connecting as sysdba.
2. Run the appropriate DDL scripts.

For example:

```
sqlplus>@<PS_HOME>/scripts/unix/epddl.sql
```

---

## Task F-9: Creating PeopleSoft Database Roles

Run the PSROLES.SQL script from SQL\*Plus to create the PeopleSoft database roles.

To create the roles for your PeopleSoft database:

1. Log on to SQL\*Plus to as the System user.
2. Run the PSROLES.SQL script:

```
SQLPLUS>@<PS_HOME>/scripts/unix/psroles.sql
```

---

## Task F-10: Creating the PeopleSoft Database Owner ID

This task creates the PeopleSoft database owner ID that will be referenced in future tasks. It grants the roles, created in the previous step, to this owner ID.

---

**Note.** You must run the PSADMIN.SQL script for each PeopleSoft database that you are going to create. When prompted for a default tablespace name, select PSDEFAULT if you are using PeopleSoft naming conventions, or your site equivalent if you are not using PeopleSoft naming conventions.

---

To create the PeopleSoft database owner ID:

1. Log on to SQL\*Plus as the System user.
2. Run the PSADMIN.SQL script.

```
SQLPLUS>@<PS_HOME>/scripts/unix/psadmin.sql
```

---

## Task F-11: Setting Up Connect ID

This section discusses:

- Understanding Connect ID
- Defining the Connect ID
- Creating the Connect ID

## Understanding Connect ID

With PeopleTools 8.4, you establish connections to a database simply by using the connect ID, which allows you to associate multiple PeopleSoft operators to the same connect ID. The connect ID has the minimum privileges required to connect to the database—that is, it has only SELECT privileges on specific PeopleTools tables. After connection, PeopleSoft Security uses the operator ID to control access to objects in the database. The PeopleSoft sign-on process validates the connect ID on the server, rather than the operator ID. Connect ID simplifies database security maintenance. You don't have to maintain access for all PeopleSoft users, just for the connect ID.

The connect ID is granted access using the following script:

*Connect.sql*: Creates the connect ID and grants CREATE SESSION privilege to the connect ID. Access to the PeopleSoft database is then granted to the connect ID explicitly via the initial Data Mover load script generated by DBSETUP to include the following grants.

```
grant select on PSSTATUS to <CONNECT_ID>;
grant select on PSOPRDEFN to <CONNECT_ID>;
grant select on PSACCESSPRFL to <CONNECT_ID>;
```

In order to work, the connect ID and connect password must be specified at the client configuration manager or the configuration file of any two-tier client accessing the application.

### Task F-11-1: Defining the Connect ID

When logging into a PeopleSoft database in two-tier mode, the user enters a Database Name, User ID, and Password in the PeopleSoft Signon dialog box.

Log-in Processing Steps	Related Database SQL Operations
The access to the PeopleSoft Database is established with the Connect ID not the User ID.	Connect=PT84/people/people
Check PSSTATUS	SELECT OWNERID, TOOLSREL, LASTREFRESHDTTM, LASTCHANGEDTTM FROM PSSTATUS
Validate the User ID and Password	SELECT VERSION, OPERPSWD, ENCRYPTED, SYMBOLICID, ACCTLOCK FROM PSOPRDEFN WHERE OPRID = :1
Get the Access ID and Password	SELECT ACCESSID, ACCESSPSWD, ENCRYPTED FROM PSACCESSPRFL WHERE SYMBOLICID = :1
Disconnect Connect ID	Disconnect
Login using the Access ID	Connect=PT84/ACCESSID/ACCESSPWD

At this point, access is governed by PeopleSoft security, which determines what applications a specific user ID has access to.

### Task F-11-2: Creating the Connect ID

To create connect ID:

1. Log on to SQL\*Plus as the System user.

2. Run the connect.sql script.

```
SQLPLUS>@<PS_HOME>/scripts/unix/connect.sql
```

3. The script will then create the connect ID and grant it CREATE Session privileges only.

---

## Task F-12: Updating Connection Information

This section discusses:

- Updating Connection Information on the Client
- Updating Connection Information on the Server

---

**Note.** You must update connection information on both the client and the server.

---

### Task F-12-1: Updating Connection Information on the Client

To update connection information on the client, update the connection information in TNSNAMES.ORA on your client to reflect your Database Name, Oracle SID, and Server Name.

### Task F-12-2: Updating Connection Information on the Server

To update connection information on the server:

1. Add the new SID name and \$ORACLE\_HOME location to the LISTENER.ORA on the database server.
2. Stop and start (or reload) the Oracle Net listener.

---

**Note.** For more information regarding optimum tnsnames.ora entry configuration for the DB server, see "Oracle Net" in the Data Management PeopleBook. Also check your Oracle documentation for further information.

---

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*, “Administering PeopleSoft Databases on Oracle.”

---

## Task F-13: Creating Data Mover Import Scripts

This task explains how to create the Data Mover Import script, which is used to populate the PeopleSoft database with data. The following procedure describes how to run Database Setup Wizard from Data Mover to generate the import scripts.

---

**Note.** This task and the next one ("Running Data Mover Import Scripts") should be executed from a Windows client machine. Before you can load PeopleSoft data from a Windows client machine, you need to install the PeopleTools CD and PeopleSoft Application CD to the Windows client machine and be sure to select File Server and Database Server.

---


**Note.** If you want to run Data Mover on the same machine as the application server or Process Scheduler, you need to start a new telnet session without running PSADMIN and make sure the PS\_SERVER\_CFG environment variable is not set. PS\_SERVER\_CFG is only set when you run PSADMIN, so if you have not run it before this should not be a concern. When running Data Mover, you do not need to run PSADMIN. Consult PeopleBooks documentation for the details on using PS\_SERVER\_CFG to set up tracing in Data Mover.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*

To create the Data Mover import script using Data Mover:

1. Verify that the same connect ID was used in the Database Setup and Configuration Manager panel displayed below.

If you accepted all defaults, the connect ID/password is: people/people (password contains the number “1”).



Configuration Manager dialog box

2. Run Data Mover in bootstrap mode, using as a user ID the access ID, which should be the user that creates the database.

When connecting to Data Mover using your access ID, you automatically sign on in bootstrap mode.

3. To invoke the Database Setup wizard, choose File, Database Setup.
4. Select your database platform.

---

**Note.** Choose the Database Type—Unicode or Non-Unicode—that you selected in the section on multilingual strategy. If you choose Non-Unicode, select the character set you decided upon in that section.

---

See “Preparing for Installation,” Planning Multilingual Strategy.

---

**Note.** The character set you select here must match the character set you used to create your database in the task "Creating an Oracle Database." If you choose to create a Unicode database, you must have created your instance using the UTF8 character set in the step "Creating an Oracle Instance."

---

5. Select your character set and click Next.

---

**Note.** DB Setup does not actually modify the character set of your database. That is done by your DBA during database creation. DB Setup will create customized scripts based on your selections.

---




---

**Note.** When you select a non-Unicode character set, only the characters within that character set can be stored in your database. If you require characters from multiple character sets or scripts to be stored in a single database, PeopleSoft recommends that you create your database using Unicode.

---

6. Select your PeopleSoft Application and click Next.



Selecting a PeopleSoft application in the Database Setup dialog box

7. Select the Demo or System radio button, depending on which type of PeopleSoft database you are installing.
8. Select the Products for which you want to create a Data Mover script from the PeopleSoft Application list box, and move the items you have selected into the Data Mover Scripts to Create list box by clicking on the Add or Add All button.

Only the products and languages that you have licensed will be available.

If you installed the Multilanguage CD, each application will be listed several times, once for each language. If you are installing languages other than English, make sure to select the appropriate language data files for each application you select in English. This will load the translated database objects.

See “Preparing for Installation,” Planning Multilingual Strategy.

If you are installing an application in any language other than English, you must also select the English component of the application. For example, if you select PeopleSoft Fin/SCM - French, you must also select PeopleSoft Fin/SCM Database - US English. This ensures that you install the necessary base-language components.

9. Set the database parameters and click Next.

Selecting the database parameters in the Database Setup dialog box

- *Database Name:* The database name that users will enter on the PeopleSoft signon screen. This corresponds to the owner ID. It can be up to eight characters long and must be entered in uppercase.
- *Symbolic ID:* This is used as the key to retrieve ACCESSID and ACCESSPSWD from PSACCESSPRFL. For initial installation set it equal to the Database Name. The symbolic ID cannot be longer than eight characters.
- *Access ID:* This is the user you used to create the database.  
This value is case sensitive. You will use the access ID every time you want to sign on to Data Mover in bootstrap mode.

---

**Note.** You must limit access ID and connect ID to eight characters or less.

---

- *Access ID Password:* This is the PeopleSoft access ID password defined in chapter 1.
- *Connect ID:* For Oracle, this is the connect ID that is used for the initial connection to Oracle. This ID is used for connecting to the database.

10. Select your database's base language and click *Finish*.




---

**Note.** This screen appears only if you selected a database for a language other than English. If you see this screen it is critical to select the correct base language. When you select a base language other than ENG, DBSETUP generates the Data Mover import script with the SWAP\_BASE\_LANGUAGE command to swap the base language.

---

At this point you are in Data Mover, with the DMS script you just created ready to run.



Selecting a base language in the Database Setup dialog box

---

**Note.** If you have not already done so, read the first chapter before determining whether to install multiple languages and whether to change your base language.

---

---

**Note.** If you are creating a database and want to load PeopleSoft-provided translations for non-English languages, you must load English (ENG) in addition to the foreign language components.

---

---

**Note.** If you are creating a non-Unicode database, you must ensure that the languages you select are all supported by the character set you used to create your database.

---

See “Preparing for Installation,” Planning Multilingual Strategy

---

**Note.** All PeopleSoft releases are shipped with English as the database's base language. Therefore when selecting components for the Data Mover Import script, you must select the English components in addition to any other languages you have licensed. During the Database Setup wizard, you need to select the database's base language that you plan to use most frequently. If your database's base language is different than the Database Setup wizard generate the `SWAP_BASE_LANGUAGE` command in the Data Mover Import script to swap the language.

---

## Task F-14: Running Data Mover Import Scripts

This section discusses:

- Understanding Data Mover Import Scripts
- Populating Tables in the PeopleSoft Database
- Validating Files
- Troubleshooting
- Improving Performance

### Understanding Data Mover Import Scripts

Now you will run the Data Mover scripts (DMS) that you created in the preceding task to import the data for your PeopleSoft database. The Data Mover script creates either a system (SYS) or a demo (DMO) database.

When you initially logged onto Data Mover to create the DMS scripts, you logged in using bootstrap mode. *Bootstrap mode* means starting Data Mover with the database Access ID and password, rather than with a PeopleSoft user ID. You need to use bootstrap mode to run the Data Mover import script, because there are not yet any PeopleSoft security tables in the database.

---

**Note.** If you want to run Data Mover on the same machine as the application server or Process Scheduler, you need to start a new telnet session without running PSADMIN and make sure the `PS_SERVER_CFG` environment variable is not set. `PS_SERVER_CFG` is only set when you run PSADMIN, so if you have not run it before this should not be a concern. When running Data Mover, you do not need to run PSADMIN.

---

When you start Data Mover in bootstrap mode, the word “BootStrap” appears in the Data Mover status bar.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*.

### Task F-14-1: Populating Tables in the PeopleSoft Database

To populate tables in the PeopleSoft database:

1. The DMS import script for your application will contain hard-coded file names for log files and data files.  
Modify the DMS script if you have moved any files from the delivered directories or want to write log files to another location than that specified in the script.
2. Select File, Run to execute the script.

When you run the script, Data Mover typically does the following:

- `IMPORT *`  
Create all the PeopleTools and application tables with their indexes.

- ENCRYPT\_PASSWORD \*  
Encrypt security information for the database.
- CREATE\_TRIGGER \*  
Create application required triggers.
- REPLACE\_VIEW \*  
Create PeopleSoft views.
- CREATE\_TEMP\_TABLE \*  
Create PeopleSoft temporary tables.

## Task F-14-2: Validating Files

Each script will produce .LOG files. The log files are located in the directory you specified in the Data Mover Script.

Examine these files after each run to make sure that all the commands were executed successfully.

## Task F-14-3: Troubleshooting

If your script has stopped midway (this can happen for a number of reasons) you need to edit the script and start again.

To edit and restart the DMS script:

1. Determine the record that was being imported (that is, which IMPORT command was running) when the script stopped. (See the note below for additional information on determining where the script stopped.)

---

**Note.** When building a DMO database or a multilingual database, adding the SET START statement can be tricky because the Data Mover script used to load the database will include more than one IMPORT statement. The key is to view the LOG files and determine which IMPORT section of the script Data Mover failed on. If the failure occurred during the first IMPORT, add the SET START statement before the first IMPORT \*; statement (no problem with this one). If the failure occurred during a subsequent IMPORT, comment out all preceding IMPORT \*; statements and add the SET START statement before the IMPORT\*; statement of the section in which the failure occurred. This is very important. If you see any 'unique index constraint' error messages in the 'Create Indexes' step (found later in the chapter), your IMPORT script failed during a subsequent IMPORT but the SET START statement was added to the first IMPORT. In this situation, you can run the Data Mover script in its originally generated form, with only one modification. In the first IMPORT section, change the statement IMPORT \*; to REPLACE\_DATA \*;. This will delete all the data in the tables, and re-import it. This process will take some time to run, and you will need to separately create each of the indexes that failed.

---

2. Add the following line before the offending IMPORT command (the one being executed when the failure occurred):

```
Set start <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The 'SET START' will begin the Data Mover import at the <RECORD NAME> specified.

---

**Note.** It is a good idea to change the name of the log file in the script before each attempt at running it. This ensures that you have a separate log file for each attempt, if you run the import more than once.

---

*Example:*

If the script stops and the table is partially inserted with a message similar to this one:

```
Importing PSPNLFIELD
Rows inserted into PSPNLFIELD
```

```
3000
```

First drop the partially inserted table (for example, record) by using the DROP TABLE command, and then restart Data Mover at the record that failed using the SET START command and continue the Data Mover import. With PeopleTools 8.4, this can be done in a single pass.

Add the following lines before the offending IMPORT command (the one being executed when the failure occurred):

```
SET START <RECORD NAME>;
```

```
DROP TABLE <RECORD NAME>;
```

where <RECORD NAME> is the name of the record that failed. Make sure to review the Data Mover log file to see where the script failed and locate the last record that imported successfully. The 'SET START' will begin the Data Mover import at the <RECORD NAME> specified.

*Example:*

**Before:**

```
REM - PeopleTools System Database - US English
/
SET LOG ptengs.log;
SET INPUT ptengs.db;

SET COMMIT 30000;

SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
SET UNICODE OFF;
IMPORT *;
```

**After:**

```
REM - PeopleTools System Database - US English
/
SET LOG ptengs.log;
SET INPUT ptengs.db;

SET COMMIT 30000;

SET NO VIEW;
SET NO SPACE;
SET NO TRACE;
```

```
SET UNICODE OFF;  
SET START PSPNLFIELD;  
  
DROP TABLE PSPNLFIELD;  
  
IMPORT *;
```

For the DROP Statement, for records with a recname without a leading PS, add PS\_ to the beginning of the recname; otherwise the table will not be found.

*Example:*

PS\_<RECNAME>

3. Re-start the script (File, Run Script).

## Task F-14-4: Improving Performance

The following tips can help you save time when running the Data Mover scripts:

- Run only a single instance of Data Mover, and do not have any other applications running during the import.
- In the PeopleSoft Configuration Manager, turn off all Trace options. Tracing during a DMS load will add considerable time to the process.

If you are comfortable changing the options available for an Oracle instance, you might consider tuning the instance used for the import. Some of these options are appropriate only during the import, so you may not want to keep them in effect after the import is complete.

For best performance during a Data Mover import, set these options as follows:

- Increase the number of database blocks.
- Increase the shared\_pool.
- Use an 8K Oracle block size.
- Use very large rollback segments.
- Increase the size of the redo log files when you create the database.
- Use asynchronous read and write.
- Use multiple db\_writers.

---

## Task F-15: Updating Database to Latest PeopleTools Release

This section discusses:

- Understanding Database Updates
- Cleaning Up Data
- Updating PeopleTools System Tables
- Updating PeopleTools Database Objects

- Updating PeopleTools Multilingual Objects
- Deleting Obsolete PeopleTools Database Objects
- Altering PeopleTools Tables
- Migrating Records to New Tablespaces
- Updating PeopleTools System Data
- Running PeopleTools Conversions
- Converting Integration Broker
- Changing the User Interface

## Understanding Database Updates

Your PeopleSoft application database may be on a PeopleTools release prior to the version that you are currently running. For you to be able to sign on to your database after running the Data Mover script to load your database, the PeopleTools versions for your database and your file server must match. The steps in this task ensure that your PeopleSoft database is in sync with the PeopleTools version that you are running.

---

**Note.** You will use Application Designer for several steps in this portion of the installation. Consult the Application Designer documentation if you have questions.

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Application Designer*

---

**Note.** If you are installing a PeopleTools System Database or if your database is delivered on PeopleTools 8.48, the delivered database already contains the updated PeopleTools objects. Skip this task and continue with the install at the task “Running Additional Data Mover Scripts.”

---

Here is a list of applications for which this task must be run because the version of the database that was shipped is different than the version of PeopleTools that you are running. If your application release is earlier than the release listed in the table, you must run this task:

Application Release	Application Database Version	Requires Update to 8.48?
CRM 8.9	8.45	Yes
CRM 9.0	8.48	No
ELS 8.8 SP1	8.43	Yes
ELS 9.0	8.47	Yes
EPM 8.9	8.46	Yes
EPM 9.0	8.48	No
Fin/SCM 8.9	8.46	Yes
Fin/SCM 9.0	8.48	No
HRMS 8.8 SP1	8.43	Yes

Application Release	Application Database Version	Requires Update to 8.48?
HRMS 8.9	8.45	Yes
Portal 8.8	8.42	Yes
Portal 8.9	8.46	Yes
RMS 8.9	8.45	Yes
RMS 8.95	8.46	Yes
SIM 8.9	8.45	Yes

If your application is not listed above, look for your application and PeopleTools release information on Customer Connection. Navigate to Site Index, product releases (roadmaps and schedules), Release Definitions, select your product line, and then select the product you are installing. If the Tools version is not 8.48, you must run this task. Otherwise, continue to the task “Running Additional Data Mover Scripts.”

## Task F-15-1: Cleaning Up Data

If your database is delivered on PeopleTools 8.48 or higher, do *not* run this step, and instead, proceed to Updating PeopleTools System Tables. If your database is delivered on PeopleTools 8.47 or earlier, perform this step to clean out obsolete message data.

---

**Warning!** Performing this task when updating from PeopleTools 8.48 or later will wipe out current valid data that is needed for your system to function properly.

---

Message functionality and structure changed as of PeopleTools 8.48 and the old data is obsolete. Edit <PS\_HOME>\scripts\ptupgibdel.sql to delete data from the tables that only exist in the old PeopleTools release. Open the script and make the following modifications, and then run the modified script using your SQL query tool:

1. Search for the string “--- End of PT8.<xx> ---” where <xx> represents the last two digits of the PeopleTools release you are upgrading from.
2. Delete the entire portion of the script below this string.
3. Save the script as <PS\_HOME>\scripts\ptupgibdel8<xx>.sql where <xx> represents the last two digits of the PeopleTools release you are upgrading from, as determined in Step 1.

---

**Note.** Save the script using the naming convention shown above! This will preserve the original script for use in updating other databases at different PeopleTools releases.

---

4. Using a SQL query tool, run the ptupgibdel8<xx>.sql script against your PeopleSoft database.

## Task F-15-2: Updating PeopleTools System Tables

Run SQL scripts to update your PeopleTools system tables to the latest PeopleTools release (currently 8.48).

Use a query tool, such as Query SQL\*Plus, to run SQL scripts while in the PeopleSoft database.

1. Run the appropriate SQL scripts for your application version.

The following scripts are found in the <PS\_HOME>\scripts directory.

Use the scripts in the following table for non-Unicode databases:

Application Database Version	Required Scripts for Non-Unicode Databases
8.40	rel841, rel842, rel843, rel844, rel845, rel846, rel847, and rel848
8.41	rel842, rel843, rel844, rel845, rel846, rel847, and rel848
8.42	rel843, rel844, rel845, rel846, rel847, and rel848
8.43	rel844, rel845, rel846, rel847, and rel848
8.44	rel845, rel846, rel847, and rel848
8.45	rel846, rel847, and rel848
8.46	rel847 and rel848
8.47	rel848 <b>Note.</b> If you are installing ELM 9.0, run rel848n.sql instead.
8.48	None

Use the scripts in the following table for Unicode databases:

Application Database Version	Required Scripts for Unicode Databases
8.40	rel841u, rel842u, rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.41	rel842u, rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.42	rel843u, rel844u, rel845u, rel846u, rel847u, and rel848u
8.43	rel844u, rel845u, rel846u, rel847u, and rel848u
8.44	rel845u, rel846u, rel847u, and rel848u
8.45	rel846u, rel847u, and rel848u
8.46	rel847u and rel848u
8.47	rel848u <b>Note.</b> If you are installing ELM 9.0, run rel848un.sql instead.
8.48	None

- If the application database version you are installing is either 8.42 or 8.43, run the following SQL command:

```
DROP TABLE PS_PSMCFQUEUESLANG
```

---

**Note.** PS\_PSMCFQUEUESLANG may not exist in some 8.43 application databases. Do *not* drop the table PSMCFQUEUESLANG.

---



3. If the application database you are installing is 8.45 or lower, run the following SQL command:

```
DROP TABLE PSOPTSTATUS
```

4. Edit and run the grant.sql script in the <PS\_HOME>\scripts directory. This will grant permissions to the Connect ID.
5. Invoke Data Mover by running <PS\_HOME>\bin\client\winx86\psdmt.exe.  
The PeopleSoft Logon window appears.  
Log on using a valid PeopleSoft Operator ID, such as PS for HRMS or VP1 for FDM.
6. Run the storedddl.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update your platform-specific DDL model statements.  
Log out of Data Mover for the next step.
7. Invoke Data Mover by running <PS\_HOME>\bin\client\winx86\psdmt.exe.  
The PeopleSoft Logon window appears.  
Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.  
This will start Data Mover in bootstrap mode.
8. Run the msgtlsupg.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update the PeopleTools messages in your database.

## Task F-15-3: Updating PeopleTools Database Objects

To update PeopleTools database objects to the current release you must be in Application Designer. The Copy from File functionality lets you update your PeopleTools database objects from a file. You must perform this step to bring the database objects in sync with the PeopleTools release. Failure to run this step will introduce problems to your environment.


To update PeopleTools database objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PPLTLS84CUR from the list of projects and click the Select button.

---

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.


---



Selecting PPLTLS84CUR in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and then click the Copy button. When the progress window disappears, the project has been copied.



The Copy From File dialog box showing that PPLTLS84CUR will be copied

If you see the following types of messages in the output window do not worry; they are acceptable because the field label properties were copied with the object definition:

- Definition Name: OPERPSWD.OPERPSWD not copied, entire definition already copied (62,32).
- Definition Name: OPRID.NEW not copied, entire definition already copied (62,32).

## Task F-15-4: Updating PeopleTools Multilingual Objects

If you are currently updating a PeopleSoft Multilingual Database, you must also apply the project PPLTLS84CURML, which contains the translations of the PeopleTools Objects.


**Note.** If you have licensed and installed French into this database, copy the PPLTLSML project instead of the PPLTLS84CURML project for French *only*. Substitute the project name PPLTLSML instead of PPLTLS84CURML in the instructions below. Copy the PPLTLS84CURML project to update any non-French languages that are installed in the database.

To update PeopleTools database objects to the current release you must be in Application Designer. The Copy from File functionality lets you update your PeopleTools database objects from a file.

To apply the translation project for PeopleTools 8.48:


1. Bring up the Configuration Manager and select the Display tab.  
Ensure that the language matches the base language of your database. Always run upgrade copy as a base language user.
2. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
3. Select Tools, Copy Project, From File.
4. In the resulting dialog box, change the import directory to <PS\_HOME>\projects.
5. Select PPLTLS84CURML from the list of projects and click the Select button.

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.



Selecting PPLTLS84CURML in the Copy From File dialog box

6. The Upgrade Copy dialog box appears.  
Make sure that all object types are selected.
7. Click the Options button, select the Copy Options tab, and ensure that only the non-English languages you have installed are selected.  
Please note that English and Common should *not* be selected.
8. Select the languages that you are currently installing from the Copy Options dialog box.
9. Click the Copy button.



The Copy From File dialog box showing that PPLTLS84CURML will be copied

When the progress dialog box disappears, the project has been copied.

## Task F-15-5: Deleting Obsolete PeopleTools Database Objects

This process removes obsolete PeopleTools objects from your database. To update PeopleTools database objects to the current release you must be in Application Designer. You will use the Copy from File functionality to delete the obsolete objects from the database.


To delete obsolete PeopleTools database objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PPLTLS84CURDEL from the list of projects and click Select.

---

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.


---



Selecting PPLTLS84CURDEL in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and click the Copy button. When the progress dialog box disappears, the project has been copied.



The Copy From File dialog box showing that PPLTLS84CURDEL will be copied

**Note.** If you are applying a required for install PeopleTools patch *and if a database project is included*, apply the database projects now. Make sure to read the patch release notes to find out if database changes are in the patch.


## Task F-15-6: Altering PeopleTools Tables

ALTER AUDIT is an online utility used to check whether the PeopleTools tables are synchronized with the underlying SQL data tables in your database. This process compares the data structures of your database tables with the PeopleTools tables to uncover inconsistencies. ALTER AUDIT then reports its findings. In this release, we expect to see differences between the database structure and the tools tables. You will generate and run a SQL script to synchronize the PeopleTools table definitions with the underlying tables in your database.

To alter PeopleTools tables:

1. Launch PeopleTools and sign on to the installed database.
2. From the Application Designer, select File, Open.
3. Select *Project*, enter *PPLTLS84CUR* in the name dialog box, and click OK.
4. Select Build, Project.

The Build dialog box appears:




The Build dialog box

5. Select Create Tables and Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
6. Select Build script file in the Build Execute Options region.
7. Click Settings.

The Build Settings dialog box appears:






Build Settings dialog box: Scripts tab

8. Select the Scripts tab.
9. Select Write Alter comments to script.
10. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region.


Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.

Make sure that the option Alter by Table Rename is selected in the Alter Table Options region.



Build Settings dialog box: Alter tab

11. Select the Create tab and ensure that the Skip table if it already exists, Recreate view if it already exists, and Recreate index only if modified options are selected.



Build Settings dialog box: Create tab

12. Click OK.

The Build dialog box reappears.

13. Click Build.

14. Click Close when the process is completed.

15. Edit the generated SQL script for the correct tablespace names and sizing parameters if you are not using delivered PeopleSoft Tablespace names.

16. Run the generated SQL script in your platform-specific query tool to bring your database structure in sync with the PeopleTools tables.

## Task F-15-7: Migrating Records to New Tablespaces

This section discusses:

- Copying the Tablespace Record Project
- Running Alter Tools Tables


### Copying the Tablespace Record Project

PeopleSoft has moved some delivered tables to different Tablespaces in 8.44 and above. You must run this step to move the tables.

To copy the Tablespace Record project:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects, select PT84TBLSPC from the list of projects, and click Select.

**Note.** If the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.




Selecting PT84TBLSPC in the Copy From File dialog box

4. The Copy From File dialog box appears.

Select all object types and click the Options button. Navigate to General Options and make sure that the Take DDL from Source option is selected.


Click OK.



Upgrade Options dialog box: General Options tab

5. Click the Copy button.

When the progress dialog box disappears, the project has been copied.




The Copy From File dialog box showing that PT84TBLSPC will be copied

## Running Alter Tools Tables

To run Alter Tools tables:

1. Launch PeopleTools and sign on to Installed database.
2. From the Application Designer, select File, Open.
3. Select Project, enter PT84TBLSPC in the name dialog box, and click OK.
4. Select Build, Project.


The Build dialog box appears:



The Build dialog box

5. Select Alter Tables in the Build Options region (Create Indexes and Create Trigger will automatically be selected).
6. Select Build script file in the Build Execute Options region.
7. Click Settings.


The Build Settings dialog box appears:



Build Settings dialog box: Scripts tab

8. Select the Scripts tab.
9. Select Write Alter comments to script.
10. Select the Alter tab and ensure that the Adds, Changes, Renames, and Deletes check boxes are selected in the Alter Any region, and that the Alter even if no changes check box has been selected.

Drop column if data present should be selected in the Drop Column Options region, and Truncate data if field too short should be selected in the Change Column Length Options region.



Build Settings dialog box: Alter tab

11. Click OK.

The Build dialog box reappears.

12. Click Build.
13. Click Close when the process is completed.
14. Edit the generated SQL script for the correct Tablespace names and sizing parameters if you are not using delivered PeopleSoft Tablespace names.
15. Run the generated SQL script in your platform-specific query tool move the tables to the correct Tablespaces.

## Task F-15-8: Updating PeopleTools System Data

Data Mover scripts that update PeopleTools system data are run to enable new features and load new messages for the PeopleTools 8.48 release. Several of the scripts that you need to run are dependent upon the version of the application you are running.

See Understanding Database Updates.

To update PeopleTools system data:

1. Invoke Data Mover by running <PS\_HOME>\bin\client\winx86\psdmt.exe.



The PeopleSoft Logon window appears.

2. Log on using the access ID you specified when you created your Data Mover scripts with the Database Setup program.

This will start Data Mover in bootstrap mode.

3. Run the appropriate Data Mover scripts for your application database version.

The application database version refers to the version before you started this step. Be sure to run the scripts in the order listed. The scripts are found in the <PS\_HOME>\scripts directory:

Application Database Version	Scripts to Run
8.40	pt841tls, pt842tls, pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.41	pt842tls, pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.42	pt843tls, pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.43	pt844tls, pt845tls, pt846tls, pt847tls, and pt848tls
8.44	pt845tls, pt846tls, pt847tls, and pt848tls
8.45	pt846tls, pt847tls, and pt848tls
8.46	pt847tls and pt848tls
8.47	pt848tls
8.48	None

4. Run the pslanguages.dms Data Mover script in the <PS\_HOME>\scripts directory.

This script loads language-specific seed data.

5. Run the tlsupgnoncomp.dms Data Mover script in the <PS\_HOME>\scripts directory.

This will import the updated PeopleTools Trees, Roles, and Access Groups into your database.

6. If you are a Multilingual customer, from the Data Mover script that was created for your PeopleSoft database installation, find the UPDATE to PSLANGUAGES.

The statement should look similar to the following:

```
UPDATE PSLANGUAGES SET INSTALLED=1 WHERE LANGUAGE_CD = 'xxx' ;
```

where xxx is one of the PeopleSoft three-letter language code identifiers, as described earlier.

See “Preparing for Installation,” Planning Multilingual Strategy.

Run the SQL command identified above using your SQL tool.

7. Open Data Mover using a valid PeopleSoft Operator ID, such as PS for HRMS or VP1 for FDM.
8. If you are a Multilingual customer and have licensed non-English languages, run the pt848tlsxxx.dms scripts in the <PS\_HOME>\scripts directory.

This will update the language-specific PeopleTools system data in your database.

---

**Note.** The portion of the script name *xxx* is equivalent to the language code (that is, FRA, CFR, GER, JPN, and so on) of the non-English languages you have installed. There will be a Data Mover script for each non-English language.

---

9. Run the msgtleng.dms Data Mover Script in the <PS\_HOME>\scripts directory.  
Non-English message data was loaded in the pt848tlsx.dms scripts. This will update the messages in your database.
10. Run the ptstreng.dms Data Mover script in the <PS\_HOME>\scripts directory.  
Non-English system data was loaded in the pt848tlsx.dms scripts. This will update the SQR strings in your database.
11. Run the storept.dms Data Mover script in the <PS\_HOME>\src\cbl\base directory.  
This will update your PeopleTools COBOL stored statements.
12. Run the ptdefnsec.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will update the PeopleTools Definition Security group.
13. Run the createvw.dms Data Mover script in the <PS\_HOME>\scripts directory.  
This will recreate all the views in your database.

## Task F-15-9: Running PeopleTools Conversions

This section discusses:

- Convert Portal Objects
- Convert Query Headings
- Convert Setup Manager
- Convert Navigation Collection and Pagelet Wizard Data
- Convert Additional Pagelet Wizard Data

### Convert Portal Objects

The Application Engine program UPG844PORTAL splits PSPRSMDEFN.PORTAL\_URLTEXT into segments. This is performed for PeopleSoft Components URLs to extract Menu, Component, and Market information. Record, Field, Event, and Function Names are extracted from Iscript URLs. This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role. The following SQL will identify which users have the PeopleSoft Administrator or Portal Administrator roles:

```
select ROLEUSER, ROLENAME from PSROLEUSER where ROLENAME in ('PeopleSoft⇒
Administrator','Portal Administrator')
```

Run the UPG844PORTAL Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R⇒
INSTALL -AI UPG844PORTAL
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <oprid>, respectively. However, be aware that <pswd> is not the same as the connect password that you entered on the Configuration Manager startup tab. Enter a value for <pswd> that is the password you want to be associated with the <oprid>.

See “Setting Up the Install Workstation.”

See Running the Database Configuration Wizard.

You may see some of the following errors when running this Application Engine program:

- Not authorized CRef: <Portal Object Name> (95,5032).

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

- Security synchronization failed for Portal Object: <Portal Object Name> (96,61).

This is not a fatal error. It may be caused by a content reference that contains invalid URL text and indicates that there was an internal error writing to the security table. The invalid URL text may be pointing to a component or script that does not exist in the database. If you receive this error, please check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database.

- Cref <Portal Object Name> points to Menu: <Menu Name>, Component <Component Name> which doesn't exist. (96,80).

The content reference is pointing to an invalid Menu/Component combination. If you receive this error, please check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database.

See *Enterprise PeopleTools 8.48 PeopleBook: Internet Technology*.

## Convert Query Headings

Crystal 9 when run through Process Scheduler will not handle queries with two or more prompts that have the same heading. These duplicates are also not legal in Query. Any old queries that have this condition need to be altered to work with Crystal. This Application Engine program searches for duplicate prompt headings in the table PSQRYBIND and appends numbers onto the text. For example "Item ID" would become "Item ID 2".

Run the UPGQRYDUPHED Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R⇒
INSTALL -AI UPGQRYDUPHED
```

---

**Note.** If a duplicate heading is found that will exceed the length of the field HEADING, the heading will need to be manually changed. The following error will be written to the log file in these cases :

The prompt heading <HEADING> for Query <QUERY> is duplicated.  
Please manually correct. (108, 1108)

---

See *Enterprise PeopleTools 8.48 PeopleBook: PeopleSoft Query*.

## Convert Setup Manager

The application engine program UPGPTSMDAT upgrades Setup Manager Version 1 (shipped with Fin SCM 8.8, CRM 8.9, and with HCM 8.9) to Setup Manager Version 2 (shipped with PeopleTools 8.46 and above). The program moves all data from Setup Manager Version 1 tables to Version 2 tables.

The application engine program was designed so that it can be run in any database, and can be rerun in the same database. In either case, it will determine if there is data to convert and run as appropriate. For detailed information, see comments attached to the Steps and Actions in this Application Engine Program within Application Designer. This program must be run by a PeopleSoft User with PeopleSoft Administrator role.

Run the UPGPTSMDAT Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
INSTALL -AI UPGPTSMDAT
```

## Convert Navigation Collection and Pagelet Wizard Data

The application engine program UPGPT846PP adds Navigation Collection and Pagelet Wizard data from the Common Components and Enterprise Portal storage tables into PeopleTools tables.

The application engine program performs the following conversions:

1. Moves data from Common Components tables to PeopleTools tables.
2. Moves data from Enterprise Portal tables to PeopleTools tables.
3. Updates the registry definitions to enable displaying Navigation pages.
4. Adds, updates, and deletes the Navigation Collections folders and content references in the portal registry to the new structures.
5. Converts Pagelet Wizard definitions to the PeopleTools Pagelet Wizard version.
6. Renames Navigation Collection and Pagelet Wizard portal registry attributes to the PeopleTools attribute names.

This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role.

Run the UPGPT846PP Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
R INSTALL -AI UPGPT846PP
```

You may see the following error when running this Application Engine program:

```
You are not authorized for the <objecttype>...
```

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

You can ignore any other errors encountered on PeopleSoft delivered objects at this time. Check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database. You can safely rerun UPGPT846PP to check for any remaining errors after applying patches.

## Convert Additional Pagelet Wizard Data

The application engine program UPGPT848PP adds the following Pagelet Wizard data sources from Enterprise Portal to PeopleTools: IB Connector, Integration Broker, SOAP, and URL. In addition, the application program transforms the WSRP Portlets created in PeopleTools 8.46 or 8.47 versions of Pagelet Wizard. The process includes the following:

- Move data from Enterprise Portal tables to PeopleTools tables.
- Convert WSRP Portlets created by Pagelet Wizard to the new version.

This program must be run by a PeopleSoft user with the Portal Administrator or PeopleSoft Administrator role.

Run the UPGPT848PP Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
INSTALL -AI UPGPT848PP
```

You may see the following error when running this Application Engine program:

```
You are not authorized for the <objecttype>...
```

This means that you do not have proper privileges to run this conversion. The user ID that you are using to run this conversion needs to have Portal Administrator permissions.

You can ignore any other errors encountered on PeopleSoft delivered objects at this time. Check PeopleSoft Customer Connection for Required at Install patches for your application and apply the patches after installing your database. You can safely rerun UPGPT848PP to check for any remaining errors after applying patches.

## Task F-15-10: Converting Integration Broker

This section discusses:

- Updating Integration Broker Defaults
- Creating Integration Broker Objects
- Saving Application Messaging Objects
- Exporting Node Transactions
- Deleting Application Messaging Objects
- Deleting Node Transactions

If your database is delivered with PeopleTools 8.48 or higher, do *not* run this task since the database is already delivered with the new Integration Broker objects as of PeopleTools 8.48. Instead, proceed to Changing the User Interface.

### Updating Integration Broker Defaults

User-level node security and transactional security have been added as of PeopleTools 8.48. Service namespace information, a low-level user on the node, and a low-level permission list for service operations, need to be specified. Edit <PS\_HOME>\scripts\ptibupgrade.dms and make the necessary modifications as documented in the script. Consult with your Integration Broker specialist for assistance.

Open Data Mover using a valid PeopleSoft Operator ID and run this script.

### Creating Integration Broker Objects

The application engine program UPGPT848IBUG converts Application Package metadata into Integration Broker metadata. It also creates the projects PTUPGIBCLONE and PTUPGIBDELETE, and the script ptupg\_trx.dms.

---

**Note.** Conversion errors in the Application Engine log file will be resolved by applying application-specific Required for Install patches.

---

Run the UPGPT848IBUG Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <oprid> -CP <pswd> -R=>
INSTALL -AI UPGPT848IBUG
```

## Saving Application Messaging Objects

The PTUPGIBCLONE project was created by the UPGPT848IBUG Application Engine program and contains objects that were successfully converted. Copy this project to a directory of your choice where it will not be overwritten. The objects are copied to file as a precautionary measure since you will delete them from the database in a subsequent step.

To save Application Messaging Objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. From the Application Designer, select File, Open.
3. Select Project, enter *PTUPGIBCLONE* in the name dialog box, and click OK.
4. Select Tools, Copy Project, To File.
5. In the resulting dialog box, change the export directory to one of your choice, and click Copy.

When the progress dialog box disappears, the project has been copied to the specified location.

## Exporting Node Transactions

Open Data Mover using a valid PeopleSoft Operator ID and run the script *<PS\_HOME>\scripts\ptupg\_trx\_export.dms* to save the old pre-conversion node transaction data.

## Deleting Application Messaging Objects

Delete the obsolete pre-conversion object definitions from the database by first copying the PTUPGIBDELETE project to file, and then copying the same project from file. This project was created by the UPGPT848IBUG Application Engine program and contains the same objects as PTUPGIBCLONE.

To delete Application Messaging Objects:

1. Launch Application Designer and sign on to your database with a valid PeopleSoft user ID.
2. From the Application Designer, select File, Open.
3. Select Project, enter *PTUPGIBDELETE* in the name dialog box, and click OK.
4. Select Tools, Copy Project, To File.
5. In the resulting dialog box, change the export directory to the same one you used for PTUPGIBCLONE, and click Copy.

When the progress dialog box disappears, the project has been copied to the specified location.

6. Select Tools, Copy Project, From File.
7. In the resulting dialog box, change the import directory to the previously specified directory, select PTUPGIBDELETE from the list of projects, and click Select.

---

**Note.** Because the project already exists on the database, a confirmation dialog box appears asking if you want to overwrite the existing project. Select the File radio button and click OK to overwrite the existing project.

---

8. Select all object types and click the Copy button.

When the progress dialog box disappears, the project has been copied. The actions in the project are set to Delete, so this will delete the obsolete pre-conversion object definitions from the database.

## Deleting Node Transactions

The script `ptupg_trx.dms` is generated by the UPGPT848IBUG Application Engine program. This script can be found in the location specified in the OUTPUT variable set in Configuration Manager.

To view the OUTPUT variable:

1. Open Configuration Manager.
2. Select the Profile tab.
3. Click Edit to open the Default profile.
4. Select the Process Scheduler tab.
5. Examine the Output Directory value.

Open Data Mover using a valid PeopleSoft Operator ID and run this script to remove obsolete node transaction data associated with the obsolete objects in the PTUPGIBDELETE project.

## Task F-15-11: Changing the User Interface

PeopleTools has updated the styles that define the user interface. This PeopleTools release delivers the classic (old) style as well as two new styles: a dark blue style and a light blue style. PeopleTools System Databases and PeopleSoft 8.4 applications use the classic style, but all other applications use the new dark blue style. The classic style is set as the default. To use one of the new user interfaces, you have to delete the substyle sheets associated with the classic style and replace them with either the light or dark blue substyle sheet.

---

**Note.** The new user interface is supported by Internet Explorer release 5 and above and Netscape Navigator release 6 and above. If you are using a browser and release other than these, the system defaults to the classic style.

---

To enable a new user interface:

1. In Application Designer, select File, Open.
2. On the Open Definition dialog box, select *Style Sheet* from the Definition drop-down list.
3. Enter the name *PSSTYLEDEF* in the Selection Criteria Name field, and select Open.
4. Highlight *PSSTYLEDEF* in the list, and select Open.
5. Click the *PSALTERNATE* Sub Style Sheet and press DELETE.
6. Select Insert, Insert Sub Style Sheet.
7. Select *PSALTERNATE\_LIGHTBLUE* or *PSALTERNATE\_DARKBLUE*.
8. Repeat steps 5 through 7 for the *PTSTYLEDEF* Sub Style Sheet, making sure to use the same extension (*\_LIGHTBLUE* or *\_DARKBLUE*) you used for *PSALTERNATE*.
9. Select File, Save.
10. Open the style sheet *PSQUERYSTYLEDEF* as in steps 1 through 4.
11. Click the *PTQUERYSTYLESUB* Sub Style Sheet and press DELETE.
12. Select Insert, Insert Sub Style Sheet.
13. Select *PTQUERYSTYLESUB\_LIGHTBLUE* or *PTQUERYSTYLESUB\_DARKBLUE*.

Use the same extension that you used in step 8.

14. Select File, Save.

---

## Task F-16: Running Additional Data Mover Scripts

To import additional data for your specific PeopleSoft database, or to make other required changes, you may need to run additional Data Mover scripts. These script files have the extension .dms and are sometimes referred to as “DMS scripts.” They are located in the <PS\_HOME>\scripts directory of your file server, and need to be run from the file server by means of Data Mover.

For the details on which additional application-specific Data Mover scripts to run, consult your application-specific installation instructions.

If you have installed a language other than English, you may need additional instructions on language-specific Data Mover scripts.

See Installing a Multilingual PeopleTools System Database.

---

## Task F-17: Installing a Multilingual PeopleTools System Database

This section discusses:

- Understanding the Multilingual Database Project
- Applying the Multilingual Database Project
- Populating the Translated System Data

### Understanding the Multilingual Database Project

The information in this section applies if you are installing a multilingual PeopleTools System database. If not, skip this task and go on to the task “Running VERSION Application Engine Program.” If you are installing an application database (for example, HRMS, FSCM, EPM, and so on), you do not need to run this task.

If you are adding a new (PeopleSoft-delivered) language to the PTSYS database, you must execute this step for that language. For example, if you want to add Polish to your current multilingual database, you should install Polish from PPLTLSML so you will get all objects. If you only “upgrade” your database to have Polish using PPLTLS84CURML, you will only get the objects that changed between 8.40 and the current release.

If you are installing a PeopleTools System database and you want it to be multilingual, you need to perform the steps in the following section after the database has been loaded with Data Mover.

See Applying the Multilingual Database Project.

---

**Note.** When you log onto the multilingual database, be sure to select the base language of the database.

---



## Task F-17-1: Applying the Multilingual Database Project

This procedure describes how to apply the multilingual database project that contains translations of the PeopleTools objects.

To apply the multilingual database project:

1. Launch Application Designer.
2. Select Tools, Copy Project, From File.
3. In the resulting dialog box, change the import directory to <PS\_HOME>\projects.
4. Select *PPLTSLML* from the list of projects and click the Open button.
5. In the Upgrade Copy dialog box, make sure that all object types are selected.
6. Click the Options button, select the Copy Options tab, and ensure that only the non-English languages you have installed are selected.

Please note that English and Common should *not be selected*.

7. Select the languages that you are currently installing from the Copy Options dialog box.
8. Click the Copy button.

(The Reset Done Flags check box will be selected; accept this default.)

## Task F-17-2: Populating the Translated System Data

To populate the translated system data:

---

**Note.** You need to run the following script in User mode.

---

1. Launch Data Mover.
2. Open the pt848tlsx.dms script using File, Open.
3. Select File, Run

---

**Note.** The portion of the script name xxx is equivalent to the language code (that is, FRA, CFR, GER, JPN, and so on) of the languages you have installed. There will be a Data Mover script for each language.

---

## Task F-18: Running VERSION Application Engine Program

Run the VERSION Application Engine program on your database. From the DOS command line, the syntax is:

```
<PS_HOME>\bin\client\winx86\psae -CD <dbname> -CT ORACLE -CO <userid> -CP=>
<userpswd> -R INSTALL -AI VERSION
```

Use the values for the database name and user ID that you entered on the startup tab of the Configuration Manager for <dbname> and <userid> respectively. However, be aware that <userpswd> is not the same as the connect password you entered on the Configuration Manager startup tab. Enter a value for <userpswd> that is the password you want to be associated with the <userid>.

See “Setting Up the Install Workstation.”

See Running the Database Configuration Wizard.

## Task F-19: Changing the Base Language

Chapter 1 will help you determine whether you should change your base language, and lists the currently supported languages.

See “Preparing for Installation,” Planning Multilingual Strategy.

This task applies only if your users will be operating PeopleSoft applications *primarily* in one particular language other than English. It gives a performance boost to the language you designate as the base language, but requires more administrative overhead than leaving English as the base language. The details are spelled out in the following PeopleBook:

See *Enterprise PeopleTools 8.48 PeopleBook: Global Technology*.

## Task F-20: Running SQR Reports

This section discusses:

- Running SQRs on the Client Workstation
- Creating a Shortcut to Run SQRs


**Note.** The following instructions describe how to run SQR reports from the client workstation. On the Windows client, you may prefer to create a shortcut to allow you to run the reports repeatedly. You can use these instructions to run SQRs required in the upcoming task “Checking the Database.” You can also choose to run SQR reports from the command line in console mode.

### Task F-20-1: Running SQRs on the Client Workstation

To run an SQR on the client workstation:

1. Select Start, Run, click Browse, and navigate to <PS\_HOME>\bin\sqr\ORA\binw.  
Select sqrw.exe and click Open.
2. Add any needed flags at the end of the command line.

Refer to the table that follows. For those flags that require attributes, append the attributes to the flags with no intervening spaces (for example, `-fd:\psbase\psenv\cr881dmo\`).




Running an SQR report on the client

The following table summarizes the SQR report arguments used by PeopleSoft. (For a full listing of report arguments, press the Help button to view the SQR help topic for this dialog box.)

Flag	Description
-I	Specifies the directories that SQR will search for the #INCLUDE files. (A trailing slash is required.)
-f	Specifies the directory where the report output will be sent. If you use the <code>-keep</code> flag, specify a directory with an ending slash. If you use the <code>-printer</code> flag, specify a full pathname with a filename for the HTML file.
-ZIF	Sets the full path and name of the SQR initialization file. The <code>-ZIF</code> flag should point to your <code>&lt;PS_HOME&gt;\sqr\pssqr.ini</code> file.
-keep	Keeps the .SPF file after the program runs. This enables you to view the report with the SQR viewer.
-printer:ht	Generates the output file in HTML format. Specify the filename, with path location, with the <code>-f</code> flag.

- Click OK.

The resulting dialog box should look something like this:



SQR for PeopleSoft dialog box

- Enter the following values:
  - Enter the report name.  
You must specify the full path.
  - Enter the access ID in the Username field.
  - Enter the access password in the Password field.
  - Enter the database name.
- Click OK to run the SQR report.

---

**Note.** In the Properties dialog box for your SQR icon, make sure that the Start in path points to your Oracle connectivity on the Shortcut tab. If you take the default, you may see a misleading error message about TNS packet writer failure.

---

## Task F-20-2: Creating a Shortcut to Run SQRs

If you think you may need to run the SQR reports more than once, you may want to create a shortcut on the Windows client workstation. To save the report arguments:

1. Open Windows Explorer on the machine on which you want to run SQR.
2. Navigate to <PS\_HOME>\bin\sqr\ORA\binw.
3. Right-click sqrw.exe and click Create Shortcut.
4. Right-click the shortcut that you just created and select Properties.
5. On the Shortcut tab, add the same sqr flags that you used in the previous task after sqrw.exe in the Target entry box.
6. Click OK.
7. To run the report, double-click the shortcut and specify the following information in the dialog box:
  - Report Name: Enter the full path and the name.
  - Database name
  - Username: Enter the access ID.
  - Password: Enter the access password.
  - Report arguments: Make any necessary modifications to the saved arguments.
8. Click OK.

---

## Task F-21: Checking the Database

Run and examine two SQR reports to verify that your database is complete.

See Preparing to Run SQR.

To verify that the database is complete, run the following SQR reports from the <PS\_HOME>\sqr directory:

- dddaudit.sqr
- sysaudit.sqr.

For further information about the dddaudit and sysaudit reports, consult PeopleBooks. This documentation includes specific information on how to interpret the reports and how to fix any errors found there.

See *Enterprise PeopleTools 8.48 PeopleBook: Data Management*, “Ensuring Data Integrity.”

You can greatly improve the performance and run time of sysaudit.sqr run by making the following configuration changes to the Oracle init.ora for your SID:

```
db_file_multiblock_read_count = 16
db_block_buffers = 2000 or greater
```

```
log_checkpoint_interval = 9999999
log_buffer = 102400
```

If you are using rollback segments, you may also want to increase the size of the RBSBIG rollback segment to 500 MB.

---

**Note.** If any records show up in the VIEWS-2 or TABLE-3 section of dddaudit and are contained within the PPLTLS84CURDEL project, you may safely drop these records using the SQL query tool for your platform.

---

## See Also

*Enterprise PeopleTools 8.48 PeopleBook: Data Management*

*Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*

---

## Task F-22: Running SETSPACE.SQR


Run the SETSPACE.SQR script to populate or synchronize Tablespace information with the system catalog. To run SETSPACE.SQR:

1. Using the instructions provided in the earlier task "Preparing to Run SQR," run SETSPACE.SQR from the <PS\_HOME>\SQR directory.

---

**Note.** Your results will vary depending on the application you are loading.

---



Running SETSPACE.SQR on the SQR for PeopleSoft dialog box

2. Click OK.
3. As SETSPACE.SQR runs you see a progress indicator similar to the following.

```
Set Table Space Name in PSRECTBLSPC
```

```
Table PSRECTBLSPC column DDLSPACENAME have been updated
with the tablespace found in the system catalog table.
The total number of records updated appears at the bottom of this report.
```

Recname	New DDLSpaceName	Old DDLSpaceName
-----		
This phase of SETSPACE will sync up the PSRECTBLSPC and PSTBLSPCCAT tables		
PSRECTBLSPC Records Updated:		0
PSTBLSPCCAT Records Inserted:		0
Ending SQR.		

## APPENDIX G

# Relinking SQR on UNIX

This appendix discusses:

- Understanding SQR Relinking
- Relinking SQR on UNIX
- Relinking SQR on HP-UX

---

## Understanding SQR Relinking

PeopleSoft SQR is now linked with Unicode libraries and therefore no longer requires relinking with Unicode libraries. PeopleSoft SQR uses dynamic linking for database connectivity libraries and should not require relinking to support new versions of database connectivity. The exception to this rule is if the PeopleTools release spans multiple RDBMS versions and the database connectivity changes the names or functionality of required libraries in the new release. In addition, relinking may be required for invoking an external application's APIs using the UFUNC.C interface, as described in the SQR for PeopleSoft Developers PeopleBook.

See *Enterprise PeopleTools 8.48 PeopleBook: SQR for PeopleSoft Developers* “Using Interoperability Features.”

For example, PeopleTools 8.4 is currently supported on two major Oracle releases (Oracle 8i and Oracle 9i). Based on the timing of our release we built the SQR modules for a specific PeopleSoft release with the lowest supported RDBMS version. For PeopleTools 8.4x, the minimum supported Oracle version is Oracle 8i (8.1.7.2.0). This means PeopleSoft SQR will work right out of the box on Oracle 8i (no relink required). For Oracle 9i support we need to relink SQR so that the symbol names or functionality in the newer version can be found.

---

**Note.** For PeopleTools 8.4x and Oracle, the only platform upon which SQR needs to be relinked is HP-UX. Relinking on HP-UX is described in detail later in this appendix.

---

---

## Task G-1: Relinking SQR on UNIX

Here's a high-level overview of what you need to do, on a UNIX platform, to relink SQR:

1. Export the following environment variables:
  - SQRDIR, the location of the SQR executable.
  - PS\_HOME, the PeopleSoft home directory.
  - PS\_DB, the platform identifier variable:  
ORA for Oracle

2. Export the database install home directory:

```
ORACLE_HOME
```

3. Add SQRDIR to the library path.

```
export LD_LIBRARY_PATH=$SQRDIR:$LD_LIBRARY_PATH
```

or

```
export SHLIB_PATH=$SQRDIR:$SHLIB_PATH
```

4. CD to <PS\_HOME>/bin/sqr/<PS\_DB>/lib

5. Run sqrmake.

---

**Note.** The following section is a step-by-step example illustrating how to relink SQR on the HP-UX/Oracle platforms. Other OS-platform combinations work in a similar fashion.

---

## Task G-2: Relinking SQR on HP-UX

To relink SQR on HP-UX:

1. If the psconfig.sh shell script has not been executed, check for SQR env variables and set them as necessary.

---

**Note.** If your <PS\_HOME>/psconfig.sh correctly sets the environment variables described below, you can skip this step.

---

```
env | grep SQRDIR
```

```
SQRDIR=
```

```
export SQRDIR=/home/hp844901run/bin/sqr/ORA/bin
```

```
env | grep PS_HOME
```

```
PS_HOME=
```

```
export PS_HOME=/home/hp844901run
```

```
env | grep PS_DB
```

```
PS_DB=
```

```
export PS_DB=ORA
```

```
env | grep ORACLE_HOME
```

```
ORACLE_HOME=
```

```
export ORACLE_HOME=/products/oracle/b.9.2.0-64bit
```

```
export SHLIB_PATH=/home/hp844901run/bin/sqr/ORA/bin:$SHLIB_PATH
```

2. Recheck the SQR env:

```
sp-hp12:$ env | grep -i sqr
```

```
SHLIB_PATH=/home/hp844901run/bin/sqr/ORA/bin:/lib:/usr/lib:/usr/local/lib:/usr⇒
/lib/X11:/sqr/prod/dbx/4.3.4/bin:/tuxedo/prod/6.5-j1.2/lib:/cobol/prod/
svrexp-2.2/coblib:/pt/products/hpux-11-parisc/lib:/dsl/home/db2udb7/sqllib/lib
SQRDIR=/home/hp844901run/bin/sqr/ORA/bin
```



```
PWD=/home/hp844901run/bin/sqr/ORA/bin
```

### 3. Relink SQR for Oracle9i.

```
sp-hp12:$ sqrmake
        /usr/ccs/bin/ld -o sqr /usr/ccs/lib/crt0.o -u__exit -umain cprpt0.o⇒
+s -s sqr.o rosette.o sqr.a libsti.a bcl.a pdf.a zlib.a -L. -lsqrbtunicode
-L/products/oracle/b.9.2.0-64bit/lib32 -L/products/oracle/b.9.2.0-64bit/rdbms⇒
/lib32 -lcIntsh -lpthread -lstd_v2 -lCsup_v2 -lm -lcl -lc /usr/lib/libdld.sl -
l:libcl.sl -l:librt.sl -lpthread -l:libnss_dns.1 -l:libdld.sl
        /usr/ccs/bin/ld -o sqrp /usr/ccs/lib/crt0.o -u__exit -umain cprpt0.o⇒
+s -s sqrp.o rosette.o sqrp.a libsti.a bcl.a pdf.a zlib.a -L. -lsqrbtunicode
-lpthread -lstd_v2 -lCsup_v2 -lm -lcl -lc /usr/lib/libdld.sl -l:libcl.sl -l:⇒
librt.sl -lpthread -l:libnss_dns.1 -l:libdld.sl
        /usr/ccs/bin/ld -o sqrt /usr/ccs/lib/crt0.o -u__exit -umain cprpt0.o⇒
+s -s sqrt.o rosette.o sqrt.a libsti.a bcl.a pdf.a zlib.a -L. -lsqrbtunicode
-L/products/oracle/b.9.2.0-64bit/lib32 -L/products/oracle/b.9.2.0-64bit/rdbms⇒
/lib32 -lcIntsh -lpthread -lstd_v2 -lCsup_v2 -lm -lcl -lc /usr/lib/libdld.sl -
l:libcl.sl -l:librt.sl -lpthread -l:libnss_dns.1 -l:libdld.sl
sp-hp12:$
```

### 4. Validate the relinked SQR executable:

Once linked, cd to \$SQRDIR

```
sp-hp12:$ cd $SQRDIR
```

```
sp-hp12:$ pwd
```

```
/home/hp844901run/bin/sqr/ORA/bin
```

Validate SQR executable

```
sp-hp12:$ sqr -id
```

```
SQR for PeopleSoft/8.44/HP 9000/HPUX B.11.00/Oracle 8.0.6/Jun 25 2002
```

Use, duplication or disclosure by the Government is subject to restrictions as set forth in subparagraph (c) (1) (ii) of DFARS 52.227-7013 for the DOD and as set forth in FAR 52.227-19 (a) - (d) for civilian agencies.

SQR is a registered trademark.

Any other brand and product names used herein may be trademarks or registered trademarks of their respective companies.

```
sp-hp12:$
```

```
sp-hp12:$ sqr
```

SQR for PeopleSoft V8.44

SQR for PeopleSoft [program] [username/password] [-flags...] [pars...] [@file..]

where

```

    program = Report filename
    username = Database username
    password = Database password

    -A = Append to existing output file
    -Bn = Fetch n rows at a time
    -Burst:{xx} = Generate .LIS using specified burst mode (S,T or P)
    -Dn = Display report while processing, pause every n lines
    -DEBUGxx = Compile #DEBUG[x] lines
    -DNT:{xx} = Set the default numeric type (Decimal,Integer,Float)
    -E[file] = Direct errors to {program}.ERR or specified file
    -EH_BQD[:file] = Create BQD file or set linkage for Enhanced HTML
    -EH_APPLETS:dir = Set applets directory name for Enhanced HTML
    -EH_BROWSER:{xx} = Specify target browser for Enhanced HTML
    -EH_CSV[:file] = Create CSV file or set CSV linkage for Enhanced HTML
    -EH_CSVONLY = Create CSV file but do not create HTML file
    -EH_ICONS:dir = Set icons directory name for Enhanced HTML
    -EH_IMAGES:dir = Set images directory name for Enhanced HTML
    -EH_KEEP = Copy (not move) files when used with -EH_ZIP
    -EH_FULLHTML:{xx} = Specify the level of the generated Enhanced HTML
    -EH_LANGUAGE:{xx} = Specify language for Enhanced HTML navigation bar
    -EH_PDF = Set PDF linkage for Enhanced HTML
    -EH_SCALE:nn = Set scaling factor for Enhanced HTML
    -EH_XIMG = Do not remove directory path from IMAGE reference
    -EH_XML[:file] = Set XML linkage for Enhanced HTML
    -EH_ZIP[:file] = Move files to ZIP container file
    -F[dir/file] = Use [dir]{program}.LIS or specified file for output
    -Idir_list = Directory list to be searched for include files
    -ID = Display copyright banner
    -KEEP = Keep the .SPF file(s) after program run
    -LL{s|d}{c|i} = Load-Lookup: S=SQR, D=DB, C=Case Sensitive, I=Insensitive
    -Mfile = Maximum sizes declared in file
    -NOLIS = Do not generate .LIS file(s) from .SPF file(s)
    -O[file] = Direct log messages to console or specified file
    -PRINTER:{xx} = Printer mode: EP, EH, HT, LP, HP, PD, or PS
    -RS = Save run time file in {program}.sqt
    -RT = Use run time file (skip compile)
    -S = Display cursor status at end of run
    -Tn = Test report for n pages, ignore 'order by's
    -XB = Do not display the program banner
    -XI = Do not allow user interaction during program run
    -XL = Do not logon to database (no SQL in program)
    -XLFF = Do not generate trailing report form feed
    -XTB = Do not trim blanks from LP .LIS files

```

```

        -XNAV = Do not put navigation bar into .HTM file
        -XTOC = Do not generate Table Of Contents
    -ZEN{name} = Set default encoding name
    -ZIF[file] = Complete pathname of the initialization file to use
    -ZMF[file] = Complete pathname of the message file to use
        pars = Report parameters for ASK and INPUT commands
        @file = File containing report parameters, one per line
sp-hp12:$

```

5. CD to the actual location of \$PS\_HOME to set the PeopleSoft env with the correct SQR ENV.

```

sp-hp12:$ . ./psconfig.sh
sp-hp12:$

```

6. Test SQR from the UNIX command line, entering the access ID and password for the database <DBNAME>.

---

**Note.** Remember that this example is specifically for Oracle. The commands for other RDBMS platforms may be different.

---

```

sp-hp12:$ sqr $PS_HOME/sqr/xrffwin <ACCESS_ID>/<ACCESS_PSWD>@<DBNAME> -ZIF$PS_⇒
HOME/sqr/pssqr.unx
SQR for PeopleSoft V8.47
Database Name (Optional, Press ENTER to continue):
Process Instance (Optional, Press ENTER to continue):

SQR for PeopleSoft: End of Run.
sp-hp12:$

```



## APPENDIX H

# Securing the Report Repository for HTTP

This appendix discusses:

- Setting Up Security in the Web Server
- Updating the Report Node Definition

---

**Note.** The SchedulerTransfer Java servlet is used to migrate reports to and from the report repository when using HTTP or HTTPS transfer protocol.

---

## Task H-1: Setting Up Security in the Web Server

This section discusses:

- Understanding Web Server Security
- Setting Up Basic Authentication in Oracle Application Server
- Setting Up Basic Authentication in WebLogic
- Setting Up Basic Authentication in WebSphere

### Understanding Web Server Security

To prevent unauthorized users from accessing the report repository, when using HTTP or HTTPS transfer protocol, access to the SchedulerTransfer Java servlet needs to be secured. To do this you first need to set up an authorized user ID through the web server. Procedures for setting up the user ID are different in Oracle Application Server, WebLogic, and WebSphere.

### Task H-1-1: Setting Up Basic Authentication in Oracle Application Server

You should carry out the procedure in this section to edit the application EAR file before deploying the application to Oracle Application Server (OAS).

To set up basic authentication in OAS:

1. Extract the application EAR file into a temp directory (for example, C:\temp).

---

**Note.** For single server installation, the EAR file is peoplesoft-OAS.ear. For multi-server installation, the EAR file is PIA.ear.

---

2. Modify the application.xml file and add the text as shown below in the <security\_role> area.
  - a. Open C:\temp\META-INF\application.xml.

- b. Add the security section shown below (bold font):

```

<application>
...
...
</module>
<module id="WebModule_1084297392069">
<web>
<web-uri>PSEMHUB</web-uri>
<context-root>/PSEMHUB</context-root>
</web>
</module>
<b><security-role id="SecurityRole_1083944662253">
<description>Role for SchedulerTransfer Servlet</description>
<role-name>SchedulerTransferRole</role-name>
</security-role>
</application>

```

- c. Save and close the file.

3. Modify the PORTAL web.xml file.

- a. Extract C:\temp\PORTAL.war to C:\temp\PORTAL directory.  
b. Open C:\temp\PORTAL\WEB-INF\web.xml.  
c. Add the following section (bold font) after the <welcome-file-list> element, and before the </web-app> element:

```

<welcome-file-list>
<welcome-file>index.html</welcome-file>
</welcome-file-list>
<b><security-constraint>
<web-resource-collection>
<web-resource-name>SchedulerTransferWebResource</web-resource-name>
<description>SchedulerTransferWebResourceDescription</description>
<url-pattern>/SchedulerTransfer/*</url-pattern>
<http-method>GET</http-method>
<http-method>POST</http-method>
</web-resource-collection>
<auth-constraint>
<description></description>
<role-name>SchedulerTransferRole</role-name>
</auth-constraint>
</security-constraint>
<b><security-role>
<description></description>
<role-name>SchedulerTransferRole</role-name>
</security-role>
</web-app>

```

- d. Save and close the file.

4. Recreate the EAR file by running the following commands:

- a. `cd C:\temp`
- b. For single server installation:
 

```
jar -cvf ..\peoplesoft-OAS.ear .
```


 For multi-server installation:
 

```
jar -cvf ..\PIA.ear .
```
5. Run the PIA installation with the modified EAR file.
6. Set up Users and associate the Roles to the Users using Application Server Control as follows:
  - a. Open the OAS Application Server Control.
 

See “Working with Oracle Application Server,” PeopleSoft Customer Connection (Support, Documentation, Documentation Updates, Enterprise).
  - b. Click the OC4J component where the application was installed.

**Note.** Refer to installation instructions about the name of the components created during PIA installation. This example uses the application “PeopleSoft.”

See “Setting Up the PeopleSoft Pure Internet Architecture (in GUI Mode or Console Mode),” Installing the PeopleSoft Pure Internet Architecture on Oracle Application Server (in GUI Mode or Console Mode).



Oracle Application Server Control window

- c. Select the link Applications.

ORACLE Enterprise Manager 10g  
Application Server Control  
Farm > Application Server: OAS022805instance.ple-ssankinea.peoplesoft.com >  
OC4J: PeopleSoft

Home Applications Administration

Page Refreshed Sep 2, 2005 5:16:02 PM

**General**

Status **Up** [Stop](#) [Restart](#)  
Start Time **Sep 2, 2005 3:03:47 PM**  
Virtual Machines **1**

**JDBC Usage**

Open JDBC Connections	0
Total JDBC Connections	0
Active Transactions	0
Transaction Commits	0
Transaction Rollbacks	0

**Status**

CPU Usage (%)	0.05
Memory Usage (MB)	46.91
Heap Usage (MB)	9.73

**Response - Servlets and JSPs**

Active Sessions	0
Active Requests	1
Request Processing Time (seconds)	0.00
Requests per Second	0.17

**Response - EJBs**

Active EJB Methods	0
Method Execution Time (seconds)	0.00
Method Execution Rate (per second)	0.00

Related Link [All Metrics](#)

Home Applications Administration

Reviewing component information on the OAS control window

- d. Click the application name.

ORACLE Enterprise Manager 10g  
Application Server Control  
Farm > Application Server: OAS022805instance.ple-ssankinea.peoplesoft.com >  
OC4J: PeopleSoft

Home Applications Administration

Page Refreshed Sep 2, 2005 5:17:02 PM

Default Application Name [default](#)  
Default Application Path [application.xml](#)

**Deployed Applications**

[Edit](#) [Undeploy](#) [Redeploy](#) [Deploy EAR file](#) [Deploy WAR file](#)

Select	Name	Path	Parent Application	Active Requests	Request Processing Time (seconds)	Active EJB Methods
<input checked="" type="radio"/>	PeopleSoft	../applications/PeopleSoft.ear	default	0	0.002	0

OAS Control window: Applications tab

- e. In the Administration area, select Security.

**Administration**

<a href="#">Properties</a>	<a href="#">Resources</a>	<a href="#">Security</a>
<a href="#">General</a>	<a href="#">Data Sources</a>	<a href="#">Security</a>
<a href="#">Advanced Properties</a>	<a href="#">JMS Providers</a>	

Administration area on the OAS Control window

- f. Click the Add User button.



Oracle Enterprise Manager 10g  
Application Server Control

Page Refreshed Sep 2, 2005 5:19:28 PM

Security

Principals

User Manager Name JAZNUserManager  
User Manager Class oracle.security.jazn.oc4j.JAZNUserManager

Groups

Select Name  
No groups found using the specified User Manager

Users

Select Name  
No users found using the specified User Manager

Security Roles

Select Name  
No security roles found in this application

Viewing application security information on the OAS Control window

- g. Enter the user name and password, and click OK.

**Note.** Specify a user that is part of the Administration group on Windows. On UNIX, use the root user name and password, or a user who has permission to run OAS.

Oracle Enterprise Manager 10g  
Application Server Control

Security: Add User

General

Name  
Description  
Password  
Confirm Password

Group Memberships

Select Group Name

Cancel OK

Adding a user on the OAS Control window

- h. Click on the button "Map Roles to Principals" that is part of Security Roles.
- i. Select the check box for the user just created and click the Apply button.

Oracle Enterprise Manager 10g  
Application Server Control

Role: SlamSessRole

Page Refreshed Sep 2, 2005 5:26:41 PM

Map Role To Groups

Select Group Name

Map Role To Users

Select All | Select None

Select User Name

☒ jazn.com/abc

Revert Apply

Mapping role to users on the OAS Control window

7. Restart the OC4J component.

## Task H-1-2: Setting Up Basic Authentication in WebLogic

The procedure for restricting and securing access for servlets on WebLogic is covered in PeopleBooks documentation. To restrict access to the SchedulerTransfer Java servlet, substitute */SchedulerTransfer/\** for “/” when the procedure asks you to specify the URL which will require authentication.

See *Enterprise PeopleTools 8.48 PeopleBook: System and Server Administration*, “Working with BEA WebLogic.”

---

**Note.** When prompted for a User Name and Password, specify the WebLogic system ID and password. If you followed the default WebLogic Server install, the User Name and Password are system and password. Otherwise, specify the password supplied during your WebLogic server installation.

---

## Task H-1-3: Setting Up Basic Authentication in WebSphere

To set up basic authentication in WebSphere:

1. Open Admin Console and enable security.
  - a. Select Security, Global Security, and select the Enabled check box.
  - b. Click OK and then enter the user name and password.
  - c. Enter the user ID and password.

---

**Note.** When prompted for a user ID and password, specify a user that is part of the Administration group on Windows. On UNIX, use the root user name and password, or a user who has permission to run WebSphere.

---

- d. Save the configuration in the Admin Console and log out.
2. Modify the application.xml file and add the text below in the <security\_role> area.
  - a. Open <PS\_HOME>\webserve\<cell>\_<node>\_<server>\peoplesoft.ear\META-INF\application.xml
  - b. Add the security section shown below:

```
</module>
<module id="WebModule_1084297392069">
  <web>
    <web-uri>PSEMHUB</web-uri>
    <context-root>/PSEMHUB</context-root>
  </web>
</module>
<security-role id="SecurityRole_1083944662253">
  <description>Role for SchedulerTransfer Servlet</description>
  <role-name>SchedulerTransferRole</role-name>
</security-role>
</application>
```

- c. Save and close the file.
3. Modify the ibm-application-bnd.xmi file.
  - a. Open <PS\_HOME>\webserve\<cell>\_<node>\_<server>\peoplesoft.ear\META-INF\ibm-application-bnd.xmi.
  - b. Make the change indicated below:

---

**Note.** In the UserName line to be replaced, make sure you have added the user name to access the servlet.

---

*Before Update:*

```
<?xml version="1.0" encoding="UTF-8"?>

<com.ibm.ejs.models.base.bindings.applicationbnd:ApplicationBinding xmi:⇒
version="2.0" xmlns:xmi="http://www.omg.org/XMI" xmlns:⇒
com.ibm.ejs.models.base.bindings.applicationbnd="applicationbnd.xmi" xmi:id=⇒
"ApplicationBinding_1064609410468">

<authorizationTable xmi:id="AuthorizationTable_1064609410468"/>
<application href="META-INF/application.xml#Application_ID"/>
<runAsMap xmi:id="RunAsMap_1064609410468"/>
</com.ibm.ejs.models.base.bindings.applicationbnd:ApplicationBinding>
```

*After Update:*

```
<?xml version="1.0" encoding="UTF-8"?>

<applicationbnd:ApplicationBinding xmi:version="2.0" xmlns:xmi="http:⇒
//www.omg.org/XMI" xmlns:applicationbnd="applicationbnd.xmi" xmi:id=⇒
"ApplicationBinding_1083944662253">
<authorizationTable xmi:id="AuthorizationTable_1083944662253">
<authorizations xmi:id="RoleAssignment_1083944662253">
<users xmi:id="User_1083944662253" name="<Change to UserName part of
Admin group on NT and on UNIX either root or any user set up to
run as non-root>"/>
<role href="META-INF/application.xml#SecurityRole_1083944662253"/>
<groups xmi:id="Group_1083946750626" name="Administrators"/>
</authorizations>
</authorizationTable>
<application href="META-INF/application.xml#Application_ID"/>
</applicationbnd:ApplicationBinding>
```

- c. Save and close the file.
4. Modify the web.xml file.
  - a. Open <PS\_HOME>\webserv\<cell>\_<node>\_<server>\peoplesoft.ear\PORTAL\WEB-INF\web.xml.
  - b. Add the following section after the <welcome-file-list> element, and before the </web-app> element:

```
<welcome-file-list>
<welcome-file>index.html</welcome-file>
</welcome-file-list>
<security-constraint>
<web-resource-collection>
<web-resource-name>SchedulerTransferWebResource</web-resource-name>
<description>SchedulerTransferWebResourceDescription</description>
<url-pattern>/SchedulerTransfer/*</url-pattern>
<http-method>
```

```

GET</http-method>
<http-method>
POST</http-method>
</web-resource-collection>
<auth-constraint>
<description></description>
<role-name>SchedulerTransferRole</role-name>
</auth-constraint>
</security-constraint>
<security-role>
<description></description>
<role-name>SchedulerTransferRole</role-name>
</security-role>
</web-app>

```

- c. Save and close the file.
5. Test authentication.
  - a. Re-start the Websphere server, as follows:

```
stopServer server1 -user <username> -password <password>
```

```
startServer server1 -user <username> -password <password>
```

- b. You will be prompted for the user name and password. Enter the user name and password that were defined in the <PS\_HOME>\web serv\<cell>\_<node>\_<server>\peoplesoft.ear\META-INF\ibm-application-bnd.xmi file.
- c. You will be allowed access to the servlet after you enter the user name and password.

To secure the SchedulerTransfer servlet in clustered environment using ND (Network Deployment), refer to the clustering and high availability Red Paper. It has instructions for creating a single EAR file. Update the following files within the exploded EAR file using the instructions in this section to secure the servlet.

```

<PS_HOME>\web serv\<cell>_<node>_<server>\peoplesoft.ear\META-INF⇒
\application.xml
<PS_HOME>\web serv\<cell>_<node>_<server>\peoplesoft.ear\META-INF\ibm⇒
\application-bnd.xmi
<PS_HOME>\web serv\<cell>_<node>_<server>\peoplesoft.ear\PORTAL\WEB-INF⇒
\web.xml

```

After updating the files, compress the exploded PIA into a single EAR. Continue the rest of the instructions to deploy EAR to ND.

See Clustering and High Availability for PeopleSoft 8.4, PeopleSoft Customer Connection (Implement, Optimize + Upgrade, Implementation Guide, Implementation Documentation and Software, Red Paper Library).

## Task H-2: Updating the Report Node Definition

To secure the report repository, the new web server user account is added to the report node definition. The Distribution Agent will use this login information when it accesses the report repository to post files.

**Http Distribution Node** **ETP/XCopy Distribution Node**

### Report Node Definition

**Node Name:** DCRAIG042302

☐ Ftp/XCopy ☒ **Http Information**

**Distribution Node Details**

**URL:**

**Description:**

**Operating System:**

**Connection Information**

☒ **http** ☐ https

**URI Host:**  **URI Port:**

**URI Resource:**

**Login ID:**

**Password:**  **Confirm Password:**

Process Scheduler - Report Node Definition page

To update the report node definition:

1. Sign into the PeopleSoft system.
2. Navigate to PeopleTools, Process Scheduler, Report Nodes.
3. Select Find an Existing Value, and enter the report node name associated with the report repository where the basic authentication was set up.
4. Select Search.

The Report Node Definition page appears.

5. Go to the Connection Information section and enter the new web server user account information:
  - *Login ID* — Webserver user ID that was created in the previous procedure.
  - *Password* — Password for the webserver user ID.
  - *Confirm Password* — Enter the password again as confirmation.



## APPENDIX I

# Using the XSLT Mapper with Oracle BPEL Process Manager

This appendix discusses:

- Understanding the XSLT Mapper
- Installing BPEL Process Manager
- Setting Up the XSLT Mapper

---

## Understanding the XSLT Mapper

The Extensible Stylesheet Language Transformation (XSLT) mapper is intended for application developers and consultants who write PeopleSoft Application Engine programs of type “transform.” The XSLT mapper allows you to write transformation programs without hard-coding each XSLT step. The XSLT mapper is integrated with JDeveloper BPEL Designer, a component of Oracle BPEL Process Manager. To use the XSLT mapper, you must first install Oracle BPEL Process Manager, and then specify the location of the JDeveloper files in your PeopleSoft installation.

This section assumes that you have installed the PeopleSoft workstation.

### See Also

“Setting Up the Install Workstation”

*Enterprise PeopleTools 8.48 PeopleBook: Integration Broker*, “Applying Filtering, Transformation and Translation”

---

## Task I-1: Installing BPEL Process Manager

Download the Oracle BPEL Process Manager software and installation instructions from the Oracle Technology Network (OTN). Install the BPEL Process Manager on a Windows-based machine.

See Oracle Technology Network, <http://www.oracle.com/technology/index.html>

Search the OTN documentation web site for information on installing BPEL Process Manager.

See Oracle Documentation, <http://www.oracle.com/technology/documentation/index.html>


Be sure to obtain any patches that are required for the installation from the following location:

<ftp://ftp.peoplesoft.com/outgoing/ptools/Oracle/BPEL>

## Task I-2: Setting Up the XSLT Mapper

To use the XSLT mapper, use Configuration Manager to specify the directory for JDeveloper:

1. Launch Configuration Manager by doing one of the following:
  - Select Start, Program, PeopleTools 8.48, Configuration Manager.
  - Double-click <PS\_HOME>/bin/client/winx86/pscfcg.exe.
2. Select the Crystal/Bus. Interlink/JDeveloper tab.



Configuration Manager: Crystal/Bus. Interlink/JDeveloper tab

3. Click the JDeveloper Path browse button (...) and select the JDeveloper directory.  
In a default installation of the BPEL Process Manager, the JDeveloper path is <OraBPELPM\_HOME>/integration/jdev.  
Configuration Manager will verify that the version of JDeveloper is valid. If not, when you click OK to save the changes and exit Configuration Manager, an error message appears.
4. Click OK.



## APPENDIX J

# Setting Up the PeopleSoft Installation with Oracle 10g RAC

This appendix discusses:

- Understanding the PeopleSoft Installation on Oracle 10g RAC
- Prerequisites
- Setting Up the Database
- Configuring Database Security
- Configuring the Tnsnames and Listener Files
- Configuring the Application Server

---

## Understanding the PeopleSoft Installation on Oracle 10g RAC

If you are installing PeopleTools using the Oracle 10g Real Application Cluster (RAC) database platform, read this appendix to understand the differences in the installation procedures. An Oracle 10g RAC configuration is a multi-Oracle instance environment that uses cluster software to communicate between different Oracle instances and cluster members.

You must use the manual database creation procedure if you are installing on an Oracle 10g RAC database. The manual procedure gives you the ability to specify multiple mounting points for raw devices, edit database setup scripts, and edit data mover scripts. You must also configure the PeopleSoft application server and process scheduler.

See “Creating a Database Manually on UNIX.”

See “Creating a Database Manually on Windows.”

---

## Prerequisites

To use the Oracle 10g RAC system with PeopleTools, the cluster environment must support the cluster file system. Before beginning the installation, verify that your system satisfies the following requirements:

- Oracle datafiles and control files must be raw devices unless a cluster file system is supported by the cluster software.
- Each datafile or control file is a single raw device that must be shareable to all cluster members.
- You must have installed Operating System Cluster Software.

- You must have installed the RAC version of the Oracle database.
- You must modify certain operating system parameters.

See *Oracle® Real Application Clusters Installation and Configuration Guide 10g Release 1 (10.1) for AIX-Based Systems, Apple Mac OS X, hp HP-UX, hp Tru64 UNIX, Linux, Solaris Operating System, and Windows Platforms Part No. B10766-08*

---

## Task J-1: Setting Up the Database

This section discusses:

- Understanding the Database Setup
- Creating Raw Devices
- Editing the CREATEDB10.SQL Script
- Editing the UTLSPACE.SQL Script
- Editing the XXDDL Script
- Creating Initialization Files

### Understanding the Database Setup

Use the following guidelines in setting up the Oracle 10g RAC database:

- Follow the instructions in the appendix for creating a database manually on either UNIX or Windows.

See “Creating a Database Manually on Windows.”

See “Creating a Database Manually on UNIX.”

- Use the examples in this appendix to edit the following scripts:

- createdb10.sql
- utlspace.sql
- xxddl.sql

- Create an ORACLE\_SID for each Oracle instance.

Each Oracle instance must have its own ORACLE\_SID and its own Oracle initialization file. Within each specific Oracle initialization file, you must define the *thread*, *instance\_number*, *instance\_thread*, *undo tablespaces*, the name of a common initialization file, and service name. Within the common initialization file, you must specify the *control files* and the value *cluster\_database=true*.

### Task J-1-1: Creating Raw Devices

You must create raw volumes for each tablespace and control file which the database uses unless a cluster file system is supported by the cluster software. The following list is an example of raw devices and sizes used in the xxddl.sql script.

Raw Devices Function	Example Names	Sizes (MB)
<i>Oracle Instance required:</i>		
Control file 1		
Control file 2		
System	/dev/vg_rac/rlv_system	350
Sysaux	/dev/did/rdsk/rlv_sysaux	500
Log 1	/dev/did/rdsk/rlv_log1	190
Log 2	/dev/did/rdsk/rlv_log2	190
Log 3	/dev/did/rdsk/rlv_log3	190
Log 4	/dev/did/rdsk/rlv_log4	190
Undo 1	/dev/did/rdsk/rlv_psundo1	300
Undo 2	/dev/did/rdsk/rlv_psundo2	300
Temp	/dev/did/rdsk/rlv_pstemp	100
Default	/dev/did/rdsk/rlv_psdefault	250

## Task J-1-2: Editing the CREATEDB10.SQL Script

You must edit the createdb10.sql script to:

- have sufficient maxinstances
- have sufficient maxlogfiles
- create different log files for each oracle instance
- create a different thread for each oracle instance

You must configure the createdb10.sql script to ensure that each cluster member has its own Oracle Instance, which has its own log file and its own thread. For example:

*Original createdb.sql*

```

create database    <SID>
  maxdatafiles    1021
  maxinstances    1
  maxlogfiles     8
  maxlogmembers   4
  CHARACTER SET   WE8ISO8859P15
  NATIONAL CHARACTER SET UTF8
0240K MAXSIZE UNLIMITED<SID>/system01.dbf' SIZE 2000M REUSE AUTOEXTEND ON NEXT⇒
1EXTENT MANAGEMENT LOCAL
SYSAux DATAFILE '/u01/oradata/<SID>/sysaux01.dbf' SIZE 120M REUSE AUTOEXTEND ON
NEXT 10240K MAXSIZE UNLIMITED

```

```

DEFAULT TEMPORARY TABLESPACE TEMP TEMPFILE '/u01/oradata/<SID>/temp01.dbf' SIZE
20M REUSE AUTOEXTEND ON NEXT 640K MAXSIZE UNLIMITED
M REUSE AUTOEXTEND ON NEXT 5120K MAXSIZE UNLIMITEDSID>/psundots01.dbf' SIZE 300
LOGFILE GROUP 1 ('/u01/oradata/<SID>/redo01.log') SIZE 100M,
        GROUP 2 ('/u01/oradata/<SID>/redo02.log') SIZE 100M,
        GROUP 3 ('/u01/oradata/<SID>/redo03.log') SIZE 100M;

```

*Createdb.sql after editing:*

```

create database RAC
    maxdatafiles 1021
    maxinstances 2
    maxlogfiles 8
    maxlogmembers 4
    character set WE8ISO8859P15
    datafile
        '/dev/did/rds/rlv_system' size 350M
SYSaux DATAFILE '/dev/did/rds/rlv_sysaux' SIZE 500M
UNDO TABLESPACE PSUNDO1 DATAFILE '/dev/did/rds/rlv_psundo1' SIZE 300M
maxinstances 2
logfile
    '/dev/did/rds/rlv_log1' size 190M,
    '/dev/did/rds/rlv_log2' size 190M;
alter database add logfile thread 2
    '/dev/did/rds/rlv_log3' size 190M,
    '/dev/did/rds/rlv_log4' size 190M;
alter database enable thread 2;

```

## Task J-1-3: Editing the UTLSPACE.SQL Script

Edit the utlspace.sql script to create an additional UNDO tablespace, and to specify the correct raw devices for the tablespaces. Each Oracle instance needs its own UNDO tablespace. The following examples use the names and locations given in the section Creating Raw Devices.

Modify the script to include the following statement for the second UNDO tablespace:

```

CREATE UNDO TABLESPACE PSUNDO2
DATAFILE          '/dev/did/rds/rlv_psundo2'
REUSE AUTOEXTEND ON NEXT 5120K MAXSIZE UNLIMITED
;

```

Modify the script to specify raw devices. This example is for the PSTEMP tablespace:

```

REM * Create a temporary tablespace for database users.
REM *
CREATE TEMPORARY TABLESPACE PSTEMP
TEMPFILE          '/dev/did/rds/rlv_pstemp'          SIZE 300M
EXTENT MANAGEMENT LOCAL UNIFORM SIZE 128K
;

```

## Task J-1-4: Editing the XXDDL Script

Edit the `xxddl.sql` script (xx is a two-letter code for your product line) to reflect the correct tablespace naming and tablespace sizing if you are using raw devices. For example, to specify the size of the PSIMAGE tablespace:

```
CREATE TABLESPACE PSIMAGE DATAFILE '/dev/did/rdsk/rlv_psimimage' SIZE 100M
EXTENT MANAGEMENT LOCAL AUTOALLOCATE
```

In addition, for Oracle 10g RAC, autoextend of tablespaces is not supported if you are using raw devices. Do not uncomment the autoextend SQL statements in the `xxddl.sql` script.

## Task J-1-5: Creating Initialization Files

Each Oracle instance must have its own ORACLE\_SID and its own Oracle initialization file. For example:

*Oracle initialization file for first Oracle Instance where ORACLE\_SID=RAC1:*

```
InitRAC1.ora:

instance_name=RAC1
instance_number=1
thread=1
ifile= initRAC.ora
service_names=RAC
undo_tablespace=PSUNDO1
```

*Oracle initialization file for second Oracle Instance where ORACLE\_SID=RAC2:*

```
InitRAC2.ora:

instance_name=RAC2
instance_number=2
thread=2
ifile= initRAC.ora
service_names=RAC
undo_tablespace=PSUNDO2
```

*Common Oracle initialization file:*

This file contains the following parameters that must be listed in addition to the regular Oracle initialization file parameters.

```
initRAC.ora

compatible = 10.1.0
cluster_database=true
cluster_database_instances=2
undo_management=auto
undo_tablespace=PSUNDO1
control_files=/dev/did/rdsk/rlv_cnt1
open_cursors=300
```

---

**Note.** Any control\_files must be changed to raw devices if there is no cluster file system support.

---

## Task J-2: Configuring Database Security

There must be an entry in ps.psdowner for each Oracle instance. The Owner ID field must be the same for all entries and the DBNAME must be a name that PeopleSoft uses in its connection to the Oracle database. There can be multiple entries in ps.psdowner depending on how tnsnames.ora is set up.

See Configuring the Tnsnames and Listener Files

Make sure the ps.psdowner table contains entries to the multiple DBNAMES and Owner IDs; for example:

DBNAMES	Owner ID
-----	-----
RAC1	RAC1
RAC2	RAC1

To add an entry to the ps.psdowner table, use SQL\*Plus; for example:

```
sqlplus>RAC1/RAC1
Insert into ps.psdowner values ('RAC2','RAC1');
Commit;
```

---

## Task J-3: Configuring the Tnsnames and Listener Files

As a safeguard, the information on database security is defined in two locations. The tnsnames.ora file includes an ADDRESS\_LIST containing an IP address and a unique CONNECT\_DATA (SERVICE\_NAME) for each cluster member. Each corresponding listener.ora file includes this unique SERVICE\_NAME and the INSTANCE\_NAME that is associated with it.

Example of tnsnames.ora:

```
rac =
  (DESCRIPTION =
    (load_balance=on)
    (ADDRESS = (PROTOCOL = TCP) (host = pt-suncluster01.peoplesoft.com) (port
= 1521))
    (ADDRESS = (PROTOCOL = TCP) (host = 192.168.225.80) (port = 1521))
    (CONNECT_DATA =
      (service_name = rac)
    )
  )

rac1 =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP) (host = pt-suncluster01.peoplesoft.com) (port =
1521))
    (ADDRESS = (PROTOCOL = TCP) (host = pt-sun29.peoplesoft.com) (port = 1521))
```

```

(CONNECT_DATA =
  (service_name = rac)
)
)

rac2 =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP) (host = 192.168.225.80) (port = 1521))
    (ADDRESS = (PROTOCOL = TCP) (host = pt-sun30.peoplesoft.com) (port = 1521))
    (CONNECT_DATA =
      (service_name = rac)
    )
  )
)

```

#### Example of listener.ora:

```

SID_LIST_LISTENER_PT-SUN30 =
  (SID_LIST =
    (SID_DESC =
      (SID_NAME = PLSExtProc)
      (ORACLE_HOME = /products/oracle/10.1.0.3-64bit)
      (PROGRAM = extproc)
    )
  )

SID_LIST_LISTENER_PT-SUN29 =
  (SID_LIST =
    (SID_DESC =
      (SID_NAME = PLSExtProc)
      (ORACLE_HOME = /products/oracle/10.1.0.3-64bit)
      (PROGRAM = extproc)
    )
  )

LISTENER_PT-SUN30 =
  (DESCRIPTION_LIST =
    (DESCRIPTION =
      (ADDRESS_LIST =
        (ADDRESS = (PROTOCOL = IPC)(KEY = EXTPROC))
      )
      (ADDRESS_LIST =
        (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.225.80)(PORT = 1521))
      )
      (ADDRESS_LIST =
        (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.225.78)(PORT = 1521))
      )
    )
  )

LISTENER_PT-SUN29 =

```

```

      (DESCRIPTION_LIST =
        (DESCRIPTION =
          (ADDRESS_LIST =
            (ADDRESS = (PROTOCOL = IPC)(KEY = EXTPROC))
          )
          (ADDRESS_LIST =
            (ADDRESS = (PROTOCOL = TCP)(HOST = pt-suncluster01.peoplesoft.com)(PORT
= 1521))
          )
          (ADDRESS_LIST =
            (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.225.77)(PORT = 1521))
          )
        )
      )
    )
  )
)

```

To start the listener, use the following command, where *<CLUSTER\_MEMBER>* is the name of the cluster member in the listener.ora file:

```
lsnrctl start <CLUSTER_MEMBER>
```

For example, to start the listener on the first cluster member in the example above, use the following command:

```
lsnrctl start LISTENER_PT-SUN29
```

---

## Task J-4: Configuring the Application Server

When configuring the application server, follow these guidelines:

- Make sure that the PS\_MACH field in the application server configuration file corresponds to the proper IP address for the cluster member. It may be using the internal connection IP address for the cluster.
- The DBNAME must be one of the values in ps.psdowner.
- Configure additional application servers to point to the additional RAC instance.



# Index

## A

- additional languages 13
- ALTER AUDIT
  - running as part of updating database to latest PeopleTools release 134, 198, 576, 629
  - running during database creation 157, 221
- alter PeopleTools tables
  - as part of updating database to latest PeopleTools release 134, 198, 576, 629
- Application CD
  - installing 91, 99
- application server 5
  - configuring domain processes 240
  - configuring domains, UNIX 242
  - configuring domains, Windows 229
  - creating domains, UNIX 242
  - creating domains, Windows 229
  - designating the application server administrator 54
  - getting started, UNIX 241
  - getting started, Windows 228
  - importing configuration, UNIX 246
  - importing configuration, Windows 232
  - reconfiguring a domain, UNIX 248
  - reconfiguring a domain, Windows 234
  - setting up on UNIX 239
  - setting up on Windows 227
  - specifying domain parameters, UNIX 248
  - specifying domain parameters, Windows 234
  - starting domains, UNIX 242
  - starting domains, Windows 229
- Asian languages
  - configuration issues on UNIX 250
  - configuration issues on Windows 237
- auditing database 155, 219, 597, 650
- authentication
  - setting up on OAS for report repository 659
  - setting up on WebLogic for report repository 664

- setting up on WebSphere for report

- repository 664

- authentication domains, using in console mode 289

- authentication domains, using in GUI mode 255

## B

- backups 19
- base language
  - changing 595, 648
  - choosing 11
- base time zone option 286, 308
- batch server 6
- BEA WebLogic
  - installing on Windows 37
- BPEL Process Manager, installing for XSLT mapper integration 669
- BusinessObjects Enterprise XI
  - changing Report Repository data source 439
  - creating a web server on UNIX or Linux 404
  - creating a web server on Windows 383
  - enabling logging 445
  - installation overview 362
  - installing on UNIX or Linux 399
  - installing on Windows 372
  - license code types 448
  - PeopleSoft permission lists 437
  - PeopleSoft roles 437
  - PeopleSoft users 437
  - Report Repository 439

## C

- catalog views 553, 607
- CBLBLD.BAT 470
- CBLMAKE.BAT 471
- CDs
  - mounting and unmounting for MicroFocus Server Express 75
  - mounting and unmounting for the PeopleSoft installer 80
- Central Management Console (BusinessObjects Enterprise XI) 370

- Change Assistant, *See* PeopleSoft Change Assistant
- character set 13
- CIA, *See* PeopleSoft Change Impact Analyzer
- client connectivity 18
  - testing 19
- client setup 104
- CMC, *See* Central Management Console
- COBOL 15
  - compiling on UNIX 478
  - compiling on Windows 470
  - distributing binaries 473
  - linking 479–480
  - recompiling 480
  - setting up for Remote Call 228, 242
- COBOL compiler
  - installing on UNIX or Linux 65
  - installing on Windows 65
- compiling COBOL
  - on UNIX 478
  - on Windows 470
- configuration
  - planning initial 3
- Configuration Manager
  - Client Setup tab 104
  - editing profiles 103
  - starting 102
  - startup options 102
- connect ID
  - creating 555, 609
- CONNECT.SQL 555, 609
- connection information
  - updating 556, 611
- CREATEDB.SQL 607
- Crystal Reports 9
  - installing 360
- Crystal Reports XI
  - installing 433
  - removing 436

## D

- data field length checking option 286, 308
- Data Mover
  - creating scripts 558, 611
  - running additional scripts 151, 215, 593, 646
  - running scripts 563, 616
  - using for troubleshooting, UNIX 184

- using for troubleshooting, Windows 121
- database
  - auditing 155, 219, 597, 650
  - comparing Oracle and PeopleSoft 8
  - creating 607
  - names 8
  - planning creation of 7
  - server 5
  - updating database name and type 285, 307
  - updating to latest PeopleTools release 124, 188, 566, 619
  - verifying connectivity 229, 242
- Database Configuration Wizard
  - checking log files, UNIX 184
  - checking log files, Windows 121
  - prerequisites, UNIX 164
  - prerequisites, Windows 108
  - running on UNIX 169
  - running on Windows 113
  - troubleshooting, UNIX 184
  - troubleshooting, Windows 121
- database engine
  - installing 16–17
- database roles 554, 609
- database scripts
  - editing 551, 602
  - running 554, 608
- database server
  - overview 5
- DBOWNER.SQL 553, 608
- Dbspaces
  - creating application-specific 554, 608
- dddaudit.sqr 155, 219, 597, 650
- Distribution Agent
  - starting on UNIX 342
  - starting on Windows 316
- documentation
  - assembling installation related 2
  - installing PeopleBooks 499

## E

- E-Delivery 80
- environment variables
  - setting 324
  - setting for application server configuration 241
  - setting for COBOL compilation 476

**F**

- file server 5
- installing the PeopleTools CD 97
- files
  - GNT and INT 473

**G**

- GNT files 473

**H**

- hardware and software requirements 2
- HTTP
  - securing Report Repository for 659
- HTTP proxy server
  - installing for WebSphere 46

**I**

- install workstation
  - prerequisites 101
- instance
  - creating Oracle 604
- INT files 473
- Integration Broker, updating 148, 212, 590, 643
- Integration Gateway URL, configuring for BusinessObjects Enterprise XI 425
- Internet Architecture (PeopleSoft), *See* PeopleSoft Pure Internet Architecture

**L**

- laser printer 7
- liblist, modifying 476
- linking COBOL 479–480
- logical drive
  - creating 96

**M**

- mapping logical drive 96
- message data, cleaning obsolete 126, 190, 568, 621
- Micro Focus Net Express 65
- Micro Focus Server Express 65
- Microsoft Office 16
- Mobile Agent
  - configuring 515
  - finding the installation program 511
  - installing on a laptop 512
  - installing on a PDA 513
  - modifying, repairing, or removing 514

- PDA initialization 514
- troubleshooting 515
- understanding 511

## mounting CDs

- for MicroFocus Server Express 75
- for the PeopleSoft Installer 80

## multi-currency option 286, 308

## Multilanguage CD

- loading 92, 100

## multilingual objects

- updating PeopleTools 130, 194, 572, 625

## multilingual strategy

- planning 10

## multilingual system database

- installing 151, 215, 593, 646

**N**

## Navigation Collection data

- converting 147, 211, 589, 642

## new tablespaces

- migrating records to 138, 202, 580, 633

## NLS\_LANG

- setting in the Windows Registry 557, 606

## NLSPATH environment variable 324

## non-Unicode databases 14

**O**OAS, *See* Oracle Application Server

## Oracle 10g RAC

- configuring database security 676
- configuring the Application Server 678
- configuring the tnsnames.ora and listener.ora files 676
- installing PeopleSoft 671

## Oracle Application Server

- environment variables 24
- installing 25
- installing PeopleSoft Pure Internet Architecture in console mode 290
- installing PeopleSoft Pure Internet Architecture in GUI mode 256
- setting up authentication for report repository 659
- uninstalling 36
- uninstalling PeopleSoft Pure Internet Architecture in console mode 294

- uninstalling PeopleSoft Pure Internet Architecture in GUI mode 266
- using custom port numbers 24
- Oracle database
  - creating 607
- Oracle instance
  - creating 604
- Oracle Net
  - installing on client 18
  - installing on server 17
  - testing connectivity 19
- owner ID
  - for PeopleSoft database 555, 609
  - PeopleSoft, compared with Oracle user ID 8

## P

- Pagelet Wizard data
  - converting 147, 211, 589, 642
- PATH environment variable 324
- PeopleBooks
  - configuring context sensitive help 507
  - enabling F1 help 508
  - implementing a PSOL server 502
  - installation overview 499
  - installing the CD-ROM 499
  - setting up a reverse proxy server 507
- PeopleSoft Change Assistant
  - firewall settings 485
  - installing 484
  - introduction 20
  - setting email options 487
  - setting environment management options 488
  - setting up web services options 487
  - specifying Change Assistant options 486
- PeopleSoft Change Impact Analyzer
  - installing 493
  - introduction 20
- PeopleSoft Database Configuration Wizard, *See* Database Configuration Wizard
- PeopleSoft database owner ID 555, 609
- PeopleSoft Installer
  - running 84
  - running in console mode 88
  - running in GUI mode 86
  - running with single CD 82
  - running without swapping CDs 83

- PeopleSoft integration with BusinessObjects Enterprise XI
  - permission lists, roles, and users 437
- PeopleSoft Pure Internet Architecture
  - installing in console mode on Oracle Application Server 290
  - installing in console mode on WebLogic 294
  - installing in console mode on WebSphere 300
  - installing in GUI mode on Oracle Application Server 256
  - installing in GUI mode on WebSphere 275
  - installing on Oracle Application Server in GUI mode 256
  - installing on WebLogic in GUI mode 266
  - installing on WebSphere in console mode 299
  - installing on WebSphere in GUI mode 274
  - testing the installation, console mode 304
  - testing the installation, GUI mode 282
  - uninstalling from Oracle Application Server in console mode 294
  - uninstalling from Oracle Application Server in GUI mode 266
  - uninstalling on WebSphere in console mode 303
  - uninstalling on WebSphere in GUI mode 281
  - using authentication domains in console mode 289
  - using authentication domains in GUI mode 255
- PeopleSoft servers 78
- PeopleTools CD
  - installing on the file server 97
- PeopleTools database objects
  - deleting obsolete 132, 196, 574, 627
  - updating 128, 192, 570, 623
- PeopleTools Development Environment 4
- PeopleTools Mobile Agent
  - finding the installation program 511
  - understanding 511
- PeopleTools multilingual objects
  - updating 130, 194, 572, 625
- PeopleTools system data

- updating 143, 207, 585, 638
- PeopleTools system database
  - installing multilingual 151, 215, 593, 646
- PeopleTools system tables
  - updating 126, 190, 568, 621
- PeopleTools tables
  - altering 134, 198, 576, 629
- PIA, *See* PeopleSoft Pure Internet Architecture
- Portal objects
  - converting 145, 209, 587, 640
- printer 7
- Process Scheduler server
  - configuring for Word for Windows 334
  - creating on UNIX 350
  - creating on Windows 325
  - overview 6
  - reconfiguring on UNIX 354
  - reconfiguring on Windows 328
  - Report Repository, on UNIX 339
  - Report Repository, on Windows 313
  - setting up distribution settings on UNIX 347
  - setting up distribution settings on Windows 322
  - setting up Process Scheduler Server Agent on UNIX 348
  - setting up Process Scheduler Server Agent on Windows 324
  - setting up security on UNIX 338
  - setting up security on Windows 310
  - starting as Windows service 331
  - verifying status on UNIX 355
  - verifying status on Windows 329
- product modules
  - adding 497
- profile
  - editing default 103
- PS.PSDBOWNER table 553, 608
- PSADMIN
  - and application server domains, UNIX 242
  - and application server domains, Windows 229
  - importing application server domain with, UNIX 246
  - importing application server domain with, Windows 232

- PsCIA, *See* PeopleSoft Change Impact Analyzer
- psconfig.sh
  - running 168
- psolmanager.htm 509
- PSROLES.SQL 554, 609

## Q

- QAS, *See* Query Access Services
- Query Access Services
  - configuring for BusinessObjects Enterprise XI 425
  - overview 368
- query headings
  - converting 146, 210, 588, 641

## R

- recompiling COBOL 480
- records
  - migrating to new tablespaces 138, 202, 580, 633
- Remote Call
  - setting up COBOL for 228, 242
- REN server
  - configuring for UNIX 244
  - configuring for Windows 231
- Report Manager
  - setting up sending and receiving of report folders on UNIX 348
  - setting up sending and receiving of report folders on Windows 323
- report node
  - defining to use FTP on UNIX 345
  - defining to use FTP on Windows 320
  - defining to use HTTP/HTTPS on UNIX 343
  - defining to use HTTP/HTTPS on Windows 317
  - defining to use XCOPY 319
  - updating definition 667
- Report Repository
  - enabling on UNIX 342
  - enabling on Windows 316
  - securing for HTTP 659
  - selecting transfer protocol on UNIX 342
  - selecting transfer protocol on Windows 316
  - setting up single signon on UNIX 341

- setting up single signon on Windows 315
- Report Repository, UNIX 339
- Report Repository, Windows 313
- roles
  - database 554, 609
- RPT Conversion utility 452
- Rules Editor, installing 493

## S

- seed database 17
- servers
  - PeopleSoft types 78
  - setting the SMTP server 487
  - supported combinations 78
- SETSPACE.SQR
  - running 156, 220, 598, 651
- Setup Manager
  - configuring 334
  - converting 146, 210, 588, 641
- single signon
  - for Report Repository access on UNIX 341
  - for Report Repository access on Window 315
- sort order option 286, 308
- SQL tools 552, 605
- SQR 16
  - database auditing 155, 219, 597, 650
  - relinking on HP-UX 654
  - relinking on UNIX 653
  - running 153, 217, 595, 648
- supporting applications 15
- sysaudit.sqr 155, 219, 597, 650

## T

- Tablespaces
  - populate or synchronize with the system catalog 156, 220, 598, 651
- transformation programs, PeopleSoft Application Engine 669
- TrueType fonts
  - installing 251
- TUXDIR environment variable 324
- Tuxedo
  - checking Windows Services 55
  - checklist for installing on UNIX 62
  - designating the owner 63

- installing on UNIX 63
- installing on Windows 55
- prerequisites for installing on UNIX 61
- prerequisites for installing on Windows 52
- removing on UNIX 61
- setting up services 56
- uninstalling from Windows 53
- verifying installation on Windows 58
- verifying server installation on UNIX 64

## U

- Unicode databases
  - choosing when selecting a character set 13
- unmounting CDs
  - for MicroFocus Server Express 75
  - for the PeopleSoft Installer 80
- updates and fixes 14
- updating database 124, 188, 566, 619
- updating PeopleTools
  - database objects 128, 192, 570, 623
  - multilingual objects 130, 194, 572, 625
  - Navigation Collection data 147, 211, 589, 642
  - Pagelet Wizard Data 147, 211, 589, 642
  - Portal objects 145, 209, 587, 640
  - query headings 146, 210, 588, 641
  - Setup Manager 146, 210, 588, 641
  - system data 143, 207, 585, 638
  - system tables 126, 190, 568, 621
- UPG844PORTAL Application Engine program 145, 209, 587, 640
- UPGPT846PP Application Engine program 147, 211, 589, 642
- UPGPT848PP Application Engine program 147, 211, 589, 642
- UPGPTSMDAT Application Engine program 146, 210, 588, 641
- UPGQRYDUPHED Application Engine program 146, 210, 588, 641
- user interface
  - changing 150, 214, 592, 645
- utility tablespaces 553, 607
- UTLSPACE.SQL 553, 607

**V**

VERSION Application Engine  
program 152, 216, 594, 647

**W**

Web Application Deployment tools 517  
installing on OAS in console mode 534  
installing on OAS in GUI mode 518  
installing on WebLogic in console  
mode 536  
installing on WebLogic in GUI  
mode 524  
installing on WebSphere in console  
mode 540  
installing on WebSphere in GUI  
mode 529

web server  
setting up security 659  
supported types 6

WebLogic  
installing on Windows 37  
installing PeopleSoft Pure Internet  
Architecture in console mode 294  
installing PeopleSoft Pure Internet  
Architecture in GUI mode 266  
setting up authentication for report  
repository 664

WebSphere  
HTTP proxy server installation 46  
installing Network Deployment  
manager 48  
installing PeopleSoft Pure Internet  
Architecture in console mode 300  
installing PeopleSoft Pure Internet  
Architecture in GUI mode 275  
installing WebSphere Base with the silent  
method 45  
setting up authentication for report  
repository 664  
troubleshooting the installation 49  
uninstalling PeopleSoft Pure Internet  
Architecture in console mode 303  
uninstalling PeopleSoft Pure Internet  
Architecture in GUI mode 281  
uninstalling the default application 46  
upgrading 48

WebSphere Application Server  
installing 39  
installing base product 42

prerequisites 41  
WebSphere ND 48  
Windows service  
starting Process Scheduler as 331  
Tuxedo 55  
Windows-based clients 4  
Word for Windows  
configuring Process Scheduler for 334  
workstations 4

**X**

XSLT mapper 669

