

Oracle® Beehive

Administrator's Reference Guide

Release 1 (1.3)

E10483-02

August 2008

This book is a reference volume containing specific information on Oracle Beehive templates, command-line utilities, and error codes.

Oracle Beehive Administrator's Reference Guide, Release 1 (1.3)

E10483-02

Copyright © 2008, Oracle. All rights reserved.

Primary Authors: Raymond Gallardo, Andrew Mitchell

Contributing Authors: Sylvia Perez, Jennifer Waywell

Contributors: Matthew Carrier, Jia-der Day, Manon Delilse, Richard Hall, Lenny Karpel, Joe Paradise, Rajesh Parakkal, Dan Rabe, Joshua Stanley

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Contents

1 Oracle Beehive XML File Reference

Audit Templates	1-1
Sample Audit Templates.....	1-2
AuditPolicyInfo	1-2
AuditTrailInfo	1-2
AuditTemplateInfo	1-3
Category Templates	1-3
Sample Category Templates	1-4
CategoryDefinition	1-4
CEN (type).....	1-5
CatTemplate (type)	1-5
AttributeDefinition (type).....	1-5
AttributeTemplate (type)	1-6
Group Templates	1-7
groups	1-8
group	1-8
query	1-9
operator	1-9
predicate	1-10
attribute	1-10
address.....	1-10
property	1-11
members	1-11
operation (type).....	1-11
removeincluded	1-11
removeexcluded	1-11
addresses	1-12
item (child element of addresses)	1-12
properties.....	1-12
item (child element of properties)	1-12
preferenceprofiles.....	1-13
memberships.....	1-13
item.....	1-13
Policy Definitions	1-13
Sample Policy Definitions	1-15
PolicyInfo.....	1-16

attributes.....	1-16
RuleInfo	1-16
ConditionInfo.....	1-17
logical expression (type).....	1-17
boolean expression (type)	1-17
Simple	1-18
ActionInfo.....	1-18
ActionPreferenceInfo	1-18
Workflow Templates	1-18
Sample Workflow Templates	1-20
WorkflowTemplateInfo.....	1-20
attribute	1-21
Attributes for SerialWorkflow	1-21
Attributes for ParallelVoteWorkflow	1-21
Workspace Templates	1-22
Template Variables	1-27
System Defined Template Variable	1-27
User Defined Template Variable	1-27
Expressions	1-28
Sample Workspace Templates	1-29
ace.....	1-29
accessor.....	1-30
address	1-31
type.....	1-31
addressBook.....	1-31
personContact.....	1-32
attributes (body of personalWorkspace)	1-32
attributes (body of teamWorkspace)	1-32
body (personalWorkspaceTemplate)	1-32
body (teamWorkspaceTemplate).....	1-33
calendar	1-34
occurrence	1-34
occurrenceSeries.....	1-34
contentLocation	1-35
entities.....	1-36
environment.....	1-36
label.....	1-36
expression.....	1-36
file	1-37
folder	1-37
versionControlConfiguration.....	1-37
forum.....	1-37
topic.....	1-38
announcement	1-38
messageBody	1-38
group.....	1-38
label	1-39

location.....	1-39
participant	1-39
identity.....	1-39
role.....	1-39
personalWorkspaceTemplate.....	1-40
priority	1-40
Promptable Non-Empty String (type).....	1-40
Promptable Template Time (type).....	1-40
role.....	1-41
grantPrivilege	1-41
sensitivity	1-42
summary.....	1-42
inlineSummary	1-43
teamWorkspaceTemplate	1-43
templateAttributes	1-43
templateVariable	1-44
temporalExpression	1-44
taskList.....	1-44
todo	1-44

2 Oracle Beehive Command-Line Utility

Summary of Commands	2-1
Common Options	2-13
System Object Identifiers.....	2-15
Providing Secure Values	2-15
Tabular Output.....	2-16
Boolean Values.....	2-16
activate_configuration	2-16
add_assigned_role.....	2-17
add_attendant.....	2-17
add_audit_policy	2-18
add_audit_template	2-18
add_audit_trail.....	2-19
add_blocked_device.....	2-19
add_category.....	2-19
add_category_application.....	2-20
add_category_configuration.....	2-20
add_client_application_configuration	2-21
add_client_application_provisioning.....	2-21
add_coexistence_connector.....	2-22
add_conference	2-23
add_conference_template	2-23
add_custom_user_property	2-24
add_device_command	2-25
add_directory_profile	2-25
add_dmz_home_instance.....	2-26
add_event_subscription	2-27

add_external_bpel_pm	2-27
add_external_contact	2-28
add_filesystem_reference	2-31
add_group	2-31
add_local_ace.....	2-32
add_organization	2-32
add_policy.....	2-32
add_policy_schema	2-33
add_policy_template.....	2-33
add_preference_profile	2-33
add_preference_property	2-34
add_preference_set.....	2-35
add_record	2-36
add_resource.....	2-36
add_role_definition	2-38
add_sensitivity	2-38
add_sensitivity_ace	2-39
add_team_workspace.....	2-40
add_trusted_identity.....	2-41
add_urm	2-42
add_user	2-42
add_user_subscription	2-47
add_version_configuration.....	2-47
add_virus_scan_engine	2-48
add_voice_enterprise	2-48
add_voice_facility.....	2-49
add_workflow_schema	2-49
add_workflow_template	2-49
add_workspace_template	2-50
append_value	2-50
clear_proposed_configuration	2-51
clone_midtier.....	2-51
clone_oc4j_instance.....	2-52
clone_preparation.....	2-53
clone_site.....	2-53
delete_assigned_role.....	2-54
delete_attendant	2-55
delete_attendant_prompt.....	2-55
delete_audit_policy	2-56
delete_audit_template	2-56
delete_audit_trail.....	2-56
delete_category	2-57
delete_category_application.....	2-57
delete_category_configuration.....	2-57
delete_client_application.....	2-58
delete_client_application_configuration	2-58
delete_client_application_patchset.....	2-58

delete_client_application_version	2-59
delete_coexistence_connector	2-59
delete_coexistence_profile	2-60
delete_conference	2-60
delete_conference_template	2-61
delete_custom_user_property	2-61
delete_device_profile	2-61
delete_device_type	2-62
delete_directory_profile	2-62
delete_dmz_home_instance	2-63
delete_event_subscription	2-63
delete_external_contact	2-63
delete_filesystem_reference	2-64
delete_group	2-64
delete_local_ace	2-65
delete_organization	2-65
delete_policy	2-66
delete_policy_action	2-66
delete_policy_schema	2-66
delete_policy_template	2-67
delete_preference_profile	2-67
delete_preference_property	2-67
delete_preference_set	2-68
delete_property	2-68
delete_record	2-69
delete_resources	2-69
delete_role_definition	2-69
delete_sensitivity	2-70
delete_sensitivity_ace	2-70
delete_team_workspace	2-71
delete_trusted_identity	2-71
delete_user	2-71
delete_version_configuration	2-72
delete_virus_scan_engine	2-72
delete_voice_enterprise	2-73
delete_voice_facility	2-73
delete_workflow_schema	2-74
delete_workflow_template	2-74
delete_workspace_template	2-74
download_device_logs	2-75
download_language_pack	2-75
download_ldap_group_data	2-76
download_ldap_user_data	2-77
download_syncml_messages	2-77
download_syncml_sessions	2-78
download_workspace_template_schema	2-78
export_audit_trail	2-79

export_client_application_configuration.....	2-79
export_errorcodes	2-79
export_filesystem_logs.....	2-81
export_icalendar	2-84
export_logs.....	2-85
export_policy.....	2-87
export_workflow_template	2-87
import_documents	2-88
import_icalendar.....	2-89
import_timezones.....	2-90
list_access_control_fields.....	2-90
list_access_types	2-91
list_assigned_roles	2-91
list_attendant_aaml.....	2-91
list_attendant_prompts	2-92
list_attendants.....	2-92
list_audit_events.....	2-92
list_audit_policies	2-93
list_audit_templates.....	2-93
list_audit_trails	2-93
list_bootstrap_configuration.....	2-94
list_calendars.....	2-94
list_categories.....	2-95
list_category.....	2-95
list_category_configuration.....	2-96
list_client_application_configuration	2-96
list_client_application_modules	2-97
list_client_application_patchsets	2-97
list_client_application_versions.....	2-97
list_client_applications	2-98
list_coexistence_connectors.....	2-98
list_coexistence_profiles	2-98
list_coexistence_status.....	2-99
list_command_metadata	2-99
list_commands	2-100
list_components.....	2-101
list_conference_templates.....	2-102
list_conferences.....	2-102
list_configuration_versions.....	2-103
list_connection_pools	2-103
list_custom_user_properties.....	2-103
list_device_commands.....	2-104
list_device_logs.....	2-104
list_device_profiles	2-104
list_device_types.....	2-105
list_devices.....	2-105
list_directory_profiles	2-105

list_enterprises	2-106
list_errorcode_catalog	2-106
list_events	2-107
list_external_contacts	2-107
list_file_plan	2-110
list_filesystem_references	2-111
list_groups	2-111
list_language_pack	2-113
list_local_acl	2-113
list_max_address_count	2-114
list_my_conferences	2-114
list_organizations	2-114
list_policies	2-115
list_policy_actions	2-116
list_policy_schemas	2-116
list_policy_templates	2-116
list_ports	2-117
list_preference_profiles	2-118
list_preference_properties	2-118
list_preference_sets	2-119
list_privileges	2-119
list_properties	2-119
list_property_metadata	2-120
list_resources	2-120
list_role_definitions	2-121
list_sensitivities	2-121
list_sensitivity_acl	2-122
list_statistics	2-122
list_supported_entity_types	2-122
list_tasklists	2-123
list_timezones	2-123
list_trusted_identity	2-124
list_users	2-124
list_version_configuration	2-128
list_workflow_schemas	2-128
list_workflow_templates	2-129
list_workflows	2-129
list_workspace_templates	2-130
list_workspaces	2-130
modify_access_control_fields	2-131
modify_assigned_role	2-132
modify_attendant	2-132
modify_audit_policy	2-133
modify_audit_trail	2-134
modify_beectl	2-134
modify_bootstrap_configuration	2-134
modify_category	2-135

modify_category_configuration	2-136
modify_change_number	2-136
modify_coexistence_connector	2-136
modify_coexistence_profile	2-137
modify_connection_pool	2-138
modify_database.....	2-139
modify_directory_profile.....	2-140
modify_email_port.....	2-141
modify_email_queue	2-141
modify_enterprise	2-141
modify_external_contact	2-143
modify_group.....	2-147
modify_hostname.....	2-147
modify_ip_phone_password_seed	2-148
modify_local_ace	2-149
modify_local_configuration_files	2-149
modify_max_address_count.....	2-150
modify_notification_template	2-150
modify_organization	2-151
modify_personal_workspace	2-152
modify_policy	2-153
modify_policy_schema.....	2-153
modify_policy_template	2-154
modify_port.....	2-154
modify_preference_set.....	2-156
modify_property	2-156
modify_resource_classifications	2-158
modify_resources	2-158
modify_role_definition	2-160
modify_search	2-161
modify_search_engine.....	2-162
modify_secure_property	2-162
modify_sensitivity	2-163
modify_sensitivity_ace.....	2-163
modify_team_workspace	2-164
modify_timezones	2-165
modify_trusted_identity	2-166
modify_user.....	2-167
modify_user_subscription	2-172
modify_version_configuration	2-172
modify_virus_scan_policy	2-173
modify_workspace_template	2-173
obfuscate	2-174
restart	2-174
start.....	2-174
status	2-175
stop	2-176

upload_attendant_prompt	2-176
upload_client_application	2-177
upload_device_profiles	2-178
upload_language_pack.....	2-178
validate_audit_trail	2-180
validate_configuration	2-180
validate_directory_entry	2-181
validate_virus_scan_engine_connectivity	2-182
version	2-182

3 Oracle Beehive Error Codes

Access Control Error Codes	3-1
Address Book Error Codes	3-2
Audit Error Codes	3-19
Authentication Service Error Codes	3-20
Bom Object Distinguished Naming Error Codes	3-21
Client Management Service Error Codes	3-22
Device Management Error Codes	3-23
Diagnosability Error Codes	3-29
Discussions Error Codes	3-30
Email Service Error Codes	3-30
Foundation Services Error Codes	3-33
Instant Messaging Service Error Codes	3-33
Message Delivery Service Error Codes	3-35
Mobile DM Server Error Codes	3-36
Mobile Data Sync Server Error Codes	3-37
Mobile Mail Server Error Codes	3-38
Mobile Push Server Error Codes	3-39
Notification Service Error Codes	3-39
Policy Management Error Codes	3-41
Presence Service Error Codes	3-43
RM Service Error Codes	3-44
Search Error Codes	3-44
Subscription Service Error Codes	3-44
System Management Error Codes	3-46
Time Management And Coexistence With Exchange Error Codes	3-46
User Directory Services Error Codes	3-47
Virus Scanner Error Codes	3-67
Web Conferencing Streaming Media Error Codes	3-70
Web Conferencing Transcoding Error Codes	3-71
Web Conferencing Error Codes	3-72
Workflow Service Error Codes	3-73
Workspaces Error Codes	3-74
Workspaces Templates Error Codes	3-80
XMPP Protocol Service Error Codes	3-82

List of Tables

1-1	AuditPolicyInfo Elements.....	1-2
1-2	AuditTrailInfo Elements	1-2
1-3	AuditTemplateInfo Elements	1-3
Category Template Example 3		
1-4	Elements of CategoryDefinition	1-4
1-5	Elements of CEN (type).....	1-5
1-6	Elements of CatTemplate (type)	1-5
1-7	Elements of AttributeDefinition (type).....	1-5
1-8	Elements of AttributeTemplate (type)	1-6
Static Group Creation With Users 7		
1-9	Elements of groups	1-8
1-10	Attributes of groups	1-8
1-11	Elements of group	1-8
1-12	Attributes of group	1-9
1-13	Elements of query	1-9
1-14	Elements of operator	1-9
1-15	Attributes of operator.....	1-9
1-16	Elements of predicate	1-10
1-17	Elements of attribute	1-10
1-18	Elements of address.....	1-10
1-19	Elements of property	1-11
1-20	Elements of members	1-11
1-21	Elements of operation (type).....	1-11
1-22	Attributes of operation (type)	1-11
1-23	Elements of removeincluded.....	1-11
1-24	Elements of removeexcluded	1-11
1-25	Elements of addresses	1-12
1-26	Elements of item (child element of addresses)	1-12
1-27	Elements of properties.....	1-12
1-28	Elements of item (child element of properties)	1-12
1-29	Elements of preferenceprofiles.....	1-13
1-30	Elements of memberships.....	1-13
1-31	Elements of item.....	1-13
Password Policy 13		
1-32	Elements of PolicyInfo.....	1-16
1-33	Elements of attributes.....	1-16
1-34	Elements of RuleInfo	1-16
1-35	Attributes of RuleInfo.....	1-17
1-36	Elements of ConditionInfo.....	1-17
1-37	Elements of logical expression (type).....	1-17
1-38	Elements of boolean expression (type)	1-18
1-39	Elements of Simple	1-18
1-40	Elements of ActionInfo.....	1-18
1-41	Elements of ActionPreferenceInfo	1-18
Sample Workflow Template 19		
1-42	Elements of WorkflowTemplateInfo.....	1-20
1-43	Elements of attribute	1-21
Basic Team Workspace Template 22		
Basic Personal Workspace Template 24		
1-44	Elements of ace	1-30
1-45	Elements of accessor	1-30
1-46	Attributes of accessor	1-30

1-47	Elements of address	1-31
1-48	Elements of addressBook	1-31
1-49	Elements of personContact	1-32
1-50	Elements of attributes (body of personalWorkspace)	1-32
1-51	Elements of attributes (body of teamWorkspace)	1-32
1-52	Elements of body (personalWorkspaceTemplate)	1-32
1-53	Elements of body (teamWorkspaceTemplate)	1-33
1-54	Elements of calendar	1-34
1-55	Elements of occurrence	1-34
1-56	Elements of occurrenceSeries	1-35
1-57	Elements of contentLocation	1-35
1-58	Elements of entities	1-36
1-59	Elements of environment	1-36
1-60	Elements of label	1-36
1-61	Elements of expression	1-36
1-62	Elements of file	1-37
1-63	Elements of folder	1-37
1-64	Elements of versionControlConfiguration	1-37
1-65	Elements of forum	1-37
1-66	Elements of topic	1-38
1-67	Elements of announcement	1-38
1-68	Elements of messageBody	1-38
1-69	Elements of group	1-38
1-70	Elements of label	1-39
1-71	Elements of location	1-39
1-72	Elements of participant	1-39
1-73	Elements of identity	1-39
1-74	Attributes of identity	1-39
1-75	Elements of role	1-39
1-76	Elements of personalWorkspaceTemplate	1-40
1-77	Elements of Promptable Non-Empty String (type)	1-40
1-78	Elements of Promptable Template Time (type)	1-40
1-79	Attributes of Promptable Template Time (type)	1-40
1-80	Elements of role	1-41
1-81	Elements of sensitivity	1-42
1-82	Elements of summary	1-42
1-83	Elements of inlineSummary	1-43
1-84	Elements of teamWorkspaceTemplate	1-43
1-85	Elements of templateAttributes	1-43
1-86	Elements of templateVariable	1-44
1-87	Elements of templateVariable	1-44
1-88	Elements of taskList	1-44
1-89	Elements of todo	1-45
2-1	Category: access control	2-2
2-2	Category: audit	2-2
2-3	Category: client application	2-3
2-4	Category: cloning	2-4
2-5	Category: coexistence	2-4
2-6	Category: configuration	2-4
2-7	Category: contents	2-6
2-8	Category: devices	2-6
2-9	Category: language packs	2-7
2-10	Category: messaging	2-7
2-11	Category: organizations	2-7
2-12	Category: policies	2-7

2-13	Category: process control	2-8
2-14	Category: real time.....	2-8
2-15	Category: records	2-8
2-16	Category: resources	2-8
2-17	Category: security	2-9
2-18	Category: subscription	2-9
2-19	Category: templates	2-9
2-20	Category: time management	2-9
2-21	Category: time zones	2-9
2-22	Category: users.....	2-10
2-23	Category: utilities	2-11
2-24	Category: workflows	2-12
2-25	Category: workspace	2-12
3-1	Access Control	3-1
3-2	Address Book.....	3-4
3-3	Audit	3-20
3-4	Authentication Service	3-20
3-5	Bom Object Distinguished Naming.....	3-22
3-6	Client Management Service.....	3-22
3-7	Device Management	3-23
3-8	Diagnosability.....	3-30
3-9	Discussions.....	3-30
3-10	Email Service	3-31
3-11	Foundation Services	3-33
3-12	Instant Messaging Service	3-33
3-13	Message Delivery Service	3-35
3-14	Mobile DM Server.....	3-36
3-15	Mobile Data Sync Server	3-37
3-16	Mobile Mail Server.....	3-38
3-17	Mobile Push Server.....	3-39
3-18	Notification Service.....	3-40
3-19	Policy Management	3-41
3-20	Presence Service	3-43
3-21	RM Service	3-44
3-22	Search.....	3-44
3-23	Subscription Service	3-45
3-24	System Management	3-46
3-25	Time Management And Coexistence With Exchange	3-47
3-26	User Directory Services.....	3-48
3-27	Virus Scanner.....	3-68
3-28	Web Conferencing Streaming Media	3-71
3-29	Web Conferencing Transcoding	3-72
3-30	Web Conferencing	3-72
3-31	Workflow Service.....	3-73
3-32	Workspaces	3-75
3-33	Workspaces Templates.....	3-80
3-34	XMPP Protocol Service.....	3-82

Preface

The *Oracle Beehive Administrator's Reference Guide* describes administration tasks associated with Oracle Beehive.

Audience

The *Oracle Beehive Administrator's Reference Guide* is directed at any administrator whose task is the installation, deployment, configuration, administration, and maintenance of Oracle Beehive.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, 7 days a week. For TTY support, call 800.446.2398. Outside the United States, call +1.407.458.2479.

Related Documents

For more information, see the following documents in the Oracle Beehive Release 1.0 documentation set:

- *Oracle Beehive Administrator's Guide*
- *Oracle Beehive Application Developer's Guide*
- *Oracle Beehive Concepts*
- *Oracle Beehive Deployment Guide*
- *Oracle Beehive Installation Guide for Linux*
- *Oracle Beehive Installation Guide for Microsoft Windows*
- *Oracle Beehive Installation Guide for Solaris Operating System (SPARC 64-Bit)*

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Oracle Beehive XML File Reference

This module describes the structure of the following XML files:

- [Audit Templates](#)
- [Category Templates](#)
- [Group Templates](#)
- [Policy Definitions](#)
- [Workflow Templates](#)
- [Workspace Templates](#)

Note: The tables in this module describe all the permitted elements for each XML element. The **Min.** column is the minimum number of elements required. The **Max.** column is the maximum number of elements allowed.

Audit Templates

An audit policy is a definition of rules and actions that determine which events should be recorded in the auditing logs, and the context (user or content) in which you want to do so.

To create an audit policy, you need an audit policy template and an audit policy definition.

An audit policy template is an XML file that has [AuditTemplateInfo](#) as its root element. It specifies which auditable events should be recorded in the auditing logs. To activate an audit policy template, you associate it with an audit policy definition.

An audit policy definition is an XML file that has [AuditPolicyInfo](#) as its root element. It specifies which audit policy template to activate, and which level of scope (user, organization, or enterprise) or level of the content hierarchy (such as an individual entity, folder, or workspace) to apply the audit policy template.

As a result, the audit service will record the events specified in the audit policy template in the auditing logs in the scope you specified in the audit policy definition.

You may also create an audit trail. An audit trail is a collection of audit records that have common characteristics such as the user or group who performed or triggered the event, the date and time that the event occurred, and the type of event. You create an audit trail with an audit trail template. This is an XML file that has [AuditTrailInfo](#) as its root element. It specifies which characteristics each audit record in the audit trail must have.

Sample Audit Templates

The directory `<Oracle home>/beehive/audit` contains the following sample audit templates:

- `policy_ex.xml`: Sample audit policy definition
- `template_ex.xml`: Sample audit policy template
- `trail_ex.xml`: Sample audit trail template

The `policy` directory also contains the file `audit.xsd` that defines the structure of audit policy definitions, audit policy templates, and audit trail templates.

AuditPolicyInfo

Root element of audit policy definitions.

Table 1–1 AuditPolicyInfo Elements

Element Name	Min.	Max.	Description
createdOn	1	1	DateTime
name	1	1	String, name of the audit policy
description	1	1	String, description of the audit policy
template	1	1	String, audit template's identifier. It can either be the collabID or the template's name.
container	0	1	String, identifier of the container or audit scope. Default value is the identifier of the enterprise.
actor	0	unbounded	<p>Complex type that contains two attributes:</p> <ul style="list-style-type: none"> ■ <code>add</code>: Boolean, if false, and the XML template is used to update an existing audit policy, then this actor/group will be removed from the filter list. ■ <code>id</code>: String <p>List of audit filter identifiers. Each identifier can either be the organization user's identifier or the group's identifier.</p> <p>Default value is for all users if this element is not specified or empty.</p>

AuditTrailInfo

Root element of audit trail templates.

Table 1–2 AuditTrailInfo Elements

Element Name	Min.	Max.	Description
createdOn	1	1	DateTime
name	1	1	String, name of the audit trail
description	1	1	String, description of the audit trail
actor	0	unbounded	String, list of identifiers of the users to be used as a predicate when searching for audit records. Default is to use all users

Table 1–2 (Cont.) AuditTrailInfo Elements

Element Name	Min.	Max.	Description
entity	0	unbounded	String, list of identifiers of the entities that generated the audit records
startTime	0	1	DateTime, audit record start time
endTime	0	1	DateTime, audit record end time
eventType	1	1	String
serviceName	1	1	String
userName	1	1	String
activity	1	1	String
predicate	1	1	String
limit	1	1	Unsigned integer

AuditTemplateInfo

Root element of audit policy templates.

Table 1–3 AuditTemplateInfo Elements

Element Name	Min.	Max.	Description
createdOn	1	1	DateTime
name	1	1	String
description	1	1	String
event	1	unbounded	String

Category Templates

With category templates, you may perform the following tasks:

- Create categories with the `beectl add_category` command
- Delete categories with the `beectl delete_category` command
- Apply them to objects in a workspace with the `beectl add_category_application` command
- Remove them from objects in a workspace with the `beectl delete_category_application` command

The following example creates a subcategory named `My subcategory` that has two attributes.

Example 1–1 Category Template Example

```
<CategoryDefinition xmlns="http://xmlns.oracle.com/beehive/category">
  <name>My subcategory</name>
  <description>My subcategory description</description>
  <abstract>F</abstract>
  <parentCEN>
    <enterpriseId>521D</enterpriseId>
    <siteId>7D48</siteId>
    <objectType>catg</objectType>
    <eid>395E4535BD17BB82E040578CB50964750000000007F3</eid>
  </parentCEN>
```

```
<attributes>
  <attribute>
    <name>First attribute</name>
    <description>Description of first attribute</description>
    <propertyType>String</propertyType>
    <searchable>T</searchable>
    <defaultValue>Hello</defaultValue>
  </attribute>
  <attribute>
    <name>Second attribute</name>
    <description>Description of second attribute</description>
    <propertyType>String</propertyType>
    <searchable>T</searchable>
    <defaultValue>World!</defaultValue>
  </attribute>
</attributes>
</CategoryDefinition>
```

Sample Category Templates

The directory `<Oracle home>/beehive/templates/workspaces` contains the following sample category templates:

- `add_category_template1.xml`
- `add_category_template2.xml`
- `add_subcategory_template.xml`

The `workspaces` directory also contains the file `category.xsd` that defines the structure of category templates.

CategoryDefinition

Root element of category templates.

Table 1–4 Elements of CategoryDefinition

Element Name	Min.	Max.	Description
categoryCEN	0	1	CEN (type)
name	1	1	String
description	0	1	String
ownerCEN	0	1	CEN (type)
parentCEN	0	1	CEN (type)
subcategoryCEN	0	unbounded	CEN (type)
visibility	0	1	Either a value of V (the category is visible) or N (the category is not visible).
abstract	0	1	Boolean, either a value of T (true) or F (false)
creatorCEN	0	1	CEN (type)
modifiedByCEN	0	1	CEN (type)
defaultTemplate	0	1	CatTemplate (type)
attributes	0	1	Contains zero to any amount of elements named <code>attribute</code> of type AttributeDefinition (type)

Table 1–4 (Cont.) Elements of CategoryDefinition

Element Name	Min.	Max.	Description
deletedAttributes	0	1	Contains zero to any amount of elements named <code>cens</code> of type CEN (type) .

CEN (type)

Represents the collaboration entity name, which uniquely identifies an entity in the system.

Table 1–5 Elements of CEN (type)

Element Name	Min.	Max.	Description
enterpriseId	0	1	String
siteId	0	1	String
objectType	0	1	String
eid	0	1	String

CatTemplate (type)

Table 1–6 Elements of CatTemplate (type)

Element Name	Min.	Max.	Description
categoryTemplateCEN	0	1	CEN (type)
categoryCEN	1	1	CEN (type)
copyOnVersion	0	1	Boolean, either a value of T (true) or F (false)
mandatory	0	1	Boolean, either a value of T (true) or F (false)
finalInd	0	1	Boolean, either a value of T (true) or F (false)
isMissing	0	1	Boolean, either a value of T (true) or F (false)
attributeTemplates	0	1	Contains zero to any number of elements named <code>attributeTemplate</code> of type AttributeTemplate (type)
deletedAttrTemplates	0	1	Contains zero to any amount of elements named <code>cens</code> of type CEN (type) .

AttributeDefinition (type)

Table 1–7 Elements of AttributeDefinition (type)

Element Name	Min.	Max.	Description
attributeDefCEN	0	1	CEN (type)
name	1	1	String
description	0	1	String

Table 1–7 (Cont.) Elements of AttributeDefinition (type)

Element Name	Min.	Max.	Description
propertyType	1	1	String, one of INTEGER, STRING, DATE, CHAR, BOOLEAN, FLOAT, DOUBLE, LONG, BYTE, TIME, RAW, or DATETIME
searchable	0	1	Boolean, either a value of T (true) or F (false)
minValue	0	1	String
minValueInc	0	1	Boolean, either a value of T (true) or F (false)
maxValue	0	1	String
maxValueInc	0	1	Boolean, either a value of T (true) or F (false)
allowedValues	0	1	Contains zero to any number of elements named allowedVal of string type.
defaultValue	0	1	String

AttributeTemplate (type)

Table 1–8 Elements of AttributeTemplate (type)

Element Name	Min.	Max.	Description
attributeTempCEN	0	1	CEN (type)
attributeDef	1	1	AttributeDefinition (type)
mandatory	0	1	Boolean, either a value of T (true) or F (false)
prompted	1	1	Boolean, either a value of T (true) or F (false)
finalized	0	1	Boolean, either a value of T (true) or F (false)
forceDefault	0	1	Boolean, either a value of T (true) or F (false)
minValue	0	1	String
minValueInc	0	1	Boolean, either a value of T (true) or F (false)
maxValue	0	1	String
maxValueInc	0	1	Boolean, either a value of T (true) or F (false)
allowedValues	0	1	Contains zero to any number of elements named allowedVal of string type.
defaultValue			String

Group Templates

Use group templates to create or modify groups.

The following example creates a dynamic group called `all_extended_enterprise` that consists of external users that belong to the enterprise defined by the `cen` element.

The following example creates a static group with a set of explicitly-identified users:

Example 1–2 Static Group Creation With Users

```
<?xml version="1.0" encoding="utf-8"?>
<groups>
  <group type="grup">
    <name>beehive_test_group</name>
    <description>My first static group</description>
    <scope>
      <cen>2B1C:6844:enpr:31FF590FA21BD45EE040578CC60514DF0000000001A3</cen>
    </scope>
    <guid/>
    <query/>
    <members>
      <add>
        <actor>
          <item>
            <cen>2B1C:6844:user:0100E3E88D0A49CAA85C6B54EC8CD772000000000007</cen>
          </item>
          <item>
            <cen>2B1C:6844:user:0100E3E88D0A49CAA85C6B54EC8CD772000000000001C</cen>
          </item>
        </actor>
        <subgroup>
          <item>
            <cen>2B1C:6844:grup:0100E3E88D0A49CAA85C6B54EC8CD7720000000000041</cen>
          </item>
        </subgroup>
        <principal/>
      </add>
    </members>
    <addresses>
      <add>
        <item>
          <address>mailto:bob_smith@mycompany.com</address>
          <addresstype>NONE</addresstype>
        </item>
      </add>
      <remove>
        <item>
          <address>authid:bob_smith</address>
          <addresstype>NONE</addresstype>
        </item>
      </remove>
      <defaultaddressbytype>
        <item>
          <address>authid:sblack</address>
          <addresstype>NONE</addresstype>
        </item>
      </defaultaddressbytype>
      <defaultaddressbyscheme>
        <item>
          <address>authid:rajpal.goyal</address>
```

```
        <addresstype>NONE</addresstype>
      </item>
    </defaultaddressbyscheme>
    <primaryaddress>
      <item>
        <address>authid:example</address>
        <addresstype>NONE</addresstype>
      </item>
    </primaryaddress>
  </addresses>
  <memberships>
    <add>
      <item>
        <cen>2B1C:6844:orgn:31FF590FA21BD45EE040578CC60514DF0000000001AA</cen>
      </item>
    </add>
  </memberships>
  <properties>
    <add>
      <item>
        <name>IS_AUTO_CONFIRM_ON</name>
        <value>true</value>
        <description>xxx</description>
      </item>
    </add>
    <remove>
      <item>
        <name>xxxx</name>
      </item>
    </remove>
  </properties>
</group>
</groups>
```

groups

Table 1–9 Elements of groups

Element Name	Min.	Max.	Description
group	1	unbounded	

Table 1–10 Attributes of groups

Attribute Name	Description
directoryid	String

group

Table 1–11 Elements of group

Element Name	Min.	Max.	Description
name	0	1	String
description	0	1	String

Table 1–11 (Cont.) Elements of group

Element Name	Min.	Max.	Description
scope	0	1	Contains zero to any number of cen elements. The cen element contains a collabID (no other child elements).
ismembershipgroup	0	1	String
guid	0	1	String
query	0	1	
members	0	1	
addresses	0	1	
properties	0	1	
preferenceprofiles	0	1	
memberships	0	1	

Table 1–12 Attributes of group

Attribute Name	Description
cen	String, collabID of the group, This is required if you are modifying the group.
type	Required attribute, enumerated type, one of the following: <ul style="list-style-type: none"> ▪ grup ▪ dgrp

query

Table 1–13 Elements of query

Element Name	Min.	Max.	Description
operator	0	1	

operator

Table 1–14 Elements of operator

Element Name	Min.	Max.	Description
operator	0	1	
operator	0	1	
predicate	0	1	
predicate	0	1	

Table 1–15 Attributes of operator

Attribute Name	Description
type	Required attribute, enumerated value, one of NONE, AND, or OR

predicate

Table 1–16 *Elements of predicate*

Element Name	Min.	Max.	Description
attribute	1	1	
address	1	1	
property	1	1	

attribute

Table 1–17 *Elements of attribute*

Element Name	Min.	Max.	Description
name	1	1	Enumerated value, one of the following: <ul style="list-style-type: none"> ▪ BUSINESS_1 ▪ BUSINESS_2 ▪ BUSINESS_3 ▪ BUSINESS_4 ▪ BUSINESS_5 ▪ OTHER_1 ▪ OTHER_2 ▪ OTHER_3 ▪ OTHER_4 ▪ OTHER_5 ▪ PERSONAL_1 ▪ PERSONAL_2 ▪ PERSONAL_3 ▪ PERSONAL_4 ▪ PERSONAL_5
value	1	1	String

address

Table 1–18 *Elements of address*

Element Name	Min.	Max.	Description
uri	1	1	anyURI
type	1	1	Enumerated value, one of the following: <ul style="list-style-type: none"> ▪ ASSISTANT ▪ BUSINESS ▪ NONE ▪ PERSONAL ▪ SPOUSE

property

Table 1–19 Elements of property

Element Name	Min.	Max.	Description
name	1	1	
value	1	1	attribute predicate value (type)

members

Table 1–20 Elements of members

Element Name	Min.	Max.	Description
add	0	1	operation (type)
remove	0	1	operation (type)
removeincluded	0	1	
removeexcluded	0	1	

operation (type)

Table 1–21 Elements of operation (type)

Element Name	Min.	Max.	Description
actor	0	1	Contains zero to any number of item elements
agent	0	1	Contains zero to any number of item elements
subgroup	0	1	Contains zero to any number of item elements
principal	0	1	Contains zero to any number of item elements

Table 1–22 Attributes of operation (type)

Attribute Name	Description
type	Enumerated type, either NONE, AND, or OR.

removeincluded

Table 1–23 Elements of removeincluded

Element Name	Min.	Max.	Description
actor	0	1	Contains zero to any number of item elements
agent	0	1	Contains zero to any number of item elements
subgroup	0	1	Contains zero to any number of item elements
principal	0	1	Contains zero to any number of item elements

removeexcluded

Table 1–24 Elements of removeexcluded

Element Name	Min.	Max.	Description
actor	0	1	Contains zero to any number of item elements

addresses

Table 1–25 Elements of addresses

Element Name	Min.	Max.	Description
add	0	1	Contains zero to any number of item (child element of addresses) elements
remove	0	1	Contains zero to any number of item (child element of addresses) elements
defaultaddressbytype	0	1	Contains zero to any number of item (child element of addresses) elements
defaultaddressbyscheme	0	1	Contains zero to any number of item (child element of addresses) elements
primaryaddress	0	1	Contains zero to any number of item (child element of addresses) elements

item (child element of addresses)

Table 1–26 Elements of item (child element of addresses)

Element Name	Min.	Max.	Description
address	0	1	anyURI
addressType	0	1	Enumerated value, one of the following: <ul style="list-style-type: none"> ■ ASSISTANT ■ BUSINESS ■ NONE ■ PERSONAL ■ SPOUSE

properties

Table 1–27 Elements of properties

Element Name	Min.	Max.	Description
add	0	1	Contains zero to any number of item (child element of properties) elements
remove	0	1	Contains zero to any number of item (child element of properties) elements

item (child element of properties)

Table 1–28 Elements of item (child element of properties)

Element Name	Min.	Max.	Description
name	0	1	String
value	0	1	String
description	0	1	String

preferenceprofiles

Table 1–29 Elements of preferenceprofiles

Element Name	Min.	Max.	Description
add	0	1	Contains zero to any number of item elements
remove	0	1	Contains zero to any number of item elements
active	0	1	Contains zero to any number of item elements

memberships

Table 1–30 Elements of memberships

Element Name	Min.	Max.	Description
add	0	1	Contains zero to any number of item elements
remove	0	1	Contains zero to any number of item elements

item

Table 1–31 Elements of item

Element Name	Min.	Max.	Description
cen	0	1	String

Policy Definitions

A policy definition defines a set of rules containing conditions and an action to perform if those conditions are satisfied.

The following is a policy definition that validates user passwords. It checks if the user's password matches one of the following criteria:

- Less than 8 characters long
- Greater than 128 characters long
- Contains the user name as a substring
- Does not contain both upper and lower case characters
- Matches a password previously used by the user

If any of these criteria are true, then the password is rejected.

Example 1–3 Password Policy

```
<?xml version = '1.0' encoding = 'UTF-8'?>
<PolicyInfo isExtensible="true">
  <policy>plcy=PasswordPolicy,enpr=Acme</policy>
  <scope>enpr=Acme</scope>
  <template></template>
  <name>PasswordPolicy</name>
  <description>Password policy desc</description>
  <RuleInfos>
    <RuleInfo priority="1">
      <name>Password Auth PLSQL Rule</name>
      <description>Password Auth rule description</description>
      <eventTypeName>ON_AUTH_USER_PASSWD_MODIFICATION</eventTypeName>
```

```
<ruleId>
  2ACE:6047:rule:3AC0E3FA73872328E040578C939A44FF0000000F4496
</ruleId>
<toRemove>>false</toRemove>
<templateRuleId/>
<ConditionInfo>
  <DisjunctionInfo>
    <LeftBooleanExpression>
      <DisjunctionInfo>
        <LeftBooleanExpression>
          <DisjunctionInfo>
            <LeftBooleanExpression>
              <DisjunctionInfo>
                <LeftBooleanExpression>
                  <Simple>
                    <!-- This expression checks if the user's password
                        is less than 8 characters long -->
                    <leftSide>
                      <!-- Returns the length of the string -->
                      LENGTH(
                        CUSTOM_ATTRIBUTES.USER_PASSWD)
                    </leftSide>
                    <operator>&lt;</operator>
                    <rightSide>8</rightSide>
                  </Simple>
                </LeftBooleanExpression>
              <RightBooleanExpression>
                <Simple>
                  <!-- This expression checks if the user's password
                      is greater than 128 characters long -->
                  <leftSide>
                    LENGTH(
                      CUSTOM_ATTRIBUTES.USER_PASSWD)
                  </leftSide>
                  <operator>></operator>
                  <rightSide>128</rightSide>
                </Simple>
              </RightBooleanExpression>
            </DisjunctionInfo>
          </LeftBooleanExpression>
        <RightBooleanExpression>
          <Simple>
            <!-- This expression checks if the user's password
                contains both alphabetic and numeric
                characters -->
            <leftSide>
              AUTH_POLICY_FUNC_PKG.
              VERIFY_ALPHANUM(
                CUSTOM_ATTRIBUTES.USER_PASSWD)
            </leftSide>
            <operator>=</operator>
            <rightSide>0</rightSide>
          </Simple>
        </RightBooleanExpression>
      </DisjunctionInfo>
    </LeftBooleanExpression>
    <RightBooleanExpression>
      <Simple>
```



```

        <!-- This expression checks if the user name is contained
             in the password -->
        <leftSide>
            AUTH_POLICY_FUNC_PKG.CONTAINS_USERNAME(
                CUSTOM_ATTRIBUTES.USER_NAME,
                CUSTOM_ATTRIBUTES.USER_PASSWD)
        </leftSide>
        <operator>=</operator>
        <rightSide>0</rightSide>
    </Simple>
</RightBooleanExpression>
</DisjunctionInfo>
</LeftBooleanExpression>
<RightBooleanExpression>
    <Simple>
        <!-- This expression checks if the password contains both
             upper and lower case characters -->
        <leftSide>
            AUTH_POLICY_FUNC_PKG.VERIFY_CASE(
                CUSTOM_ATTRIBUTES.USER_PASSWD)
        </leftSide>
        <operator>=</operator>
        <rightSide>0</rightSide>
    </Simple>
</RightBooleanExpression>
</DisjunctionInfo>
</LeftBooleanExpression>
<RightBooleanExpression>
    <Simple>
        <leftSide>
            <!-- This expression checks if the password matches a password
                 previously used by the user -->
            AUTH_POLICY_FUNC_PKG.IN_HISTORY(
                CUSTOM_ATTRIBUTES.USER_NAME,
                CUSTOM_ATTRIBUTES.ENCRYPTED_PASSWD)
        </leftSide>
        <operator>=</operator>
        <rightSide>0</rightSide>
    </Simple>
</RightBooleanExpression>
</DisjunctionInfo>
</ConditionInfo>
<ActionInfo>
    <name>Password modification action</name>
</ActionInfo>
<ActionPreferenceInfos/>
</RuleInfo>
</RuleInfos>
</PolicyInfo>

```

Sample Policy Definitions

The directory `<Oracle home>/beehive/templates/policy` contains the following sample policy definitions:

- AddPolicyTest_conjunction.xml
- AddPolicyTest_disjunction.xml
- AddPolicyTest_simple.xml

- `ModifyPolicyTest.xml`

The policy directory also contains XSD files that define the structure of policy definitions.

PolicyInfo

Root element of policy definitions.

Table 1–32 Elements of PolicyInfo

Element Name	Min.	Max.	Description
collabId	0	1	String
scope	0	1	String
templateId	0	1	String
policy	0	1	String
scope	0	1	String
template	0	1	String
name	1	1	String
description	1	1	String
attributes	1	unbounded	
RuleInfos	1	1	Contains at least one to any number of RuleInfo elements
ActionPreferenceInfos	1	1	Contains at least one to any number of ActionPreferenceInfo elements. These are key/value pairs that are sent to the action
isExtensible	1	1	Boolean

attributes

Table 1–33 Elements of attributes

Element Name	Min.	Max.	Description
attributeDefId	1	1	String
name	1	1	String
value	1	1	String

RuleInfo

Contains one or more conditions defined by the ConditionInfo element. These conditions are evaluated as true or false. Depending on the results of these conditions, the rule may activate an action. The ActionInfo element defines these actions.

Table 1–34 Elements of RuleInfo

Element Name	Min.	Max.	Description
name	1	1	String
description	1	1	String
eventTypeName	1	1	String, name of an Oracle Beehive event

Table 1–34 (Cont.) Elements of RuleInfo

Element Name	Min.	Max.	Description
ruleId	1	1	String
toRemove	1	1	Boolean, if true, the rule specified by ruleId will be removed from the policy
templateRuleId	1	1	String
ConditionInfo	1	1	Defines the conditions that must be true in order to activate the action(s) specifies in ActionInfo
ActionInfo	1	unbounded	Defines the action(s) this rule will activate.

Table 1–35 Attributes of RuleInfo

Attribute Name	Description
priority	Integer, specifies the order in which rules are evaluated. A rule with a lower priority will be evaluated before one with a higher priority.

ConditionInfo

Contains logical expressions.

The ConditionInfo element may contain either one ConjunctionInfo element or one DisjunctionInfo element.

Table 1–36 Elements of ConditionInfo

Element Name	Min.	Max.	Description
ConjunctionInfo	0	1	logical expression (type) , evaluates to true if both of its boolean expressions evaluate to true. This is like a logical AND operator.
DisjunctionInfo	1	1	logical expression (type) , evaluates to true if one or both of its boolean expressions evaluate to true. This is like the logical OR operator.
Simple	0	1	Simple

logical expression (type)

Represents the elements ConjunctionInfo and DisjunctionInfo. Contains two boolean expressions.

Table 1–37 Elements of logical expression (type)

Element Name	Min.	Max.	Description
LeftBooleanExpression	1	1	boolean expression (type)
RightBooleanExpression	1	1	boolean expression (type)

boolean expression (type)

Represents the elements LeftBooleanExpression and RightBooleanExpression.

May contain only one of the elements listed in the following table. The ConjunctionInfo and DisjunctionInfo elements allow you to nest boolean expressions.

Table 1–38 Elements of boolean expression (type)

Element Name	Min.	Max.	Description
ConjunctionInfo	0	1	logical expression (type)
DisjunctionInfo	0	1	logical expression (type)
Simple	0	1	

Simple

Defines a boolean expression that consists of two operands (the leftSide and rightSide elements) and an operator (the element operator).

Table 1–39 Elements of Simple

Element Name	Min.	Max.	Description
leftSide	1	1	String
operator	1	1	One of the following operators: <ul style="list-style-type: none"> ■ = (equals) ■ != (not equal) ■ &lt; (less than) ■ > (greater than) ■ &lt;= (less than or equal to) ■ >= (greater than or equal to)
rightSide	1	1	String

ActionInfo

Specifies the action to be performed if the expressions in ConditionInfo evaluate to true. The command `beectl list_actions` lists all available actions.

Table 1–40 Elements of ActionInfo

Element Name	Min.	Max.	Description
name	1	1	Name of the action to be performed if the expressions in ConditionInfo evaluate to true.

ActionPreferenceInfo

Table 1–41 Elements of ActionPreferenceInfo

Element Name	Min.	Max.	Description
key	1	1	String
value	1	1	String

Workflow Templates

A workflow template determines the conditions for a workflow to take place, as well as the context (a container) in which it applies. The following is a sample workflow template:

Example 1–4 Sample Workflow Template

```

<WorkflowTemplateInfo
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation=
    "http://xml.oracle.com/beehive/workflow workflow_template.xsd"
  xmlns="http://xml.oracle.com/beehive/workflow"
  isfinal="false">
  <name>Oracle Beehive Sample Workflow Template</name>
  <collabid></collabid>
  <description>A Template for Serial Workflow</description>
  <schemaname>SerialWorkflow</schemaname>
  <containerid>
    540E:29F5:wstm:0F74CE0314C74715BFAE8E8F77DFC44300000000001F
  </containerid>
  <templatekey>DOCUMENT_CREATE</templatekey>
  <Attributes>
    <attribute>
      <name>justification</name>
      <defaultValue>
        Request to create a document in the Oracle Beehive Lab Workspace
      </defaultValue>
      <prompted>true</prompted>
      <required>false</required>
    </attribute>
    <attribute>
      <name>workflowtimeout</name>
      <defaultValue>0</defaultValue>
      <prompted>true</prompted>
      <required>false</required>
    </attribute>
    <attribute>
      <name>approvertimeout</name>
      <defaultValue>0</defaultValue>
      <prompted>true</prompted>
      <required>false</required>
    </attribute>
    <attribute>
      <name>approvers</name>
      <defaultValue>tolkin</defaultValue>
      <prompted>true</prompted>
      <required>false</required>
    </attribute>
    <attribute>
      <name>payload</name>
      <defaultValue>defaultpayload</defaultValue>
      <prompted>true</prompted>
      <required>false</required>
    </attribute>
    <attribute>
      <name>tasktitle</name>
      <defaultValue>
        Request to create a document in the Oracle Beehive Lab Workspace
      </defaultValue>
      <prompted>true</prompted>
      <required>false</required>
    </attribute>
    <attribute>
      <name>initiator</name>
      <defaultValue>rahad</defaultValue>
      <prompted>true</prompted>

```

```

        <required>false</required>
      </attribute>
    </Attributes>
  </WorkflowTemplateInfo>

```

Sample Workflow Templates

The directory `<Oracle home>/beehive/templates/workflow` contains the following sample workflow template:

- `AddWorkflowTemplateTest.xml`

The workflow directory also contains the XSD file `Workflow_template.xsd` that defines the structure of workflow templates.

WorkflowTemplateInfo

Table 1–42 Elements of WorkflowTemplateInfo

Element Name	Min.	Max.	Description
name	1	1	String
collabid	1	1	String
description	1	1	String, description of the workflow template
schemaname	1	1	<p>String, name of an existing workflow. Oracle Beehive comes with two workflows:</p> <ul style="list-style-type: none"> ■ SerialWorkflow: Allows an action to be approved when a number of responders have reviewed the request in order. If any responder rejects the request, the action will not be performed. ■ ParallelVoteWorkflow: Allows an action to be approved when a number of responders have reviewed the request in parallel. <p>These workflows are cancelled when it is no longer mathematically possible for the workflow to be approved, and approved when it is no longer mathematically possible for the workflow to be rejected. For example, in a workflow with two responders and two required "yes" votes, if one user rejects the request, the request will immediately be cancelled.</p>
containerid	1	1	Specifies the container in with the workspace template applies
templatekey	1	1	String, name of an Oracle Beehive Event. The workflow template determines whether this event may be performed.
Attributes	1	unbounded	Contains one to any number of attribute elements
isfinal	1	1	Boolean

attribute

Table 1–43 *Elements of attribute*

Element Name	Min.	Max.	Description
name	1	1	String
defaultValue	1	1	String
prompted	1	1	Boolean
required	1	1	Boolean

Attributes for SerialWorkflow

The following are the available attributes for SerialWorkflow:

- justification: Optional justification for request
- workflowtimeout: Number of days before request expires. A value of zero indicates that the request does not expire.

Note: Time out values (both workflowtimeout and approvertimeout) should be in the form PxDyHzM. For example, P1D = 1 day; P1D6H = 1 day 6 hours; P2D3H30M = 2 days 3 hours 30 minutes; P0D = zero days, which means that the request does not expire.

- approvertimeout: Number of days that approvers may review the request before approving it; a value of zero indicates that approvers do not have a limited duration of time
- approvers: Comma-delimited list of users who must review this request. The users must review the request in the order they appear in this attribute. The user's login ID should appear here.
- tasktitle: The Oracle Beehive task that is created will have this title
- initiator: The default value is the name of the user who initiated the request. When the workflow is invoked, this attribute is automatically set to the user who actually triggered the event to be invoked. For instance, if the user john.a.macdonald uploads a document, the workflow will be triggered with john.a.macdonald as the initiator. This default value is provided for fallback purposes only.

Attributes for ParallelVoteWorkflow

The following are the available attributes for ParallelVoteWorkflow:

- justification: Optional justification for request
- workflowtimeout: Number of days before request expires; a value of zero indicates that the request does not expire

Note: Time out values (both workflowtimeout and approvertimeout) should be in the form PxDyHzM. For example, P1D = 1 day; P1D6H = 1 day 6 hours; P2D3H30M = 2 days 3 hours 30 minutes; P0D = zero days, which means that the request does not expire.

- **approvertimeout:** Number of days that approvers may review the request before approving it; a value of 0 indicates that approvers do not have a limited duration of time
- **approvers:** Comma-delimited list of users who may review this request
- **votepercent:** Defines the percentage of approvers that need to approve the parallel workflow. If this percentage is not met and all approvers have responded, the workflow is rejected. Do not include the percent (%) symbol. For example, use the value 50 in the XML file, not 50%.
- **tasktitle:** The Oracle Beehive task that is created will have this title
- **initiator:** The default value is the name of the user who initiated the request. When the workflow is invoked, this attribute is automatically set to the user who actually triggered the event to be invoked. For instance, if the user john.a.macdonald uploads a document, the workflow will be triggered with john.a.macdonald as the initiator. This default value is provided for fallback purposes only.

Note: All timeout values must be either 0 (which means no timeout) or in the form PxDyH, where *x* is the number of days, and *y* is the number of hours. For example, P1D represents one day, and P1D6H represents one day and six hours.

Workspace Templates

Workspace templates populate new workspaces with a specified folder hierarchy and set up workspace properties. Oracle Beehive comes with four workspace templates:

- Basic Personal Workspace Template
- Basic Team Workspace Template
- Community of Practice Workspace Template
- Project Workspace Template

The following is a basic team workspace template:

Example 1–5 Basic Team Workspace Template

```
<teamWorkspaceTemplate
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns="http://xmlns.oracle.com/beehive/transportabletemplate"
  xsi:schemaLocation="http://xmlns.oracle.com/beehive/transportabletemplate
    http://xmlns.oracle.com/beehive/transportabletemplate.xsd">

  <templateAttributes>
    <author>Oracle</author>
    <authorCreationTime>2004-08-12</authorCreationTime>
    <contactInfo>Oracle Corporation</contactInfo>
    <copyrightInfo>
      Copyright (c) 2007 Oracle Corporation. All rights reserved.
    </copyrightInfo>
    <description>Basic team workspace template</description>
    <name>Basic Team Workspace Template</name>
    <templateId>oracle.com.basic-team-workspace-template</templateId>
    <domain>general</domain>
  </templateAttributes>
```



```

<body>
  <publicSensitivityTemplateBodyId>
    public_sensitivity
  </publicSensitivityTemplateBodyId>
  <defaultSensitivityTemplateBodyId>
    default_sensitivity
  </defaultSensitivityTemplateBodyId>

  <attributes>
    <name prompt="true">teamWorkspace</name>
    <description>workspace for managing team information</description>
    <participationMode>INVITE_ONLY</participationMode>
  </attributes>

  <sensitivity id="default_sensitivity">
    <name>Normal</name>
    <description>normal sensitivity</description>
    <sensitivityOnly>false</sensitivityOnly>
    <delegatable>true</delegatable>
    <ace>
      <grantAccessType>DISCOVER</grantAccessType>
      <accessor type="GROUP">
        <systemDefinedGroupName>
          ALL_USERS
        </systemDefinedGroupName>
      </accessor>
    </ace>
  </sensitivity>

  <sensitivity id="public_sensitivity">
    <name>Public</name>
    <description>public sensitivity</description>
    <sensitivityOnly>false</sensitivityOnly>
    <delegatable>true</delegatable>
    <ace>
      <grantAccessType>DISCOVER</grantAccessType>
      <grantAccessType>READ</grantAccessType>
      <accessor type="GROUP">
        <systemDefinedGroupName>
          ALL_USERS
        </systemDefinedGroupName>
      </accessor>
    </ace>
  </sensitivity>

  <defaultAnnouncementsForum id="default_ann_forum">
    <name>Announcements</name>
    <description>forum for workspace announcements</description>
  </defaultAnnouncementsForum>

  <defaultAddressBook id="default_address_book">
    <name>Contacts</name>
    <description>team address book</description>
  </defaultAddressBook>

  <defaultCalendar id="default_calendar">
    <name>Calendar</name>
    <description>team calendar</description>
  </defaultCalendar>

```

```
<defaultInbox id="inbox_folder">
  <name>INBOX</name>
  <description>inbox for email messages</description>
</defaultEmailInbox>

<defaultTaskList id="default_task_list">
  <name>Tasks</name>
  <description>team tasks</description>
</defaultTaskList>

<entities>
  <folder id="documents_folder">
    <name>Documents</name>
    <description>folder for team documents</description>
  </folder>
</entities>

<summary>
  <inlineSummary>
    <fileName>summary.html</fileName>
    <mediaType>text/html</mediaType>
    <body>
      &lt;title&gt; Workspace Summary for Members &lt;/title&gt;
      &lt;b&gt; ${sys.workspace.name} &lt;/b&gt;
      &lt;p&gt;The Workspace Coordinator should edit this text to share
        private information about this project with the team. For example,
        add a little text here describing the project goals, milestones and
        progress. &lt;/p&gt;
    </body>
  </inlineSummary>
</summary>

<publicSummary>
  <inlineSummary>
    <fileName>publicSummary.html</fileName>
    <mediaType>text/html</mediaType>
    <body> &lt;title&gt; Workspace Public Summary &lt;/title&gt;
      &lt;b&gt; ${sys.workspace.name} &lt;/b&gt;
      &lt;p&gt; The Workspace Coordinator should edit this text to share
        public information about this project with others in your company.
        For example, add a little text here describing the project goals,
        milestones and progress. &lt;/p&gt;
    </body>
  </inlineSummary>
</publicSummary>

</body>

</teamWorkspaceTemplate>
```

The following is a basic personal workspace template

Example 1–6 Basic Personal Workspace Template

```
<personalWorkspaceTemplate
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns="http://xmlns.oracle.com/beehive/transportabletemplate"
  xsi:schemaLocation="http://xmlns.oracle.com/beehive/transportabletemplate
    http://xmlns.oracle.com/beehive/transportabletemplate.xsd">
```

```

<templateAttributes>
  <author>Oracle</author>
  <authorCreationTime>2004-08-12</authorCreationTime>
  <contactInfo>Oracle Corporation</contactInfo>
  <copyrightInfo>
    Copyright (c) 2007 Oracle Corporation. All rights reserved.
  </copyrightInfo>
  <description>Basic personal workspace template</description>
  <name>Basic Personal Workspace Template</name>
  <templateId>oracle.com.basic-personal-workspace-template</templateId>
  <domain>general</domain>
</templateAttributes>

<environment>

  <label>
    <name>Personal</name>
    <description>marker for personal items</description>
  </label>

  <label>
    <name>Business</name>
    <description>marker for business items</description>
  </label>

</environment>

<body>
  <publicSensitivityTemplateBodyId>
    public_sensitivity
  </publicSensitivityTemplateBodyId>
  <defaultSensitivityTemplateBodyId>
    default_sensitivity
  </defaultSensitivityTemplateBodyId>

  <attributes>
    <name prompt="true">personalWorkspace</name>
    <description>workspace for managing personal information</description>
  </attributes>

  <sensitivity>
    <name>Confidential</name>
    <description>confidential sensitivity</description>
    <sensitivityOnly>false</sensitivityOnly>
    <delegatable>true</delegatable>
    <ace>
      <grantAccessType>DISCOVER</grantAccessType>
      <accessor type="GROUP">
        <systemDefinedGroupName>
          ALL_USERS
        </systemDefinedGroupName>
      </accessor>
    </ace>
  </sensitivity>

  <sensitivity id="default_sensitivity">
    <name>Normal</name>
    <description>normal sensitivity</description>
    <sensitivityOnly>false</sensitivityOnly>

```

```
<delegatable>true</delegatable>
<ace>
  <grantAccessType>DISCOVER</grantAccessType>
  <accessor type="GROUP">
    <systemDefinedGroupName>ALL_USERS</systemDefinedGroupName>
  </accessor>
</ace>
</sensitivity>

<sensitivity>
  <name>Private</name>
  <description>private sensitivity</description>
  <sensitivityOnly>true</sensitivityOnly>
  <delegatable>false</delegatable>
  <ace>
    <grantAccessType>DISCOVER</grantAccessType>
    <accessor type="GROUP">
      <systemDefinedGroupName>
        ALL_USERS
      </systemDefinedGroupName>
    </accessor>
  </ace>
</sensitivity>

<sensitivity id="public_sensitivity">
  <name>Public</name>
  <description>public sensitivity</description>
  <sensitivityOnly>false</sensitivityOnly>
  <delegatable>true</delegatable>
  <ace>
    <grantAccessType>DISCOVER</grantAccessType>
    <grantAccessType>READ</grantAccessType>
    <accessor type="GROUP">
      <systemDefinedGroupName>
        ALL_USERS
      </systemDefinedGroupName>
    </accessor>
  </ace>
</sensitivity>

<defaultAddressBook id="default_address_book">
  <name>Address Book</name>
  <description>contacts</description>
</defaultAddressBook>

<defaultEmailInbox id="inbox_folder">
  <name>INBOX</name>
  <description>inbox for email messages</description>
</defaultEmailInbox>

<defaultNotificationList id="default_notification_list">
  <name>Notifications</name>
  <description>folder for notification messages</description>
</defaultNotificationList>

<defaultSubscriptionList id="default_subscription_list">
  <name>Subscriptions</name>
  <description>folder for subscriptions</description>
</defaultSubscriptionList>
```

```

<entities>
  <folder id="documents_folder">
    <name>Documents</name>
    <description>folder for documents</description>
  </folder>
</entities>

<summary>
  <inlineSummary>
    <fileName>summary.html</fileName>
    <mediaType>text/html</mediaType>
    <body>
      &lt;title&gt;Personal Summary&lt;/title&gt;
      &lt;b&gt; Your Name Here &lt;/b&gt;
      &lt;p&gt; Edit this text to share information about yourself that you
        want others in your company to see. For example, you can place a little
        text here describing your current job role and projects that you are
        working on. &lt;/p&gt;
      &lt;p&gt; NOTE: You must apply Public sensitivity to this document in
        order for it to be viewed by other members of your company. &lt;/p&gt;
    </body>
  </inlineSummary>
</summary>

</body>

</personalWorkspaceTemplate>

```

Template Variables

You may specify parametric information with two kinds of template variables: system defined and user defined.

System Defined Template Variable

Oracle Beehive Release 1 supports the following system defined template variables:

- `sys.workspace.name`: Value of the name element in the [templateAttributes](#) element
- `sys.workspace.description`: Value of the description element in the [templateAttributes](#) element
- `sys.workspace.owner.collabid`: The CEN of the workspace owner

User Defined Template Variable

Use the `templateVariable` element to define your own variables. The following is an example of how to define a user defined template variable:

```

<templateVariable>
  <name>default-announcement-body</name>
  <description>Welcome new workspace memeber!</description>
</templateVariable>

```

The following is an example of how to use a system defined template variable (`sys.workspace.name`) and a user defined template variable (`default-announcement-body`):

```

<announcement>
  <subject>Welcome to workspace ${sys.workspace.name}</subject>

```

```
<messageBody>
  <mediaType>text/plain</mediaType>
  <body>${default-announcement-body}</body>
</messageBody>
</announcement>
```

Expressions

Expressions allow you to create variables that have references to other template variables and perform arithmetic operations on them. Two types of expressions are available: arithmetic expressions and temporal expressions.

Arithmetic Expressions

An arithmetic expression consists of two operands and an arithmetic operator. The operands may be a template variable, a constant, or another arithmetic expression. The operator may be plus, minus, or product.

Temporal Expressions

A temporal expression evaluates to a specific time or instant. It consists of a template variable, an operator, and an offset:

- The template variable refers to a specific time or instant.
- The operator may be either plus or minus.
- The offset is a constant or an arithmetic expression that specifies a duration of time to add or subtract (depending on the operator) from the template variable. It supports the time units hour, minute, second, or millisecond. The default time unit is millisecond.

The following is an example of a temporal expression that sets the due time of a task named One Day Later:

```
<templateVariable>
  <name>task_reference_start_time_variable</name>
</templateVariable>

<todo>

  <name>One Day Later</name>
  ...
  <dueTime>
    <temporalExpression>
      <templateVariableRef>
        ${task_reference_start_time_variable}
      </templateVariableRef>
      <operator>PLUS</operator>
      <offset timeUnit="HOUR">24</offset>
    </temporalExpression>
  </dueTime>
  ...
</todo>
```

The following is an example of a temporal expression that sets the start time of a task named End of Vacation:

```
<templateVariable>
  <name>beginning_of_vacation</name>
</templateVariable>
```

```

<templateVariable>
  <name>vacation_days</name>
</templateVariable>
...
<todo>
  <name>End of Vacation</name>
  ...
  <startTime>
    <temporalExpression>
      <templateVariableRef>${total_vacation_hours}</templateVariableRef>
      <operator>PLUS</operator>
      <offset timeUnit="HOUR">
        <expression>
          <leftOperand>
            <value>${vacation_days}</value>
          </leftOperand>
          <operator>PRODUCT</operator>
          <rightOperand>
            <value>24</value>
          </rightOperand>
        </expression>
      </offset>
    </temporalExpression>
  </startTime>
  ...
</todo>

```

Sample Workspace Templates

The directory `<Oracle home>/beehive/templates/workspaces` contains the following sample workspace templates:

- `add_category_template1.xml`: Adds a category at the root level with no attributes
- `add_category_template2.xml`: Creates a category with attributes
- `add_subcategory_template.xml`: Creates a subcategory

The `workspaces` directory also contains the XSD file `category.xsd` that defines the structure of workspace templates.

ace

Access Control Entity, grants or restricts the access type specified by the `grantAccessType` and `denyAccessType` elements, respectively.

Table 1–44 Elements of ace

Element Name	Min.	Max.	Description
grantAccessType	1	1	Enumerated type, grants one of the following access types: <ul style="list-style-type: none"> ■ READ: Permission to open or read the object ■ WRITE: Permission to add, alter, or make changes to the object. Note that version control preserves previous versions, so WRITE access does not itself provide DELETE access. ■ DELETE: Permission to delete the object ■ EXECUTE: Permission to invoke or assign the object or cause it to perform its function ■ DISCOVER: Permission to see the object in lists, look it up in directories, find it in searches, and so forth. When DISCOVER privileges are revoked, a user cannot detect the existence of that object using any Oracle Beehive client process
denyAccessType	1	1	Same as grantAccessType, except denies one of the five access types
accessor	0	unbounded	

accessor

Specifies for whom the ACE applies (such as a user, or members of a specified group).

One, and only one, of the elements in the following table must appear:

Table 1–45 Elements of accessor

Element Name	Min.	Max.	Description
systemDefinedGroupName	0	1	Enumerated type, ALL_USERS
cen	0	1	String, reference to an existing accessor
subgroupTemplateBodyId	0	1	IDREF, ID of a template defined in the template itself

Table 1–46 Attributes of accessor

Attribute Name	Description
type	Enumerated value, one of the following: <ul style="list-style-type: none"> ■ GROUP ■ USER

address

Table 1–47 Elements of address

Element Name	Min.	Max.	Description
uri	1	1	String
type	0	1	Enumerated value
defaultForScheme	0	1	Boolean
defaultForType	0	1	Boolean
primary	0	1	Boolean

type

Enumerated value, one of the following:

- BUSINESS_1
- BUSINESS_2
- BUSINESS_3
- BUSINESS_4
- BUSINESS_5
- OTHER_1
- OTHER_2
- OTHER_3
- OTHER_4
- OTHER_5
- PERSONAL_1
- PERSONAL_2
- PERSONAL_3
- PERSONAL_4
- PERSONAL_5

addressBook

Table 1–48 Elements of addressBook

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String
personContact	0	unbounded	
subAddressBook	0	unbounded	addressBook
ace	0	unbounded	

personContact**Table 1–49 Elements of personContact**

Element Name	Min.	Max.	Description
givenName	1	1	String
middleName	0	1	String
familyName	0	1	String
nickname	0	1	String
profession	0	1	String
company	0	1	String
peopleListEntry	0	1	Boolean
priority	0	1	
address	0	unbounded	
ace	0	unbounded	

attributes (body of personalWorkspace)**Table 1–50 Elements of attributes (body of personalWorkspace)**

Element Name	Min.	Max.	Description
name	1	1	Promptable Non-Empty String (type)
description	0	1	String

attributes (body of teamWorkspace)

In Oracle Beehive Release 1, you cannot specify workspace contact with workspace templates.

Table 1–51 Elements of attributes (body of teamWorkspace)

Element Name	Min.	Max.	Description
name	1	1	Promptable Non-Empty String (type)
description	0	1	String
publiclyListed	0	1	Boolean
participationMode			Enumerated value, either INVITE_ONLY or OPEN

body (personalWorkspaceTemplate)**Table 1–52 Elements of body (personalWorkspaceTemplate)**

Element Name	Min.	Max.	Description
publicSensitivityTemplateBodyId	0	1	IDREF, ID of a public sensitivity template defined in the workspace template
defaultSensitivityTemplateBodyId	0	1	IDREF, ID of a sensitivity template defined in the workspace template

Table 1–52 (Cont.) Elements of body (personalWorkspaceTemplate)

Element Name	Min.	Max.	Description
attributes	0	1	attributes (body of personalWorkspace)
sensitivity	0	unbounded	
defaultAddressBook	0	1	addressBook
defaultCalendar	0	1	calendar
defaultEmailInbox	0	1	folder
defaultNotificationList	0	1	folder
defaultTaskList	0	1	taskList
defaultSubscriptionList	0	1	folder
entities	0	1	
summary	0	1	
ace	0	unbounded	

body (teamWorkspaceTemplate)**Table 1–53 Elements of body (teamWorkspaceTemplate)**

Element Name	Min.	Max.	Description
publicSensitivityTemplateBodyId	0	1	IDREF, ID of a public sensitivity template defined in the workspace template
defaultSensitivityTemplateBodyId	0	1	IDREF, ID of a sensitivity template defined in the workspace template
defaultRoleTemplateBodyId	0	1	IDREF
attributes	0	1	attributes (body of teamWorkspace)
address	0	unbounded	
role	0	unbounded	
sensitivity	0	unbounded	
group	0	unbounded	
participant	0	unbounded	
defaultAnnouncementsForum	0	1	forum
defaultAddressBook	0	1	addressBook
defaultCalendar	0	1	calendar
defaultInbox	0	1	folder
defaultTaskList	0	1	taskList
entities	0	1	
summary	0	1	
publicSummary	0	1	summary
ace	0	unbounded	

calendar

In Oracle Beehive Release 1, you cannot specify time zone and available hours with workspace templates.

Table 1–54 Elements of calendar

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String
defaultPriority	0	1	priority
inheritTimeZoneFromOwner	0	1	
allowDoubleBooking	0	unbounded	Boolean
includeInFreeBusy	0	1	Boolean
deriveAvailableHoursFromOwnerWorkingHours	0	1	Boolean
enrollmentType	0	1	Enumerated value, may be either PUBLIC or PRIVATE.
occurrence	0	unbounded	
occurrenceSeries	0	unbounded	
ace	0	unbounded	

occurrence

Table 1–55 Elements of occurrence

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String
priority	0	1	
location	0	1	
startTime	0	unbounded	Boolean
endTime	0	1	Boolean
occurrenceType	0	1	Enumerated value, either DAY_EVENT, HOLIDAY, or MEETING
dialInInfo	0	1	String
organizer	0	1	accessor
participant	0	unbounded	accessor
ace	0	unbounded	

occurrenceSeries

In Oracle Beehive Release 1, you cannot specify time zone and available hours with workspace templates.

Table 1–56 Elements of occurrenceSeries

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String
priority	0	1	
location	0	1	
occurrenceType	0	unbounded	Enumerated value, either DAY_EVENT, HOLIDAY, or MEETING
dialInInfo	0	1	String
updateMode	0	1	Enumerated value, one of the following <ul style="list-style-type: none"> SERIES_AND_ALL_OCCURRENCES SERIES_AND_NON_DIRECTLY_MODIFIED_EXCEPTIONS SERIES_ONLY
frequency	1	1	Contains one element with the following structure: <pre><enumeratedFrequency> <startEndTime> <startTime/> <endTime/> </startEndTime> </enumeratedFrequency></pre> <p>The enumeratedFrequency element must contain one to any number of startEndTime elements.</p> <p>The startEndTime element must contain one startTime and one endTime element.</p> <p>The elements startTime and endTime are of type Promptable Template Time (type).</p>
duration	1	1	Must have one of the following elements: <ul style="list-style-type: none"> templateVariableRef: String length: Integer May contain one of the following attributes: <ul style="list-style-type: none"> prompt: Boolean promptMessage: String
organizer	0	unbounded	accessor
participant	0	unbounded	accessor
ace	0	unbounded	

contentLocation

Table 1–57 Elements of contentLocation

Element Name	Min.	Max.	Description
contentID	1	1	String
location	1	1	String

entities

Table 1–58 Elements of entities

Element Name	Min.	Max.	Description
folder	0	unbounded	
calendar	0	unbounded	
taskList	0	unbounded	
forum	0	unbounded	
file	0	unbounded	

environment

Specifies entities that should be available in the ancestor scopes of the workspace. If no matching entity is available for any specified entity at the time of workspace creation, a new entity will be created in the parent scope, provided the current user has the required privileges.

Table 1–59 Elements of environment

Element Name	Min.	Max.	Description
label	0	unbounded	

label

Table 1–60 Elements of label

Element Name	Min.	Max.	Description
name	1	1	String
description	1	1	String

expression

Table 1–61 Elements of expression

Element Name	Min.	Max.	Description
leftOperand	1	1	Contains one element named value. The value element may be a constant (a numerical value), a template variable or another expression. Refer to " Template Variables ".
operator	1	1	PLUS, MINUS, or PRODUCT.
rightOperand	1	1	Contains one element named value. The value element may be a constant (a numerical value) a template variable, or another expression. Refer to " Template Variables ".

file

Table 1–62 Elements of file

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String
content	0	1	Contains one element, contentID, a string. The element contentID is a reference to content ID in contentID-file-path map defined at the beginning of the template.
ace	0	unbounded	

folder

Also represents defaultEmailInbox, defaultNotificationList, and defaultSubscriptionList.

Table 1–63 Elements of folder

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String
versionControlConfiguration	0	1	
entities	0	1	
ace	0	unbounded	

versionControlConfiguration

Table 1–64 Elements of versionControlConfiguration

Element Name	Min.	Max.	Description
versionControlModel	1	1	String
maxVersionsToKeep	0	1	Unsigned integer
autoLabel	0	1	Boolean
labelFormat	0	1	Enumerated type, one of the following values: <ul style="list-style-type: none"> DECIMAL_FORMAT INTEGER_FORMAT LOWER_CASE_FORMAT ROMAN_NUMERAL_FORMAT UPPERCASE_FORMAT
isFinal	0	1	Boolean

forum

Table 1–65 Elements of forum

Element Name	Min.	Max.	Description
name	1	1	String

Table 1–65 (Cont.) Elements of forum

Element Name	Min.	Max.	Description
description	0	1	String
incrementViewCount	0	1	Boolean
subForum	0	unbounded	Same as forum
topic	0	unbounded	
announcement	0	unbounded	
ace	0	unbounded	

topic**Table 1–66 Elements of topic**

Element Name	Min.	Max.	Description
subject	1	1	String
messageBody	1	1	String
ace	0	unbounded	

announcement**Table 1–67 Elements of announcement**

Element Name	Min.	Max.	Description
subject	1	1	String
messageBody	0	1	String
activatesOn	0	1	Promptable Template Time (type)
expiresOn	0	1	Promptable Template Time (type)
ace	0	unbounded	

messageBody**Table 1–68 Elements of messageBody**

Element Name	Min.	Max.	Description
mediaType	1	1	String
body	1	1	String

group**Table 1–69 Elements of group**

Element Name	Min.	Max.	Description
name	1	1	String
description	1	1	String

label

Table 1–70 Elements of label

Element Name	Min.	Max.	Description
name	1	1	String
description	1	1	String

location

Table 1–71 Elements of location

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String

participant

Table 1–72 Elements of participant

Element Name	Min.	Max.	Description
identity	1	1	
role	0	unbounded	

identity

Table 1–73 Elements of identity

Element Name	Min.	Max.	Description
systemDefinedGroupName	0	1	Either this element or cen must appear Enumerated value: ALL_USERS
cen	0	1	String, either this element or systemDefinedGroupName must appear

Table 1–74 Attributes of identity

Attribute Name	Description
type	Required attribute, enumerated value, may have a value of GROUP or USER.

role

Table 1–75 Elements of role

Element Name	Min.	Max.	Description
cen	1	1	String, reference to an existing role
entityTemplateBodyId	1	1	IDREF, reference to a role ID specified in the template itself

personalWorkspaceTemplate

Table 1–76 Elements of personalWorkspaceTemplate

Element Name	Min.	Max.	Description
templateAttributes	1	1	
contentLocation	0	unbounded	
templateVariable	0	unbounded	
environment	0	1	
body	1	1	body (personalWorkspaceTemplate)

priority

Enumerated value, one of the following:

- HIGH
- MEDIUM
- LOW
- NONE

Promptable Non-Empty String (type)

The attributes `prompt` and `promptMessage` can be used for providing hints to GUI tools for template exploration. In Oracle Beehive Release 1, these attributes have no other semantic effect.

Table 1–77 Elements of Promptable Non-Empty String (type)

Attribute Name	Description
<code>prompt</code>	Boolean, optional.
<code>promptMessage</code>	String, optional

Promptable Template Time (type)

Table 1–78 Elements of Promptable Template Time (type)

Element Name	Min.	Max.	Description
<code>templateVariableRef</code>	0	1	String, either this element or <code>offset</code> may appear
<code>offset</code>	0	1	Integer, offset in milliseconds with respect to entity creation time Either this element or <code>templateVariableRef</code> may appear

Table 1–79 Attributes of Promptable Template Time (type)

Attribute Name	Description
<code>prompt</code>	Boolean, optional
<code>promptMessage</code>	String, optional

role

Table 1–80 Elements of role

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String
grantPrivilege	0	unbounded	Enumerated type
grantAccessType	0	unbounded	Enumerated type, one of the following: <ul style="list-style-type: none"> ▪ READ ▪ WRITE ▪ DELETE ▪ EXECUTE ▪ DISCOVER
denyAccessType	0	unbounded	Same as grantAccessType

grantPrivilege

Enumerated value, one of the following

- ARCHIVE_MGR
- AUDIT_ADMIN
- AUDITOR
- BYPASS
- CALENDAR_MGR
- CALENDAR_USER
- CONF_MGR
- CONF_USER
- DIAGNOSE
- DM_MGR
- EMAIL_MGR
- EMAIL_USER
- EXCEED_QUOTA
- FORUM_MGR
- FORUM_USER
- IM_MGR
- IM_USER
- LOGIN
- MARKER_MGR
- MODIFY_ACL
- NOTIFICATION_MGR
- NOTIFICATION_USER

- ORGANIZATION_MGR
- POLICY_MGR
- PROTOCOL_USER
- QUOTA_MGR
- READALL
- RESOURCE_MGR
- ROLE_MGR
- SECURITY
- SUBSCRIPTION_MGR
- SUBSCRIPTION_USER
- SYSTEM_OPER
- TASK_MGR
- TASK_USER
- TIMEZONE_MGR
- USER_MGR
- VERSION_MGR
- VOICE_USER
- WORKFLOW_MGR
- WORKFLOW_TASK_MGR
- WORKSPACE_ADD
- WORKSPACE_MGR

sensitivity

Table 1–81 Elements of sensitivity

Element Name	Min.	Max.	Description
name	1	1	String
description	1	1	String
sensitivityOnly	1	1	Boolean
delegatable	1	1	Boolean
ace	0	unbounded	

summary

Also represents the publicSummary element.

Table 1–82 Elements of summary

Element Name	Min.	Max.	Description
uri	0	1	String, either this element or inlineSummary must exist. Use this element for template variables.

Table 1–82 (Cont.) Elements of summary

Element Name	Min.	Max.	Description
inlineSummary	0	1	Either this element or uri must exist

inlineSummary**Table 1–83 Elements of inlineSummary**

Element Name	Min.	Max.	Description
filename	1	1	String
mediaType	1	1	String
body	1	1	String

teamWorkspaceTemplate**Table 1–84 Elements of teamWorkspaceTemplate**

Element Name	Min.	Max.	Description
templateAttributes	1	1	
contentLocation	0	unbounded	
templateVariable	0	unbounded	
body	1	1	body (teamWorkspaceTemplate)

templateAttributes**Table 1–85 Elements of templateAttributes**

Element Name	Min.	Max.	Description
author	1	1	String, this could be different than the creator attribute of the template entity if, for example, the template is created by a third-party vendor
authorCreationTime	1	1	String, this could be different than the createdOn attribute of the template entity if, for example, the template is created by a third-party vendor
contactInfo	0	1	String, more specifically, how to contact the vendor who created this template
copyrightInfo	0	1	String
description	1	1	String
name	1	1	String
templateId	1	1	String
domain	0	1	String

templateVariable

Table 1–86 Elements of templateVariable

Element Name	Min.	Max.	Description
name	1	1	String, name of the user defined template variable
type	0	1	String
description	0	1	String, value assigned to the user defined template variable
defaultValue	0	1	String, integer, or dateTime This value is assigned to the user defined template variable unless the user explicitly chooses a different value at the time of template instantiation. Note: defaultValue is not honored in Oracle Beehive Release 1.

temporalExpression

Refer to ["Expressions"](#) for more information.

Table 1–87 Elements of templateVariable

Element Name	Min.	Max.	Description
templateVariableRef	1	1	String, name of the user defined template variable
operator	1	1	One of PLUS or MINUS.
offset	1	1	A constant (a numerical value) or an value of type expression . You may optionally specify the attribute timeUnit. It may have the value HOUR, MINUTE, SECOND, or MILLISECOND. The default value is MILLISECOND.

taskList

In Oracle Beehive Release 1, you cannot specify time zone with workspace templates.

Table 1–88 Elements of taskList

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String
defaultPriority	0	1	priority
inheritTimeZoneFromOwner	0	1	Boolean
todo	0	unbounded	todo
ace	0	1	

todo

In Oracle Beehive Release 1, you cannot specify iCalPriority, status, url, or iCalUid with workspace templates.

Table 1–89 *Elements of todo*

Element Name	Min.	Max.	Description
name	1	1	String
description	0	1	String
priority	0	1	
location	0	1	
startTime	0	unbounded	Promptable Template Time (type) or temporalExpression
dueTime	0	1	Promptable Template Time (type) or temporalExpression
organizer	0	1	accessor
participant	0	unbounded	accessor
ace	0	unbounded	

Oracle Beehive Command-Line Utility

This module contains instructions on the usage and syntax for all commands shipped with the Oracle Beehive beectl utility. The utility is installed in the \$ORACLE_HOME/bee hive/bin directory.

The Oracle Beehive beectl utility is always used in conjunction with a qualifying command. This module contains instructions about each command, and its available options. When running an beectl command, the following syntax should be used:

```
beectl command --option <argument>
```

Where *command* represents the beectl command, --*option* represents an available option(s) to use with the command, and <*argument*> represents a valid argument passed with an option.

Using beectl Commands in Shell Mode Without Authentication

The beectl commands can also be used in shell mode. To invoke the shell, run the beectl utility without any qualifying commands. The following shell prompt will be returned on the command-line:

```
beectl>
```

Once this prompt appears on the command-line, there is no need to specify beectl when using a command.

Note: The beectl shell expires if inactive for more than 30 minutes.

Using beectl Commands in Shell Mode With Authentication

Many beectl commands require authentication using the --authuser and --authpassword options. To invoke the beectl shell with authenticated user credentials, use the following command in the beectl shell mode:

```
beectl> login --authuser <authuser> --authpassword <authpassword> -obfuscated
```

Where <authuser> represents the user with which to authenticate, and <authpassword> represents the obfuscated user password. For information about obfuscating a password, see the obfuscate command.

Summary of Commands

The following tables list all the available beectl commands.

Table 2–1 Category: access control

Utility	Function
add_assigned_role	Creates an AssignedRole entity.
add_local_ace	Adds an Access Control Entry (ACE) to an entity's Local Access Control List (LACL).
add_role_definition	Creates a RoleDefinition entity.
add_sensitivity	Creates a Sensitivity entity.
add_sensitivity_ace	Adds an Access Control Entry (ACE) to a Sensitivity entity's Sensitivity ACL (SACL).
delete_assigned_role	Deletes an AssignedRole entity.
delete_local_ace	Deletes an Access Control Entry (ACE) from the Local Access Control List (LACL) of an entity.
delete_role_definition	Deletes a RoleDefinition entity.
delete_sensitivity	Deletes a Sensitivity entity.
delete_sensitivity_ace	Deletes an Access Control Entry (ACE) from the Sensitivity Access Control List (SACL) of a Sensitivity entity.
list_access_control_fields	Lists the AccessControlFields of an entity.
list_access_types	Lists available access type names and identifiers.
list_assigned_roles	Lists AssignedRole entities.
list_local_acl	Lists the Local Access Control List (LACL) of an entity.
list_privileges	Lists available Privilege names.
list_role_definitions	Lists RoleDefinition entities.
list_sensitivities	Lists Sensitivity entities.
list_sensitivity_acl	Lists the Sensitivity Access Control List (SACL) of a Sensitivity.
modify_access_control_fields	Modifies the AccessControlFields of an existing entity.
modify_assigned_role	Modifies an existing AssignedRole entity.
modify_local_ace	Replaces an Access Control Entry (ACE) in the Local Access Control List (LACL) of an entity.
modify_role_definition	Modifies an existing RoleDefinition entity.
modify_sensitivity	Modifies an existing Sensitivity entity.
modify_sensitivity_ace	Replaces an Access Control Entry (ACE) in the Sensitivity Access Control List (SACL) of a Sensitivity entity.

Table 2–2 Category: audit

Utility	Function
add_audit_policy	Creates an audit policy from the XML file information
add_audit_template	Creates an audit policy template from the XML file information
add_audit_trail	Creates an audit trail from the search result generated using the XML file
delete_audit_policy	Deletes an existing audit
delete_audit_template	Deletes an existing audit policy template
delete_audit_trail	Deletes an existing audit trail
export_audit_trail	Exports an existing audit trail by the given identifier
list_audit_events	Lists auditable events
list_audit_policies	Lists audit policies and prints policy information
list_audit_templates	Lists audit policy templates and prints template information. Use --name option for detailed information about each audit policy template

Table 2–2 (Cont.) Category: audit

Utility	Function
list_audit_trails	Lists audit trails and prints trail information
modify_audit_policy	Modifies an existing audit policy
modify_audit_trail	Modifies an existing audit trail
validate_audit_trail	Validates an existing audit trail

Table 2–3 Category: client application

Utility	Function
add_attendant	Adds an auto attendant or copies an existing one under a new name. When copying any prompts will also be copied.
add_client_application_configuration	Creates a client application configuration object from a supplied input file. The resulting object will be used for client application provisioning.
add_client_application_provisioning	Provisions client applications to a community.
add_voice_enterprise	Creates a voice enterprise with the given name.
add_voice_facility	Creates a voice facility with the given name.
delete_attendant	Deletes an auto attendant by name.
delete_attendant_prompt	Deletes a prompt.
delete_client_application	Deletes a client application.
delete_client_application_configuration	Deletes the client application configuration with the given identifier.
delete_client_application_patchset	Deletes a client application patchset.
delete_client_application_version	Deletes a client application version.
delete_voice_enterprise	Deletes a voice enterprise with the given id.
delete_voice_facility	Deletes a voice facility with the given id.
export_client_application_configuration	Exports a client application configuration to a local file.
list_attendant_aaml	Prints the Auto Attendant Markup Language for an auto attendant.
list_attendant_prompts	Lists all prompts that have been uploaded for an attendant.
list_attendants	Lists all attendants in the system.
list_client_application_configuration	Lists the client application configurations.
list_client_application_modules	Lists the modules for a given client application patchset.
list_client_application_patchsets	Lists the patchsets for a given client application version.
list_client_application_versions	Lists all the versions for a given client application.
list_client_applications	Lists all the client applications.
modify_attendant	Update an existing attendant with a new markup file or rename it.
modify_ip_phone_password_seed	Resets the seed of the password generator for IP phones. To send commands to an IP phone the requestor must be authenticated. The password is generated based on information in the phone but must be seeded to ensure security.
upload_attendant_prompt	Upload a prompt to the database.
upload_client_application	Uploads client application binaries to the repository. Either a binary file path or path to a directory containing binary files should be specified. If the community option is specified, the uploaded client application patchset will also be provisioned to the community.

Table 2–4 Category: cloning

Utility	Function
clone_midtier	Top level clone command that clones a Oracle Beehive Application tier.
clone_oc4j_instance	Creates a new oc4j instance by cloning the given oc4j instance.
clone_preparation	Prepares the existing oracle home for cloning.
clone_site	Top level clone command that clones a Oracle Beehive Application tier in a new deployment (i.e., site). This command is part of the Deployment Cloning solution. Please see the administrator guide for details.
modify_beectl	This command updates the beectl file with the given oracle home & perl home

Table 2–5 Category: coexistence

Utility	Function
add_coexistence_connector	Configures a new coexistence connector.
delete_coexistence_connector	Deletes a coexistence connector.
delete_coexistence_profile	Deletes the coexistence profile of user.
list_coexistence_connectors	Lists all configured coexistence connectors.
list_coexistence_profiles	Lists the users configured with a coexistence profile.
list_coexistence_status	Reports the status of the containers and users involved in the coexistence. By default this command outputs the status of calendars, address books,email inboxes as well as of the users configured for coexistence. One can restrict the information being returned by specifying one or more of the optional parameters.
modify_coexistence_connector	Modifies the configuration of a coexistence connector.
modify_coexistence_profile	Specifies the coexistence profile of a user.

Table 2–6 Category: configuration

Utility	Function
activate_configuration	Saves proposed configuration and activate it.
add_blocked_device	Creates a blocked device. The system object identifier of the resulting object needs to be added to the 'DeviceManagementService' system object, using modify_property command, to block this device from accessing Beehive Mobile Services.
add_coexistence_connector	Configures a new coexistence connector.
add_dmz_home_instance	Creates configuration for a Beehive installation in the DMZ that is, outside the firewall.
add_external_bpel_pm	Creates system model objects for External BPEL process manager and a corresponding Bpel Cluster
add_urm	Configures an agent for a Universal Records Management instance.
add_virus_scan_engine	Adds a new virus scan engine to the collection of engines configured for the Site. If this is the first scan engine being added, this command will create a new collection for the Site and add the virus scan engine to it.
append_value	Appends the specified value to the existing value of the named property. If the named property value is cleared before executing this command, then after executing this command it will contain the new value.
clear_proposed_configuration	Clears proposed configuration of the Beehive system object model
clone_midtier	Top level clone command that clones a Oracle Beehive Application tier.
clone_oc4j_instance	Creates a new oc4j instance by cloning the given oc4j instance.
clone_preparation	Prepares the existing oracle home for cloning.

Table 2–6 (Cont.) Category: configuration

Utility	Function
clone_site	Top level clone command that clones a Oracle Beehive Application tier in a new deployment (i.e., site). This command is part of the Deployment Cloning solution. Please see the administrator guide for details.
delete_coexistence_connector	Deletes a coexistence connector.
delete_dmz_home_instance	Removes configuration for a Beehive installation in the DMZ that is, outside the firewall.
delete_property	Clears the value of specified property in the configuration object identified by specified id.
delete_virus_scan_engine	Deletes specified virus scan engine from the collection of engines configured for the Site. If this is the last scan engine being deleted, this command will also delete the virus scan engine collection and update the Site to remove the virus scan engine collection from it. Either the scan_engine option or the hostname and port options will need to be specified.
download_language_pack	Exports language pack resources managed by the Beehive deployment. The exact resources exported and the output destination details are controlled by command options.
list_bootstrap_configuration	Displays bootstrap configuration for local Oracle Beehive Application tier.
list_components	Lists components in the configuration repository.
list_configuration_versions	Lists all available configuration versions and activation time information
list_connection_pools	Lists available connection pools in the system.
list_language_pack	Displays details of the language pack resources managed by the Beehive deployment.
list_ports	Lists various available ports.
list_properties	Prints property value of a component given a component identifier and property name. If property name is not specified then all the properties will be listed.
list_property_metadata	Lists the metadata about all the properties of a system model object.
list_trusted_identity	This commands lists the trusted identities. The type has to be specified. For type SES, it lists the names of the trusted entities.
modify_beectl	This command updates the beectl file with the given oracle home & perl home
modify_bootstrap_configuration	Modify the connect string or credentials for the central configuration repository also known as bootstrap database. Misconfiguration will result in Oracle Beehive Application tier and site being not operable.
modify_coexistence_connector	Modifies the configuration of a coexistence connector.
modify_connection_pool	Modifies the connection pool configuration.
modify_database	Modifies given database configuration.
modify_hostname	Modifies the configuration repository for hostname of the system and updates required configuration files.
modify_local_configuration_files	This command updates configuration files local to current Oracle Beehive Application tier with activated changes to centralized configuration. It can restart one or more components on current Oracle Beehive Application tier if needed to make the changes take effect. Some updates to local configuration files require this command to restart all Oracle Beehive Application tier components.
modify_port	Modifies various ports.
modify_property	Modifies the value(s) of a named property of the component identified by --component. Multiple values can be set for one property.
modify_search	Create system model objects for Search and configure them
modify_secure_property	This command updates the sensitive property of the system model object identified by the --component.

Table 2–6 (Cont.) Category: configuration

Utility	Function
modify_virus_scan_policy	Modifies the virus scan policy configured for the Site. Valid values for the scan policy are: NO_SCAN_OR_REPAIR, SCAN_ONLY, SCAN_AND_REPAIR. Default is NO_SCAN_OR_REPAIR.
upload_language_pack	Loads language pack resources into the system.
validate_configuration	Validates the configuration for given component id or for the whole system model tree.
validate_virus_scan_engine_connectivity	Tests the connectivity to the virus scan engine running at the specified host and port.

Table 2–7 Category: contents

Utility	Function
add_filesystem_reference	Creates a reference in Beehive to a directory on the file system.
delete_filesystem_reference	Removes a file system reference from Beehive.
import_documents	Imports documents into Beehive from files on the server without copying the file content. Data on the server files will be treated as read-only; should an imported document be edited in Beehive, a copy of the content will be made at that time.
list_filesystem_references	Lists the file system path, read-only status, and identifier of all available file system references.

Table 2–8 Category: devices

Utility	Function
add_blocked_device	Creates a blocked device. The system object identifier of the resulting object needs to be added to the 'DeviceManagementService' system object, using <code>modify_property</code> command, to block this device from accessing Beehive Mobile Services.
add_device_command	Creates a device command for a given device.
delete_device_profile	Deletes the device profile with the given identifier. The command can also optionally delete all the device types associated with this device profile.
delete_device_type	Deletes the device type with the given identifier.
download_device_logs	Downloads the logs for a device. This command can either all log files for a device or all log files for a given application on the device or a particular log file.
download_syncml_messages	Downloads SyncML messages.
download_syncml_sessions	Downloads SyncML messages.
list_device_commands	Lists the device commands for a given device. The list can be further filtered by specifying the status of the device command.
list_device_logs	Lists the device logs for a given device.
list_device_profiles	Lists all the device profiles.
list_device_types	Lists all the device types.
list_devices	Lists the devices for a user.
upload_device_profiles	Uploads device profiles to the repository. An XML file or a directory containing XML files can be used as the source for the device profiles. The file can also contain device types and device profile schema.

Table 2–9 *Category: language packs*

Utility	Function
download_language_pack	Exports language pack resources managed by the Beehive deployment. The exact resources exported and the output destination details are controlled by command options.
list_language_pack	Displays details of the language pack resources managed by the Beehive deployment.
upload_language_pack	Loads language pack resources into the system.

Table 2–10 *Category: messaging*

Utility	Function
modify_email_port	Modifies Email service' SMTP or IMAP port number
modify_email_queue	Enables or disables Email asynchronous queue processing

Table 2–11 *Category: organizations*

Utility	Function
add_organization	Creates an organization in the given scope
delete_organization	Deletes an existing organization
list_enterprises	Lists all enterprises and prints names and identifiers
list_organizations	Lists organizations in the given scope
modify_enterprise	Modifies an existing enterprise
modify_organization	Modifies an existing organization

Table 2–12 *Category: policies*

Utility	Function
add_event_subscription	Creates an event subscription using data in an XML file.
add_policy	Creates a policy using data in an XML file.
add_policy_schema	Creates a policy schema using data in an XML file.
add_policy_template	Creates a policy template using data in an XML file.
delete_event_subscription	Deletes an event subscription from the Oracle Beehive repository.
delete_policy	Deletes a policy.
delete_policy_action	Deletes a policy action.
delete_policy_schema	Deletes a policy schema.
delete_policy_template	Deletes a policy template.
export_policy	Exports policy data into an XML file.
list_events	Lists all business object events.
list_policies	Lists policies in a specific container. Details returned include policy names and identifiers.
list_policy_actions	Lists all policy actions.
list_policy_schemas	Lists policy schemas in the current enterprise. Details returned include policy schema names and identifiers.
list_policy_templates	Lists policy templates in a specified container. Details returned include policy template names and identifiers.
modify_policy	Modifies an existing policy using data in an XML file.
modify_policy_schema	Modifies an existing policy schema using data in an XML file.
modify_policy_template	Modifies an existing policy template using data in an XML file.

Table 2–13 Category: process control

Utility	Function
modify_search_engine	Starts or stops the search crawl process for a specific source type
restart	Manages OC4J Instances, Beehive Transport Infrastructure Monitors and Oracle HTTP servers components. The command "beectl status" displays the component id and the status of these manageable components.
start	Manages OC4J Instances, Beehive Transport Infrastructure Monitors and Oracle HTTP servers components. The command "beectl status" displays the component id and the status of these manageable components.
status	Displays the status of all managed components.
stop	Manages OC4J Instances, Beehive Transport Infrastructure Monitors and Oracle HTTP servers components. The command "beectl status" displays the component id and the status of these manageable components.

Table 2–14 Category: real time

Utility	Function
add_conference	Creates conference artifact under workspace
add_conference_template	Creates conference-template artifact under workspace
delete_conference	Deletes conference artifact under workspace
delete_conference_template	Deletes conference template artifact under workspace
list_conference_templates	Lists conference-template artifacts under workspace
list_conferences	Lists conference artifacts under workspace
list_my_conferences	Lists conference artifacts under workspace

Table 2–15 Category: records

Utility	Function
add_record	Adds a record or non-record.
delete_record	Deletes a record or non-record.
list_file_plan	Lists the file plan.

Table 2–16 Category: resources

Utility	Function
add_resource	Creates a new resource.
delete_resources	Deletes a resource.
list_resources	Lists resources.
modify_resource_classifications	This command set the given category as resource root classification.
modify_resources	Modifies an existing resource.

Table 2–17 Category: security

Utility	Function
add_trusted_identity	This commands registers a trusted identity. There are two types of trusted identities: WSSEC and SES. Default type is WSSEC. For WSSEC type, please make sure that the service has a valid certificate registered in the wallet and the correct associated key alias is passed into this command. This command also creates the principal(s) associated with this trusted identity in the Beehive system. On the other hand, for SES type, this command stores the given trusted identity name and password information.
delete_trusted_identity	This commands unregisters a trusted identity. If the type of identity is not specified, it is defaulted to WSSEC.
modify_trusted_identity	This commands modifies the details of the trusted identity. At least one of the options new_service_name or new_key_alias need to be specified for this modification if the type is WSSEC. If the type of identity is not specified, it is defaulted to WSSEC.

Table 2–18 Category: subscription

Utility	Function
add_user_subscription	Creates a user subscription from a pre-defined rule in a subscription template.
modify_user_subscription	Enables or disables an existing subscription

Table 2–19 Category: templates

Utility	Function
modify_notification_template	Modifies a specified notification template for the Notification service.

Table 2–20 Category: time management

Utility	Function
export_icalendar	Export invitations and assignments from a calendar and/or tasklist to an iCalendar file.
import_icalendar	Import an iCalendar file to an existing calendar and/or tasklist. If an iCalendarObject has a UID that already exists in the destination calendar and/or tasklist it will be re-created. VCALENDAR components can have many VEVENT and VTODO sub-components with different UIDs but sub-components of the same UID must be consecutive. A VCALENDAR component imported with a METHOD:X-ORACLE-DELETE will cause all sub-components to be deleted.
list_calendars	Lists the existing calendars of a user, resource or workspace.
list_tasklists	Lists existing tasklists of a user, resource or workspace.

Table 2–21 Category: time zones

Utility	Function
import_timezones	Imports time zone definitions to the database.
list_timezones	Lists time zones in the database. The list can be limited by common time zones or by time zone names.
modify_timezones	Modify a time zone.

Table 2–22 Category: users

Utility	Function
add_custom_user_property	The <code>add_custom_user_property</code> command adds custom user properties.
add_directory_profile	The <code>add_directory_profile</code> command adds a new directory profile.
add_external_contact	The <code>add_external_contact</code> command adds new external contact.
add_group	The <code>add_group</code> command adds new groups. The group information is supplied in an XML file.
add_preference_profile	The <code>add_preference_profile</code> command adds a new preference profile and associates it with a consumer. There can be only one preference profile for a consumer.
add_preference_property	The <code>add_preference_property</code> command adds a new preference property to a preference set.
add_preference_set	The <code>add_preference_set</code> command adds a preference set to a preference profile.
add_user	The <code>add_user</code> command adds new users. The user information is supplied either on command line or in an XML file.
delete_coexistence_profile	Deletes the coexistence profile of user.
delete_custom_user_property	The <code>delete_custom_user_property</code> command deletes a custom property. If there are multiple custom properties with same name, then only the first occurrence of the attribute with specified name is deleted. Any values of the property being deleted will also be deleted.
delete_directory_profile	The <code>delete_directory_profile</code> command deletes a directory profile.
delete_external_contact	The <code>delete_external_contact</code> command deletes an external contact with an option to purge.
delete_group	The <code>delete_group</code> command deletes a group with an option to purge.
delete_preference_profile	The <code>delete_preference_profile</code> command deletes a preference profile.
delete_preference_property	The <code>delete_preference_property</code> command deletes a preference property from a preference set.
delete_preference_set	The <code>delete_preference_set</code> command deletes a preference set.
delete_user	The <code>delete_user</code> command deletes a user with an option to purge.
download_ldap_group_data	The <code>download_ldap_group_data</code> command downloads groups information for an external directory into an XML file. The generated XML file can be used with <code>add_group</code> command to create the groups.
download_ldap_user_data	The <code>download_ldap_user_data</code> command downloads user information for an external directory into an XML file. The generated XML file can be used with <code>add_users</code> command to create the users.
list_coexistence_profiles	Lists the users configured with a coexistence profile.
list_custom_user_properties	The <code>list_custom_user_properties</code> command lists all custom properties of users.
list_directory_profiles	The <code>list_directory_profiles</code> command lists directory profiles in an XML file.
list_external_contacts	The <code>list_external_contacts</code> command lists contacts that match specified search criteria. If search criteria are not specified, then all contacts are listed. It also lists the details of the contact(s) whose identifier is specified.
list_groups	The <code>list_groups</code> command lists groups that match specified search criteria. If search criteria are not specified, then all groups are listed.
list_max_address_count	The <code>list_max_address_count</code> command lists the maximum number of addresses of an address type that can be set for a given person-contact, group-contact or resource-contact in an address-book. The address types determine the type of address like BUSINESS, PERSONAL and OTHER. This command also lists the system defined maximum limit, which cannot be exceeded.
list_preference_profiles	The <code>list_preference_profiles</code> command lists preference profiles for a consumer.

Table 2–22 (Cont.) Category: users

Utility	Function
list_preference_properties	The list_preference_properties command lists all effective preference properties of a preference set.
list_preference_sets	The list_preference_sets command lists all preference sets for a preference profile.
list_users	The list_users command lists users that match specified search criteria. If search criteria are not specified, then all users are listed.
modify_change_number	Modifies the change log number of a profile.
modify_coexistence_profile	Specifies the coexistence profile of a user.
modify_directory_profile	The modify_directory_profile command modifies an existing directory profile. Modification to the profile name cannot be done.
modify_external_contact	The modify_external_contact command modifies existing external contact.
modify_group	The modify_group command modifies a group. The group information is supplied in an XML file.
modify_max_address_count	The modify_max_address_count command modifies maximum number of addresses of an address type that can be set for a given person-contact, group-contact or resource-contact in an address-book. The address types determine the type of address like BUSINESS, PERSONAL & OTHER. The maximum count specified in this command must be less than the system defined maximum limit, which can be determined by running list_max_address_count command.
modify_preference_set	The modify_preference_set command modifies the preference set by setting the extends from attribute.
modify_user	The modify_user command modifies existing users.
validate_directory_entry	Validates the directory entry in ldap with corresponding entry in beehive. The directory entry can be of type user, group or external person. The command provides an option to correct any data inconsistencies by applying necessary changes in beehive. The state of the profile specified in this command can either be ENABLE or DISABLE.

Table 2–23 Category: utilities

Utility	Function
export_errorcodes	Search for occurrences of error codes
export_filesystem_logs	Search log files stored on host machines.
export_logs	With an option of refreshing the repository first, query the repository to get relevant log records from log files stored on host machines.
list_command_metadata	Lists all the metadata about given command.
list_commands	Lists the command names based on the given criteria.
list_errorcode_catalog	List all error code definitions in beehive.
list_statistics	Lists the statistics for a given type or system object or for the entire site (default).
list_supported_entity_types	Prints the supported entity types which can be used in business object distinguished naming pattern instead of system generated identifier and their description.
obfuscate	Obfuscates the prompted string.
version	This command shows the version information of the Beehive products.

Table 2–24 *Category: workflows*

Utility	Function
add_workflow_schema	Deploys a workflow and seeds workflow information.
add_workflow_template	Creates a workflow template using data in an XML file.
delete_workflow_schema	Deletes a workflow schema.
delete_workflow_template	Deletes a workflow template.
export_workflow_template	Exports a workflow template into an XML file.
list_workflow_schemas	Lists workflow schemas.
list_workflow_templates	Lists workflow templates deployed in a container. Details returned include workflow template names and identifiers.
list_workflows	List all workflows for which the active user has privileges. Specify user and status options for filtering.

Table 2–25 *Category: workspace*

Utility	Function
add_category	Creates a category at the enterprise scope
add_category_application	Applies a category on a given entity
add_category_configuration	Creates a category configuration on the given scope or heterogeneous folder.
add_team_workspace	Creates a team workspace from a template
add_version_configuration	Creates a version configuration on the given scope or heterogeneous folder.
add_workspace_template	Creates a workspace template in an organization or enterprise
delete_category	Deletes a category and all category applications.
delete_category_application	Removes a category from an entity
delete_category_configuration	Deletes a given category configuration.
delete_team_workspace	Deletes an existing team workspace
delete_version_configuration	Deletes a given version configuration.
delete_workspace_template	Deletes an existing workspace template
download_workspace_template_schema	Downloads workspace template XML schema to a file
list_categories	Lists the categories in the enterprise.If the recurse option is used then sub-categories are also listed.
list_category	Prints information about a category given a category identifier
list_category_configuration	Lists the category configuration on the given scope or heterogeneous folder.
list_version_configuration	Lists the version configuration on the given scope or heterogeneous folder.
list_workspace_templates	Lists all workspace templates
list_workspaces	Lists workspaces in an organization or enterprise
modify_category	Modifies an existing category
modify_category_configuration	Updates a given category configuration.
modify_personal_workspace	Modifies an existing personal workspace
modify_team_workspace	Modifies an existing team workspace
modify_version_configuration	Updates a given version configuration.
modify_workspace_template	Modifies an existing workspace template

Common Options

The beectl command options can be broken down into two types: common options, and command specific options. This section describes common options that can be used with any beectl command.

The following is a complete list of common options for all beectl commands:

--format

Specify the output format type. Valid options are `multiline`, `xml`, `table`, and `tilled`. The default format is `multiline`.

--separator

Specify the separator to use when formatting an output type of `tilled` with the **--format** option. Any character may be used as a separator. The default separator is `"|"`.

--entity_format

Specify display format of the entity. Valid entity format options are `name`, `id`, and `name_and_id`. Default format is `name`.

--timezone_id

Specify the time zone to use if any date and time information is returned by the command. To determine a time zone ID, use the `list_timezones` command.

--no_confirmation

Allow the command to be executed without prompting for any confirmation. This option applies only to remove and delete commands.

--version

Print the version information of a beectl command. This option does not require an argument.

--help

Print a usage message.

--log_level

Specify the logging level. Valid arguments for this option are: `FINEST`, `FINER`, `FINE`, `CONFIG`, `INFO`, `WARNING`, `SEVERE`, `ERROR`, `INTERNAL_ERROR`, `NOTIFICATION`, and `TRACE`. If no log level is specified, the default, `INFO`, will be used. This option cannot be used while in shell mode or batch mode. Specify the option when invoking either mode.

--logdir

Specify the full path to the log directory. The default value is `ORACLE_HOME/bee hive/logs/beectl/`. This option cannot be used while in shell mode or batch mode. Specify the option when invoking either mode.

--batchfile

Specify the full path and file name of a batch file. Commands and options can be specified in a file and passed with this option for batch processing.

--continue

Force Oracle Beehive to continue with the next command when using the **--batchfile** option. The next command will be executed regardless of the exit code of the previous command.

--activate_configuration

Commands that deal with updating the system object model make use of this option to determine if they need to save their modification to the configuration system.

--no_wrap

If specified, the cell values in the tabular format output of a command will not be wrapped.

--no_stagger

If specified, the columns of the tabular format output of a command will not be staggered.

--column_format

Specify customized column format string. For example, 10%10%20%. This option is applicable only to commands that have tabular output. If not specified or an incorrect value is specified, it will be ignored, and the maximum content length for each column will be used to set column width.

--terminal_width

Modify the default terminal width. By default, the terminal width is 80 characters.

--obfuscated

Specify this option when all passwords passed with the command are obfuscated.

--authuser

Specify the user name for beectl commands requiring authentication.

--authpassword

Specify the user password for the user specified with the **--authuser** option. The argument for this option must be obfuscated using the **--obfuscated** if passed on the command line.

Notes: Option arguments should not start with a hyphen (-). If an option argument needs to start with hyphen, use one of the following options:

- Use the *<option name>= <option value>* format; this is the preferred way to specify option values starting with hyphens.
- Prefix the option value with string `ESCAPE:`.
- Prefix the option value with an escaped backslash (`\`). This is the least preferred way. This may not work in some operating systems; it does not work in Microsoft Windows.

Option values should not contain the any special characters (such as *, \$, and %). If an option value contains a special character, then enclose the option value in double quotes (").

System Object Identifiers

System model objects in the system model can be uniquely identified with the following mechanisms:

System Object Identifier

A unique identifier assigned to each system model object at the time of creation. The system object identifier is read-only and it cannot be changed. For example, 8ae5c0e8-02c8-429e-9773-186e6a79997b.

Built-In Alias

A unique, built-in alias is assigned to certain system model objects at the time of creation. Built-in alias names are read-only and it cannot be changed. For example, `_CURRENT_SITE` refers to the current site system model object and `_CURRENT_ENTERPRISE` refers to the current enterprise system model object.

User Defined Alias

You can assign a unique user defined name to each system model object. Oracle Beehive ensures that all user defined aliases are unique. The user defined alias are mutable and can be modified at any point of time. For example, `oracle_smtp_service` can refer to an SMTP service system model object.

Encoded System Object Identifier

To refer to a system model objects that lies deep in the system model hierarchy, use the following syntax:

```
<unique ID>[:<property name>][:<property name>][:<property name>]
```

`<unique ID>` is a system object identifier, built-in alias, or user defined alias of a system model object, and `<property name>` is a valid property name of the preceding model object. The type of property should be a system model object.

For example, the following command list the properties of the logging properties of the database of the current site:

```
beectl list_properties --component _CURRENT_SITE:Database:LoggingProperties
```

Providing Secure Values

The following are the available methods to provide secure values, such as passwords, to a command:

Prompt

Only provide the option (without providing the secure value). The beectl tool will prompt you for the secure value. Some commands may ask you to reconfirm the secure value.

Obfuscate

Obfuscate the secure value with the [obfuscate](#) command. Use the obfuscated value for the option that requires the secured value along with the common option `--obfuscated`.

Clear Text

To provide secure values in clear text, run commands in beectl shell mode.

Tabular Output

The following options allow you to control the display of tabular output:

--no_wrap

Specify that content wrapping will not be applied to cell values.

--no_stagger

Specify that columns will not be staggered. By default, columns will not be staggered if there are three or less columns.

--column_format

Specify the column widths (in chars) for each column. This value will be ignored if number of columns given in this option do not match the number of columns in the resultant table. The following is an example of this option:

```
beectl list_property_metadata
--type ManagementService
--full_report
--column_format 10%10%10%10%10%
```

Property name	Property Type	Metadata	Short description	Long description
AutoSyncSaveListener	int	Not ReadOn ly-Mutable	[Short description k	[Long description ke
SleepIntervalInSeconds		-Mandatory	ey not set .]	y not set.]
...				

You may not specify this option with **--no_stagger** or **--no_wrap**.

--terminal_width

Specify the terminal width of the terminal in which you are running the beectl tool. Specify this option if you have resized your terminal to more than 80 character widths and you want the command output to fit the entire width of your terminal. The Default (minimum) value for terminal width is 80.

Boolean Values

If an option requires a boolean value (either `true` or `false`), and you specify the option without specifying a value, the command assumes a value of `true` for the option.

activate_configuration

Saves proposed configuration and activate it.

SYNTAX

```
beectl activate_configuration
```


OPTIONS

This command has no options

EXAMPLES

```
beectl activate_configuration
```

add_assigned_role

Creates an AssignedRole entity.

SYNTAX

```
beectl add_assigned_role [--scope <unique identifier of the Scope>] --name <name
of AssignedRole> [--description <description>] --assigned_scope <assigned_unique
identifier of the Scope> --role_definition <unique identifier of the
RoleDefinition> [--accessor <unique identifier of an Accessor>]...]
```

OPTIONS**--scope**

Specify the unique identifier of the Scope in which the AssignedRole should be created.

--name

Specify the name of the AssignedRole.

--description

Specify a description for the AssignedRole.

--assigned_scope

Specify the unique identifier of an assigned Scope for the AssignedRole.

--role_definition

Specify the unique identifier of an assigned RoleDefinition for the AssignedRole.

--accessor

Specify the unique identifier of an Accessor to add to the AssignedRole. This option can be specified more than once.

EXAMPLES

```
beectl add_assigned_role --scope
wkspace=MyWorkspace,enpr=MyEnterprise --name MyAssignedRole
--assigned_scope wkspace=MyWorkspace,enpr=MyEnterprise --role_
definition
acrd=MyRoleDefinition,wkspace=MyWorkspace,enpr=MyEnterprise
```

add_attendant

Adds an auto attendant or copies an existing one under a new name. When copying any prompts will also be copied.

SYNTAX

```
beectl add_attendant { --file <AAML file> | --name <new name> --copy_from  
<existing attendant> }
```

OPTIONS**--file**

An auto-attendant markup language file describing the attendant to be added. When specified, name and copy_from must be specified.

--name

Name to be given to copied attendant. When specified, copy_from must also be specified and file must not be specified

--copy_from

Name of attendant to copy. When specified, copy_from must also be specified and file must not be specified

EXAMPLES

```
beectl add_attendant --file example.aaml
```

```
beectl add_attendant --name copiedAttendant --copy_from  
someAttendant
```

add_audit_policy

Creates an audit policy from the XML file information

SYNTAX

```
beectl add_audit_policy --file <Full path of the input file>
```

OPTIONS**--file**

Full path name of the input XML file

EXAMPLES

```
beectl add_audit_policy --file /tmp/policy_ex.xml
```

add_audit_template

Creates an audit policy template from the XML file information

SYNTAX

```
beectl add_audit_template --file <Full path of the input file>
```

OPTIONS**--file**

Full path of the input file

EXAMPLES

```
beectl add_audit_template --file /tmp/templ_ex.xml
```

add_audit_trail

Creates an audit trail from the search result generated using the XML file

SYNTAX

```
beectl add_audit_trail --file <Full path of the input file>
```

OPTIONS**--file**

Full path name of the input XML file

EXAMPLES

```
beectl add_audit_trail --file /tmp/trail_ex.xml
```

add_blocked_device

Creates a blocked device. The system object identifier of the resulting object needs to be added to the 'DeviceManagementService' system object, using `modify_property` command, to block this device from accessing Beehive Mobile Services.

SYNTAX

```
beectl add_blocked_device --device <deviceid> [--description <description>]
```

OPTIONS**--device**

Specify the local device identifier.

--description

Describe why the device is being blocked.

EXAMPLES

```
beectl add_blocked_device --device 981214
```

add_category

Creates a category at the enterprise scope

SYNTAX

```
beectl add_category --file <Full path of the category XML file>
```

OPTIONS**--file**

Full path name of the XML file. The file must contain the properly formatted data to create the category

EXAMPLES

```
beectl add_category --file /tmp/category.xml
```

add_category_application

Applies a category on a given entity

SYNTAX

```
beectl add_category_application --category <Identifier of the category to be
applied> -- entity <Identifier of the entity to which the category needs to be
applied>
```

OPTIONS**--category**

Specify the identifier of the category.

--entity

Specify the identifier of an Oracle Beehive entity to which the category needs to be applied.

EXAMPLES

```
beectl add_category_application --category
catg=MyCategory,enpr=MyEnterprise --entity
adoc=MyDocument,flldr=MyFolder,wksp=MyWorkspace,enpr=MyEnterprise
```

add_category_configuration

Creates a category configuration on the given scope or heterogeneous folder.

SYNTAX

```
beectl add_category_configuration --container <Configuration scope or heterogenous
folder> --file <Full path of the configuration XML file>
```

OPTIONS**--container**

Scope or heterogeneous folder on which the category configuration should be defined.

--file

Full path of the category configuration XML file. The file must contain properly formatted data.

EXAMPLES

```
beectl add_category_configuration --container
orgn=MyOrganization,enpr=MyEnterprise --file
/tmp/configuration.xml
```

add_client_application_configuration

Creates a client application configuration object from a supplied input file. The resulting object will be used for client application provisioning.

SYNTAX

```
beectl add_client_application_configuration --file <path to the XML file>
```

OPTIONS**--file**

Specify the full path and name of the XML input file. The file should contain information about how to create a client application configuration.

EXAMPLES

```
beectl add_client_application_configuration --file
/tmp/app-config.xml
```

add_client_application_provisioning

Provisions client applications to a community.

SYNTAX

```
beectl add_client_application_provisioning --community <community identifier>
{--configuration <client application configuration identifier>... | --all | --none
| --patchset <Identifier of the client application patchset>}
```

OPTIONS**--community**

Specify the identifier of the community.

--configuration

Specify the identifier of the client application configuration. This option can be specified more than once.

--all

Specify this option to provision the latest patchset of all client applications to this community.

--none

Specify this option to deprovision any client applications provisioned earlier. The users belonging to this community would get the applications provisioned at the parent community level.

--patchset

Specify this option to provision the specified patchset to this community.

EXAMPLES

```
beectl add_client_application_provisioning --community
1234:5678:entr:2E0329B0705F0E40E040578C92160957000000000434
--configuration
1234:5678:capc:2E0329B0705F0E40E040578C92160957000000000434
--configuration
1234:5678:capc:2E0329B0705F0E40E040578C92160957000000000434

beectl add_client_application_provisioning --community
1234:5678:entr:2E0329B0705F0E40E040578C92160957000000000434
--all

beectl add_client_application_provisioning --community
1234:5678:entr:2E0329B0705F0E40E040578C92160957000000000434
--none

beectl add_client_application_provisioning --community
1234:5678:entr:2E0329B0705F0E40E040578C92160957000000000434
--patchset
21EC:0AE5:capp:406E6CD925A8F087E040578C921636E5000000000979
```

add_coexistence_connector

Configures a new coexistence connector.

SYNTAX

```
beectl add_coexistence_connector --name <name> [--url <url> | --use_secure_
connection <use_secure_connection> --host_name <host_name> --port <port_number>}
--sitekey [<obfuscated_sitekey> --obfuscated] [--timezone_alias_namespace
<timezone_alias_namespace>]
```

OPTIONS**--name**

Specify the name of the coexistence connector.

--url

Specify the URL of the coexistence connector.

--use_secure_connection

Specify whether "HTTPS" MUST be used.

--host_name

Specify the host name of the connector.

--port

Specify the port number used by the connector. Value MUST be an integer.

--sitekey

Specify the site key of the coexistence connector.

--timezone_alias_namespace

Specify the time zone alias namespace used by the connector.

EXAMPLES

```
beectl add_coexistence_connector --name MsExch2003_1 --url
http://www.example.com:7777 --sitekey
```

```
beectl add_coexistence_connector --name MsExch2003_1 --url
http://www.example.com:7777 --sitekey
5YD7Dj9/AIEgWuuAzmb7o5TULTVzqO31uby7ZcOfIY4j/mPAxT83nc8+7RK281jQ
--obfuscated
```

```
beectl add_coexistence_connector --name MsExch2003_1 --host_name
www.example.com --port 7777 --sitekey
```

add_conference

Creates conference artifact under workspace

SYNTAX

```
beectl add_conference --parent <Workspace identifier> --name <Conference name>
--template <Conference identifier>
```

OPTIONS**--parent**

Workspace identifier

--name

Conference name

--template

Conference identifier

EXAMPLES

```
beectl add_conference --parent
6490:45C8:wspr:F20E3F75004040B5AE14B64B96F89C3A000000000022
--name MyConference --template
6490:45C8:owct:B3EABD85714E4DBDA92201A54EAE56C3000000002C2C
```

add_conference_template

Creates conference-template artifact under workspace

SYNTAX

```
beectl add_conference_template --parent <Workspace identifier> --name <Conference name> --model <Conference or conference template identifier> --settings-xml-file <Conference settings XML file>
```

OPTIONS

--parent

Workspace identifier

--name

Conference name

--model

Conference identifier

--settings-xml-file

Conference settings XML file

EXAMPLES

```
beectl add_conference_template --parent
6490:45C8:wspr:F20E3F75004040B5AE14B64B96F89C3A000000000022
--name Template_from_template --model
6490:45C8:owct:B3EABD85714E4DBDA92201A54EAE56C30000000002C2C

beectl add_conference_template --parent
6490:45C8:wspr:F20E3F75004040B5AE14B64B96F89C3A000000000022
--name Template_from_xmlfile --settings-xml-file /tmp/default_
settings.xml sample settings file: <settings> <roles> <role>
<name>Guests</name> <accessors> <accessor_
id>2FD3:6B7D:user:42B3D7467840404AA8ABF34BAE421CC5000000000000</
accessor_id> </accessors> <properties> <property>
<name>chat.can_enable</name> <value>
<permission>GRANTED</permission> </value> </property>
</properties> </role> </roles> </settings>
```

add_custom_user_property

The add_custom_user_property command adds custom user properties.

SYNTAX

```
beectl add_custom_user_property --name <property_name> --type <property_type> [
--description <description> ]
```

OPTIONS

--name

Name of the custom property

--type

Type of the property. Supported types are BOOLEAN, COLLABID, DATETIME, DOUBLE, STRING.

--description

Description of the custom property.

EXAMPLES

```
beectl add_custom_user_property --name employeenumber --type
DOUBLE
```

add_device_command

Creates a device command for a given device.

SYNTAX

```
beectl add_device_command --device <identifier of the device> --action <device
command action>
```

OPTIONS**--device**

Specify the identifier of the device. Use list_devices command to determine the identifier of the device.

--action

Specify the action of the device command. The following are the valid command actions: UPLOADLOG UPLOADCONFIG CHECKUPDATE WIPEOUT .

EXAMPLES

```
beectl add_device_command --device
1234:5678:devi:2E0329B0705F0E40E040578C92160957000000000434
--action CHECKUPDATE
```

add_directory_profile

The add_directory_profile command adds a new directory profile.

SYNTAX

```
beectl add_directory_profile --file <filename> [ --no_validate ]
```

OPTIONS**--file**

XML file containing directory profile.

--no_validate

Skips the validation of profile.

EXAMPLES

```
beectl add_directory_profile --file MyDirectoryProfile.xml  
beectl add_directory_profile --file MyDirectoryProfile.xml --no_validate
```

add_dmz_home_instance

Creates configuration for a Beehive installation in the DMZ that is, outside the firewall.

SYNTAX

```
beectl add_dmz_home_instance --hostname <hostname> --bti_unique_id <unique id for  
BTI on this oracle home> --no_of_client_workers <number of client workers>  
[--oracle_home <oracle home path>] [--opmn_request_port <OPMN request port>]  
[--opmn_remote_port <OPMN remote port>] [--bti_server_port <BTI server port>]  
[--instance_name <instance name>]
```

OPTIONS**--hostname**

Host name of the machine.

--oracle_home

oracle home path.

--bti_unique_id

The site-wide unique identifier of BTI installed on the DMZ host. Please specify the value which is present in the oracle_home/bee hive/conf/bti.properties file on the DMZ host.

--no_of_client_workers

This is the number of MX processes in the DMZ Oracle Beehive Application tier. The value of this parameter should be the value of "NumberOfClientWorkers" in \$OH/bee hive/conf/bti.properties in DMZ Oracle Beehive Application tier.

--opmn_request_port

OPMN request port

--opmn_remote_port

OPMN remote port

--bti_server_port

The server port.

--instance_name

instance name of DMZ Oracle Beehive Application tier

EXAMPLES

```
beectl add_dmz_home_instance --hostname dmzhost.example.com  
--bti_unique_id 813130873 --no_of_client_workers 4
```

add_event_subscription

Creates an event subscription using data in an XML file.

SYNTAX

```
beectl add_event_subscription --file <full path to the event subscription xml
file>
```

OPTIONS

--file

Specify the absolute path of the XML file that contains data to create the event subscription.

EXAMPLES

```
beectl add_event_subscription --file
/private/xml/MyEventSubscription.xml
```

add_external_bpel_pm

Creates system model objects for External BPEL process manager and a corresponding Bpel Cluster

SYNTAX

```
beectl add_external_bpel_pm --oc4j_instance_name <name> --oc4j_admin_password
<obfuscated password> --domain <domain name> --domain_password <obfuscated domain
password> --OBFUSCATED --bpel_application_name <bpel application name> --bpel_
admin_password <obfuscated bpel administrator password> --host_name
<hostname>--opmn_port<opmn request port>
```

OPTIONS

--oc4j_instance_name

OC4J instance name.

--oc4j_admin_password

OC4J admin password.

--bpel_admin_password

Bpel administrator password.

--domain

Domain id of the BPEL process

--domain_password

Domain password of the bpel process manager.

--bpel_application_name

Bpel application name.

--host_name

Host name of the machine.

--opmn_port

The OPMN Request Port to administer AS11g managed Oc4j.

EXAMPLES

```
beectl add_external_bpel_pm --oc4j_instance_name oc4j_soa
--oc4j_admin_password pwd234 --domain domain.com--domain_
password pwdefrfrfr4 --bpel_application_name orabpel --bpel_
admin_password pwdefrfrfrfrf --host_name host.example.com
--opmn_port 1243
```

add_external_contact

The add_external_contact command adds new external contact.

SYNTAX

```
beectl add_external_contact    --family_name <[locale:]family name>    [ --family_
name <[locale:]family name> ... ]    [ --scope <identifier of contacts parent> ]
[ --given_name <[locale:]given name> ... ]    [ --display_name <[locale:]display
name> ... ]    [ --middle_name <[locale:]middle name> ... ]    [ --job_title
<[locale:]job title> ... ]    [ --prefix <[locale:]prefix> ... ]    [ --suffix
<[locale:]suffix> ... ]    [ --nick_name <[locale:]nick name> ... ]    [ --office_
location <office location of the contact> ]    [ --company <company of the
contact> ]    [ --profession <profession of the contact> ]    [ --timezone <time
zone of the contact> ]    [ --locale <locale of the contact> ]    [ --department
<department of the contact> ]    [ --organization <organization identifier> ... ]
[ --property <name(assistant|profession|certificate|notes)=value=description> ...
]    [ --address <type of address(business_1|other_5|personal_4|proxy_
1|...):scheme(im|mailto|...):value> ... ]    [ --default_address_for_type <type of
address(business_1|other_5|personal_4|proxy_1|...):scheme(im|mailto|...):value> ]
[ --default_address_for_scheme <type of address(business_1|other_5|personal_
4|proxy_1|...):scheme(im|mailto|...):value> ]    [ --primary_address <type of
address(business_1|other_5|personal_4|proxy_1|...):scheme(im|mailto|...):value> ]
```

OPTIONS**--family_name**

Family name of the contact in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--scope

Identifier of the enterprise under which this contact will be created.

--given_name

Given name of the contact in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--display_name

Display name of the contact in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--middle_name

Middle name of the contact in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--job_title

Job title of the contact in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--prefix

Prefix of the contact in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--suffix

Suffix of the contact in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--nick_name

Nick name of the contact in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--office_location

Office location of the contact.

--company

Company of the contact.

--profession

Profession of the contact.

--timezone

time zone of the contact. list_timezones lists the valid time zones

--locale

Locale details of the contact. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--department

Department of the contact.

--organization

Identifiers of the organizations the contact belongs to.

--property

Details of the property in the format name=value=description. Supported names are certificate, assistant, profession and notes. Note, no equals to symbol(=) should be present in the name or value or description.

--address

Address of the contact in the format type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--default_address_for_type

Address of the contact in the format type:scheme:value. Sets the specified address as the default for the specified type. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--default_address_for_scheme

Address of the contact in the format type:scheme:value. Sets the specified address as the default for the specified scheme. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--primary_address

Primary address of the contact in the format type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

EXAMPLES

```
beectl add_external_contact --family_name Contact1FamilyName
--scope enpr=example
```

```
beectl add_external_contact --family_name Contact1FamilyName
--given_name Contact1GivenName --display_name "Contact1
GivenName" --organization orgn=contact1orgn,enpr=contact1enpr
```

```
beectl add_external_contact --family_name Contact1FamilyName
--scope enpr=example --address BUSINESS_
1:mailto:contact1@example.com --address BUSINESS_2:fax:121345222
```

```
beectl add_external_contact --family_name Contact1FamilyName
--scope enpr=example --property prop1:prop1Value
```

add_filesystem_reference

Creates a reference in Beehive to a directory on the file system.

SYNTAX

```
beectl add_filesystem_reference --name <file system reference name> --filesystem_
path <Server path> --read_only <true or false>
```

OPTIONS

--name

Name to give to this file system reference.

--filesystem_path

Fully-qualified path on the file system to which this reference should point.

--read_only

Whether the referenced file system directory should be treated as read-only by Beehive.

EXAMPLES

```
beectl add_filesystem_reference --name MyFilesystemReference
--filesystem_path /usr/local/bin --read_only true
```

add_group

The add_group command adds new groups. The group information is supplied in an XML file.

SYNTAX

```
beectl add_group --file <filename> [ --ldapbootstrap ]
```

OPTIONS

--file

Filename of the XML file containing group definition.

--ldapbootstrap

LDAP bootstrap flag. If this flag is specified, then uds groups will be created with directory locator and directory id. This is relevant only when --file option is used.

EXAMPLES

```
beectl add_group --file MyGroup.xml
```

```
beectl add_group --file MyGroup.xml --ldapbootstrap
```

add_local_ace

Adds an Access Control Entry (ACE) to an entity's Local Access Control List (LACL).

SYNTAX

```
beectl add_local_ace --entity <unique identifier of the entity> --accessor <unique
identifier of the Accessor> [--access_types <access types string>]
```

OPTIONS

--entity

Specify the unique identifier of the entity to which the ACE will be added.

--accessor

Specify the Accessor to whom the access types will apply.

--access_types

Specify the access types string for the Accessor.

EXAMPLES

```
beectl add_local_ace --entity
adoc=MyDocument,wksp=MyWorkspace,enpr=MyEnterprise --accessor
loginid=MyUser --access_types +RW-D
```

add_organization

Creates an organization in the given scope

SYNTAX

```
beectl add_organization --name <Organization name> --scope <Identifier of
enterprise or organization>
```

OPTIONS

--name

Name of the organization

--scope

Identifier of the parent scope (enterprise or organization)

EXAMPLES

```
beectl add_organization --name Sample_organization --scope
9941:2345:enpr:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

add_policy

Creates a policy using data in an XML file.

SYNTAX

```
beectl add_policy --file <full path to the policy xml file>
```

OPTIONS**--file**

Specify the absolute path of the XML file that contains the policy data.

EXAMPLES

```
beectl add_policy --file /private/xml/MyPolicy.xml
```

add_policy_schema

Creates a policy schema using data in an XML file.

SYNTAX

```
beectl add_policy_schema --file <full path to the policy schema xml file>
```

OPTIONS**--file**

Specify the absolute path of the XML file that contains the policy schema data.

EXAMPLES

```
beectl add_policy_schema --file /private/xml/MyPolicySchema.xml
```

add_policy_template

Creates a policy template using data in an XML file.

SYNTAX

```
beectl add_policy_template --file <full path to the policy template xml file>
```

OPTIONS**--file**

Specify the absolute path of the XML file that contains the policy template data.

EXAMPLES

```
beectl add_policy_template --file  
/private/xml/MyPolicyTemplate.xml
```

add_preference_profile

The add_preference_profile command adds a new preference profile and associates it with a consumer. There can be only one preference profile for a consumer.

SYNTAX

```
beectl add_preference_profile --consumer <identifier> --name <profile-name> [
--description <description> ]
```

OPTIONS**--consumer**

Identifier of the consumer

--name

Name of the preference profile to be created.

--description

Description of preference profile.

EXAMPLES

```
beectl add_preference_profile --consumer loginid=user1 --name
MyProfile
```

add_preference_property

The add_preference_property command adds a new preference property to a preference set.

Supported types are :

IDENTIFIABLE

IDENTIFIABLE_LIST

STRING

STRING_LIST

INTEGER

INTEGER_LIST

BOOLEAN

BOOLEAN_LIST

DATE

DATE_LIST

URI

URI_LIST

FLOAT

FLOAT_LIST

SYNTAX

```
beectl add_preference_property --set <identifier> --name <property-name> --type
<string | date | ... | identifiable> [ --value <property-value> ] [ --file
<file-name> ] [ --final ]
```

OPTIONS

--set

Identifier of the preference set specified in id format, which can be determined by running list_preference_sets command with "--entity_format id" option.

--name

Name of the preference property.

--type

Type of preference property.

--value

Value of preference property.

--file

File name for business hours type preference property.

--final

Whether the preference property be overridden in extended property.

EXAMPLES

```
beectl add_preference_property --set
5965:3658:prfs:B7CAC0E31E554593B7A93B24B0FD09F2000000000979
--name MyProperty --type integer --value 100 --final

beectl add_preference_property --set
5965:3658:prfs:B7CAC0E31E554593B7A93B24B0FD09F2000000000979
--name MyProperty --type integer_list --value 100 --value 200
--value 300 --final
```

add_preference_set

The add_preference_set command adds a preference set to a preference profile.

SYNTAX

```
beectl add_preference_set --parent <preference-profile-identifier> --name
<preference-set-name> [ --extends <preference-set-identifier> ]
```

OPTIONS

--parent

Identifier of the preference profile to which the preference set is added.

--name

Name of the preference set.

--extends

Identifier of the preference set from which the new preference set is extended.

EXAMPLES

```
beectl add_preference_set --parent prfp=MyProfile,loginid=user1
--name MyPreferenceSet
```

add_record

Adds a record or non-record.

SYNTAX

```
beectl add_record --artifact <identifier of the artifact to be filed as a record
or non-record> { --retention_category <identifier of the Universal Records
Management retention category> | --record_folder <identifier of the Universal
Records Management record folder> } [ --no_retention <boolean specifying a record
or non-record> ]
```

OPTIONS**--artifact**

identifier of the artifact to be filed as a record or non-record

--retention_category

identifier of the Universal Records Management retention category

--record_folder

identifier of the Universal Records Management record folder

--no_retention

boolean specifying a record or non-record

EXAMPLES

```
beectl add_record --artifact myArtifact --retention_category
myRetentionCategory --no_retention
```

add_resource

Creates a new resource.

SYNTAX

```
beectl add_resource --name <name> --email_address <email address> --resource_type
<type> [--enterprise <enterpriseid>] [--capacity <capacity>] [--identifier
<identifier>] [--phone_number <phone_number>] [--website <website>]
[--postal_address <postal address>] [--timezone <time zone name>]
[--location <location>] [--add_approver <approverid>] [--description
<description>] [--booking_info <booking info>] [--booking_characteristics
<[O]pen|[F]CFS>] beectl add_resource --external --name <name> --email_address
<email address> --resource_type <type> [--enterprise <enterpriseid>]
[--capacity <capacity>] [--phone_number <phone_number>] [--website
<website>] [--postal_address <postal address>] [--timezone <time zone
name>] [--location <location>] [--booking_info <booking info>]
[--description <description>]
```

OPTIONS

--name

Define the unique name of the resource.

--enterprise

Specify the identifier of the enterprise under which the resource will be created.

--resource_type

Specify the type of the resource. Accepted arguments for this option are: e, equipment, o, other, r and room. Arguments are case insensitive.

--bookableresource_type

Deprecated option. Use --resource_type instead.

--email_address

Specify the BUSINESS_1 e-mail address of the resource.

--phone_number

Specify the BUSINESS_1 phone number of the resource.

--website

Specify the BUSINESS_1 web site of the Resource.

--postal_address

Specify the BUSINESS_1 postal address of the resource.

--identifier

Specify the identifier of the resource. The identifier can be used as an alternative to the name: such as a room or serial number.

--capacity

Specify the capacity of the resource.

--external

Create the resource as an external resource. If this option is not specified, a BookableResource will be created.

--add_approver

Resource approver to add.

--booking_characteristics

Specify resource default calendar booking characteristics. The characteristics can be Open or First Come First Serve.

--booking_info

Specify resource booking information. It must be a XHTML string.

--description

Specify the description of the resource. It must be a XHTML string.

--timezone

Specify the time zone of the Resource.

--location

Specify the location description of the resource. It must be a XHTML string.

EXAMPLES

```
beectl add_resource --name "Resource1" --email_address
resource1@example.com --resource_type "room" --identifier
"us:OP200:20P74" --capacity 8 --timezone "America/Los_Angeles"
```

add_role_definition

Creates a RoleDefinition entity.

SYNTAX

```
beectl add_role_definition [--scope <unique identifier of the Scope>] --name <name
of RoleDefinition> [--description <description>] [--privilege <privilege
name>]... [--access_types <access types string>] [--always_enabled <boolean
value>]
```

OPTIONS**--scope**

Specify the unique identifier of the Scope in which the RoleDefinition should be created.

--name

Specify the name of the RoleDefinition.

--description

Specify a description for the RoleDefinition.

--privilege

Specify a privilege which will be granted by the RoleDefinition. This option can be specified more than once.

--access_types

Specify the access types string for the RoleDefinition.

--always_enabled

Specify the AlwaysEnabled option for RoleDefinition.

EXAMPLES

```
beectl add_role_definition --scope
wksp=MyWorkspace,enpr=MyEnterprise --name MyRoleDefinition
```

add_sensitivity

Creates a Sensitivity entity.

SYNTAX

```
beectl add_sensitivity --workspace <unique identifier of the Workspace> --name
<name of Sensitivity> [--description <description>] [--sensitivity_only <boolean
value>] [--delegatable <boolean value>]
```

OPTIONS

--workspace

Specify the unique identifier of the Workspace in which the Sensitivity should be created.

--name

Specify the name of the Sensitivity.

--description

Specify a description for the Sensitivity.

--sensitivity_only

Specify the SensitivityOnly option for the Sensitivity.

--delegatable

Specify the Delegatable option for the Sensitivity.

EXAMPLES

```
beectl add_sensitivity --workspace
wksp=MyWorkspace,enpr=MyEnterprise --name MySensitivity
```

add_sensitivity_ace

Adds an Access Control Entry (ACE) to a Sensitivity entity's Sensitivity ACL (SACL).

SYNTAX

```
beectl add_sensitivity_ace --sensitivity <unique identifier of the entity>
--accessor <unique identifier of the Accessor> [--access_types <access types
string>]
```

OPTIONS

--sensitivity

Specify the unique identifier of the Sensitivity to which the ACE will be added.

--accessor

Specify the unique identifier of an Accessor to whom the access types will apply.

--access_types

Specify the access types string for the Accessor.

EXAMPLES

```
beectl add_sensitivity_ace --sensitivity
acsn=MySensitivity,wksp=MyWorkspace,enpr=MyEnterprise --accessor
loginid=MyUser --access_types +RW-D
```

add_team_workspace

Creates a team workspace from a template

SYNTAX

```
beectl add_team_workspace --name <Workspace name> --scope <Identifier of
enterprise or organization> [--template <Workspace template identifier>] [--file
<Full path of the input file>] [--email_address <Team workspace email address>]
[--description <Description>][--participation_mode <Team workspace participation
mode. Value can be INVITE_ONLY, OPEN, or APPROVE_REQUIRED>] [--directory_listed
<TRUE|FALSE. Default value is FALSE>] [--hard_quota <Hard quota in megabytes (MB).
Use 'UNLIMITED' for unlimited quota> --soft_quota <Soft quota in megabytes (MB).
Use 'UNLIMITED' for unlimited quota>]
```

OPTIONS

--name

Workspace name

--scope

Identifier of enterprise or organization

--template

Workspace template identifier

--file

Full path of the input file

--email_address

Team workspace email address

--description

Description

--participation_mode

Team workspace participation mode. Value can be INVITE_ONLY, OPEN, or APPROVE_REQUIRED

--directory_listed

TRUE | FALSE. Default value is FALSE

--hard_quota

Hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--soft_quota

Soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

EXAMPLES

```
beectl add_team_workspace --scope
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453
--name My_Team_worksapce --hard_quota UNLIMITED --soft_quota 100

beectl add_team_workspace --scope
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453
--template
9941:2345:wtss:88D193D162CE4ED89FF66AB4E55745B6345464545453
--file /tmp/input.xml --hard_quota 1000 --soft_quota 100
--email_address teamworkspace@company.com
```

add_trusted_identity

This commands registers a trusted identity. There are two types of trusted identities: WSSEC and SES. Default type is WSSEC. For WSSEC type, please make sure that the service has a valid certificate registered in the wallet and the correct associated key alias is passed into this command. This command also creates the principal(s) associated with this trusted identity in the Beehive system. On the other hand, for SES type, this command stores the given trusted identity name and password information.

SYNTAX

```
beectl add_trusted_identity [--type WSSEC --is_service <boolean> [--key_alias <Key
Alias>] --service_name <Principal Name>] [--type SES --name <Trusted Entity Name>
--password <Trusted Entity Password>]
```

OPTIONS**--key_alias**

The alias of the service which is used to register the certificate in the wallet. This option is mandatory if registering a web service, i.e. if is_service is true and type is WSSEC. For all other cases, this is not a mandatory option.

--is_service

Boolean value, true if this is a service. This option is mandatory if type is WSSEC.

--service_name

String value of the service principal name with which it will be identified in Beehive. This option is mandatory if type is WSSEC.

--type

String value indicating the type of trusted identity: SES or WSSEC. SES refers to Secure Enterprise Search. WSSEC refers to Web services security.

--name

String value representing the name of the SES trusted entity.

--password

Secure string value representing the password of the SES trusted entity.

EXAMPLES**add_urm**

Configures an agent for a Universal Records Management instance.

SYNTAX

```
beectl add_urm --rm_admin_name <RM Admin Name for the Universal Records Management
instance.> --rm_admin_password <RM Admin Pass for the Universal Records
Management instance.> --urm_url <The URL for the Universal Records Management
instance.> [ --disposition_loader_interval <The Disposition Loader Interval for
the Universal Records Management instance.> ] [ --disposition_processor_interval
<The Disposition Processor Interval for the Universal Records Management
instance.> ] [ --agent_name <The Agent Name for the Universal Records Management
instance.> ]
```

OPTIONS**--rm_admin_name**

RM Admin Name for the Universal Records Management instance.

--rm_admin_password

RM Admin Pass for the Universal Records Management instance.

--urm_url

The URL for the Universal Records Management instance.

--disposition_loader_interval

The Disposition Loader Interval for the Universal Records Management instance.

--disposition_processor_interval

The Disposition Processor Interval for the Universal Records Management instance.

--agent_name

The Agent Name for the Universal Records Management instance.

EXAMPLES

```
beectl add_urm --rm_admin_name myRmAdminName --rm_admin_password
myRmAdminObfuscatedPassword --urm_url myUrmUrl --disposition_
loader_interval myDispositionLoaderInterval --disposition_
processor_interval myDispositionProcessorInterval --agent_name
myAgentName
```

add_user

The add_user command adds new users. The user information is supplied either on command line or in an XML file.

SYNTAX

```
beectl add_user {          --family_name <[locale:]family name>          [ --family_
name <[locale:]family name> ... ]          --scope <identifier of users parent>
--login_id <login_id>          --login_password <password>          [ --given_name
<[locale:]given name> ... ]          [ --display_name <[locale:]display name> ... ]
[ --middle_name <[locale:]middle name> ... ]          [ --job_title <[locale:]job
title> ... ]          [ --prefix <[locale:]prefix> ... ]          [ --suffix
<[locale:]suffix> ... ]          [ --nick_name <[locale:]nick name> ... ]          [
--office_location <office location of the user> ]          [ --company <company of
the user> ]          [ --profession <profession of the user> ]          [ --timezone
<time zone of the user> ]          [ --locale <locale of the user> ]          [
--department <department of the user> ]          [ --assistant <assistant identifier>
]          [ --manager <manager identifier> ]          [ --organization <organization
identifier> ... ]          [ --voice_principal <voice devicenum> ]          [
--voice_pin <pin> ]          [ --property <name(certificate|notes)=value=description>
... ]          [ --protocol_principal <protocol principal> ]          [ --protocol_
password <protocol password> ]          [ --address <type of address(business_
1|other_5|personal_4|proxy_1|...):scheme(im|mailto|...):value> ... ]          [
--default_address_for_type <type of address(business_1|other_5|personal_4|proxy_
1|...):scheme(im|mailto|...):value> ]          [ --default_address_for_scheme <type
of address(business_1|other_5|personal_4|proxy_1|...):scheme(im|mailto|...):value>
]          [ --primary_address <type of address(business_1|other_5|personal_4|proxy_
1|...):scheme(im|mailto|...):value> ]          [ --external_inbox <true|false> ]
[ --extended_enterprise_user <true|false> ]          |          --file <filename> [
--ldapbootstrap ] }
```

OPTIONS

--family_name

Family name of the user in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--scope

Identifier of the enterprise or organization under which this user will be created.

--given_name

Given name of the user in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--display_name

Display name of the user in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--middle_name

Middle name of the user in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--job_title

Job title of the user in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--prefix

Prefix of the user in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--suffix

Suffix of the user in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--nick_name

Nick name of the user in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--office_location

Office location of the user.

--company

Company of the user.

--profession

Profession of the user.

--timezone

Time zone of the user. list_timezones lists the valid time zones

--locale

Locale details of the user. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--department

Department of the user.

--assistant

Identifier of the assistant.

--manager

Identifier of the manager.

--organization

Identifiers of the organizations the user belongs to.

--property

Details of the property in the format name=value=description. Supported names are certificate, and notes. Note, no equals to symbol(=) should be present in the name or value or description.

--address

Address of the user in the format type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--default_address_for_type

Address of the user in the format type:scheme:value. Sets the specified address as the default for the specified type. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--default_address_for_scheme

Address of the user in the format type:scheme:value. Sets the specified address as the default for the specified scheme. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--primary_address

Primary address of the user in the format type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--login_id

The login credentials of the user.

--login_password

Login password.

--voice_principal

Voice principal of the user.

--voice_pin

Pin number for the voice device.

--protocol_principal

Protocol principal of the user.

--protocol_password

Protocol password.

--file

Name of the file, which contains user information in XML format.

--ldapbootstrap

LDAP bootstrap flag. This option is used to specify that users are mastered in a LDAP server. This is relevant only when --file option is used.

--external_inbox

Boolean if user's inbox is external or not.

--extended_enterprise_user

Boolean if user is an external user or not.

EXAMPLES

```
beectl add_user --family_name User1FamilyName --login_id
user@example.com --login_password hioquery731419== --scope
enpr=example --obfuscated
```

```
beectl add_user --family_name User1FamilyName --login_id
user@example.com --login_password hioquery731419== --scope
enpr=example --given_name User1GivenName --display_name "User1
Name" --organization orgn=beehive1,enpr=oracle1 --obfuscated
```

```
beectl add_user --family_name User1FamilyName --login_id
user@example.com --login_password hioquery731419== --scope
enpr=example --address BUSINESS_1:mailto:example@example.com
--address BUSINESS_2:fax:121345222 --obfuscated
```

```
beectl add_user --family_name User1FamilyName --login_id
user@example.com --login_password hioquery731419== --scope
enpr=example --property notes=xxx --obfuscated
```

```
beectl add_user --family_name User1FamilyName --login_id
user@example.com --login_password hioquery731419== --scope
enpr=example --extended_enterprise_user true --obfuscated
```

```
beectl add_user --file Users.xml
```

```
beectl add_user --file Users.xml --ldapbootstrap
```

add_user_subscription

Creates a user subscription from a pre-defined rule in a subscription template.

SYNTAX

```
beectl add_user_subscription --source_entity_class <sourceEntityClass of template>
--rule <rule name> --attach <identifier of attached entity> --subscriber
<identifier of subscriber>
```

OPTIONS

--source_entity_class

Specify the name of the source entity Class that is defined in subscription template.

--rule

Specify the name of the pre-defined rule that is selected for creating subscription.

--attach

Specify the Identifier of the entity to which the subscription is attached.

--subscriber

Specify the identifier of the subscriber who owns the subscription.

EXAMPLES

```
beectl add_user_subscription --source_entity_class Invitation
--rule NOTIFY_ON_ANY_UPDATED_INVITATION --attach
5457:7954:clnd:337F34E37E8E81F1E040578C921630B7000000000B864
--subscriber
5457:7954:user:6390824F2C4C4BD1B54A21B2DD7423F3000000000000A
```

add_version_configuration

Creates a version configuration on the given scope or heterogeneous folder.

SYNTAX

```
beectl add_version_configuration --container <Configuration scope or heterogenous
folder> --file <Full path of the configuration XML file>
```

OPTIONS

--container

Scope or heterogeneous folder on which the version configuration should be defined.

--file

Full path of the version configuration XML file. The file must contain properly formatted data.

EXAMPLES

```
beectl add_version_configuration --container  
orgn=MyOrganization,enpr=MyEnterprise --file  
/tmp/configuration.xml
```

add_virus_scan_engine

Adds a new virus scan engine to the collection of engines configured for the Site. If this is the first scan engine being added, this command will create a new collection for the Site and add the virus scan engine to it.

SYNTAX

```
beectl add_virus_scan_engine [ --hostname <scanengine_hostname> ] [ --port  
<scanengine_port> ] [ --validate_connection <true/false> ]
```

OPTIONS**--hostname**

Name of the host where the virus scan engine is installed. Default is localhost.

--port

Port number used by the virus scan engine for communication with its clients. Default is 1344.

--validate_connection

Indicates if the connection to the virus scan engine needs to be validated.

EXAMPLES

```
beectl add_virus_scan_engine --hostname  
scanenginehost.example.com --port 1344 --validate_connection  
true
```

add_voice_enterprise

Creates a voice enterprise with the given name.

SYNTAX

```
beectl add_voice_enterprise --name <name>
```

OPTIONS**--name**

Name to be assigned to this voice enterprise.

EXAMPLES

```
beectl add_voice_enterprise --name sample
```


add_voice_facility

Creates a voice facility with the given name.

SYNTAX

```
beectl add_voice_facility --name <name>
```

OPTIONS

--name

Name to be assigned to this voice facility.

EXAMPLES

```
beectl add_voice_facility --name 13125551234
```

add_workflow_schema

Deploys a workflow and seeds workflow information.

SYNTAX

```
beectl add_workflow_schema --file <full path to the workflow jar file>
```

OPTIONS

--file

Specify the absolute path of the workflow schema jar file.

EXAMPLES

```
beectl add_workflow_schema --file  
/private/bpel/MyWorkflowSchema.jar
```

add_workflow_template

Creates a workflow template using data in an XML file.

SYNTAX

```
beectl add_workflow_template --file <full path to the workflow template xml file>
```

OPTIONS

--file

Specify the absolute path of the XML file that contains data to create the workflow template.

EXAMPLES

```
beectl add_workflow_template --file  
/private/bpel/MyWorkflowTemplate.xml
```

add_workspace_template

Creates a workspace template in an organization or enterprise

SYNTAX

```
beectl add_workspace_template --scope <Identifier of enterprise or organization>
--file <Full path of the template file>
```

OPTIONS

--scope

Identifier of enterprise or organization

--file

Full path of the input file

EXAMPLES

```
beectl add_workspace_template --scope
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453
--file /tmp/template.xml
```

append_value

Appends the specified value to the existing value of the named property. If the named property value is cleared before executing this command, then after executing this command it will contain the new value.

Note: Option value should not start with hyphen(-). If an option value starts with hyphen, use any one of the following syntaxes. 1. Use <option-name>=<option value> format. This is the preferred way to specify the option values starting with hyphens. 2. Prefix the option value with string "ESCAPE:". 3. Prefix the option value with backslash "\\". This is the least preferred way. This may not work in some platforms, esp in windows platforms it will not work.

SYNTAX

```
beectl append_value --component <system object identifier or alias> --name <name>
--value <value>...
```

OPTIONS

--component

component id.

--name

Name of the property.

--value

Value of the property.

EXAMPLES

The command execution below would modify the log level for code in module oracle.ocs.commandline to FINEST and code in module oracle.ocs.management to FINE. These new settings are appended to existing list of package names in the ModuleLogLevel property of the LoggingProperties config object in current site. If the ModuleLogLevel property was cleared before executing this command, then it will contain the new values now.

```
beectl append_value --component _CURRENT_SITE:LoggingProperties
--name "ModuleLogLevel" --value "oracle.ocs.commandline:FINEST"
--value "oracle.ocs.management:FINE"
```

clear_proposed_configuration

Clears proposed configuration of the Beehive system object model

SYNTAX

```
beectl clear_proposed_configuration
```

OPTIONS

This command has no options

EXAMPLES

```
beectl clear_proposed_configuration
```

clone_midtier

Top level clone command that clones a Oracle Beehive Application tier.

SYNTAX

```
beectl clone_midtier --ias_instance_name <ias instance name > --host_name <host
name> --db_schema_password <db schema password> [--oui_inv_ptr_loc <oui data>]
[--oracle_home_name <oracle home name>] [--do_not_start_at_end]
```

OPTIONS**--ias_instance_name**

Ias instance name with out appending host name. For example "myinstance"

--host_name

Fully qualified host name of the new Oracle Beehive Application tier.

--db_schema_password

Database schema password.

--oui_inv_ptr_loc

OUI inventory pointer location.

--oracle_home_name

Oracle home name. The default value is the value for --ias_instance_name option.

--do_not_start_at_end

If specified, beehive components will not be started at the end.

EXAMPLES

```
beectl clone_midtier --ias_instance_name MyIASInstance --host_
name machine1.example.com --db_schema_password
dbbeehiveschemapassword
```

clone_oc4j_instance

Creates a new oc4j instance by cloning the given oc4j instance.

Most of properties of the newly created oc4j instance is similar to that of the source oc4j instance.

All the service instance present in the source oc4j instance system model is deployed into the newly cloned oc4j instance.

Further, after deploying all the service instances, newly cloned oc4j instance is restarted once.

Only Beehive oc4j instances should be cloned using this command. Non Beehive oc4j instances can't be cloned using this command

Beehive Management oc4j instance should not be cloned. This command will error out when management oc4j instance is cloned.

SYNTAX

```
beectl clone_oc4j_instance [--source_oc4j_instance_id <source oc4j instance system
model id> | --source_oc4j_instance_name <source oc4j instance name>] --target_
oc4j_instance_name <target oc4j instance name> [--working_list <ServiceInterface
or archive file name without path> ...] [--exclusion_list <ServiceInterface or
archive file name without path> ...]
```

OPTIONS**--source_oc4j_instance_id**

Source oc4j instance system model id.

--source_oc4j_instance_name

Source oc4j instance name.

--target_oc4j_instance_name

Target oc4j instance name.

--exclusion_list

Given ServiceInterfaces or archive file names provided via this option will be excluded.

--working_list

Only given ServiceInterfaces or archive file names provided via this option will be included.

EXAMPLES

```
beectl clone_oc4j_instance --source_oc4j_instance_name BEEAPP
--target_oc4j_instance_name BEEAPP_CLONE
```

--exclusion_list ClientManagementService can be passed to exclude ClientManagementService service interface.

--working_list ClientManagementService can be passed to include only ClientManagementService service interface.

clone_preparation

Prepares the existing oracle home for cloning.

SYNTAX

```
beectl clone_preparation --file <output file name>
```

OPTIONS**--file**

Fully qualified name of the file which will store the list of files to be cloned. This files has to be outside the oracle home.

EXAMPLES

```
beectl clone_preparation --file /tmp/clone-list.txt
```

clone_site

Top level clone command that clones a Oracle Beehive Application tier in a new deployment (i.e., site). This command is part of the Deployment Cloning solution. Please see the administrator guide for details.

SYNTAX

```
beectl clone_site --ias_instance_name <ias instance name > --host_name <host name>
--db_schema_password <db schema password> --db_connect_string <db connect String>
[--oui_inv_ptr_loc <oui data>] [--db_schema_name <db schema name>] [(--db_rac_
node_information <XA Service name>) ...] [(--db_xa_service_name <rac node
information>) ...] [--retain_rac_node_information] [--oracle_home_name <oracle
home name>] [--do_not_start_at_end] [--site_name <New site name>]
```

OPTIONS**--ias_instance_name**

Ias instance name with out appending host name. For example "myinstance"

--host_name

Fully qualified host name of the new Oracle Beehive Application tier.

--db_connect_string

Database connect string.

--db_schema_password

Database schema password.

--db_schema_name

Database schema name.

--db_rac_node_information

Database RAC node information. It should be of the format hostname:port. For example: sample.com:1521

--db_xa_service_name

Database XA service name.

--retain_rac_node_information

Retains the old RAC node and ONS information. By default old RAC node information is removed.

--oracle_home_name

Oracle home name. The default value is the value provided for --ias_instance_name option.

--oui_inv_ptr_loc

OUI inventory pointer location.

--do_not_start_at_end

If specified, beehive components will not be started at the end.

--site_name

New site name

EXAMPLES

```
beectl clone_site --ias_instance_name MyIASInstance --host_name
machine1.example.com --db_schema_password
dbbeehiveschemapassword --db_connect_string
" (DESCRIPTION= (ADDRESS= (PROTOCOL=TCP) (HOST=machine2.example.com)
(PORT=1521)) (CONNECT_DATA= (SERVICE_NAME=oracle)) " --db_schema_
name MySchema --retain_rac_node_information
```

delete_assigned_role

Deletes an AssignedRole entity.

SYNTAX

```
beectl delete_assigned_role --assigned_role <unique identifier of the
AssignedRole>
```

OPTIONS**--assigned_role**

Specify the unique identifier of the AssignedRole to be deleted.

EXAMPLES

```
beectl delete_assigned_role --assigned_role
acar=MyAssignedRole,wksp=MyWorkspace,enpr=MyEnterprise
```

delete_attendant

Deletes an auto attendant by name.

SYNTAX

```
beectl delete_attendant --name <name of attendant>
```

OPTIONS**--name**

Name of the attendant to delete.

EXAMPLES

```
beectl delete_attendant --name my_attendant
```

delete_attendant_prompt

Deletes a prompt.

SYNTAX

```
beectl delete_attendant_prompt --name <attendant name> --type <prompt type>
--language <prompt language>
```

OPTIONS**--name**

Name of the attendant to which the prompt belongs.

--type

The type of the prompt. Can be one of language, menu, greeting, option1, option2, option3, option4, option4, option5, option6, option7, option8, option9, noinput, noinput-term, nomatch, nomatch-term.

--language

The language of the prompt.

EXAMPLES

```
beectl delete_attendant_prompt --name myAttendant --type
greeting --language en_US
```

```
beectl delete_attendant_prompt --name myAttendant --type  
language
```

delete_audit_policy

Deletes an existing audit

SYNTAX

```
beectl delete_audit_policy --policy <Audit policy identifier>
```

OPTIONS

--policy

Audit policy identifier

EXAMPLES

```
beectl delete_audit_policy --policy aupl=MyAuditPolicy
```

delete_audit_template

Deletes an existing audit policy template

SYNTAX

```
beectl delete_audit_template --template <Audit template identifier>
```

OPTIONS

--template

Audit template identifier

EXAMPLES

```
beectl delete_audit_template --template autp=MyAuditTemplate
```

delete_audit_trail

Deletes an existing audit trail

SYNTAX

```
beectl delete_audit_trail --trail <Audit trail identifier>
```

OPTIONS

--trail

Audit trail identifier

EXAMPLES

```
beectl delete_audit_trail --trail autr=MyAuditTrail
```


delete_category

Deletes a category and all category applications.

SYNTAX

```
beectl delete_category --category <Identifier of the category to be deleted>
```

OPTIONS

--category

Specify the identifier of the category.

EXAMPLES

```
beectl delete_category --category
421C:6639:catg:3BF460625AB3FCC9E040548C1C82796300000000020B
```

```
beectl delete_category --category catg=Resource_
US, catg=Resource_ROOT, enpr=bee_ent
```

delete_category_application

Removes a category from an entity

SYNTAX

```
beectl delete_category_application --category <Identifier of the category to be
removed> --entity <Identifier of the entity from which the category needs to be
removed>
```

OPTIONS

--category

Specify the identifier of the category to be removed.

--entity

Specify the identifier of an Oracle Beehive entity from which the category needs to be removed.

EXAMPLES

```
beectl delete_category_application --category
catg=MyCategory, enpr=MyEnterprise --entity
adoc=MyDocument, fldr=MyFolder, wksp=MyWorkspace, enpr=MyEnterprise
```

delete_category_configuration

Deletes a given category configuration.

SYNTAX

```
beectl delete_category_configuration --configuration <Configuration identifier>
```

OPTIONS

--configuration

Category configuration to be deleted.

EXAMPLES

```
beectl delete_category_configuration --configuration
9941:2345:ctcf:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

delete_client_application

Deletes a client application.

SYNTAX

```
beectl delete_client_application --application <identifier of the client
application>
```

OPTIONS

--application

Specify the identifier of the client application. Use list_client_applications command to determine the identifier of the client application.

EXAMPLES

```
beectl delete_client_application --application
1234:5678:capn:2E0329B0705F0E40E040578C92160957000000000434
```

delete_client_application_configuration

Deletes the client application configuration with the given identifier.

SYNTAX

```
beectl delete_client_application_configuration --configuration <identifier of the
client application configuration>
```

OPTIONS

--configuration

Specify the identifier of the client application configuration.

EXAMPLES

```
beectl delete_client_application_configuration --configuration
1234:5678:capc:2E0329B0705F0E40E040578C92160957000000000434
```

delete_client_application_patchset

Deletes a client application patchset.

SYNTAX

```
beectl delete_client_application_patchset --patchset <identifier of the client
application patchset>
```

OPTIONS**--patchset**

Specify the identifier of the client application patchset. Use `list_client_application_patchsets` command to determine the identifier of a client application patchset.

EXAMPLES

```
beectl delete_client_application_patchset --patchset
1234:5678:capp:2E0329B0705F0E40E040578C92160957000000000434
```

delete_client_application_version

Deletes a client application version.

SYNTAX

```
beectl delete_client_application_version --application_version <identifier of the
client application version>
```

OPTIONS**--application_version**

Specify the identifier of the client application version. Use `list_client_application_versions` command to determine the identifier of a client application version.

EXAMPLES

```
beectl delete_client_application_version --application_version
1234:5678:capv:2E0329B0705F0E40E040578C92160957000000000434
```

delete_coexistence_connector

Deletes a coexistence connector.

SYNTAX

```
beectl delete_coexistence_connector [--connector <connectorid>] [--select_by_name
<connector_name>]
```

OPTIONS**--select_by_name**

Specify the name of the coexistence connector.

--connector

Specify the identifier of the coexistence connector.

EXAMPLES

```
beectl delete_coexistence_connector  
  
beectl delete_coexistence_connector --select_by_name MsExch2003_  
1
```

delete_coexistence_profile

Deletes the coexistence profile of user.

SYNTAX

```
beectl delete_coexistence_profile {--user <user_cen> | --select_by_name <user_  
name> | --select_by_address <user_address> --select_by_authuser <user_loginid>}
```

OPTIONS**--user**

Specify the identifier of the user.

--select_by_name

Specify the name of the user.

--select_by_address

Specify the email address of the user.

--select_by_authuser

Specify the login ID of the user.

EXAMPLES

```
beectl delete_coexistence_profile --select_by_authuser user_  
login_id
```

delete_conference

Deletes conference artifact under workspace

SYNTAX

```
beectl delete_conference --conference_id <Conference identifier>
```

OPTIONS**--conference_id**

Conference identifier

EXAMPLES

```
beectl delete_conference --conference_id  
6490:45C8:owch:B3EABD85714E4DBDA92201A54EAE56C3000000002C2C
```

delete_conference_template

Deletes conference template artifact under workspace

SYNTAX

```
beectl delete_conference_template --template_id <Conference identifier>
```

OPTIONS

--template_id

Conference identifier

EXAMPLES

```
beectl delete_conference_template --template_id
6490:45C8:owch:B3EABD85714E4DBDA92201A54EAE56C3000000002C2C
```

delete_custom_user_property

The delete_custom_user_property command deletes a custom property. If there are multiple custom properties with same name, then only the first occurrence of the attribute with specified name is deleted. Any values of the property being deleted will also be deleted.

SYNTAX

```
beectl delete_custom_user_property --name <name>
```

OPTIONS

--name

Property name. Example: employeenumber.

EXAMPLES

```
beectl delete_custom_user_property --name employeenumber
```

delete_device_profile

Deletes the device profile with the given identifier. The command can also optionally delete all the device types associated with this device profile.

SYNTAX

```
beectl delete_device_profile --profile <identifier of the device profile>
[--delete_device_types]
```

OPTIONS

--profile

Identifier of the device profile.

--delete_device_types

Deletes all the device types associated with this device profile.

EXAMPLES

```
beectl delete_device_profile --profile
1234:5678:devp:2E0329B0705F0E40E040578C92160957000000000434

beectl delete_device_profile --profile
1234:5678:devp:2E0329B0705F0E40E040578C92160957000000000434
--delete_device_types
```

delete_device_type

Deletes the device type with the given identifier.

SYNTAX

```
beectl delete_device_type --type <identifier of the device type>
```

OPTIONS**--type**

Identifier of the device type.

EXAMPLES

```
beectl delete_device_type --type
1234:5678:devt:2E0329B0705F0E40E040578C92160957000000000434
```

delete_directory_profile

The delete_directory_profile command deletes a directory profile.

Change log number for the directory profile is not deleted from beehive, unless the activate_configuration option is used. To delete the change log number from beehive, run this command by specifying the common option activate_configuration with value as true.

SYNTAX

```
beectl delete_directory_profile --profile <profile-name>
```

OPTIONS**--profile**

Profile name to be deleted.

EXAMPLES

```
beectl delete_directory_profile --profile MyDirectoryProfile
```

delete_dmz_home_instance

Removes configuration for a Beehive installation in the DMZ that is, outside the firewall.

SYNTAX

```
beectl delete_dmz_home_instance --id <dmz beehive instance id>
```

OPTIONS

--id

Identifier for DMZ beehive instance.

EXAMPLES

```
beectl delete_dmz_home_instance --id dmz_on_server1
```

delete_event_subscription

Deletes an event subscription from the Oracle Beehive repository.

SYNTAX

```
beectl delete_event_subscription --subscription <identifier of the event subscription to be deleted>
```

OPTIONS

--subscription

Specify the identifier of the event subscription to be deleted.

EXAMPLES

```
beectl delete_event_subscription --subscription
9941:2345:enpr:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

delete_external_contact

The delete_external_contact command deletes an external contact with an option to purge.

SYNTAX

```
beectl delete_external_contact { --contact <identifier of external contact > |
--email <Email address of the contact> } --purge
```

OPTIONS

--contact

identifier of external contact

--email

Email id of the external contact

--purge

Purges the external contact after deletion.

EXAMPLES

```
beectl delete_external_contact --contact  
6A95:21EB:extp:D9E9FC8134544BCE9D60559F9B997CCD000000000000
```

```
beectl delete_external_contact --email contact1@example.com
```

```
beectl delete_external_contact --email contact1@example.com  
--purge
```

delete_filesystem_reference

Removes a file system reference from Beehive.

SYNTAX

```
beectl delete_filesystem_reference --filesystem_reference_id <Identifier of the  
file system reference>
```

OPTIONS**--filesystem_reference_id**

Identifier of the file system reference to delete.

EXAMPLES

```
beectl delete_filesystem_reference --filesystem_reference_id  
fsref=MyFilesystemReference,enpr=MyEnterprise
```

delete_group

The delete_group command deletes a group with an option to purge.

SYNTAX

```
beectl delete_group { --group <group_identifier> | --email <group_email> } [  
--purge ]
```

OPTIONS**--group**

Identifier of the group.

--email

EmailID of the group.

--purge

Purges the group after deletion.

EXAMPLES

```
beectl delete_group --group grup=MyGroup,enpr=Example
```

```
beectl delete_group --group grup=MyGroup,enpr=Example --purge
```

delete_local_ace

Deletes an Access Control Entry (ACE) from the Local Access Control List (LACL) of an entity.

SYNTAX

```
beectl delete_local_ace --entity <unique identifier of the entity> --accessor
<unique identifier of the Accessor>
```

OPTIONS**--entity**

Specify the unique identifier of the entity from which the ACE will be deleted.

--accessor

Specify the unique identifier of the accessor to whom the access types were applied.

EXAMPLES

```
beectl delete_local_ace --entity
adoc=MyDocument,wksp=MyWorkspace,enpr=MyEnterprise --accessor
loginid=MyUser
```

delete_organization

Deletes an existing organization

SYNTAX

```
beectl delete_organization --organization <Organization identifier> [--async]
```

OPTIONS**--organization**

Organization identifier

--async

Delete organization asynchronously

EXAMPLES

```
beectl delete_organization --organization
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

delete_policy

Deletes a policy.

SYNTAX

```
beectl delete_policy --policy <identifier of the policy to be deleted>
```

OPTIONS

--policy

Specify the identifier of the policy to be deleted. Use the `list_policies` command to obtain the policy identifier.

EXAMPLES

```
beectl delete_policy --policy plcy=MyPolicy,enpr=MyEnterprise
```

delete_policy_action

Deletes a policy action.

SYNTAX

```
beectl delete_policy_action --action_name <name of action to be deleted>
```

OPTIONS

--action_name

Specify the name of the policy action to be deleted.

EXAMPLES

```
beectl delete_policy_action --action_name MyActionName
```

delete_policy_schema

Deletes a policy schema.

SYNTAX

```
beectl delete_policy_schema --policy_schema <identifier of the policy schema to be deleted>
```

OPTIONS

--policy_schema

Specify the identifier of the policy schema to be deleted.

EXAMPLES

```
beectl delete_policy_schema --policy_schema  
9941:2345:plsh:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

delete_policy_template

Deletes a policy template.

SYNTAX

```
beectl delete_policy_template --policy_template <identifier of the policy template to be deleted>
```

OPTIONS

--policy_template

Specify the identifier of the policy template to be deleted.

EXAMPLES

```
beectl delete_policy_template --policy_template
9941:2345:plct:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

delete_preference_profile

The delete_preference_profile command deletes a preference profile.

SYNTAX

```
beectl delete_preference_profile --profile <Preference profile identifier>
```

OPTIONS

--profile

Identifier of the preference profile to be deleted.

EXAMPLES

```
beectl delete_preference_profile --profile
prfp=MyProfile,loginid=user1
```

delete_preference_property

The delete_preference_property command deletes a preference property from a preference set.

SYNTAX

```
beectl delete_preference_property --set <set-identifier> --name <property-name>
```

OPTIONS

--set

Identifier of the preference set specified in id format, which can be determined by running list_preference_sets command with "--entity_format id" option.

--name

Name of the preference property.

EXAMPLES

```
beectl delete_preference_property --set
5965:3658:prfs:B7CAC0E31E554593B7A93B24B0FD09F2000000000979
--name MyProperty
```

delete_preference_set

The delete_preference_set command deletes a preference set.

SYNTAX

```
beectl delete_preference_set --set <set-identifier>
```

OPTIONS**--set**

Identifier of the preference set specified in id format, which can be determined by running list_preference_sets command with "--entity_format id" option.

EXAMPLES

```
beectl delete_preference_set --set
5965:3658:prfs:B7CAC0E31E554593B7A93B24B0FD09F2000000000979
```

delete_property

Clears the value of specified property in the configuration object identified by specified id.

SYNTAX

```
beectl delete_property --component <system object identifier or alias> --name
<property name>
```

OPTIONS**--component**

Identifier of a configuration object. The list_components command can be used to lookup the identifier

--name

The property to be cleared.

EXAMPLES

The command execution shown below would clear the value of Alias property of the current site.

```
beectl delete_property --component _CURRENT_SITE --name Alias
```

delete_record

Deletes a record or non-record.

SYNTAX

```
beectl delete_record --artifact <identifier of the artifact to be deleted as a
record/non-record>
```

OPTIONS

--artifact

identifier of the artifact to be deleted as a record/non-record

EXAMPLES

```
beectl delete_record --artifact myArtifact
```

delete_resources

Deletes a resource.

SYNTAX

```
beectl delete_resources --resource <resourceid> | --select_by_name <name>
[--external]
```

OPTIONS

--resource

Specify the identifier of the resource. Use list_resources command to obtain the identifier of the resource.

--select_by_name

Specify the name criteria of the resource.

--external

Specify this option if the resource is external. If this option is not specified, bookable resources will be deleted.

EXAMPLES

```
beectl delete_resources --resource
395A:346B:bkrs:2C5F7E98E076D382E040578CA60B0D0E000000062327
```

delete_role_definition

Deletes a RoleDefinition entity.

SYNTAX

```
beectl delete_role_definition --role_definition <unique identifier of the
RoleDefinition>
```

OPTIONS

--role_definition

Specify the unique identifier of the RoleDefinition to be deleted.

EXAMPLES

```
beectl delete_role_definition --role_definition
acrd=MyRoleDefinition,wksp=MyWorkspace,enpr=MyEnterprise
```

delete_sensitivity

Deletes a Sensitivity entity.

SYNTAX

```
beectl delete_sensitivity --sensitivity <unique identifier of the Sensitivity>
```

OPTIONS

--sensitivity

Specify the unique identifier of the Sensitivity to be deleted.

EXAMPLES

```
beectl delete_sensitivity --sensitivity
acsn=MySensitivity,wksp=MyWorkspace,enpr=MyEnterprise
```

delete_sensitivity_ace

Deletes an Access Control Entry (ACE) from the Sensitivity Access Control List (SACL) of a Sensitivity entity.

SYNTAX

```
beectl delete_sensitivity_ace --sensitivity <unique identifier of the Sensitivity>
--accessor <unique identifier of the Accessor>
```

OPTIONS

--sensitivity

Specify the unique identifier of the Sensitivity from which the ACE will be deleted.

--accessor

Specify the unique identifier of the accessor to whom the access types were applied.

EXAMPLES

```
beectl delete_sensitivity_ace --sensitivity
acsn=MySensitivity,wksp=MyWorkspace,enpr=MyEnterprise --accessor
loginid=MyUser
```

delete_team_workspace

Deletes an existing team workspace

SYNTAX

```
beectl delete_team_workspace --workspace <Workspace identifier> [--async]
```

OPTIONS

--workspace

Workspace identifier

--async

Delete workspace asynchronously

EXAMPLES

```
beectl delete_team_workspace --workspace
9941:2345:twsp:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

delete_trusted_identity

This commands unregisters a trusted identity. If the type of identity is not specified, it is defaulted to WSSEC.

SYNTAX

```
beectl delete_trusted_identity [--type WSSEC --service_name <Trusted Entity Name>]
[--type SES --name <Trusted Entity Name>]
```

OPTIONS

--service_name

String value of the service principal name with which it will be identified in Beehive. This option is mandatory if type is WSSEC.

--type

String value indicating the type of trusted identity: SES or WSSEC. SES refers to Secure Enterprise Search. WSSEC refers to Web services security.

--name

String value representing the name of the SES trusted entity.

EXAMPLES

delete_user

The delete_user command deletes a user with an option to purge.

SYNTAX

```
beectl delete_user { --user <user_identifier> | --email <user_email> } [ --purge ]
```

OPTIONS

--user

Identifier of the user. When purging an already deleted user, the user must be specified in id format. The value in id format can be determined by running list_users command as: list_users --attribute_name STATUS --attribute_type ATTRIBUTE --attribute_value DELETED --entity_format id.

--email

EmailID of the user.

--purge

Purges the user after deletion.

EXAMPLES

```
beectl delete_user --user loginid=user1
```

```
beectl delete_user --user loginid=user1 --purge
```

delete_version_configuration

Deletes a given version configuration.

SYNTAX

```
beectl delete_version_configuration --configuration <Configuration identifier>
```

OPTIONS

--configuration

Version configuration to be deleted.

EXAMPLES

```
beectl delete_version_configuration --configuration  
9941:2345:avcg:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

delete_virus_scan_engine

Deletes specified virus scan engine from the collection of engines configured for the Site. If this is the last scan engine being deleted, this command will also delete the virus scan engine collection and update the Site to remove the virus scan engine collection from it. Either the scan_engine option or the hostname and port options will need to be specified.

SYNTAX

```
beectl delete_virus_scan_engine { --scan_engine <scanengine_systemid> | {  
--hostname <scanengine_hostname> --port <scanengine_port> }}
```


OPTIONS**--scan_engine**

Identifier of the scan engine to be deleted.

--hostname

Name of the host where the virus scan engine is installed.

--port

Port number used by the virus scan engine for communication with its clients.

EXAMPLES

```
beectl delete_virus_scan_engine --scan_engine 12345
```

```
beectl delete_virus_scan_engine --hostname
scanenginehost.example.com --port 1344
```

delete_voice_enterprise

Deletes a voice enterprise with the given id.

SYNTAX

```
beectl delete_voice_enterprise --name <name>
```

OPTIONS**--name**

Identifier of the voice enterprise to be removed.

EXAMPLES

```
beectl delete_voice_enterprise --name
a1d290a8-f8a7-46ea-ae3d-0696c0bde331
```

delete_voice_facility

Deletes a voice facility with the given id.

SYNTAX

```
beectl delete_voice_facility --name <name>
```

OPTIONS**--name**

Identifier of the voice facility to be removed.

EXAMPLES

```
beectl delete_voice_facility --name
a1d290a8-f8a7-46ea-ae3d-0696c0bde331
```

delete_workflow_schema

Deletes a workflow schema.

SYNTAX

```
beectl delete_workflow_schema --workflow_schema <identifier of the workflow schema to be deleted>
```

OPTIONS

--workflow_schema

Specify the identifier of the workflow schema to be deleted. To determine the identifier of a workflow schema, use the `list_workflow_schemas` command.

EXAMPLES

```
beectl delete_workflow_schema --workflow_schema wfsc=myWorkflowSchema, enpr=myEnterprise
```

delete_workflow_template

Deletes a workflow template.

SYNTAX

```
beectl delete_workflow_template --workflow_template <identifier of the workflow template to be deleted>
```

OPTIONS

--workflow_template

Specify the identifier of the workflow template to be deleted. To determine the identifier of a workflow template, use the `list_workflow_templates` command.

EXAMPLES

```
beectl delete_workflow_template --workflow_template wftm=myTemplateKey, enpr=myEnterprise
```

delete_workspace_template

Deletes an existing workspace template

SYNTAX

```
beectl delete_workspace_template --template <Workspace template identifier>
```

OPTIONS

--template

Workspace template identifier

EXAMPLES

```
beectl delete_workspace_template --template
9941:2345:ttws:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

download_device_logs

Downloads the logs for a device. This command can either all log files for a device or all log files for a given application on the device or a particular log file.

SYNTAX

```
beectl download_device_logs --dest_dir <destination directory> [--device_log
<identifier of the device log> | --device <identifier of the device>
[--all|--application_name <name of the application> [--log_file_name <name of the
log file>]]}
```

OPTIONS**--dest_dir**

Specify the full path of the destination directory. The directory must already exist.

--device_log

Specify the identifier of the device log. Use list_device_logs command to determine the identifier of the device log.

--device

Specify the identifier of the device. Use list_devices command to determine the identifier of the device.

--all

Specify this option to download all the log files for this device.

--application_name

Application Name

--log_file_name

Log File Name

EXAMPLES

```
beectl download_device_logs --dest_dir /tmp --device
1234:5678:devi:2E0329B0705F0E40E040578C92160957000000000434
--application_name MobileMail --log_file_name log.txt
```

download_language_pack

Exports language pack resources managed by the Beehive deployment. The exact resources exported and the output destination details are controlled by command options.

SYNTAX

```
beectl download_language_pack [ --full ] [ --only_built_in ] [ --only_custom ] [
```

```
--include_class_files ] [ --destination_file <dest_file> ] [ --destination_directory <dest_dir> ] [ --base_name <base_name> ] [ --locale <locale> ]
```

OPTIONS

--full

include everything; other options are silently ignored.

--only_built_in

include built-in xliif file versions.

--only_custom

include custom xliif file versions.

--include_class_files

include jar of internal classes used by runtime.

--destination_file

output destination file; directory extension should be provided, zip/jar recommended; the file must not exist.

--destination_directory

output destination directory; may exist; must not be used with --dest-file.

--base_name

include xliif with this base name; may be repeated; if omitted all base names are implicitly included.

--locale

include this locale for all base names; if omitted all locales are implicitly included.

EXAMPLES

```
beectl download_language_pack --full --destination_directory  
"/tmp" --base_name "oracle.beehive.core.util" --locale "en_us"
```

download_ldap_group_data

The `download_ldap_group_data` command downloads groups information for an external directory into an XML file. The generated XML file can be used with `add_group` command to create the groups.

SYNTAX

```
beectl download_ldap_group_data --file <filename> --profile <profile-name>
```

OPTIONS

--file

Name of the file to be created with group information in xml format.

--profile

Name of the directory profile.

EXAMPLES

```
beectl download_ldap_group_data --file Groups.xml --profile
MyDirectoryProfile
```

download_ldap_user_data

The `download_ldap_user_data` command downloads user information for an external directory into an XML file. The generated XML file can be used with `add_users` command to create the users.

SYNTAX

```
beectl download_ldap_user_data --file <filename> --profile <profile-name>
```

OPTIONS**--file**

Name of the file to be created with user information in xml format.

--profile

Name of the directory profile.

EXAMPLES

```
beectl download_ldap_user_data --file Users.xml --profile
MyDirectoryProfile
```

download_syncml_messages

Downloads SyncML messages.

SYNTAX

```
beectl download_syncml_messages --directory <directory> --date <yyyy-MM-DD> [ --id
<id> | --user_id <user_id>]
```

OPTIONS**--directory**

Specify output destination directory. The directory must exist within the same server environment used by the Management Service.

--date

Specify the date of the oldest SyncML messages to download. Use the YYYY-MM-DD format.

--id

Specify the server side synchronization session ID of the SyncML messages to download.

--user_id

Specify the server side synchronization session ID of the SyncML messages to download.

EXAMPLES

```
beectl download_syncml_messages --directory /syncml_messages
--date 2006-10-12 --id 105
```

download_syncml_sessions

Downloads SyncML messages.

SYNTAX

```
beectl download_syncml_sessions --file <file> --date <yyyy-MM-DD> [ --id <id> |
--user_id <user_id>]
```

OPTIONS**--file**

Specify output destination file. The file will be created within the same server environment used by the Management Service.

--date

Specify the date of the oldest SyncML messages to download. Use the YYYY-MM-DD format.

--id

Specify the server side synchronization session ID of the SyncML messages to download.

--user_id

Specify the server side synchronization session ID of the SyncML messages to download.

EXAMPLES

```
beectl download_syncml_sessions --file /syncml_sessions.log
--date 2006-10-12 --id 105
```

download_workspace_template_schema

Downloads workspace template XML schema to a file

SYNTAX

```
beectl download_workspace_template_schema [--file <Full path of the output file>]
```

OPTIONS**--file**

Full path of the output file

EXAMPLES

```
beectl download_workspace_template_schema --file /tmp/schema.xsd
```

export_audit_trail

Exports an existing audit trail by the given identifier

SYNTAX

```
beectl export_audit_trail --trail <Audit trail identifier> --file <Full path of  
the output file>
```

OPTIONS**--trail**

Audit trail identifier

--file

Full path name of the export file

EXAMPLES

```
beectl export_audit_trail --trail autr=MyAuditTrail --file  
/tmp/trail.xml
```

export_client_application_configuration

Exports a client application configuration to a local file.

SYNTAX

```
beectl export_client_application_configuration --configuration <client application  
configuration identifier> --file <destination file>
```

OPTIONS**--configuration**

Specify the identifier of the client application configuration.

--file

Specify the full path and file name. Oracle recommends using the .xml extension. If the file already exists, it will be overwritten.

EXAMPLES

```
beectl export_client_application_configuration --configuration  
1234:5678:capc:1234567890123456789012 --file  
/tmp/client-app-config.xml
```

export_errorcodes

Search for occurrences of error codes

SYNTAX

```
beectl export_errorcodes [--start <DATE_TIME>] [--end <DATE_TIME>] [--errorcode
<STRING> ... |--exclude_errorcode <STRING> ... ] [--severity <string>] [--text
<string>] [--max_results <INTEGER>] [--display_exception_stack] [--display_columns
<STRING_LIST>] [--from_logs] beectl export_errorcodes --get_count_service_by_ec
<STRING> beectl export_errorcodes --get_count_ec_by_service <STRING>
```

OPTIONS

--start

Start of time range

--end

End time range

--errorcode

Specific error codes to query for

--exclude_errorcode

Specific error codes to not search for

--severity

Minimum severity to restrict to

--text

Text in Exception stack or metadata parameters to search for

--max_results

Maximum number of results to return

--display_exception_stack

Should the Exception stack be printed

--display_columns

Comma separated list of columns to be displayed. Valid values are [service, messageid, displayname, severity, cause, effect, action, timestamp, exception_stack, ecid, service_inst_id, ctx_map]

--ecid

Execution Context ID

--service_inst_id

Service Instance ID

--get_count_service_by_ec

Service instance ID to get error code counts from, or all to aggregate over all service instances.

--get_count_ec_by_service

Error code to get counts from, or all to aggregate over all error codes.

--from_logs

Query the logs instead of the database.

EXAMPLES

```
beectl export_errorcodes --start 2007-10-10T06:00:00 --end
2007-10-10T08:00:00 --errorcode BEEU-10364
```

Search for all instances of BEEU-10364 between 6AM and 8AM on October 10, 2007.

```
beectl export_errorcodes --start 2007-10-10T06:00:00 --severity
WARNING --text 'QuotaException' --exclude_errorcode BEES-37968
```

Search for all error codes reported since 6AM on October 10, 2007

with severity at least warning and 'QuotaException' in any parameters passed to the error codes except for BEES-37968.

```
beectl export_errorcodes --errorcode BEES-38216 --display_
columns timestamp,cause,action,exception_stack
```

Search for all instances of error code BEES-38216, and display the timestamp, cause, action, and exception stack.

```
beectl export_errorcodes --get_count_service_by_ec
b94885f7-2876-4d95-90aa-76a060875ac6
```

Get counts of error code occurrences in service instance b94885f7-2876-4d95-90aa-76a060875ac6, by error code.

```
beectl export_errorcodes --get_count_ec_by_service BEEU-00822
```

Get counts of error code occurrences of type BEEU-00822, by service.

export_filesystem_logs

Search log files stored on host machines.

SYNTAX

```
beectl export_filesystem_logs --search_string <string> [--maximum_results <int>]
[--file_name_filter <string>] [--host_name_filter <string>] [--beehive_home_filter
<string>] [--output_target <string>] [--output_format <string>] [--display_source
<true|false>] [--display_original_copy <true|false>] [--columns <string_list>]
[--log_analysis <true|false>] [--report_time_range <string>] [--report_message_
type <string>]
```

OPTIONS

--search_string

A search string is composed of a single or a combination of search conditions. A search condition has a field name (e.g. user_id='janedoe'), an operation type (e.g. op='contains') and condition operands (!, &&, | |). The brackets "()" are used to group search conditions together. Valid search field names are: <ORG_ID | COMPONENT_ID | INSTANCE_ID | MSG_ID | HOSTING_CLIENT_ID | MSG_TYPE | MSG_GROUP | MSG_LEVEL | MODULE_ID | PROCESS_ID | THREAD_ID | USER_ID | SUPPL_ATTRS | SUPPL_ATTR.NAME | SUPPL_ATTR.VALUE | UPSTREAM_COMPONENT_ID | DOWNSTREAM_COMPONENT_ID | EXEC_CONTEXT_UNIQUE_ID | EXEC_CONTEXT_SEQ | ERROR_UNIQUE_ID | ERROR_SEQ | MSG_TEXT | MSG_ARGS | NAME | VALUE | DETAIL_PATH | SUPPL_DETAIL | TSTZ_ORIGINATING | TSTZ_NORMALIZED | HOST_ID | HOST_NWADDR | PROB_KEY | BEE_COMPID | BEE_COMPNAME | BEE_PRINCIPALID | BEE_LOGONRECID | BEE_VTHREADID | ATTRIBUTE_VALUE_TO_PRINCIPAL_ID | LOGIN_ID_TO_PRINCIPAL_ID>. Valid operation types are: <EQUALS | CONTAINS | STARTS_WITH | EQUALS_IGNORE_CASE | CONTAINS_IGNORE_CASE | STARTS_WITH_IGNORE_CASE | MATCHES | MATCHES_IGNORE_CASE>. Note: The search string must be enclosed in a pair of double-quotes and \ must be used to escape ! operand. Time stamp query condition can contain two values separated by a comma. Query fields ATTRIBUTE_VALUE_TO_PRINCIPAL_ID and LOGIN_ID_TO_PRINCIPAL_ID are special cases. Field ATTRIBUTE_VALUE_TO_PRINCIPAL_ID works with four operation types: <equals | contains | beginsWith | endsWith> and the search operation is always case-insensitive. But the operation type is not applicable to field LOGIN_ID_TO_PRINCIPAL_ID and any operation type specified for it will be ignored. Those fields are used to match corresponding BEE_PRINCIPAL_ID. Then the matched BEE_PRINCIPAL_ID will be used for the subsequent search with operation type <EQUALS_IGNORE_CASE> only.

--maximum_results

Maximum number of returned records. It tops out at 1,000, if the output_target is screen, otherwise there is no limit.

--file_name_filter

A file name filter is used to speed up searches. Use a comma to separate multiple values and a prefix # to specify excluding. Note: the prefix # is applied to all the values following it.

--host_name_filter

A host name filter is used to speed up searches. Use a comma to separate multiple values and a prefix # to specify excluding. Note: the prefix # is applied to all the values following it.

--beehive_home_filter

A beehive home filter is used to speed up searches. Use a comma to separate multiple values and a prefix # to specify excluding. Note: the prefix # is applied to all the values following it.

--output_target

Specify if direct the output to the screen or to a file.

--output_format

Specify output format. Supported formats are ODL-Text and XML.

--display_source

Default to false. Specify if display the name of the log file source for the returned record.

--display_original_copy

Default to false. Specify if display the original copy for the returned record.

--columns

Default is to display all the log record fields. Restrict to display only specified fields. Valid field names are: <ORG_ID | COMPONENT_ID | INSTANCE_ID | MSG_ID | HOSTING_CLIENT_ID | MSG_TYPE | MSG_GROUP | MODULE_ID | PROCESS_ID | THREAD_ID | USER_ID | SUPPL_ATTRS | UPSTREAM_COMPONENT_ID | DOWNSTREAM_COMPONENT_ID | EXEC_CONTEXT_UNIQUE_ID | ERROR_UNIQUE_ID | MSG_TEXT | MSG_ARGS | DETAIL_PATH | SUPPL_DETAIL | TSTZ_ORIGINATING | TSTZ_NORMALIZED | HOST_ID | HOST_NWADDR | PROB_KEY | BEE_COMPID | BEE_PRINCIPALID | BEE_COMPNAME | BEE_LOGONRECID | BEE_VTHREADID>. Note: field TSTZ_ORIGINATING will always be displayed.

--log_analysis

Default to false. Specify if choose to do the log analysis.

--report_time_range

Specify the desired time range for log analysis report. Only apply when option log_analysis is true.

--report_message_type

Specify the desired message type of the unique message count for log analysis report. Only apply when option log_analysis is true.

EXAMPLES

```
beectl export_filesystem_logs --search_string "(user_id='janedoe' || user_id='johndoe') && \!component_id='j2ee' ) && (msg_text='esb_console' op='contains') "
```

```
beectl export_filesystem_logs --search_string "(TSTZ_ORIGINATING='2007-05-31T17:06:45.620-07:00,2007-05-31T17:08:15.639-07:00') "
```

```
beectl export_filesystem_logs --search_string "(TSTZ_ORIGINATING='2007-05-31T17:06:45.620-07:00') " --maximum_results 10
```

```
beectl export_filesystem_logs --search_string "(user_id='janedoe'&&module_id='security.oc4j') " --file_name_filter beeapp/log.txt,beemgmt --host_name_filter #some-host-name,some-other-host-name --beehive_home_filter /root/dir/product/1.0.6.1.0/beehive_119 --output_target /tmp/temp.log --output_format xml --maximum_results 16
```

export_icalendar

Export invitations and assignments from a calendar and/or tasklist to an iCalendar file.

SYNTAX

```
beectl export_icalendar --file <file> [--overwrite] [--charset <charset>] { --do_
as <unique_identifier> | --do_as_address <uri> | --do_as_authuser <authuser> } [{
--calendar <unique_identifier> | --nocalendar }] [{ --tasklist <unique_identifier>
| --notasklist }] [--filter_uid <icalendar_uid>] [--filter_timerange_start
<date-time>] [--filter_timerange_end <date-time>] [--authuser <authuser>
--authpassword <password>] [--obfuscated]
```

OPTIONS

--file

Specify the full path and name of the iCalendar file to export.

--overwrite

Specify this option to overwrite the iCalendar export file if it already exists.

--charset

Specify the charset that is to be used in the iCalendar file that is being exported (<http://www.iana.org/assignments/character-sets>).

--do_as

Specify the unique identifier of the user or resource performing the action.

--do_as_address

Specify the Uniform Resource Identifier (URI) of the user or resource performing the action.

--do_as_authuser

Specify the login name of the user performing the action.

--calendar

Specify the unique identifier of the source calendar, the default calendar of the "do_as" entity will be used if nothing is specified.

--tasklist

Specify the unique identifier of the source tasklist, the default tasklist of the "do_as" entity will be used if nothing is specified.

--filter_uid

Specify a iCalendar UID. This will filter the export to include only invitations and assignments matching the iCalendar UID.

--filter_timerange_start

Specify a start date. This will filter the export to include only invitations and assignments after the specified date.

--filter_timerange_end

Specify an end date. This will filter the export to include only invitations and assignments before the specified date.

--nocalendar

Do not export from a calendar (VEVENT components will not be exported).

--notasklist

Do not export from a tasklist (VTOD components will not be exported).

EXAMPLES

```
beectl export_icalendar --file file.ics --do_as_address
user@example.com --filter_timerange_start 2007-01-01T01:01:01Z
--filter_timerange_end 2007-02-01T01:01:01Z
```

export_logs

With an option of refreshing the repository first, query the repository to get relevant log records from log files stored on host machines.

SYNTAX

```
beectl export_logs {{ --query_string <string> [ --refresh_repository <true> ] } |
--refresh_repository <true> } [--order_by <string>] [--sort <string>] [--columns
<string_list>] [--output_target <string>] [--output_format <string>] [--display_
source <true|false>] [--maximum_results <int>]
```

OPTIONS**--query_string**

Mandatory if option "refresh_repository" is not specified. A query string is composed of a single or a combination of query conditions. A query condition has a field name (e.g. user_id='janedoe'), an operation type (e.g. op='contains') and condition operands (!, &&, ||). The brackets "(" are used to group query conditions together. Valid query field names are: <TSTZ_ORIGINATING | TSTZ_NORMALIZED | ORG_ID | COMPONENT_ID | MSG_ID | HOSTING_CLIENT_ID | MSG_TYPE | MSG_GROUP | MSG_LEVEL | HOST_ID | HOST_NWADDR | MODULE_ID | PROCESS_ID | USER_ID | UPSTREAM_COMPONENT_ID | DOWNSTREAM_COMPONENT_ID | EXEC_CONTEXT_UNIQUE_ID | ERROR_UNIQUE_ID | THREAD_ID | INSTANCE_ID | MSG_TEXT | BEE_COMPID | BEE_PRINCIPALID | BEE_COMPNAME | BEE_LOGONRECID | BEE_VTHREADID | ATTRIBUTE_VALUE_TO_PRINCIPAL_ID | LOGIN_ID_TO_PRINCIPAL_ID>. Valid operation types are: <EQUALS | CONTAINS | STARTS_WITH | EQUALS_IGNORE_CASE | CONTAINS_IGNORE_CASE | STARTS_WITH_IGNORE_CASE | MATCHES | MATCHES_IGNORE_CASE>. Note: The query string must be enclosed in a pair of double-quotes and \ must be used to escape ! operand. Time stamp query condition can contain two values separated by a comma. Query fields ATTRIBUTE_VALUE_TO_PRINCIPAL_ID and LOGIN_ID_TO_PRINCIPAL_ID are special cases. Field ATTRIBUTE_VALUE_TO_PRINCIPAL_ID works with four operation types: <equals | contains | beginsWith | endsWith> and the search operation is always case-insensitive. But the operation type is not applicable to field LOGIN_ID_TO_PRINCIPAL_ID and any operation type specified for it will be ignored. Those fields are used to match corresponding BEE_PRINCIPAL_ID. Then the matched BEE_

PRINCIPAL_ID will be used for the subsequent query with operation type <EQUALS> only.

--refresh_repository

Mandatory if option "query_string" is not specified. Force an upload of all the log files to refresh the repository.

--order_by

Valid order-by column names are: <TSTZ_ORIGINATING | TSTZ_NORMALIZED | ORG_ID | COMPONENT_ID | MSG_ID | HOSTING_CLIENT_ID | MSG_TYPE | MSG_GROUP | MSG_LEVEL | HOST_ID | HOST_NWADDR | MODULE_ID | PROCESS_ID | USER_ID | UPSTREAM_COMPONENT_ID | DOWNSTREAM_COMPONENT_ID | EXEC_CONTEXT_UNIQUE_ID | ERROR_UNIQUE_ID | THREAD_ID | INSTANCE_ID | MSG_TEXT | BEE_COMPID | BEE_PRINCIPALID | BEE_COMPNAME | BEE_LOGONRECID | BEE_VTHREADID>.

--sort

The query result set can be sorted in ascending or descending order.

--columns

Default is to display all the log record fields. Restrict to display only specified fields. Valid field names are: <ORG_ID | COMPONENT_ID | INSTANCE_ID | MSG_ID | HOSTING_CLIENT_ID | MSG_TYPE | MSG_GROUP | MODULE_ID | PROCESS_ID | THREAD_ID | USER_ID | SUPPL_ATTRS | UPSTREAM_COMPONENT_ID | DOWNSTREAM_COMPONENT_ID | EXEC_CONTEXT_UNIQUE_ID | ERROR_UNIQUE_ID | MSG_TEXT | MSG_ARGS | DETAIL_PATH | SUPPL_DETAIL | TSTZ_ORIGINATING | TSTZ_NORMALIZED | HOST_ID | HOST_NWADDR | PROB_KEY | BEE_COMPID | BEE_PRINCIPALID | BEE_COMPNAME | BEE_LOGONRECID | BEE_VTHREADID>. Note: field TSTZ_ORIGINATING will always be displayed.

--output_target

Specify if direct the output to the screen or to a file.

--output_format

Specify output format. Supported formats are ODL-Text and XML.

--display_source

Default to false. Specify if display the name of the log file source for the returned record.

--maximum_results

Maximum number of returned records.

EXAMPLES

```
beectl export_logs --refresh_repository true
```

```
beectl export_logs --query_string "((user_id='janedoe' || user_id='johndoe') && \!component_id='j2ee') && (msg_text='esb_console' op='contains')"
```

```

beectl export_logs --query_string "(TSTZ_
ORIGINATING='2007-05-31T17:06:45.620-07:00,2007-05-31T17:08:15.6
39-07:00') "

beectl export_logs --query_string "(TSTZ_
ORIGINATING='2007-05-31T17:06:45.620-07:00') " --maximum_results
10

beectl export_logs --query_string "(user_id='janedoe'&&module_
id='security.oc4j') " --order_by THREAD_ID --sort descending
--columns MODULE_ID --columns USER_ID --columns USER_ID
--columns MSG_TEXT --columns THREAD_ID --output_target
/tmp/temp.log --output_format xml --display_source true
--maximum_results 10

```

export_policy

Exports policy data into an XML file.

SYNTAX

```

beectl export_policy --policy_name <name of the policy to export> --scope
<identifier of the container where the policy is defined> --destination
<destination directory where the XML file will be exported>--verbose true or false
to store in verbose or compact form

```

OPTIONS

--policy_name

Specify the name of the policy to export.

--scope

Specify the policy container identifier.

--destination

Specify the destination directory for the XML file.

--verbose

Specify whether to store the rule conditions of policy in verbose form or compact form.

EXAMPLES

```

beectl export_policy --policy_name MyPolicy --scope
enpr=MyEnterprise --destination /private--verbose true

```

export_workflow_template

Exports a workflow template into an XML file.

SYNTAX

```

beectl export_workflow_template --workflow_template <identifier of the workflow
template to be exported> --destination <destination directory of the generated xml
file>

```

OPTIONS

--workflow_template

Specify the identifier of the workflow template to be exported. To determine the identifier of a workflow template, use the `list_workflow_templates` command.

--destination

Specify the destination directory for the XML file.

EXAMPLES

```
beectl export_workflow_template --workflow_template
31BE:6DDD:wftm:3B8937F59ACC1A3AE040578C9509017900000007A121
--destination /private
```

import_documents

Imports documents into Beehive from files on the server without copying the file content. Data on the server files will be treated as read-only; should an imported document be edited in Beehive, a copy of the content will be made at that time.

SYNTAX

```
beectl import_documents --filesystem_reference <Identifier of the filesystem
reference> --folder_path <Folder path> [ --name_filter <Name filter> ] [
--conflict_resolution_mode <ABORT, OVERWRITE, or CREATE_UNIQUE> ]
```

OPTIONS

--filesystem_reference

Identifier of the file system reference to import from.

--folder_path

Full path of the Beehive folder to import to. E.g.

`/MyEnterprise/MyOrganization/MyWorkspace/Documents/MyFolder` would import to `MyFolder`.

--name_filter

(Optional) Filter to use for choosing which documents to import. Syntax is equivalent to SQL LIKE. E.g. `'file%'` would import `file1`, `file2.txt`, but not `my_file`. If not specified, defaults to `'%'`, which includes all documents.

--conflict_resolution_mode

(Optional) How to handle naming conflicts between existing Beehive documents and new documents being imported. `ABORT` will avoid creating the conflicting document, `OVERWRITE` will overwrite the conflicting document, and `CREATE_UNIQUE` will create a unique name for the imported document. If not specified, defaults to `CREATE_UNIQUE`.

EXAMPLES

```
beectl import_documents --filesystem_reference
fsref=MyFileSystemReference,enpr=MyEnterprise --folder_path
```



```
/MyEnterprise/MyOrganization/MyWorkspace/Documents/MyFolder
--name_filter %.txt --conflict_resolution_mode CREATE_UNIQUE
```

import_icalendar

Import an iCalendar file to an existing calendar and/or tasklist. If an iCalendarObject has a UID that already exists in the destination calendar and/or tasklist it will be re-created. VCALENDAR components can have many VEVENT and VTODO sub-components with different UIDs but sub-components of the same UID must be consecutive. A VCALENDAR component imported with a METHOD:X-ORACLE-DELETE will cause all sub-components to be deleted.

SYNTAX

```
beectl import_icalendar --file <file> [--charset <charset>] { --do_as <unique_
identifier> | --do_as_address <uri> | --do_as_authuser <authuser> } [--continue]
[{ --calendar <unique_identifier> | --nocalendar }] [{ --tasklist <unique_
identifier> | --notasklist }] [--authuser <authuser> --authpassword <password>]
[--obfuscated] [--holiday] [--migration]
```

OPTIONS

--file

Specify the full path and name of the iCalendar file to import.

--charset

Specify the charset that is used in the iCalendar file that is being imported (<http://www.iana.org/assignments/character-sets>).

--do_as

Specify the unique identifier of the user or resource performing the action.

--do_as_address

Specify the Uniform Resource Identifier (URI) of the user or resource performing the action.

--do_as_authuser

Specify the login name of the user performing the action.

--continue

If it is passed along with --batchfile, it allows next commands to be executed even if previous one fails.

--calendar

Specify the unique identifier of the destination calendar, the default calendar of the "do_as" entity will be used if nothing is specified.

--tasklist

Specify the unique identifier of the destination tasklist, the default tasklist of the "do_as" entity will be used if nothing is specified.

--nocalendar

Do not import to a calendar (Discard VEVENT components).

--notasklist

Do not import to a tasklist (Discard VTODO components).

--holiday

All events imported in a team workspace will be imported as Holiday events.

--migration

Specify that all the iCalendar file will be imported in the context of a migration. All users participation status can be set by the importer and a limited number of beehive events will be raised.

EXAMPLES

```
beectl import_icalendar --file file.ics --do_as_address
user@example.com
```

import_timezones

Imports time zone definitions to the database.

SYNTAX

```
beectl import_timezones --file <absolute path of tzInfoPkg.xml>
```

OPTIONS**--file**

Specify the full path and file name of the time zone definition file (tzInfoPkg.xml).

EXAMPLES

```
beectl import_timezones --file $ORACLE_
HOME/beehive/seed/tm/tzInfoPkg.xml
```

list_access_control_fields

Lists the AccessControlFields of an entity.

SYNTAX

```
beectl list_access_control_fields --entity <unique identifier of the entity>
```

OPTIONS**--entity**

Specify the unique identifier of the entity for which the AccessControlFields should be listed.

EXAMPLES

```
beectl list_access_control_fields --entity
adoc=MyDocument, wksp=MyWorkspace, enpr=MyEnterprise
```

list_access_types

Lists available access type names and identifiers.

SYNTAX

```
beectl list_access_types
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_access_types
```

list_assigned_roles

Lists AssignedRole entities.

SYNTAX

```
beectl list_assigned_roles [--scope <unique identifier of the Scope>] [--name
<like string>]
```

OPTIONS**--scope**

Specify the unique identifier of the Scope of the AssignedRoles to be listed. If not specified the Scope will be the Enterprise.

--name

Specify the name pattern for the AssignedRoles to be listed. If not specified all accessible AssignedRoles will be returned.

EXAMPLES

```
beectl list_assigned_roles --scope
wksp=MyWorkspace, enpr=MyEnterprise --name MyAssignedRole
```

list_attendant_aaml

Prints the Auto Attendant Markup Language for an auto attendant.

SYNTAX

```
beectl list_attendant_aaml --name <attendant name>
```

OPTIONS**--name**

Name of the attendant to be displayed.

EXAMPLES

```
beectl list_attendant_aaml --name myAttendant
```

list_attendant_prompts

Lists all prompts that have been uploaded for an attendant.

SYNTAX

```
beectl list_attendant_prompts --name <attendant name>
```

OPTIONS**--name**

Name of the attendant for which to display prompts.

EXAMPLES

```
beectl list_attendant_prompts --name my_attendant
```

list_attendants

Lists all attendants in the system.

SYNTAX

```
beectl list_attendants
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_attendants
```

list_audit_events

Lists auditable events

SYNTAX

```
beectl list_audit_events
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_audit_events
```

list_audit_policies

Lists audit policies and prints policy information

SYNTAX

```
beectl list_audit_policies [--name <Name of the audit policy>] [--container  
<Container identifier>]
```

OPTIONS**--name**

Name of the audit policy

--container

Container identifier

EXAMPLES

```
beectl list_audit_policies --name MyAuditPolicy
```

```
beectl list_audit_policies --name MyAuditPolicy --container  
enpr=MyEnterprise
```

list_audit_templates

Lists audit policy templates and prints template information. Use --name option for detailed information about each audit policy template

SYNTAX

```
beectl list_audit_templates [--name <Name of the audit template>]
```

OPTIONS**--name**

Name of the audit template

EXAMPLES

```
beectl list_audit_templates --name "Artifact access"
```

list_audit_trails

Lists audit trails and prints trail information

SYNTAX

```
beectl list_audit_trails [--name <Name of the audit trail>]
```

OPTIONS**--name**

Name of the audit trail

EXAMPLES

```
beectl list_audit_trails --name MyAuditTrail
```

list_bootstrap_configuration

Displays bootstrap configuration for local Oracle Beehive Application tier.

SYNTAX

```
beectl list_bootstrap_configuration
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_bootstrap_configuration
```

list_calendars

Lists the existing calendars of a user, resource or workspace.

SYNTAX

```
beectl list_calendars { --calendarowner <unique_identifier> | --select_by_address  
<uri> | --select_by_authuser <authuser> --select_by_user_name <user_name> |  
--select_by_resource_name <resource_name> | --select_by_workspace_name <workspace_  
name> } [--authuser <authuser> --authpassword <password>] [--obfuscated]
```

OPTIONS**--calendarowner**

Specify the unique identifier of a user, resource or workspace.

--select_by_address

Specify the Uniform Resource Identifier (URI) of a user, resource or team workspace.

--select_by_authuser

Specify the login name of a user.

--select_by_user_name

Specify the name of a user.

--select_by_resource_name

Specify the name of a resource.

--select_by_workspace_name

Specify the name of a workspace.

EXAMPLES

```
beectl list_calendars --select_by_address user@example.com
```

list_categories

Lists the categories in the enterprise. If the recurse option is used then sub-categories are also listed.

SYNTAX

```
beectl list_categories --recurse <Y/N> --parent_category <Identifier of the parent category> --output_format <XML>
```

OPTIONS**--recurse**

Control the categories that are returned. Use the Y argument with this option to return all categories in an enterprise. Use the N argument with this option to return only root level categories.

--parent_category

Unique Identifier for Parent Category.

--output_format

If 'XML' the output is sent as xml to standard out else its printed as table on standard output.

EXAMPLES

```
beectl list_categories --recurse Y --parent_category
421C:6639:catg:3BF460625AB3FCC9E040548C1C8279630000000001FF
```

```
beectl list_categories --recurse Y --parent_category
catg=Resource_US,catg=Resource_ROOT,enpr=bee_ent --output_format
XML
```

list_category

Prints information about a category given a category identifier

SYNTAX

```
beectl list_category --category <Identifier of the category to be listed>
```

OPTIONS**--category**

Specify the identifier of the category.

EXAMPLES

```
beectl list_category --category
421C:6639:catg:3BF460625AB3FCC9E040548C1C82796300000000020B

beectl list_category --category catg=Resource_US,catg=Resource_
ROOT,enpr=bee_ent
```

list_category_configuration

Lists the category configuration on the given scope or heterogeneous folder.

SYNTAX

```
beectl list_category_configuration --container <Configuration scope or
heterogenous folder>
```

OPTIONS**--container**

Scope or heterogeneous folder on which the category configuration should be listed.

EXAMPLES

```
beectl list_category_configuration --container
orgn=MyOrganization,enpr=MyEnterprise
```

list_client_application_configuration

Lists the client application configurations.

SYNTAX

```
beectl list_client_application_configuration [--configuration <client application
configuration identifier >|--community <community identifier>]
```

OPTIONS**--community**

Specify the identifier of the community.

--configuration

Specify the identifier of the client application configuration.

EXAMPLES

```
beectl list_client_application_configuration --configuration
1234:5678:capc:2E0329B0705F0E40E040578C92160957000000000434

beectl list_client_application_configuration --configuration
1234:5678:capc:2E0329B0705F0E40E040578C92160957000000000434
--community
1234:5678:orgn:2E0329B0705F0E40E040578C92160957000000000321
```


list_client_application_modules

Lists the modules for a given client application patchset.

SYNTAX

```
beectl list_client_application_modules --patchset <identifier of the client
application patchset>
```

OPTIONS

--patchset

Specify the identifier of the client application patchset. Use `list_client_application_patchsets` command to determine the identifier of a client application patchset.

EXAMPLES

```
beectl list_client_application_modules --patchset
1234:5678:capp:2E0329B0705F0E40E040578C92160957000000000434
```

list_client_application_patchsets

Lists the patchsets for a given client application version.

SYNTAX

```
beectl list_client_application_patchsets --application_version <identifier of the
client application version>
```

OPTIONS

--application_version

Specify the identifier of the client application version. Use `list_client_application_versions` command to determine the identifier of a client application version.

EXAMPLES

```
beectl list_client_application_patchsets --application_version
1234:5678:capv:2E0329B0705F0E40E040578C92160957000000000434
```

list_client_application_versions

Lists all the versions for a given client application.

SYNTAX

```
beectl list_client_application_versions --application <identifier of the client
application>
```

OPTIONS

--application

Specify the identifier of the client application. Use `list_client_applications` command to determine the identifier of the client application.

EXAMPLES

```
beectl list_client_application_versions --application
1234:5678:capn:2E0329B0705F0E40E040578C92160957000000000434
```

list_client_applications

Lists all the client applications.

SYNTAX

```
beectl list_client_applications
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_client_applications
```

list_coexistence_connectors

Lists all configured coexistence connectors.

SYNTAX

```
beectl list_coexistence_connectors
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_coexistence_connectors
```

list_coexistence_profiles

Lists the users configured with a coexistence profile.

SYNTAX

```
beectl list_coexistence_profiles [--display_user_id] [--users_without_profile
--file users.xml]
```

OPTIONS**--display_user_id**

Specify if the CollabId of users should be displayed.

--users_without_profile

List users without a coexistence profile.

--file

Specify the name of the file in which the list of non coexisting users should be written.

EXAMPLES

```
beectl list_coexistence_profiles
```

```
beectl list_coexistence_profiles --users_without_profile --file  
users.xml
```

list_coexistence_status

Reports the status of the containers and users involved in the coexistence. By default this command outputs the status of calendars, address books, email inboxes as well as of the users configured for coexistence. One can restrict the information being returned by specifying one or more of the optional parameters.

SYNTAX

```
beectl list_coexistence_status [--calendar] [--addressbook] [--email] [--user]
```

OPTIONS**--calendar**

Lists calendar coexistence status.

--addressbook

Lists address book coexistence status.

--email

Lists email coexistence status.

--user

Lists user provision status.

EXAMPLES

```
beectl list_coexistence_status
```

```
beectl list_coexistence_status --user
```

```
beectl list_coexistence_status --calendar
```

```
beectl list_coexistence_status --calendar --addressbook --email
```

list_command_metadata

Lists all the metadata about given command.

SYNTAX

```
beectl list_command_metadata --command_name <command name>
```

OPTIONS

--command_name

Command name.

EXAMPLES

```
beectl list_command_metadata --command_name list_command_
metadata
```

list_commands

Lists the command names based on the given criteria.

It also lists all the available categories and actions for easy access. If the command is executed with various options then the result would be command names qualifying for ALL specified criteria rather than ONE OR MORE of the criteria.

SYNTAX

```
beectl list_commands (--display_actions | --display_categories | ( [--action
<action name>] [--category <category name> ] [--name <substring of desired command
list> ] [--advanced | --deprecated] | --all)
```

OPTIONS

--display_actions

Displays all available actions.

--display_categories

Displays all available categories.

--action

Search will be based on given action.

--category

Search will be based on given category. This option can be supplied multiple times.

--name

Command name substring, a regular expression using * or ? can be used as option value. Blank search using * or ? meta characters only is not supported. Though these characters can be used at the end of the pattern. For example, list* is a valid pattern, but *list is not.

--advanced

Only ADVANCED commands will be listed.

--deprecated

Only DEPRECATED commands will be listed.

--all

Command name substring, a regular expression using * or ? can be used as option value. Blank search using * or ? meta characters only is not supported. Though these

characters can be used at the end of the pattern. For example, list* is a valid pattern, but *list is not.

EXAMPLES

```
beectl list_commands --display_actions
```

```
beectl list_commands --display_categories
```

```
beectl list_commands --advanced
```

```
beectl list_commands --category "users" --category "coexistence"
--action LIST
```

Above example will return all command names having general visibility, categories users, coexistence and action LIST.

```
beectl list_commands --category "users" --name oc4j
```

Above example will list all the commands which have "oc4j" in their name.

list_components

Lists components in the configuration repository.

If no option is specified, then all the components in the configuration repository will be listed.

When --type <type name> is specified all the components of that type are listed.

When --use_local_home flag is specified, only managed system components from the current ORACLE HOME is returned.

All the property values are assumed to be strings and with that assumption search is performed.

SYNTAX

```
beectl list_components (--display_types | [--type <type name>]) [--use_local_home]
[--configuration_version ( proposed | active | <long version number> )])
```

OPTIONS

--display_types

Displays all the valid component types.

--type

Lists all components of given type.

--use_local_home

Searches only in the current ORACLE HOME.

--configuration_version

Configuration version. Valid values are active, proposed, any positive long number.

EXAMPLES

```
beectl list_components
```

```
beectl list_components --type ServiceInstance
```

Lists all the components of type ServiceInstance.

```
beectl list_components --display_types
```

Above example lists all valid component type names.

list_conference_templates

Lists conference-template artifacts under workspace

SYNTAX

```
beectl list_conference_templates --parent <Workspace identifier> --count-limit <A  
count limit for a list of conference templates>
```

OPTIONS**--parent**

Workspace identifier

--count-limit

A count limit for a list of conference templates

EXAMPLES

```
beectl list_conference_templates --parent  
6490:45C8:wspr:F20E3F75004040B5AE14B64B96F89C3A000000000022
```

list_conferences

Lists conference artifacts under workspace

SYNTAX

```
beectl list_conferences --parent <Workspace identifier> --count-limit <A count  
limit for a list of conferences>
```

OPTIONS**--parent**

Workspace identifier

--count-limit

A count limit for a list of conferences

EXAMPLES

```
beectl list_conferences --parent
6490:45C8:wspr:F20E3F75004040B5AE14B64B96F89C3A000000000022
```

list_configuration_versions

Lists all available configuration versions and activation time information

SYNTAX

```
beectl list_configuration_versions
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_configuration_versions
```

list_connection_pools

Lists available connection pools in the system.

SYNTAX

```
beectl list_connection_pools
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_connection_pools
```

list_custom_user_properties

The list_custom_user_properties command lists all custom properties of users.

SYNTAX

```
beectl list_custom_user_properties
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_custom_user_properties
```

list_device_commands

Lists the device commands for a given device. The list can be further filtered by specifying the status of the device command.

SYNTAX

```
beectl list_device_commands --device <identifier of the device> [--status <device  
command status>]
```

OPTIONS

--device

Specify the identifier of the device. Use list_devices command to determine the identifier of the device.

--status

Specify the status of the device command. The following are the valid command statuses: PENDING SUCCESS ERROR WARNING

EXAMPLES

```
beectl list_device_commands --device  
1234:5678:devi:1234567890123456789012 --status PENDING
```

list_device_logs

Lists the device logs for a given device.

SYNTAX

```
beectl list_device_logs --device <identifier of the device>
```

OPTIONS

--device

Specify the identifier of the device. Use list_devices command to determine the identifier of the device.

EXAMPLES

```
beectl list_device_logs --device  
1234:5678:devi:1234567890123456789012
```

list_device_profiles

Lists all the device profiles.

SYNTAX

```
beectl list_device_profiles
```


OPTIONS

This command has no options

EXAMPLES

```
beectl list_device_profiles
```

list_device_types

Lists all the device types.

SYNTAX

```
beectl list_device_types
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_device_types
```

list_devices

Lists the devices for a user.

SYNTAX

```
beectl list_devices --user <identifier of the user>
```

OPTIONS**--user**

Specify the identifier of the user owing the device. Use list_users command to determine the identifier of a user.

EXAMPLES

```
beectl list_devices --user  
1234:5678:user:2E0329B0705F0E40E040578C921609570000000000434
```

list_directory_profiles

The list_directory_profiles command lists directory profiles in an XML file.

SYNTAX

```
beectl list_directory_profiles --file <filename>
```

OPTIONS**--file**

XML file to be created.

EXAMPLES

```
beectl list_directory_profiles --file MyDirectoryProfile.xml
```

list_enterprises

Lists all enterprises and prints names and identifiers

SYNTAX

```
beectl list_enterprises
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_enterprises
```

list_errorcode_catalog

List all error code definitions in beehive.

SYNTAX

```
beectl list_errorcode_catalog [--display_columns <STRING_LIST>] [--errorcode_range  
<xxxxx-yyyyy>] [--errorcode <BEEEX-12345> ... ]
```

OPTIONS**--display_columns**

Comma separated list of columns to be displayed. Valid arguments are [service, messageid, displayname, severity, cause, effect, action]

--errorcode_range

Dash-separated range of error codes to list from the catalog, without the prefix.
Default: 00000-99999

--errorcode

An individual error code to display information about, including prefix.

EXAMPLES

```
beectl list_errorcode_catalog
```

Lists all error code definitions in beehive.

```
beectl list_errorcode_catalog --display_columns  
messageid,displayname,cause --errorcode_range 00400-00499
```

Lists the messageid, display name, and cause of all errorcodes
between 00400 and 00499

```
beectl list_errorcode_catalog --errorcode 'BEEU-00822'
```

Lists all catalog information on the error BEEU-00822

list_events

Lists all business object events.

SYNTAX

```
beectl list_events [ --event_name <event name to be listed> ]
```

OPTIONS

--event_name

Specify the name of the event to be listed.

EXAMPLES

```
beectl list_events --event_name MyEvent
```

list_external_contacts

The list_external_contacts command lists contacts that match specified search criteria. If search criteria are not specified, then all contacts are listed. It also lists the details of the contact(s) whose identifier is specified.

SYNTAX

```
beectl list_external_contacts {      --count <true|false>      |      --contact
<identifier of external contact >    [ --show <show attributes(ALL|MORE)> ]
|      --email_id <Email address of the user>      [ --show <show
attributes(ALL|MORE)> ]      |      [ --family_name <family name of the contact>
... ]      [ --given_name <given name of the contact> ... ]      [ --display_
name <display name of the contact> ... ]      [ --middle_name <middle name of the
contact> ... ]      [ --job_title <job title of the contact> ... ]      [
--prefix <prefix of the contact> ... ]      [ --suffix <suffix of the contact>
... ]      [ --nick_name <nick name of the contact> ... ]      [ --office_
location <office location of the contact> ... ]      [ --company <company of the
contact> ... ]      [ --profession <profession of the contact> ... ]      [
--department <department of the contact> ... ]      [ --organization
<organization identifier> ... ]      [ --property
<name(assistant|profession|certificate|notes)=value=description> ... ]      [
--address <type of address(business_1|other_5|personal_4|proxy_
1|...):scheme(im|mailto|...):value> ... ]      [ --status <status of
contact(enabled|disabled)> ... ]      [ --is_deleted <true|false> ]      [
--created_by <identifier of creator> ... ]      [ --modified_by <identifier of
modifier> ... ]      [ --show <show attributes(ALL|MORE)> ]      }
```

OPTIONS

--contact

The identifier of the external contact

--email_id

Email id of the external contact

--family_name

Family name of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--given_name

Given name of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--display_name

Display name of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--middle_name

Middle name of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--job_title

Job title of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--prefix

Prefix of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--suffix

Suffix of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--nick_name

Nickname of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--office_location

Office location of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--company

Company of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--profession

Profession of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--department

Department of the contact. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--organization

Identifiers of the organizations the contact belongs to.

--property

Details of the property in the format name=value. Supported names are certificate, assistant, profession and notes. Note, no equals to symbol(=) should be present in the name or value.

--address

Address of the contact in the format type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--status

Sets the provisioning status of the external contact. Supported values are ENABLED, DISABLED.

--is_deleted

Contacts whose provisioning status is deleted.

--created_by

Identifier of the entity who created the contact.

--modified_by

Identifier of the entity who modified the contact.

--count

Lists the number of contacts. When this option is used, no other information about the contacts is listed.

--show

Lists some or all the attributes of the contact. Valid values are ALL or MORE. If nothing is specified the default important attributes are listed.

--match

If all the predicates values should match with the attributes of the contact or one or more attributes should match. Permitted values are ALL or ANY. Default is ANY.

EXAMPLES

```
beectl list_external_contacts
```

```
beectl list_external_contacts --count
```

```
beectl list_external_contacts --contact  
6A95:21EB:extp:D9E9FC8134544BCE9D60559F9B997CCD000000000000  
--show ALL
```

```
beectl list_external_contacts --email_id person1@example.com  
--show MORE
```

```
beectl list_external_contacts --given_name User1GivenName --show  
ALL
```

```
beectl list_external_contacts --given_name User1% --office_  
location 4A0% --match ALL --show MORE
```

list_file_plan

Lists the file plan.

SYNTAX

```
beectl list_file_plan
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_file_plan
```

list_filesystem_references

Lists the file system path, read-only status, and identifier of all available file system references.

SYNTAX

```
beectl list_filesystem_references
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_filesystem_references
```

list_groups

The list_groups command lists groups that match specified search criteria. If search criteria are not specified, then all groups are listed.

SYNTAX

```
beectl list_groups { --count <true|false> | --group <Identifier
of the group> [ --show <show attributes(ALL|MORE|MEMBERS)> ] |
--email <Email address of the group> [ --show <show
attributes(ALL|MORE|MEMBERS)> ] | [ --name <name of the group> ... ]
[ --description <description of the group> ... ] [ --scope <scope of the
group> ... ] [ --organization <organization identifier> ... ] [
--property <name(is_auto_confirm_on|moderator)=value=description> ... ] [
--address <type of address(business_1|other_5|personal_4|proxy_
1|...):scheme(im|mailto|...):value> ] [ --is_deleted <true|false> ... ]
[ --created_by <identifier of creator> ... ] [ --modified_by <identifier of
modifier> ... ] [ --match <match attributes(ANY|ALL)> ... ] [ --show
<show attributes(ALL|MORE|MEMBERS)> ] }
```

OPTIONS

--group

Identifier of the group

--email

Email id of the group

--family_name

Name of the group. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--description

Description of the group. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1%

will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--scope

Scope or parent identifier of the group.

--organization

Identifiers of the organizations the group belongs to.

--property

Details of the property in the format name=value. Supported names are is_auto_confirm_on, moderator. Note, no equals to symbol(=) should be present in the name or value.

--address

Address of the group in the format type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--is_deleted

Groups whose status is deleted.

--created_by

Identifier of the entity who created the group.

--modified_by

Identifier of the entity who modified the group.

--count

Lists the number of groups. When this option is used, no other information about the groups is listed.

--show

Lists some or all attribute or the members of the group. Valid values are ALL or MORE OR MEMBERS. If nothing is specified the default important attributes are listed.

--match

If all the predicates values should match with the attributes of the user or one or more attributes should match. Permitted values are ALL or ANY. Default is ANY.

EXAMPLES

```
beectl list_groups
```

```
beectl list_groups --count
```



```
beectl list_groups --group grup=group1,enpr=example --show ALL
```

```
beectl list_groups --email group1@example.com --show MORE
```

```
beectl list_groups --group grup=group1,enpr=example --MEMBERS
```

```
beectl list_groups --name Group1Name --show ALL
```

```
beectl list_groups --name Group1% --scope enpr=enpr1 --match ALL  
--show MORE
```

list_language_pack

Displays details of the language pack resources managed by the Beehive deployment.

SYNTAX

```
beectl list_language_pack [--full --base_names --locales --all_names --warnings  
--versions]
```

OPTIONS

--full

Include all details.

--base_names

include the supported base-names.

--locales

include all supported locales.

--warnings

include warnings about non-fatal inconsistencies.

--all_names

include all xcliff file names.

--versions

include version information for each listed file.

EXAMPLES

```
beectl list_language_pack --full
```

list_local_acl

Lists the Local Access Control List (LACL) of an entity.

SYNTAX

```
beectl list_local_acl --entity <unique identifier of the entity>
```

OPTIONS**--entity**

Specify the unique identifier of the entity for which the Local Access Control List (LACL) should be listed.

EXAMPLES

```
beectl list_local_acl --entity  
adoc=MyDocument,wksp=MyWorkspace,enpr=MyEnterprise
```

list_max_address_count

The `list_max_address_count` command lists the maximum number of addresses of an address type that can be set for a given person-contact, group-contact or resource-contact in an address-book. The address types determine the type of address like BUSINESS, PERSONAL and OTHER. This command also lists the system defined maximum limit, which cannot be exceeded.

SYNTAX

```
beectl list_max_address_count
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_max_address_count
```

list_my_conferences

Lists conference artifacts under workspace

SYNTAX

```
beectl list_my_conferences --count-limit <A count limit for a list of conferences>
```

OPTIONS**--count-limit**

A count limit for a list of conferences

EXAMPLES

```
beectl list_my_conferences --count-limit 1000
```

list_organizations

Lists organizations in the given scope

SYNTAX

```
beectl list_organizations --scope <Identifier of enterprise or organization>
[--recurse <TRUE|FALSE. Default value is FALSE. Recursively list organizations>]
[--name <Organization name>]
```

OPTIONS**--scope**

Identifier of the parent scope (enterprise or organization)

--recurse

TRUE|FALSE. Default value is FALSE. Recursively list organizations

--name

Organization name

EXAMPLES

```
beectl list_organizations --scope
9941:2345:enpr:58D193D162CE4ED89FF66AB4E55745B6345464545453
--recurse TRUE

beectl list_organizations --scope enpr=ORCL --name MyOrg
```

list_policies

Lists policies in an specific container. Details returned include policy names and identifiers.

SYNTAX

```
beectl list_policies [ --policy_name <name of the policy to be listed> ] [ --scope
<container where the policy is deployed> ] [ --children <boolean specifying
whether to include policies defined at child containers> ] [ --enforced <boolean
specifying whether to include enforced policies> ]
```

OPTIONS**--policy_name**

Specify the name of the policy.

--scope

Specify the identifier of the container where policy is deployed.

--children

Specify whether to include policies defined at child containers.

--enforced

Specify whether to include enforced policies.

EXAMPLES

```
beectl list_policies --policy_name MyPolicy --scope  
enpr=MyEnterprise --children true --enforced false
```

list_policy_actions

Lists all policy actions.

SYNTAX

```
beectl list_policy_actions
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_policy_actions
```

list_policy_schemas

Lists policy schemas in the current enterprise. Details returned include policy schema names and identifiers.

SYNTAX

```
beectl list_policy_schemas --name <name of the policy schema>
```

OPTIONS**--name**

Specify the name of the policy schema.

EXAMPLES

```
beectl list_policy_schemas --name ExamplePolicySchema
```

list_policy_templates

Lists policy templates in a specified container. Details returned include policy template names and identifiers.

SYNTAX

```
beectl list_policy_templates --name <name of the policy template to be listed>  
--scope <container where the policy template is defined>
```

OPTIONS**--name**

Specify the name of the policy template.

--scope

Specify the identifier of the container where policy template is deployed.

EXAMPLES

```
beectl list_policy_templates --name ExamplePolicyTemplate
--scope
9941:2345:enpr:58D193D162CE4ED89FF66AB4E55745B6345464545453
```

list_ports

Lists various available ports.

By default it shows ports used by current Oracle Beehive Application tier only.

Valid protocols are

SMTP

IMAP

XMPP

XMPPS

FTP

HTTP

HTTPS

BTP

BTPS

OC4J-AJP-RANGE

OC4J-RMI-RANGE

OC4J-RMIS-RANGE

OC4J-JMS-RANGE

OC4J-AJP-RANGE identifies the range of ports in current site for either AJP or secure AJP protocol whichever is enabled.

Description of command output:-

1- Protocol:- Contains protocol name. It can be empty, if port is internal.

2- Listen Port:- The value of the port on which listening component is listening. This is the value which will be seen in operating system port management utilities like netstat.

3- Virtual Port:- Port to which the clients will connect. This value is for entire site.

4- Defining Component:- Identifier of the component, port property is modeled.

5- Property Name:- Name of the property for port on the defining configuration object.

6- Listen Component:- Identifier of the configuration object which listens on the listen port.

SYNTAX

```
beectl list_ports [--instance <beehive instance system identifier or alias>]
[--all]
```

OPTIONS**--instance**

System object identifier of Beehive Instance for which ports should be shown.

--all

Flag indicating if all the ports in the system should be listed.

EXAMPLES

```
beectl list_ports --all
```

Above example lists ports used by all the Oracle Beehive Application tiers.

list_preference_profiles

The list_preference_profiles command lists preference profiles for a consumer.

SYNTAX

```
beectl list_preference_profiles --consumer <Identifier of the consumer>
```

OPTIONS**--consumer**

Identifier of the consumer

EXAMPLES

```
beectl list_preference_profiles --consumer loginid=user1
```

list_preference_properties

The list_preference_properties command lists all effective preference properties of a preference set.

SYNTAX

```
beectl list_preference_properties --set <Identifier of the preference set
specified in id format, which can be determined by running list_preference_sets
command with "--entity_format id" option.>
```

OPTIONS**--set**

Identifier of the preference set specified in id format, which can be determined by running list_preference_sets command with "--entity_format id" option.

EXAMPLES

```
beectl list_preference_properties --set
5965:3658:prfs:B7CAC0E31E554593B7A93B24B0FD09F2000000000979
```

list_preference_sets

The list_preference_sets command lists all preference sets for a preference profile.

SYNTAX

```
beectl list_preference_sets --profile <Preference profile identifier>
```

OPTIONS**--profile**

Identifier of the preference profile.

EXAMPLES

```
beectl list_preference_sets --profile
prfp=MyProfile,loginid=user1
```

list_privileges

Lists available Privilege names.

SYNTAX

```
beectl list_privileges
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_privileges
```

list_properties

Prints property value of a component given a component identifier and property name. If property name is not specified then all the properties will be listed.

SYNTAX

```
beectl list_properties --component <system object identifier or alias of the
component> [--name <name>] [--configuration_version ( ACTIVE | PROPOSED | <long
version number> )]
```

OPTIONS**--component**

Component identifier

--name

Name of the property

--configuration_version

Configuration version. Valid values are active, proposed, any positive long number.

EXAMPLES

```
beectl list_properties --component
288d5051-2632-4800-b796-b3e16ca58f2d --configuration_version
ACTIVE
```

list_property_metadata

Lists the metadata about all the properties of a system model object.

SYNTAX

```
beectl list_property_metadata --type <System model object type> [--full_report]
```

OPTIONS**--type**

Type of the component for which property metadata to be listed.

--full_report

Flag indicating if full report should be displayed. It contains description about properties also.

EXAMPLES

```
beectl list_property_metadata --type WorkspacesService
```

list_resources

Lists resources.

SYNTAX

```
beectl list_resources [--select_by_name <name_regex>] [--select_by_identifier
<identifier_regex>] [--select_by_capacity <capacity>] [--external]
```

OPTIONS**--select_by_name**

Specify the resource name criteria. This option accepts a regular expression match.

--select_by_identifier

Specify the resource identifier criteria. This option accepts a regular expression match.

--select_by_capacity

Specify the resource capacity.

--external

Return external resources. If this option is not specified, only bookableresources will be returned.

EXAMPLES

```
beectl list_resources --select_by_name "Resource"
```

list_role_definitions

Lists RoleDefinition entities.

SYNTAX

```
beectl list_role_definitions [--scope <unique identifier of the Scope>] [--name  
<like string>]
```

OPTIONS**--scope**

Specify the unique identifier of the Scope of the RoleDefinitions to be listed. If not specified the Scope will be the Enterprise.

--name

Specify the name pattern of the RoleDefinitions to be listed. If not specified all accessible RoleDefinitions will be returned.

EXAMPLES

```
beectl list_role_definitions --scope  
wksp=MyWorkspace,enpr=MyEnterprise --name MyRoleDefinition
```

list_sensitivities

Lists Sensitivity entities.

SYNTAX

```
beectl list_sensitivities --workspace <unique identifier of the Workspace> [--name  
<like string>]
```

OPTIONS**--workspace**

Specify the unique identifier of the Workspace of the Sensitivities to be listed.

--name

Specify the name pattern for the Sensitivities to be listed. If not specified all accessible Sensitivities will be returned.

EXAMPLES

```
beectl list_sensitivities --workspace  
wksp=MyWorkspace,enpr=MyEnterprise --name MySensitivity
```

list_sensitivity_acl

Lists the Sensitivity Access Control List (SACL) of a Sensitivity.

SYNTAX

```
beectl list_sensitivity_acl --sensitivity <unique identifier of the Sensitivity>
```

OPTIONS

--sensitivity

Specify the unique identifier of the Sensitivity whose Sensitivity Access Control List (SACL) should be listed.

EXAMPLES

```
beectl list_sensitivity_acl --sensitivity  
acsn=MySensitivity,wksp=MyWorkspace,enpr=MyEnterprise
```

list_statistics

Lists the statistics for a given type or system object or for the entire site (default).

SYNTAX

```
beectl list_statistics [--type <System model object type>] [--component <stat  
provider system model object identifier or alias>])
```

OPTIONS

--type

Type of the component for which statistics to be listed.

--component

System object identifier of the component for which statistics to be listed.

EXAMPLES

```
beectl list_statistics --type WorkspacesServiceInstance
```

list_supported_entity_types

Prints the supported entity types which can be used in business object distinguished naming pattern instead of system generated identifier and their description.

If a value contains \ (back slash) or a , (comma), then it has to be escaped using back slash. For example, "wksp=Personal workspace\, Admin,orgn=HR,enpr=oracle" refers to Workspace of name "Personal workspace, Admin" that exists in Organization "HR" that exists directly in Enterprise "Oracle".

SYNTAX

```
beectl list_supported_entity_types
```

OPTIONS

This command has no options

EXAMPLES

```
beectl list_supported_entity_types
```

list_tasklists

Lists existing tasklists of a user, resource or workspace.

SYNTAX

```
beectl list_tasklists { --tasklistowner <unique_identifier> | --select_by_address
<uri> | --select_by_authuser <authuser> --select_by_user_name <user_name> |
--select_by_resource_name <resource_name> | --select_by_workspace_name <workspace_
name> } [--authuser <authuser> --authpassword <password>] [--obfuscated]
```

OPTIONS**--tasklistowner**

Specify the unique identifier of a user, resource or workspace.

--select_by_address

Specify the Uniform Resource Identifier (URI) of a user, resource or team workspace.

--select_by_authuser

Specify the login name of a user.

--select_by_user_name

Specify the name of a user.

--select_by_resource_name

Specify the name of a resource.

--select_by_workspace_name

Specify the name of a workspace.

EXAMPLES

```
beectl list_tasklists --select_by_address user@example.com
```

list_timezones

Lists time zones in the database. The list can be limited by common time zones or by time zone names.

SYNTAX

```
beectl list_timezones [--all] | [--select_by_common] [--select_by_name
<TimezoneName>]
```

OPTIONS

--all

Lists all time zones. This option cannot be used with the `--select_by_name` or `--select_by_common` option.

--select_by_common

Lists common time zones. This is a default option if no arguments are specified.

--select_by_name

Specifies a time zone name. To list all time zones, use an asterisk(*) as an argument.

EXAMPLES

```
beectl list_timezones --all
```

```
beectl list_timezones --select_by_common
```

```
beectl list_timezones --select_by_name Asia/Shanghai
```

```
beectl list_timezones --select_by_common --select_by_name  
Asia/Shanghai
```

list_trusted_identity

This commands lists the trusted identities. The type has to be specified. For type SES, it lists the names of the trusted entities.

SYNTAX

```
beectl list_trusted_identity --type <type(SES|WSSEC)>
```

OPTIONS

--type

Type of the trusted identity. Permitted values are SES or WSSEC. SES refers to Secure Enterprise Search. WSSEC refers to Web services security.

EXAMPLES

list_users

The `list_users` command lists users that match specified search criteria. If search criteria are not specified, then all users are listed.

SYNTAX

```
beectl list_users {      --count <true|false>      |      --user <User  
Identifier>      [ --show <show attributes(ALL|MORE)> ]      |      --email  
<Email address of the user>      [ --show <show attributes(ALL|MORE)> ]      |  
[ --family_name <family name of the user> ... ]      [ --given_name <given name  
of the user> ... ]      [ --display_name <display name of the user> ... ]      [  
--middle_name <middle name of the user> ... ]      [ --job_title <job title of  
the user> ... ]      [ --prefix <prefix of the user> ... ]      [ --suffix  
<suffix of the user> ... ]      [ --nick_name <nick name of the user> ... ]  
[ --office_location <office location of the user> ... ]      [ --company <company
```

```

of the user> ... ]          [ --profession <profession of the user> ... ]          [
--department <department of the user> ... ]          [ --manager <manager identifier>
... ]          [ --extended_enterprise_user <true|false> ]          [ --organization
<organization identifier> ... ]          [ --property
<name(certificate|notes)=value=description> ... ]          [ --address <type of
address(business_1|other_5|personal_4|proxy_1|...):scheme(im|mailto|...):value>
... ]          [ --status <status of user(locked|enabled|disabled)> ... ]          [
--is_deleted <true|false> ]          [ --created_by <identifier of creator> ... ]
[ --modified_by <identifier of modifier> ... ]          [ --show <show
attributes(ALL|MORE)> ]          }

```

OPTIONS

--user

Identifier of the user.

--email

Email id of the user

--family_name

Family name of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--given_name

Given name of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--display_name

Display name of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--middle_name

Middle name of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--job_title

Job title of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--prefix

Prefix of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return

doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--suffix

Suffix of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--nick_name

Nickname of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--office_location

Office location of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--company

Company of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--profession

Profession of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--department

Department of the user. SQL wildcards '%' and '_' are also permitted. The % and _ characters will be treated as literals if preceded by the '\' character. Examples: doc1% will return doc1 and doctest whereas doctest_ will return doctest2. doc_ will return doc1 and doc_. doc_ will return doc_. Exact match is found if no wildcards exists.

--manager

Identifier of the manager.

--organization

Identifiers of the organizations the user belongs to.

--property

Details of the property in the format name=value. Supported names are certificate, assistant, profession and notes. Note, no equals to symbol(=) should be present in the name or value.

--address

Address of the user in the format type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--status

Sets the provisioning status of the user. Supported values are ENABLED, DISABLED, LOCKED.

--is_deleted

Users whose provisioning status is deleted.

--extended_enterprise_user

Lists all extended enterprise user.

--created_by

Identifier of the entity who created the user.

--modified_by

Identifier of the entity who modified the user.

--count

Lists the number of users. When this option is used, no other information about the users is listed.

--show

Lists some or all the attributes of the user. Valid values are ALL or MORE. If nothing is specified the default important attributes are listed.

--match

If all the predicates values should match with the attributes of the user or one or more attributes should match. Permitted values are ALL or ANY. Default is ANY.

EXAMPLES

```
beectl list_users
```

```
beectl list_users --count
```

```
beectl list_users --user loginid=user1@example.com --show ALL
```

```
beectl list_users --email user1@example.com --show MORE
```

```
beectl list_users --given_name User1GivenName --show ALL
```

```
beectl list_users --given_name User1% --office_location 4A0%  
--match ALL --show MORE
```

```
beectl list_users --manager loginid=user2@example.com  
--extended_enterprise_user --match ALL --show MORE
```

```
beectl list_users --address BUSINESS_1:mailto:%@example.com  
--address BUSINESS_1:mailto:user1@example.com --match ANY --show  
ALL
```

list_version_configuration

Lists the version configuration on the given scope or heterogeneous folder.

SYNTAX

```
beectl list_version_configuration --container <Configuration scope or heterogenous  
folder> --effective <TRUE|FALSE. Default value is FALSE>
```

OPTIONS

--container

Scope or heterogeneous folder on which the version configuration should be listed.

--effective

Whether the effective version configuration should be returned or the one directly defined.

EXAMPLES

```
beectl list_version_configuration --container  
orgn=MyOrganization,enpr=MyEnterprise
```

list_workflow_schemas

Lists workflow schemas.

SYNTAX

```
beectl list_workflow_schemas [ --workflow_schema <Specify the identifier of the  
workflow schema to be listed.> ]
```

OPTIONS

--workflow_schema

Specify the identifier of the workflow schema to be listed.

EXAMPLES

```
beectl list_workflow_schemas --workflow_schema
wfsc=MyWorkflowSchema,enpr=MyEnterprise
```

list_workflow_templates

Lists workflow templates deployed in a container. Details returned include workflow template names and identifiers.

SYNTAX

```
beectl list_workflow_templates --scope <container where the workflow is
configured> [ --template_key <workflow template key> ]
```

OPTIONS**--scope**

Specify the identifier of the container.

--template_key

Specify the template key. To determine the template key, use the list_events command.

EXAMPLES

```
beectl list_workflow_templates --scope enpr=MyEnterprise
--template_key MyTemplateKey
```

list_workflows

List all workflows for which the active user has privileges. Specify user and status options for filtering.

SYNTAX

```
beectl list_workflows [ --status <Specify the status of the workflows to be
listed.> ] [ --creator <Specify the identifier of the creator of the workflows to
be listed. When this option is omitted, workflows created by the active user will
be listed.> ] [ --identifier <Specify the identifier of the workflow to be
listed.> ]
```

OPTIONS**--status**

Specify the status of the workflows to be listed. The valid workflow status options are: WORKFLOWSTATUSINITIATED, WORKFLOWSTATUSCANCELED, WORKFLOWSTATUSCLOSED, WORKFLOWSTATUSCOMPLETED, WORKFLOWSTATUSEXPIRED, WORKFLOWSTATUSFAULTED.

--creator

Specify the identifier of the creator of the workflows to be listed. When this option is omitted, workflows created by the active user will be listed.

--identifier

Specify the identifier of the workflow to be listed.

EXAMPLES

```
beectl list_workflows --status MyWorkflowStatus --creator
loginid=MyUser --identifier
18A4:72D2:wkfl:43EE9FA76C0E4935E040578C95096F4E000000018F
```

list_workspace_templates

Lists all workspace templates

SYNTAX

```
beectl list_workspace_templates --scope <Identifier of enterprise or organization>
[--name <Workspace template name>] [--file <Full path of the output file>]
```

OPTIONS**--scope**

Identifier of enterprise or organization

--name

Workspace template name

--file

Full path of the output file

EXAMPLES

```
beectl list_workspace_templates --scope
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453

beectl list_workspace_templates --scope
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453
--name Test_template --file /tmp/template.xml
```

list_workspaces

Lists workspaces in an organization or enterprise

SYNTAX

```
beectl list_workspaces --scope <Identifier of enterprise or organization> [--type
<p (Personal) | t (Team) | a (All)>] [--name <Workspace name>] [--recurse]
```

OPTIONS**--scope**

Identifier of enterprise or organization

--type

p (Personal) | t (Team) | a (All)

--name

Workspace name

--recurse

Recursively list workspaces in all organizations

EXAMPLES

```
beectl list_workspaces --scope
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453
--type t

beectl list_workspaces --scope
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453
--name My_Workspace
```

modify_access_control_fields

Modifies the AccessControlFields of an existing entity.

This command alters sensitive data in the system. Oracle recommends using this command with caution.

SYNTAX

```
beectl modify_access_control_fields --entity <unique identifier of the entity>
[--owner <unique identifier of the owner Accessor>] [--owner_access_types <owner
access types string>] [--sensitivity <unique identifier of the Sensitivity>]
[--scope <unique identifier of the Scope>]
```

OPTIONS**--entity**

Specify the unique identifier of the entity to be modified.

--owner

Modify the owner of the entity. Specify the unique identifier of the new owner.

--owner_access_types

Modify the access types string for the entity's owner.

--sensitivity

Modify the Sensitivity of the entity. Specify the unique identifier of the new Sensitivity.

--scope

Modify the Scope of the entity. Specify the unique identifier of the new Scope.

EXAMPLES

```
beectl modify_access_control_fields --entity
adoc=MyDocument,wksp=MyWorkspace,enpr=MyEnterprise --owner
loginid=MyUser
```

modify_assigned_role

Modifies an existing AssignedRole entity.

SYNTAX

```
beectl modify_assigned_role --assigned_role <unique identifier of the
AssignedRole> [--name <name of AssignedRole>] [--description <description>]
[--assigned_scope <unique identifier of the assigned Scope>] [--role_definition
<unique identifier of the assigned RoleDefinition>] [--accessor <unique
identifier of an Accessor>...] [--add_accessor <unique identifier of an
Accessor>...] [--remove_accessor <unique identifier of an Accessor>...]
```

OPTIONS

--assigned_role

Specify the unique identifier of the AssignedRole to be modified.

--name

Modify the name of the AssignedRole.

--description

Modify the description of the AssignedRole.

--assigned_scope

Modify the assigned Scope of the AssignedRole. Specify the unique identifier of the new assigned Scope.

--role_definition

Modify the assigned RoleDefinition of the AssignedRole. Specify the unique identifier of the new RoleDefinition.

--accessor

Modify the set of Accessors. Specify the unique identifier of an Accessor. This option can be specified more than once.

--add_accessor

Adds an Accessor. Specify the unique identifier of an Accessor to add. This option can be specified more than once.

--remove_accessor

Removes an Accessor. Specify the unique identifier of an Accessor to remove. This option can be specified more than once.

EXAMPLES

```
beectl modify_assigned_role --assigned_role
acar=MyAssignedRole,wksp=MyWorkspace,enpr=MyEnterprise --name
MyAssignedRole2
```

modify_attendant

Update an existing attendant with a new markup file or rename it.

SYNTAX

```
beectl modify_attendant { --file <aaml file> | --name <attendant name> --new_name
<new name> }
```

OPTIONS**--file**

An auto-attendant markup language file describing the attendant to be added. When specified, name and new_name must be specified.

--name

Name of an existing attendant. Must be specified when 'new_name' is specified. Must not be specified when 'file' is specified

--new_name

The name to which the attendant should be changed. Must be specified when 'name' is specified. Must not be specified when 'file' is specified

EXAMPLES

```
beectl modify_attendant --file /var/attendant.aaml
beectl modify_attendant --name myattendant --new_name
myattendant2
```

modify_audit_policy

Modifies an existing audit policy

SYNTAX

```
beectl modify_audit_policy --policy <Audit policy identifier> [--file <Full path
of the input file>] [--enable <true|false>]
```

OPTIONS**--policy**

Audit policy identifier

--file

Full path of the input file

--enable

true: Enable audit policy

--enable

false: Disable audit policy

EXAMPLES

```
beectl modify_audit_policy --policy aupl=MyAuditPolicy --file
/tmp/policy_ex.xml
```

```
beectl modify_audit_policy --policy aupl=MyAuditPolicy --enable
false
```

modify_audit_trail

Modifies an existing audit trail

SYNTAX

```
beectl modify_audit_trail --trail <Audit trail identifier> --file <Full path of
the input file>
```

OPTIONS

--trail

Audit trail identifier

--file

Full path name of the input XML file

EXAMPLES

```
beectl modify_audit_trail --trail autr=MyAuditTrail --file
/tmp/trail_ex.xml
```

modify_beectl

This command updates the beectl file with the given oracle home & perl home

SYNTAX

```
beectl modify_beectl --new_oracle_home <new oracle home> [--new_perl_home <new
perl home>]
```

OPTIONS

--new_oracle_home

Absolute path of the new oracle home

--new_perl_home

Absolute path of the new perl home

EXAMPLES

```
beectl modify_beectl --new_oracle_home
/app/product/oracle/beehive/
```

modify_bootstrap_configuration

Modify the connect string or credentials for the central configuration repository also known as bootstrap database. Misconfiguration will result in Oracle Beehive Application tier and site being not operable.

This command will modify the local bootstrap configuration file. Additionally, it will update the central configuration repository if the properties connect string, schema name or schema password are changed. This command does not revert the changes to local bootstrap configuration file if it fails to update the central configuration repository.

SYNTAX

```
beectl modify_bootstrap_configuration --connect_string <configuration repository
connect string> --schema_name <configuration repository schema name> --schema_
password <configuration repository schema password>
```

OPTIONS

--connect_string

Configuration repository connect string.

--schema_name

Configuration repository schema name.

--schema_password

Configuration repository schema password.

EXAMPLES

```
beectl modify_bootstrap_configuration --connect_string <connect
string> --schema_name <schema name> --schema_password <schema
password>
```

modify_category

Modifies an existing category

SYNTAX

```
beectl modify_category --category <Category identifier> --file <Full path of the
category XML file>
```

OPTIONS

--category

Category to be updated.

--file

Full path name of the XML file. The file must contain properly formatted data to update the category

EXAMPLES

```
beectl modify_category --category
catg=MyCategory,enpr=MyEnterprise --file /tmp/category.xml
```

modify_category_configuration

Updates a given category configuration.

SYNTAX

```
beectl modify_category_configuration --configuration <Configuration identifier>
--file <Full path of the configuration XML file>
```

OPTIONS

--configuration

Category configuration to be updated.

--file

Full path of the category configuration XML file. The file must contain properly formatted data.

EXAMPLES

```
beectl modify_category_configuration --configuration
9941:2345:ctcf:58D193D162CE4ED89FF66AB4E55745B6345464545453
--file /tmp/configuration.xml
```

modify_change_number

Modifies the change log number of a profile.

SYNTAX

```
beectl modify_change_number --profile <profilename> --changelog_number
<changelognumber>
```

OPTIONS

--profile

Name of the profile.

--changelog_number

Change log number of the profile.

EXAMPLES

```
beectl modify_change_number --profile MyDirectoryProfileName
--changelog_number 100
```

modify_coexistence_connector

Modifies the configuration of a coexistence connector.

SYNTAX

```
beectl modify_coexistence_connector [--select_by_name <connectorid>] [--url <old_
name>] [--use_secure_connection <url>] [--host_name <use_secure_connection>]
[--port <host_name>] [--name <port_number>] [--sitekey <new_name>] [--timezone_
```



```
alias_namespace [<obfuscated_sitekey> --obfuscated]] [--{11} <timezone_alias_namespace>]
```

OPTIONS

--select_by_name

Specify the name of the coexistence connector to be modified.

--name

Specify a new name for the coexistence connector.

--url

Specify the URL of the coexistence connector.

--use_secure_connection

Specify whether "HTTPS" MUST be used.

--host_name

Specify the host name of the connector.

--port

Specify the port number used by the connector. Value MUST be an integer.

--sitekey

Specify the site key of the coexistence connector.

--timezone_alias_namespace

Specify the time zone alias namespace used by the connector.

EXAMPLES

```
beectl modify_coexistence_connector --select_by_name MsExch2001
--url http://www.example.com:7777 --name MsExch2003_1
```

modify_coexistence_profile

Specifies the coexistence profile of a user.

SYNTAX

```
beectl modify_coexistence_profile {--user <user_cen> | --select_by_name <user_name> | --select_by_address <user_address> --select_by_authuser <user_loginid> | --file <input.xml> --errors_file <errors.xml> | --select_users_without_profile --errors_file <errors.xml>} --accessible_system <system_name> ...
```

OPTIONS

--user

Specify the identifier of the user.

--select_by_name

Specify the name of the user.

--select_by_address

Specify the email address of the user.

--select_by_authuser

Specify the login ID of the user.

--select_users_without_profile

Specify all beehive users without coexistence profile.

--file

Specify the xml input file. File encoding MUST be UTF-8. Only supported for creation.

--errors_file

Specify the output file. This file will only be generated if errors occurs.

--accessible_system

Specify the collaboration system which can be accessed by the user. Supported collaboration systems are BEEHIVE and EXCHANGE.

EXAMPLES

```
beectl modify_coexistence_profile --select_by_authuser user_
login_id --accessible_system BEEHIVE
```

```
beectl modify_coexistence_profile --select_by_address
user@example.com --accessible_system EXCHANGE
```

```
beectl modify_coexistence_profile --accessible_system BEEHIVE
--accessible_system EXCHANGE --file users.xml --errors_file
errors.xml
```

```
beectl modify_coexistence_profile --accessible_system EXCHANGE
--select_users_without_profile --errors_file errors.xml
```

modify_connection_pool

Modifies the connection pool configuration.

SYNTAX

```
beectl modify_connection_pool [--connection_pool <connection pool system model
identifier or alias>] [--max_connections <maximum connections>] [--min_connections
<minimum connections>] [--max_statement_limit <maximum cached statements>]
[--initial_connections <initial connections>] [--connection_wait_timeout
<connection wait timeout>] [--inactivity_timeout <inactivity timeout>] [--time_to_
live_timeout <time to live timeout>] [--abandoned_connection_timeout <abandon
connection timeout>] [--lower_threshold_limit <lower threshold limit>]
[--property_check_interval <property check interval>] [--validate_connection
<true/false>]
```

OPTIONS

--connection_pool

Connection pool system object identifier.

--max_connections

Maximum number of connections in connection pool.

--min_connections

Number of minimum connections in connection pool.

--max_statement_limit

Maximum number of cached statements in connection pool.

--initial_connections

Number of initial connections in connection pool.

--connection_wait_timeout

Connection wait timeout.

--inactivity_timeout

Inactivity timeout.

--time_to_live_timeout

Time to live timeout.

--abandoned_connection_timeout

Abandoned connection timeout.

--lower_threshold_limit

Lower threshold limit.

--property_check_interval

Property check interval.

--validate_connection

Should connection be validated or not.

EXAMPLES

```
beectl modify_connection_pool --connection_pool
232323-der344-455-3455ded --max_connections 40
```

modify_database

Modifies given database configuration.

SYNTAX

```
beectl modify_database --database <database instance id or alias> [--schema_name
<schema name>] [--connect_string <connect string>] [--schema_password <schema
password>] [--xa_service_names <xa schema name>] [--xa_service_names < xa schema
```

```
name>] .. ] [--ons_entry <ons name host:port> [--ons_entry < ons entry host:port>]
.. ]
```

OPTIONS

--database

Database system object identifier.

--schema_name

Schema name.

--connect_string

Connection descriptor.

--schema_password

Schema password.

--xa_service_names

Multiple values of xa service names can be given. See the usage.

--ons_entry

Notification server details in form of host:port.

EXAMPLES

```
beectl modify_database --database ab222-aa4-eee333-ddede5
--schema_name schema1
```

modify_directory_profile

The modify_directory_profile command modifies an existing directory profile. Modification to the profile name cannot be done.

SYNTAX

```
beectl modify_directory_profile --file <filename> [ --no_validate ]
```

OPTIONS

--file

XML file containing directory profile.

--no_validate

Skips the validation of profile.

EXAMPLES

```
beectl modify_directory_profile --file MyDirectoryProfile.xml
beectl modify_directory_profile --file MyDirectoryProfile.xml
--no_validate
```

modify_email_port

Modifies Email service' SMTP or IMAP port number

SYNTAX

```
beectl modify_email_port --type <smtp|imap> --port <port_number>
```

OPTIONS

--type

imap: IMAP port number

--type

smtp: SMTP port number

EXAMPLES

```
beectl modify_email_port --type smtp --port 1234
```

modify_email_queue

Enables or disables Email asynchronous queue processing

SYNTAX

```
beectl modify_email_queue --type <enable|disable|process|status>
```

OPTIONS

--type

enable: Resume or enable queue processing

--type

disable: Disable queue processing

--type

process: Process all the messages in the Email asynchronous queue immediately

--type

status: Show current status

EXAMPLES

```
beectl modify_email_queue --type enable
```

```
beectl modify_email_queue --type process
```

modify_enterprise

Modifies an existing enterprise

SYNTAX

```
beectl modify_enterprise --enterprise <Enterprise identifier> [--name <Enterprise name>] [--description <Description>] [--hard_quota <Hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota>] [--sub_organization_quota <Default sub-organization quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota>] [--team_workspace_hard_quota <Default team workspace hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota>] [--team_workspace_soft_quota <Default team workspace soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota>] [--personal_workspace_hard_quota <Default personal workspace hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota>] [--personal_workspace_soft_quota <Default personal workspace soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota>] [--personal_template <Personal workspace default template identifier>] [--team_template <Team workspace default template identifier>]
```

OPTIONS

--enterprise

Enterprise identifier

--name

Enterprise name

--description

Description

--hard_quota

Hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--sub_organization_quota

Default sub-organization quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--team_workspace_hard_quota

Default team workspace hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--team_workspace_soft_quota

Default team workspace soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--personal_workspace_hard_quota

Default personal workspace hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--personal_workspace_soft_quota

Default personal workspace soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--personal_template

Personal workspace default template identifier

--team_template

Team workspace default template identifier

EXAMPLES

```
beectl modify_enterprise --enterprise
9941:2345:enpr:58D193D162CE4ED89FF66AB4E55745B6345464545453
--name New_Name --description New_description

beectl modify_enterprise --enterprise
9941:2345:enpr:58D193D162CE4ED89FF66AB4E55745B6345464545453
--hard_quota 10000 --sub_organization_quota 1500 --team_
workspace_hard_quota 1000 --team_workspace_soft_quota 1000
--personal_workspace_hard_quota 1000 --personal_workspace_soft_
quota 1000 --team_template
09F3:7265:ttws:3A599FA8F12533AEE0404498826342040000000001DC
--personal_template
09F3:7265:tpws:3A599FA8F12533AEE0404498826342040000000001DB
```

modify_external_contact

The modify_external_contact command modifies existing external contact.

SYNTAX

```
beectl modify_external_contact {      --contact <identifier of external contact
>      |      --email <Email address of the contact> }      [ --family_name
<+/-[locale:]family name> ... ]      [ --given_name <+/-[locale:]given name> ... ]
[ --display_name <+/-[locale:]display name> ... ]      [ --middle_name
<+/-[locale:]middle name> ... ]      [ --job_title <+/-[locale:]job title> ... ]
[ --prefix <+/-[locale:]prefix> ... ]      [ --suffix <+/-[locale:]suffix> ... ]
[ --nick_name <+/-[locale:]nick name> ... ]      [ --scope <identifier of contacts
parent> ]      [ --office_location <office location of the contact> ]      [ --company
<company of the contact> ]      [ --profession <profession of the contact> ]      [
--timezone <time zone of the contact> ]      [ --locale <locale of the contact> ]
[ --department <department of the contact> ]      [ --organization <organization
identifier> ... ]      [ --remove_organization <organization identifier> ... ]      [
--property <+/-name(assistant|profession|certificate|notes)=value=description> ...
]      [ --address <+/-type of address(business_1|other_5|personal_4|proxy_
1|...):scheme(im|mailto|...):value> ... ]      [ --default_address_for_type <type of
address(business_1|other_5|personal_4|proxy_1|...):scheme(im|mailto|...):value> ]
[ --default_address_for_scheme <type of address(business_1|other_5|personal_
4|proxy_1|...):scheme(im|mailto|...):value> ]      [ --primary_address <type of
address(business_1|other_5|personal_4|proxy_1|...):scheme(im|mailto|...):value> ]
[ --status <status of contact(enabled|disabled)> ]
```

OPTIONS**--contact**

The identifier of the external contact

--email

Email id of the external contact

--family_name

Family name of the contact in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--given_name

Given name of the contact in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--display_name

Display name of the contact in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--middle_name

Middle name of the contact in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--job_title

Job title of the contact in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--prefix

Prefix of the contact in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--suffix

Suffix of the contact in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--nick_name

Nick name of the contact in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--scope

Identifier of the enterprise under which this contact will be created.

--office_location

Office location of the contact.

--company

Company of the contact.

--profession

Profession of the contact.

--timezone

Time zone of the contact. list_timezones lists the valid time zones

--locale

Locale details of the contact. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--department

Department of the contact.

--organization

Identifiers of the organizations the contact must be part of.

--remove_organization

Identifiers of the organizations the contact must be removed from.

--property

Details of the property in the format [+/-]name=value=description. Supported names are certificate, assistant, profession and notes. Note, no equals to symbol(=) should be present in the name or value or description. + or no symbol means the property should be added. If - is specified that means the property should be removed. Default action is addition.

--address

Address of the contact in the format [+/-]type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytttd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25. + or - in the start of the string tells whether the address should be added or removed. + or no symbol means the address should be added. If - is specified that means the address should be removed. Default action is addition.

--default_address_for_type

Address of the contact in the format type:scheme:value. Sets the specified address as the default for the specified type. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--default_address_for_scheme

Address of the contact in the format type:scheme:value. Sets the specified address as the default for the specified scheme. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--primary_address

Primary address of the contact in the format type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--status

Sets the provisioning status of the external contact. Supported values are ENABLED, DISABLED.

EXAMPLES

```
beectl modify_external_contact --user
6A95:21EB:extp:D9E9FC8134544BCE9D60559F9B997CCD000000000000
--given_name User1GivenName --family_name -en_CA:User1FamilyName
--office_location 4A037
```

```
beectl modify_external_contact --email contact1@example.com
--property +prop1:prop1value
```

```
beectl modify_external_contact --email contact1@example.com
--address +BUSINESS_1:mailto:contact1@example.com --address
-BUSINESS_2:im:contact2@example.com
```

```
beectl modify_external_contact --email contact1@example.com
--status disabled
```

modify_group

The `modify_group` command modifies a group. The group information is supplied in an XML file.

SYNTAX

```
beectl modify_group --file <filename> [ --ldapbootstrap ]
```

OPTIONS

--file

Filename of the XML file containing group definition.

--ldapbootstrap

LDAP bootstrap flag. If this flag is specified, then uds groups will be created with directory locator and directory id. This is relevant only when `--file` option is used.

EXAMPLES

```
beectl modify_group --file MyGroups.xml
```

```
beectl modify_group --file MyGroups.xml --ldapbootstrap
```

modify_hostname

Modifies the configuration repository for hostname of the system and updates required configuration files.

SYNTAX

```
beectl modify_hostname [--no_start_at_end] [(--sync | --new_host_name <new host name> [--no_dns_validation]) [--old_host_name <old host name>]... ]
```

OPTIONS

--sync

If specified, command will read values from configuration repository and sync it to the system configuration files.

--new_host_name

New host name of the local server.

--old_host_name

Old host names of the local server. This value will be used to replace any of the old host name pattern available in local files.

--new_host_ip

New IP address of the local server.

--old_host_ip

Old IP address of the local server.

--no_start_at_end

It assures that no component will be started after modification to configuration files.

--no_dns_validation

If specified, DNS lookup validation of the new host name will not be performed.

EXAMPLES

```
beectl modify_hostname
```

Above command will read the values from file system and updates configuration files and configuration repository with it.

```
beectl modify_hostname --sync --old_host_name  
oldhost1.example.com --old_host_name oldhost2.example.com
```

Above command will read the values from configuration repository and update it to all configuration files. There will be no configuration repository updates when this option is used.

```
beectl modify_hostname --new_host_name demo.example.com
```

Above example will update configuration repository as well as all other configuration files with new hostname.

modify_ip_phone_password_seed

Resets the seed of the password generator for IP phones. To send commands to an IP phone the requestor must be authenticated. The password is generated based on information in the phone but must be seeded to ensure security.

SYNTAX

```
beectl modify_ip_phone_password_seed --enterprise <Enterprise identifier>  
[--algorithm <algorithm>] [--seed_length <seed length>]
```

OPTIONS**--enterprise**

Identifier of the enterprise for which we are resetting the password seed.

--algorithm

Name of the algorithm used to generate password, this value will be stored on the server. If not given, the value will be taken from the enterprise. An error will result if not given and not found on the enterprise. Must be a standard name allowed with instances of KeyGenerator according to appendix A of Java Cryptography Extension Reference Guide.

--seed_length

The length in bits of the seed to be generated. This value will be stored in the server. If not given, the value will be taken from the enterprise. An error will result if not given and not found on the enterprise.

EXAMPLES

```
beectl modify_ip_phone_password_seed --enterprise
<740F:6AC7:enpr:3540AA5334A61A3AE040578C60160AFD000000030D45>
[--algorithm <DES>] [--seed_length <256>]
```

modify_local_ace

Replaces an Access Control Entry (ACE) in the Local Access Control List (LACL) of an entity.

SYNTAX

```
beectl modify_local_ace --entity <unique identifier of the entity> --accessor
<unique identifier of the Accessor> [--access_types <access types string>]
```

OPTIONS**--entity**

Specify the unique identifier of the entity in which the ACE will be replaced.

--accessor

Specify the unique identifier of the Accessor to whom the access types will be applied.

--access_types

Specify the access types string for the Accessor.

EXAMPLES

```
beectl modify_local_ace --entity
adoc=MyDocument,wksp=MyWorkspace,enpr=MyEnterprise --accessor
loginid=MyUser --access_types +RW-D
```

modify_local_configuration_files

This command updates configuration files local to current Oracle Beehive Application tier with activated changes to centralized configuration. It can restart one or more components on current Oracle Beehive Application tier if needed to make the changes take effect. Some updates to local configuration files require this command to restart all Oracle Beehive Application tier components.

SYNTAX

```
beectl modify_local_configuration_files [--restart_needed]
```

OPTIONS

--restart_needed

Indicates if components should be restarted or not. If this option is specified with value false then no component will be stopped/restarted even though changes to local configuration files require a restart of one or more components for taking effect. If this option is specified with value true, and if the changes to local configuration files require a restart of one or more already running components then they will be restarted. The components which were NOT running will NOT be restarted.

EXAMPLES

```
beectl modify_local_configuration_files
```

Above command will update local configuration files with changes if any and restart one or more Oracle Beehive Application tier components if needed.

```
beectl modify_local_configuration_files --restart_needed false
```

Above command will not restart any component but it will display warnings about components which need to be restarted due to changes to local configuration files.

modify_max_address_count

The `modify_max_address_count` command modifies maximum number of addresses of an address type that can be set for a given person-contact, group-contact or resource-contact in an address-book. The address types determine the type of address like BUSINESS, PERSONAL & OTHER. The maximum count specified in this command must be less than the system defined maximum limit, which can be determined by running `list_max_address_count` command.

SYNTAX

```
beectl modify_max_address_count --max_address_count <integer value>
```

OPTIONS

--max_address_count

Maximum number of addresses of an address-type.

EXAMPLES

```
beectl modify_max_address_count --max_address_count 5
```

modify_notification_template

Modifies a specified notification template for the Notification service.

SYNTAX

```
beectl modify_notification_template --file <path to the xml instruction file>
```

OPTIONS

--file

Specify the full path and file name of the notification XML file.

EXAMPLES

```
beectl modify_notification_template --file
/tmp/nms/UpdateNewInvitationSchema.xml
```

modify_organization

Modifies an existing organization

SYNTAX

```
beectl modify_organization --organization <Organization identifier> [--name
<Organization name>] [--description <Description>] [--hard_quota <Hard quota in
megabytes (MB). Use 'UNLIMITED' for unlimited quota>] [--sub_organization_quota
<Default sub-organization quota in megabytes (MB). Use 'UNLIMITED' for unlimited
quota>] [--team_workspace_hard_quota <Default team workspace hard quota in
megabytes (MB). Use 'UNLIMITED' for unlimited quota>] --team_workspace_soft_quota
<Default team workspace soft quota in megabytes (MB). Use 'UNLIMITED' for
unlimited quota>] [--personal_workspace_hard_quota <Default personal workspace
hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota>] --personal_
workspace_soft_quota <Default personal workspace soft quota in megabytes (MB). Use
'UNLIMITED' for unlimited quota>] [--personal_template <Personal workspace default
template identifier>] [--team_template <Team workspace default template
identifier>]
```

OPTIONS

--organization

Organization identifier

--name

Organization name

--description

Description

--hard_quota

Hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--sub_organization_quota

Default sub-organization quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--team_workspace_hard_quota

Default team workspace hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--team_workspace_soft_quota

Default team workspace soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--personal_workspace_hard_quota

Default personal workspace hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--personal_workspace_soft_quota

Default personal workspace soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--personal_template

Personal workspace default template identifier

--team_template

Team workspace default template identifier

EXAMPLES

```
beectl modify_organization --organization
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453
--name New_Name --description New_description

beectl modify_organization --organization
9941:2345:orgn:58D193D162CE4ED89FF66AB4E55745B6345464545453
--hard_quota 10000 --sub_organization_quota 1500 --team_
workspace_hard_quota 1000 --team_workspace_soft_quota 1000
--personal_workspace_hard_quota 1000 --personal_workspace_soft_
quota 1000 --personal_template
09F3:7265:tpws:3A599FA8F12533AEE0404498826342040000000001DB
--team_template
09F3:7265:ttws:3A599FA8F12533AEE0404498826342040000000001DC
```

modify_personal_workspace

Modifies an existing personal workspace

SYNTAX

```
beectl modify_personal_workspace --workspace <Workspace identifier> [--name
<Workspace name>] [--description <Description>] [--hard_quota <Hard quota in
megabytes (MB). Use 'UNLIMITED' for unlimited quota> --soft_quota <Soft quota in
megabytes (MB). Use 'UNLIMITED' for unlimited quota>]
```

OPTIONS**--workspace**

Workspace identifier

--name

Workspace name

--description

Description

--hard_quota

Hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--soft_quota

Soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

EXAMPLES

```
beectl modify_personal_workspace --workspace
9941:2345:wspr:58D193D162CE4ED89FF66AB4E55745B6345464545453
--name New_Name --description New_description

beectl modify_personal_workspace --workspace
9941:2345:wspr:58D193D162CE4ED89FF66AB4E55745B6345464545453 --hard_quota 1000 --soft_quota 1000
```

modify_policy

Modifies an existing policy using data in an XML file.

SYNTAX

```
beectl modify_policy --file <full path to the policy xml file>
```

OPTIONS**--file**

Specify the absolute path of the XML file that contains the policy data.

EXAMPLES

```
beectl modify_policy --file /private/xml/MyPolicy.xml
```

modify_policy_schema

Modifies an existing policy schema using data in an XML file.

SYNTAX

```
beectl modify_policy_schema --file <full path to the xml file>
```

OPTIONS**--file**

Specify the absolute path of the XML file that contains the policy schema data.

EXAMPLES

```
beectl modify_policy_schema --file
/private/xml/MyPolicySchema.xml
```

modify_policy_template

Modifies an existing policy template using data in an XML file.

SYNTAX

```
beectl modify_policy_template --file <full path to the xml file>
```

OPTIONS

--file

Specify the absolute path of the XML file that contains the policy template data.

EXAMPLES

```
beectl modify_policy_template --file  
/private/xml/MyPolicyTemplate.xml
```

modify_port

Modifies various ports.

Valid protocols are

SMTP

IMAP

XMPP

XMPPS

FTP

HTTP

HTTPS

BTP

BTPS

OC4J-AJP-RANGE

OC4J-RMI-RANGE

OC4J-RMIS-RANGE

OC4J-JMS-RANGE

OC4J-AJP-RANGE identifies the range of ports in current site for either AJP or secure AJP protocol whichever is enabled.

SYNTAX

```
beectl modify_port [--protocol <protocol name> [[[--virtual_port <virtual port for  
the site>][--listen_port <listen port for protocol>] |[--port <common port  
value>]]] [--maximum_port <maximum value in the range> --minimum_port <minimum  
value in the range>]] |[--component <system object identifier or alias> --name  
<name of the port property> --port <value of the port> ]
```

OPTIONS

--protocol

Name of the protocol for which port needs to be modified.

--virtual_port

Port to which the clients will connect. This value will be modified for the entire site.

--listen_port

The actual port which will be opened on each Oracle Beehive Application tier. Typically a listening port.

--port

Convenience option to set both --virtual_port and --listen_port together with same value.

--component

Identifier of the configuration component to be modified. Combined with --name, this option can be used to modify internal ports. For example control port of the BTI or request port of OPMN.

--name

Name of the internal port property on the configuration object identified by --component option.

--maximum_port

Some components allocate free port dynamically during process start. For such processes, only the permitted port range is managed. This option can be used to modify the maximum value of the range for the given protocol.

--minimum_port

Some components allocate free port dynamically during process start. For such processes, only the permitted port range is managed. This option can be used to modify the maximum value of the range for the given protocol.

EXAMPLES

```
beectl modify_port --protocol HTTP --virtual_port 80 --listen_port 7774
```

Above example modifies virtual and listen port values for HTTP protocol for all Oracle Beehive Application tiers.

```
beectl modify_port --protocol HTTP --port 80
```

Above example modifies virtual and listen port values to same given port value for HTTP protocol for all Oracle Beehive Application tiers.

```
beectl modify_port --protocol HTTPS --port 7445 --component c093d4cc-d9cc-42ae-bc45-4b31fab07190
```

Above example modifies listen port value for HTTPS protocol for given HttpServer configuration component. This can also be achieved using the `beectl modify_property` command.

```
beectl modify_port --component  
c093d4cc-d9cc-42ae-bc45-4b31fab07190 --name RequestPort --port  
2003
```

Above example modifies port value identified by name RequestPort for given configuration component specified by option `--component`. This can also be achieved using the `beectl modify_property` command.

```
beectl modify_port --protocol OC4J-AJP-RANGE --maximum_port  
20601 --minimum_port 20700
```

Above example modifies port range values for given protocol for all OC4Js in all Oracle Beehive Application tiers. Use option `--component` to specify the identifier of the OC4J to be modified.

modify_preference_set

The `modify_preference_set` command modifies the preference set by setting the extends from attribute.

SYNTAX

```
beectl modify_preference_set --set <Preference set identifier> --extends  
<Preference set identifier>
```

OPTIONS

--set

Identifier of the preference set specified in id format, which can be determined by running `list_preference_sets` command with `"--entity_format id"` option.

--extends

Identifier of the preference set from which the new preference set is extended.

EXAMPLES

```
beectl modify_preference_set --set  
5965:3658:prfs:B7CAC0E31E554593B7A93B24B0FD09F2000000000979  
--extends  
5965:3658:prfs:B7CAC0E31E554593B7A93B24B0FD09F2000000000978
```

modify_property

Modifies the value(s) of a named property of the component identified by `--component`. Multiple values can be set for one property.

Note: Option value should not start with hyphen(-). If an option value starts with hyphen, use any one of the following syntaxes. 1. Use `<option-name>=<option value>`

format. This is the preferred way to specify the option values starting with hyphens. 2. Prefix the option value with string "ESCAPE:". 3. Prefix the option value with backslash "\". This is the least preferred way. This may not work in some platforms, esp in windows platforms it will not work.

SYNTAX

```
beectl modify_property --component <system object identifier or alias> --name
<name> [ --file <filename> | --revert_to_default | --value <value>... ]
```

OPTIONS

--component

component id.

--name

Name of the property.

--value

Value of the property.

--file

The contents of this file would be assigned as the value of the specified property. The property MUST be of type String.

--revert_to_default

flag indicating, if values need to be reverted back as original.

EXAMPLES

The command execution shown below would set the BaseLogLevel property of the config object to FINE.

```
beectl modify_property --component
486318ac-f162-477b-814f-140836c257af --name BaseLogLevel --value
FINE
```

The command execution shown below would revert back the BaseLogLevel property of the config object to the initial default value, if any. If there is no initial default value configured for this property on this config object then the value would be cleared.

```
beectl modify_property --component
486318ac-f162-477b-814f-140836c257af --name BaseLogLevel
--revert_to_default
```

The command execution shown below would set the contents of the specified file as the value of the PostResolutionRules property of the config object. The property PostResolutionRules must be of type String.

```
beectl modify_property --component
520118ac-f162-477b-814f-452106c257cb --name PostResolutionRules
--file /tmp/post_resolution_rules.xml
```

The command execution shown below would set the values starting '-' to the StartParameter property of the config object. The property StartParameter must be of type String.

```
beectl modify_property --component
520118ac-f162-477b-814f-452106c257cb --name StartParameter
--value="-Dhttp.maxFileInfoCacheEntries=-1 -ms128M -mx512M"
```

modify_resource_classifications

This command set the given category as resource root classification.

SYNTAX

```
beectl modify_resource_classifications [--enterprise <enterpriseid>] --category
<categoryid>
```

OPTIONS

--enterprise

Specify the identifier of the enterprise under which the resource will be created.

--category

Category identifier to set as root classification.

EXAMPLES

```
beectl modify_resource_classifications --category
395A:346B:catg:2C5F7E98E076D382E040578CA60B0D0E000000062022
```

modify_resources

Modifies an existing resource.

SYNTAX

```
beectl modify_resources <--resource resourceid | --select_by_name name > [--name
<name>] [--email_address <email address>] [--phone_number <phone_number>]
[--website <website>] [--postal_address <postal address>] [--identifier
<identifier>] [--booking_info <booking info>] [--description <description>]
[--timezone <timezoneid>] [--location <location>] [--capacity <capacity>]
[--add_approver <approverid>] [--delete_approver <approverid>] [--booking_
characteristics <[O]pen|<[F]CFS>] beectl modify_resources <--resource resourceid
| --select_by_name name > --external [--name <name>] [--email_address
<email address>] [--phone_number <phone_number>] [--website <website>] [--postal_
address <postal address>] [--capacity <capacity>] [--timezone <time zone
name>] [--location <location>] [--booking_info <booking info>]
[--description <description>]
```

OPTIONS

--resource

Resource ID.

--select_by_name

modify a resource by name

--name

Modify the name of the resource.

--email_address

Modify the e-mail address of the resource.

--phone_number

Modify the phone number of the resource.

--website

Modify the web site of the resource.

--postal_address

Specify the BUSINESS_1 postal address of the resource.

--timezone

Modify the time zone of the resource.

--location

Specify the location description of the resource. It must be a XHTML string.

--identifier

Modify the identifier of the resource.

--capacity

Modify the capacity of the resource.

--external

Specify this option when the resource is external. If this option is not specified, the command modifies bookable resources.

--add_approver

Resource approver to add.

--delete_approver

Resource approver to delete.

--booking_characteristics

Specify resource default calendar booking characteristics. The characteristics can be Open or First Come First Serve.

--booking_info

Specify resource booking information. It must be a XHTML string.

--description

Specify the description of the resource. It must be a XHTML string.

EXAMPLES

```
beectl modify_resources --resource
395A:346B:bkrs:2C5F7E98E076D382E040578CA60B0D0E000000062327
--name "Resource2" --capacity 3
```

modify_role_definition

Modifies an existing RoleDefinition entity.

SYNTAX

```
beectl modify_role_definition --role_definition <unique identifier of the
RoleDefinition> [--name <name of RoleDefinition>] [--description <description>]
[[--privilege <privilege name>]...] [--add_privilege <privilege name>]...]
[[--remove_privilege <privilege name>]...] [--access_types <access types string>]
[--always_enabled <boolean value>]
```

OPTIONS**--role_definition**

Specify the unique identifier of the RoleDefinition to be modified.

--name

Modify the name of the RoleDefinition.

--description

Modify the description of the RoleDefinition.

--privilege

Modify the privileges of the RoleDefinition. To determine a list of valid privilege arguments, use the list_privileges command. This option can be specified more than once.

--add_privilege

Add privileges to the RoleDefinition. To determine a list of valid privilege arguments, use the list_privileges command. This option can be specified more than once.

--remove_privilege

Remove privileges from the RoleDefinition. To determine a list of valid privilege arguments, use the list_privileges command. This option can be specified more than once.

--access_types

Modify the access types for the RoleDefinition.

--always_enabled

Modify the AlwaysEnabled option of the RoleDefinition. Specify the TRUE argument to enable, and FALSE to disable.

EXAMPLES

```
beectl modify_role_definition --role_definition
acrd=MyRoleDefinition,wksp=MyWorkspace,enpr=MyEnterprise --name
MyRoleDefinition2
```

modify_search

Create system model objects for Search and configure them

SYNTAX

```
beectl modify_search [--option1 <option1argument> ... ]
```

OPTIONS**--sync_frequency**

Sync frequency of the search crawler (in seconds)

--max_results

Maximum number of results to return

--cached_page_max_length

Maximum length of cached pages

--wildcard_char

The desired wildcard character

--exclude_regex

True to exclude regular expressions, false otherwise

--maximum_search_duration

Maximum time to allow a search to run before returning (in seconds)

--case_sensitive

True for case sensitivity, false otherwise

--two_db_mode

True if operating in two db mode, false otherwise

--recovery

True if operating in recovery mode, false otherwise

EXAMPLES

```
beectl modify_search --sync_frequency 100 --max_results 1000
--cached_page_max_length 1000 --wildcard_char \* --exclude_regex
```

```
false --maximum_search_duration 30 --case_sensitive false --two_
db_mode false --recovery false
```

modify_search_engine

Starts or stops the search crawl process for a specific source type

SYNTAX

```
beectl modify_search_engine --crawl <start|stop> --source <type>
```

OPTIONS

--crawl

Starts or stops the search crawl process

--source

Source type to start or stop crawling (E.g. EMAILS, DOCUMENTS, CALENDARS and ALL)

EXAMPLES

```
beectl modify_search_engine --crawl start --source all
```

modify_secure_property

This command updates the sensitive property of the system model object identified by the --component.

Note: Option value should not start with hyphen(-). If an option value starts with hyphen, use any one of the following syntaxes. 1. Use <option-name>=<option value> format. This is the preferred way to specify the option values starting with hyphens. 2. Prefix the option value with string "ESCAPE:". 3. Prefix the option value with backslash "\\\\". This is the least preferred way. This may not work in some platforms, esp in windows platforms it will not work.

SYNTAX

```
beectl modify_secure_property --component <system object identifier or alias>
--name <name> --value <obfuscated value> --obfuscated
```

OPTIONS

--component

component id.

--name

Name of the property.

--value

Value of the property.

EXAMPLES

```
beectl modify_secure_property --component
d4261c24-e917-4e37-9777-41799ef9abe8 --obfuscated --name
AdminPassword --value
```

modify_sensitivity

Modifies an existing Sensitivity entity.

SYNTAX

```
beectl modify_sensitivity --sensitivity <unique identifier of the Sensitivity>
[--name <name of Sensitivity>] [--description <description>] [--sensitivity_only
<boolean value>] [--delegatable <boolean value>]
```

OPTIONS**--sensitivity**

Specify the unique identifier of the Sensitivity to be modified.

--name

Modify the name of the Sensitivity.

--description

Modify the description of the Sensitivity.

--sensitivity_only

Modify the SensitivityOnly option for the Sensitivity. Specify the TRUE argument to enable, and FALSE to disable.

--delegatable

Modify the Delegatable option for the Sensitivity. Specify the TRUE argument to enable, and FALSE to disable.

EXAMPLES

```
beectl modify_sensitivity --sensitivity
acsn=MySensitivity,wksp=MyWorkspace,enpr=MyEnterprise --name
MySensitivity2
```

modify_sensitivity_ace

Replaces an Access Control Entry (ACE) in the Sensitivity Access Control List (SACL) of a Sensitivity entity.

SYNTAX

```
beectl modify_sensitivity_ace --sensitivity <unique identifier of the entity>
--accessor <unique identifier of the Accessor> [--access_types <access types
string>]
```

OPTIONS

--sensitivity

Specify the unique identifier of the Sensitivity in which the ACE will be replaced.

--accessor

Specify the unique identifier of the accessor to whom the access types were applied.

--access_types

Specify the access types string for the Accessor.

EXAMPLES

```
beectl modify_sensitivity_ace --sensitivity
acsn=MySensitivity,wksp=MyWorkspace,enpr=MyEnterprise --accessor
loginid=MyUser --access_types +RW-D
```

modify_team_workspace

Modifies an existing team workspace

SYNTAX

```
beectl modify_team_workspace --workspace <Workspace identifier> [--name <Workspace
name>] [--description <Description>] [--add_participant <User or group identifier>
[--role <Role definition name>]] [--remove_participant <User or group identifier>]
[--email_address <Team workspace email address>] [--participation_mode <Team
workspace participation mode. Value can be INVITE_ONLY, OPEN, or APPROVE_
REQUIRED>] [--directory_listed <TRUE|FALSE. Default value is FALSE>] [--hard_quota
<Hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota> --soft_quota
<Soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota>]
```

OPTIONS

--workspace

Workspace identifier

--add_participant

Add a user or group to the team workspace

--role

Workspace role of the user. Example: workspace-member, workspace-coordinator, workspace-viewer etc

--remove_participant

Remove a user or group from the team workspace

--email_address

Team workspace email address

--participation_mode

Team workspace participation mode. Value can be INVITE_ONLY, OPEN, or APPROVE_REQUIRED

--directory_listed

TRUE | FALSE. Default value is FALSE

--name

Workspace name

--description

Description

--hard_quota

Hard quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

--soft_quota

Soft quota in megabytes (MB). Use 'UNLIMITED' for unlimited quota

EXAMPLES

```
beectl modify_team_workspace --workspace
9941:2345:wspr:58D193D162CE4ED89FF66AB4E55745B6345464545453
--name New_Name --description New_description

beectl modify_team_workspace --workspace
9941:2345:wspr:58D193D162CE4ED89FF66AB4E55745B6345464545453 --hard
d_quota 1000 --soft_quota 1000

beectl modify_team_workspace --workspace
9941:2345:wspr:58D193D162CE4ED89FF66AB4E55745B6345464545453
--add_participant
9941:2345:user:58D193D162CE4ED89FF66AB4E55745B6345461245453
--role workspace-viewer --email_address
teamworkspace@company.com --participation_mode OPEN --directory_
listed TRUE
```

modify_timezones

Modify a time zone.

SYNTAX

```
beectl modify_timezones <--select_by_name TimeZoneName | --timezone
TimeZoneCollabId > [--common] | <--reset_to_default>
```

OPTIONS**--timezone**

Time zone ID. This option is optional and can be entered only once.

--select_by_name

Select time zone by name. This option is optional and can be entered only once.

--common

Set the specified time zone as common. This option is optional and can be entered only once.

--reset_to_default

Reset time zones to factory default. This option is optional and can be entered only once.

EXAMPLES

```
beectl modify_timezones --select_by_name America/New_York
```

```
beectl modify_timezones --reset_to_default
```

modify_trusted_identity

This commands modifies the details of the trusted identity. At least one of the options `new_service_name` or `new_key_alias` need to be specified for this modification if the type is WSSEC. If the type of identity is not specified, it is defaulted to WSSEC.

SYNTAX

```
beectl modify_trusted_identity [--type WSSEC --service_name <service name> [--new_service_name <new service name>] [--new_key_alias <new key alias>]] [--type SES --name <Trusted Entity Name> --new_name <New Trusted Entity Name> --new_password <New Trusted Entity Password>]
```

OPTIONS**--service_name**

String value of the service principal name with which it will be identified in Beehive. This option is mandatory if type is WSSEC.

--new_service_name

String value of the new service principal name with which it will be identified in Beehive. This option is mandatory if type is WSSEC.

--new_key_alias

The new alias of the service which is used to register the certificate in the wallet. This option is mandatory if type is WSSEC.

--type

String value indicating the type of trusted identity: SES or WSSEC. SES refers to Secure Enterprise Search. WSSEC refers to Web services security.

--name

String value representing the name of the SES trusted entity.

--new_name

String value representing the new name of the SES trusted entity.

--new_password

String value representing the new password of the SES trusted entity.

EXAMPLES

modify_user

The modify_user command modifies existing users.

SYNTAX

```
beectl modify_user {      --user <User Identifier>      |      --email <Email
address of the user> } [ --family_name <+/-[locale:]family name> ] [
--given_name <+/-[locale:]given name> ... ] [ --display_name
<+/-[locale:]display name> ... ] [ --middle_name <+/-[locale:]middle name> ...
] [ --job_title <+/-[locale:]job title> ... ] [ --prefix
<+/-[locale:]prefix> ... ] [ --suffix <+/-[locale:]suffix> ... ] [ --nick_
name <+/-[locale:]nick name> ... ] [ --scope <identifier of users parent> ]
[ --office_location <office location of the user> ] [ --company <company of the
user> ] [ --profession <profession of the user> ] [ --timezone <time zone of
the user> ] [ --locale <locale of the user> ] [ --department <department of
the user> ] [ --assistant <assistant identifier> ] [ --manager <manager
identifier> ] [ --organization <organization identifier> ... ] [ --remove_
organization <organization identifier> ... ] [ --login_id <+/-login_id> ] [
--login_password <password> ] [ --voice_principal <+/-voice devicenum> ]
[ --voice_pin <pin> ] [ --property
<+/-name(certificate|notes)=value=description> ... ] [ --protocol_principal
<+/-protocol principal> ] [ --protocol_password <protocol password> ] [
--address <+/-type of address(business_1|other_5|personal_4|proxy_
1|...):scheme(im|mailto|...):value> ... ] [ --default_address_for_type <type of
address(business_1|other_5|personal_4|proxy_1|...):scheme(im|mailto|...):value> ]
[ --default_address_for_scheme <type of address(business_1|other_5|personal_
4|proxy_1|...):scheme(im|mailto|...):value> ] [ --primary_address <type of
address(business_1|other_5|personal_4|proxy_1|...):scheme(im|mailto|...):value> ]
[ --status <status of user(locked|enabled|disabled)> ] [ --external_inbox
<true|false> ] [ --delegate <[+][delegated_principal_name]:identifier_of_
delegator or -delegated_principal_identifier> ] [ --lock <principal to be
locked(PRIMARY|PROTOCOL|VOICE|ALL)> ] [ --unlock <principal to be
unlocked(PRIMARY|PROTOCOL|VOICE|ALL)> ]
```

OPTIONS

--user

Identifier of the user.

--email

Email id of the user

--family_name

Family name of the user in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--given_name

Given name of the user in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_

CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--display_name

Display name of the user in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--middle_name

Middle name of the user in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--job_title

Job title of the user in the format: value or locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--prefix

Prefix of the user in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--suffix

Suffix of the user in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--nick_name

Nick name of the user in the format: [+/-]value or [+/-]locale:value. If only value is specified, the assumed value of locale is en_US. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc. + or - in the start of the string tells whether the parameter should be added or removed. + or no symbol means the parameter should be added. If - is specified that means the parameter should be removed. Default action is addition.

--scope

Identifier of the enterprise or organization under which this user will be created.

--office_location

Office location of the user. To remove the previously defined value pass either of the following strings: NULL or null.

--company

Company of the user. To remove the previously defined value pass either of the following strings: NULL or null.

--profession

Profession of the user. To remove the previously defined value pass either of the following strings: NULL or null.

--timezone

Time zone of the user. list_timezones lists the valid time zones

--locale

Locale details of the user. Example of locales are en, en_US, en_CA, zh_CN, fr_FR, ja_JP, etc.

--department

Department of the user. To remove the previously defined value pass either of the following strings: NULL or null.

--assistant

Identifier of the assistant.

--manager

Identifier of the manager.

--organization

Identifiers of the organizations the user must be part of.

--remove_organization

Identifiers of the organizations the user must be removed from.

--property

Details of the property in the format [+/-]name=value=description. Supported names are certificate, and notes. Note, no equals to symbol(=) should be present in the name or value or description. + or no symbol means the property should be added. If - is specified that means the property should be removed. Default action is addition.

--address

Address of the user in the format [+/-]type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25. + or - in the start of the string tells whether the address should be added or removed. + or no symbol means the address should be added. If - is specified that means the address should be removed. Default action is addition.

--default_address_for_type

Address of the user in the format type:scheme:value. Sets the specified address as the default for the specified type. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn,

oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--default_address_for_scheme

Address of the user in the format type:scheme:value. Sets the specified address as the default for the specified scheme. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--primary_address

Primary address of the user in the format type:scheme:value. Supported schemes are mailto, tel, fax, ftp, http, https, im, imap, ldap, news, nntp, oraalert, oraassistantphone, oracallback, oraisdn, oramobile, oracarphone, orapager, orapostal, orapush, oraradio, orasms, oratelex, orattytd, oravmail, pres, sip, urn, xmpp. Supported types are BUSINESS_1 to BUSINESS_5, PERSONAL_1 to PERSONAL_5, OTHER_1 to OTHER_5, PROXY_1 to PROXY_25.

--login_id

The login credentials of the user. A user can have only one login id. Hence if a user already has a login id then the old value will be replaced with the new value.

--login_password

Login password.

--voice_principal

Voice principal of the user. A user can have only one voice principal. Hence if a user already has a voice principal then the old value will be replaced with the new value.

--voice_pin

Pin number for the voice device.

--protocol_principal

Protocol principal of the user. A user can have only one protocol principal. Hence if a user already has a protocol principal then the old value will be replaced with the new value.

--protocol_password

Protocol password.

--status

Sets the provisioning status of the user. Supported values are ENABLED, DISABLED, LOCKED.

--external_inbox

Boolean values which indicates if user's inbox is external or not. Supported values are TRUE, FALSE.

--delegate

Details of the delegated principal in the format principal_name:delegated_identifier or -delegated_principal_identifier. principal_name is the name of the delegated principal that will be created and delegated_identifier is the identifier of the actor who is being delegated. + or - in the start of the string tells whether the principal should be added or removed. + or no symbol means the delegated principal should be added. If the principal name contains a colon(:) it should be properly escaped. If - is specified that means the delegated principal should be removed. In this case only the identifier of the delegated principal has to be specified. Default action is addition. While removing the principal the minus sign (-) has to be escaped. Example: use a s ESCAPE:-. For more details on escaping please refer to beectl help.

--lock

Locks the principal specified. Valid values are PRIMARY, PROTOCOL, VOICE, ALL. ALL will lock all the principals of the user.

--unlock

Unlocks the principal specified. Valid values are PRIMARY, PROTOCOL, VOICE, ALL. ALL will unlock all the principals of the user.

EXAMPLES

```
beectl modify_user --user loginid=user1 --given_name
User1GivenName --family_name -en_CA:User1FamilyName --office_
location 4A037
```

```
beectl modify_user --email user1@example.com --property +is_
external_user=true
```

```
beectl modify_user --email user1@example.com --address BUSINESS_
1:mailto:user1@example.com --address ESCAPE:-BUSINESS_
2:im:user1@example.com
```

```
beectl modify_user --user loginid=user1 --voice_principal
1234567 --voice_pin 123423 --protocol_principal
ESCAPE:-protocolPrincipal
```

```
beectl modify_user --user loginid=user1 --lock PROTOCOL
```

```
beectl modify_user --user loginid=user1 --unlock PRIMARY
```

```
beectl modify_user --user loginid=user1 --unlock ALL
```

```
beectl modify_user --user loginid=user1 --nick_name
+en:User1NickName --assistant loginid=user3 --manager
loginid=user2
```

```
beectl modify_user --email user1@example.com --status disabled
```

```
beectl modify_user --user loginid=user1 --delegate  
DelegatedPrincipalName:loginid=user2
```

```
beectl modify_user --user loginid=user1 --delegate  
ESCAPE:-pcpd=CalendarDelegation2,loginid=rafiul2
```

modify_user_subscription

Enables or disables an existing subscription

SYNTAX

```
beectl modify_user_subscription --enable {true|false} --subscription <Subscription  
identifier>
```

OPTIONS

--enable

Enable or disable the subscription. Permitted values are 'true' (enable subscription) or 'false' (disable subscription)

--subscription

Specify the identifier of the subscription.

EXAMPLES

```
beectl modify_user_subscription --enable true --subscription  
5457:7954:subs:337F34E37E8E81F1E040578C921630B700000000B864
```

modify_version_configuration

Updates a given version configuration.

SYNTAX

```
beectl modify_version_configuration --configuration <Configuration identifier>  
--file <Full path of the configuration XML file>
```

OPTIONS

--configuration

Version configuration to be updated.

--file

Full path of the version configuration XML file. The file must contain properly formatted data.

EXAMPLES

```
beectl modify_version_configuration --configuration
9941:2345:avcg:58D193D162CE4ED89FF66AB4E55745B6345464545453
--file /tmp/configuration.xml
```

modify_virus_scan_policy

Modifies the virus scan policy configured for the Site. Valid values for the scan policy are: NO_SCAN_OR_REPAIR, SCAN_ONLY, SCAN_AND_REPAIR. Default is NO_SCAN_OR_REPAIR.

SYNTAX

```
beectl modify_virus_scan_policy [ --scanpolicy <virusscanpolicy> ]
```

OPTIONS**--scanpolicy**

Virus scan policy. Default is NO_SCAN_OR_REPAIR.

EXAMPLES

```
beectl modify_virus_scan_policy --scanpolicy SCAN_AND_REPAIR
```

modify_workspace_template

Modifies an existing workspace template

SYNTAX

```
beectl modify_workspace_template --template <Workspace template identifier>
[--file <Full path of the template file>] [--name <Workspace template name>]
```

OPTIONS**--template**

Workspace template identifier

--file

Full path of the template file

--name

Workspace template name

EXAMPLES

```
beectl modify_workspace_template --template
9941:2345:twtt:58D193D162CE4ED89FF66AB4E55745B6345464545453
--file /tmp/template.xml
```

```
beectl modify_workspace_template --template
9941:2345:twtt:58D193D162CE4ED89FF66AB4E55745B6345464545453
--name New_Name --file /tmp/template.xml
```

obfuscate

Obfuscates the prompted string.

SYNTAX

```
beectl obfuscate [--expiration_time_in_minutes 30]
```

OPTIONS

--expiration_time_in_minutes

Indicates the time in minutes for which obfuscated string should be valid for the use in this Beehive instance. If "0" is passed, obfuscated string will never expire.

EXAMPLES

```
beectl obfuscate
```

(Prompted)Enter the password : [User types in the password which is not echoed on the standard output].

restart

Manages OC4J Instances, Beehive Transport Infrastructure Monitors and Oracle HTTP servers components. The command "beectl status" displays the component id and the status of these manageable components.

SYNTAX

```
beectl restart [ --component <component id> | --all | --serially]
```

OPTIONS

--component

Identifier of component to restart. To restart more than one component at a time, specify this option multiple times.

--all

restart all managed components.

--serially

It specified, restarts all the components one by one.

EXAMPLES

```
beectl restart --all
```

```
beectl restart --component 5792bd5f-3b46-42de-a15d-8fe4b86fd46f
```

start

Manages OC4J Instances, Beehive Transport Infrastructure Monitors and Oracle HTTP servers components. The command "beectl status" displays the component id and the status of these manageable components.

SYNTAX

```
beectl start [ --component <component id> | --all | --serially]
```

OPTIONS**--component**

Identifier of component to start. To start more than one component at a time, specify this option multiple times.

--all

start all managed components.

--serially

If specified, starts all the components one by one.

EXAMPLES

```
beectl start --all
```

```
beectl start --component 5792bd5f-3b46-42de-a15d-8fe4b86fd46f
```

status

Displays the status of all managed components.

SYNTAX

```
beectl status [--dashboard | --detail] [--all_home_instances | --all_services |  
(--component <State manageable component>) ... --all_disabled_components |  
[--disabled_beehive_instances] [--disabled_oc4js] [--disabled_service_instances]  
[--disabled_services] ]
```

OPTIONS**--dashboard**

A dashboard view of all the specified components is shown.

--detail

A detailed view of all the specified components is shown.

--all_home_instances

Status of all Beehive instances is shown.

--all_services

Status of all Services is shown.

--component

Status of the specified components is shown.

--all_disabled_components

Lists all the disabled components in the system is shown.

--disabled_beehive_instances

Lists all the disabled beehive instances in the system is shown.

--disabled_oc4js

Lists all the disabled managed oc4js in the system is shown.

--disabled_service_instances

Lists all the disabled service instances in the system is shown.

--disabled_services

Lists all the disabled services in the system is shown.

EXAMPLES

```
beectl status
```

stop

Manages OC4J Instances, Beehive Transport Infrastructure Monitors and Oracle HTTP servers components. The command "beectl status" displays the component id and the status of these manageable components.

SYNTAX

```
beectl stop [ --component <component id> | --all | --serially]
```

OPTIONS**--component**

Identifier of component to stop. To stop more than one component at a time, specify this option multiple times.

--all

stop all managed components.

--serially

It specified, stops all the components one by one.

EXAMPLES

```
beectl stop --all
```

```
beectl stop --component 5792bd5f-3b46-42de-a15d-8fe4b86fd46f
```

upload_attendant_prompt

Upload a prompt to the database.

SYNTAX

```
beectl upload_attendant_prompt --name <name of attendant> --type <type of prompt>  
[--language <language of prompt>] --file <prompt file>
```


OPTIONS

--name

Name of the attendant.

--type

Type of the prompt. Can be one of language, menu, greeting, option1, option2, option3, option4, option4, option5, option6, option7, option8, option9, noinput, noinput-term, nomatch, nomatch-term.

--language

Language of the prompt.

--file

Path to the prompt file.

EXAMPLES

```
beectl upload_attendant_prompt --name myAttendant --type menu
--language en_US --file menu.wav
```

upload_client_application

Uploads client application binaries to the repository. Either a binary file path or path to a directory containing binary files should be specified. If the community option is specified, the uploaded client application patchset will also be provisioned to the community.

SYNTAX

```
beectl upload_client_application { --file <path to the client binary> | --dir
<full path to the directory containing the client binaries>} [--community
<Identifier of a community>]...
```

OPTIONS

--file

Specify the full path and file name of the client ZIP file.

--dir

Specify the full path of the directory containing the client ZIP files.

--community

Specify the identifier of the community to be provisioned with this uploaded patchset.

EXAMPLES

```
beectl upload_client_application --file
$BH/beehive/seed/dm/pushmail_debug.PPC5.0_ARM.element.zip
beectl upload_client_application --dir $BH/beehive/seed/dm/
beectl upload_client_application --file
$BH/beehive/seed/dm/pushmail_debug.PPC5.0_ARM.element.zip
```

```
--community  
1234:5678:entr:2E0329B0705F0E40E040578C92160957000000000434
```

upload_device_profiles

Uploads device profiles to the repository. An XML file or a directory containing XML files can be used as the source for the device profiles. The file can also contain device types and device profile schema.

SYNTAX

```
beectl upload_device_profiles { --file <Full file path of the device profiles XML  
file> | --dir <Full path of the directory containing device profiles XML files>}
```

OPTIONS

--file

Specify the full path and file name of the device profiles XML file.

--dir

Specify the full path of the directory containing the device profiles XML files.

EXAMPLES

```
beectl upload_device_profiles --file /tmp/device-profiles.xml  
beectl upload_device_profiles --dir /tmp/device-profiles/
```

upload_language_pack

Loads language pack resources into the system.

SYNTAX

```
beectl upload_language_pack --source <source> [--ignore_version] [--suppress_  
warning] [--accept_builtin]
```

OPTIONS

--source

Source jar file containing one or more xcliff files or one or more helpsets. Only a jar file is permitted as source value.

--ignore_version

Ignore version information in the xcliff files; use with caution.

--suppress_warning

Suppress warnings about potential xcliff problems; only report fatal errors.

--accept_builtin

Accept xcliff files or helpsets marked as built-in. This option must be used only when necessary because uploading built-in xcliff files or helpsets is typically a maintenance activity. In absence of this option the command will fail if a built-in xcliff file or helpset

is being uploaded - this behavior has been designed to guard against accidentally uploading built-in xlfiff files or helpsets.

EXAMPLES

```
beectl upload_language_pack --source abc.jar
```

Add/modify the xlfiff file(s) or helpset(s) packaged in abc.jar to existing language pack. Command will fail if any .xlf or helpset is of filetype builtin. abc.jar is expected to package helpset(s) in the directory structure helpsets/<library_name>/custom/<locale>/<helpset.jar>. .xlf files (and associated .class files) must be packaged in langpack/xlfiff/custom/x.xlf and langpack/<java-package-tree>/x.class directories respectively. Command will fail if any .xlf does not contain version. The command will fail if the version of an .xlf file is prior to the version of corresponding .xlf file in existing language pack. Helpsets are not versioned hence all custom helpsets from abc.jar MUST overwrite custom helpsets of same name and same locale in same library in existing language pack.

```
beectl upload_language_pack --source abc.jar --accept_builtin
```

Add/modify the xlfiff file(s) or helpset(s) packaged in abc.jar to existing language pack. Command will process helpsets or xlfiff files of both filetypes - built-in and custom. abc.jar is expected to package helpset(s) in the directory structure helpsets/<library_name>/<filetype>/<locale>/<helpset.jar>. .xlf files (and associated .class files) must be packaged in langpack/xlfiff/<filetype>/x.xlf and langpack/<java-package-tree>/x.class directories respectively. Command will fail if any .xlf does not contain version. The command will fail if the version of an .xlf file is prior to the version of corresponding .xlf file in existing language pack.

```
beectl upload_language_pack --source abc.jar --ignore_version
```

Add/modify the xlfiff file(s) or helpset(s) packaged in abc.jar to existing language pack. Command will fail if any .xlf or helpset is of filetype builtin. abc.jar is expected to package helpset(s) in the directory structure helpsets/<library_name>/custom/<locale>/<helpset.jar>. .xlf files (and associated .class files) must be packaged in langpack/xlfiff/custom/x.xlf and langpack/<java-package-tree>/x.class directories respectively. Version info in xlfiff files is completely ignored i.e. all custom .xlf files from abc.jar WILL overwrite custom files of same name in existing language pack.

```
beectl upload_language_pack --source abc.jar --accept_builtin
--ignore_version
```

Add/modify the xlfiff file(s) or helpset(s) packaged in abc.jar to existing language pack. Command will process helpsets or xlfiff files of both filetypes - built-in and custom. abc.jar is expected to package helpset(s) in the directory structure

helpsets/<library_name>/<filetype>/<locale>/<helpset.jar>. .xlf files (and associated .class files) must be packaged in langpack/xliff/<filetype>/x.xlf and langpack/<java-package-tree>/x.class directories respectively. Version info in xliff files is completely ignored i.e. all custom .xlf files from abc.jar WILL overwrite custom files of same name in existing language pack.

validate_audit_trail

Validates an existing audit trail

SYNTAX

```
beectl validate_audit_trail --trail <Audit trail identifier> [--count <Maximum number of audit records to print>]
```

OPTIONS

--trail

Audit trail identifier

--count

Maximum number of audit records to print

EXAMPLES

```
beectl validate_audit_trail --trail autr=MyAuditTrail
```

validate_configuration

Validates the configuration for given component id or for the whole system model tree.

SYNTAX

```
beectl validate_configuration [ --id <system object id or alias of system object>]
```

OPTIONS

--id

component id.

EXAMPLES

```
beectl validate_configuration
```

Validates the whole configuration system model.

```
beectl validate_configuration --id  
a1d290a8-f8a7-46ea-ae3d-0696c0bde331
```

Validates the system model object identified by given id or alias.

validate_directory_entry

Validates the directory entry in ldap with corresponding entry in beehive. The directory entry can be of type user, group or external person. The command provides an option to correct any data inconsistencies by applying necessary changes in beehive. The state of the profile specified in this command can either be ENABLE or DISABLE.

SYNTAX

```
beectl validate_directory_entry ([ --email <user_email> ] | [ --identifier <user_
bodn> ] | [ --dn <user_dn> ]) --profile <Profile_name> [--commit] [--verbose]
```

OPTIONS

--identifier

Identifier of the user, group or external-person in beehive

--email

Email-ID of the user, group or external-person.

--dn

DN (distinguished name) of the user, group or external-person in ldap directory

--commit

When Command is run with this option, it makes the changes in beehive database. The default is set to non-commit mode or no database changes.

--verbose

This option is used display the detailed information.

--profile

Name of the profile

EXAMPLES

```
beectl validate_directory_entry --email user1@example.com
--profile exampleProfile --commit --verbose
```

```
beectl validate_directory_entry --dn
cn=user2,cn=users,dc=example,dc=com --profile exampleProfile
--commit --verbose
```

```
beectl validate_directory_entry --identifier
loginid=user3@example.com --profile exampleProfile --verbose
```

```
beectl validate_directory_entry --identifier
loginid=user3@example.com --profile exampleProfile
```

validate_virus_scan_engine_connectivity

Tests the connectivity to the virus scan engine running at the specified host and port.

SYNTAX

```
beectl validate_virus_scan_engine_connectivity [ --hostname <scanengine_hostname>
] [ --port <scanengine_port> ]
```

OPTIONS

--hostname

Name of the host where the virus scan engine is installed. Default is localhost.

--port

Port number used by the virus scan engine for communication with its clients. Default is 1344.

EXAMPLES

```
beectl validate_virus_scan_engine_connectivity --hostname
scanenginehost.example.com --port 1344
```

version

This command shows the version information of the Beehive products.

List of valid Beehive products is shown below. Use them as a value for the "product" option.

```
accesschecks
accesscontrol
admin
artifacts
audit
authn
beectl
beehivemail
bio
btimon
cms
common-framework
content
core
csi_r1
csi_r1-impl
cspi
```

discussions
dms
event
event-definitions
framework
ftp
im
jcr
management
mds
mgmtsvc
mobileclient
mobiledm
nms
oma
omb
owc
owc-stdmedia
platform
policy
presence
push
pushmail
search
smpp
tms
uds
uss
version
virusscanner
voice
voip
webdav
workflow
workspaces
xbom
xmpp

xms

List of valid field names is shown below. Use them as a value for "field" option.

name

build_version

internal_version

internal_version_name

public_version

public_version_name

product_description

product_suite_association_ids

beectl version command output is fully customizable. The multi-valued "product" option can be used to get version information for a specified set of products. Similarly the multi-valued "field" option can be used to get the information about the specified set of fields only.

When multi-valued product and field options are used, beectl version command display order is same as the order specified for product and field options in command line.

SYNTAX

```
beectl version [--all | [[--product <Product Name>] ...]] [[--field <Field Name>]...]
```

OPTIONS

--all

Shows version information for all products.

--product

Shows version information for the specified products. This option is multi-valued.

--field

Shows the value of the specified fields. This option is multi-valued.

EXAMPLES

```
beectl version --all
```

The above command will list the version information about all the products.

```
beectl version --product uds --field internal_version --field internal_version_name --field product_suite_association_ids
```

The above command will list internal_version, internal_version_name and product_suite information for the uds product.

Oracle Beehive Error Codes

This module contains Oracle Beehive error codes.

Access Control Error Codes

The following table lists error codes for Access Control.

Table 3–1 Access Control

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00500	A problem occurred executing an AccessControl CSI method.	FINE	See the associated exception for details.	The AccessControl CSI method failed.	Please contact Oracle Support for more information.
BEES-00501	PL/SQL returned an exception.	FINE	See the associated exception for details.	The PL/SQL failed to execute.	Please contact Oracle Support for more information.
BEES-00502	A problem occurred trying to access the database.	WARNING	See the associated exception for details.	A problem occurred trying to access the database.	Please contact Oracle Support for more information.
BEEU-00503	An illegal or invalid argument was specified.	WARNING	See the associated exception for details.	The affected CSI method failed to execute.	Correct the argument and try again. Please contact Oracle Support for more information if the problem persists.
BEEC-00504	An AccessControl service related exception occurred.	SEVERE	See the associated exception for details.	See the associated exception for details.	Please contact Oracle Support for more information.
BEER-00505	A PL/SQL exception occurred.	WARNING	A PL/SQL exception occurred.	PL/SQL execution failed.	Please contact Oracle Support for more information.
BEEZ-00506	You do not have the required access.	FINE	You do not have the required access.	You do not have the required access.	Please contact Oracle Support for more information.
BEEU-00507	There already is an Entity with similar attributes at the same Scope.	FINE	There already is an Entity with similar attributes at the same Scope.	There already is an Entity with similar attributes at the same Scope.	Please contact Oracle Support for more information.
BEEU-00508	The specified Entity does not exist.	FINE	The specified Entity does not exist.	The specified Entity does not exist.	Please contact Oracle Support for more information.
BEEU-00509	The specified Entity does not exist or has not been registered with AccessControl.	WARNING	The specified Entity does not exist or has not been registered with AccessControl.	The specified Entity does not exist or has not been registered with AccessControl.	Please contact Oracle Support for more information.

Table 3–1 (Cont.) Access Control

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00510	A PL/SQL integrity constraint violation occurred.	FINE	A PL/SQL integrity constraint violation occurred.	PL/SQL execution failed.	Please contact Oracle Support for more information.
BEEU-00511	A PL/SQL unique constraint violation occurred.	FINE	A PL/SQL unique constraint violation occurred.	PL/SQL unique failed.	Please contact Oracle Support for more information.
BEEU-00512	The specified Entity snapshot is outdated.	FINE	The specified Entity snapshot is outdated.	The specified Entity snapshot is outdated.	Please contact Oracle Support for more information.

Address Book Error Codes

The following table lists error codes for Address Book.

Table 3–2 Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03101	An error occurred during address book creation	WARNING	Duplicate entity No such entity The specified parent does not exist or cannot be used The name was not specified or cannot be used The specified name is already in use Root address book already exists for the specified parent Quota/lock check failed The user does not have the required access rights Failed to set the change status of the entity Failed to register the container with workspace Failed to register the element with workspace Failed to register the entity with access control service Failed to set access on the entity Failed to load the entity Failed to raise event for the operation Failed to perform a workspace operation	The specified address book was not created	Specify a valid value Specify another value See the log file for more details
BEEU-03102	An error occurred during address book update	INFO	A newer version of the specified entity exists in the system The specified address book is invalid No such entity The specified name is already in use The user does not have the required access rights Quota/lock check failed Failed to perform a workspace operation Failed to raise event for the operation Failed to set the change status of the entity Failed to load the entity	The specified address book was not updated	Specify a valid value Specify another value Refresh the entity and retry the operation See the log file for more details

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03103	An error occurred during address book deletion	WARNING	No such entity The specified address book is invalid A newer version of the specified entity exists in the system The user does not have the required access rights Quota/lock check failed Failed to perform a workspace operation Failed to raise event for the operation This operation is not allowed on a default address book	The specified address book was not deleted	Specify a valid value Refresh the entity and retry the operation See the log file for more details
BEEU-03104	An error occurred during address book load	INFO	No such entity The user does not have the required access rights The specified address book is invalid	The specified address book was not loaded	Specify a valid value
BEEU-03105	An error occurred during address book move	INFO	A newer version of the specified entity exists in the system The specified address book is invalid No such entity The source address book does not exist The destination address book/workspace does not exist The specified name is already in use The specified parent does not exist or cannot be used The user does not have the required access rights Quota/lock check failed Failed to perform a workspace operation Failed to raise event for the operation Failed to set access on the entity This operation is not allowed on a default address book The address book cannot be moved to one of its sub address books	The specified address book was not moved	Specify a valid value Specify another value Refresh the entity and retry the operation See the log file for more details

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03106	An error occurred during address book copy	INFO	<p>A newer version of the specified entity exists in the system</p> <p>The specified address book is invalid</p> <p>No such entity</p> <p>The source address book does not exist</p> <p>The destination address book/workspace does not exist</p> <p>The specified name is already in use</p> <p>Duplicate entity</p> <p>The specified parent does not exist or cannot be used</p> <p>The user does not have the required access rights</p> <p>Root address book already exists for the specified parent</p> <p>Quota/lock check failed</p> <p>Failed to set the change status of the entity</p> <p>Failed to register the container with workspace</p> <p>Failed to register the element with workspace</p> <p>Failed to register the entity with access control service</p> <p>Failed to set access on the entity</p> <p>Failed to load the entity</p> <p>Failed to raise event for the operation</p> <p>Failed to apply labels to the specified entity</p> <p>Failed to perform a workspace operation</p>	The specified address book was not copied	<p>Specify a valid value</p> <p>Specify another value</p> <p>Refresh the entity and retry the operation</p> <p>See the log file for more details</p>

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03107	An error occurred during address book undelete	WARNING	A newer version of the specified entity exists in the system The specified address book is invalid No such entity The specified name is already in use Duplicate entity The destination address book/workspace does not exist The specified parent does not exist or cannot be used The user does not have the required access rights Quota/lock check failed Failed to set access on the entity Failed to raise event for the operation Failed to perform a workspace operation	The specified address book was not undeleted	Specify a valid value Specify another value Refresh the entity and retry the operation See the log file for more details
BEEU-03108	An error occurred during address book get	INFO	No such entity Failed to load the entity The user was not specified or cannot be used The specified workspace is invalid The specified parent does not exist or cannot be used	The address book for the specified entity could not be retrieved	Specify a valid value
BEEU-03109	An error occurred during get element modifications for the address book	WARNING	No such entity The specified address book is invalid The specified anchor is too old	The modified elements could not be fetched for the address book	Specify a valid value Specify another value
BEEU-03110	An error occurred during address book purge	WARNING	Failed to purge the contacts in the address book Failed to unregister the entity with access control service Failed to perform a workspace operation	The specified address book was not purged	See the log file for more details
BEEU-03111	An error occurred during address book archiving	WARNING	Failed to archive the contacts in the address book Failed to unregister the entity with access control service Failed to perform a workspace operation	The specified address book was not archived	See the log file for more details
BEEU-03112	An error occurred while listing address books	WARNING	The specified address book is invalid The specified list filter is invalid A projection was not specified or cannot be used	The address books could not be listed	Specify a valid value

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03113	An error occurred during address book element bulk load	WARNING	A projection was not specified or cannot be used The specified address book element is invalid	The specified address book elements were not loaded	Specify a valid value
BEEU-03116	An error occurred during person contact creation	WARNING	The user does not have the required access rights The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified parent does not exist or cannot be used The specified bookmark value is invalid The speeddial specified is not correct or unique Failed to register the entity with access control service Failed to set access on the entity Quota/lock check failed Failed to perform a workspace operation Failed to perform the required attachment operation. Check the logs for more details. The specified roster entry exists Failed to raise event for the operation	The specified person contact was not created	Specify a valid value Specify another value Maximum count for the addresses exceeded, check the maximum addresses allowed See the log file for more details Quota exceeded, check the allowed quota
BEEU-03117	An error occurred during person contact load	WARNING	No such entity The user does not have the required access rights The specified person contact is invalid	The specified person contact was not loaded	Specify a valid value

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03118	An error occurred during person contact update	WARNING	No such entity The specified person contact is invalid A newer version of the specified entity exists in the system Failed to perform a workspace operation The specified parent does not exist or cannot be used The user does not have the required access rights Quota/lock check failed The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The speeddial specified is not correct or unique The quota for the contacts has exceeded Failed to perform the required attachment operation. Check the logs for more details. Failed to raise event for the operation The specified roster entry exists This operation is not allowed on automatically created contacts	The specified person contact was not updated	Specify a valid value Specify another value Refresh the entity and retry the operation Maximum count for the addresses exceeded, check the maximum addresses allowed See the log file for more details Quota exceeded, check the allowed quota

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03119	An error occurred during person contact delete	WARNING	No such entity The specified person contact is invalid A newer version of the specified entity exists in the system The user does not have the required access rights Quota/lock check failed Failed to perform a workspace operation Failed to delete reminders of a contact Failed to raise event for the operation This operation is not allowed on automatically created contacts	The specified person contact was not deleted	Specify a valid value Refresh the entity and retry the operation Specify another value
BEEU-03120	An error occurred during person contact undelete	WARNING	No such entity The specified person contact is invalid The specified parent does not exist or cannot be used The user does not have the required access rights Quota/lock check failed Failed to perform a workspace operation The destination address book does not exist The speeddial specified is not correct or unique Failed to set access on the entity The quota for the contacts has exceeded The specified roster entry exists Failed to raise event for the operation	The specified person contact was not undeleted	Specify a valid value Specify another value See the log file for more details Quota exceeded, check the allowed quota
BEEU-03121	An error occurred during person contact move	WARNING	No such entity The user does not have the required access rights Quota/lock check failed Failed to set access on the entity The specified person contact is invalid The specified parent does not exist or cannot be used The destination address book does not exist The quota for the contacts has exceeded Failed to raise event for the operation This operation is not allowed on automatically created contacts	The specified person contact was not moved	Specify a valid value Specify another value Quota exceeded, check the allowed quota

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03122	An error occurred during person contact copy	WARNING	No such entity The user does not have the required access rights The specified person contact is invalid The specified parent does not exist or cannot be used The destination address book does not exist The quota for the contacts has exceeded Failed to raise event for the operation Failed to apply labels to the specified entity Failed to copy attachments to the specified contact Failed to perform a workspace operation Failed to set access on the entity	The specified person contact was not copied	Specify a valid value Specify another value Quota exceeded, check the allowed quota
BEEU-03123	An error occurred during person contact purge	WARNING	Failed to unregister the entity with access control service	The specified person contact was not purged	See the log file for more details
BEEU-03124	An error occurred during person contact archiving	WARNING	Failed to unregister the entity with access control service	The specified person contact was not archived	See the log file for more details
BEEU-03125	An error occurred while listing person contacts	WARNING	The specified address book is invalid The specified list filter is invalid A projection was not specified or cannot be used	The person contacts could not be listed	Specify a valid value
BEEU-03126	An error occurred while listing duplicate person contacts	WARNING	The specified address book is invalid No attributes specified for duplicate check	The person contacts could not be listed	Specify a valid value

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03131	An error occurred during group contact creation	WARNING	The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The user does not have the required access rights Failed to register the entity with access control service Failed to set access on the entity Quota/lock check failed The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified parent does not exist or cannot be used The specified bookmark value is invalid The speeddial specified is not correct or unique The quota for the contacts has exceeded Adding or removing members to bookmarked group contacts is not allowed Failed to perform the required attachment operation. Check the logs for more details. The specified roster entry exists A bookmarked group contact cannot be a buddy list entry A buddy list group contact must have a group name Failed to raise event for the operation The specified given name is used by auto created Manager and Peers/Direct Reports group contact	The specified group contact was not created	Specify a valid value Specify another value Maximum count for the addresses exceeded, check the maximum addresses allowed See the log file for more details Quota exceeded, check the allowed quota
BEEU-03132	An error occurred during group contact load	WARNING	No such entity The user does not have the required access rights The specified group contact is invalid	The specified group contact was not loaded	Specify a valid value

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03133	An error occurred during group contact update	WARNING	No such entity The specified group contact is invalid A newer version of the specified entity exists in the system Failed to perform a workspace operation The specified parent does not exist or cannot be used The user does not have the required access rights Quota/lock check failed The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The speeddial specified is not correct or unique The quota for the contacts has exceeded Adding or removing members to bookmarked group contacts is not allowed Failed to perform the required attachment operation. Check the logs for more details. Failed to raise event for the operation The specified roster entry exists A bookmarked group contact cannot be a buddy list entry A buddy list group contact must have a group name This operation is not allowed on automatically created contacts	The specified group contact was not updated	Specify a valid value Refresh the entity and retry the operation Specify another value Maximum count for the addresses exceeded, check the maximum addresses allowed See the log file for more details Quota exceeded, check the allowed quota

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03134	An error occurred during group contact delete	WARNING	No such entity The specified group contact is invalid A newer version of the specified entity exists in the system The user does not have the required access rights Quota/lock check failed Failed to delete reminders of a contact Failed to raise event for the operation This operation is not allowed on automatically created contacts	The specified group contact was not deleted	Specify a valid value Refresh the entity and retry the operation Specify another value
BEEU-03135	An error occurred during group contact undelete	WARNING	No such entity The specified group contact is invalid The specified parent does not exist or cannot be used The user does not have the required access rights Quota/lock check failed Failed to perform a workspace operation Failed to set access on the entity The destination address book does not exist The speeddial specified is not correct or unique The quota for the contacts has exceeded The specified roster entry exists Failed to raise event for the operation	The specified group contact was not undeleted	Specify a valid value See the log file for more details Specify another value Quota exceeded, check the allowed quota
BEEU-03136	An error occurred during group contact move	WARNING	No such entity The user does not have the required access rights Quota/lock check failed Failed to set access on the entity The specified group contact is invalid The specified parent does not exist or cannot be used The destination address book does not exist The quota for the contacts has exceeded Failed to raise event for the operation This operation is not allowed on automatically created contacts	The specified group contact was not moved	Specify a valid value Specify another value Quota exceeded, check the allowed quota

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03137	An error occurred during group contact copy	WARNING	No such entity The user does not have the required access rights The specified group contact is invalid The specified parent does not exist or cannot be used The destination address book does not exist The quota for the contacts has exceeded Failed to raise event for the operation Failed to apply labels to the specified entity Failed to copy attachments to the specified contact Failed to perform a workspace operation Failed to set access on the entity	The specified group contact was not copied	Specify a valid value Specify another value Quota exceeded, check the allowed quota
BEEU-03138	An error occurred during group contact purge	WARNING	Failed to unregister the entity with access control service	The specified group contact was not purged	See the log file for more details
BEEU-03139	An error occurred during group contact archiving	WARNING	Failed to unregister the entity with access control service	The specified group contact was not archived	See the log file for more details
BEEU-03140	An error occurred while listing group contacts	WARNING	The specified address book is invalid The specified list filter is invalid A projection was not specified or cannot be used	The group contacts could not be listed	Specify a valid value
BEEU-03141	An error occurred while listing duplicate group contacts	WARNING	The specified address book is invalid No attributes specified for duplicate check	The group contacts could not be listed	Specify a valid value

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03146	An error occurred during resource contact creation	WARNING	The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The user does not have the required access rights Failed to register the entity with access control service Failed to set access on the entity Quota/lock check failed The specified parent does not exist or cannot be used The specified bookmark value is invalid The speeddial specified is not correct or unique The quota for the contacts has exceeded Failed to perform the required attachment operation. Check the logs for more details. Failed to raise event for the operation	The specified resource contact was not created	Specify a valid value Specify another value Maximum count for the addresses exceeded, check the maximum addresses allowed See the log file for more details Quota exceeded, check the allowed quota
BEEU-03147	An error occurred during resource contact load	WARNING	No such entity The user does not have the required access rights The specified resource contact is invalid	The specified resource contact was not loaded	Specify a valid value

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03148	An error occurred during resource contact update	WARNING	No such entity The specified resource contact is invalid A newer version of the specified entity exists in the system Failed to perform a workspace operation The specified parent does not exist or cannot be used The user does not have the required access rights Quota/lock check failed The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The speeddial specified is not correct or unique The quota for the contacts has exceeded Failed to perform the required attachment operation. Check the logs for more details. Failed to raise event for the operation This operation is not allowed on automatically created contacts	The specified resource contact was not updated	Specify a valid value Refresh the entity and retry the operation Specify another value Maximum count for the addresses exceeded, check the maximum addresses allowed See the log file for more details Quota exceeded, check the allowed quota

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03149	An error occurred during resource contact delete	WARNING	No such entity The specified resource contact is invalid A newer version of the specified entity exists in the system The user does not have the required access rights Quota/lock check failed Failed to perform a workspace operation Failed to delete reminders of a contact Failed to raise event for the operation This operation is not allowed on automatically created contacts	The specified resource contact was not deleted	Specify a valid value Refresh the entity and retry the operation Specify another value
BEEU-03150	An error occurred during resource contact undelete	WARNING	No such entity The specified resource contact is invalid The specified parent does not exist or cannot be used The user does not have the required access rights Quota/lock check failed Failed to perform a workspace operation Failed to set access on the entity The destination address book does not exist The speeddial specified is not correct or unique The quota for the contacts has exceeded Failed to raise event for the operation	The specified resource contact was not undeleted	Specify a valid value See the log file for more details Specify another value Quota exceeded, check the allowed quota
BEEU-03151	An error occurred during resource contact move	WARNING	No such entity Quota/lock check failed The user does not have the required access rights Failed to set access on the entity The specified resource contact is invalid The specified parent does not exist or cannot be used The destination address book does not exist The quota for the contacts has exceeded Failed to raise event for the operation This operation is not allowed on automatically created contacts	The specified resource contact was not moved	Specify a valid value Specify another value Quota exceeded, check the allowed quota

Table 3–2 (Cont.) Address Book

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03152	An error occurred during resource contact copy	WARNING	No such entity The user does not have the required access rights The specified resource contact is invalid The specified parent does not exist or cannot be used The destination address book does not exist The quota for the contacts has exceeded Failed to raise event for the operation Failed to apply labels to the specified entity Failed to copy attachments to the specified contact Failed to perform a workspace operation Failed to set access on the entity	The specified resource contact was not copied	Specify a valid value Specify another value Quota exceeded, check the allowed quota
BEEU-03153	An error occurred during resource contact purge	WARNING	Failed to unregister the entity with access control service	The specified resource contact was not purged	See the log file for more details
BEEU-03154	An error occurred during resource contact archiving	WARNING	Failed to unregister the entity with access control service	The specified resource contact was not archived	See the log file for more details
BEEU-03155	An error occurred while listing resource contacts	WARNING	The specified address book is invalid The specified list filter is invalid A projection was not specified or cannot be used	The resource contacts could not be listed	Specify a valid value
BEEU-03156	An error occurred while listing duplicate resource contacts	WARNING	The specified address book is invalid No attributes specified for duplicate check	The resource contacts could not be listed	Specify a valid value
BEEU-03161	An error occurred during cancel operation	WARNING	Failed to perform the required attachment operation. Check the logs for more details.	The operation was not canceled	Try again later. If the problem persists, contact your system administrator

Audit Error Codes

The following table lists error codes for Audit.

Table 3–3 Audit

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03201	NULL value passed in as method parameter	WARNING	One or more parameters are invalid or null		
BEEU-03202	Audit artifact matching given name or container already exists	WARNING	Check the name, container's identifier etc before invoking the method		
BEEU-03203	Audit artifact with the given identifier not found	WARNING	Invalid identifier specified or search criteria may not be valid		
BEEU-03204	Invalid parameter value supplied to service method	WARNING	Supplied parameter value or length of the value is invalid		Provide correct value for the service method parameter
BEEU-03205	User's logon record or session identifier not found	WARNING	User session may have expired		
BEEU-03206	Audit template not found	INFO	Identifier is either invalid or an audit artifact for the given identifier does not exist		
BEEU-03207	Audit policy not found	INFO	Identifier is either invalid or an audit artifact for the given identifier does not exist		
BEEU-03208	Audit trail not found	INFO	Identifier is either invalid or an audit artifact for the given identifier does not exist		
BEEU-03209	Audit record not found	INFO	No audit records matching the search criteria		
BEEU-03210	Failed to delete audit template	WARNING	An audit policy based on the given template exists		Delete the audit policy before deleting the audit template
BEEU-03211	Failed to create audit policy	WARNING	Duplicate identifier or policy name		
BEEU-03212	Failed to create audit trail	WARNING	Duplicate identifier or trail name		

Authentication Service Error Codes

The following table lists error codes for Authentication Service.

Table 3–4 Authentication Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00800	AUTH: Method not supported.	WARNING	AUTH: Method not supported.		
BEEU-00801	AUTH: User Already Exists.	WARNING	AUTH: User Already Exists.		
BEEU-00802	AUTH: User does not exist.	WARNING	AUTH: User does not exist.		

Table 3–4 (Cont.) Authentication Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00803	AUTH: Non-conformant username.	WARNING	AUTH: Non-conformant username.		
BEEU-00804	AUTH: Non-conformant password.	WARNING	AUTH: Non-conformant password. {0}		
BEEU-00805	AUTH: Non-conformant pin.	WARNING	AUTH: Non-conformant pin.		
BEEU-00806	AUTH: Non-conformant device.	WARNING	AUTH: Non-conformant device.		
BEEU-00807	AUTH: Invalid username/password.	WARNING	AUTH: Invalid username/password .		
BEEU-00808	AUTH: Device already registered.	WARNING	AUTH: Device already registered.		
BEEU-00809	AUTH: Device not registered.	WARNING	AUTH: Device not registered.		
BEEU-00810	AUTH: Invalid username/pin.	WARNING	AUTH: Invalid username/pin.		
BEEU-00811	AUTH: Password modification failiure.	WARNING	AUTH: Password modification failiure.		
BEEU-00812	AUTH: Illegal argument.	WARNING	AUTH: Illegal argument.		
BEEU-00820	AUTH: Invalid AuthenticationToken.	WARNING	AUTH: Invalid AuthenticationToken .		
BEEU-00821	AUTH: UserContext Creation Failed.	WARNING	AUTH: UserContext Creation Failed.		
BEEU-00822	AUTH: Invalid UserContext.	FINE	AUTH: Invalid UserContext.		
BEEU-00823	AUTH: Invalid Credentials.	WARNING	AUTH: Invalid Credentials.		
BEEU-00824	AUTH: Authentication Failed.	WARNING	AUTH: Authentication Failed.		
BEEU-00825	AUTH: UDS Resolve Failed.	WARNING	AUTH: UDS Resolve Failed.		
BEEU-00826	AUTH: Authorization Error.	WARNING	AUTH: Authorization Error.		
BEEU-00850	AUTH: Authentication store exception.	WARNING	AUTH: Authentication store exception.		

Bom Object Distinguished Naming Error Codes

The following table lists error codes for Bom Object Distinguished Naming.

Table 3–5 Bom Object Distinguished Naming

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03700	Bodn parsing failed.	SEVERE	Reason: {0}. Invalid bodn format provided. Invalid type "{0}" is provided. Invalid BOM type is used. Invalid BOM type is used. Reason: {0}.	Could not parse value "{0}".	Please use correct format of identifier. Please use correct bodn format (type=name). For example, orgn=yyy,enpr=xxx Please provide correct value. Please provide correct value using bom type as "{0}".
BEEU-03701	Could not find the given entity.	SEVERE	Could not resolve the given bodn into unique entity. No entity found for the given bodn. Given scope is not supported for "{0}" type. No identifiable name is found for given identifier "{0}".	Bodn parsing failed for value "{0}".	Please use collab id format for the value. Please use correct value. Please use correct scope or parent while specifying the bodn. Only collab id format can be used to refer this entity.
BEEU-03702	Internal error occurred.	SEVERE	Given entity type "{0}" is not yet supported. Naming on given Id type "{0}" is not yet supported.	Entity could not be found for "{0}".	Please use system generated identifier as the value. Naming on given Id type "{0}" is not yet supported.

Client Management Service Error Codes

The following table lists error codes for Client Management Service.

Table 3–6 Client Management Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEZ-03901	Session identity mismatch.	SEVERE	New channel identity doesn't match session identity.	Session is terminated for security reasons.	Please contact your administrator.
BEEU-03902	Some of the data or parameter you supplied was invalid or out of range.	WARNING	Number of specified EIDs doesn't match the number of entities Specified control class {0} was not found. No exact method match found. Projection {0} is undefined for snapshot {1}. Request was not recognized because it doesn't conform to specification. Request doesn't have a body. Request is empty. Request can't be parsed because it either malformed or refers to unregistered XBOM class.	Your request wasn't executed.	Correct and resubmit your request.
BEEU-03903	Batch request execution interrupted.	INFO	One of the services thrown an exception while processing one of the batch items.	Some of the items in the batch were not processed.	Correct the problem and resubmit your request.

Device Management Error Codes

The following table lists error codes for Device Management.

Table 3–7 Device Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-00600	Device Management Service Operation aborted	WARNING	Null data recieved when not null value is expected	Device Management Service Operation aborted	Make sure all the null value constraints are followed as mentioned in the documentation and try again
BEEU-00601	Create Client Application failed	INFO	Client Application cannot be created in the repository due to internal error Client Application with same details exists in the repository Client Application with same Eid already exists in the repository	Client Application will not be created	Please contact Oracle Support for more information Create Client Application with a different name or vendor or language or os or processor or language Create Client Application with a different name or vendor or language or os or processor or language
BEEU-00602	Update Client Application failed	INFO	ClientApplication cannot be updated due to internal error Client Application is not found in the repository	Client Application will not be updated	Please contact Oracle Support for more information Try the operation with a valid Eid
BEEU-00603	Delete Client Application failed	INFO	Delete Client Application failed due to internal error Client Application is not found in the repository Installable Client Application exists in this Application hierarchy	Client Application will not be deleted	Please contact Oracle Support for more information Try the operation with a valid Eid Please delete the Installable Client Application in this Application hierarchy
BEEU-00604	Load Client Application failed	INFO	Load Client Application failed due to internal error Client Application is not found in the repository	Client Application will not be loaded	Make sure that the application is uploaded. If it is uploaded contact the System Administrator to resolve the issue. Try the operation with a valid Eid
BEES-00605	Resolve Client Application Failed	INFO	Client Application is not found in the repository	Client Application will not be loaded	Please retry with different values

Table 3–7 (Cont.) Device Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00611	Client Application Version cannot be created	INFO	Client Application Version cannot be created in the repository due to internal error Client Application Version with same versionnumber for this Client Application exists in the repository Client Application Version with same Eid already exists in the repository Client Application with Eid passed is not found in the repository	Client Application Version will not be created	Please contact Oracle Support for more information Create Client Application Version with a different Eid Create Client Application Version with a different versionnumber Provide a valid Client Application reference Please delete the Installable Client Application in this Application hierarchy
BEEU-00612	Delete Client Application Version failed	INFO	Delete Client Application Version failed due to internal error Client Application Version is not found in the repository Installable Client Application exists in this Application hierarchy	Client Application Version will not be deleted	Please contact Oracle Support for more information Provide a valid Client Application Version Eid Please delete the Installable Client Application in this Application hierarchy
BEEU-00613	Load Client Application Version failed	INFO	Load Client Application Version failed due to internal error Client Application Version is not found in the repository	Client Application Patchset will not be loaded	Make sure that the Client Application Version is uploaded. If it is uploaded contact the System Administrator to resolve the issue. Provide a valid Client Application Version Eid
BEEU-00621	Client Application Patchset cannot be created	INFO	Client Application Patchset cannot be created in the repository due to internal error Client Application Patchset with same patchsetnumber for this Client Application Version exists in the repository Client Application Patchset with same Eid already exists in the repository Client Application Version with Eid passed is not found in the repository	Client Application Patchset will not be created	Please contact Oracle Support for more information Create Client Application Patchset with a different Eid Create Client Application Patchset with a different patchsetnumber Provide a valid Client Application Version reference

Table 3–7 (Cont.) Device Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00622	Delete Client Application Patchset failed	INFO	Delete Client Application Patchset failed due to internal error Client Application Patchset is not found in the repository Installable Client Application exists in this Application hierarchy	Client Application Patchset will not be deleted	Please contact Oracle Support for more information Provide a valid Client Application Patchset Eid Please delete the Installable Client Application in this Application hierarchy
BEEU-00623	Load Client Application Patchset failed	INFO	Load Client Application Patchset failed due to internal error Client Application Patchset is not found in the repository	Client Application Patchset will not be loaded	Make sure that the Client Application Patchset is uploaded. If it is uploaded contact the System Administrator to resolve the issue. Provide a valid Client Application Patchset Eid
BEEU-00631	Client Application Module cannot be created	INFO	Client Application Module cannot be created in the repository due to internal error Client Application Module with same name and destination folder for this Client Application Patchset exists in the repository Client Application Module with same Eid already exists in the repository Client Application Patchset with Eid passed is not found in the repository New ClientApplicationModules cannot be introduced between patchsets	Client Application Module will not be created	Please contact Oracle Support for more information Create Client Application Module with a different Eid Create Client Application Patchset with a different patchsetnumber Provide a valid Client Application Patchset reference Introduce a new Version or remove the new module
BEEU-00632	Delete Client Application Module failed	INFO	Delete Client Application Module failed due to internal error Client Application Module is not found in the repository	Client Application Module will not be deleted	Please contact Oracle Support for more information Provide a valid Client Application Module Eid
BEEU-00633	Load Client Application Module failed	INFO	Load Client Application Module failed due to internal error Client Application Module is not found in the repository	Client Application Module will not be loaded	Make sure that the Client Application Module is uploaded. If it is uploaded contact the System Administrator to resolve the issue. Provide a valid Client Application Module Eid

Table 3–7 (Cont.) Device Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00641	Create Device failed	INFO	Create Device failed due to internal error Device with same device id already exists in the repository Device with same device Eid already exists in the repository	Device will not be created in the repository	Please contact Oracle Support for more information Assign a different device id and try again Assign a different Eid and try again.
BEEU-00642	Update Device failed	INFO	Update device failed due to internal errors State of the device is outdated Device does not exist in the repository	Device will not be updated with the new values	Contact the system administrator Retry the operation with always update/delete option or reload the state of the device. Verify the Device identifier and try again
BEEU-00643	Delete device failed	INFO	Delete device failed due to internal errors State of the device is outdated Device does not exist in the repository Device Command exists for this device.	Device will not be deleted	Contact the system admin Retry the operation with always update/delete option or reload the state of the device. Verify the Device identifier and try again Delete all DeviceCommands for this device and try deleting this device.
BEEU-00644	Load device failed	INFO	Load device failed due to internal errors Device does not exist in the repository	Device will not be loaded	Check the device details and try again. If the problem still persist contact the system administrator Verify the Device identifier and try again
BEEU-00651	Create Device Type failed	INFO	Create Device Type failed due to internal error Device Type with same name already exists in the repository Device Type with same os, processor and device class already exists in the repository Device Type with same manufacturer, model, software version and devinfdtd version already exists in the repository Device Type with same Eid already exists in the repository Device Profile passed in with the Device Type is invalid	Device Type will not be created in the repository	Please contact Oracle Support for more information Assign a different name for the Device Type and try again Enter a different value for either or all of os, processor, device class and try again. Enter a different value for either or all of manufacturer, model, software version, devinfdtd version and try again. Assign a different Eid and try again. Try again with a valid Device Profile

Table 3–7 (Cont.) Device Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00652	Update Device Type failed	INFO	Update Device Type failed due to internal errors State of the Device Type is outdated Device Type Eid passed is not found in the repository Device Type with same os, processor and device class already exists in the repository Device Type with same manufacturer, model, software version and devinfddt version already exists in the repository	Device Type will not be updated with the new values	Contact the system administrator Either try with always update/delete option or reload the state of the Device Type and try updating Check the Eid of the Device Type and try again Enter a different value for either or all of os, processor, device class and try again. Enter a different value for either or all of manufacturer, model, software version, devinfddt version and try again.
BEEU-00653	Delete Device Type failed	INFO	Delete Device Type failed due to internal errors State of the Device Type is outdated Device Type Eid passed is not found in the repository	Device Type will not be deleted	Contact the system admin Either try with always update/delete option or reload the state of the Device Type and try updating Check the Eid of the Device Type and try again
BEEU-00654	Load Device Type failed	INFO	Load Device Type failed due to internal errors Device Type Eid passed is not found in the repository	Device Type will not be loaded	Check the Device Type details and try again. If the problem still persist contact the system administrator Check the Eid of the Device Type and try again
BEEU-00661	Create Device Profile failed	INFO	Create Device Profile failed due to internal error Device Profile with same name already exists in the repository Device Profile with same Eid already exists in the repository	Device Profile will not be created in the repository	Please contact Oracle Support for more information Assign a different name for the Device Profile and try again Assign a different Eid and try again.
BEEU-00662	Update Device Profile failed	INFO	Update Device Profile failed due to internal errors State of the Device Profile is outdated Device Profile Eid passed is not found in the repository Preference Profile passed in with the Device Profile is invalid	Device Profile will not be updated with the new values	Contact the system administrator Either try with always update/delete option or reload the state of the Device Profile and try updating Check the Eid of the Device Profile and try again Try again with a valid Preference Profile

Table 3–7 (Cont.) Device Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00663	Delete Device Profile failed	INFO	Delete Device Profile failed due to internal errors State of the Device Profile is outdated Device Profile Eid passed is not found in the repository Device Type referring to this device profile exists	Device Type will not be deleted	Contact the system admin Either try with always update/delete option or reload the state of the Device Profile and try updating Check the Eid of the Device Profile and try again Delete the Device Type referring to this Device Profile and try deleting this Device Profile
BEEU-00664	Load Device Profile failed	INFO	Load Device Profile failed due to internal errors Device Profile Eid passed is not found in the repository	Device Profile will not be loaded	Check the Device Profile details and try again. If the problem still persist contact the system administrator Check the Eid of the Device Profile and try again
BEEU-00671	Create Installable Client Application failed	INFO	Installable Client Application cannot be created in the repository due to internal error Installable Client Application with same Eid already exists in the repository Client Application to which this Installable Client Application belongs to is invalid	Installable Client Application will not be created	Please contact Oracle Support for more information Create Installable Client Application with a different Eid Create Installable Client Application with a valid ClientApplication
BEEU-00672	Update Installable Client Application failed	INFO	Update Installable Client Application failed due to internal errors State of the Installable Client Application is outdated Installable Client Application Eid passed is not found in the repository	Installable Client Application will not be updated with the new values	Contact the system administrator Either try with always update/delete option or reload the state of the Installable Client Application and try updating Check the Eid of the Installable Client Application and try again
BEEU-00673	Delete Installable Client Application failed	INFO	Delete Installable Client Application failed due to internal errors State of the Installable Client Application is outdated Installable Client Application Eid passed is not found in the repository	Installable Client Application will not be loaded	Check the Installable Client Application details and try again. If the problem still persist contact the system administrator Either try with always update/delete option or reload the state of the Installable Client Application and try updating Check the Eid of the Installable Client Application and try again

Table 3–7 (Cont.) Device Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00674	Load Installable Client Application failed	INFO	Load Installable Client Application failed due to internal errors Installable Client Application Eid passed is not found in the repository	Installable Client Application will not be loaded	Check the Installable Client Application details and try again. If the problem still persist contact the system administrator Check the Eid of the Installable Client Application and try again
BEEU-00681	Create Device Command Failed	INFO	Create Device Command Failed due to internal errors Device does not exist in the repository Device Command with the same Eid already exists in the repository The action of the device command you are creating is the same as the most recent device command that is to be executed. Cannot create any device command if the most recent device command is a WIPEOUT command.	Device Command will not be created!	Please contact system administrator Verify the Device identifier and try again Create Device Command with different Eid Please retry the operation with a different device command action. Either the WIPEOUT command needs to be deleted or needs to be executed by the device.
BEEZ-00691	The user is not authorized to perform this operation.	SEVERE	The current user doesn't have enough privileges and/or access types.	This operation cannot be performed.	Please retry this operation with a user who has more privileges and/or access types.
BEES-00692	Internal service error.	SEVERE	Could not process action due to unexpected server error.	Operation cannot be completed.	Please contact Oracle support.

Diagnosability Error Codes

The following table lists error codes for Diagnosability.

Table 3–8 *Diagnosability*

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-03601	Get log record error.	WARNING	Log viewer client unable to connect to the server.	Unable to get the log record from the server.	Contact Oracle Support for more information.
BEEU-03602	Query log record error.	WARNING	LogQueryException caught. Exception message: {0}, host: {1}, oracle-home: {2}. IOException caught. Exception message: {0}. host: {1} oracle home: {2} request port: {3} MalformedURLException caught. Exception message: {0}. host: {1} oracle home: {2} request port: {3}	Unable to query the log record.	Contact Oracle Support for more information.

Discussions Error Codes

The following table lists error codes for Discussions.

Table 3–9 *Discussions*

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-06500	Invalid parameter.	WARNING	Parent discussion form is invalid. Topic cannot be clipped at the discussions message specified. Topic cannot merge with itself. Specified updater is of the wrong type.	The operation will not be performed.	Choose a valid parent discussion forum. Specify a message to clip that is not the first message in the topic and re-try the operation. Choose a source that is different than the target for the merge and re-try the operation. Specified updater is of the wrong type.
BEEU-06501	Unsupported operation for DiscussThisForums.	WARNING	The specified operation is not supported by DiscussThisForums.	The operation cannot be performed.	The specified operation cannot be performed on a DiscussThisForum.
BEEU-06502	Invalid message body content type.	WARNING	The specified message body content type is not supported for a Discussions Message.	The operation cannot be performed.	Discussions Messages only support message bodies of type simple or multipart-related.

Email Service Error Codes

The following table lists error codes for Email Service.

Table 3–10 Email Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-01201	Database error occurred.	SEVERE	Database error occurred.	Database error occurred.	Please contact Oracle Support for more information.
BEEU-01201	Mail VMS not present	INFO	No valid Virtual Mail Servers matched for client address.	Client connection will be rejected.	Contact an administrator if you still have this problem.
BEEU-01202	Invalid mail transaction state	WARNING	Transaction not closed Transaction not open	Mail reception will fail	Please contact an administrator
BEEU-01203	Mail address parsing error	INFO	Session ID: ({0}) Error Parsing {1} command "{2}"	Mail command will be rejected	Please check syntax of mail address
BEEU-01204	Unable to submit mail	INFO	Unable to submit mail due to write failure to file	Mail will not be accepted	Please contact an administrator
BEEU-01205	Failed to commit transaction	INFO	May be due to denied access	Mail will not be accepted	Please contact an administrator
BEEU-01206	Authentication error	WARNING	Processing error during authentication	Mail command will fail	Please contact an administrator
BEEU-01207	Failure to write body	FINE	[SessionID: {0}] Unexpected IOException from server during body write, likely a timeout	Mail could not be sent	Please contact an administrator
BEEU-01208	Connection to smtp server refused	WARNING	Delivery SessionID: {0} connection to SMTP server {1} refused	Since this is the last server in our list {0}, ticket cannot be delivered at this time	Please contact an administrator
BEEU-01209	Failed to resolve MX address	SEVERE	Delivery SessionID: {0} unable to convert MX Address {1} into InetAddress. There may be a problem with the local BIND server.	Since this is the last server in our list {0}, ticket cannot be delivered at this time	Please contact an administrator
BEEU-01210	EOF from server	FINE	[SessionID: {0}] Unexpected EOF from server	Mail could not be sent	Please contact an administrator
BEEU-01211	Connection to mail server refused	FINE	Unable to connect to mail server {0}	Server may fail to send mail	Please contact an administrator
BEEU-01212	Failed to resolve mail server	FINE	Unable to resolve mail server {0}	May fail to deliver mail	Please contact an administrator
BEEU-01213	Mail server timed out	FINE	[SessionID: {0}] Mail server timed out	Could not open connection. Could not send mail	Please contact an administrator
BEEU-01214	Failed to create vms evaluator	WARNING	Exception Caught during creating vms evaluator rule engine	This will cause the server to reject all the incoming connections	Please contact an administrator
BEEU-01215	Failed to evaluate recipient	SEVERE	Exception encountered when evaluating recipient address {0} for Virtual Mail Server {1}	Mail command will be rejected	Please contact an administrator

Table 3–10 (Cont.) Email Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-01216	Failed to evaluate sender	SEVERE	Exception encountered when evaluating sender address {0} for Virtual Mail Server {1}	Mail command will be rejected	Please contact an administrator
BEEU-01217	Failed to set rule engine for recipient	INFO	Exception Caught during setting rule engine for recipient	Blank recipient rule engine will cause the server to reject all recipients	Please contact an administrator
BEEU-01218	Failed to set rule engine for sender	INFO	Exception Caught during setting rule engine for sender	Blank sender rule engine will cause the server to reject all senders	Please contact an administrator
BEEU-01219	STARTTLS not supported on the remote mail server	WARNING	STARTTLS not supported on the remote mail server {0}	Could not send mail using TLS	Please make sure remote mail server supports STARTTLS
BEEU-01220	STARTTLS command to the remote mail server fails	WARNING	STARTTLS command fails with error {0}	Could not send mail using TLS	Please check the error
BEEU-01231	Failed to fetch messages that need to be retried or recovered	FINE	This happens due to a database error	Retry or Recovery of messages will be delayed	Please investigate the database error
BEEU-01232	Unable to assemble rule engine	SEVERE	This happens due to error in loading rule engine	Blank RulesEngine will cause all mail to be parked until the rules are fixed	Please check data in the config
BEEU-01233	Unable to process retry or recovered message	INFO	Failed to process retry or recovered message {0}. This happens due to a database error	Retry or recovered message will not be delivered	Please investigate the database error
BEEU-01234	Unable to send draft message	WARNING	Unable to send draft message {0}. This happens due to a database error	The draft message could not be sent	Please investigate the database error
BEEU-01235	Failed to update message state in the database	INFO	This happens due to a database error	Message processing will be incomplete	Please investigate the database error
BEEU-01236	Failed to resolve recipients of a message	FINEST	This can happen due to database error	Message delivery to unresolved recipients will fail	Please investigate the database error
BEEU-01237	Local delivery of a message failed	WARNING	This happens due to a database error	Local recipients fail to receive the message	Please investigate the database error
BEEU-01238	Checkpointing remote recipients failed	WARNING	This happens due to failure to update information about recipients in the database	State of recipients in the database will be incorrect	Please investigate the database error
BEEU-01239	Submission processing of message fails	WARNING	Submission processing of message {0} raised throwable	Message processing fails	Please investigate the throwable
BEEU-01240	Connecting to DNS server fails	FINE	Connecting to DNS server fails due to unknown host	Remote mail delivery of a message will be impacted	Please check DNS servers

Table 3–10 (Cont.) Email Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-01241	Resolving domain fails	WARNING	Resolving domain fails due to invalid host name	Remote mail delivery will be impacted	Please check host name (domain)
BEEU-01242	Error during resolution	WARNING	Error during domain resolution due to an exception	Remote mail delivery may be impacted	Please check the exception
BEEU-01291	You do not have the required access.	SEVERE	You do not have the required access.	You do not have the required access.	Please contact Oracle Support for more information.
BEEU-01292	The specified entity does not exist.	SEVERE	The specified entity does not exist.	The specified entity does not exist.	Please contact Oracle Support for more information.
BEEU-01293	Quota overflow error occurred.	WARNING	Quota overflow error occurred.	Quota overflow error occurred.	Please contact Oracle Support for more information.

Foundation Services Error Codes

The following table lists error codes for Foundation Services.

Table 3–11 Foundation Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-00300	An error has occurred retrieving the error code from the database.	SEVERE	The error code repository refers to an invalid or non-existent error code.	This error code cannot be properly displayed.	Please contact your administrator.
BEES-00302	Service is not available.	SEVERE	See the associated exception for details.	Cannot access the service.	Please contact Oracle Support for more information.
BEES-00304	Service instance failed to init.	SEVERE	See the associated exception for details.	Cannot access the service instance.	Please contact Oracle Support for more information.
BEES-00306	Batch delete partially succeeded.	WARNING	Service side failed to delete some entities.	Some entities in the batch is not deleted.	Retry for those failed entities.
BEES-00308	Batch purge partially succeeded.	WARNING	Service side failed to purge some entities.	Some entities in the batch is not purged.	Retry for those failed entities.

Instant Messaging Service Error Codes

The following table lists error codes for Instant Messaging Service.

Table 3–12 Instant Messaging Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-01301	IM service encountered an internal error.	WARNING	See stack trace for details.	Instant Messaging could fail.	Contact system administrator or see stack trace for further action.
BEEZ-01302	Login failure	SEVERE	User doesn't have sufficient privileges to login to Instant Messaging.	Login failed.	Contact your system administrator.
BEEZ-01303	Access is denied.	SEVERE	The client does not have appropriate privileges.	Listing of conversation transcript failed.	Please contact an administrator if you still have this problem.

Table 3–12 (Cont.) Instant Messaging Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEZ-01304	Access is denied.	SEVERE	The client does not have appropriate privileges.	Failed to delete conversation transcript.	Please contact an administrator if you still have this problem.
BEEZ-01305	Access is denied.	SEVERE	The client does not have appropriate privileges.	Listing of offline messages failed.	Please contact an administrator if you still have this problem.
BEEZ-01306	Access is denied.	SEVERE	The client does not have appropriate privileges.	Failed to delete offline message.	Please contact an administrator if you still have this problem.
BEEZ-01307	User is not provisioned to use Instant Messaging.	SEVERE	User is not provisioned to use Instant Messaging.		
BEES-01311	Cannot store offline message.	SEVERE	See stack trace for details.	Unable to handle this offline message, it will be lost.	Contact system administrator or see stack trace for further action.
BEES-01312	Fetching offline messages for the user failed.	SEVERE	See stack trace for details.	You will not be able to see offline messages.	Contact system administrator or see stack trace for further action.
BEES-01313	Fetching conversation transcripts for the user failed.	SEVERE	See stack trace for details.	You will not be able to see conversation transcripts.	Contact system administrator or see stack trace for further action.
BEES-01314	Error loading OnlineInstantMessageSet.	SEVERE	Requested entity does not exist.	User will not be able to see instant messages.	Contact Oracle Support.
BEES-01315	Could not send message to the destination.	SEVERE	Bus connection might be down.	InstantMessaging will not work.	Restart Beehive/Omb.
BEES-01316	Error updating the InstantMessageReceptacle.	SEVERE	Some problem accessing the DB.	User may not be able to login and use instant messaging.	Retry. Contact Oracle Support if the problem persists.
BEES-01317	Error updating the InstantMessageReceptacle.	WARNING	Bus connection might be down.	Other service instances may not come to know of this logout or if the user was coming online with same resource again, the earlier instance may not get logged out.	Restart Beehive/Omb.
BEES-01318	Error updating the InstantMessageReceptacle.	SEVERE	Some problem accessing the DB.	User may not be able to login and use instant messaging.	Retry. Contact Oracle Support if the problem persists.
BEES-01319	Error updating the InstantMessageReceptacle.	SEVERE	Some problem accessing the DB.	User may not be able to login and use instant messaging.	Retry. Contact Oracle Support if the problem persists.
BEES-01320	Error loading InstantMessageReceptacle.	SEVERE	Some problem accessing the DB.	InstantMessaging may not work properly.	Retry. Contact Oracle Support if the problem persists.
BEES-01321	Error loading InstantMessageReceptacle.	SEVERE	Requested entity does not exist.	InstantMessaging may not work properly.	Contact system administrator or see stack trace for further action.

Table 3–12 (Cont.) Instant Messaging Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-01322	Error deleting instant message transcript.	SEVERE	Some problem accessing the DB.	User will not be able to delete his instant message transcript.	Contact system administrator or see stack trace for further action.
BEES-01323	Error deleting offline instant message.	SEVERE	Some problem accessing the DB.	User will not be able to delete his offline instant message.	Contact system administrator or see stack trace for further action.
BEES-01324	Could not fetch archive folder.	SEVERE	Some problem accessing the DB.	Server side archiving may not work.	Contact system administrator or see stack trace for further action.
BEES-01325	Error loading offline instant message.	SEVERE	Some problem accessing the DB.	InstantMessaging may not work properly.	Retry. Contact Oracle Support if the problem persists.
BEES-01326	Error loading offline instant message.	SEVERE	Requested entity does not exist.	InstantMessaging may not work properly.	Contact system administrator or see stack trace for further action.
BEES-01327	IMService could not get initialized properly.	SEVERE	Could not activate service command channel.	IMService will not work properly.	Restart IMService.
BEES-01341	Error updating the InstantMessageReceptacle.	SEVERE	User is not provisioned to use Instant Messaging.	User may not be able to login and use instant messaging.	Contact system administrator or see stack trace for further action.
BEES-01342	Error updating the InstantMessageReceptacle.	SEVERE	Resource value is null. User can't login with empty resource.	User may not be able to login and use instant messaging.	Provide a non null resource value.

Message Delivery Service Error Codes

The following table lists error codes for Message Delivery Service.

Table 3–13 Message Delivery Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-02000	Message Delivery Service failed to initialize.	INTERNAL_ERROR	Unexpected failure during initialization. Unexpected failure during initialization of {0} delivery handler.	Message Delivery may not be fully available.	Please contact Oracle Support.
BEES-02001	Unable to login to remote service.	WARNING	Invalid username/password credentials.	Message Delivery can not proceed without valid credentials.	Define correct username/password credentials and try again.
BEEP-02070	SMPP ENQUIRE_LINK PDU time longer than expected.	CONFIG	SMPP ENQUIRE_LINK PDU time longer than expected.	SMPP Performance could be degraded due to network latency.	Administrator check network settings and correct as required.

Table 3–13 (Cont.) Message Delivery Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEP-02071	XMS delivery time longer than expected.	CONFIG	XMS delivery time longer than expected.	XMS Performance could be degraded due to network latency.	Administrator check network settings and correct as required.
BEER-02080	SMPP connection closed unexpectedly.	WARNING	SMPP connection closed unexpectedly.	SMPP connection should auto-reconnect.	Administrator check network settings and correct as required.
BEES-02099	Internal server error.	INTERNAL_ERROR	Unable to process delivery request.	Delivery request can not be completed.	Please contact Oracle Support.

Mobile DM Server Error Codes

The following table lists error codes for Mobile DM Server.

Table 3–14 Mobile DM Server

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-02500	Mobile DM Server failed to initialize.	SEVERE	Service Instance is not initialized yet.	Mobile DM Server is not available.	Try again in a few minutes. If still fails, contact Oracle Support.
BEEZ-02501	Could not login to MobileDM Server.	WARNING	Invalid username/password combination.	Client cannot access the Mobile DM Server.	Type correct username/password combination and try again.
BEEZ-02502	Cannot proceed, as user is not authenticated.	WARNING	User cannot execute this command unless authenticated.	Command cannot be executed unless user is authenticated.	User must authenticate first before proceeding.
BEEZ-02503	Cannot proceed, as device is invalid.	WARNING	User cannot execute this command as device is invalid.	Command cannot be executed unless user re-authenticate with valid deviceID.	User must authenticate first before proceeding.
BEEZ-02504	Cannot proceed, as user context failed to initialize.	SEVERE	User context failed to be copied. User context failed to be re-attached.	Command cannot be executed unless user is authenticated.	Please contact system administrator.
BEED-02510	MobileDM Server cannot process this request.	WARNING	Invalid syntax for command {0}.	Command cannot be processed.	Correct the syntax and try again.
BEED-02511	Module not found.	WARNING	Invalid module ID sent on this command.	Module cannot be downloaded.	Check the module ID and re-send the download command.
BEED-02512	Too many invalid attempts from this client.	WARNING	Client send too many invalid command attempts.	Session is being closed and invalidated.	System administrator should verify server logs and potentially block offending client.
BEES-02591	Cannot fulfill Client request at this time.	SEVERE	Server capacity reached.	No new clients can be served at this time.	Administrator must increase the Mobile DM Server's capacity to allow new clients to be served.
BEES-02599	Internal server error.	SEVERE	Could not process command due to unexpected server error.	Operation cannot be completed.	Please contact Oracle Support for more information.

Mobile Data Sync Server Error Codes

The following table lists error codes for Mobile Data Sync Server.

Table 3–15 *Mobile Data Sync Server*

Message ID	Display Name	Severity	Cause	Effect	Action
BEEZ-02200	Oracle Mobile Data Sync Service failed to initialize.	INTERNAL_ERROR	This could be a deployment issue.	Oracle Mobile Data Sync Service will not be available.	Correct any error in the stacktrace and restart Oracle Mobile Data Sync Service. Contact Oracle Support if error persists.
BEEZ-02201	Could not log in to Oracle Mobile Data Sync Service.	WARNING	Invalid username/password combination.	The synchronization between the client and server would fail.	Type correct username/password combination and try again.
BEEZ-02202	Cannot proceed, because user is not authenticated.	WARNING	User cannot execute this command unless authenticated.	Command cannot be executed unless user is authenticated.	User must authenticate first before proceeding.
BEED-02210	Oracle Mobile Data Sync Service failed to parse or render the SYNCML message.	SEVERE	The client SYNCML message could be corrupted or the server could have a bug.	The synchronization between the client and server would fail.	Turn the SYNCML message log on and inspect the incoming message.
BEED-02211	Oracle Mobile Data Sync Service failed to parse or render the SYNCML messages in WBXML format.	SEVERE	The client WBXML message could be corrupted or the server could have a bug.	The synchronization between the client and server would fail.	Turn the SYNCML message log on and inspect the incoming message.
BEER-02280	Metadata persistence error.	SEVERE	Oracle Mobile Data Sync Service has failed when saving or accessing metadata. The database could be down or the database access layer could have an issue.	Oracle Mobile Data Sync Service will not be available.	Contact your database administrator. If the database is up and normal, contact Oracle Support
BEER-02281	An error occurred at the Oracle Mobile Data Sync Service transport layer.	SEVERE	The network connection between the client and the server could be broken. This could be a temporary network error.	The synchronization between the client and server would fail.	Correct the network error and retry the sync.
BEES-02290	Cannot fulfill client request at this time.	SEVERE	Server capacity reached.	No new clients can be served at this time.	Administrator must increase the Oracle Mobile Data Sync Service's capacity to allow new clients to be served.

Table 3–15 (Cont.) Mobile Data Sync Server

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-02291	The data synchronization protocol handler experienced an error.	SEVERE	The data synchronization protocol handler has failed when processing the client request.	The synchronization between the client and server would fail.	Contact Oracle Support for more information.
BEES-02292	Oracle Mobile Data Sync Service has failed when interacting with a back-end service.	SEVERE	The back-end service could be down. See stack trace for details.	The synchronization of the affected data store would fail.	Make sure the back-end is up and retry the sync.
BEES-02299	Oracle Mobile Data Sync Service encountered an internal error.	INTERNAL_ERROR	Can not proceed due to unexpected error.	Sync could fail.	Contact Oracle Support for more information.

Mobile Mail Server Error Codes

The following table lists error codes for Mobile Mail Server.

Table 3–16 Mobile Mail Server

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-02300	Mobile Mail Server failed to initialize.	INTERNAL_ERROR	Unexpected error.	Mobile Mail Server will not be available.	Please, contact Oracle support.
BEEZ-02301	Could not login to Mobile Mail Server.	WARNING	Invalid username/password combination.	Client cannot access Mobile Mail Server.	Verify username and password, and try again.
BEEZ-02302	Invalid state.	WARNING	User is in invalid state to do the operation.	Command is not executed.	Try again with the valid state {0}.
BEEZ-02303	User authorization process failure.	WARNING	Failed to associate user {0} to device {1}.	User will be unable to use Mobile Mail.	Try to logout and login back. If problem persists, please contact your system administrator.
BEED-02310	Invalid Mobile Mail request.	WARNING	Client has sent an invalid request.	Mobile Mail Server will not process the request.	Please, verify your Mobile Mail Client.
BEED-02311	Mobile Mail Server cannot process the command.	WARNING	Invalid syntax for command {0} from device {1}.	Command cannot be processed.	Mobile Mail client must correct the syntax and try again.
BEER-02380	Data streaming error.	WARNING	Data streaming error for device {0}.	Device end-to-end connection will be closed.	Device {0} needs to reconnect and reauthenticate.
BEER-02381	Unable to connect to Beehive Mail server.	SEVERE	Unexpected error.	Device end-to-end connection will be closed.	Check Beehive Mail server status, if the problem persists talk to your system administrator.
BEES-02390	Cannot fulfill Client request at this time.	WARNING	Server capacity reached.	No new clients can be served at this time.	Administrator must increase the "Service Name" Server's capacity to allow new clients to be served.
BEES-02399	Internal server error.	INTERNAL_ERROR	Could not process command due to an internal server error.	Command cannot be processed.	Please, contact the administrator for more details.

Mobile Push Server Error Codes

The following table lists error codes for Mobile Push Server.

Table 3–17 Mobile Push Server

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-02400	Mobile Push Server failed to initialize.	INTERNAL_ERROR	Unexpected error.	Mobile Push Server will not be available.	Please, contact Oracle support.
BEEZ-02401	Could not login to Mobile Push Server.	WARNING	Invalid username/password combination.	Client cannot access Mobile Push Server.	Verify username and password, and try again.
BEEZ-02402	The operation requires the user to be authenticated.	WARNING	User cannot execute this command unless is authenticated.	Command is not executed.	User must authenticate first and try again.
BEEZ-02403	User authorization process failure.	WARNING	Failed to associate user {0} to device {1}.	User might not receive any notification.	Try to logout and login back. If problem persists, please contact your system administrator.
BEED-02410	Invalid Push request.	WARNING	Client has sent an invalid request.	Mobile Push Server will not respond to the request.	Please, verify your Push Client.
BEED-02411	Mobile Push Server cannot process this command.	WARNING	Invalid syntax for command {0}.	Command cannot be processed.	Push client must correct the syntax and try again.
BEEU-02430	Too many invalid commands.	WARNING	User {0} has sent many invalid commands through device {1}.	User connection is dropped.	Please, verify your data and try again.
BEER-02480	Communication channel is closed.	WARNING	You have a network problem or BTI service has failed to start.	Communication will not be established.	Retry, if problem persists, contact Oracle Support.
BEER-02481	Could not connect to Push Client.	WARNING	Communication channel to Push Client on device {0} is not available.	Push Client will not receive any data.	Please check your device, if the problem persists talk to your system administrator.
BEES-02491	Subscription failure.	SEVERE	Could not find event producer to application {0}.	User {0} will not receive any events on device {1}.	Try again, if problem persists contact your system administrator.
BEES-02492	Failed to initialize subscription manager.	SEVERE	Failed to associate an event listener to the user {0} and device {1}.	Push Server will not notify client about events.	Please, logout and try to login again. If problem persists, please contact your system administrator.
BEES-02499	Internal server error.	INTERNAL_ERROR	Could not process command due to an internal server error.	Command cannot be processed.	Please, contact the administrator for more details.

Notification Service Error Codes

The following table lists error codes for Notification Service.

Table 3–18 Notification Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEES-01900	Notification service failed to initialize.	SEVERE	See stack trace for details.	Notification service will not be available.	Please contact Oracle Support.
BEEED-01910	Notification schema xml parsing failed.	WARNING	Schema xml parsing caused an exception.	Schema will not be created.	Recreate Xml and try again.
BEEED-01911	Notification properties xml parsing failed.	WARNING	Exception was thrown while converting to xml	Notification will not be created.	Recreate notification properties and try again.
BEEED-01912	Invalid notification content error	WARNING	Notification content argument is incorrect	Notification will not be created.	Recreate notification content using SimpleContent and try again.
BEEU-01930	Notification schema creation failed.	WARNING	Schema by this name already exists.	Schema will not be created.	Change the name of the schema or update existing schema.
BEEU-01931	Schema attributes creation failed.	WARNING	Exception was thrown while creating attribute definitions	Schema will not be created.	Recreate schema attributes and try again.
BEEU-01932	An error occurred in the DB.	WARNING	See stack trace for details.		
BEEU-01933	Entity was not found in the system.	WARNING	See stack trace for details.		
BEEU-01934	Access control check failed.	WARNING	Insufficient privileges or access type.	Operation was not completed.	User needs more privileges.
BEEU-01935	Operation to update/delete entity failed.	WARNING	Invalid state of the object.	Operation was not completed.	Reload entity and then retry.
BEEU-01936	Notification schema create failed.	WARNING	See stack trace for details.	Schema will not be {0}.	Correct the error and retry.
BEEU-01937	Notification schema load failed.	WARNING	See stack trace for details.	Schema will not be {0}.	Correct the error and retry.
BEEU-01938	Notification schema update failed.	WARNING	See stack trace for details.	Schema will not be {0}.	Correct the error and retry.
BEEU-01939	Notification schema delete failed.	WARNING	See stack trace for details.	Schema will not be {0}.	Correct the error and retry.
BEEU-01940	Notification schema list failed.	WARNING	See stack trace for details.	Schema will not be {0}.	Correct the error and retry.
BEEU-01941	Notification create failed.	WARNING	See stack trace for details.	Notification will not be {0}.	Correct the error and retry.
BEEU-01942	Notification load failed.	WARNING	See stack trace for details.	Notification will not be {0}.	Correct the error and retry.
BEEU-01943	Notification update failed.	WARNING	See stack trace for details.	Notification will not be {0}.	Correct the error and retry.
BEEU-01944	Notification delete failed.	WARNING	See stack trace for details.	Notification will not be {0}.	Correct the error and retry.
BEEU-01945	Notification list failed.	WARNING	See stack trace for details.	Notification will not be {0}.	Correct the error and retry.

Table 3–18 (Cont.) Notification Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-01946	Notification create failed.	WARNING	Unable to overwrite delivery channel preference.	Notification will not be {0}.	Remove delivery channels try again.
BEER-01980	An error occurred in the DB.	WARNING	An Exception occurred in the DB.	Operation was not completed.	
BEES-01999	Internal service error.	SEVERE	Could not process action due to unexpected server error.	Operation cannot be completed.	Please contact Oracle Support.

Policy Management Error Codes

The following table lists error codes for Policy Management.

Table 3–19 Policy Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00901	Failed to create the policy schema	INFO	Policy schema with the same name already exists	Failed to create the policy schema {0}	
BEEU-00902	Failed to update the policy schema	INFO	A rule definition refers to this attribute definition Policy schema with the same name already exists Attribute definition {0} is not present in the schema Rule definition {0} does not exist Policy schema does not exist	Failed to update the policy schema {0}	
BEEU-00903	Failed to delete the policy schema	INFO	Policy schema does not exist Cannot delete policy schema as some policy template refers to this schema	Failed to delete the policy schema {0}	
BEEU-00904	Failed to load the policy schema	INFO	Policy schema does not exist	Failed to load the policy schema {0}	
BEEU-00911	Failed to create the policy template	INFO	Rule definition is already imported into the template. A Policy template referring to same policy schema at the container already present Policy template cannot be created other than at scope levels	Failed to create the policy template {0}	

Table 3–19 (Cont.) Policy Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00912	Failed to update the policy template	INFO	Rule definition is already imported into the template. Policy template does not exist A Policy template referring to same policy schema at the container already present Cannot delete template as some policy refers to this template A policy has rule instance for this same template rule definition {0} Rule {0} is not present in policy template A policy template at the lower scope also refers to the same rule definition {0} Policy template at sub-container exist	Failed to update the policy template {0}	
BEEU-00913	Failed to delete the policy template	INFO	Policy template does not exist Cannot delete template as some policy refers to this template	Failed to delete the policy template {0}	
BEEU-00914	Failed to load the policy template	INFO	Policy template does not exist	Failed to load the policy template {0}	
BEEU-00921	Failed to create the policy	INFO	Rule is already imported from the template to the policy A policy with the same name already present in the container Policy cannot be created other than at scope levels Another policy also refers to the same policy template at the given container	Failed to create the policy {0}	
BEEU-00922	Failed to update the policy	INFO	Rule is already imported from the template to the policy A policy with the same name already present in the container Policy does not exist Rule {0} does not exist Rule {0} is not present in policy template Attribute application value is not present for attribute definition {0} Cannot import the rule {0} since there is no template for the policy Cannot update the rule {0} that is imported	Failed to update the policy {0}	

Table 3–19 (Cont.) Policy Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00923	Failed to delete the policy	INFO	Policy does not exist	Failed to delete the policy {0}	
BEEU-00924	Failed to load the policy	INFO	Policy does not exist	Failed to load the policy {0}	
BEEU-00981	Access denied. Insufficient privileges	INFO	Access denied. Insufficient privileges		

Presence Service Error Codes

The following table lists error codes for Presence Service.

Table 3–20 Presence Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-01801	Internal server error	SEVERE	Internal server error	Cannot service the request	Contact system administrator
BEEU-01802	The entity handle passed in is not supported	WARNING	The given Entity handle is not understood by the Presence service	Cannot service the request	Please use a valid entity handle
BEEU-01803	Database is not up or unreachable	SEVERE	Database is not up or unreachable	Cannot service the request	Check database connectivity and connection parameters
BEEU-01804	The presence handle received is not valid	WARNING	The presence handle received is not valid	Cannot service the request	Check the presence handle being passed
BEEU-01805	The updater implementation passed is not supported by presence service	WARNING	The updater implementation passed is not supported by presence	Cannot service the request	Please use the updater instantiated from PresenceFactory
BEEU-01806	The requested operation is not supported by presence service	SEVERE	The requested operation is not supported by presence service	Cannot service the request	Please use valid methods from PresenceControl
BEEU-01807	Timed out waiting for reply from presence service backend	WARNING	Presence service is down or bus connectivity is lost	Cannot service the request	Check presence service status and/or bus connectivity
BEEU-01808	The requested class is not supported by presence service	WARNING	The requested class is not supported by presence service	Cannot service the request	Please check the parameter passed
BEEU-01809	User is not authorized for the operation	SEVERE	The user doesn't have enough privileges for the operation	Cannot service the request	Please authenticate with appropriate credentials
BEEU-01810	Activity start time or end time or both exceed limits	WARNING	Activity start time or end time or both exceed limit	Cannot service the request	Please have start time that is not too ahead in the future and end time that is in the future
BEEU-01811	Presence object is not loaded for the requested attribute	WARNING	Object has not been loaded with the proper Projection	Cannot service the request	Please use right Projection that covers the requested attribute

RM Service Error Codes

The following table lists error codes for RM Service.

Table 3–21 RM Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-04011	Cannot Recordize artifact with collabid {0}	WARNING	Artifact is already a Record Cannot Recordize artifact of type {0} Invalid Retention Category / Folder id {0}	Cannot Recordize artifact with collabid {0}	
BEEU-04012	Cannot UnRecordize artifact with collabid {0}	WARNING	RM_CANNOT_RECORDIZE_NON_RECORD_CAUSE Cannot UnRecordize artifact of type {0}	Cannot UnRecordize artifact with collabid {0}	
BEER-04031	Cannot Recordize artifact with collabid {0}	SEVERE	Cannot Recordize artifact as URM is not available or responsive Cannot Recordize as URM returned an unknown error.	Cannot Recordize artifact with collabid {0}	Please re-try recordizing the artifact later.
BEER-04032	Cannot UnRecordize artifact with collabid {0}	SEVERE	Cannot UnRecordize artifact as URM is not available or responsive Cannot UnRecordize as URM returned an unknown error.	Cannot UnRecordize artifact with collabid {0}	Please re-try unrecordizing the artifact later.
BEER-04033	Cannot retrieve file plan information	SEVERE	Cannot get file plan as URM is not available or responsive Cannot get file plan as URM returned an unknown error.	Cannot retrieve file plan information	Please re-try retrieving file plan info later.

Search Error Codes

The following table lists error codes for Search.

Table 3–22 Search

Message ID	Display Name	Severity	Cause	Effect	Action
BEEC-03500	SEARCH_QUERY_NOT_SUPPORTED	SEVERE	SEARCH_QUERY_NOT_SUPPORTED_CAUSE	SEARCH_QUERY_NOT_SUPPORTED_EFFECT	SEARCH_QUERY_NOT_SUPPORTED_ACTION

Subscription Service Error Codes

The following table lists error codes for Subscription Service.

Table 3–23 Subscription Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-02101	Subscription service encountered an internal error.	INFO	See stack trace for details.	Operation on Subscription was not completed.	Correct the error and retry.
BEEU-02102	Access control check failed.	INFO	Insufficient privileges or access type.	Operation was not completed.	User needs proper privileges for the operation.
BEEU-02111	Subscription Template exists.	INFO	Subscription Template with the same value already exist.	Operation was not completed.	Fix the failure and try again
BEEU-02112	Subscription Template not found.	INFO	Subscription Template with the specified value cannot be found.	Subscription Template was not loaded.	Fix the failure and try again
BEEU-02113	Subscription Template xml parsing failed.	INFO	Exception was thrown while parsing xml	Subscription Template is not created.	Fix error and try again.
BEEU-02114	Subscription Template creation encountered an error.	INFO	See stack trace for details.	Create on Subscription Template was not completed.	Correct the error and retry.
BEEU-02115	Subscription Template retrieval encountered an error.	INFO	See stack trace for details.	Load on Subscription Template was not completed.	Correct the error and retry.
BEEU-02116	Subscription Templates retrieval encountered an error.	INFO	See stack trace for details.	Loading Subscription Template List was not completed.	Correct the error and retry.
BEES-02117	Internal error while processing the upload.	INFO	See stack trace for details.	Load on Subscription Template was not completed.	Correct the error and retry.
BEES-02118	Unable to use jaxb for unmarshalling.	INFO	See stack trace for details.	Load on Subscription Template was not completed.	Correct the error and retry.
BEEU-02119	Invalid XML content is encountered.	INFO	See stack trace for details.	Load on Subscription Template was not completed.	Correct the error and retry.
BEEU-02120	Faild to update subscription template.	INFO	See stack trace for details.	Operation on Subscription was not completed.	Correct the error and retry.
BEEU-02121	Subscription creation encountered an error.	INFO	See stack trace for details.	Creation on Subscription was not completed.	Correct the error and retry.
BEEU-02122	Subscription update encountered an error.	INFO	See stack trace for details.	Update on Subscription was not completed.	Correct the error and retry.
BEEU-02123	Subscription deletion encountered an error.	INFO	See stack trace for details.	Delete on Subscription was not completed.	Correct the error and retry.
BEEU-02124	Subscription retrieval encountered an error.	INFO	See stack trace for details.	Load on Subscription was not completed.	Correct the error and retry.
BEEU-02125	Subscriptions retrieval encountered an error.	INFO	See stack trace for details.	Loading Subscription List was not completed.	Correct the error and retry.
BEEU-02126	Faild to load source.	INFO	See stack trace for details.	Operation on Subscription was not completed.	Correct the error and retry.

Table 3–23 (Cont.) Subscription Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-02127	Failed to create Subscription Schema.	INFO	See stack trace for details.	Creation on Subscription was not completed.	Correct the error and retry.
BEEU-02128	could not load Subscription Schema by Collab Id.	INFO	See stack trace for details.	Load on Subscription was not completed.	Correct the error and retry.
BEEU-02129	could not load SubscriptionRuleDefinitio n by Collab Id.	INFO	See stack trace for details.	Load on Subscription was not completed.	Correct the error and retry.
BEEU-02130	could not check write Access.	INFO	See stack trace for details.	Creation on Subscription was not completed.	Correct the error and retry.
BEEU-02131	could not load Subscription by Collab Id.	INFO	See stack trace for details.	Load on Subscription was not completed.	Correct the error and retry.
BEEU-02132	could not enable/disable Subscription by Collab Id.	INFO	See stack trace for details.	Load on Subscription was not completed.	Correct the error and retry.
BEEU-02133	could not delete Subscription by Collab Id.	INFO	See stack trace for details.	Delete on Subscription was not completed.	Correct the error and retry.
BEEU-02134	could not undelete Subscription by Collab Id.	INFO	See stack trace for details.	Operation on Subscription was not completed.	Correct the error and retry.
BEEU-02151	User Context returned null cen, throwing CsiException.	INFO	See stack trace for details.	Operation on Subscription was not completed.	Correct the error and retry.
BEEU-02152	PLSQL status is NOT Success.	INFO	See stack trace for details.	Operation on Subscription was not completed.	Correct the error and retry.

System Management Error Codes

The following table lists error codes for System Management.

Table 3–24 System Management

Message ID	Display Name	Severity	Cause	Effect	Action
BEEZ-03800	System Management Access Denied.	SEVERE	The User does not have the required Privilege to do system management.	The User will not be allowed to do system management.	Grant the required Privilege to the User.

Time Management And Coexistence With Exchange Error Codes

The following table lists error codes for Time Management And Coexistence With Exchange.

Table 3–25 Time Management And Coexistence With Exchange

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-01101	The entity could not be found.	FINE	The entity could not be found.	The entity cannot be accessed.	Specify a valid entity.
BEEU-01102	You do not have the required access.	FINE	You do not have the required access.	You do not have the required access.	Contact the owner of the entity to be granted access.
BEEU-01103	The user is not enabled for Time Management.	FINE	The user is not enabled for Time Management.	The user cannot perform Time Management operations.	Contact your administrator to enable the user for Time Management.
BEEU-01104	Optimistic locking failed.	FINE	The entity was modified.	The modifications cannot be applied.	Reload the entity and reapply the modification.
BEEU-01105	An invalid argument was provided.	WARNING	An invalid argument was provided.	The requested operation cannot be performed.	Please notify your system administrator.
BEEU-01106	A configuration parameter is missing.	SEVERE	A configuration parameter cannot be accessed from the Time Management Service's pl/sql.	The requested operation cannot be performed.	Please notify your system administrator.
BEEU-01107	This Time Management entity is locked.	FINE	This Time Management entity is locked.	The entity cannot be updated is this moment.	Retry the operation later, or contact the owner to unlock the workspace.
BEEU-01108	There already is an Entity with similar attributes at the same Scope.	FINE	There already is an Entity with similar attributes at the same Scope.	The operation cannot be performed.	Retry the operation with unique values, or update the conflicting entity.
BEEU-01109	Unable to exceed a limit defined by the Time Management Service.	FINE	The requested operation would cause a Time Management limit to be exceeded.	The requested operation cannot be performed.	Contact the administrator to increase the limit.
BEEU-01110	A scheduling conflict occurred.	FINE	A participant that does not allow double booking is already scheduled at this time.	The calendar event cannot be scheduled at this time.	Remove the conflicting participant, or reschedule the calendar event at another time.
BEEU-01111	A data constraint occurred.	WARNING	Inconsistent data was provided.	The requested operation cannot be performed.	Verify the values and retry the operation.
BEEU-01112	The operation cannot be completed in a timely fashion.	FINE	The resources required for this operation are currently busy.	The requested operation cannot be performed at this time.	Please retry the operation.
BEEU-01113	Unexpected error.	SEVERE	An unexpected internal error occurred.	The requested operation cannot be performed.	Please notify your system administrator.

User Directory Services Error Codes

The following table lists error codes for User Directory Services.

Table 3–26 *User Directory Services*

Message ID	Display Name	Severity	Cause	Effect	Action
BEER-00700	A database operation failed due to a transient or permanent error	SEVERE	A database operation failed due to a transient or permanent error Failed to read data from database object	The attempted operation could not be completed	Try again later. If the problem persists, contact your system administrator
BEED-00701	User creation error during external directory synchronization	WARNING	Duplicate entity The specified principal type is not valid The specified principal was not created Failed to process the external directory synchronization event Invalid enterprise {0} found for synchronization event Invalid organization {0} found for synchronization event The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid An error occurred during user creation	External directory user not created	Specify a valid value
BEER-00701	An external directory operation failed due to a transient or permanent error	SEVERE	Unable to establish a connection to the external directory External directory authentication failed Check the plugin {0} name or path	Failed to start sync for {0}	Try again later. If the problem persists, contact your system administrator Check external directory is available and changelog enabled. Make sure that profile has correct user and group search base, with correct user credentials. Check the plugin name or path Check directory user credentials.

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00701	An error occurred during preference set creation	WARNING	Duplicate entity The specified parent does not exist or cannot be used No such entity The preference set cannot extend from another set with a different name The preference set cannot extend from another set with a different template schema The preference set cannot extend from the one specified because it would cause a cyclic dependency The preference set contains a preference property that cannot be overridden from its super set The preference property cannot be added to the preference set because it is not specified in the template The preference property cannot be added to the preference set because the value is not invalid as per the template The specified preference profile does not exist or cannot be used	The specified preference set was not created	Specify a valid value Specify another value

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEED-00702	User modification error during external directory synchronization	WARNING	No such entity The specified principal type is not valid The specified principal was not created The specified principal was not updated The specified principal was not deleted The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid An error occurred during user update Failed to process the external directory synchronization event	External directory user not updated	Specify a valid value in the external directory
BEEU-00702	An error occurred during preference set update	INFO	The specified parent does not exist or cannot be used A newer version of the specified entity exists in the system No such entity The preference set cannot extend from another set with a different name The preference set cannot extend from another set with a different template schema The preference set cannot extend from the one specified because it would cause a cyclic dependency The preference set contains a preference property that cannot be overridden from its super set	The specified preference set was not updated	Specify a valid value Specify another value Refresh the entity and retry the operation
BEED-00703	User deletion error during external directory synchronization	WARNING	No such entity An error occurred during user deletion Failed to process the external directory synchronization event	External directory user not deleted	Specify a valid value in the external directory

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00703	An error occurred during preference set deletion	WARNING	No such entity A newer version of the specified entity exists in the system UDS_PARENT_NOT_DELETED	The specified preference set was not deleted	Specify a valid value Specify another value Refresh the entity and retry the operation
BEEU-00704	An error occurred during preference set loading	INFO	No such entity	The specified preference set was not loaded	Specify a valid value
BEEU-00705	An error occurred during preference profile creation	WARNING	No such entity Duplicate entity The specified parent does not exist or cannot be used The preference profile already contains the specified preference set A preference profile already exists for the specified entity	The specified preference profile was not created	Specify a valid value Specify another value
BEEU-00706	Group creation error during external directory synchronization	WARNING	Duplicate entity Failed to process the external directory synchronization event Invalid enterprise {0} found for synchronization event Invalid organization {0} found for synchronization event The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid An error occurred during group creation	External directory group not created	Specify a valid value in the external directory
BEEU-00706	An error occurred during preference profile update	INFO	The specified parent does not exist or cannot be used A newer version of the specified entity exists in the system No such entity The preference profile already contains the specified preference set	The specified preference profile was not updated	Specify a valid value Specify another value Refresh the entity and retry the operation

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00707	Group modification error during external directory synchronization	WARNING	No such entity The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid An error occurred during group update Failed to process the external directory synchronization event	External directory group not updated	Specify a valid value in the external directory
BEEU-00707	An error occurred during preference profile deletion	WARNING	No such entity The preference profile is currently active A newer version of the specified entity exists in the system	The specified preference profile was not deleted	Specify a valid value Specify another value Refresh the entity and retry the operation
BEEU-00708	Group deletion error during external directory synchronization	WARNING	No such entity An error occurred during group deletion Failed to process the external directory synchronization event	External directory group not deleted	Specify a valid value in the external directory
BEEU-00708	An error occurred during preference profile loading	INFO	No such entity	The specified preference profile was not loaded	Specify a valid value

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEC-00711	Error during initialization of external directory synchronization	SEVERE	<p>Failed to created the directory object</p> <p>Failed to get default directory object</p> <p>Failed to connect to external directory</p> <p>Failed to get ldap server Invalid</p> <p>Directory type Failed to get the changelog DN from external directory Enterprise not found in directory object User type not found in directory object Group type not found in directory object Invalid group dn {0} found for the external directory Invalid user dn {0} found for the external directory Could not find the default user DN for the external directory Could not find the default group DN for the external directory Could not find the DN {0} in the external directory Invalid user name or password of the external directory user Invalid external directory host or port Invalid external directory host or port User configured in the profile doesnot have permission to access the hierarchy {0} in the external directory Invalid external directory credentials found, correct it and retry Invalid target attribute sub type {0} Invalid target attribute type {0} Invalid source attribute type {0} Invalid target attribute name {0} Target attribute type not found Target attribute type not found Source attribute type not found Target attribute name not found Invalid attribute map for {0} Invalid attribute name {0} in source attribute {1}</p>	External directory synchronization not initialized. Profile validation failed.	<p>Specify a valid value</p> <p>Check external directory is available and changelog enabled. Make sure that profile has correct user and group search base, with correct user credentials. Specify another value Valid principal types are PRIMARY, PROTOCOL and VOICE Provide primary principal mapping Provide group name mapping Provide family name mapping For {0} valid source attribute format is {1} For {0} valid target attribute names are {1}</p>

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEED-00711	Error in processing the external directory synchronization event	WARNING	Failed to initialize external directory synchronization plugin Failed to connect to external directory Failed to get the changelog DN from external directory Failed to get the unique global identifier from external directory Failed to search the external directory Failed to get the directory events from the external directory Failed to get the current change log number from the external directory	Failed to process the external directory synchronization event	Specify a valid value Check external directory is available and changelog enabled. Make sure that profile has correct user and group search base, with correct user credentials. Specify another value
BEEU-00711	An error occurred during principal creation	WARNING	The specified identifier is already in use The specified name is already in use The name was not specified or cannot be used The specified parent does not exist or cannot be used A specified sufficient principal does not exist or cannot be used The specified delegate does not exist or cannot be used The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified principal type is not valid	The specified principal was not created	Specify a valid value Specify another value

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEC-00712	UDS_RECONCILE_INITIALIZATION_ERROR	SEVERE	Failed to get Directory for given profile Profile {0} does not exist. Failed to get service locator. Entry type not supported Entry type is undefined Failed to get entry type Failed to get directory locator of entry Unsupported attribute Invalid Format A database operation failed due to a transient or permanent error Ldap or external directory type is not supported Entry not Created By sync or by current profile Manager or assistant not present in the system, DN:{0} Group member not present in the system, DN:{0} Group not of type static group Error in getting directory locator by collabId The entry cannot be found either in the system or in the external directory Entry absent in ldap server Cannot reconcile deleted entry. Failed to get data from Ldap server. Error in getting entry data by directory locator Error in terminating Ldap connection	Validation operation failed	Specify a valid value Provide correct profile name. Try again later. If the problem persists, contact your system administrator Purge entry and retry Use emailId or any valid Attribute Define entry type In external directory Check external directory is available and changelog enabled. Make sure that profile has correct user and group search base, with correct user credentials. Use valid value Check database Reconcile works only for Static groups Value in external directory not proper Create manager or assistant Check external directory connections.
BEEU-00712	An error occurred during principal update	INFO	The specified name is already in use The specified parent does not exist or cannot be used A specified sufficient principal does not exist or cannot be used The specified delegate does not exist or cannot be used The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified principal type is not valid A newer version of the specified entity exists in the system	The specified principal was not updated	Specify a valid value Specify another value Refresh the entity and retry the operation

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00713	An error occurred during principal deletion	WARNING	No such entity A newer version of the specified entity exists in the system Failed to unregister the entity with access control service	The specified principal was not deleted	Specify a valid value Refresh the entity and retry the operation
BEEU-00714	An error occurred during principal loading	INFO	No such entity	The specified principal was not loaded	Specify a valid value
BEEU-00715	An error occurred during principal resolution	INFO	No such entity The user for the specified principal is disabled, deleted or locked	The specified name was not resolved to a principal	Specify a valid value Enable the user and retry
BEEU-00721	Failed to generate user data.	WARNING	User does not have a valid manager. Profile {0} does not exist. Failed to get service locator. Principal or unique identifier not found. Invalid file {0} name or location. Invalid ldap credentials. Invalid scope identifier. Invalid membership identifier. Attributes not found for user generation. Family name not found. Failed to find user type for {0}. Failed to find principal for {0}. Invalid attribute. Invalid property. Invalid address. Failed to generate user xml data. Failed to transform xml user data. Failed to generate user data.	Failed to download user data.	Provide correct manager or assistant value. Provide correct profile name. Provide family name for user {0}. Provide valid principal value. Try again later. If the problem persists, contact your system administrator Provide attribute map for profile {0}. Provide valid file location. Correct user type mapping and retry user generation. Provide valid ldap credentials. Provide valid scope identifier for {0}. Provide valid membership identifier for {0}. Provide valid user type. Check if user has required unique identifier or principal.

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00721	An error occurred during user creation	WARNING	<p>The specified identifier is already in use</p> <p>The specified parent does not exist or cannot be used</p> <p>The specified owner does not exist or cannot be used</p> <p>The operation cannot be performed while running in external directory mode</p> <p>The operation is valid only in external directory mode</p> <p>The family name was not specified</p> <p>The specified community does not exist or cannot be used</p> <p>The specified assistant does not exist or cannot be used</p> <p>The specified manager does not exist or cannot be used</p> <p>The specified preference profile does not exist or cannot be used</p> <p>The specified timezone does not exist or cannot be used</p> <p>The specified address is invalid</p> <p>An entity with the specified address already exists</p> <p>No such address</p> <p>The type of address has a suffix beyond the configured range of the system</p> <p>The type of the address is invalid</p> <p>The scheme of the address is invalid</p> <p>The specified personal workspace does not exist or cannot be used</p> <p>A provisioning policy could not be applied during user creation</p> <p>The specified locale does not exist or cannot be used.</p> <p>The specified value for the parameter {0} is too large (Limit is {1})</p> <p>The specified property is invalid; Name = {0}, Value = {1}</p> <p>The specified group is being modified. The automatic manager/peer contacts could not be created for the user</p>	The specified user was not created	<p>Specify a valid value</p> <p>Specify another value</p> <p>See the log file for more details</p> <p>Either the operation cannot be performed with the current configuration, or the mode of directory service has to be changed</p> <p>Try again later.</p> <p>If the problem persists, contact your system administrator</p>

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEED-00722	Failed to add users.	WARNING	Unable to find users manager Unable to find users assistant Failed to get service locator. Failed to find profilename {0}. Invalid filename {0} or location. Invalid ldap credentials. Invalid enterprise identifier. Invalid organization identifier. Invalid user type. Invalid user attribute. Invalid user property. Invalid user address {0}. Invalid format of identifier {0}. Invalid user principal. Failed to parse user xml file Missing family name Failed to add groups. Failed to modify groups. Failed to add users.	Add user failed.	Provide valid manager value. Provide assistant principal name. Provide correct profile name. Try again later. If the problem persists, contact your system administrator Provide valid file name or location. Provide valid ldap user credentials. Provide valid enterprise identifier. Provide valid organization identifier. Provide valid user type. Provide valid principal identifier. Provide valid unique identifier. Provide valid address. Provide valid identifier. Provide valid value. Provide valid xml file Provide family name

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00722	An error occurred during user update	WARNING	<p>The specified parent does not exist or cannot be used The user was not specified or cannot be used The specified owner does not exist or cannot be used The operation cannot be performed while running in external directory mode The operation is valid only in external directory mode The family name was not specified The specified community does not exist or cannot be used The specified assistant does not exist or cannot be used The specified manager does not exist or cannot be used The specified preference profile does not exist or cannot be used The specified timezone does not exist or cannot be used The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The specified personal workspace does not exist or cannot be used The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) A newer version of the specified entity exists in the system The specified group is being modified. The values {0} are mastered in the external directory. These are read only entries. The automatic manager/peer/directs contacts could not be updated for the user</p>	The specified user was not updated	<p>Specify a valid value Specify another value Either the operation cannot be performed with the current configuration, or the mode of directory service has to be changed Perform the operation/changes in external directory. Try again later. If the problem persists, contact your system administrator</p>

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00723	An error occurred during user deletion	WARNING	No such entity The user was not specified or cannot be used A user mastered in an external directory must be deleted in the external directory A newer version of the specified entity exists in the system A de-provisioning policy could not be applied during user deletion The operation cannot be performed while running in external directory mode The operation is valid only in external directory mode The automatic manager/peer/directs contacts could not be deleted for the user	The specified user was not deleted	Specify a valid value Specify another value Refresh the entity and retry the operation See the log file for more details Either the operation cannot be performed with the current configuration, or the mode of directory service has to be changed
BEEU-00724	An error occurred during user load	WARNING	No such entity The user was not specified or cannot be used	The specified user was not loaded	Specify a valid value
BEEU-00725	An error occurred during user purge	WARNING	No such entity The specified user has not been deleted and cannot be purged The user was not specified or cannot be used Failed to unregister the entity with access control service	The specified user was not purged	Specify a valid value Try again later. If the problem persists, contact your system administrator Try again later. If the problem persists, contact your system administrator
BEEU-00726	An error occurred while listing users	WARNING	A projection was not specified or cannot be used	The users could not be listed	Specify a valid value

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00731	An error occurred during group creation	WARNING	<p>Duplicate entity The specified address is invalid No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The query was not specified or cannot be used The scope was not specified or cannot be used An entity with the specified address already exists The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The scope was not specified or cannot be used UDS_INVALID_PREDICATE The name was not specified or cannot be used The specified parent is not a team workspace The query was not specified or cannot be used The specified name is already in use An error occurred when raising events The operation cannot be performed while running in external directory mode The operation is valid only in external directory mode The specified group is being modified.</p>	The specified group was not created	Specify a valid value Specify another value Either the operation cannot be performed with the current configuration, or the mode of directory service has to be changed Try again later. If the problem persists, contact your system administrator

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00732	An error occurred during group update	WARNING	<p>The specified parent does not exist or cannot be used The specified group is invalid A newer version of the specified entity exists in the system No such entity The query was not specified or cannot be used The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified name is already in use Cannot convert a workspace group to enterprise group The specified preference profile does not exist or cannot be used An error occurred when raising events The operation cannot be performed while running in external directory mode The operation is valid only in external directory mode The specified group is being modified. The name was not specified or cannot be used The specified owner does not exist or cannot be used The values {0} are mastered in the external directory. These are read only entries.</p>	The specified group was not updated	Specify a valid value Specify another value Either the operation cannot be performed with the current configuration, or the mode of directory service has to be changed Perform the operation/changes in external directory. Try again later. If the problem persists, contact your system administrator

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00733	An error occurred during group deletion	WARNING	No such entity The specified group is invalid A newer version of the specified entity exists in the system This operation cannot be performed on the ALL_USERS group This operation cannot be performed on team workspace group A group mastered in an external directory must be deleted in the external directory An error occurred when raising events The operation cannot be performed while running in external directory mode The operation is valid only in external directory mode The specified group is being modified.	The specified group was not deleted	Specify a valid value Specify another value Either the operation cannot be performed with the current configuration, or the mode of directory service has to be changed Try again later. If the problem persists, contact your system administrator
BEEU-00734	An error occurred during group load	WARNING	No such entity The specified group is invalid	The specified group was not loaded	Specify a valid value
BEEU-00735	An error occurred during addition or removal of group member	WARNING	The specified member is invalid The member could not be added to the group The member could not be deleted from the group The member was not added to the group as it would create cyclic loop The specified entity is already part of the group The member exists in a scope which is not visible to the group The specified entity is already excluded from the group Removal of excluded member failed	The members could not be added or removed	Specify a valid value Check the group member details and remove the duplicate entity Check the group member details and remove the already excluded member from the list

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00736	An error occurred during group purge	WARNING	No such entity The specified group is invalid This operation cannot be performed on the ALL_USERS group This operation cannot be performed on the group with this status This operation cannot be performed on team workspace group An error occurred when raising events Failed to unregister the entity with access control service	The specified group was not purged	Specify a valid value Specify another value The group should be in a different status to perform this operation
BEEU-00737	An error occurred while getting the element modifications	WARNING	The scope was not specified or cannot be used The specified scope does not exist	Could not get the element modifications for the specified container	Specify a valid value Specify another value
BEEU-00738	An error occurred during group undelete	WARNING	No such entity The specified group is invalid This operation cannot be performed on the ALL_USERS group This operation cannot be performed on the group with this status This operation cannot be performed on team workspace group An error occurred when raising events	The specified group could not be undeleted	Specify a valid value Specify another value The group should be in a different status to perform this operation
BEEU-00739	An error occurred while listing groups	WARNING	A projection was not specified or cannot be used	The groups could not be listed	Specify a valid value

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00751	An error occurred during external contact creation	WARNING	The specified identifier is already in use The specified parent does not exist or cannot be used The specified owner does not exist or cannot be used The operation cannot be performed while running in external directory mode The operation is valid only in external directory mode The family name was not specified The specified community does not exist or cannot be used The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified timezone does not exist or cannot be used The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid	The specified external contact was not created	Specify a valid value Specify another value Either the operation cannot be performed with the current configuration, or the mode of directory service has to be changed

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00752	An error occurred during external contact update	WARNING	The specified parent does not exist or cannot be used The external person was not specified or cannot be used The specified owner does not exist or cannot be used The operation cannot be performed while running in external directory mode The operation is valid only in external directory mode The family name was not specified The specified community does not exist or cannot be used The specified property is invalid; Name = {0}, Value = {1} The specified value for the parameter {0} is too large (Limit is {1}) The specified timezone does not exist or cannot be used The specified address is invalid An entity with the specified address already exists No such address The type of address has a suffix beyond the configured range of the system The type of the address is invalid The scheme of the address is invalid The values {0} are mastered in the external directory. These are read only entries.	The specified external contact was not updated	Specify a valid value Specify another value Either the operation cannot be performed with the current configuration, or the mode of directory service has to be changed Perform the operation/changes in external directory.
BEEU-00753	An error occurred during external contact deletion	WARNING	No such entity The external person was not specified or cannot be used A external person mastered in an external directory must be deleted in the external directory A newer version of the specified entity exists in the system The operation cannot be performed while running in external directory mode The operation is valid only in external directory mode	The specified external contact was not deleted	Specify a valid value Specify another value Refresh the entity and retry the operation Either the operation cannot be performed with the current configuration, or the mode of directory service has to be changed

Table 3–26 (Cont.) User Directory Services

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00754	An error occurred during external contact loading	WARNING	No such entity The external person was not specified or cannot be used	The specified external contact was not loaded	Specify a valid value
BEEU-00755	An error occurred during external contact purge	WARNING	No such entity The external person was not specified or cannot be used The specified external contact has not been deleted and cannot be purged The entity cannot be purged	The specified external contact was not purged	Specify a valid value Try again later. If the problem persists, contact your system administrator
BEEU-00756	An error occurred while listing external persons	WARNING	A projection was not specified or cannot be used	The external persons could not be listed	Specify a valid value

Virus Scanner Error Codes

The following table lists error codes for Virus Scanner.

Table 3–27 Virus Scanner

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-03001	Request sent to the virus scan engine is not a valid one.	WARNING	Error parsing request sent to the scan engine running at {0}:{1} due to syntax or other errors. The operation requested is not a valid one. The service requested does not correspond to an available service on the scan engine running at {0}:{1}. ICAP version, {0}, used to communicate with the virus scan engine running at {1}:{2} is not a supported one.	Unable to service request made to the virus scan engine at {0}:{1}.	Verify the configuration settings on the virus scan engine, {0}:{1}. Verify the request being sent to the scan engine. Verify the Beehive configuration settings for the virus scan engine, {0}:{1}. Verify that the file {0} exists and is readable by the virus scan engine at {1}:{2}
BEEC-03002	Unable to scan for viruses due to a configuration error on the virus scan engine.	WARNING	License on virus scan engine running at {0}:{1} is not valid.	Unable to service any requests made to the virus scan engine at {0}:{1}.	Verify that the license on the virus scan engine, {0}:{1}, is valid.
BEES-03003	Unable to scan for viruses due to an I/O error.	WARNING	IO error encountered during scan of {0}. Request was made to engine, {1}:{2}. IO error encountered during communication with the virus scan engine running at {0}:{1}. Generic IO error. Unable to read input to be scanned {0} .	Unable to service scan request made to the virus scan engine at {0}:{1}.	Verify that the virus scan engine configured to be running at {1}:{2} is up and that there are no network connectivity issues between the Beehive middle tier and the scan engine. Additionally, verify that the input {0} exists and is readable by the virus scan engine. Check the system permissions on the file or directory {0}.
BEES-03004	Unable to remove viruses due to an I/O error.	WARNING	IO error encountered during repair of {0}. Request was made to engine, {1}:{2}. Unable to read input to be scanned {0} . Output file {0} not writeable. Generic IO error. IO error encountered during communication with the virus scan engine running at {0}:{1}.	Unable to service repair request made to the virus scan engine at {0}:{1}.	Verify that the virus scan engine configured to be running at {1}:{2} is up and that there are no network connectivity issues between the Beehive middle tier and the scan engine. Additionally, verify that the input {0} exists and is readable by the virus scan engine. If the request type specifies that the repairs need to be written to a file on disk, ensure that the scan engine has permission to write to disk. Check the system permissions on the file or directory {0}.

Table 3–27 (Cont.) Virus Scanner

Message ID	Display Name	Severity	Cause	Effect	Action
BEEC-03005	Unable to repair content of viruses due to a configuration error on the virus scan engine.	WARNING	License on virus scan engine running at {0}:{1} is not valid.	Unable to service any requests made to the virus scan engine at {0}:{1}.	Verify that the license on the virus scan engine, {0}:{1}, is valid.
BEES-03006	Response returned by the virus scan engine is not a valid/expected one.	WARNING	Response returned by the virus scan engine running at {0}:{1} is not a valid/expected one. Response returned by the virus scan engine running at {0}:{1} cannot be parsed.	Unable to service request made to the virus scan engine at {0}:{1}.	Verify the configuration settings on the virus scan engine, {0}:{1}.
BEES-03007	Unable to contact virus scan engine.	WARNING	IO error encountered during communication with the virus scan engine running at {0}:{1}. Unable to contact virus scan engine running on host: {0}. Unable to resolve the hostname, {0}, for the virus scan engine. Generic IO error.	Unable to service request made to the virus scan engine at {0}:{1}.	Verify that the virus scan engine configured to be running at {0}:{1} is up and that there are no network connectivity issues between the Beehive middle tier and the scan engine. Verify that the virus scan engine host and port configuration values in Beehive, which are currently set to {0} and {1} respectively, are correct. VIR_CHECK_SERVER_NETWORKING_ACTION Check to see if the virus scan engine on host {0} has been started.
BEES-03008	Unable to retrieve virus definition information from the virus scan engine.	WARNING	Error parsing virus definition information, {0}, returned by the scan engine running at {1}:{2}. Virus definition information is missing from response, {0}, returned by the scan engine running at {1}:{2}.	Unable to service request made to the virus scan engine at {0}:{1}.	Verify the configuration settings on the virus scan engine, {0}:{1}.
BEES-03009	Unable to retrieve capabilities information from the virus scan engine.	WARNING	IO error encountered during communication with the virus scan engine running at {0}:{1}.	Unable to service request made to the virus scan engine at {0}:{1}.	Verify the configuration settings on the virus scan engine, {0}:{1}.
BEES-03010	Virus scan engine cannot process request due to errors on the server where the engine is running.	WARNING	Scan engine at {0}:{1} has a memory or disk error. Scan engine at {0}:{1} has encountered an internal error.	Unable to service request made to the virus scan engine at {0}:{1}.	Check the logs for the scan engine at {0}:{1} to determine the error. Ensure that there is sufficient disk and memory available on the scan engine server, {0}:{1}, to process requests.

Table 3–27 (Cont.) Virus Scanner

Message ID	Display Name	Severity	Cause	Effect	Action
BEES-03011	Virus scan engine has encountered an error processing request.	WARNING	Virus scan engine, {0}:{1}, is unable to process request.	Unable to service request made to the virus scan engine at {0}:{1}.	Verify connectivity, configuration, and resource availability on the virus scan engine server, {0}:{1}.
BEES-03012	Error encountered when manipulating/querying virus scan related data.	WARNING	Data manipulation/query of {0} failed due to {1}.	Unable to service request to manipulate/query data in {0}.	Check the error and take appropriate action, including and not limited to verification of request.
BEEC-03013	Beehive configuration settings disallow this request.	WARNING	Beehive configuration setting for the VirusScanPolicy is set to {0}. This disallows the request to {1}.	Unable to service request made to the virus scan engine at {0}:{1}.	Beehive configuration for the VirusScanPolicy needs to be set to either SCAN_ONLY or SCAN_AND_REPAIR in order to proceed with your request.
BEEC-03014	No virus scan engine found in the Beehive configuration system.	WARNING	Beehive configuration does not have any virus scan engines configured for use.	Unable to service your scan/repair request.	Verify the Beehive configuration settings and ensure that there is at least one virus scan engine configured. Also verify that the VirusScanPolicy is set to either SCAN_ONLY or SCAN_AND_REPAIR.
BEES-03015	None of the virus scan engines are available at this time.	WARNING	Unable to connect to any of the virus scan engines configured in the Beehive configuration system.	Unable to service your scan/repair request.	Verify that at least one of the virus scan engines configured for use is up and that there are no network connectivity issues between the Beehive middle tier and the scan engine.

Web Conferencing Streaming Media Error Codes

The following table lists error codes for Web Conferencing Streaming Media.

Table 3–28 Web Conferencing Streaming Media

Message ID	Display Name	Severity	Cause	Effect	Action
BEEC-03301	Failed to listen on the configured port.	SEVERE	Configured listen port was already in use or the user did not have permission to listen on this port.	Service is down.	Configure the listen port to a different value and restart the service.
BEEZ-03302	Failed to authenticate the user.	INFO	User provided invalid username/password .	User cannot access the requested conference	User must use proper username and password to access the conference
BEEZ-03303	Failed to authorize the user	WARNING	User not authorized to access this conference	User cannot access the requested conference	User must be a valid user in the system authorized to access the conference. Contact system administrator for authorization.
BEEU-03304	Conference does not exist.	WARNING	Either user requested a wrong conference id or the requested conference has been invalidated in the system.	User cannot access the requested conference.	User must use a valid conference identifier which is either running on the system or request the system administrator for authorization approval.
BEER-03305	Client abruptly got disconnected.	WARNING	Network error occurred resulting in a low bandwidth.	User was interrupted while connected to the service.	Player will retry to connect to the same conference without user intervention. User might need to seek to a particular position in the timeline in case of recorded conference or (s)he might see no frills after reconnection in case of live conference.
BEES-03306	Connection to MediaSession was lost.	SEVERE	An internal error occurred in WebConferencing service.	User will be disconnected from the service.	User needs to reconnect for the same conference.
BEEP-03307	The server is busy.	SEVERE	The server has already reached the maximum limit on number of clients it can serve at this moment.	User was not served.	User should try after sometime.

Web Conferencing Transcoding Error Codes

The following table lists error codes for Web Conferencing Transcoding.

Table 3–29 Web Conferencing Transcoding

Message ID	Display Name	Severity	Cause	Effect	Action
BEE5-03401	Transcoding failed.	SEVERE	An error occurred while transcoding a conference.	Transcoding for a particular conference did not complete.	None. The service will pick up this task again in sometime.
BEEC-03402	Transcoding for a conference timed out.	SEVERE	Transcoding failed because of time-out.	Transcoding for a particular conference could not be completed in the timeout duration.	None. Contact system administrator for increasing the timeout duration if these failure are coming more often.

Web Conferencing Error Codes

The following table lists error codes for Web Conferencing.

Table 3–30 Web Conferencing

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00400	Failed to create Conference Artifact.	SEVERE	Invalid parameters specified. Invalid Conference Property name or value specified. Invalid Conference Role name. Invalid Conference Role accessor specified.		
BEEU-00401	Failed to create Conference Template.	SEVERE	Invalid parameters specified. Invalid Conference Property name or value specified. Invalid Conference Role name. Invalid Conference Role accessor specified.		
BEEU-00402	WC_CONFERENC E_UPDATE_FAILED	SEVERE	Invalid parameters specified. Invalid Conference Property name or value specified. Invalid Conference Role name. Invalid Conference Role accessor specified. Failed to update entity because it was modified by another user.		
BEEU-00403	WC_TEMPLATE_ UPDATE_FAILED	SEVERE	Invalid parameters specified. Invalid Conference Property name or value specified. Invalid Conference Role name. Invalid Conference Role accessor specified. Failed to update entity because it was modified by another user.		

Table 3–30 (Cont.) Web Conferencing

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-00404	Failed to load Conference Artifact.	SEVERE	Invalid parameters specified.		Verify the parameters.
BEEU-00405	Failed to join to the Conference.	SEVERE	Invalid parameters specified. All servers are busy or system malfunction occurred. Request to join the Conference didn't complete within a given timeframe and was canceled by the server.	User failed to join the Conference session.	Verify the parameters. Retry to join to the Conference or contact your system administrator. Contact your system administrator.
BEEU-00406	Failed to join the Conference due to insufficient privileges to start the new Conference session.	WARNING	User is not granted with the privilege to start the Conference session.	User failed to join the Conference session.	Wait for host or other authorized user to start the Conference session.

Workflow Service Error Codes

The following table lists error codes for Workflow Service.

Table 3–31 Workflow Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEC-02901	Invalid BPEL Cluster found in the Workflow service configuration. The cluster has {0} BPEL Process Managers in it.	FINE	Invalid BPEL Cluster found in the Workflow service configuration. The cluster has {0} BPEL Process Managers in it.		
BEEC-02902	Invalid or Unsupported BPEL Process Manager found in the BPEL Cluster.	FINE	Invalid or Unsupported BPEL Process Manager found in the BPEL Cluster.		
BEEC-02903	Unable to establish connection with the BPEL Process Manager/Cluster's domain {0} using properties {1}.	FINE	Unable to establish connection with the BPEL Process Manager/Cluster's domain {0} using properties {1}.		
BEEU-02911	A null value is provided for mandatory attribute/parameter {0}. Please provide a non-null value.	FINE	A null value is provided for mandatory attribute/parameter {0}. Please provide a non-null value.		
BEEU-02912	An error occurred during the processing of the attributes. This is typically due to incorrect data types/values.	FINE	An error occurred during the processing of the attributes. This is typically due to incorrect data types/values.		

Table 3–31 (Cont.) Workflow Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-02913	Unable to initiate a Workflow with name {0} and parameters{1} due to an internal workflow engine error. Please contact the administrator for more information.	FINE	Unable to initiate a Workflow with name {0} and parameters{1} due to an internal workflow engine error. Please contact the administrator for more information.		
BEEU-02914	Unable to cancel Workflow with id {0} due to an internal error. Please contact the administrator for more information.	FINE	Unable to cancel Workflow with id {0} due to an internal error. Please contact the administrator for more information.		
BEEU-02915	Unable to create a workflow schema with the name {0} as a workflow schema with the same name already exists. Please use a different name.	FINE	Unable to create a workflow schema with the name {0} as a workflow schema with the same name already exists. Please use a different name.		
BEEU-02916	Cannot override a workflow template marked as 'final' in the parent folder.	FINE	Cannot override a workflow template marked as 'final' in the parent folder.		
BEEU-02917	Unable to create a workflow entity with the same {0}.	FINE	Entity with eid {0} does not exist.		
BEEU-02918	Entity with eid {0} does not exist.	FINE	Entity with eid {0} does not exist.	The requested operation cannot be performed.	Re-try the operation with valid Collab Id.
BEEU-02919	Workflow template with such scope key exists.	FINE	Workflow template with such scope key exists.		
BEER-02931	An internal DB Exception occurred. Please re-try the operation or contact administrator for assistance.	FINE	An internal DB Exception occurred. Please re-try the operation or contact administrator for assistance.		
BEER-02932	BPEL Workflow Service is currently unavailable. You will not be able to initiate or cancel workflows. Please try again later. If the problem persists, please contact the administrator.	FINE	BPEL Workflow Service is currently unavailable. You will not be able to initiate or cancel workflows. Please try again later. If the problem persists, please contact the administrator.		
BEER-02933	Unable to obtain a Database Connection.	FINE	Unable to obtain a Database Connection.		
BEEZ-02941	WKFL_ACCESS_DENIED	FINE	WKFL_ACCESS_DENIED		

Workspaces Error Codes

The following table lists error codes for Workspaces.

Table 3–32 Workspaces

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-06000	Unexpected error.	SEVERE	An unexpected internal error occurred.	The requested operation cannot be performed	Contact system administrator.
BEEU-06001	Entity not found.	WARNING	The specified entity was not found. The specified parent entity not found. The specified target entity not found. No common parent entity exists for the specified entities.	Verify the Entity specified.	Retry the operation with a valid entity. Retry the operation with a valid entity. Retry the operation with a valid entity. Retry the operation with a set of entities that have a common parent.
BEEU-06002	Failed to perform the operation.	WARNING	Optimistic locking verification failed as the specified snapshot id does not match the server snapshot id.	The requested operation cannot be performed on the entity.	Reload the entity to be updated and then re-try.
BEEU-06003	Entity not checked out.	WARNING	The requested operation is not allowed on a entity that is not checked out.	The requested operation cannot be performed.	Checkout the entity and re-try the operation.
BEEU-06004	Deleted entity.	WARNING	The requested operation is not allowed on a deleted entity.	The requested operation cannot be performed.	Undelete the entity and re-try the operation.
BEEU-06005	Locked entity.	WARNING	The requested operation is not allowed on a locked entity.	The requested operation cannot be performed.	Unlock the entity and re-try the operation.
BEEU-06006	Duplicate entity.	WARNING	The specified entity identifier already exists.	The requested operation cannot be performed.	Specify a different entity identifier and re-try the operation.
BEEU-06007	Duplicate entity name.	WARNING	the specified entity name already exists.	The requested operation cannot be performed.	Specify a different entity name and re-try the operation.
BEEU-06008	Quota overflow.	WARNING	The hard quota limit for this scope has been exceeded.	The requested operation cannot be performed.	Get your quota increased!

Table 3–32 (Cont.) Workspaces

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-06009	Invalid Quota configuration.	WARNING	Invalid Quota configuration. Zero or negative quota values were specified. Soft quota value provided is greater than hard quota value. Specified quota configuration violates parent quota configuration. Specified quota configuration invalidates current children quota configuration.	Quota configuration update cannot be performed.	Review the specified quota configuration to make it comply with the quota configuration and status of the parent Scope. Review the specified quota configuration to make it comply with the quota configuration and status of the parent Scope. Review the specified quota configuration to make it comply with the quota configuration and status of the parent Scope. Review the specified quota configuration to make it comply with the quota configuration and status of the parent Scope. Review the specified quota configuration to make it comply with the quota configuration and status of the parent Scope.
BEEU-06010	INBOX update failed.	WARNING	The name of this folder is invalid.	INBOX will not be updated.	Folder name must be INBOX.
BEEU-06011	Cannot delete workspace default folder.	WARNING	Folder being deleted is a default workspace folder required by other services.	The specified folder will not be deleted.	Change the default workspace folder for that service to another folder and then re-try the delete operation.
BEEU-06012	Cannot move workspace default folder across scopes.	WARNING	Folder being moved is a default workspace folder required by other services.	The specified folder will not be moved.	Change the default workspace folder for that service to another folder and then re-try the move operation.
BEEU-06013	getElementModification s failed.	WARNING	The container snapshot id specified is too old to compute the list of modified elements.	Container modifications will not be retrieved.	Reload the whole container.
BEEU-06014	Copy was not complete.	WARNING	One or more of the contained items could not be copied because an error occurred.	Some of the items of the specified container will not be copied into the destination.	Manually copy the failed items after having reviewed and fixed the reason of their failure.

Table 3–32 (Cont.) Workspaces

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-06015	Update of team workspace participants failed.	WARNING	Team workspace participant list could not be updated because an error occurred. Team workspace participation mode does not allow for self-joining. Team workspace participant list could not be updated because a null participant was provided. Team workspace owner cannot be removed from the participant list. Cannot update the role of accessor who is not a team workspace participant. Cannot remove all accessors granted Workspace Coordinator role.	Team workspace participant list will not be updated.	Re-try the update of team workspace participants after having removed the problem encountered. Re-try the update of team workspace participants after having removed the problem encountered. Re-try the update of team workspace participants after having removed the problem encountered. Re-try the update of team workspace participants after having removed the problem encountered. Re-try the update of team workspace participants after having removed the problem encountered. Re-try the update of team workspace participants after having removed the problem encountered. Re-try the update of team workspace participants after having removed the problem encountered.
BEEU-06016	Non deleted entity.	WARNING	Cannot undelete an entity which is not deleted.	The requested operation cannot be performed.	Move the entity to the new destination.
BEEU-06017	Entity is checked out.	WARNING	The requested operation is not allowed on a entity that is checked out. The entity was already checked out when the OperationContext was created, and so the operation cannot be canceled properly via this API.	The requested operation cannot be performed.	Re-try the operation once the entity is not checked out. Invoke CancelCheckout to roll back all changes to the working copy. Alternatively, re-try the operation.
BEEU-06018	Operation could not be performed.	WARNING	Another operation is being performed on the resource.	The result of this operation will not be available.	Please try again later.
BEEU-06019	Operation could not be performed.	WARNING	The resource has moved.	The result of this operation will not be available.	Please try again later.

3-78 Oracle Beehive Administrator's Reference Guide

[illegible]

Table 3–32 (Cont.) Workspaces

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-06051	Invalid operation on a hierarchical configuration.	WARNING	Versioning operations are prohibited in this container. The {0} configuration does not exist. A {0} configuration is already defined on this container. An existing ancestor {0} configuration is marked as final. Cannot mark as final when subcontainer has a {0} configuration defined. Cannot remove the default {0} configuration from an enterprise. Configuration update with these values would leave it in an invalid state. Container move failed because it would modify a {0} configuration marked as final.	The operation has failed due to a {0} configuration error.	Versioning operations are prohibited in this container. Specify a valid {0} configuration. Either update the existing {0} configuration or delete it and then create a new one. Mark the final {0} configuration as non-final and retry, or abort creation of the new configuration. Create or update the {0} configuration as non-final, or delete all {0} configurations on subcontainers. Update the enterprise {0} configuration instead of removing it. Ensure that the updated values of the {0} configuration are all valid. Remove the {0} configuration from the container to move, or mark the configuration in the destination as non-final.
BEEU-06052	The operation caused a naming conflict with another entity.	WARNING	A document already exists in this folder with the specified name; aborting due to the chosen conflict resolution mode.	The operation has not completed due to the conflict.	Choose a different name or a different conflict resolution mode.
BEEU-06053	A pending change conflict has occurred.	WARNING	The operation is in conflict with another pending change to this entity.	The operation has not completed due to the conflict.	Retry the operation or change the name of the document.
BEEU-06054	A error has occurred with the OperationContext.	WARNING	The OperationContext either does not exist or is not valid for this operation type. The OperationContext exists but is outdated since a conflicting operation has committed.	The operation has not completed due to the error.	Retry the operation with a valid OperationContext. Cancel the operation and try again.
BEEU-06055	Mandatory categories cannot be removed from an entity.	WARNING	The specified category was defined as a mandatory category in the effective category configuration for the parent container of the entity.	The specified category will not be removed from the specified entity.	Ensure that the category to be removed from the entity is not specified as being required in the effective category configuration for the parent container of the entity.

Table 3–32 (Cont.) Workspaces

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-06056	The specified category is not in the list of available categories of the effective category configuration of the entity.	WARNING	The specified category was not in the list of available categories as configured in the effective category configuration of the entity being categorized.	The specified category will not be applied to the specified entity.	Ensure that the category to be applied to the entity is in the list of available categories of the effective category configuration of the entity being categorized.
BEEU-06057	The delete of the directory failed.	WARNING	The directory cannot be deleted because document(s) imported from it to Beehive still remain.	The directory will continue to exist in Beehive.	Refrain from deleting the directory unless all documents imported from it in Beehive are first purged.
BEEU-06058	The update of the version failed.	WARNING	A version cannot be updated if it represents the working copy.	The version will not be updated.	Check the working copy in, and then update the version.
BEEU-06059	Invalid lock type specified	WARNING	Locking an entity with the given lock type is not allowed.	The requested operation cannot be performed.	Re-try with a different lock type.
BEEU-06060	Locked entity.	WARNING	Entity is locked with a Workflow lock.	The requested operation cannot be performed.	Wait until workflow is completed and re-try operation.
BEEU-06061	Recordized entity.	WARNING	Entity is recordized.	The requested operation cannot be performed.	Operation permitted only once entity is un-recordized.

Workspaces Templates Error Codes

The following table lists error codes for Workspaces Templates.

Table 3–33 Workspaces Templates

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-06200	Invalid workspace sub-group reference in template	WARNING	The specified template body id does not refer to a workspace sub-group template body ID.	The dependent entity will not be created. For example, if the reference is for a task participant, the task will not be created.	Specify a valid workspace sub-group template body ID.
BEEU-06201	Unsupported file parent in template	WARNING	A container other than a heterogeneous folder is specified as the parent of the file.	The file will not be created.	Specify a heterogeneous folder as the parent of the file.
BEEU-06202	Unsupported calendar parent in template	WARNING	A container other than a workspace is specified as the parent of the calendar.	The calendar will not be created.	Specify a workspace as the parent of the calendar.
BEEU-06203	Unsupported task list parent in template	WARNING	A container other than a workspace is specified as the parent of the task list.	The task list will not be created.	Specify a workspace as the parent of the task list.

Table 3–33 (Cont.) Workspaces Templates

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-06204	failed to store workspace-to-default folder mapping	WARNING	Attempt to store mapping between a workspace and a default folder (e.g., INBOX) in database failed with the following error : {0}	The default folder will not be functional, e.g., emails may not be delivered to INBOX folder.	Contact system administrator. Additional information may be available in log files.
BEEU-06205	Current actor's identifier is null	WARNING	Attempt to retrieve current actor for user context failed.	Current operation was terminated.	Contact Oracle support.
BEEU-06206	workspace template creation failed	WARNING	The following error was encountered during workspace template creation: {0}	The workspace template was not created.	Retry after correcting the error. Ask system administrator to check additional information about the underlying error printed out in log file.
BEEU-06207	workspace template deletion failed	WARNING	The following error was encountered during workspace template deletion: {0}	The workspace template was not deleted.	Retry after correcting the error. Ask system administrator to check additional information about the underlying error printed out in log file.
BEEU-06208	workspace template retrieval failed	WARNING	The following error was encountered during workspace template retrieval: {0}	The workspace template was not retrieved.	Retry after correcting the error. Ask system administrator to check additional information about the underlying error printed out in log file.
BEEU-06209	workspace template update failed	WARNING	The following error was encountered while updating workspace template: {0}	The workspace template was not updated.	Retry after correcting the error. Ask system administrator to check additional information about the underlying error printed out in log file.
BEEU-06210	syntax error encountered in workspace template	WARNING	Syntax error at line {0}, column {1} : {2}	The workspace template was not created.	Retry after correcting the syntax error.
BEEU-06211	syntax error in workspace summary URI specified in workspace template	WARNING	The following syntax error was encountered in summary URI: {0}	The workspace was not created	Retry after correcting the syntax error. Ask system administrator to check additional information about the error printed out in log file.
BEEU-06212	failed to store template-to-entity mapping	WARNING	Attempt to store mapping between a template and a an entity created from it failed with the following error : {0}	The entity was not created.	Contact system administrator. Additional information may be available in log files.
BEEU-06213	failed to unmarshall template	WARNING	Attempt to unmarshall template failed with the following exception: {0}	The template was not unmarshalled.	Contact system administrator. Additional information may be available in log files.

Table 3–33 (Cont.) Workspaces Templates

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-06214	failed to retrieve workspace template XML schema	WARNING	Attempt to retrieve workspace template XML schema failed with the following exception: {0}	The workspace template XML schema was not retrieved.	Contact system administrator. Additional information may be available in log files.
BEEU-06215	the operation was partially successful	WARNING	Some of the steps executed during the operation failed.	Not all intended results of the operation will be available. For example, if the intended result of the operation was to create an entity, the entity may not be fully functional.	Contact system administrator. The details of exceptions encountered during the operation are printed out in log files.
BEEU-06216	a sub-operation failed causing partial success of the overall operation	WARNING	The following sub-operation failed causing partial success of the overall operation: {0}	The result of this sub-operation will not be available after the completion of the overall operation.	See nested exception for the cause of failure of this sub-operation.
BEEU-06217	Duplicate name	WARNING	An entity with the give name is reserved by some other user.	Cannot create the document/folder with the given name.	Please choose a different name.
BEEU-06218	Values for one or more mandatory attributes for Categories or Workflow are missing.	WARNING	Attribute values mandated by the prevalent Category or Workflow configuration were not provided.	The content services specific operation cannot proceed until all mandatory values are provided.	Ensure all mandatory attribute values are provided when invoking the content operation.
BEEU-06219	The specified category parent predicate is invalid. Allowed values for the parent predicate are enterprise or other categories.	WARNING	The specified category parent predicate is invalid. Allowed values for the parent predicate are enterprise or other categories.	The category listing cannot be filtered based on the invalid parent predicate.	Ensure category parent predicate is valid.

XMPP Protocol Service Error Codes

The following table lists error codes for XMPP Protocol Service.

Table 3–34 XMPP Protocol Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-02801	XMPP: Error in stream sent by client	SEVERE	XMPP: Error in stream ,Invalid XML	XMPP: You have been disconnected	XMPP: Please Log-in again.
BEES-02804	XMPP: Error caused by other services	WARNING	XMPP: Exception thrown by other services e.g UDS,AUTH	XMPP: Requested operation couldn't be performed	XMPP: Contact Administrator for this error.
BEES-02805	XMPP: Internal server error	SEVERE	XMPP: internal server error ,cause by some unexpected exception	XMPP: You have been disconnected.	XMPP: Please Log-in again.

Table 3–34 (Cont.) XMPP Protocol Service

Message ID	Display Name	Severity	Cause	Effect	Action
BEEU-02806	XMPP: Recoverable error caused by erroneous xmpp MESSAGE packet sent by client	WARNING	XMPP: Some harmless erroneous tags/data in MESSAGE packet or packet is not RFC compliant	XMPP: Recieved MESSAGE packet had some erroneous data , ignoring the packet.	XMPP: To send the ignored packet again , correct it first and then repeat the operation.
BEEU-02807	XMPP: Recoverable error caused by erroneous xmpp IQ packet sent by client	WARNING	XMPP: Some harmless erroneous tags/data in IQ packet or packet is not RFC compliant	XMPP: Recieved IQ packet had some erroneous data , ignoring the packet.	XMPP: To send the ignored packet again , correct it first and then repeat the operation.
BEEU-02808	XMPP: Recoverable error caused by erroneous xmpp PRESENCE packet sent by client	WARNING	XMPP: Some harmless erroneous tags/data in PRESENCE packet or packet is not RFC compliant	XMPP: Recieved PRESENCE packet had some erroneous data , ignoring the packet.	XMPP: To send the ignored packet again , correct it first and then repeat the operation.

