

Oracle® Retail Workspace
Installation Guide
Release 13.0.2

January 2009

Copyright © 2009, Oracle. All rights reserved.

Primary Author: Wade Schwarz

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software—Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Value-Added Reseller (VAR) Language

Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

(i) the software component known as **ACUMATE** developed and licensed by Lucent Technologies Inc. of Murray Hill, New Jersey, to Oracle and imbedded in the Oracle Retail Predictive Application Server – Enterprise Engine, Oracle Retail Category Management, Oracle Retail Item Planning, Oracle Retail Merchandise Financial Planning, Oracle Retail Advanced Inventory Planning, Oracle Retail Demand Forecasting, Oracle Retail Regular Price Optimization, Oracle Retail Size Profile Optimization, Oracle Retail Replenishment Optimization applications.

(ii) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.

(iii) the **SeeBeyond** component developed and licensed by Sun Microsystems, Inc. (Sun) of Santa Clara, California, to Oracle and imbedded in the Oracle Retail Integration Bus application.

(iv) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.

(v) the software component known as **Crystal Enterprise Professional and/or Crystal Reports Professional** licensed by SAP and imbedded in Oracle Retail Store Inventory Management.

(vi) the software component known as **Access Via™** licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.

(vii) the software component known as **Adobe Flex™** licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

(viii) the software component known as **Style Report™** developed and licensed by InetSoft Technology Corp. of Piscataway, New Jersey, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.

(ix) the software component known as **DataBeacon™** developed and licensed by Cognos Incorporated of Ottawa, Ontario, Canada, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, “alteration” refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle’s licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.

Contents

Preface	ix
Audience	ix
Related Documents.....	ix
Customer Support.....	ix
Review Patch Documentation.....	ix
Oracle Retail Documentation on the Oracle Technology Network.....	ix
Conventions.....	x
1 Preinstallation Tasks.....	1
Check Application Server Requirements.....	1
Supported Oracle Retail Products	2
Check Client PC and Web Browser Requirements.....	2
Prerequisites for External Applications	2
Prerequisites for ORW Oracle BI EE Alerts Application.....	2
Prerequisites for ORW BPEL Portlets.....	3
2 Oracle Retail Workspace Overview.....	5
LDAP Data.....	5
Portlets.....	5
Example Dashboards.....	5
BPEL Portlets	5
BPEL Pages Application.....	5
Oracle BI EE Alerts Application.....	6
Oracle Retail Workspace Application	6
3 LDAP Data	7
Required Oracle Internet Directory (OID) Information.....	7
LDAP Data Utility.....	7
Expand and Execute the ORW LDAP Data Utility	10
Workspace Administrator Users.....	11
4 Retail Portlets Installation.....	13
Create a New OC4J Instance and Group for Portlets.....	13
Associate OC4J with OID.....	14
Expand the Retail Portlets Application Distribution	15
Run the Retail Portlets Application Installer.....	15
Resolving Errors Encountered During Application Installation.....	16
Manual Deployment Option	16
Backups Created by Installer.....	17
Test the Retail Portlets Application	17
5 Example Dashboards Installation	19
Create a New OC4J Instance and Group for Dashboards	19
Associate OC4J with OID.....	20

Expand the Retail Dashboards Distribution.....	21
Run the Retail Dashboards Installer.....	21
Resolving Errors Encountered During Application Installation.....	22
Manual Deployment Option	22
Test the Demo Dashboards Applications	23
6 BPEL Portlets Installation.....	25
Configure SOA Suite OC4J Instance.....	25
Associate SOA Suite OC4J with OID.....	26
Expand the BPEL Portlets Distribution.....	26
Run the BPEL Portlets Installer.....	27
Resolving Errors Encountered During Application Installation.....	27
Manual Deployment Option	27
Backups Created by Installer.....	28
Test the BPEL Portlets Application	28
7 BPEL Pages Installation.....	29
Create a New OC4J Instance and Group for BPEL Pages	29
Associate OC4J with OID.....	30
Expand the BPEL Pages Distribution.....	31
Run the BPEL Pages Installer	31
Resolving Errors Encountered During Application Installation.....	32
Manual Deployment Option	32
Backups Created by Installer.....	33
Test the BPEL Pages Application.....	33
8 Oracle BI EE Alerts Application Installation	35
Create a New OC4J Instance and Group for Oracle BI EE Alerts	35
Associate OC4J with OID.....	36
Expand the Oracle BI EE Alerts Distribution.....	37
Run the Oracle BI EE Alerts Installer	37
Statically Protect Oracle BI EE Alerts Application	38
Resolving Errors Encountered During Application Installation.....	38
Manual Deployment Option	38
Backups Created by Installer.....	39
Test the Oracle BI EE Alerts Applications	39
9 Workspace Application Installation	41
Create a New OC4J Instance and Group for ORW	41
Associate OC4J with OID.....	42
Expand the ORW Distribution.....	43
Run the ORW Installer	43
Resolving Errors Encountered During Application Installation.....	43
Oracle Configuration Manager	44
Manual Deployment Option	44
Backups Created by Installer.....	45

Test the ORW Application.....	45
A Appendix: Portlets Application Installer Screens	47
B Appendix: Dashboards Installer Screens	53
C Appendix: BPEL Portlets Installer Screens	66
D Appendix: BPEL Pages Installer Screens	71
E Appendix: Oracle BI EE Alerts Installer Screens	81
F Appendix: Workspace Installer Screens	87
G Appendix: Installer Silent Mode	129
Repeating an Installation Attempt.....	129
H Appendix: Common Installation Errors.....	131
Unreadable Buttons in the Installer	131
“Unable to get a deployment manager” Message	131
“Could not create system preferences directory” Warning	132
ConcurrentModificationException in Installer GUI.....	132
“Couldn't find X Input Context” Warnings	132
Error while unpacking EAR file.....	133
Installer Errors Tab Section Full of Informational Messages	133
Installer Appears to Hang after EAR deployment	133
I Appendix: URL Reference	135
Deployer URI.....	135
J Appendix: Installation Order	137

Preface

Oracle Retail Installation Guides contain the requirements and procedures necessary for the retailer to install Oracle Retail products.

Audience

This Installation Guide is written for the following audiences:

- System analysts and designers
- Integrators and implementation staff

Related Documents

For more information, see the following documents in the Oracle Retail Workspace Release 13.0.2 documentation set:

- *Oracle Retail Workspace Release Notes*
- *Oracle Retail Workspace Implementation Guide*
- *Oracle Retail Workspace Online Help*
- *Oracle Retail Workspace Administration Guide*

Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:

<https://metalink.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

Review Patch Documentation

If you are installing the application for the first time, you install either a base release (for example, 13.0) or a later patch release (for example, 13.0.2). If you are installing a software version other than the base release, be sure to read the documentation for each patch release (since the base release) before you begin installation. Patch documentation can contain critical information related to the base release and code changes that have been made since the base release.

Oracle Retail Documentation on the Oracle Technology Network

In addition to being packaged with each product release (on the base or patch level), all Oracle Retail documentation is available on the following Web site (with the exception of the Data Model which is only available with the release packaged code):

http://www.oracle.com/technology/documentation/oracle_retail.html

Documentation should be available on this Web site within a month after a product release. Note that documentation is always available with the packaged code on the release date.

Conventions

Navigate: This is a navigate statement. It tells you how to get to the start of the procedure and ends with a screen shot of the starting point and the statement “the Window Name window opens.”

Note: This is a note. It is used to call out information that is important, but not necessarily part of the procedure.

This is a code sample
It is used to display examples of code

A [hyperlink](#) appears like this.

Preinstallation Tasks

Oracle Retail Workspace (ORW) is a web application that runs in Oracle WebCenter Suite 10g. The Oracle Retail Workspace Bundle includes this ORW application plus the JSR168-compliant retail portlets, a set of example dashboards, the Oracle Business Intelligence Enterprise Edition (BI EE) Alerts application, the BPEL Portlets, and the BPEL Pages application. The ORW application uses an Oracle Internet Directory (OID) LDAP server for user data for security purposes.

Check Application Server Requirements

General requirements for an application server capable of running the Workspace application include:

Supported On:	Versions Supported:
Application Server OS	Solaris 10 (SPARC) HP-UX 11.31 (Integrity) AIX 5.3 Oracle Enterprise Linux 4 Update 5 for x86-64. <ul style="list-style-type: none"> ▪ Minimum kernel version 2.6.9-55.0.0.0.2.ELsmp. Oracle WebCenter Suite 10g 10.1.3.3 for Linux x86 Patches: <ul style="list-style-type: none"> ▪ 5632264 (NEED UPDATED TIMEZONE FILES (VERSION 4) FOR MORE DST RULE CHANGES) ▪ 5398506 (RUNTIME EXCEPTION DID NOT ROLLBACK MESSAGE ON EGATE (SEEBEYOND) TOPIC) Oracle WebCenter Suite 10g 10.1.3.3 for AIX 5.3 Patches: <ul style="list-style-type: none"> ▪ 5946958 (JAVA CACHE: PATCH JOC DISTRIBUTED MODE FAILURE WHEN REGISTERING GROUP MEMBERS)
Application Server	Oracle Application Server Infrastructure Services 10.1.2.2 Patches: <ul style="list-style-type: none"> ▪ 5861907 (IAS 10.1.2.2 PATCHSET UPDATES ORACLEHOMEPROPERTIES.XML WITH WRONG ARU_ID & ARU_I) ▪ 5632264 (NEED UPDATED TIMEZONE FILES (VERSION 4) FOR MORE DST RULE CHANGES)

Supported Oracle Retail Products

Product	Version
Oracle Retail Merchandising System (RMS)	13.0.2
Oracle Retail Store Inventory Management (SIM)	13.0.2
Oracle Retail Invoice Matching (ReIM)	13.0.2
Oracle Retail Allocation	13.0.2
Oracle Retail Active Retail Intelligence (ARI)	13.0.2
Oracle Retail Price Management (RPM)	13.0.2
Oracle Retail Data Warehouse (RDW)	13.0.2
Oracle Retail Markdown Optimization	13.0
Oracle Retail Promote	13.0.2
Oracle Retail Predictive Application Server (RPAS)	13.0.2

Check Client PC and Web Browser Requirements

Requirement	Version
Operating system	Windows 2000 or XP
Display resolution	1024x768 or higher
Processor	1GHz or higher
Memory	512MBytes or higher
Networking	intranet with at least 10Mbps data rate
Browser	Microsoft Internet Explorer 6 or higher

Prerequisites for External Applications

When OSSO is configured to use Oracle Database 10g Release 2 (10.2.0) or later, the `init{SID}.ora` configuration file must contain a specific "event" entry for the *External Applications* facility to work. For more information on this configuration, see the following:

Metalink Note: 344602.1

WWC-00006 and WWC-41400 When Trying To Login To An External Application on the Metalink Web.

Prerequisites for ORW Oracle BI EE Alerts Application

Integration with the Oracle BI Delivers Alerts requires an OSSO enabled Oracle BI EE server 10.1.3.3 with iBots enabled for Delivers.

For information on how to OSSO enable Oracle BI EE see the *Oracle BI EE Deployment Guide*, Chapter 11 – Enabling Oracle Single Sign-On for Oracle Business Intelligence.

For information on how to enable iBots for Delivers see Oracle BI EE documentation or Metalink note 752517.1

Prerequisites for ORW BPEL Portlets

Integration with the Oracle BPEL Workflows and BPM Worklists requires an OSSO enabled Oracle SOA Suite 10.1.3.3.

Oracle Retail Workspace Overview

Installation of the ORW application bundle consists of seven different components, installed in the order in which they appear below:

LDAP Data

The LDAP realm stores user, group (aka role), and permission grant information used by ORW. You need to add the ORW specific data to your realm as outlined in the *LDAP Data* chapter of this document. There is a utility included with the ORW release that automates the creation of this information using example group data. This data is imported using provided LDIF scripts. There are two sets of scripts used: one containing required data and one that has a set of sample users and groups.

Portlets

The ORW application bundle includes a set of JSR-168 portlets. These portlets provide services which are consumed by the dashboards. There is an installer that configures and deploys these portlets to an OC4J instance in Oracle WebCenter. See the *Retail Portlets Installation* chapter of this document for instructions.

Example Dashboards

The ORW application comes with a set of external example dashboards.

External dashboards are independent J2EE applications that the ORW application pulls in and displays in its content panel. This release includes four external dashboards (Executive, Merchant, Stores, and Planner).

The external example dashboards provided with the ORW application bundle are all installed by a single Example Dashboards installer that is included with the release. See the *Example Dashboards Installation* chapter of this document for instructions.

BPEL Portlets

ORW provides a set of two PDK portlets called ORWBPELWorklistPortlet and ORWBPELWorkflowPortlet. The ORWBPELWorklistPortlet is cloned from the Worklist PDK portlet provided with the BPEL installation.

There is an installer that configures and deploys the portlets to an OC4J instance in the SOA Suite OAS. See the *BPEL Portlets Installation* chapter of this document for instructions.

BPEL Pages Application

BPELPages is an application consisting of two web pages, one for displaying BPM Worklists and the other for displaying BPEL Workflows.

The BPEL Pages application provided with the ORW application bundle is installed with the BPEL Pages application installer that is included with the release. See the *BPEL Pages Installation* chapter of this document for instructions.

Oracle BI EE Alerts Application

The ORW Oracle BI EE Alerts application is used to display Oracle BI EE Ibot Alerts for a user in ORW. This application is used with the Alerts Portlet provided by ORW to display the alerts in a Portlet. The user can click on an alert to view the alert or on the Manage Alerts link on the Portlet to view, clear and open the ibot alert. There is an installer that configures and deploys Oracle BI EE Alerts application to an OC4J instance in the OAS that hosts the Oracle BI EE server. See the *Oracle BI EE Alerts Application Installation* chapter of this document for instructions.

Oracle Retail Workspace Application

The ORW application is the core of the product. This is the application that contains the navigation panel with all of the links to other applications and resources and the content panel which displays the dashboards. See the *ORW Application Installation* chapter of this document for instructions.

LDAP Data

ORW uses the Oracle Internet Directory LDAP server for storage of user, group, and security policy information. ORW supplies a set of required OID LDAP data needed for ORW to function correctly. In addition to the required data, ORW supplies a set of sample users, groups, and permission grants.

This chapter describes the LDAP data creation and installation process.

Required Oracle Internet Directory (OID) Information

The supported directory server for ORW is Oracle Internet Directory (OID). It is assumed that you have installed OID and created a realm to store the ORW users and groups. You need the following pieces of information to run the utility:

LDAP server host	(Example: myhost.mydomain)
LDAP server port	(Example: 389)
Admin user	(Example: orcladmin)
Admin password	
Realm Name	(Example: us)
Realm DN	(Example: dc=us,dc=mycompany,dc=com)

Additionally, you need to know if the LDAP server port uses the Secure Socket Layer (SSL) to establish connections.

This information is used during the ORW application installation.

LDAP Data Utility

The ORW LDAP Data Utility creates Lightweight Directory Interface Files (LDIFs) to specify the data loaded into the LDAP. The tool may execute the ldapadd utility to actually load the data or you may perform this step manually.

The ORW LDAP Data utility is responsible for creating the following required data used by the ORW application:

- The ORW application login entries.
- Permission grants to the ADF anyone role to allow unauthenticated access to the main ORW JSPX page.
- The Retail_Workspace_Users group and the Workspace administrators group.
- Permission grants to the Workspace administrators group and those for all ORW users.

Additionally, the ORW LDAP Data utility can create sample users, groups and permission grants that can access the sample dashboards.

The behavior of the tool is controlled by the file, `ldap_util.properties`. These properties are:

Property: `ldap.host`

Example: `ldap.host=localhost`

Description: Specifies the host name where the OID server is located. Only used if the property `"execute.ldap.scripts"` is set to `"true"`.

Property: `ldap.port`

Example: `ldap.port=389`

Description: Specifies the TCP port number for the OID LDAP interface. Only used if the property `"execute.ldap.scripts"` is set to `"true"`.

Property: `ldap.user.dn`

Example: `ldap.user.dn=cn=orcladmin`

Description: Specifies the Distinguished Name of the user the script will use to log into the OID LDAP server. This user must have the privileges necessary to create users, groups, and permission grants. Only used if the property `"execute.ldap.scripts"` is set to `"true"`.

Property: `ldap.ssl`

Example: `ldap.ssl=0`

Description: This property specifies the Secure Socket Layer (SSL) characteristic of the LDAP connection. A value of 0 specifies no SSL, 1 specifies SSL with neither server nor client authentication, 2 for one-way (server) authentication, and 3 for two-way authentication. Using a value of 2 or 3 requires additional setup outside the scope of this document. Only used if the property `"execute.ldap.scripts"` is set to `"true"`.

Property: `workspace.realm.name`

Example: `workspace.realm.name=us`

Description: This property specifies the realm name required by certain records, such as permission grants. This property is used by almost all targets.

Property: `workspace.realm.dn`

Example:

`workspace.realm.dn=dc=${workspace.realm.name},dc=<mycompany>,dc=com`

Description: This property specifies the distinguished name of the realm. All realm specific information is contained by this name. This includes all of the realm's users, groups, and grants made to these groups and users. This property is used by almost all targets.

Property: workspace.users.group

Example: workspace.users.group=Retail_Workspace_Users

Description: This property specifies Group name used to contain all ORW Users. All groups mentioned below must be members of this group. This entry has a dependency on the deployment descriptors used by the ORW application and Dashboards. Because of this dependency, changing the value of this property is not recommended.

Property: workspace.admins.group

Example: workspace.admins.group=DEMO_Workspace_Admin

Description: This property specifies the Group (aka role) name used for Retail Workspace administrators. ORW administrators are assumed to have the capabilities to manage the ORW application. Additional capabilities, such as the ability to create permission grants, users, or groups are assumed, but may have to be granted separately. The templates include the realm specific user named 'orcladmin' as part of this group.

Property: workspace.executives.group

Example: workspace.executives.group=DEMO_Executive

Description: This property specifies the Group (aka role) name used for "Executive" users. The sample templates grant Executive users' access to the Executive Dashboard. Other groups in the sample templates contain the Executive group, thus allowing an Executive user access to their functionality as well. These capabilities may be altered later via an ORW administrator.

Property: workspace.planners.group

Example: workspace.planners.group=DEMO_Planner

Description: This property specifies the Group (aka role) name used for "Planner" users. Planner users have access to specific applications and the "Planner" dashboard. The sample template's definition of the planner group includes the Executive group mentioned above.

Property: workspace.merchants.group

Example: workspace.merchants.group=DEMO_Merchant

Description: This property specifies the Group (aka role) name used for "Merchant" users. Merchant users have access to specific applications and the "Merchant" dashboard. The sample template's definition of the planner group includes the executive group mentioned above.

Property: workspace.stores.group

Example: workspace.stores.group=DEMO_Store_Manager

Description: This property specifies the Group (aka role) name used for "Store Manager" users. Store Manager users have access to specific applications and the "Store Manager" dashboard. The sample template's definition of the planner group includes the executive group mentioned above.

Property: workspace.password

Example: workspace.password=welcome1

Description: This property defines the default password used by the ORW users created in the "create-demo-users" target. These users (or an administrator) may change this password after they have been created.

Property: execute.ldap.scripts

Example: execute.ldap.scripts=false

Description: This property controls whether or not the LDIF created script is loaded into the OID LDAP. A value of "false" specifies the script to only create the LDIF script. A value of "true" specifies the script to create and load the LDIF script.

Note: Some scripts will contain password information and an administrator should either delete them after loading or limit access to these files.

Expand and Execute the ORW LDAP Data Utility

1. Log into the server running your OID installation.
2. Set your ORACLE_HOME environment variable to point to this OID installation.
3. Create a new staging directory for the ORW LDAP Data utility (orw-ldap-data.zip). There should be a minimum of 10MB disk space available for these files.

Example: /opt/oracle/retail/workspace/

This location is referred to as INSTALL_DIR for the remainder of this chapter.

4. Set your JAVA_HOME to \$ORACLE_HOME/jdk.
5. Copy orw-ldap-data.zip to INSTALL_DIR and extract its contents.
6. Change directories to INSTALL_DIR/workspace/ldap.

Example: cd /opt/oracle/retail/workspace/workspace/ldap

7. Set your ANT_HOME to the location where ANT was expanded.

Example:

```
ANT_HOME=`pwd`/ant
export ANT_HOME
```

8. Put the ANT_HOME/bin directory in your PATH variable so you can run the "ant" command from anywhere. This also overrides any other "ant" that may be found in your path.

Example:

```
PATH=$ANT_HOME/bin:$PATH
export PATH
```

9. Modify the ldap_util.properties file with the settings for your realm. This is where you need to provide the settings described in the previous section (Create or Locate Realm in Oracle Internet Directory).
10. Run the load_ldap_required_data.sh script. If the script is configured only to create the LDIF files, then you must load the files into the LDAP in the same order they were created which is as follows:

- setup_oracle_retail_app_user_id.ldif
 - create_anyone_grants.ldif
 - create_rw_admin_user_groups.ldif
 - create_admin_grants.ldif
 - create_rw_user_grants.ldif
11. (Optional) Run the load_ldap_demo_data.sh script. As in the previous script, you must load the files into the LDAP in the same order they were created if the ORW LDAP Utility is not configured to load the data itself. The order is as follows:
- create_demo_groups.ldif
 - create_demo_users.ldif
 - create_grants.ldif
12. Examine the ldif-errors.txt file for any errors that occurred during demo data creation.

Workspace Administrator Users

One group created by the ORW Data Utility is the Workspace administrators group. The name of this group is controlled by the ldap_util.properties file. After the required data is loaded, members of this group will have the necessary privileges to see and execute the Permissions Management page in the ORW application.

However, additional privileges are needed for actually managing permission grants. These privileges are granted to other, well known, groups found in an OID instance, such as the IASAdmins group or the OracleContextAdmins group.

In order for an administrator to use the Delegated Administration Services (DAS) application for user and group management, the user must belong to a group such as the OracleDASAdmin group.

The scripts used by the ORW Data Utility do not add any member to these groups. Membership to these groups may be achieved via LDIF scripts, the oidadmin utility or the DAS application.

There are separate groups which control access to realm-specific and non-realm specific permission grants. Privileges needed to create grants to the ADF Anyone role require membership to groups outside of any realm. The DAS application is specific to a single realm. Thus, to create a permission grant to the ADF Anyone role, one must be a member of a global group, such as the IASAdmins group (found at cn=iASAdmins,cn=Groups,cn=OracleContext) or the JAZNAdminGroup (found at cn=JAZNAdminGroup,cn=Groups,cn=JAZNContext,cn=Products,cn=OracleContext). Group membership for these groups can only be modified via the oidadmin tool or via LDIF scripts.

Retail Portlets Installation

The ORW application bundle includes a set of four JSR 168-compliant portlets: The Report portlet, the URL portlet; the RSS portlet and the OBIEEAlerts Portlet. These portlets are consumed by the ORW application by the example dashboards (also included in the ORW bundle).

This chapter describes the portlets installation process which configures and deploys these portlets to an OC4J instance with Oracle Webcenter extensions.

Create a New OC4J Instance and Group for Portlets

Skip to the next section if you are redeploying to an existing OC4J group in Oracle WebCenter 10.1.3.3.

The Retail Portlets application must be deployed to its own dedicated OC4J instance and group (See Appendix A for details). For instructions on how to create a new OC4J group and instance, see *Managing OC4J Instances in a Group* in the *Configuring and Managing Clusters and OC4J Groups* chapter of the *Oracle Application Server Administrator's Guide*.

1. Log into the server which is running your Oracle WebCenter installation. Set your ORACLE_HOME environment variable to point to this installation.
2. Choose a name for the new OC4J instance and group.

Example: portlets_oc4j
portlets_group

Create this OC4J instance and group as documented in the *Oracle Application Server Administrator's Guide*.

Example:

```
$ORACLE_HOME/bin/createinstance
-instanceName portlets_oc4j -groupName portlets_group
```

When prompted for the oc4jadmin password, provide the same administrative password you gave for the WebCenter installation. All OC4J instances running Oracle Retail applications must have the same oc4jadmin password.

3. If these portlets must contact URLs that require an HTTP proxy server, you need to set the following JVM system properties for the Portlets OC4J instance in \$ORACLE_HOME/opmn/conf/opmn.xml:

```
-Dhttp.proxyHost=myhost -Dhttp.proxyPort=7000
```

Substitute your proxy server host and port for the values above. These properties should go in the java-options section of start-parameters.

After making any change to opmn.xml you must reload OPMN

Example: \$ORACLE_HOME/opmn/bin/opmnctl reload

4. (This step required only if Retail Portlets will be installed on AIX 5.3) Be aware that Retail Portlets requires an upgrade of the Java version when running on AIX 5.3. The version must be at least JRE version 1.5 SR7. If Retail Portlets will be installed on AIX 5.3, then you need to modify the \$ORACLE_HOME/opmn/conf/opmn.xml to

upgrade the Java version that Retail Portlets uses. Locate the OC4J instance you just created for Retail Portlets, and add or modify the "java-bin" within the "start-parameters" section

Example:

```
<process-type id="portlets_oc4j" module-id="OC4J"
status="enabled">

  <module-data>

    <category id="start-parameters">

      <data id="java-bin"
value="path/to/JAVA_HOME/bin/java" />

      ...

    </category>

    ...

  </module-data>

  ...

</process-type>
```

-
-
- Force OPMN to reload the configuration file.

Example: \$ORACLE_HOME/opmn/bin/opmnctl reload

- Start the OC4J group. You can do this through the Enterprise Manager web interface, or on the command line using the opmnctl utility:

Example: \$ORACLE_HOME/opmn/bin/opmnctl @cluster
startproc ias-component=portlets_group

- Verify that the OC4J group was fully started. If you are using the Enterprise Manager web interface, the instance should have a green arrow indicating that it is running. On the command line, verify that the instance has a status of "Alive".

Example: \$ORACLE_HOME/opmn/bin/opmnctl status

If you are unable to start an OC4J instance after several attempts, try increasing the startup timeouts in ORACLE_HOME/opmn/conf/opmn.xml. If that does not help, consult the Oracle Application Server documentation for further assistance.

Associate OC4J with OID

Skip to the next section if you are redeploying to an existing OC4J group in Oracle WebCenter 10.1.3.3 whose instance is already associated with your OID server.

The ORW solution requires OID-based security on all OC4J instances running its applications. Before installing the portlets application you must associate the portlets OC4J instance with your OID server.

Follow the instructions provided in the Oracle Application Server 10g Security Guide. See the *Associate Oracle Internet Directory with OC4J* section of the *Oracle Identity Management* chapter. This involves providing the OID host and port to OC4J. You also need to provide a username and password for an admin user (for example, orcladmin) that OC4J uses to add its own entry to the directory.

The result of this operation is a `jazn.xml` file for the OC4J instance that contains the OID server host, port, and default realm. There is a new entry in the directory whose DN and encrypted password are stored in `jazn.xml` and used by the OC4J instance for authentication.

Note: Even though you are associating a particular OC4J instance (example: `portlets_oc4j`) with OID, the ASControl application might save the resulting settings in the `jazn.xml` file for the `home` instance instead. You must look at the `jazn.xml` files from both `portlets_oc4j` and the `home` OC4J instance. If only the `home` OC4J instance was updated with the OID details you need to copy the `jazn.xml` from the `home` instance to `portlets_oc4j`.

`jazn.xml` files are located in the
`$ORACLE_HOME/j2ee/<instance>/config/ directories.`

Restart the OC4J instance after making this change.

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster restartproc ias-component=portlets_group`

Expand the Retail Portlets Application Distribution

1. Log into the application server as the user who owns the WebCenter ORACLE_HOME installation.
2. Create a new staging directory for the Retail Portlets application distribution (RetailPortletsApplication.zip). There should be a minimum of 100 MB disk space available for the application installation files.

Example: `$ORACLE_HOME/j2ee/portlets_oc4j/portlets-staging`

This location is referred to as `INSTALL_DIR` for the remainder of this chapter.

3. Copy `RetailPortletsApplication.zip` to `INSTALL_DIR` and extract its contents.

Run the Retail Portlets Application Installer

Once you have an OC4J instance that is configured and started, you can run the Retail Portlets application installer. This installer configures and deploys the Portlets application.

Note: Appendix A contains details on every screen and field in the portlets installer.

1. Change directories to `INSTALL_DIR/workspace/portlets`.
2. Set the `ORACLE_HOME` and `JAVA_HOME` environment variables. `ORACLE_HOME` should point to your WebCenter installation. `JAVA_HOME` should point to the Java 5.0 (1.5.0) JDK located at `$ORACLE_HOME/jdk`.

Note: Java 1.5 (SR7) is required if you are using AIX 5.3.

3. If you are using an X server such as Exceed, set the `DISPLAY` environment variable so that you can run the installer in GUI mode (recommended). If you are not using an

X server, or the GUI is too slow over your network, unset the DISPLAY environment variable for text mode.

4. Run the install.sh script. This launches the installer. After installation is complete, a detailed installation log file is created; portletsinstall.<timestamp>.log.

Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it halts execution immediately. If you re-run the installer you are presented with the option to pre-load your previous inputs so that you do not need to type them again. You can also run the installer in silent mode to skip the installer screens entirely and use the generated ant.install.properties input file. See Appendix G of this document for instructions on silent mode.

See Appendix H of this document for some common installation errors.

Since the application installation is a full reinstall every time, any previous partial installs are overwritten by the successful installation.

Manual Deployment Option

Skip this section if you chose the default option of allowing the installer to complete installation to the application server.

The installer includes the option to configure the application locally and skip deployment to the application server. If this option is chosen, the installer makes the configured application files available under <INSTALL_DIR>/workspace/portlets/workspace13/configured-output/.

If you chose this installer option, you can complete the installation by following these steps:

1. Make sure there have not been any application server configuration changes since the installer was run. You can do this by comparing the backup files created by the installer in the staging area to the same files in the application server.

Example: diff
<INSTALL_DIR>/workspace/portlets/workspace13/configured-output/appserver/ORACLE_HOME/j2ee/myinstance/config/jazn.xml.200710300919
\$ORACLE_HOME/j2ee/myinstance/config/jazn.xml

If there are changes to the application server's configuration file, they should be merged into the local copy under configured-output before proceeding to the next step.

2. Inspect the contents of the <INSTALL_DIR>/workspace/portlets/workspace13/configured-output/appserver/ORACLE_HOME directory, and then overlay the files in the application server's ORACLE_HOME, using the same directory structure. This installs library files required by the application and required application server configuration changes.
3. Restart the OC4J group where Retail Portlets will be deployed.

Example: \$ORACLE_HOME/opmn/bin/opmnctl @cluster restartproc ias-component=portlets_group

4. Deploy the Retail Portlets ear file to the OC4J group using the Enterprise Manager web interface. The configured ear file is located at `<INSTALL_DIR>/workspace/portlets/workspace13/configured-output/RetailPortlets.ear`. When deploying the ear file, you should provide the same application name you gave to the installer. These values are stored in the `<INSTALL_DIR>/workspace/portlets/ant.install.properties` file by the installer for later reference.

Backups Created by Installer

The Retail Portlets application installer backs up some application files by renaming them with `<timestamp>` suffixes. This is done to prevent the removal of any custom changes you might have. These backup directories can be safely removed without affecting the current installation.

Example: RetailPortlets.200711011726

Test the Retail Portlets Application

After the application installer completes you should have a working Retail Portlets application installation. The portlets are consumed by other applications and do not have a user interface. However, you can at least verify that they are accessible by pointing a web browser to its Web Services URL
`http://<host>:<port>/<ctxroot>/portlets/wsrp2?WSDL`.

Example:
`http://myhost:7777/RetailPortlets/portlets/wsrp2?WSDL`

You should see XML data that is returned to the browser. If you get any HTTP errors accessing this document then there is a problem with your Portlets installation.

Example Dashboards Installation

The ORW application comes with a set of external example dashboards. External dashboards are independent J2EE applications that the ORW application pulls in and displays in its content panel. This release includes four external dashboards (Executive, Merchant, Stores, and Planner).

This chapter describes the example dashboards installation process which configures and deploys these dashboards to an OC4J instance with Oracle Webcenter extensions.

Note that the content of the portlets in the dashboards is not configured until the ORW application installation.

Please also note that these example dashboards are non-GA and therefore not supported.

Create a New OC4J Instance and Group for Dashboards

Skip to the next section if you are redeploying to an existing OC4J group in Oracle WebCenter 10.1.3.3.

The Retail Dashboards application must be deployed to its own dedicated OC4J instance and group (See Appendix B for details). For instructions on how to create a new OC4J group and instance, see *Managing OC4J Instances in a Group* in the *Configuring and Managing Clusters and OC4J Groups* chapter of the *Oracle Application Server Administrator's Guide*.

1. Log into the server which is running your Oracle WebCenter installation. Set your ORACLE_HOME environment variable to point to this installation.
2. Choose a name for the new OC4J instance and group.

Example: dashboards_oc4j
dashboards_group

Create this OC4J instance and group as documented in the *Oracle Application Server Administrator's Guide*.

Example:
\$ORACLE_HOME/bin/createinstance
-instanceName dashboards_oc4j -groupName
dashboards_group

When prompted for the oc4jadmin password, provide the same administrative password you gave for the WebCenter installation. All OC4J instances running Oracle Retail applications must have the same oc4jadmin password.

3. (This step required only if Retail Dashboards will be installed on AIX 5.3) Be aware that Retail Dashboards requires an upgrade of the Java version when running on AIX 5.3. The version must be at least JRE version 1.5 SR7. If Retail Dashboards will be installed on AIX 5.3, then you will need to modify the \$ORACLE_HOME/opmn/conf/opmn.xml to upgrade the Java version that Retail Dashboards uses. Locate the OC4J instance you just created for Retail Dashboards, and add or modify the "java-bin" within the "start-parameters" section

Example:

```

<process-type id="dashboards_oc4j" module-
id="OC4J" status="enabled">
  <module-data>
    <category id="start-parameters">
      <data id="java-bin"
value="path/to/JAVA_HOME/bin/java" />
      ...
    </category>
    ...
  </module-data>
  ...
</process-type>

```

4. Force OPMN to reload the configuration file.

Example: `$ORACLE_HOME/opmn/bin/opmnctl reload`

5. Start the OC4J group. You can do this through the Enterprise Manager web interface, or on the command line using the opmnctl utility:

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster startproc ias-component=dashboards_group`

6. Verify that the OC4J group was fully started. If you are using the Enterprise Manager web interface, the instance should have a green arrow indicating that it is running. On the command line, verify that the instance has a status of "Alive".

Example: `$ORACLE_HOME/opmn/bin/opmnctl status`

If you are unable to start an OC4J instance after several attempts, try increasing the startup timeouts in `ORACLE_HOME/opmn/conf/opmn.xml`. If that does not help, consult the Oracle Application Server documentation for further assistance.

Associate OC4J with OID

Skip to the next section if you are redeploying to an existing OC4J group in Oracle WebCenter 10.1.3.3 whose instance is already associated with your OID server.

The ORW solution requires OID-based security on all OC4J instances running its applications. Before installing the example dashboards you must associate the dashboards OC4J instance with your OID server.

Follow the instructions provided in the Oracle Application Server 10g Security Guide. See the *Associate Oracle Internet Directory with OC4J* section of the *Oracle Identity Management* chapter. This involves providing the OID host and port to OC4J. You also need to provide a username and password for an admin user (for example, orcladmin) that OC4J uses to add its own entry to the directory.

The result of this operation is a `jazn.xml` file for the OC4J instance that contains the OID server host, port, and default realm. There is a new entry in the directory whose DN and encrypted password is stored in `jazn.xml` and used by the OC4J instance for authentication.

Note: Even though you are associating a particular OC4J instance (example: *dashboards_oc4j*) with OID, the ASControl application might save the resulting settings in the jazn.xml file for the *home* instance instead. You must look at the jazn.xml files from both *dashboards_oc4j* and the *home* OC4J instance. If only the *home* OC4J instance was updated with the OID details you need to copy the jazn.xml from the *home* instance to *dashboards_oc4j*.

jazn.xml files are located in the
`$ORACLE_HOME/j2ee/<instance>/config/` directories.

Restart the OC4J instance after making this change.

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster restartproc ias-component=dashboards_group`

Expand the Retail Dashboards Distribution

1. Log into the application server as the user who owns the WebCenter ORACLE_HOME installation. Create a new staging directory for the Retail Dashboards application distribution (orw-dashboards.zip). There should be a minimum of 100 MB disk space available for the application installation files.

Example:
`$ORACLE_HOME/j2ee/dashboards_oc4j/dashboards-staging`

This location is referred to as `INSTALL_DIR` for the remainder of this chapter.

2. Copy `orw-dashboards.zip` to `INSTALL_DIR` and extract its contents.

Run the Retail Dashboards Installer

Once you have an OC4J instance that is configured and started, you can run the Retail Dashboards application installer. This installer configures and deploys the example dashboards.

Note: Appendix B contains details on every screen and field in the dashboards installer.

1. Change directories to `INSTALL_DIR/workspace/dashboards`.
2. Set the `ORACLE_HOME` and `JAVA_HOME` environment variables. `ORACLE_HOME` should point to your WebCenter installation. `JAVA_HOME` should point to the Java 5.0 (1.5.0) JDK located at `$ORACLE_HOME/jdk`.

Note: Java 1.5 (SR7) is required if you are using AIX 5.3.

3. If you are using an X server such as Exceed, set the `DISPLAY` environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset `DISPLAY` for text mode.
4. Run the `install.sh` script. This launches the installer. After installation is complete, a detailed installation log file is created: `dashboardsinstall.<timestamp>.log`.

Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it halts execution immediately. If you re-run the installer you are presented with the option to pre-load your previous inputs so that you do not need to type them again. You can also run the installer in silent mode to skip the installer screens entirely and use the generated `ant.install.properties` input file. See Appendix G of this document for instructions on silent mode.

See Appendix H of this document for some common installation errors.

Since the application installation is a full reinstall every time, any previous partial installs will be overwritten by the successful installation.

Manual Deployment Option

Skip this section if you chose the default option of allowing the installer to complete installation to the application server.

The installer includes the option to configure the application locally and skip deployment to the application server. If this option is chosen, the installer makes the configured application files available under `<INSTALL_DIR>/workspace/dashboards/workspace13/configured-output/`.

If you chose this installer option, you can complete the installation by following these steps:

1. Make sure there have not been any application server configuration changes since the installer was run. You can do this by comparing the backup files created by the installer in the staging area to the same files in the application server.

Example: diff
`<INSTALL_DIR>/workspace/dashboards/workspace13/configured-output/appserver/ORACLE_HOME/j2ee/myinstance/config/jazn.xml.200710300919`
`$ORACLE_HOME/j2ee/myinstance/config/jazn.xml`

If there are changes to the application server's configuration file, they should be merged into the local copy under `configured-output` before proceeding to the next step.

2. Inspect the contents of the `<INSTALL_DIR>/workspace/dashboards/workspace13/configured-output/appserver/ORACLE_HOME` directory, and then overlay the files in the application server's `ORACLE_HOME`, using the same directory structure. This installs library files required by the application and required application server configuration changes.
3. Restart the OC4J group where Retail Dashboards will be deployed.

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster restartproc ias-component=dashboards_group`

4. Deploy the Retail Dashboards ear files to the OC4J group using the Enterprise Manager web interface. The configured ear files are located at `<INSTALL_DIR>/workspace/dashboards/workspace13/configured-output/Demo*Dashboard.ear`. When deploying the ear files, you should provide the same application names you gave to the installer. These values are stored in the `<INSTALL_DIR>/workspace/dashboards/ant.install.properties` file by the installer for later reference.

5. Backups Created by Installer

The Retail Dashboards application installer backs up some application files by renaming them with <timestamp> suffixes. This is done to prevent the removal of any custom changes you might have. These backup directories can be safely removed without affecting the current installation.

Example: dashboards-mds-stores.200711011726

Test the Demo Dashboards Applications

Use the URLs supplied at the end of the Dashboards installation process.

Example:

<http://myhost:7777/ExecutiveDashboard/faces/DemoExecutiveDashboard.jspx>

<http://myhost:7777/MerchantDashboard/faces/DemoMerchantDashboard.jspx>

<http://myhost:7777/PlannerDashboard/faces/DemoPlannerDashboard.jspx>

<http://myhost:7777/StoresDashboard/faces/DemoStoresDashboard.jspx>

Paste each of the URLs in a browser window and click Go.

Type the login credentials when prompted. If you get a blank screen (this is an SSO bug) paste the URL in the same browser window and click Go. This should bring up the dashboard with errors or no content in the portlets. That is a successful test since the portlets need a number of parameters that are not supplied in this test.

BPEL Portlets Installation

The ORW application bundle includes a set of two PDK portlets: The ORWBPEL WorklistPortlet, and the ORWBPELWorkflowPortlet. The ORWBPELWorklistPortlet is cloned from the Worklist PDK portlet provided with the BPEL installation. These portlets are consumed by the ORWBPELPages application (also included in the ORW bundle and whose installation is described later).

This chapter describes the portlets installation process which configures and deploys these portlets to a SOA suite instance where BPEL is installed as a middleware service. These portlets must be deployed as a child application(ORWBPELportlets) under the 'orabpel' application in the SOA suite instance of the SOA suite OAS server.

Note: The BPEL Portlets must be installed on the SOA Suite OAS server.

Configure SOA Suite OC4J Instance

1. (Required only if BPEL Portlets will be installed on AIX 5.3) Be aware that BPEL Portlets requires an upgrade of the Java version when running on AIX 5.3. The version must be at least JRE version 1.5 SR7. If BPEL Portlets will be installed on AIX 5.3, then you will need to modify the \$ORACLE_HOME/opmn/conf/opmn.xml to upgrade the Java version that BPEL Portlets uses. Locate the OC4J instance for the SOA Suite, and add or modify the "java-bin" within the "start-parameters" section

Example:

```
<process-type id="oc4j_soa" module-id="OC4J"
status="enabled">
  <module-data>
    <category id="start-parameters">
      <data id="java-bin"
value="path/to/JAVA_HOME/bin/java"/>
      ...
    </category>
    ...
  </module-data>
  ...
</process-type>
```

2. Force OPMN to reload the configuration file.

Example: \$ORACLE_HOME/opmn/bin/opmnctl reload

Associate SOA Suite OC4J with OID

Skip to the next section if you are redeploying to an existing OC4J group in SAO Suite 10.1.3.3 whose instance is already associated with your OID server.

The ORW solution requires OID-based security on all OC4J instances running its applications. Before installing the BPEL Portlets, you must associate the SOA suite OC4J instance with your OID server.

Follow the instructions provided in the Oracle Application Server 10g Security Guide. See the *Associate Oracle Internet Directory with OC4J* section of the *Oracle Identity Management* chapter. This involves providing the OID host and port to OC4J. You also need to provide a username and password for an admin user (for example, orcladmin) that OC4J uses to add its own entry to the directory.

The result of this operation is a `jazn.xml` file for the OC4J instance that contains the OID server host, port, and default realm. There is a new entry in the directory whose DN and encrypted password is stored in `jazn.xml` and used by the OC4J instance for authentication.

Note: Even though you are associating a particular OC4J instance (example: `soa_oc4j`) with OID, the ASControl application might save the resulting settings in the `jazn.xml` file for the *home* instance instead. You must look at the `jazn.xml` files from both `soa_oc4j` and the *home* OC4J instance. If only the *home* OC4J instance was updated with the OID details you need to copy the `jazn.xml` from the *home* instance to `soa_oc4j`.

`jazn.xml` files are located in the
`$ORACLE_HOME/j2ee/<instance>/config/directories`.

Restart the OC4J instance after making this change.

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster restartproc ias-component=default_group`

Note: Since the ORWBPELPortles application uses 'orabpel' and 'hwservices' applications under SOA suite OC4J instance, make sure that these three applications (orabpel, hwservices, ORWBPELPortles) are associated with the same OID that WebCenter uses as a security provider

Expand the BPEL Portlets Distribution

1. Log into the application server as the user who owns the SOA Suite ORACLE_HOME installation. Create a new staging directory for the BPEL Portlets application distribution (`orw-bpel-portlets.zip`). There should be a minimum of 20 MB disk space available for the application installation files.

Example: `$ORACLE_HOME/j2ee/oc4j_soa/bpelportlets-staging`

This location is referred to as `INSTALL_DIR` for the remainder of this chapter.

2. Copy `orw-bpel-portlets.zip` to `INSTALL_DIR` and extract its contents.

Run the BPEL Portlets Installer

Once you have created your staging directory, you can run the BPEL Portlets application installer. This installer configures and deploys the BPEL Portlets application.

Note: Appendix C contains details on every screen and field in the BPEL Portlets installer.

1. Change directories to `INSTALL_DIR/workspace/bpelportlets`.
2. Set the `ORACLE_HOME` and `JAVA_HOME` environment variables. `ORACLE_HOME` should point to your SOA Suite. `JAVA_HOME` should point to the Java 5.0 (1.5.0) JDK located at `$ORACLE_HOME/jdk`.

Note: Java 1.5 (SR7) is required if you are using AIX 5.3.

3. If you are using an X server such as Exceed, set the `DISPLAY` environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset `DISPLAY` for text mode.
4. Run the `install.sh` script. This launches the installer. After installation is complete, a detailed installation log file is created: `bpelportlets-install.<timestamp>.log`.

Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it halts execution immediately. If you re-run the installer you are presented with the option to pre-load your previous inputs so that you do not need to type them again. You can also run the installer in silent mode to skip the installer screens entirely and use the generated `ant.install.properties` input file. See Appendix G of this document for instructions on silent mode.

See Appendix H of this document for some common installation errors.

Since the application installation is a full reinstall every time, any previous partial installs will be overwritten by the successful installation.

Manual Deployment Option

Skip this section if you chose the default option of allowing the installer to complete installation to the application server.

The installer includes the option to configure the application locally and skip deployment to the application server. If this option is chosen, the installer makes the configured application files available under

`<INSTALL_DIR>/workspace/bpelportlets/workspace13/configured-output/`.

If you chose this installer option, you can complete the installation by following these steps:

1. Make sure there have not been any application server configuration changes since the installer was run. You can do this by comparing the backup files created by the installer in the staging area to the same files in the application server.

Example: `diff <INSTALL_DIR>/workspace/bpelportlets
/workspace13/configured-
output/appserver/ORACLE_HOME/j2ee/myinstance/conf
ig/jazn.xml.200710300919
$ORACLE_HOME/j2ee/myinstance/config/jazn.xml`

If there are changes to the application server's configuration file, they should be merged into the local copy under configured-output before proceeding to the next step.

2. Inspect the contents of the <INSTALL_DIR>/workspace/bpelportlets /workspace13/configured-output/appserver/ORACLE_HOME directory, and then overlay the files in the application server's ORACLE_HOME, using the same directory structure. This installs library files required by the application and required application server configuration changes.
3. Restart the OC4J group where the BPEL Portlets application will be deployed.

Example: \$ORACLE_HOME/opmn/bin/opmnctl @cluster
restartproc ias-component=default_group

4. Deploy the BPEL Portlets ear files to the OC4J group using the Enterprise Manager web interface. Make sure that you choose "orabpel" as the parent application. If "orabpel" is not available as a parent application, you may be using the incorrect OC4J instance, or the SOA Suite is not set up correctly. The configured ear files are located at <INSTALL_DIR>/workspace/bpelportlets/workspace13/configured-output/ oretail-orwbpelportlets.ear. When deploying the ear files, you should provide the same application names you gave to the installer. These values are stored in the <INSTALL_DIR>/workspace/bpelportlets/ant.install.properties file by the installer for later reference.

Backups Created by Installer

The BPEL Portlets application installer backs up some application files by renaming them with <timestamp> suffixes. This is done to prevent the removal of any custom changes you might have. These backup directories can be safely removed without affecting the current installation.

Test the BPEL Portlets Application

Use the URL supplied at the end of the BPEL Portlets installation process.

Example:

<http://myhost:7777/ORWBPELPortlets/providers>

Paste the URL in a browser window and click Go. You should be able to see a test page verifying that BPEL Portlets is installed.

BPEL Pages Installation

The ORW application comes with a BPEL Pages application consisting of two pages, each consuming one of the BPEL PDK portlets described above. These pages are part of an independent J2EE application that the ORW application displays in its content area.

This chapter describes the BPEL Pages installation process which configures and deploys these pages to an OC4J instance with Oracle Webcenter extensions.

Create a New OC4J Instance and Group for BPEL Pages

Skip to the next section if you are redeploying to an existing OC4J group in Oracle WebCenter 10.1.3.3.

The BPEL Pages application must be deployed to its own dedicated OC4J instance and group (See Appendix D for details). For instructions on how to create a new OC4J group and instance, see *Managing OC4J Instances in a Group* in the *Configuring and Managing Clusters and OC4J Groups* chapter of the *Oracle Application Server Administrator's Guide*.

Note that this OC4J instance and group could belong in the same WebCenter installation as the one housing the ORW application itself.

1. Log into the server which is running your Oracle WebCenter installation. Set your ORACLE_HOME environment variable to point to this installation.
2. Choose a name for the new OC4J instance and group.

Example: bpelpages_oc4j
bpelpages_group

Create this OC4J instance and group as documented in the *Oracle Application Server Administrator's Guide*.

Example:
\$ORACLE_HOME/bin/createinstance
-instanceName bpelpages_oc4j -groupName
bpelpages_group

When prompted for the oc4jadmin password, provide the same administrative password you gave for the WebCenter installation. All OC4J instances running Oracle Retail applications must have the same oc4jadmin password.

3. (This step required only if BPEL Pages will be installed on AIX 5.3) Be aware that BPEL Pages requires an upgrade of the Java version when running on AIX 5.3. The version must be at least JRE version 1.5 SR7. If BPEL Pages will be installed on AIX 5.3, then you will need to modify the \$ORACLE_HOME/opmn/conf/opmn.xml to upgrade the Java version that BPEL Pages uses. Locate the OC4J instance you just created for BPEL Pages, and add or modify the "java-bin" within the "start-parameters" section

Example:

```
<process-type id="bpelpages_oc4j" module-
id="OC4J" status="enabled">
  <module-data>
    <category id="start-parameters">
```

```

<data id="java-bin"
value="path/to/JAVA_HOME/bin/java"/>
...
</category>
...
</module-data>
...
</process-type>

```

4. Force OPMN to reload the configuration file.

Example: `$ORACLE_HOME/opmn/bin/opmnctl reload`

5. Start the OC4J group. You can do this through the Enterprise Manager web interface, or on the command line using the opmnctl utility:

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster startproc ias-component=bpelpages_group`

6. Verify that the OC4J group was fully started. If you are using the Enterprise Manager web interface, the instance should have a green arrow indicating that it is running. On the command line, verify that the instance has a status of "Alive".

Example: `$ORACLE_HOME/opmn/bin/opmnctl status`

If you are unable to start an OC4J instance after several attempts, try increasing the startup timeouts in `ORACLE_HOME/opmn/conf/opmn.xml`. If that does not help, consult the Oracle Application Server documentation for further assistance.

Associate OC4J with OID

Skip to the next section if you are redeploying to an existing OC4J group in Oracle WebCenter 10.1.3.3 whose instance is already associated with your OID server.

The ORW solution requires OID-based security on all OC4J instances running its applications. Before installing the BPEL Pages, you must associate the BPEL Pages OC4J instance with your OID server.

Follow the instructions provided in the Oracle Application Server 10g Security Guide. See the *Associate Oracle Internet Directory with OC4J* section of the *Oracle Identity Management* chapter. This involves providing the OID host and port to OC4J. You also need to provide a username and password for an admin user (for example, orcladmin) that OC4J uses to add its own entry to the directory.

The result of this operation is a `jazn.xml` file for the OC4J instance that contains the OID server host, port, and default realm. There is a new entry in the directory whose DN and encrypted password is stored in `jazn.xml` and used by the OC4J instance for authentication.

Note: Even though you are associating a particular OC4J instance (example: *bpelpages_oc4j*) with OID, the ASControl application might save the resulting settings in the *jazn.xml* file for the *home* instance instead. You must look at the *jazn.xml* files from both *bpelpages_oc4j* and the *home* OC4J instance. If only the *home* OC4J instance was updated with the OID details you need to copy the *jazn.xml* from the *home* instance to *bpelpages_oc4j*.

jazn.xml files are located in the
`$ORACLE_HOME/j2ee/<instance>/config/directories.`

Restart the OC4J instance after making this change.

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster restartproc ias-component=bpelpages_group`

Expand the BPEL Pages Distribution

1. Log into the application server as the user who owns the WebCenter ORACLE_HOME installation. Create a new staging directory for the BPEL Pages application distribution (*orw-bpelpages-application.zip*). There should be a minimum of 20 MB disk space available for the application installation files.

Example:
`$ORACLE_HOME/j2ee/bpelpages_oc4j/bpelpages-staging`

This location is referred to as `INSTALL_DIR` for the remainder of this chapter.

2. Copy *orw-bpelpages-application.zip* to `INSTALL_DIR` and extract its contents.

Run the BPEL Pages Installer

Once you have an OC4J instance that is configured and started, you can run the BPEL Pages application installer. This installer configures and deploys the BPEL Pages application.

Note: Appendix D contains details on every screen and field in the BPEL Pages installer.

1. Change directories to `INSTALL_DIR/workspace/bpelpages`.
2. Set the `ORACLE_HOME` and `JAVA_HOME` environment variables. `ORACLE_HOME` should point to your WebCenter installation. `JAVA_HOME` should point to the Java 5.0 (1.5.0) JDK located at `$ORACLE_HOME/jdk`.

Note: Java 1.5 (SR7) is required if you are using AIX 5.3.

3. If you are using an X server such as Exceed, set the `DISPLAY` environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset `DISPLAY` for text mode.
4. Run the `install.sh` script. This launches the installer. After installation is complete, a detailed installation log file is created: `bpelpages-install.<timestamp>.log`.

Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it halts execution immediately. If you re-run the installer you are presented with the option to pre-load your previous inputs so that you do not need to type them again. You can also run the installer in silent mode to skip the installer screens entirely and use the generated `ant.install.properties` input file. See Appendix G of this document for instructions on silent mode.

See Appendix H of this document for some common installation errors.

Since the application installation is a full reinstall every time, any previous partial installs will be overwritten by the successful installation.

Manual Deployment Option

Skip this section if you chose the default option of allowing the installer to complete installation to the application server.

The installer includes the option to configure the application locally and skip deployment to the application server. If this option is chosen, the installer makes the configured application files available under `<INSTALL_DIR>/workspace/bpelpages/workspace13/configured-output/`.

If you chose this installer option, you can complete the installation by following these steps:

1. Make sure there have not been any application server configuration changes since the installer was run. You can do this by comparing the backup files created by the installer in the staging area to the same files in the application server.

Example: diff
`<INSTALL_DIR>/workspace/bpelpages/workspace13/configured-output/appserver/ORACLE_HOME/j2ee/myinstance/config/jazn.xml.200710300919`
`$ORACLE_HOME/j2ee/myinstance/config/jazn.xml`

If there are changes to the application server's configuration file, they should be merged into the local copy under `configured-output` before proceeding to the next step.

2. Inspect the contents of the `<INSTALL_DIR>/workspace/bpelpages/workspace13/configured-output/appserver/ORACLE_HOME` directory, and then overlay the files in the application server's `ORACLE_HOME`, using the same directory structure. This installs library files required by the application and required application server configuration changes.
3. Restart the OC4J group where BPEL Pages will be deployed.

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster restartproc ias-component=bpelpages_group`

4. Deploy the BPEL Pages ear file to the OC4J group using the Enterprise Manager web interface. The configured ear file is located at `<INSTALL_DIR>/workspace/bpelpages/workspace13/configured-output/oretail-orwbpelpages.ear`. When deploying the ear files, you should provide the same application names you gave to the installer. These values are stored in the `<INSTALL_DIR>/workspace/bpelpages/ant.install.properties` file by the installer for later reference.

Backups Created by Installer

The BPEL Pages application installer backs up some application files by renaming them with <timestamp> suffixes. This is done to prevent the removal of any custom changes you might have. These backup directories can be safely removed without affecting the current installation.

Example: bpelpages-mds-stores.200711011726

Test the BPEL Pages Application

Use the URLs supplied at the end of the BPEL Pages installation process.

Example:

`http://myhost:7777/ORWBPELPages/faces/ORWBPMWor
klist.jspx`

`http://myhost:7777/ORWBPELPages/faces/ORWBPELWo
rkflow.jspx`

Paste each of the URLs in a browser window and click Go.

Type the login credentials when prompted. If you get a blank screen (this is an SSO bug) paste the URL in the same browser window and click Go. This should bring up the corresponding application.

Oracle BI EE Alerts Application Installation

The ORW Oracle BI EE Alerts application in conjunction with ORW Oracle BI EE Alerts Portlet is used to display Oracle BI EE iBot Alerts for a user in ORW. The user can click on an alert headline to view the alert or on “Manage Alerts” link on the Portlet to view, clear and open the Alert.

This chapter describes the Oracle BI EE Alerts application installation process which configures and deploys this application to an OC4J instance.

Note: The Oracle BI EE Alerts application should be deployed on the same OAS which hosts the Oracle BI EE server. The reason is that the same origin policy of browsers does not allow the Oracle BI EE Alerts application to parse the Alerts published as RSS Feed by Oracle BI EE if it is deployed on a host which is different than Oracle BI EE.

Create a New OC4J Instance and Group for Oracle BI EE Alerts

The Oracle BI EE Alerts application must be deployed to its own dedicated OC4J instance and group (See Appendix E for details) on the same Oracle Application Server where Oracle BI EE is deployed. Create a new OC4J instance and group on Oracle Application Server where BI Presentation services are running.

For instructions on how to create a new OC4J group and instance, see *Managing OC4J Instances in a Group* in the *Configuring and Managing Clusters and OC4J Groups* chapter of the *Oracle Application Server Administrator's Guide*.

1. Log into the Oracle Application Server. Set your ORACLE_HOME environment variable to point to this installation.
2. Choose a name for the new OC4J instance and group.

Example: obieealerts_oc4j
obieealerts_group

Create this OC4J instance and group as documented in the *Oracle Application Server Administrator's Guide*.

Example:
\$ORACLE_HOME/bin/createinstance
-instanceName obieealerts_oc4j -groupName
obieealerts_group

When prompted for the oc4jadmin password, provide the same administrative password you gave for the oracle application server installation.

3. (This step required only if Oracle BI EE Alerts will be installed on AIX 5.3) Be aware that Oracle BI EE Alerts requires an upgrade of the Java version when running on AIX 5.3. The version must be at least JRE version 1.5 SR7. If Oracle BI EE Alerts will be installed on AIX 5.3, then you will need to modify the \$ORACLE_HOME/opmn/conf/opmn.xml to upgrade the Java version that Oracle BI EE Alerts uses. Locate the OC4J instance you just created for Oracle BI EE Alerts, and add or modify the "java-bin" within the "start-parameters" section

Example:

```

<process-type id="obieeaalerts_oc4j" module-
id="OC4J" status="enabled">
  <module-data>
    <category id="start-parameters">
      <data id="java-bin"
value="path/to/JAVA_HOME/bin/java" />
      ...
    </category>
    ...
  </module-data>
  ...
</process-type>

```

4. Force OPMN to reload the configuration file.

Example: `$ORACLE_HOME/opmn/bin/opmnctl reload`

5. Start the OC4J group. You can do this through the Enterprise Manager web interface, or on the command line using the opmnctl utility:

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster startproc ias-component=obieeaalerts_group`

6. Verify that the OC4J group was fully started. If you are using the Enterprise Manager web interface, the instance should have a green arrow indicating that it is running. On the command line, verify that the instance has a status of "Alive".

Example: `$ORACLE_HOME/opmn/bin/opmnctl status`

If you are unable to start an OC4J instance after several attempts, try increasing the startup timeouts in `ORACLE_HOME/opmn/conf/opmn.xml`. If that does not help, consult the Oracle Application Server documentation for further assistance.

Associate OC4J with OID

Skip to the next section if you are redeploying to an existing OC4J group in Oracle WebCenter 10.1.3.3 whose instance is already associated with your OID server.

The ORW solution requires OID-based security on all OC4J instances running its applications. Before installing the Oracle BI EE Alerts application you must associate the Oracle BI EE Alerts OC4J instance with your OID server.

Follow the instructions provided in the Oracle Application Server 10g Security Guide. See the *Associate Oracle Internet Directory with OC4J* section of the *Oracle Identity Management* chapter. This involves providing the OID host and port to OC4J. You also need to provide a username and password for an admin user (for example, orcladmin) that OC4J uses to add its own entry to the directory.

The result of this operation is a jazn.xml file for the OC4J instance that contains the OID server host, port, and default realm. There is a new entry in the directory whose DN and encrypted password are stored in jazn.xml and used by the OC4J instance for authentication.

Note: Even though you are associating a particular OC4J instance (example: *obieealerts_oc4j*) with OID, the ASControl application might save the resulting settings in the *jazn.xml* file for the *home* instance instead. You must look at the *jazn.xml* files from both *obieealerts_oc4j* and the *home* OC4J instance. If only the *home* OC4J instance was updated with the OID details you need to copy the *jazn.xml* from the *home* instance to *obieealerts_oc4j*.

jazn.xml files are located in the
`$ORACLE_HOME/j2ee/<instance>/config/` directories.

Restart the OC4J instance after making this change.

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster restartproc ias-component=obieealerts_group`

Expand the Oracle BI EE Alerts Distribution

1. Log into the application server as the user who owns the Oracle Application Server ORACLE_HOME installation. Create a new staging directory for the Oracle BI EE Alerts application distribution (*orw-obieealerts-application.zip*). There should be a minimum of 20 MB disk space available for the application installation files.

Example:
`$ORACLE_HOME/j2ee/obieealerts_oc4j/orwobieealerts-staging`

This location is referred to as `INSTALL_DIR` for the remainder of this chapter.

2. Copy *orw-obieealerts-application.zip* to `INSTALL_DIR` and extract its contents.

Run the Oracle BI EE Alerts Installer

Once you have a new OC4J instance that is configured and started on the OAS server where Oracle BI EE is installed, you can run the ORW Oracle BI EE Alerts application installer. This installer configures and deploys the ORW Oracle BI EE Alerts application.

Note: Appendix E contains details on every screen and field in the ORW Oracle BI EE Alerts installer.

1. Change directories to `INSTALL_DIR/workspace/obieealerts`.
2. Set the `ORACLE_HOME` and `JAVA_HOME` environment variables. `ORACLE_HOME` should point to your Oracle Application Server. `JAVA_HOME` should point to the Java 5.0 (1.5.0) JDK located at `$ORACLE_HOME/jdk`.

Note: Java 1.5 (SR7) is required if you are using AIX 5.3.

3. If you are using an X server such as Exceed, set the `DISPLAY` environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset `DISPLAY` for text mode.
4. Run the `install.sh` script. This launches the installer. After installation is complete, a detailed installation log file is created: `obieealerts-install.<timestamp>.log`.

Statically Protect Oracle BI EE Alerts Application

The Oracle BI EE Alerts application must be statically protected to provide user specific Alerts to be displayed in the Oracle BI EE Alerts portlet. In order to statically protect the application, modify `mod_osso.conf` to add lines.

```
<Location /ORWOBIEEAlerts>
  Header unset Pragma
  OsoSendCacheHeaders off
  AuthType Basic
  require valid-user
</Location>
```

where 'ORWOBIEEAlerts' is the context root where the application is deployed . If you changed the context root during installation of the ORWOBIEEAlerts application, change 'ORWOBIEEAlerts' above to the context-root you have specified during installation. If necessary, modify the `httpd.conf` file to include `mod_osso.conf` and restart HTTP Server.

Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it halts execution immediately. If you re-run the installer you are presented with the option to pre-load your previous inputs so that you do not need to type them again. You can also run the installer in silent mode to skip the installer screens entirely and use the generated `ant.install.properties` input file. See Appendix G of this document for instructions on silent mode.

See Appendix H of this document for some common installation errors.

Since the application installation is a full reinstall every time, any previous partial installs will be overwritten by the successful installation.

Manual Deployment Option

Skip this section if you chose the default option of allowing the installer to complete installation to the application server.

The installer includes the option to configure the application locally and skip deployment to the application server. If this option is chosen, the installer makes the configured application files available under

`<INSTALL_DIR>/workspace/obieealerts/workspace13/configured-output/`.

If you chose this installer option, you can complete the installation by following these steps:

1. Make sure there have not been any application server configuration changes since the installer was run. You can do this by comparing the backup files created by the installer in the staging area to the same files in the application server.

```
Example: diff <INSTALL_DIR>/workspace/ obieealerts
/workspace13/configured-
output/appserver/ORACLE_HOME/j2ee/myinstance/conf
ig/jazn.xml.200710300919
$ORACLE_HOME/j2ee/myinstance/config/jazn.xml
```

If there are changes to the application server's configuration file, they should be merged into the local copy under `configured-output` before proceeding to the next step.

2. Inspect the contents of the `<INSTALL_DIR>/workspace/ obieealerts /workspace13/configured-output/appserver/ORACLE_HOME` directory, and then overlay the files in the application server's `ORACLE_HOME`, using the same

directory structure. This installs library files required by the application and required application server configuration changes.

- Restart the OC4J group where the ORW Oracle BI EE Alerts application will be deployed.

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster
restartproc ias-component=orwobiealerts_group`

- Deploy the ORW Oracle BI EE Alerts ear files to the OC4J group using the Enterprise Manager web interface. The configured ear files are located at `<INSTALL_DIR>/workspace/obiealerts/workspace13/configured-output/oretail-obiealerts.ear`. When deploying the ear files, you should provide the same application names you gave to the installer. These values are stored in the `<INSTALL_DIR>/workspace/obiealerts/ant.install.properties` file by the installer for later reference.

Backups Created by Installer

The Oracle BI EE Alerts application installer backs up some application files by renaming them with `<timestamp>` suffixes. This is done to prevent the removal of any custom changes you might have. These backup directories can be safely removed without affecting the current installation.

Test the Oracle BI EE Alerts Applications

Use the URLs supplied at the end of the ORW Oracle BI EE Alerts installation process.

Example:

`http://myhost:7777/ORWOBIEEAlerts/faces/ORWOBIEE
AlertsDisplay.jsp?OBIEE_CONTEXT_ROOT=analytics`

where `OBIEE_CONTEXT_ROOT` is the context root where
OBIEE presentation services are deployed.

Paste the URL in a browser window and click Go.

Type the login credentials when prompted. You should be able see a list of your Ibot Alerts.

Workspace Application Installation

Create a New OC4J Instance and Group for ORW

Skip to the next section if you are redeploying to an existing OC4J group in Oracle WebCenter 10.1.3.3.

The ORW application must be deployed to its own dedicated OC4J instance and group (see Appendix F for details). For instructions on how to create a new OC4J group and instance, see *Managing OC4J Instances in a Group* in the *Configuring and Managing Clusters and OC4J Groups* chapter of the *Oracle Application Server Administrator's Guide*.

1. Log into the server which is running your Oracle WebCenter installation. Set your ORACLE_HOME environment variable to point to this installation.
2. Choose a name for the new OC4J instance and group.

Example: orw_oc4j
 orw_group

Create this OC4J instance and group as documented in the *Oracle Application Server Administrator's Guide*.

Example:
\$ORACLE_HOME/bin/createinstance
-instanceName orw_oc4j

-groupName orw_group

When prompted for the oc4jadmin password, provide the same administrative password you gave for the WebCenter installation. All OC4J instances running Oracle Retail applications must have the same oc4jadmin password.

3. (This step required only if ORW will be installed on AIX 5.3) Be aware that ORW requires an upgrade of the Java version when running on AIX 5.3. The version must be at least JRE version 1.5 SR7. If ORW will be installed on AIX 5.3, then you will need to modify the \$ORACLE_HOME/opmn/conf/opmn.xml to upgrade the Java version that ORW uses. Locate the OC4J instance you just created for ORW, and add or modify the "java-bin" within the "start-parameters" section

Example:

```
<process-type id="orw_oc4j" module-id="OC4J"
status="enabled">
  <module-data>
    <category id="start-parameters">
      <data id="java-bin"
value="path/to/JAVA_HOME/bin/java"/>
      ...
    </category>
    ...
  </module-data>
  ...
</process-type>
```

```
</process-type>
```

4. Force OPMN to reload the configuration file.

Example: \$ORACLE_HOME/opmn/bin/opmnctl reload

5. Start the OC4J group. You can do this through the Enterprise Manager web interface, or on the command line using the opmnctl utility:

Example: \$ORACLE_HOME/opmn/bin/opmnctl @cluster
startproc ias-component=orw_group

6. Verify that the OC4J group is fully started. If you are using the Enterprise Manager web interface, the instance should have a green arrow indicating that it is running. On the command line, verify that the instance has a status of "Alive".

Example: \$ORACLE_HOME/opmn/bin/opmnctl status

If you are unable to start an OC4J instance after several attempts, try increasing the startup timeouts in ORACLE_HOME/opmn/conf/opmn.xml. If that does not help, consult the Oracle Application Server documentation for further assistance.

Associate OC4J with OID

Skip to the next section if you are redeploying to an existing OC4J group in Oracle WebCenter 10.1.3.3 whose instance is already associated with your OID server.

The ORW solution requires OID-based security on all OC4J instances running its applications. Before installing the ORW application you must associate the ORW OC4J instance with your OID server.

Follow the instructions provided in the Oracle Application Server 10g Security Guide. See the *Associate Oracle Internet Directory with OC4J* section of the *Oracle Identity Management* chapter. This involves providing the OID host and port to OC4J. You also need to provide a username and password for an admin user (for example, orcladmin) that OC4J uses to add its own entry to the directory.

The result of this operation is a jazn.xml file for the OC4J instance that contains the OID server host, port, and default realm. There is a new entry in the directory whose DN and encrypted password is stored in jazn.xml and used by the OC4J instance for authentication.

Note: Even though you are associating a particular OC4J instance (example: *orw_oc4j*) with OID, the ASControl application might save the resulting settings in the jazn.xml file for the *home* instance instead. You must look at the jazn.xml files from both *orw_oc4j* and the *home* OC4J instance. If only the *home* OC4J instance was updated with the OID details you need to copy the jazn.xml from the *home* instance to *orw_oc4j*.

jazn.xml files are located in the
\$ORACLE_HOME/j2ee/<instance>/config/ directories.

Restart the OC4J instance after making this change.

Example: \$ORACLE_HOME/opmn/bin/opmnctl @cluster
restartproc ias-component=orw_group

Expand the ORW Distribution

1. Log into the application server as the user who owns the WebCenter ORACLE_HOME installation. Create a new staging directory for the ORW application distribution (RetailWorkspaceApplication.zip). There should be a minimum of 60 MB disk space available for the application installation files.

Example: \$ORACLE_HOME/j2ee/orw_oc4j/workspace-staging

This location is referred to as INSTALL_DIR for the remainder of this chapter.

2. Copy RetailWorkspaceApplication.zip to INSTALL_DIR and extract its contents.

Run the ORW Installer

Once you have an OC4J instance that is configured and started, you can run the ORW application installer. This installer configures and deploys the ORW application.

Note: Appendix F contains details on every screen and field in the workspace application installer.

1. Change directories to INSTALL_DIR/workspace/workspaceapp.
2. Set the ORACLE_HOME and JAVA_HOME environment variables. ORACLE_HOME should point to your WebCenter installation. JAVA_HOME should point to the Java 5.0 (1.5.0) JDK located at \$ORACLE_HOME/jdk.

Note: Java 1.5 (SR7) is required if you are using AIX 5.3.

3. If you are using an X server such as Exceed, set the DISPLAY environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset DISPLAY for text mode.
4. Run the install.sh script. This launches the installer. After installation is complete, a detailed installation log file is created: workspaceinstall.<timestamp>.log.

Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it halts execution immediately. If you re-run the installer you are presented with the option to pre-load your previous inputs so that you do not need to type them again. You can also run the installer in silent mode to skip the installer screens entirely and use the generated ant.install.properties input file. See Appendix G of this document for instructions on silent mode.

See Appendix H of this document for some common installation errors.

Since the application installation is a full reinstall every time, any previous partial installs are overwritten by the successful installation.

Oracle Configuration Manager

The Oracle Retail OCM Installer packaged with this release does not install the latest version of OCM. Oracle Retail recommends that retailers upgrade to the latest version of OCM from ARU. See OCM documentation for further instructions on how to automatically upgrade.

For more information, see the following:

My Oracle Support Note: 559539.1

The Oracle Configuration Manager Installer Guide describes the procedures and interface of the Oracle Retail Oracle Configuration Manager Installer that a retailer runs near the completion of its installation process.

OCM Documentation Link

<http://www.oracle.com/technology/documentation/ocm.html>

Manual Deployment Option

Skip this section if you chose the default option of allowing the installer to complete installation to the application server.

The installer includes the option to configure the application locally and skip deployment to the application server. If this option is chosen, the installer makes the configured application files available under `<INSTALL_DIR>/workspace/workspaceapp/workspace13/configured-output/`.

If you chose this installer option, you can complete the installation by following these steps:

1. Make sure there have not been any application server configuration changes since the installer was run. You can do this by comparing the backup files created by the installer in the staging area to the same files in the application server.

```
Example: diff
<INSTALL_DIR>/workspace/workspaceapp/workspace13
/configured-
output/appserver/ORACLE_HOME/j2ee/myinstance/conf
ig/jazn.xml.200710300919
$ORACLE_HOME/j2ee/myinstance/config/jazn.xml
```

If there are changes to the application server's configuration file, they should be merged into the local copy under `configured-output` before proceeding to the next step.

2. Inspect the contents of the `<INSTALL_DIR>/workspace/workspaceapp/workspace13/configured-output/appserver/ORACLE_HOME` directory, and then overlay the files in the application server's `ORACLE_HOME`, using the same directory structure. This installs library files required by the application and required application server configuration changes.
3. Restart the OC4J group where Retail Workspace will be deployed.

```
Example: $ORACLE_HOME/opmn/bin/opmnctl @cluster
restartproc ias-component=orw_group
```

4. Deploy the Retail Workspace ear file to the OC4J group using the Enterprise Manager web interface. The configured ear file is located at `<INSTALL_DIR>/workspace/workspaceapp/workspace13/configured-output/RetailWorkspace.ear`. When deploying the ear file, you should provide the same application name you gave to the installer. This value is stored in the `<INSTALL_DIR>/workspace/workspaceapp/ant.install.properties` file by the installer for later reference.

Backups Created by Installer

The ORW application installer backs up some application files by renaming them with `<timestamp>` suffixes. This is done to prevent the removal of any custom changes you might have. These backup directories can be safely removed without affecting the current installation.

Example: `RetailWorkspace.200711011726`

Test the ORW Application

After the application installer completes you should have a working ORW application installation. You can test this by accessing the front page of the application.

`http://<host>:<port>/<ctxroot>`

Example: `http://myhost:7777/RetailWorkspace`

Appendix: Portlets Application Installer Screens

You need the following details about your environment for the installer to successfully deploy the Retail Portlets application. Depending on the options you select, you may not see some screens or fields.

Screen: HTTP Proxy Server




This is an informational screen that explains a manual configuration requirement if you are using an HTTP proxy server for your portlets.

Screen: Application Server Details – Oracle WebCenter



Fields on this screen:

Field Title	Hostname
Field Description	Application server host
Example	Myhost
Field Title	OPMN request port
Field Description	Port on which OPMN listens for requests to forward on to OC4J instances. This port can be found in the ORACLE_HOME/opmn/conf/opmn.xml file: <code><port local="6100" remote="6200" request="6003"/></code> The installer attempts to present a default value that matches your environment.
Example	6003

Screen: Manual Deployment Option**Fields on this screen:**

Field Title	Install files to app server?
Field Description	If you do not have write access under ORACLE_HOME, you can still use the installer to gather your settings and configure the portlets files locally in the staging area. Then, at a later time, an administrator can manually copy over the portlets files and deploy the ear file. If you select this option, instructions are printed to the console and the installer log file for the steps needed to complete the installation.

Screen: OC4J Instance and Group

ORACLE

OC4J Instance and Group

Enter the name of the OC4J instance to which the application will be deployed

Portlets OC4J instance

The OC4J instance for portlets must belong to an OC4J group created specifically for this portlets deployment. This installer will deploy the portlets into the group. You must have a group with just one member OC4J instance. Do NOT use default_group in this field.

Portlets OC4J group

Fields on this screen:

Field Title	Portlets OC4J instance
Field Description	Name of the OC4J instance that was created for the portlets application.
Example	portlets_oc4j
Field Title	Portlets OC4J group
Field Description	Name of the OC4J group that was created for this portlets application. The OC4J instance given for the Portlets OC4J Instance field should be a member of this group. The installer deploys the portlets application to all OC4J instances which are members of this group. For this reason, you should not use default_group. A new group dedicated to portlets should be created instead.
Example	portlets_group

Screen: Application Deployment Details

Application Deployment Details

The default values shown below are examples

Enter the deployment name for this application. This is the name by which the application will be identified in the application server. IMPORTANT: The OC4J application name for these portlets must be unique across the Oracle Application Server environment.

Portlets app deployment name

Enter the web context root for this application. The web URL used by portlet consumers to access these portlets will be http://server:port/contextroot

Portlets context root

Cancel Back Next Install

Fields on this screen:

Field Title	Portlets app deployment name
Field Description	Name by which this portlets application is identified in the application server
Example	RetailPortlets
Field Title	Portlets context root
Field Description	Path relative to the HTTP server URL where the portlets are accessed.
Example	RetailPortlets

Screen: OC4J Administrative User

ORW 13 Portlets Installer - Oracle Retail

ORACLE

OC4J Administrative User

Enter the administrative user and password for the OC4J instance to which the application will be deployed.

OC4J admin user

OC4J admin password

Cancel Back Next Install

Fields on this screen:

Field Title	OC4J admin user
Field Description	Username of the admin user for OC4J instance to which the Portlets application is being deployed.
Example	oc4jadmin
Field Title	OC4J admin password
Field Description	Password for the OC4J admin user. You chose this password when you created the OC4J instance (managed OC4J) or when you started the instance for the first time (standalone OC4J).

Appendix: Dashboards Installer Screens

You need the following details about your environment for the installer to successfully deploy the Example Dashboards applications. Depending on the options you select, you may not see some screens or fields.

Screen: Application Server Details – Oracle WebCenter

Fields on this screen:

Field Title	Hostname
Field Description	Application server host
Example	myhost

Field Title	OPMN request port
Field Description	Port on which OPMN listens for requests to forward on to OC4J instances. This port can be found in the ORACLE_HOME/opmn/conf/opmn.xml file: <pre><port local="6100" remote="6200" request="6003"/></pre> The installer attempts to present a default value that matches your environment.
Example	6003

Screen: Manual Deployment Option**Fields on this screen:**

Field Title	Install files to app server?
Field Description	If you do not have write access under ORACLE_HOME, you can still use the installer to gather your settings and configure the dashboard files locally in the staging area. Then, at a later time, an administrator can manually copy over the dashboard files and deploy the ear file. If you select this option, instructions are printed to the console and the installer log file for the steps needed to complete the installation.

Screen: Application Names

Fields on this screen:

Field Title	Executive Dashboard
Field Description	Name by which the Executive Dashboard application is identified in the application server
Example	DemoExecutiveDashboardApp
Field Title	Merchant Dashboard
Field Description	Name by which the Merchant Dashboard application is identified in the application server
Example	DemoMerchantDashboardApp
Field Title	Stores Dashboard
Field Description	Name by which the Stores Dashboard application is identified in the application server
Example	DemoStoresDashboardApp

Field Title	Planner Dashboard
Field Description	Name by which the Planner Dashboard application is identified in the application server
Example	DemoPlannerDashboardApp

Screen: OC4J Instance and Group

OC4J Instance and Group

Enter the name of the OC4J instance to which the dashboards will be deployed

Dashboards OC4J instance

The OC4J instance for dashboards must belong to an OC4J group created specifically for this dashboards deployment. This installer will deploy the dashboards into the group. You must have a group with just one member OC4J instance. Do NOT use default_group in this field.

Dashboards OC4J group

Cancel Back Next Install

Fields on this screen:

Field Title	Dashboards OC4J instance
Field Description	Name of the OC4J instance that was created for the dashboard applications.
Example	dashboards_oc4j
Field Title	Dashboards OC4J group
Field Description	Name of the OC4J group that was created for these dashboard applications. The OC4J instance given for the Dashboards OC4J Instance field should be a member of this group. The installer deploys the dashboard applications to all OC4J instances which are members of this group. For this reason, you should not use default_group. A new group dedicated to dashboards should be created instead.
Example	dashboards_group

Screen: Context Roots

Context Roots

A web context root determines how an application will be accessed via an HTTP URL (i.e. http://host:port/contextroot). Enter context roots below.

Executive Dashboard	ExecutiveDashboard
Merchant Dashboard	MerchantDashboard
Stores Dashboard	StoresDashboard
Planner Dashboard	PlannerDashboard

Cancel Back Next Install

Fields on this screen:

Field Title	Executive Dashboard
Field Description	Path relative to the HTTP server URL where the Executive Dashboard is accessed.
Example	ExecutiveDashboard
Field Title	Merchant Dashboard
Field Description	Path relative to the HTTP server URL where the Merchant Dashboard is accessed.
Example	MerchantDashboard
Field Title	Stores Dashboard
Field Description	Path relative to the HTTP server URL where the Stores Dashboard is accessed.
Example	StoresDashboard

Field Title	Planner Dashboard
Field Description	Path relative to the HTTP server URL where the Planner Dashboard is accessed.
Example	PlannerDashboard

Screen: OC4J Administrative User

OC4J Administrative User

Enter the administrative user and password for the OC4J instance to which the application will be deployed.

OC4J admin user

OC4J admin password

Fields on this screen:

Field Title	OC4J admin user
Field Description	Username of the admin user for OC4J instance to which the dashboard applications are being deployed.
Example	oc4jadmin
Field Title	OC4J admin password
Field Description	Password for the OC4J admin user. You chose this password when you created the OC4J instance (managed OC4J) or when you started the instance for the first time (standalone OC4J).

Screen: Dashboards MDS Directories

Dashboards MDS Directories

MDS (MetaData Services) is a feature of Oracle WebCenter applications that is used to store metadata required for the WebCenter application and the portlets displayed in the application. By default the ORW application and dashboards use file-based MDS. You must provide a separate MDS directory path for each of the dashboards.

Executive Dashboard MDS Dir	oc4j/dashboards-mds-executive	Select Folder
Merchant Dashboard MDS Dir	oc4j/dashboards-mds-merchant	Select Folder
Stores Dashboard MDS Dir	/s_oc4j/dashboards-mds-stores	Select Folder
Planner Dashboard MDS Dir	/_oc4j/dashboards-mds-planner	Select Folder

Cancel Back Next Install

Fields on this screen:

Field Title	Executive Dashboard MDS Dir
Field Description	Path to a directory that is used to store MDS data for the Executive Dashboard. If this directory already exists the installer backs it up with a timestamp suffix and creates a new one in its place. Note: Each Dashboard's MDS directory must be unique.
Example	/path/to/ORACLE_HOME/j2ee/dashboards_oc4j/dashboards-mds-executive
Field Title	Merchant Dashboard MDS Dir
Field Description	Path to a directory that is used to store MDS data for the Merchant Dashboard. If this directory already exists the installer backs it up with a timestamp suffix and creates a new one in its place. Note: Each Dashboard's MDS directory must be unique.
Example	/path/to/ORACLE_HOME/j2ee/dashboards_oc4j/dashboards-mds-merchant

Field Title	Stores Dashboard MDS Dir
Field Description	Path to a directory that is used to store MDS data for the Stores Dashboard. If this directory already exists the installer backs it up with a timestamp suffix and creates a new one in its place. Note: Each Dashboard's MDS directory must be unique.
Example	/path/to/ORACLE_HOME/j2ee/dashboards_oc4j/dashboards-mds-stores

Field Title	Planner Dashboard MDS Dir
Field Description	Path to a directory that is used to store MDS data for the Planner Dashboard. If this directory already exists the installer backs it up with a timestamp suffix and creates a new one in its place. Note: Each Dashboard's MDS directory must be unique.
Example	/path/to/ORACLE_HOME/j2ee/dashboards_oc4j/dashboards-mds-planner

Screen: Portlets
Fields on this screen:

Field Title	Portlets Web Services URL
Field Description	<p>Web services URL used to access the retail portlets. The XML obtained through this URL provides abstract information about the deployed portlet producer. This URL corresponds to the Retail Portlets install also covered in this document.</p> <p>This URL uses the following format <code>http://<portletshost>:<httpport>/<contextroot>/portlets/wsrp2?WSDL</code></p> <p>Note: You can test this URL in a web browser. You should see an XML document that is returned when you access the URL.</p>
Example	<code>http://myportletshost:7777/RetailPortlets/portlets/wsrp2?WSDL</code>
Field Title	Use proxy?
Field Description	Check box true/false field to indicate whether or not an HTTP proxy server must be used to access the portlets in your environment.

Screen: Portlets Proxy Settings

Fields on this screen:

Field Title	Portlets HTTP proxy host
Field Description	Host of the HTTP proxy server.
Example	myproxyhost
Notes	This screen depends on checking the “Use proxy?” box in the previous Portlets screen and will not be displayed if it is unchecked.
Field Title	Portlets HTTP proxy port
Field Description	Port of the HTTP proxy server.
Example	80
Notes	This screen depends on checking the “Use proxy?” box in the previous Portlets screen and will not be displayed if it is unchecked.

Appendix: BPEL Portlets Installer Screens

You need the following details about your environment for the installer to successfully deploy the BPEL Portlets application.

Screen: Application Server Details – Oracle WebCenter

ORACLE®

Application Server Details – Oracle Application Server

Hostname

The OPMN request port is found in ORACLE_HOME/opmn/conf/opmn.xml

OPMN request port


Cancel Back Next Install

Fields on this screen:

Field Title	Hostname
Field Description	Application server host
Destination	
Example	myhost

Field Title	OPMN request port
Field Description	Port on which OPMN listens for requests to forward on to OC4J instances. This port can be found in the ORACLE_HOME/opmn/conf/opmn.xml file: <pre><port local="6100" remote="6200" request="6003"/></pre> The installer attempts to present a default value that matches your environment.
Destination	
Example	6003

Screen: Manual Deployment Option



Fields on this screen:

Field Title	Install files to app server?
Field Description	If you do not have write access under ORACLE_HOME, you can still use the installer to gather your settings and configure the BPEL Portlets files locally in the staging area. Then, at a later time, an administrator can manually copy over the BPEL Portlets files and deploy the ear file. If you select this option, instructions are printed to the console and the installer log file for the steps needed to complete the installation.
Destination	

Screen: Oracle SOA Suite

Oracle SOA Suite

BPEL Portlets must be deployed to an OC4J instance that contains the Oracle SOA Suite.

Enter the name of the OC4J instance that the Oracle SOA Suite is currently deployed under.

SOA Suite OC4J instance

Enter the name of the OC4J group containing the SOA Suite OC4J instance.

SOA Suite OC4J group

Fields on this screen:

Field Title	SOA Suite OC4J instance
Field Description	Name of the OC4J instance where the Oracle Service-Oriented Architecture (SOA) Suite is located. This OC4J instance will also contain the BPEL Portlets application.
Example	oc4j_soa
Field Title	SOA Suite OC4J group
Field Description	Name of the SOA Suite OC4J group. The OC4J instance given for the SOA Suite OC4J Instance field should be a member of this group.
Example	default_group

Screen: Application Deployment Details

Application Deployment Details

The default values shown below are examples

Enter the deployment name for this application. This is the name by which the application will be identified in the application server. **IMPORTANT:** The OC4J application name for this application must be unique across the Oracle Application Server environment.

BPEL Portlets app name


Enter the web context root for this application. The web URL used to access this application will be http://server:port/contextroot

BPEL Portlets context root

Fields on this screen:

Field Title	BPEL Portlets app name
Field Description	Name by which this BPEL Portlets application is identified in the application server.
Example	ORWBPELPortlets
Field Title	BPEL Portlets context root
Field Description	Path relative to the HTTP server URL where the BPEL Portlets application is accessed.
Example	ORWBPELPortlets

Screen: OC4J Administrative User



Fields on this screen:

Field Title	OC4J admin user
Field Description	Username of the admin user for OC4J instance to which the BPEL Portlets application is being deployed.
Example	oc4jadmin
Field Title	OC4J admin password
Field Description	Password for the OC4J admin user. You chose this password when you created the OC4J instance (managed OC4J) or when you started the instance for the first time (standalone OC4J).

Appendix: BPEL Pages Installer Screens


You need the following details about your environment for the installer to successfully deploy the BPEL Pages application. Depending on the options you select, you may not see some screens or fields.

Screen: Application Server Details – Oracle WebCenter

Fields on this screen:


Field Title	Hostname
Field Description	Application server host
Example	Myhost

Field Title	OPMN request port
Field Description	Port on which OPMN listens for requests to forward on to OC4J instances. This port can be found in the ORACLE_HOME/opmn/conf/opmn.xml file: <pre><port local="6100" remote="6200" request="6003"/></pre> The installer attempts to present a default value that matches your environment.
Example	6003

Screen: Manual Deployment Option**Fields on this screen:**

Field Title	Install files to app server?
Field Description	If you do not have write access under ORACLE_HOME, you can still use the installer to gather your settings and configure the BPEL Pages files locally in the staging area. Then, at a later time, an administrator can manually copy over the BPEL Pages files and deploy the ear file. If you select this option, instructions are printed to the console and the installer log file for the steps needed to complete the installation.

Screen: OC4J Instance and Group



Fields on this screen:

Field Title	BPEL Pages OC4J instance
Field Description	Name of the OC4J instance that was created for the BPEL Pages application.
Example	bpelpages_oc4j
Field Title	BPEL Pages OC4J group
Field Description	Name of the OC4J group that was created for this BPEL Pages application. The OC4J instance given for the BPEL Pages OC4J Instance field should be a member of this group. The installer deploys the application to all OC4J instances which are members of this group. For this reason, you should not use default_group. A new group dedicated to BPEL Pages should be created instead.
Example	bpelpages_group

Screen: Application Deployment Details

Application Deployment Details

The default values shown below are examples

Enter the deployment name for this application. This is the name by which the application will be identified in the application server. IMPORTANT: The OC4J application name for this application must be unique across the Oracle Application Server environment.

BPEL Pages app name

Enter the web context root for this application. The web URL used to access this application will be http://server:port/contextroot

BPEL Pages context root

Cancel Back Next Install

Fields on this screen:

Field Title	BPEL Pages app name
Field Description	Name by which this BPEL Pages application is identified in the application server.
Example	ORWBPELPages
Field Title	BPEL Pages context root
Field Description	Path relative to the HTTP server URL where the BPEL Pages application is accessed.
Example	ORWBPELPages

Screen: OC4J Administrative User

ORW 13 BPEL Pages Installer - Oracle Retail

ORACLE

OC4J Administrative User

Enter the administrative user and password for the OC4J instance to which the application will be deployed.

OC4J admin user

OC4J admin password

Cancel Back Next Install

Fields on this screen:

Field Title	OC4J admin user
Field Description	Username of the admin user for OC4J instance to which the BPEL Pages application is being deployed.
Example	oc4jadmin
Field Title	OC4J admin password
Field Description	Password for the OC4J admin user. You chose this password when you created the OC4J instance (managed OC4J) or when you started the instance for the first time (standalone OC4J).

Screen: MDS Directories**Fields on this screen:**

Field Title	MDS Directory
Field Description	Path to a directory that is used to store MDS data for the BPEL Pages application. If this directory already exists the installer backs it up with a timestamp suffix and creates a new one in its place.
Example	/path/to/ORACLE_HOME/j2ee/bpepages_oc4j/bpepages-mds

Screen: BPEL Portlets



Fields on this screen:

Field Title	BPEL Portlets Web Services URL
Field Description	<p>Web services URL used to access the BPEL Portlets. The XML obtained through this URL provides abstract information about the deployed portlet producer. This URL corresponds to the BPEL Portlets install also covered in this document.</p> <p>This URL uses the following format <code>http://<portletshost>:<httpport>/<contextroot>/providers</code></p> <p>Note: You can test this URL in a web browser. You should see a document with the text "Congratulations! You have successfully reached your Provider's Test Page." when you access the URL.</p>
Example	<code>http://myhost:7777/ORWBPELPortlets/providers</code>
Field Title	Use proxy?
Field Description	Check box true/false field to indicate whether or not an HTTP proxy server must be used to access the BPEL Portlets in your environment.

Screen: BPEL Portlets Proxy Settings

ORACLE®

BPEL Portlets Proxy Settings

Enter the proxy server settings for BPEL Portlets.

BPEL Portlets HTTP proxy host

BPEL Portlets HTTP proxy port

Cancel Back Next Install

Fields on this screen:

Field Title	Portlets HTTP proxy host
Field Description	Host of the HTTP proxy server.
Example	myproxyhost
Notes	This screen depends on checking the “Use proxy?” box in the previous BPEL Portlets screen and will not be displayed if it is unchecked.
Field Title	Portlets HTTP proxy port
Field Description	Port of the HTTP proxy server.
Example	80
Notes	This screen depends on checking the “Use proxy?” box in the previous BPEL Portlets screen and will not be displayed if it is unchecked.

Appendix: Oracle BI EE Alerts Installer Screens


You need the following details about your environment for the installer to successfully deploy the Oracle BI EE Alerts application.

Screen: Application Server Details – Oracle WebCenter

Fields on this screen:


Field Title	Hostname
Field Description	Application server host
Example	Myhost

Field Title	OPMN request port
Field Description	Port on which OPMN listens for requests to forward on to OC4J instances. This port can be found in the ORACLE_HOME/opmn/conf/opmn.xml file: <pre><port local="6100" remote="6200" request="6003"/></pre> The installer attempts to present a default value that matches your environment.
Example	6003

Screen: Manual Deployment Option**Fields on this screen:**

Field Title	Install files to app server?
Field Description	If you do not have write access under ORACLE_HOME, you can still use the installer to gather your settings and configure the Oracle BI EE Alerts files locally in the staging area. Then, at a later time, an administrator can manually copy over the Oracle BI EE Alerts files and deploy the ear file. If you select this option, instructions are printed to the console and the installer log file for the steps needed to complete the installation.

Screen: OC4J Instance and Group



Fields on this screen:

Field Title	Oracle BI EE Alerts OC4J instance
Field Description	Name of the OC4J instance that was created for the ORW Oracle BI EE Alerts application.
Example	obieealerts_oc4j
Field Title	Oracle BI EE Alerts OC4J group
Field Description	Name of the OC4J group that was created for this ORW Oracle BI EE Alerts application. The OC4J instance given for the ORW Oracle BI EE Alerts OC4J Instance field should be a member of this group. The installer deploys the application to all OC4J instances which are members of this group. For this reason, you should not use default_group. A new group dedicated to ORW Oracle BI EE Alerts should be created instead.
Example	obieealerts_group

Screen: Application Deployment Details

Application Deployment Details

The default values shown below are examples

Enter the deployment name for this application. This is the name by which the application will be identified in the application server. IMPORTANT: The OC4J application name for this application must be unique across the Oracle Application Server environment.

OBIEE Alerts app name

Enter the web context root for this application. The web URL used to access this application will be http://server:port/contextroot


OBIEE Alerts context root

Cancel Back Next Install

Fields on this screen:

Field Title	Oracle BI EE Alerts app name
Field Description	Name by which this Oracle BI EE Alerts application is identified in the application server.
Example	ORWOBIEEAlerts
Field Title	Oracle BI EE Alerts context root
Field Description	Path relative to the HTTP server URL where the Oracle BI EE Alerts application is accessed.
Example	ORWOBIEEAlerts

Screen: OC4J Administrative User



Fields on this screen:

Field Title	OC4J admin user
Field Description	Username of the admin user for OC4J instance to which the Oracle BI EE Alerts application is being deployed.
Example	oc4jadmin
Field Title	OC4J admin password
Field Description	Password for the OC4J admin user. You chose this password when you created the OC4J instance (managed OC4J) or when you started the instance for the first time (standalone OC4J).

Appendix: Workspace Installer Screens


You need the following details about your environment for the installer to successfully deploy the ORW application. Depending on the options you select, you may not see some screens or fields.

Screen: Application Server Details – Oracle WebCenter

Fields on this screen:

Field Title	Hostname
Field Description	Application server host
Example	myhost

Field Title	HTTP Port
Field Description	<p>Port on which OC4J listens for HTTP requests. This port can be found in the ORACLE_HOME/Apache/Apache/conf/httpd.conf file for enterprise OC4J containers:</p> <p>Listen 8888</p> <p>Or in the ORACLE_HOME/j2ee/home/config/default-web-site.xml file otherwise:</p> <pre><web-site ... port="8888" ... ></pre> <p>The installer attempts to present a default value that matches your environment.</p>
Example	8888
Field Title	OPMN request port
Field Description	<p>Port on which OPMN listens for requests to forward on to OC4J instances. This port can be found in the ORACLE_HOME/opmn/conf/opmn.xml file:</p> <pre><port local="6100" remote="6200" request="6003"/></pre> <p>The installer attempts to present a default value that matches your environment.</p>
Example	6003

Screen: Manual Deployment Option**Fields on this screen:**

Field Title	Install files to app server?
Field Description	If you do not have write access under ORACLE_HOME, you can still use the installer to gather your settings and configure the ORW files locally in the staging area. Then, at a later time, an administrator can manually copy over the ORW files and deploy the ear file. If you select this option, instructions are printed to the console and the installer log file for the steps needed to complete the installation.

Screen: Application Deployment Details

Application Deployment Details

The default values shown below are examples

Enter the deployment name for this application. This is the name by which the application will be identified in the application server.

ORW app deployment name

Enter the web context root for this application. The web URL used to access ORW will be http://server:port/contextroot

ORW context root

Fields on this screen:

Field Title	ORW app deployment name
Field Description	Name by which this ORW application is identified in the application server
Example	orw
Field Title	ORW context root
Field Description	Path relative to the HTTP server URL where the ORW application is accessed.
Example	RetailWorkspace

Screen: OC4J Instance and Group

ORACLE

OC4J Instance and Group

Enter the name of the OC4J instance and group to which the application will be deployed

ORW OC4J instance

The OC4J instance for ORW must belong to an OC4J group created specifically for this ORW deployment. This installer will deploy the ORW application into the group. You must have a group with just one member OC4J instance. Do NOT use default_group in this field.

ORW OC4J group

Fields on this screen:

Field Title	ORW OC4J instance
Field Description	Name of the OC4J instance that was created for the ORW applications.
Example	orw_oc4j
Field Title	ORW OC4J group
Field Description	Name of the OC4J group that was created for the ORW application. The OC4J instance given for the ORW OC4J Instance field should be a member of this group. The installer deploys the ORW application to all OC4J instances which are members of this group. For this reason, you should not use default_group. A new group dedicated to ORW should be created instead.
Example	orw_group

Screen: OC4J Administrative User

OC4J Administrative User

Enter the administrative user and password for the OC4J instance to which the application will be deployed. The password field must be filled out to move on to the next screen.

OC4J admin user: oc4jadmin

OC4J admin password: *****

Buttons: Cancel, Back, Next, Install

Fields on this screen:

Field Title	OC4J admin user
Field Description	Username of the admin user for OC4J instance to which the ORW application is being deployed.
Example	oc4jadmin
Field Title	OC4J admin password
Field Description	Password for the OC4J admin user. You chose this password when you created the OC4J instance (managed OC4J) or when you started the instance for the first time (standalone OC4J).

Screen: Oracle Wallet

Oracle Wallet

An Oracle Wallet is an encrypted container used to store and retrieve sensitive information, such as user credentials. A new Wallet is created to contain passwords used by ORW, such as those for LDAP and the BIPublisher and OBIEE reports servers. Every Wallet is itself protected by a password, and the field for this Wallet password must be filled out to move on to the next screen.

Oracle Wallet password


Please re-enter password

Cancel Back Next Install

Fields on this screen:

Field Title	Oracle Wallet file password
Field Description	<p>Password for the new Oracle Wallet which is created during installation to hold several passwords used by the ORW application. This password is required to open the wallet and retrieve its contents.</p> <p>It is recommended that this password be at least 8 characters in length and contain both letters and numbers.</p>
Field Title	Please re-enter password
Field Description	Confirm the new Oracle Wallet password by re-entering it in this field.

Screen: ORW MDS Directory



Fields on this screen:

Field Title	ORW MDS Directory
Field Description	<p>Path to a directory that will be used to store MDS data for the ORW application. If this directory already exists the installer will back it up with a timestamp suffix and create a new one in its place.</p> <p>Note: MDS directories should not be shared between applications. The ORW MDS directory and the Example Dashboard MDS directories must each be unique.</p>
Example	/path/to/ORACLE_HOME/j2ee/orw_oc4j/workspace-mds

Screen: LDAP Directory Server

LDAP Directory Server

The ORW application and its dashboards use the OID (Oracle Internet Directory) LDAP directory server for user data. The ORW application has its own login to the LDAP server. The password for this login is stored in the Oracle Wallet under the ldap-user-pw alias. This password is also referred to in the ldap_util.properties file used in the creation of the ORW application login.

LDAP server host: [host]
 LDAP server port: 389
 LDAP login password: *****
 LDAP realm name: [LDAP realm name]
 LDAP realm DN: [LDAP realm DN]
 Use SSL in LDAP connection?


Buttons: Cancel, Back, Next, Install

Fields on this screen:

Field Title	LDAP server host
Field Description	Name of computer hosting the OID LDAP server.
Example	myldaphost
Field Title	LDAP server port
Field Description	Port LDAP server is listening on
Example	389
Field Title	LDAP login password
Field Description	The ORW application and its dashboards use the OID (Oracle Internet Directory) LDAP directory server for user data. The password for this LDAP login DN is configurable in the ldap_util.properties and must match the ldap-user-pw alias in the wallet.

Field Title	LDAP realm name
Field Description	Realm nickname
Example	us
Field Title	LDAP realm DN
Field Description	Distinguished name of Realm
Example	dc=us,dc=oracle,dc=com
Field Title	Use SSL in LDAP connection?
Field Description	Determines if the ORW application communicates with the OID LDAP via an SSL connection

Screen: Reports Integration



Fields on this screen:

Field Title	Enable BIP Reporting?
Field Description	Determines if the BIP reporting tool will be used in ORW.
Field Title	Enable Oracle BI EE Reporting?
Field Description	Determines if the Oracle BI EE reporting tool will be used in ORW.

Screen: BIP settings

BIP settings

Settings for the BIP reporting tool. The BIP login ID must be that of an administrator that has access to the BIP webservice.

BIP Webservices URL prefix

Make sure the BIP Webservices URL prefix is not OSSO protected (see Implementation Guide for more detail)

BIP Reports URL Prefix

BIP Login ID

BIP Password Alias

BIP login password

BIP Shared Reports Folder(s)

Cancel Back Next Install

Fields on this screen:

Field Title	BIP Webservices URL prefix
Field Description	<p>This is the prefix for the BIP Web Services URL e.g. <code>http://<servername>:<portnumber>/xmlpserver/services</code>. This is used by Workspace to call the BI Publisher ServiceGateway web service in order to query the list of reports the logged-in user has access to.</p> <p>If the BIP server's URL is SSO protected, the services URL must not be protected or should be explicitly unprotected. This can be checked in the <code>ORACLE_HOME/Apache/Apache/conf/mod_osso.conf</code> file. See the "Interfacing with Reports Servers" section of the Implementation Guide for more details.</p>
Example	<code>http://myhost:7777/xmlpserver/services</code>
Notes	This screen depends on checking the "Enable BIP Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.

Field Title	BIP Reports URL Prefix
Field Description	Prefix (e.g. http://<servername>:<portnumber>/xmlpserver) used by ORW to compose the first portion of each report's URL. The composed URL is then provided as a link in the Reports work list of ORW's navigation panel.
Example	http://myhost:7777/xmlpserver
Notes	This screen depends on checking the "Enable BIP Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.
Field Title	BIP Login ID
Field Description	ID that needs to be defined under the BI Publisher administrator role. This is so it is capable of accessing the shared folders and any user folders on behalf of the logged-in user.
Example	admin
Notes	This screen depends on checking the "Enable BIP Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.
Field Title	BIP Password Alias
Field Description	The BIP login password's alias specified to identify the password in the Oracle Wallet that is created at install time. If this parameter is empty, it is assumed that the BIP Login ID has no password.
Example	bipPwdAlias
Notes	This screen depends on checking the "Enable BIP Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.
Field Title	BIP login password
Field Description	Password for the BI Publisher administrator role. If nothing is entered, empty password will be stored in Oracle Wallet.
Notes	This screen depends on checking the "Enable BIP Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.

Field Title	BIP Shared Reports Folder(s)
Field Description	Contains a folder or folders defined in the BI Publisher tool under the Shared Folders. This could contain multiple shared folders that are comma separated. Field is optional. If nothing is entered, no corresponding folder will show up in the Reports work list of the ORW navigation pane.
Example	Guest
Notes	This screen depends on checking the "Enable BIP Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.

Screen: Oracle BI EE settings

Fields on this screen:

Field Title	Oracle BI EE Webservices URL prefix
Field Description	<p>This is the prefix for the Oracle BI EE Web Services URL e.g. <code>http://<servername>:<portnumber>/analytics/services</code>. This is used by Workspace to call the Oracle BI EE SAWSessionService and WebCatalogService web services in order to query the list of reports the logged-in user has access to.</p> <p>If the Oracle BI EE analytics URL is SSO protected, the services URL must not be protected or should be explicitly unprotected. This can be checked in the <code>ORACLE_HOME/Apache/Apache/conf/mod_osso.conf</code> file. See the "Interfacing with Reports Servers" section of the Implementation Guide for more details.</p>
Example	<code>http://myhost:7777/analytics/services</code>
Notes	This screen depends on checking the "Enable Oracle BI EE Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.

Field Title	Oracle BI EE Reports URL Prefix
Field Description	Prefix (e.g. http://<servername>:<portnumber>/analytics/saw.dll) used by ORW to compose the first (common) portion of each report's URL. The composed URL is then provided as a link in the Reports work list of ORW's navigation panel.
Example	http://myhost:7777/analytics/saw.dll
Notes	This screen depends on checking the "Enable Oracle BI EE Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.
Field Title	Oracle BI EE Login ID
Field Description	ID defined as an Oracle BI EE administrator or impersonator. This is so it is capable of accessing the shared folders and any user folders on behalf of the logged-in user.
Example	administrator
Notes	This screen depends on checking the "Enable Oracle BI EE Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.
Field Title	Oracle BI EE Password Alias
Field Description	The Oracle BI EE login password's alias specified to identify the password in the Oracle Wallet that is created at install time. If this parameter is empty, it is assumed that the Oracle BI EE Login ID has no password.
Example	obieePwdAlias
Notes	This screen depends on checking the "Enable Oracle BI EE Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.
Field Title	Oracle BI EE login password
Field Description	Password for the Oracle BI EE administrator role. If nothing is entered, empty password will be stored in Oracle Wallet.
Notes	This screen depends on checking the "Enable Oracle BI EE Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.

Field Title	Oracle BI EE Users Folder Name
Field Description	Contains the folder name where the Oracle BI EE tool stores its users' folders. For example if this folder is called "Users" and the logged in user name is executive, this user's folders are found in /Users/executive. This field is optional. If nothing is entered, it is assumed that Oracle BI EE stores its users' folders directly under the user's folder e.g. /executive.
Example	users
Notes	This screen depends on checking the "Enable Oracle BI EE Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.

Field Title	Oracle BI EE Shared Reports Folder(s)
Field Description	Contains a folder or folders defined in the Oracle BI EE tool under the Shared folders. This could contain multiple shared folders that are comma separated. This field is optional. If nothing is entered, no corresponding folder will show up in the Reports work list of the ORW navigation pane.
Example	shared
Notes	This screen depends on checking the "Enable Oracle BI EE Reporting?" box in the previous Reports Integration screen and will not be displayed if it is unchecked.

Screen: Oracle BI EE Alerts Integration



Fields on this screen:

Field Title	Enable Oracle BI EE Alerts Integration?
Field Description	Determines if Oracle BI EE Alerts will be used in ORW.

Screen: Oracle BI EE Alerts Integration Settings

Retail Workspace Installer - Oracle Retail

ORACLE

OBIEE Alerts Integration Settings

Settings for OBIEE Alerts integration.


OBIEE Manage Alerts URL

Cancel Back Next Install

Fields on this screen:

Field Title	Oracle BI EE Manage Alerts URL
Field Description	This is the Oracle Oracle BI EE Delivers Alerts URL. This is used by Workspace to launch the Manage Alerts URL of the Oracle BI EE.
Example	http://myhost:7777/analytics/saw.dll?Alerts

Screen: BPEL Integration



Fields on this screen:

Field Title	Enable BPEL Integration?
Field Description	Determines if BPEL will be used in ORW.

Screen: BPEL Integration Settings

ORACLE

BPEL Integration Settings

Settings for BPEL integration.

BPEL Admin App URL


BPM Worklists page URL

BPEL Workflows page URL

Fields on this screen:

Field Title	BPEL Admin App URL
Field Description	This URL will be used to administer BPEL Workflows/Processes and Domains on the BPEL server.
Example	http://myhost:7777/BPELConsole
Field Title	BPM Worklists page URL
Field Description	This URL will be used to display the ORWBPMWorklist page which consumes the ORWBPELWorklist Portlet.
Example	http://myhost:7777/ORWBPELPages/faces/ORWBPMWorklist.jspx
Field Title	BPEL Workflows page URL
Field Description	This URL will be used to display the ORWBPELWorkflow page which consumes the ORWBPELWorkflowPortlet.
Example	http://myhost:7777/ORWBPELPages/faces/ORWBPELWorkflow.jspx

Screen: Example Dashboards



Fields on this screen:

Field Title	Enable Executive Dashboard?
Field Description	Determines if the Executive Dashboard will be displayed in ORW.
Field Title	Enable Planner Dashboard?
Field Description	Determines if the Planner Dashboard will be displayed in ORW.
Field Title	Enable Merchant Dashboard?
Field Description	Determines if the Merchant Dashboard will be displayed in ORW.

Field Title	Enable Stores Dashboard?
Field Description	Determines if the Stores Dashboard will be displayed in ORW.

Screen: Executive Dashboard Settings

Fields on this screen:

Field Title	Executive Dashboard URL
Field Description	URL used to access Demo Executive Dashboard. This URL was displayed at the end of the Demo Dashboards installation.
Example	http://myhost:7777/ExecutiveDashboard/faces/DemoExecutiveDashboard.jspx
Notes	This screen depends on checking the "Enable Executive Dashboard?" box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Top Report URL
Field Description	URL displayed by the Report portlet in the top row of the Executive Dashboard.
Example	http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Sales%20Contribution
Notes	This screen depends on checking the "Enable Executive Dashboard?" box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Top Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the top row of the Executive Dashboard that lets you open this URL in a new window.
Example	<code>http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Sales%20Contribution</code>
Notes	This screen depends on checking the “Enable Executive Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Middle Report URL
Field Description	URL displayed by the Report portlet in the middle row of the Executive Dashboard.
Example	<code>http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Sales%20Contribution%20Bar%20Chart</code>
Notes	This screen depends on checking the “Enable Executive Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Middle Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the middle row of the Executive Dashboard that lets you open this URL in a new window.
Example	<code>http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Sales%20Contribution%20Bar%20Chart</code>
Notes	This screen depends on checking the “Enable Executive Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Bottom Report URL
Field Description	URL displayed by the Report portlet in the bottom row of the Executive Dashboard.
Example	<code>http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Sales%20Markdown%20Contribution</code>
Notes	This screen depends on checking the “Enable Executive Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Bottom Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the bottom row of the Executive Dashboard that lets you open this URL in a new window.
Example	http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Sales%20Markdown%20Contribution
Notes	This screen depends on checking the “Enable Executive Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Top RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the top row of the Executive Dashboard.
Example	http://www.oracle.com/rss/rss_ocom_pr.xml
Notes	This screen depends on checking the “Enable Executive Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Middle RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the middle row of the Executive Dashboard.
Example	http://www.oracle.com/rss/rss_ocom_corpnews.xml
Notes	This screen depends on checking the “Enable Executive Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Bottom RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the bottom row of the Executive Dashboard.
Example	http://www.oracle.com/technology/syndication/rss_otn_soft.xml
Notes	This screen depends on checking the “Enable Executive Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Screen: Planner Dashboard Settings

Planner Dashboard Settings

Planner Dashboard URL: hboard/faces/DemoPlannerDashboard.jspx

Parameters:

First Row Report URL: %2Freports%2FYesterday%27s%20Flash%20Sales

First Row Report Alternate URL: %2Freports%2FYesterday%27s%20Flash%20Sales

First Row Left RSS URL: tp://www.oracle.com/rss/rss_ocom_pr.xml

First Row Right RSS URL: ww.oracle.com/rss/rss_ocom_corpnews.xml

Second Row Report URL: ed%2FsalesTrend%2F_portal%2FsalesTrend4

Second Row Report Alt URL: ed%2FsalesTrend%2F_portal%2FsalesTrend4

Second Row RSS URL: 1/technology/syndication/rss_otn_soft.xml

Third Row Report URL: %2FThis%20Week%27s%20Top%20Performers

Buttons: Cancel, Back, Next, Install

Fields on this screen:

Field Title	Planner Dashboard URL
Field Description	URL used to access Demo Planner Dashboard. This URL was displayed at the end of the Demo Dashboards installation.
Example	http://myhost:7777/PlannerDashboard/faces/DemoPlannerDashboard.jspx
Notes	This screen depends on checking the "Enable Planner Dashboard?" box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	First Row Report URL
Field Description	URL displayed by the Report portlet in the first row of the Planner Dashboard.
Example	http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FYesterday%27s%20Flash%20Sales
Notes	This screen depends on checking the "Enable Planner Dashboard?" box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	First Row Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the first row of the Planner Dashboard that lets you open this URL in a new window.
Example	http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FYesterday%27s%20Flash%20Sales
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	First Row Left RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the first row on the left side of the Planner Dashboard.
Example	http://www.oracle.com/rss/rss_ocom_pr.xml
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	First Row Right RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the first row on the right side of the Planner Dashboard.
Example	http://www.oracle.com/rss/rss_ocom_corpnews.xml
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Second Row Report URL
Field Description	URL displayed by the Report portlet in the second row of the Planner Dashboard.
Example	http://myhost:7777/analytics/saw.dll?PortalPages&PortalPath=%2Fshared%2FsalesTrend%2F_portal%2FsalesTrend4
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Second Row Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the second row of the Planner Dashboard that lets you open this URL in a new window.
Example	http://myhost:7777/analytics/saw.dll?PortalPages&PortalPath=%2Fshared%2FsalesTrend%2F_portal%2FsalesTrend4
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Second Row RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the second row of the Planner Dashboard.
Example	http://www.oracle.com/technology/syndication/rss_otn_soft.xml
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Third Row Report URL
Field Description	URL displayed by the Report portlet in the third row of the Planner Dashboard.
Example	http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Top%20Performers
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Third Row Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the third row of the Planner Dashboard that lets you open this URL in a new window.
Example	http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Top%20Performers
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Fourth Row Report URL
Field Description	URL displayed by the Report portlet in the fourth row of the Planner Dashboard.
Example	http://myhost:7777/analytics/saw.dll?PortalPages&PortalPath=%2Fshared%2FClassPerf%2F_portal%2FClassPerf_dashboard
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Fourth Row Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the fourth row of the Planner Dashboard that lets you open this URL in a new window.
Example	http://myhost:7777/analytics/saw.dll?PortalPages&PortalPath=%2Fshared%2FClassPerf%2F_portal%2FClassPerf_dashboard
Notes	This screen depends on checking the “Enable Planner Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Screen: Merchant Dashboard Settings

Merchant Dashboard Settings

Merchant Dashboard URL: board/faces/DemoMerchantDashboard.jspx

Parameters:

Top Report URL: i2FThis%20Week%27s%20Top%20Performers

Top Report Alternate URL: i2FThis%20Week%27s%20Top%20Performers

Middle Report URL: Fopo.xdo&_xt=OPO&_xf=html&_xmode=4

Middle Report Alternate URL: Fopo.xdo&_xt=OPO&_xf=html&_xmode=4

Bottom Report URL: \reports%2FYesterday%27s%20Flash%20Sales

Bottom Report Alternate URL: \reports%2FYesterday%27s%20Flash%20Sales

Top RSS URL: tp://www.oracle.com/rss/rss_ocom_pr.xml

Middle RSS URL: www.oracle.com/rss/rss_ocom_corpnews.xml

Buttons: Cancel, Back, Next, Install

Fields on this screen:

Field Title	Merchant Dashboard URL
Field Description	URL used to access Demo Merchant Dashboard. This URL was displayed at the end of the Demo Dashboards installation.
Example	http://myhost:7777/MerchantDashboard/faces/DemoMerchantDashboard.jspx
Notes	This screen depends on checking the "Enable Merchant Dashboard?" box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Top Report URL
Field Description	URL displayed by the Report portlet in the top row of the Merchant Dashboard.
Example	http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Top%20Performers
Notes	This screen depends on checking the "Enable Merchant Dashboard?" box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Top Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the top row of the Merchant Dashboard that lets you open this URL in a new window.
Example	<code>http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Top%20Performers</code>
Notes	This screen depends on checking the “Enable Merchant Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Middle Report URL
Field Description	URL displayed by the Report portlet in the middle row of the Merchant Dashboard.
Example	<code>http://myhost:7777/xmlpserver/Guest/RMS/12.1int/Orders/opo/opo.xdo?_xpf=&_xpt=0&_xdo=%2FGuest%2FRMS%2F12.1int%2FOrders%2Fopo%2Fopo.xdo&_xt=OPO&_xf=html&_xmode=4</code>
Notes	This screen depends on checking the “Enable Merchant Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Middle Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the middle row of the Merchant Dashboard that lets you open this URL in a new window.
Example	<code>http://myhost:7777/xmlpserver/Guest/RMS/12.1int/Orders/opo/opo.xdo?_xpf=&_xpt=0&_xdo=%2FGuest%2FRMS%2F12.1int%2FOrders%2Fopo.xdo&_xt=OPO&_xf=html&_xmode=4</code>
Notes	This screen depends on checking the “Enable Merchant Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Bottom Report URL
Field Description	URL displayed by the Report portlet in the bottom row of the Merchant Dashboard.
Example	<code>http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FYesterday%27s%20Flash%20Sales</code>
Notes	This screen depends on checking the “Enable Merchant Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Bottom Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the bottom row of the Merchant Dashboard that lets you open this URL in a new window.
Example	http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FYesterday%27s%20Flash%20Sales
Notes	This screen depends on checking the “Enable Merchant Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Top RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the top row of the Merchant Dashboard.
Example	http://www.oracle.com/rss/rss_ocom_pr.xml
Notes	This screen depends on checking the “Enable Merchant Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Middle RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the middle row of the Merchant Dashboard.
Example	http://www.oracle.com/rss/rss_ocom_corpnews.xml
Notes	This screen depends on checking the “Enable Merchant Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Bottom RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the bottom row of the Merchant Dashboard.
Example	http://www.oracle.com/technology/syndication/rss_otn_soft.xml
Notes	This screen depends on checking the “Enable Merchant Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Screen: Stores Dashboard Settings

Stores Dashboard Settings

Stores Dashboard URL: shboard/faces/DemoStoresDashboard.jspx

Parameters:

Top Report URL: tal%2FYesterday%27s%20Sales%20Scorecard

Top Report Alternate URL: tal%2FYesterday%27s%20Sales%20Scorecard

Middle Report URL: i2FThis%20Week%27s%20Sales%20Scorecard

Middle Report Alternate URL: i2FThis%20Week%27s%20Sales%20Scorecard

Bottom Report URL: i2FThis%20Week%27s%20Top%20Performers

Bottom Report Alternate URL: i2FThis%20Week%27s%20Top%20Performers

Top RSS URL: tp://www.oracle.com/rss/rss_ocom_pr.xml

Bottom RSS URL: www.oracle.com/rss/rss_ocom_corpnews.xml

Buttons: Cancel, Back, Next, Install

Fields on this screen:


Field Title	Stores Dashboard URL
Field Description	URL used to access Demo Stores Dashboard. This URL was displayed at the end of the Demo Dashboards installation.
Example	http://myhost:7777/StoresDashboard/faces/DemoStoresDashboard.jspx
Notes	This screen depends on checking the "Enable Stores Dashboard?" box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Top Report URL
Field Description	URL displayed by the Report portlet in the top row of the Stores Dashboard.
Example	http://myhost:7777/analytics/saw.dll?PortalPages&PortalPath=%2Fshared%2FRDW%20Packaged%20Reports%2F_portal%2FYesterday%27s%20Sales%20Scorecard
Notes	This screen depends on checking the "Enable Stores Dashboard?" box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Top Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the top row of the Stores Dashboard that lets you open this URL in a new window.
Example	<code>http://myhost:7777/analytics/saw.dll?PortalPages&PortalPath=%2Fshared%2FRDW%20Packaged%20Reports%2F_portal%2FYesterday%27s%20Sales%20Scorecard</code>
Notes	This screen depends on checking the “Enable Stores Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Middle Report URL
Field Description	URL displayed by the Report portlet in the middle row of the Stores Dashboard.
Example	<code>http://myhost:7777/analytics/saw.dll?PortalPages&PortalPath=%2Fshared%2FRDW%20Packaged%20Reports%2F_portal%2FThis%20Week%27s%20Sales%20Scorecard</code>
Notes	This screen depends on checking the “Enable Stores Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Middle Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the middle row of the Stores Dashboard that lets you open this URL in a new window.
Example	<code>http://myhost:7777/analytics/saw.dll?PortalPages&PortalPath=%2Fshared%2FRDW%20Packaged%20Reports%2F_portal%2FThis%20Week%27s%20Sales%20Scorecard</code>
Notes	This screen depends on checking the “Enable Stores Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.
Field Title	Bottom Report URL
Field Description	URL displayed by the Report portlet in the bottom row of the Stores Dashboard.
Example	<code>http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Top%20Performers</code>
Notes	This screen depends on checking the “Enable Stores Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Bottom Report Alternate URL
Field Description	Optional. If an alternate URL is entered, a link is added to the Report portlet in the bottom row of the Stores Dashboard that lets you open this URL in a new window.
Example	http://myhost:7777/analytics/saw.dll?Go&Path=%2Fshared%2FRDW%20Packaged%20Reports%2FThis%20Week%27s%20Top%20Performers
Notes	This screen depends on checking the “Enable Stores Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Top RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the top row of the Stores Dashboard.
Example	http://www.oracle.com/rss/rss_ocom_pr.xml
Notes	This screen depends on checking the “Enable Stores Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Field Title	Bottom RSS URL
Field Description	URL to an RSS feed displayed by the RSS portlet in the bottom row of the Stores Dashboard.
Example	http://www.oracle.com/rss/rss_ocom_corpnews.xml
Notes	This screen depends on checking the “Enable Stores Dashboard?” box in the previous Example Dashboards screen and will not be displayed if it is unchecked.

Screen: Oracle Retail Products**Fields on this screen:**

Field Title	Oracle Retail Product Checkbox
Field Description	One checkbox for each Oracle retail application or resource that ORW can launch. Check the corresponding box of the application to have access to it from ORW.

Screen: Oracle Retail Product Connection Details

ARI Connection Details

ARI (Active Retail Intelligence) is an exception management and resolution system driven by business rules that you define.

The launch URL is the base URL for the forms servlet used to access the retail application (Example: `http://myhost:7777/forms/frmservlet` where 7777 is the HTTP port of the Forms application server).

ARI launch URL

The config parameter corresponds to a formsweb.cfg entry for the application. This parameter is part of the query string used to launch the ARI application. For example, a config value of "myapp" with a base URL of `http://myhost:7777/forms/frmservlet` results in a launch URL of `http://myhost:7777/forms/frmservlet?config=myapp`

Config parameter

Cancel Back Next Install

Fields on this screen:

Field Title	Launch URL
Field Description	URL used to access the particular Oracle retail product or resource. The ORW application connects using this URL and gives access to the product or resource.
Example	<code>http://myhost:7777/contextroot</code>
Field Title	Config parameter
Field Description	Config parameter that corresponds to a formsweb.cfg entry for the application which defines a URL. This parameter is sent in the request to the launch URL.
Example	config value myapp results in this request: <code>[launch-url]?config=myapp</code> .
Notes	The config parameter text field may not be available depending on which Oracle Retail Product screen you are on.

Field Title	Template parameter
Field Description	Template parameter that corresponds to a JNLP template file included with the application. This parameter is sent in the request to the launch URL.
Example	template value mytemplate results in this request: [launch-url]?template=mytemplate.
Notes	The template parameter text field may not be available depending on which Oracle Retail Product screen you are on.

Field Title	Domain parameter
Example	domain value mydomain results in this request: [launch-url]?domain=mydomain.
Notes	The domain parameter text field may not be available depending on which Oracle Retail Product screen you are on.

Screen: Central Office Connection Details

Central Office Connection Details

Retail Central Office details:

Central Office launch URL:

Central Office App Name:

Central Office App ID:

Buttons: Cancel, Back, Next, Install

Fields on this screen:

Field Title	Central Office Launch URL
Field Description	URL used to access Central Office. The ORW application connects using this URL and gives access to the product or resource.
Example	http://myhost:7777/contextroot/jSecAppORW.html
Field Title	Central Office App Name
Field Description	Application name defining the main Central Office URL. This entry must match the Central Office application definition in the appinfo.xml file.
Example	CentralOffice
Notes	The appinfo.xml file is used by the jSecAppORW.html or jSecAppRemote.html pages to define the main Central Office URL and the OSSO server location. See the ORW Implementation Guide for details on using these sample HTML and associated JavaScript files.

Field Title	Central Office App ID
Field Description	The OSSO External Application ID defining the login URL for the Central Office application.
Example	6AE243F9B5B1E5A94C76CB936DEA6033
Notes	This ID is maintained by the OSSO External Application sub-system.

Appendix: Installer Silent Mode

Repeating an Installation Attempt

In addition to the GUI and text interfaces of the Oracle Retail Workspace installers, there is a silent mode that can be run. This mode is useful if you wish to run a repeat installation attempt without going through the installer screens again.

The installer runs in two distinct phases. The first phase involves gathering settings from the user. At the end of the first phase, a properties file named `ant.install.properties` is created with the settings that were provided. Then the second phase begins, where this properties file is used to provide your settings for the installation.

To skip the first phase and re-use the `ant.install.properties` file from a previous run, follow these instructions:

1. Edit the `ant.install.properties` file and correct any invalid settings that may have caused the installer to fail in its previous run.
2. Re-enter any passwords. Properties in this file that are for passwords are cleared out by the installer.
3. Run the installer again with the **silent** argument.

Example: `install.sh silent`

Appendix: Common Installation Errors

This section provides some common errors encountered during installation of Retail Workspace.

Unreadable Buttons in the Installer

If you are unable to read the text within the installer buttons, it could mean that your `JAVA_HOME` is pointed to an older version of the JDK than is supported by the installer. Set `JAVA_HOME` to `$ORACLE_HOME/jdk` from the Oracle Application Server 10.1.3 installation and run the installer again.

“Unable to get a deployment manager” Message

Symptom:

The application installer quits with the following error message:

```
[oracle:deploy] Unable to get a deployment manager.
[oracle:deploy]
[oracle:deploy] This is typically the result of an invalid deployer URI
format being supplied, the target server not being in a started state or
incorrect authentication details being supplied.
[oracle:deploy]
[oracle:deploy] More information is available by enabling logging --
please see the Oracle Containers for J2EE Configuration and
Administration Guide for details.
```

Solution:

This error can be caused by any of the following conditions:

- OC4J instance provided is not running.
- Incorrect OC4J instance name provided
- Incorrect OC4J administrative username and/or password
- Incorrect OPMN request port provided.

Make sure that the OC4J instance is running, and then check the `ant.install.properties` file for entry mistakes. Pay close attention to the `input.deployer.uri` (see Appendix I: *URL Reference*), `input.oc4j.instance`, `input.admin.user`, and `input.admin.password` properties. If you need to make a correction, you can run the installer again with this file as input by running silent mode (see Appendix G of this document).

“Could not create system preferences directory” Warning

Symptom:

The following text appears in the installer Errors tab:

```
May 22, 2006 11:16:39 AM java.util.prefs.FileSystemPreferences$3 run
WARNING: Could not create system preferences directory. System preferences are
unusable.
May 22, 2006 11:17:09 AM java.util.prefs.FileSystemPreferences
checkLockFile0ErrorCode
WARNING: Could not lock System prefs. Unix error code -264946424.
```

Solution:

This is related to Java bug 4838770. The `/etc/.java/.systemPrefs` directory may not have been created on your system. See <http://bugs.sun.com> for details.

This is an issue with your installation of Java and does not affect the Oracle Retail product installation.

ConcurrentModificationException in Installer GUI

Symptom:

In GUI mode, the errors tab shows the following error:

```
java.util.ConcurrentModificationException
    at
java.util.AbstractList$Itr.checkForComodification(AbstractList.java:448)
    at java.util.AbstractList$Itr.next(AbstractList.java:419)
... etc
```

Solution:

You can ignore this error. It is related to third-party Java Swing code for rendering of the installer GUI and does not affect the Oracle Retail product installation.

“Couldn't find X Input Context” Warnings

Symptom:

The following text appears in the console window during execution of the installer in GUI mode:

```
Couldn't find X Input Context
```

Solution:

This message is harmless and can be ignored.

Error while unpacking EAR file

Symptom:

The following text (using sim12.ear for an example) appears in the console window during execution of the installer:

```
07/12/19 10:53:17 Notification ==>Error while unpacking sim12.ear
java.util.zip.ZipException: error in opening zip file
```

Solution:

This is a known bug (BugID 6330834) related to Solaris and NFS in Oracle Application Server 10.1.3.3. Follow the workaround documented for this bug: in the opmn.xml file in \$ORACLE_HOME/opmn/conf: add the following parameter to the java-options for the instance you are installing.

```
-Doc4j.autoUnpackLockCount=-1
```

After making this change you should reload OPMN, restart the affected OC4J instance(s), and retry the retail application installation.

Installer Errors Tab Section Full of Informational Messages

Symptom:

In GUI mode, the errors tab shows a large amount of warning messages regarding EAR file predeployment.

```
INFO: Current Proxy URL      :
Dec 20, 2007 4:14:43 PM DeploymentProfile validate
INFO: Current Proxy Port    : 0
Dec 20, 2007 4:14:43 PM DeploymentProfile validatePortletProducer
```

Solution:

You can ignore these warnings. There is warning text sent to stderr by certain ANT tasks used by the installer.

Installer Appears to Hang after EAR deployment

Symptom:

An installer that is a part of the Oracle Retail Workspace solution appears to hang for a period of several minutes.

Solution:

You should allow the installer to finish. The installer uses ANT tasks included with Oracle WebCenter which appears to cause output from subsequent ANT tasks to go to the log file but not the console. You will see the shell prompt appear when the installer is finished and you should be able to see the missing output in the installer log file.

Appendix: URL Reference

The application installers for the ORW product asks for several different URLs. These include the following.

Deployer URI

The deployer URI is used by the Oracle ANT tasks to deploy an application to an OC4J group. The application installer does not ask the user for this value; it is constructed based on other inputs and written to the `ant.install.properties` file for input to the installation script. For repeat installations using silent mode, you may need to correct mistakes in the deployer URI in `ant.install.properties`.

Note: There are several different formats for the deployer URI depending on your cluster topology. Consult the *Deploying with the OC4J Ant Tasks* chapter of the *OC4J Deployment Guide* for further details.

Syntax (managed OC4J): `deployer:cluster:opmn://<host>:<port>/<group>`

- `<host>`: hostname of the OracleAS environment
- `<port>`: OPMN request port of the OracleAS environment. This can be found in the `<ORACLE_HOME>/opmn/conf/opmn.xml` file.
- `<group>`: Name of the OC4J group where the application is deployed.

Example:
`deployer:cluster:opmn://myhost:6003/portlets_group`

Syntax (standalone OC4J): `deployer:oc4j:<host>:<port>`

- `<host>`: hostname of the OracleAS environment
- `<port>`: RMI port of the OC4J server. This can be found in the `ORACLE_HOME/j2ee/home/config/rmi.xml` file.

Example: `deployer:oc4j:myhost:23791`

Appendix: Installation Order

This section provides a guideline as to the order in which the Oracle Retail applications should be installed. If a retailer has chosen to use some, but not all, of the applications the order is still valid less the applications not being installed.

1. Oracle Retail Merchandising System (RMS), Oracle Retail Trade Management (RTM), Oracle Retail Sales Audit (ReSA)
2. Oracle Retail Service Layer (RSL)
3. Oracle Retail Extract, Transform, Load (RETL)
4. Oracle Retail Active Retail Intelligence (ARI)
5. Oracle Retail Warehouse Management System (RWMS)
6. Oracle Retail Allocation
7. Oracle Retail Invoice Matching (ReIM)
8. Oracle Retail Price Management (RPM)

Note: During installation of RPM, you are asked for the RIBforRPM provider URL. Since RIB is installed after RPM, make a note of the URL you enter. If you need to change the RIBforRPM provider URL after you install RIB, you can do so by editing the `jndi_provider.xml` file.

9. Oracle Retail Central Office (ORCO)
10. Oracle Retail Back Office (ORBO) or Back Office with Labels and Tags (ORLAT)
11. Oracle Retail Store Inventory Management (SIM)

Note: During installation of SIM, you are asked for the AIP provider URL. Since AIP is installed after SIM, make a note of the URL you enter. If you need to change the AIP provider URL after you install AIP, you can do so by editing the `jndi_providers_ribclient.xml` file.

12. Oracle Retail Predictive Application Server (RPAS)
13. Oracle Retail Merchandise Financial Planning (MFP)
14. Oracle Retail Size Profile Optimization (SPO)
15. Oracle Retail Assortment Planning (AP)
16. Oracle Retail Item Planning (IP)
17. Oracle Retail Item Planning configured for COE (IPCOE)
18. Oracle Retail Advanced Inventory Planning (AIP)
19. Oracle Retail Integration Bus (RIB)
20. Oracle Retail Point-of-Service (ORPOS)
21. Oracle Retail Mobile Point-of-Service (ORMPOS)
22. Oracle Retail Analytics Applications
23. Oracle Retail Data Warehouse (RDW)
24. Oracle Retail Workspace (ORW)