

## **Oracle® Retail Back Office**

Installation Guide, Volume 2 - IBM Stack

Release 13.3.0.1

June 2011

Copyright © 2011, Oracle and/or its affiliates. All rights reserved.

Primary Author: Bernadette Goodman

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

## Value-Added Reseller (VAR) Language

### Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

(i) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.

(ii) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.

(iii) the software component known as **Access Via**™ licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.

(iv) the software component known as **Adobe Flex**™ licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.



---

---

# Contents

|   |             |
|---|-------------|
| <b>Send Us Your Comments .....</b>                                    | <b>xi</b>   |
| <b>Preface .....</b>  | <b>xiii</b> |
| Audience.....   | xiii        |
| Documentation Accessibility .....                                     | xiii        |
| Related Documents .....   | xiv         |
| Customer Support .....  | xiv         |
| Review Patch Documentation .....                                      | xiv         |
| Oracle Retail Documentation on the Oracle Technology Network .....    | xiv         |
| Conventions .....   | xv          |
| <br><b>1 Preinstallation Tasks</b>                                    |             |
| <b>Determine the Back Office Distribution .....</b>                   | <b>1-1</b>  |
| <b>Check Supported Database Server Requirements.....</b>              | <b>1-1</b>  |
| Required Setting for Database Installation.....                       | 1-1         |
| <b>Check Supported Application Server Requirements.....</b>           | <b>1-2</b>  |
| Check for SSL Certificate.....  | 1-2         |
| Check that the Fonts Needed for Reports are Installed.....            | 1-2         |
| <b>Check Oracle Retail Software Dependencies .....</b>                | <b>1-2</b>  |
| <b>Check Third-Party Software Dependencies.....</b>                   | <b>1-3</b>  |
| <b>Check Additional Oracle Technologies .....</b>                     | <b>1-3</b>  |
| <b>Check Supported Client PC and Web Browser Requirements .....</b>   | <b>1-3</b>  |
| <b>Hardware Requirements .....</b>                                    | <b>1-3</b>  |
| <b>Implementation Guidelines for Security .....</b>                   | <b>1-4</b>  |
| <br><b>2 Installation of the IBM Stack on SLEPOS</b>                  |             |
| <b>Check the WebSphere Application Server Settings .....</b>          | <b>2-1</b>  |
| Secure Configuration .....  | 2-1         |
| <b>Create the Database Schema Owner and Data Source Users .....</b>   | <b>2-1</b>  |
| <b>Expand the Back Office Distribution .....</b>                      | <b>2-2</b>  |
| <b>Obtain Third-Party Library Files Required by Back Office .....</b> | <b>2-3</b>  |
| <b>Set Up to Integrate with the Central Office JMS Server.....</b>    | <b>2-4</b>  |
| <b>Enable Data Import.....</b>  | <b>2-4</b>  |
| <b>Oracle Configuration Manager.....</b>                              | <b>2-4</b>  |

|  |      |
|--|------|
| Installation Options .....   | 2-5  |
| Database Install Options .....   | 2-5  |
| Manually Creating the Database Schema .....  | 2-5  |
| Secure the JDBC for the IBM DB2 Database .....   | 2-7  |
| Set up the JMS SSL Key Store .....   | 2-7  |
| Configure AccessVia for Labels and Tags .....  | 2-8  |
| Run the Back Office Application Installer .....  | 2-8  |
| Resolve Errors Encountered During Application Installation .....                         | 2-9  |
| Configure IBM WebSphere MQ .....   | 2-9  |
| Update JMS Configuration for Integration of Point-of-Service with Returns Management.... | 2-9  |
| Manual Deployment of the Back Office Application .....                                   | 2-10 |
| Install Parameters .....   | 2-11 |
| Import Initial Parameters .....  | 2-11 |
| Importing Parameters Through the User Interface .....                                    | 2-11 |
| Importing Parameters by using an Ant Target .....  | 2-12 |
| Load Templates for Labels and Tags .....   | 2-12 |
| Load Optional Purge Procedures .....   | 2-12 |
| Using the Back Office Application .....  | 2-12 |

### **3 Configuring the AccessVia Print Engine for Labels and Tags for the IBM Stack**

|   |     |
|---|-----|
| Creating the AccessVia Print Engine .ini File .....             | 3-2 |
| Configuring the Database for the AccessVia Print Engine .....   | 3-2 |
| Configuring for IBM WebSphere .....                             | 3-2 |
| Adding Multiple Printers .....                                  | 3-3 |
| Updating the AccessVia License File .....                       | 3-4 |
| Back Office Installation .....                                  | 3-4 |
| Labels and Tags Templates .....                                 | 3-4 |
| Updating or Creating Templates .....                            | 3-4 |
| Configuring Multiple Printers .....                             | 3-5 |
| Testing the AccessVia Print Engine .....                        | 3-5 |
| AccessVia Print Engine .ini File .....                          | 3-5 |
| .ini File Settings .....  | 3-6 |
| .ini File Example .....   | 3-7 |
| Setting up a USB Printer in a Network .....                     | 3-8 |
| Troubleshooting Labels and Tags Problems on the IBM Stack ..... | 3-9 |

### **A Appendix: Installer Screens for the IBM Stack**

### **B Appendix: Installer Silent Mode**

### **C Appendix: Reinstalling Back Office**

|   |     |
|---|-----|
| Reinstalling Back Office on the IBM Stack ..... | C-1 |
|---|-----|

### **D Appendix: URL Reference**

|                              |     |
|------------------------------|-----|
| URLs for the IBM Stack ..... | D-1 |
|------------------------------|-----|

|          |  |     |
|----------|--|-----|
|          | JDBC URL for a Database .....  | D-1 |
|          | JNDI Provider URL for an Application .....                           | D-1 |
| <b>E</b> | <b>Appendix: Common Installation Errors</b>                          |     |
|          | Unreadable Buttons in the Installer .....                            | E-1 |
| <b>F</b> | <b>Appendix: Best Practices for Passwords</b>                        |     |
|          | Password Guidelines .....  | F-1 |
|          | Special Security Options for IBM DB2 Databases .....                 | F-2 |
| <b>G</b> | <b>Appendix: Secure JDBC with IBM DB2</b>                            |     |
|          | Summary .....  | G-1 |
|          | Prerequisites .....  | G-1 |
|          | Setting up the Key Store .....                                       | G-2 |
|          | Creating a Self-signed Digital Certificate for Testing.....          | G-2 |
|          | Configuring the IBM DB2 Server .....                                 | G-2 |
|          | Exporting a Certificate from iKeyman .....                           | G-4 |
|          | Configuring the IBM FIPS-compliant Provider for SSL (optional) ..... | G-4 |
|          | Specific Instructions for Back Office.....                           | G-5 |
|          | Useful Links .....   | G-6 |
| <b>H</b> | <b>Appendix: Installation Order</b>                                  |     |
|          | Enterprise Installation Order .....                                  | H-1 |

## List of Figures

|      |   |      |
|------|---|------|
| A-1  | Introduction .....                          | A-1  |
| A-2  | Oracle Customer Information .....           | A-2  |
| A-3  | Requirements .....                          | A-3  |
| A-4  | License Agreement .....                     | A-3  |
| A-5  | Supported Languages .....                   | A-4  |
| A-6  | Enter Default Locale .....                  | A-5  |
| A-7  | Database Owner .....                        | A-6  |
| A-8  | Data Source User .....                      | A-7  |
| A-9  | Enable Secure JDBC .....                    | A-8  |
| A-10 | Data Source SSL Configuration .....         | A-9  |
| A-11 | Enable DIMP .....                           | A-10 |
| A-12 | DIMP Configuration .....                    | A-11 |
| A-13 | Database Install Options .....              | A-12 |
| A-14 | Back Office Administrator User .....        | A-13 |
| A-15 | Cryptology Settings .....                   | A-14 |
| A-16 | Enter Store ID .....                        | A-15 |
| A-17 | App Server WAS_HOME .....                   | A-16 |
| A-18 | Access Via Configuration .....              | A-17 |
| A-19 | Mail Session Details .....                  | A-18 |
| A-20 | Application Server Details .....            | A-19 |
| A-21 | JMS Server Details .....                    | A-20 |
| A-22 | Select JMS SSL Level .....                  | A-21 |
| A-23 | Filter Based on Distinguished Name .....    | A-22 |
| A-24 | Distinguished Name Filter .....             | A-23 |
| A-25 | Central Office JMS Server Integration ..... | A-24 |
| A-26 | Central Office JMS Server Details .....     | A-25 |
| A-27 | Configure WebSphere MQ Option .....         | A-26 |
| A-28 | WebSphere MQ Directory .....                | A-27 |
| A-29 | JMS SSL Keystore Passwords .....            | A-28 |
| A-30 | Manual Deployment Option .....              | A-29 |
| A-31 | Application Deployment Details .....        | A-30 |
| A-32 | Install Parameters Option .....             | A-31 |
| A-33 | Load Templates Option .....                 | A-32 |
| A-34 | Value-Added Tax (VAT) .....                 | A-33 |
| A-35 | Installation Progress .....                 | A-34 |
| A-36 | Installation Complete .....                 | A-34 |



**List of Tables**

|     |  |     |
|-----|--|-----|
| 1-1 | Database Server Requirements .....     | 1-1 |
| 1-2 | Application Server Requirements .....  | 1-2 |
| 1-3 | Labels and Tags Requirements .....     | 1-2 |
| 1-4 | Supported Oracle Retail Products ..... | 1-3 |
| 1-5 | Additional Oracle Technologies .....   | 1-3 |



---

---

## Send Us Your Comments

Oracle Retail Back Office Installation Guide, Volume 2 - IBM Stack, Release 13.3.0.1

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

---

---

**Note:** Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the Online Documentation available on the Oracle Technology Network Web site. It contains the most current Documentation Library plus all documents revised or released recently.

---

---

Send your comments to us using the electronic mail address: [retail-doc\\_us@oracle.com](mailto:retail-doc_us@oracle.com)

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at <http://www.oracle.com>.



---

# Preface

This Installation Guide describes the requirements and procedures to install this Oracle Retail Back Office, and the optional Labels and Tags module, release.

## Audience

This Installation Guide is written for the following audiences:

- Database Administrators (DBA)
- System analysts and designers
- Integrators and implementation staff

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

### Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

### Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

### Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/support/contact.html> or visit <http://www.oracle.com/accessibility/support.html> if you are hearing impaired.

## Related Documents

For more information, see the following document in the Oracle Retail Back Office Release 13.3.0.1 documentation set:

- *Oracle Retail Back Office Release Notes*

## Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:

<https://support.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

## Review Patch Documentation

When you install the application for the first time, you install either a base release (for example, 13.3) or a later patch release (for example, 13.3.1). If you are installing the base release, additional patch, and bundled hot fix releases, read the documentation for all releases that have occurred since the base release before you begin installation. Documentation for patch and bundled hot fix releases can contain critical information related to the base release, as well as information about code changes since the base release.

## Oracle Retail Documentation on the Oracle Technology Network

Documentation is packaged with each Oracle Retail product release. Oracle Retail product documentation is also available on the following Web site:

[http://www.oracle.com/technology/documentation/oracle\\_retail.html](http://www.oracle.com/technology/documentation/oracle_retail.html)

(Data Model documents are not available through Oracle Technology Network. These documents are packaged with released code, or you can obtain them through My Oracle Support.)

Documentation should be available on this Web site within a month after a product release.

# Conventions

The following text conventions are used in this document:

| Convention             | Meaning  |
|------------------------|--|
| <b>boldface</b>        | Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.         |
| <i>italic</i>          | Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.                          |
| <code>monospace</code> | Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter. |





---

## Preinstallation Tasks

---

This chapter describes the requirements for the IBM stack that must be met before Oracle Retail Back Office can be installed.

---

**Note:** This is the IBM stack configuration that was tested for this release. While Back Office may work in other configurations, this configuration was tested.

---

If you will be installing multiple Oracle Retail applications, see [Appendix H](#) for a guideline for the order in which the applications should be installed.

### Determine the Back Office Distribution

This document covers installation of two different product releases:

1. Oracle Retail Back Office (ORBO): Back Office application without the Labels and Tags module.
2. Oracle Retail Labels and Tags (ORLAT): Back Office application plus the Labels and Tags module.

---

**Note:** The Labels and Tags module requires AccessVia software.

---

The Oracle Retail Labels and Tags installation contains the full Oracle Retail Back Office installation. You should have one of the above distributions, but not both.

### Check Supported Database Server Requirements

[Table 1–1](#) lists the general requirements for a database server running Oracle Retail Back Office and the versions supported for this release.

**Table 1–1 Database Server Requirements**

| Supported on     | Versions Supported                                 |
|------------------|--|
| Operating System | IBM SLEPOS 11 SP1                                  |
| Database         | IBM DB2 9.7 (64-bit) from WRS 7.1 Standard Edition |

### Required Setting for Database Installation

During database creation, the database must be set to UTF8.

## Check Supported Application Server Requirements

Table 1–2 lists the general requirements for an application server capable of running Back Office and the versions supported for this release.

**Table 1–2 Application Server Requirements**

| Supported on                | Version Supported                                       |
|-----------------------------|---|
| Operating System            | IBM SLEPOS 11 SP1                                       |
| J2EE Application Server     | IBM WebSphere ND 7.0.0.11 from WRD 7.1 Standard Edition |
| J2EE Application Server JVM | IBM JRE 1.6.0   |
| Messaging Provider          | IBM WebSphere MQ 7.0.1.3 from WRD 7.1 Standard Edition  |
| System Management Agent     | IBM WebSphere Admin Console 7.0.0.11                    |

Table 1–3 lists the general requirements for Labels and Tags and the versions supported for this release. This software is only needed if Back Office with the Labels and Tags module is being installed.

**Table 1–3 Labels and Tags Requirements**

| Supported on                     | Version Supported   |
|----------------------------------|---|
| Print Engine for Labels and Tags | AccessVia 7.5 (includes the GD graphics library 2.0.0 and Xerces 2.7.0) |
| Client software                  | IBM DB2 9.7 (includes unixODBC 2.2.14)                                  |

## Check for SSL Certificate

Oracle Retail Back Office is accessed through a secure HTTP connection. The installation of an SSL Certificate is required on your application server. If the certificate is not installed, warnings are displayed when trying to access Oracle Retail Back Office.

For information on installing the SSL Certificate, refer to your application server documentation.

## Check that the Fonts Needed for Reports are Installed

To correctly export reports from Oracle Retail Back Office to a PDF file, any fonts used in the PDF must exist in the application server JVM. To install fonts to the application server:

1. Stop the application server.
2. Copy any needed fonts to the library folder of the JRE used by the application server. The following is an example of the path name to the folder:

```
<IBM WebSphere installation directory>/jdk/jre/lib/fonts
```

3. Start the application server.

## Check Oracle Retail Software Dependencies

Table 1–4 lists the Oracle Retail products that Oracle Retail Back Office is integrated with and the required versions.

**Table 1–4 Supported Oracle Retail Products**

| Integrates with                    | Version |
|------------------------------------|---------|
| Oracle Retail Central Office       | 13.3    |
| Oracle Retail Merchandising System | 13.2    |
| Oracle Retail Point-of-Service     | 13.3    |
| Oracle Retail Price Management     | 13.2    |

## Check Third-Party Software Dependencies

The following third-party software must be obtained:

- The Pager Tag library must be downloaded and the `pager-taglib.jar` file must be extracted.
- The `db2jcc.jar` and `db2jcc_license_cu.jar` files must be obtained from your IBM DB2 database server.

For more information, see ["Obtain Third-Party Library Files Required by Back Office"](#) in [Chapter 2](#).

## Check Additional Oracle Technologies

[Table 1–5](#) lists the Oracle technologies used by Oracle Retail Back Office and the required versions.

**Table 1–5 Additional Oracle Technologies**

| Integrates with   | Version   |
|---|---|
| Oracle Business Intelligence Publisher for Retail Back Office | 10.1.3.4<br><b>Note:</b> This software is included in the Back Office distribution. |

## Check Supported Client PC and Web Browser Requirements

The general requirements for the client system include the following:

- Adobe Acrobat Reader or another application capable of rendering Portable Data Format (PDF) files

The following web browsers are supported on Microsoft Windows XP SP2:

- Microsoft Internet Explorer 7
- Mozilla Firefox 3.6

## Hardware Requirements

Specific hardware requirements for the machines running Oracle Retail Back Office depend on variables including the number of users and other applications running on the same machine.

Please note the following about the hardware requirements:

- The CPU requirement depends on variables including the operating system and middleware selected.

- Memory requirements and performance depend on variables including the number of active promotions and best deal calculations when Back Office is installed on the same machine as the Point-of-Service server.
- Disk size can vary based on the operating system and middleware requirements as well as the amount of data storage needed. Data storage depends on variables including the number of items and promotions defined, data retention period, and so on.

You need to determine your hardware requirements, based on the variables mentioned here, as well as any additional variables specific to your environment. For more information, contact Customer Support.

## Implementation Guidelines for Security

---

**Note:** It is recommended that the passwords for key stores and trust stores are changed from the values set by default.

---

The following document is available through My Oracle Support. Access My Oracle Support at the following URL:

<https://support.oracle.com>

***Oracle Retail POS Suite Implementation Guide, Volume 2 - Security (Doc ID: 1277445.1)***

This implementation guide volume describes specific security features and implementation guidelines for the POS Suite products.

---

## Installation of the IBM Stack on SLEPOS

---

Before proceeding, you must install the database and application server software. For a list of supported versions, see [Chapter 1](#).

During installation, the Back Office database schema will be created and the Back Office application will be deployed. The Java JDK that is included with the IBM WebSphere Application Server will be used to run the application.

---

**Note:** The Authentication Cache Timeout setting for the IBM WebSphere application server must be set correctly for Back Office password processing. For information on how to determine the value you should use for this setting and how to set it for the application server, refer to your IBM WebSphere documentation.

---

### Check the WebSphere Application Server Settings

Some application server settings affect Back Office processing and deployment. Verify that the following setting is set correctly for your installation.

### Secure Configuration

For a secure configuration, SSL is required for login. The **Requires SSL** flag must be set in the IBM WebSphere master configuration. To set the flag:

1. From the WebSphere Administration Console, under **Security**, select **Global Security**.
2. Select Web and SIP security.
3. Select **Single Sign-on (SSO)**.
4. Select the **Requires SSL** check box.
5. To save the change to the master configuration, select **Save**.

### Create the Database Schema Owner and Data Source Users

The following recommendations should be considered for schema owners:

- Database administrators should create an individual schema owner for each application, unless the applications share the same data. In the case of Oracle Retail Back Office and Point-of-Service, the database schema owner are the same because these applications share a database.
- The schema owners should only have enough privileges to install the database.

For information on the best practices for passwords, see [Appendix F](#).

---

**Note:** Do not delete the database schema owner after installation. When using Data Import (DIMP), the schema owner privileges are needed for DIMP processing which includes creating and dropping tables. For information on DIMP, see ["Enable Data Import"](#).

---

To create the database schema owner and database source users:

1. Log in using the database administrator user ID.
2. Create the schema owner user.

```
CREATE SCHEMA <schema_name> AUTHORIZATION <schema_username>
```

3. Grant the privileges, shown in the following example, to the user.

```
GRANT CREATETAB, BINDADD, CONNECT, IMPLICIT_SCHEMA ON DATABASE TO USER  
<schema_username>
```

4. Grant the following object level privileges to the schema owner user.

```
GRANT CREATEIN, DROPIN, ALTERIN ON SCHEMA <schema_name> TO USER  
<schema_username> WITH GRANT OPTION
```

5. Create the data source user.

```
CREATE SCHEMA <data_source_schema_name> AUTHORIZATION <data_source_username>
```

6. Grant the privileges, shown in the following example, to the data source user.

```
GRANT CONNECT, IMPLICIT_SCHEMA ON DATABASE TO USER <data_source_username>
```

7. Grant the following object level privileges to the data source user.

```
GRANT CREATEIN ON SCHEMA <data_source_schema_name> TO USER <data_source_  
username> WITH GRANT OPTION
```

The installer grants the data source user access to the application database objects. If you choose **No** on the Manual Deployment Option screen, you need to grant the access after the installer completes. For more information, see ["Manual Deployment of the Back Office Application"](#).

## Expand the Back Office Distribution

To extract the Back Office files:

1. Extract the ORBO-13.3.0.1.zip (or ORLAT-13.3.0.1.zip) file from the Back Office 13.3.0.1 distribution zip file.
2. Log into the UNIX server as the user who owns the IBM WebSphere installation. Create a new staging directory for the Back Office application distribution (ORBO-13.3.0.1.zip or ORLAT-13.3.0.1.zip), for example, /tmp/orbo-staging.

---

**Note:** The staging directory (<staging\_directory>) can exist anywhere on the system. It does not need to be under tmp.

---

3. Copy or upload ORBO-13.3.0.1.zip (or ORLAT-13.3.0.1.zip) to *<staging\_directory>* and extract its contents. The following files and directories should be created under *<staging\_directory>/ORBO-13.3.0.1*:

```
ant/
ant-ext/
antinstall/
backoffice/
connectors/
external-lib/
installer-resources/
ocm-integration/
retail-public-security-api/
.postinstall.cmd
.postinstall.sh
.preinstall.cmd
.preinstall.sh
.preinstall-oas.cmd
.preinstall-oas.sh
.preinstall-was.cmd
.preinstall-was.sh
.preinstall-wl.cmd
.preinstall-wl.sh
antinstall-config.xml
build.xml
build-common.xml
build-common-backoffice.xml
build-common-oas.xml
build-common-retailinv.xml
build-common-was.xml
build-common-webapps.xml
build-common-wl.xml
build-test.cmd
checkdeps.cmd
checkdeps.sh
install.cmd
install.sh
jmsconfiguration.dat
prepare.xml
retail-OCM-stores.zip
wallet.xml
```

For the remainder of this chapter, *<staging\_directory>/ORBO-13.3.0.1* is referred to as *<INSTALL\_DIR>*.

## Obtain Third-Party Library Files Required by Back Office

The Back Office application uses the Pager Tag Library from JSPTags and the DB2 drivers from IBM. Before running the Back Office application installer, you must download the necessary files from the JSPTags Web site and obtain the DB2 files from your database server.

To get the Pager Tag library:

1. Download the pager-taglib-2.0.war file from the JSPTags Web site:  
<http://jsptags.com/tags/navigation/pager/download.jsp>
2. Extract the pager-taglib.jar file from the WEB-INF/lib subdirectory in the pager-taglib-2.0.war file.
3. Copy pager-taglib.jar into *<INSTALL\_DIR>/external-lib/*.

To get the DB2 files:

1. Obtain the `db2jcc.jar` and `db2jcc_license_cu.jar` files from your database server at `<IBM_DB2_INSTALL_DIR>`.

---

**Note:** The `db2jcc_license_cu.jar` file is needed to permit JDBC/SQLJ connectivity to the IBM DB2 database. The file is the standard license included with all editions of the IBM DB2 database.

---

2. Copy the jar files into `<INSTALL_DIR>/external-lib/`.

## Set Up to Integrate with the Central Office JMS Server

On the "Central Office JMS Server Integration" installer screen, you select whether Back Office will be integrated with the Central Office JMS server. See [Figure A-25](#). To integrate with Central Office, select **Yes** on the screen.

Before running the Back Office installer, verify that the Central Office application is running. The Central Office application must be running in order for the Back Office files to be installed correctly.

## Enable Data Import

Data Import (DIMP) is used by external systems to send data bundles to Back Office for routine data loading of certain types of data. To use DIMP, you need to create a directory for the incoming bundles and a directory where the bundles are archived after being processed.

On the Enable DIMP installer screen, you select whether DIMP will be used. See [Figure A-11](#). If **Yes** is selected on the screen, you then provide the paths to the directories on the DIMP Configuration installer screen. See [Figure A-12](#).

For detailed information on DIMP, see the *Oracle Retail POS Suite/Merchandising Operations Management Implementation Guide*.

## Oracle Configuration Manager

The Oracle Retail OCM Installer packaged with this release installs the latest version of OCM.

The following document is available through My Oracle Support. Access My Oracle Support at the following URL:

<https://support.oracle.com>

***Oracle Retail Oracle Configuration Manager (OCM) Installer Guide (Doc ID: 1071030.1)***

This guide describes the procedures and interface of the Oracle Retail Oracle Configuration Manager Installer that a retailer runs near the completion of its installation process.

### OCM Documentation Link

[http://www.oracle.com/technology/documentation/oracle\\_retail.html](http://www.oracle.com/technology/documentation/oracle_retail.html)



## Installation Options

During installation, there are options that enable you to select whether the installer completes parts of the installation or if you want to complete those parts manually. For information on the available options, see the following sections:

- ["Database Install Options"](#)
- ["Manual Deployment of the Back Office Application"](#)
- ["Install Parameters"](#)

For information on loading the templates for Labels and Tags, see ["Load Templates for Labels and Tags"](#).

## Database Install Options

The database schema must be created and populated before configuring the application server. On the Install Database Option screen, you select whether the installer creates and populates the database schema or if you want to do this manually.

- If you choose **Create schema with sample dataset**, the installer creates and populates the database with sample data, such as item data. This is the default selection on the screen. The sample dataset includes the minimum dataset and report data. If you want data available to use for demonstrating Back Office functionality after installation, you can select this option.
- If you choose **Create schema with minimum dataset**, the installer creates and populates the database with the minimum amount of data needed to launch and run Back Office. The minimum dataset includes report data. If you want to load your own data after installation, you can select this option.
- If you choose **Skip schema creation and data loading**, the installer does not create and populate the database schema. You choose this option if you want to create and populate the database schema manually. For information on manually creating and populating the database schema, see ["Manually Creating the Database Schema"](#).

---

**Note:** You must populate the database schema before running the installer. Otherwise, the installer will fail when configuring security.

---

## Manually Creating the Database Schema

To manually create and populate the database schema:

1. Change to the `<INSTALL_DIR>/backoffice/db` directory.
2. Set the `JAVA_HOME` and `ANT_HOME` environment variables. You can use the JDK and Ant that are installed with the IBM WebSphere Application Server.

```
JAVA_HOME=<WAS_INSTALL_DIR>/Java; ANT_HOME=<INSTALL_DIR>/ant; export JAVA_HOME
ANT_HOME
```

3. Add `$JAVA_HOME/bin` and `$ANT_HOME/bin` to the front of the `PATH` environment variable.

```
PATH=$JAVA_HOME/bin:$ANT_HOME/bin:$PATH; export PATH
```

4. Expand the `backofficeDBInstall.jar` file.

```
jar -xvf backofficeDBInstall.jar
```

5. Modify `db.properties`.

- a. Uncomment the DB2 properties and comment out the properties for the other vendors such as Oracle and MS-SqlServer.
- b. Set the following properties with your database settings. The values to be set are shown in bold in the examples.

Set the hash algorithm, for example, to SHA-256.

```
# Hash Algorithm
inst.hash.algorithm=HASH_ALGORITHM
```

Enter the values for the users in the following example:

```
inst.app.admin.user=my-pos-admin-user
inst.app.admin.password-encrypted=my-encrypted-pos-admin-password
```

```
db.user=DB_USER_ID
db.password-encrypted=DB_PASSWORD_ENCRYPTED
```

```
db.owner.user=DB_OWNER_USER_ID
db.owner.password-encrypted=DB_OWNER_PASSWORD_ENCRYPTED
```

The ant target will prompt for the passwords. Run the following ant target to encrypt the passwords:

```
ant -f db.xml encrypt-webapp-passwords
```

Enter the values for the URL used by the Back Office application to access the database schema. See [Appendix D](#) for the expected syntax:

```
db.jdbc-url=jdbc:db2://DB_HOST_NAME:DB_PORT_NUMBER/DB_NAME
```

Enter the value for the store ID shown in the following example:

```
configured.store.id=04241
```

Enter the value for the supported locales shown in the following example:

```
gen.locales=fr,zh
```

- c. Set the host name and port number for the `parameters.apphost` property to point to your Back Office installation.

```
parameters.apphost=t3://localhost:<rm_i_port_number>
```

- d. In the `parameters.classpath` property, replace the semicolons used as separators with colons. This is needed to run with Linux systems.

6. Uncomment the following properties in `jndi.properties`. This file is in the `jndi` directory.

```
java.naming.factory.initial=com.evermind.server.rmi.RMIInitialContextFactory
java.naming.security.principal=<user>
java.naming.security.credentials=<user>
```

7. Run one of the available Ant targets to create the database schema and load data.

- `load_sample`: creates the database schema containing the sample dataset. The sample dataset includes the minimum dataset and report data.

- `load_minimum`: creates the database schema containing the minimum dataset. The minimum dataset includes report data.
- `load_reports`: loads report data.

For example: `ant load_sample`

To specifically load the report data, use the following command:

```
ant -f db.xml load_reports
```

## Secure the JDBC for the IBM DB2 Database

On the Enable Secure JDBC screen, you select whether secure JDBC will be used for communication with the database. See [Figure A-9](#).

- If **Yes** is selected, you must install the database digital certificate into the application server truststore.
  1. Log in to the WebSphere Integrated Solutions Console (Admin Console).
  2. Expand the Security menu.
  3. Click the **SSL certificate and key management** option.
  4. In the Related Items list, click **Key stores and certificates**.
  5. Click the **NodeDefaultTrustStore** link in the list.
  6. In the Additional Properties list, click the **Signer certificates** link.
  7. Click the **Add** button.
  8. Enter a distinct alias and the full path to the certificate file on the server in the File name field. Make sure the Data type corresponds to the type in the file. The certificate should appear in the list of Signer certificates.
- If **No** is selected and you want to manually set up the secure JDBC after the installer completes, see [Appendix G](#).

## Set up the JMS SSL Key Store

Selecting US Strength or Export Strength on the Select JMS SSL Level screen requires that a CA certificate and Key Store are used for IBM WebSphere Application Server and WebSphere MQ. You can manually deploy the CA certificate and Key Store for IBM WebSphere Application Server and WebSphere MQ or you can have the installer perform the deployment.

The Key Store entry alias and the Key Store type that the installer uses are contained in the following script:

```
<INSTALL_DIR>/backoffice/appservers/was/cert-env.sh
```

The default alias is `myalias`. The default type of the source Key Store is `jks`. These values can be changed in the script. The type has to be a type supported by the IBM `ikmcmd` utility.

To have the installer do the deployment, enter the details on the JMS SSL Keystore Details screen. See [Figure A-29](#).

---

**Note:** The JMS SSL level must be the same for Back Office and Central Office.

---

If **Yes** is selected on the Filter Based on Distinguished Name screen, you enter the filter name on the Distinguished Name Filter screen. See [Figure A-23](#) and [Figure A-24](#). It is recommended that SSL certificates contain a distinguished name which follows the retailer's naming convention.

## Configure AccessVia for Labels and Tags

If you are installing Back Office with Labels and Tags, you must install and configure the AccessVia software before running the Back Office installer. See [Chapter 3](#).

## Run the Back Office Application Installer

The installer will configure and deploy the Back Office application.

---

---

**Note:** To see details on every screen and field in the application installer, see [Appendix A](#).

---

---

1. Change to the `<INSTALL_DIR>` directory.
2. Set the `JAVA_HOME` environment variable to point to the Java in the IBM WebSphere application server, that is, `<WAS_INSTALL_DIR>/Java`.

---

---

**Note:** The installer is not compatible with versions of Java earlier than 1.6.

---

---

3. If you are using an X server such as Exceed, set the `DISPLAY` environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset `DISPLAY` for text mode.

---

---

**Caution:** Password fields are masked in GUI mode, but in text mode your input is shown in plain text in the console window.

---

---

4. Run the installer.
  - a. Log into the Linux server as a user who is authorized to install software.
  - b. Change the mode of `install.sh` to executable.
  - c. Run the `install.sh` script. This will launch the installer.

---

---

**Note:** The usage details for `install.sh` are shown below. The typical usage for GUI mode does not use arguments.

---

```
install.sh [text | silent websphere]
```

---

After installation is complete, a detailed installation log file is created:  
`orbo-install-app.<timestamp>.log`

The installer leaves behind the  
`ant.install.properties` and `cwallet.sso` files for repeat installations.

## Resolve Errors Encountered During Application Installation

If the application installer encounters any errors, it will halt execution immediately. You can run the installer in silent mode so that you do not have to reenter the settings for your environment. For instructions on silent mode, see [Appendix B](#).

For a list of common installation errors, see [Appendix E](#).

Since the application installation is a full reinstall every time, any previous partial installs will be overwritten by the successful installation.

## Configure IBM WebSphere MQ

IBM WebSphere MQ must be configured with a queue manager and the JMS queues and topics required by Back Office, before Back Office can be deployed. On the Configure MQ Series Option screen, you select whether the installer configures IBM WebSphere MQ or if you manually configure it.

---

**Note:** If IBM WebSphere MQ is installed on a different machine than IBM WebSphere Application Server, you must manually configure it.

---

Typically, when IBM WebSphere MQ is installed, a special user ID (usually `mqm`), and a user group (also `mqm`) are created in the operating system. The MQ installation files and directories have their owner and group set to the IBM WebSphere MQ user ID and group ID.

The user ID used for the Back Office installation, must be made a member of IBM WebSphere MQ's user group, before attempting to create the Back Office queue manager, queues, and topics. For example, if Back Office is installed as user `root`, then `root` must be made a member of the `mqm` group.

Use the following commands to configure IBM WebSphere MQ. `MQ_Install_Dir` is the directory where IBM WebSphere MQ was installed. The values for `<input.jms.server.queue>` and `<input.jms.server.port>` come from the `ant.install.properties` file.

```
<MQ_Install_Dir>/bin/crtmqm -q <input.jms.server.queue>
<MQ_Install_Dir>/bin/strmqm <input.jms.server.queue>
<MQ_Install_Dir>/bin/runmqslr -m <input.jms.server.queue> -p
<input.jms.server.port> -t tcp &
<MQ_Install_Dir>/bin/runmqsc <input.jms.server.queue> <
<INSTALL_DIR>/backoffice/appserver/was/createq.dat
<MQ_Install_Dir>/bin/runmqsc <input.jms.server.queue> <
<MQ_Install_Dir>/java/bin/MQJMS_PSQ.mqsc
<MQ_Install_Dir>/bin/strmqbrk -m <input.jms.server.queue>
```

## Update JMS Configuration for Integration of Point-of-Service with Returns Management

If Point-of-Service will be integrated with Returns Management and a JMS queue is the method that will be used for sending return result messages to Returns Management, you can create a remote queue for the store server for processing the final result messages. Use of the remote queue is an optional alternative to the default released configuration.

---

**Note:** To use the remote queue, updates are also needed to the JMS configuration for Point-of-Service and Returns Management. For more information, see the following guides:

- *Oracle Retail Point-of-Service Installation Guide, Volume 2 - IBM Stack*
  - *Oracle Retail Returns Management Installation Guide, Volume 2 - IBM Stack*
- 

To connect the Back Office JMS server FinalResults queue to the Returns Management JMS server, update the Back Office JMS configuration:

```
DEFINE QLOCAL( 'BO.TO.RM.ERR' ) usage (NORMAL)

DEFINE QLOCAL( 'BO.TO.RM' ) trigger initq('SYSTEM.CHANNEL.INITQ') usage (xmitq)
BOQNAME('BO.TO.RM.ERR') DEFPSIST(YES) TRIGDATA('BO.TO.RM')

DEFINE QREMOTE('FINALRESULT') xmitq('BO.TO.RM') RNAME( 'FINALRESULT' )
RQMQNAME('<QUEUE_MANAGER>')

DEFINE CHANNEL ('BO.TO.RM') chlttype(SDR) xmitq('BO.TO.RM') conname('<HOST(1415)>')
trptype(tcp)
```

1. Replace `<QUEUE_MANAGER>` with the queue manager defined for the Returns Management server.
2. Replace `<HOST(1415)>` with the Returns Management host name and Messaging Engine port.

## Manual Deployment of the Back Office Application

Skip this section if you chose the default option of allowing the installer to complete installation to the application server.

The installer includes the option to configure the application locally and skip deployment to the application server. If this option is chosen, the installer will make the configured application files available under `<INSTALL_DIR>/backoffice/configured-output/`.

If you chose this installer option, you can deploy the Back Office ear file by following these steps:

- To deploy using the ant target:
  1. Update the following property in the `ant.install.properties` file.

```
input.install.to.appserver = true
```
  2. Run the following ant target:

```
install.sh ant init app-ear-deploy -propertyfile ant.install.properties
```

- To deploy from the application server console:

---

**Note:** When deploying the ear file, provide the same application name and context root you gave to the installer. These values were stored in the `<INSTALL_DIR>/ant.install.properties` file by the installer.

---

1. Move your ear file to `<INSTALL_DIR>/backoffice/ear`.
2. Change to the `<INSTALL_DIR>` directory.
3. Configure the ear file.

```
./install.cmd ant init configure
```

4. Manually deploy the ear file from the following location:

```
<INSTALL_DIR>/backoffice/backoffice.ear
```

## Install Parameters

The application parameters must be installed before the Back Office application is fully operational. On the Install Parameters screen, you select whether the installer completes installation of the parameters.

- If you chose Yes, you do not need to perform any further steps to install the parameters. This is the default selection on the screen.
- If you chose No, the installer did not install the parameters. For information on installing the parameters, see ["Import Initial Parameters"](#).

## Import Initial Parameters

---

**Note:** If you did not choose to have the installer set the initial parameters, you must import an initial set of parameters before you can use Oracle Retail Back Office. For more information on parameters, see the *Oracle Retail POS Suite Configuration Guide*.

---

This section provides an overview of the procedures for importing an initial set of parameters. You can import the parameters through the Oracle Retail Back Office user interface or by using an ant target. You only need to use one of the procedures. The procedure for importing parameters through the application user interface is described in more detail in the *Oracle Retail Back Office User Guide*.

These instructions assume you have already expanded the `backofficeDBInstall.jar` file under the `<INSTALL_DIR>` directory as part of the database schema installation earlier in this chapter.

## Importing Parameters Through the User Interface

To import the initial parameters through the user interface:

1. Open the Oracle Retail Back Office application in a web browser. The address is provided at the end of the installer output and in the log file.

```
https://<your host name>:<port number>/<context root>
```

2. Log in to the application as user ID **pos** and password **pos**, or any other user ID that has full administrative rights.
3. Click the **Admin** tab and then the **Job Manager** subtab. Click the **Available Imports** left navigation link. The Available Imports screen appears.
4. To import the master parameter set, click the **File** link in the Import Parameters for Distribution row. Follow the instructions to import `parameterset.xml` from the `<INSTALL_DIR>/backoffice/db` folder.
5. To import the initial set of Oracle Retail Back Office application parameters, click the **File** link in the Import BackOffice Parameters row. Follow the instructions to import `backoffice.xml` from the `<INSTALL_DIR>/backoffice/db` folder.

## Importing Parameters by using an Ant Target

To import parameters using an ant target:

1. Change to the `<INSTALL_DIR>/backoffice/tmp/db` directory.
2. Execute the following command:

```
ant load_parameters
```

## Load Templates for Labels and Tags

To load the templates for Oracle Retail Labels and Tags:

1. Change to the `<INSTALL_DIR>/backoffice/configured-output/db` directory.
2. Run the following command:

```
ant init_labels
```

## Load Optional Purge Procedures

For information on how to invoke the procedures provided for purging aged data, see the *Oracle Retail Back Office Operations Guide*.

To load the purge procedures:

1. Run the available Ant target to load the procedures.  

```
ant load_purge_procedures
```
2. Log in as the database schema owner, `<schema_username>`.
3. Create a user for running the purge procedures. This user should only have the privileges required to run the purge procedures.

## Using the Back Office Application

---

**Note:** When you are done installing Back Office, log out and close the browser window. This ensures that your session information is cleared and prevents another user from accessing Back Office with your login information.

---



After the application installer completes and you have run the initial parameter load, you should have a working Back Office application installation. To launch the application, open a web browser and go to

`https://<servername>:<portnumber>/<context root>`

For example, `https://myhost:9443/backoffice`

---

**Note:** Before viewing any reports for the first time after Back Office is installed, you must open the store. Opening the store creates data that is needed for Reports functionality to work correctly.

---



---

## Configuring the AccessVia Print Engine for Labels and Tags for the IBM Stack

This document also pertains to Oracle customers who have licensed Oracle Retail Signs in conjunction with Oracle Retail Labels and Tags. The Oracle Retail Labels and Tags product restricts printing not to exceed six square inches. To print a size greater than six square inches, the customer must license Oracle Retail Signs.

In order to use the Labels and Tags functionality of Back Office, you need to install the AccessVia product and configure the AccessVia Print Engine.

Before configuring the AccessVia Print Engine, you must have completed the following procedures:

- The installation and configuration of all prerequisite software including the AccessVia product and the database server.
- The installation of the database and creation of the database schema.
- The installation of the application server.
- The installation of the printer.

The following libraries are required for using Labels and Tags. For the tested versions, see [Chapter 1](#):

- AccessVia Print Engine
- IBM DB2 Client
- unixODBC
- GD library
- Xerces

Configuring the AccessVia Print Engine includes the following tasks:

- ["AccessVia Print Engine .ini File"](#)
- ["Configuring the Database for the AccessVia Print Engine"](#)
- ["Configuring for IBM WebSphere"](#)
- ["Updating the AccessVia License File"](#)
- ["Testing the AccessVia Print Engine"](#)
- ["Adding Multiple Printers"](#)

To troubleshoot printing problems, see ["Troubleshooting Labels and Tags Problems on the IBM Stack"](#).

## Creating the AccessVia Print Engine .ini File

The AccessVia Print Engine requires an .ini file for configuration. An initial version of this file is found in `<staging_directory>/backoffice/lib/thirdparty/accessvia7.5/accessvia_IRES/dsign/program/dsign.ini`.

Updates to the .ini file are done as part of the configuration for the application server. For a description and example of this file, see ["AccessVia Print Engine .ini File"](#).

## Configuring the Database for the AccessVia Print Engine

Because Labels and Tags needs to access data from Back Office, AccessVia requires open database connectivity (ODBC) to the Back Office database. AccessVia stores template information in the following Back Office data tables:

- SGFORM—This table stores templates.
- SGELEM—This table stores template attributes.
- SGSQL—This table stores .zip files of SQL, which fetch template data at the time of printing.
- SGCONFIG—This table stores the paths for .ini files required by AccessVia.

## Configuring for IBM WebSphere

For the following steps, `<staging_directory>/backoffice/lib/thirdparty/accessvia7.5/accessvia_IRES` is referred to as `<ACCESSVIA_HOME>`.

To configure for IBM WebSphere:

1. Install the DB2 client and catalog the database for CLI. To catalog the database:
  - a. `db2 catalog tcpip node node1 remote <database_host_name> server <database_port_number>`
  - b. `db2 catalog database <database_name> as <database_alias_name> at node node1`  
The `<database_alias_name>` is used for DBALIAS in the `dsign.ini` file. See [".ini File Example"](#).
2. The DB2 client includes unixODBC. Verify that unixODBC is installed at `/usr/lib/unixODBC`.
3. Copy the `<ACCESSVIA_HOME>/dsign` folder to `/usr/` on the SLEPOS server.
4. Copy `libgd.so.2.0.0` from `<ACCESSVIA_HOME>/usr/lib` to `/usr/lib` on the SLEPOS server.

---

**Note:** If the files already exist, do not replace them.

---

5. Copy the following files from `<ACCESSVIA_HOME>/usr/local/lib` to `/usr/local/lib` on the SLEPOS server:
  - `libxerces-c.so.27.0`
  - `libxerces-depdom.so.27.0`
6. Copy the `odbcinst.ini` file from `<ACCESSVIA_HOME>/etc/unixODBC` to `/usr/local/lib` on the SLEPOS server. Verify that the driver path is correct.

7. Copy the `.odbc.ini` file from `<ACCESSVIA_HOME>/root` to `/root` on the SLEPOS server. Update the database related information.
8. Give executable permissions to all the `.so` files under `/usr/dsign/program`, `/usr/lib/libgd.so.*`, and `/usr/local/lib`.
9. Give executable permission to the `dsign.*` and `*.sh` files under `/usr/dsign/program`.
10. Create the following links. Open a command shell and run the following commands:  
 Navigate to `/usr/lib`.
  - a. `ln -s libgd.so.2.0.0 libgd.so.2`
  - b. `ln -s libgd.so.2 libgd.so`
 Navigate to `/usr/local/lib`.
  - a. `ln -s libodbcpsql.so.1.0.0 libodbcpsql.so.1`
  - b. `ln -s libxerces-c.so.27.0 libxerces-c.so.27`
  - c. `ln -s libxerces-c.so.27 libxerces-c.so`
  - d. `ln -s libxerces-depdom.so.27.0 libxerces-depdom.so.27`
  - e. `ln -s libxerces-depdom.so.27 libxerces-depdom.so`
11. Encrypt the database password in the `/usr/dsign/program/dsign.ini` file:
  - a. Update the user ID and password information for the database schema owner. For information on the schema owner, see ["Create the Database Schema Owner and Data Source Users"](#) in [Chapter 2](#).
  - b. Enter the password in clear text for the PWD property. The field is highlighted in the following example.  

```
CONNECTION=DSN=orbolat1;UID=ORBOLAT1;PWD=mypassword12;DBQ=ORCL;DBA=W;APA=T;
EXC=F;FEN=T;QTO=T;FRC=10;FDL=10;LOB=T;RST=T;BTD=F;BNF=F;BAM=IfAllSuccessful
;NUM=NLS;DPM=F;MTS=T;MDI=F;CSR=F;FWC=F;FBS=64000;TLO=0;
```
  - c. Run the `/usr/dsign/program/env.sh` script.
  - d. To encrypt the password, run the following command:  

```
/usr/dsign/program/dsign -zdsign.ini -x"ENCRYPT_DSN()"
```
  - e. Verify that the password is encrypted in the file.
12. Edit `.bashrc` and verify that the environment is correctly set. There is a sample file at `<ACCESSVIA_HOME>/root`.

## Adding Multiple Printers

To use multiple printers for printing labels and tags, add the printers to the `<INSTALL_DIR>\backoffice\templates\printers.properties` file. The instructions for adding printers are included in the file. This file is deployed to the application server by the installer.

## Updating the AccessVia License File

Oracle Retail Labels and Tags is shipped with a demonstration license file for AccessVia. The demonstration license file needs to be replaced by a full-use production license file.

1. When a retailer purchases Oracle Retail Labels and Tags, Oracle requests the full-use production license file from AccessVia Support through e-mail. AccessVia returns the license file to Oracle within one business day.

The full-use production license file includes the user name and a license end date or an end date of perpetual.

2. Oracle provides the full-use production license file to the retailer or system integrator.
3. The retailer or system integrator updates the license file in the AccessVia installation. The file should be in the same folder as the dsign executable file, for example:

```
/usr/dsign/program/dsign.lic
```

---

---

**Note:** According to AccessVia, if the license file is transferred to a non-Windows platform, an ASCII transfer is required to maintain the correct file format.

---

---

## Back Office Installation

After completing the above steps, run the installer. The following information is needed during the install:

- The paths to the dJava.jar and dsign.ini files are entered on the AccessVia Configuration installer screen. See [Figure A-18](#). These files are found in the following locations:
  - usr/dsign/program/djava.jar
  - usr/dsign/program/dsign.ini
- Sample templates are shipped with the release. On the Load Templates Options installer screen, you select whether to load the templates into the database. See [Figure A-33](#). For information on the templates, see "Labels and Tags Templates".

## Labels and Tags Templates

The templates shipped with this release are found in the following zip file:

```
<install_dir>/backoffice/configured-output/db/template.zip
```

The installer imports the templates in this zip file into the database. For the location of the templates in the database, see ["Configuring the Database for the AccessVia Print Engine"](#).

## Updating or Creating Templates

If templates are updated or new templates are created, a zip file containing the templates can be imported into Back Office using the **Import Labels and Tags Template** import task. For information on the import, see the *Oracle Retail Back Office User Guide*.

Software is available, for example from AccessVia, that can be used to create and update templates. For more information, contact your integrator or implementation staff.

## Configuring Multiple Printers

To use multiple printers for printing labels and tags:

1. To enable users to select from a list of printers on the Add Batch and Batch Detail screens, set up the Allow Multiple Printers parameter. For information on the parameter, see the *Oracle Retail POS Suite Configuration Guide*.
2. If you did not set up the list of printers before running the Back Office installer, add the printers in the `<WAS_PROFILE_DIR>/properties/printers.properties` file. The instructions for adding printers are included in the file.

## Testing the AccessVia Print Engine

After the steps in "[Configuring for IBM WebSphere](#)" are completed and Back Office is installed, test the AccessVia Print Engine.

---

**Note:** The test program is intended to only be used with test data.

---

To test AccessVia for IBM WebSphere:

1. Stop the IBM WebSphere server.
2. Change to the `/usr/dsign/program` directory.
3. To compile the test program, run `compileTest.sh`. This file may need to be updated to meet your configuration.
4. Run the `test_j.sh` test program. This file may need to be updated to meet your configuration.

The template SALTEMP prints.

- If you are getting lib not found, the required dll is not in the system path.
  - If you are getting unsatisfiedLinkerror, the dSIGN dlls and SDK dll do not match.
5. Start the IBM WebSphere server.

## AccessVia Print Engine .ini File

The AccessVia Print Engine requires an .ini file for configuration. This file controls all AccessVia operations and includes the settings for printers, resource paths (fonts and graphics), data source to be used, and so on. For information on the file contents, see "[.ini File Settings](#)". For an example of an .ini file, see "[.ini File Example](#)".

The default name for the AccessVia .ini file is `dsign.ini`. That name is used to refer to it throughout this chapter.

## .ini File Settings

This file contains a series of settings:

- Path settings—These are used by the AccessVia APIs to fetch appropriate attributes at the time of printing. See the *System Setup* section for the paths. GraphicPath, FontPath, and ExePath must point to individual folders. The remaining paths can point to a common folder because they are not used as often. In order for UserPath to be functional, Back Office must have write permission to the dst directory.
  - DataPath—This must point to the folder that contains all the necessary data (data).
  - GraphicPath—This must point to the folder that contains all images required for the print templates (images).
  - FontPath—This must point to the folder that contains all the font files required by the print templates (fonts).
  - UserPath—This must point to the user directory (dst).
  - ExePath—This must point to the folder that contains all AccessVia .dll files (program).
  - SystemPath—This must point to the folder that contains all necessary system files (system).
  - WorkPath—This must point to the folder used by AccessVia APIs to write temp files during the printing process.
- Printer settings—These are the printer attributes. They are located in the *Printer Setup* section. Most of them are the same as the system printer settings. PrintFile, PrintToFile, and PrinterName are the most important attributes; the remaining ones can use default settings.
  - PrinterPort=WS:
  - PrintFile=<AccessVia\_install\_dir>/temp/output.prn
  - PrintToFile=No. However, for initial testing, you can arrange for templates to be printed in an output file (PrintFile) by setting PrintToFile to Yes.
  - PrinterDriver=<printer driver>. Set to the printer driver, for example, POSTSCRIPT. The AccessVia Print Engine prefers PostScript printers to PCL printers.
  - PrinterName=<printer name>. Set to your printer name or use the default printer name.
  - PortSetting1=<IP address>. Set to the IP address of your printer.
  - PortSetting2=<port number>. Set to the port number of your printer.
- Data source settings—These provide AccessVia APIs with the location of templates and template data. These can be stored in the same place, in which case the two settings are identical. In the data sources, set the DSN name, database name, server name, user ID, and password correctly.
  - DATABASE—This is the data source for template data.
  - FORMATS—This is the data source for templates and template attributes.



## .ini File Example

The following is an example of an .ini file.

```
;-----
;--- Database Connection Section -----
;-----

[DCM Global]
DataDriver=ODBC
ConnectRetry=4

;----- DATABASE Connection Properties -----
[DATABASE]
Enabled=True
DataDriver=ODBC
CONNECTION=DSN=ACCVIA;DBALIAS=ACCVIA;UID=orbolat1;PWD=E*s "q#|,<*: (8&6$4"2
;CONNECTION=DSN=smjtest;DBALIAS=SMJTEST
;CONNECTION=DSN=dsign;DBALIAS=DSIGN
SCHEMA_SYS=ACCVIA

[SYSTEM]
Enabled=False

[FORMATS]
Enabled=False

[IMPORTS]
Enabled=False

[EXPORTS]
Enabled=False

[STARTUP]
InitApp=No

;----- System Setup
DataPath=/opt/accessvia/program
GraphicPath=/opt/accessvia/program
FormatPath=/opt/accessvia/program
ExePath=/opt/accessvia/program
SystemPath=/opt/accessvia/system/
FontPath=/opt/accessvia/program
WorkPath=/opt/accessvia/program
UserPath=/opt/accessvia/program

;----- Printer Setup
PrintDriver=POSTSCRIPT
PrinterName=LEXMARK OPTRA T
PrinterPort=WS:
;PrinterPort=/dev/lp0
PrintToFile=Y
PrintFile=output.ps
PrintSpooler=
BumpPageX=0
BumpPageY=0
PaperTray=
PrintCopies=1
PrintMode=No
SignOffset=1
PrinterPortMode=NEW
PrinterOptimizationType=NONE
```

```

PageTotal=No
PortSetting1=10.1.1.49
PortSetting2=9100
PortSetting3=9600,n,8,1

;----- Messaging and Errors
ErrorLog=dsign.err
;Debug=No
;MessageMode=SILENT
;DebugMode=SILENT
Debug=Yes
MessageMode=EXTENSIVE
DebugMode=EXTENSIVE

[ FONTS ]

```

## Setting up a USB Printer in a Network

To set up the printer for printing labels:

1. Install the driver that was included with the printer on the device where the printer is connected.
2. Add an anonymous user.
  - a. Open the Printer Properties for the printer.
  - b. Select the **Security** tab.
  - c. Click **Add**.
  - d. Add the user—**ANONYMOUS LOGON**.
  - e. Click **OK**.
3. Enable network access to the anonymous user.
  - a. From the Control Panel, open **Administrative Tools**. Select **Local Security Policy**.
  - b. Expand Local Policies. Select **Security Options**.
  - c. Select **Network access: Let Everyone permissions apply to anonymous users**. In the window, select **Enabled** and then click **OK**.
4. Add the following printer settings to the `dsign.ini` file.

```

----- Printer Setup -----
PrinterDriver=GDI
PrinterName=\\<printer_IP_address>\DYM0,WinPrint,USB002
PrinterPort=<port_number>
PrinterOptimizationType=NONE
PrintFile=output.ps
PrintToFile=No
PrintCopies=1
PrintMode=No
SignOffset=-d
PrinterPortMode=NEW
PageTotal=No
PortSetting1=
PortSetting2=
PortSetting3=9600,N,8,1
PrintItem=Yes
CustomPaperSize=No

```

## Troubleshooting Labels and Tags Problems on the IBM Stack

This section contains information that may be useful if you encounter problems using Labels and Tags.

- If any problem occur running the test program, make sure the correct version of unixODBC is installed.
- If `test_j.sh` fails, check the `dsign.ini` file. The `Userid` field must be all uppercase, for example:  

```
Userid=ORBOLAT1
```
- If you see an error related to print format, modify the printer settings. The possible values for the `PrinterDriver` field are GDI and PS. The possible values for `PrinterPort` are PM: and WS:.
- In the `dsign.ini` file, modify the `PortSetting` field to the IP address for your network printer.  

```
PortSetting1=10.143.200.26
```
- To improve performance, turn off debug mode in the `dsign.ini` file.  

```
Debug=No
```
- If there is any problem related to the configuration, turn on debug mode in the `dsign.ini` file. Look for the errors in the `dsDebug.txt` and `dsign.err` files.  

```
Debug=Yes
```
- If the testing runs fine but printing from the application server fails, set `PrintToFile=Y` in the `dsign.ini` file. This settings causes the output to be printed to the `output.ps` file. Open the file with Notepad and see if the item information is present.
- If you see an `unsatisfiedLinkError`, verify the paths used to load the `AccessVia` libraries.
- If you have a problem connecting to the database using Designer 7.5, make sure that during the creation of a connection, the schema name is uppercase under the advanced settings.
- If there is any problem with the database connections not getting closed after printing a template, there may be a memory leak issued. Contact `AccessVia` for more information.
- Postscript does not support frames, rules, and layers. When creating templates with `AccessVia`, do not use these options.
- Make sure the ini file path in the `SGCONFIG` table is correctly pointing to the ini file. If it is not, run the update sql. For example:  

```
update SGCONFIG set FCONFIGPARAMVALUE='/usr/dsign/program/dsign.ini'
where FCONFIGPARAMNAME='AccessViaIniFilePath'
```
- Make sure the printer drivers are installed where `AccessVia` is configured.
- In the Printer Setup section, verify that the printer IP address is correct.



---

## Appendix: Installer Screens for the IBM Stack

You need specific details about your environment for the installer to successfully deploy the Back Office application, or the Back Office application with the Labels and Tags module, on the IBM Stack. Depending on the options you select, you may not see some screens or fields.


For each field on a screen, a table is included in this appendix that describes the field.

---

**Note:** When installing the Back Office application with the Labels and Tags module, the title on the installer screens is Labels and Tags Installer. The content of the screens is the same for either installer.

---

**Figure A–1** Introduction



**Figure A–2 Oracle Customer Information**

The screenshot shows a window titled "Back Office Installer - Oracle Retail". Inside, there's a section titled "ORACLE" and "Oracle Customer Information". Below this, a message states: "Provide your email address to be informed of security issues, install the product and initiate configuration manager. See <http://www.oracle.com/support/policies.html> for details." There are three input fields: "Email:" with the placeholder "[username@oracle.com]", "Easier for you if you use your My Oracle Support email address/username." (which is a hint), and "My Oracle Support Password:". Between the email and password fields, there is a checkbox labeled "I wish to receive security updates via My Oracle Support." which is checked. At the bottom, there are four buttons: "Cancel", "Back", "Next", and "Install".

This screen is only displayed if Oracle Configuration Manager (OCM) is to be installed. The OCM collector must be registered with your My Oracle Support account so that the uploaded configuration information can be stored properly and be readily available during the resolution of a service request.

After the Central Office installer completes, the OCM installer runs if OCM is not already installed. For information on OCM, see "[Oracle Configuration Manager](#)" in [Chapter 2](#).


The fields on this screen are described in the following tables.

| Field Title       | Email                                      |
|-------------------|--|
| Field Description | Email address to use for OCM installation. |

| Field Title       | I wish to receive security updates via My Oracle Support. |
|-------------------|---|
| Field Description | To receive security updates, check the box.               |

| Field Title       | My Oracle Support Password   |
|-------------------|--|
| Field Description | Password for the My Oracle Support user to receive security updates. |

**Figure A–3 Requirements**




**Figure A–4 License Agreement**



**Note:** You must choose to accept the terms of the license agreement in order for the installation to continue.

**Figure A–5**    *Supported Languages*



The field on this screen is described in the following table.

| Field Title       | Please enter the supported languages  |
|-------------------|---|
| Field Description | Select the languages that will be available for the Back Office application.<br><br>The languages selected on this screen determine the available choices on the Enter Default Locale screen. |
| Example           | English   |



Figure A-6 Enter Default Locale



The field on this screen is described in the following table.

| Field Title       | Enter Default Locale   |
|-------------------|--|
| Field Description | <p>Locale support in Back Office enables the date, time, currency, calendar, address, and phone number to be displayed in the format for the selected default locale.</p> <p>The choices for default locale are dependent on the selections made on the Supported Languages screen. For each selected language, the default locale for that language is displayed on the Enter Default Locale screen. For example, if English and French are selected on the Supported Languages screen, en_US and fr_FR are the available choices for the default locale.</p> |
| Example           | en_US  |

**Figure A-7 Database Owner**

Back Office Installer - Oracle Retail

ORACLE

**Database Owner**

Provide the details for the Back Office schema user that will create the schema objects.

Schema Username

Schema Password

Cancel Back Next Install

The fields on this screen are described in the following tables.

| Field Title       | Schema Username   |
|-------------------|---|
| Field Description | Schema user name that manages the objects in the schema. This user has Create, Drop, and Alter privileges in the schema, that is, Data Definition Language (DDL) execution privileges. For information on creating this user, see <a href="#">"Create the Database Schema Owner and Data Source Users"</a> in <a href="#">Chapter 2</a> .<br><br><b>Note:</b> This user creates the database objects used by Back Office. |
| Example           | DBOWNER   |

| Field Title       | Schema Password                  |
|-------------------|----------------------------------|
| Field Description | Password for the database owner. |

Figure A-8 Data Source User

Back Office Installer - Oracle Retail

ORACLE

**Data Source User**

Provide the details for the Back Office schema user

JDBC URL

Data Source Username

Data Source password

Cancel Back Next Install


The fields on this screen are described in the following tables.

| Field Title       | JDBC URL   |
|-------------------|--|
| Field Description | URL used by the Back Office application to access the database schema. See <a href="#">Appendix D</a> for the expected syntax. |
| Example           | jdbc:db2://myhost:50001/mydb   |

| Field Title       | Data Source Username   |
|-------------------|--|
| Field Description | Database user name that can access and manipulate the data in the schema. This user can have Select, Insert, Update, Delete, and Execute privileges on objects in the schema, that is, Data Manipulation Language (DML) execution privileges. For information on creating this user, see " <a href="#">Create the Database Schema Owner and Data Source Users</a> " in <a href="#">Chapter 2</a> . |
|                   | <b>Note:</b> This schema user is used by Back Office to access the database.   |
| Example           | DBUSER   |

| Field Title       | Data Source Password               |
|-------------------|------------------------------------|
| Field Description | Password for the data source user. |


**Figure A–9    Enable Secure JDBC**



The field on this screen is described in the following table.

| Field Title       | Enable Secure JDBC?   |
|-------------------|---|
| Field Description | Select whether secure JDBC is to be used for communication with the database. |
| Example           | Yes   |


**Figure A–10 Data Source SSL Configuration**



This screen is only displayed if **Yes** is selected on the Enable Secure JDBC screen. The field on this screen is described in the following table.

| Field Title       | Data Source SSL Port                  |
|-------------------|---------------------------------------|
| Field Description | SSL port used to access the database. |
| Example           | 20397                                 |


**Figure A-11 Enable DIMP**



The field on this screen is described in the following table.

| Field Title       | Enable DIMP?   |
|-------------------|--|
| Field Description | Select whether DIMP will be used. For information on DIMP, see <a href="#">"Enable Data Import"</a> in <a href="#">Chapter 2</a> . |
| Example           | Yes  |

**Figure A-12 DIMP Configuration**




This screen is only displayed if **Yes** is selected on the Enable DIMP screen.

The fields on this screen are described in the following tables.

| Field Title       | DIMP Incoming Path                                       |
|-------------------|--|
| Field Description | Directory where the incoming data import bundles arrive. |
| Example           | /tmp/dataimport/incoming                                 |

| Field Title       | DIMP Archive Path   |
|-------------------|---|
| Field Description | Directory where the incoming data import bundles are archived after processing. |
| Example           | /tmp/dataimport/archive   |

Figure A-13 Database Install Options



The field on this screen is described in the following table.

| Field Title       | Create the database schema?  |
|-------------------|--|
| Field Description | <p>The database schema must be created and populated before starting Back Office. This screen gives you the option to have the installer create and populate the database schema or leave the database schema unmodified.</p> <ul style="list-style-type: none"><li>■ To have the installer create and populate the database schema, select <b>Yes</b>.</li><li>■ To have the installer leave the database schema unchanged, select <b>No</b>.</li></ul> <p>For more information, see "<a href="#">Database Install Options</a>" in <a href="#">Chapter 2</a>.</p> |
| Example           | Yes  |



Figure A-14 Back Office Administrator User

Back Office Installer - Oracle Retail

ORACLE

**Back Office Administrator User**

Enter the username and password for the Back Office administrator account.

The password must satisfy the following criteria:

- Contain at least one alphabetic character
- Contain at least one numeric character
- At least seven characters in length

Back Office Administrator Username: pos

Back Office Administrator Password:


Cancel Back Next Install

The fields on this screen are described in the following tables.

| Field Title       | Back Office Administrator Username                  |
|-------------------|---|
| Field Description | Administrator user for the Back Office application. |
| Example           | pos   |

| Field Title       | Back Office Administrator Password   |
|-------------------|--------------------------------------|
| Field Description | Password for the administrator user. |

**Figure A-15 Cryptology Settings**



Back Office Installer - Oracle Retail

ORACLE

**Cryptology Settings**

Enter the hashing algorithm used to hash passwords.

Hash Algorithm

The field on this screen is described in the following table.

| Field Title       | Hash Algorithm  |
|-------------------|---|
| Field Description | Enter the name of the algorithm used to hash passwords. |
| Example           | SHA-256   |

Figure A-16 Enter Store ID

Back Office Installer - Oracle Retail

ORACLE

**Enter Store ID**

Please enter the 5 digit store id. Pad with leading zeros if necessary.


Store ID

Cancel Back Next Install

The field on this screen is described in the following tables.

| Field Title       | Store ID           |
|-------------------|--------------------|
| Field Description | ID for this store. |
| Example           | 04241              |


**Figure A-17 App Server WAS\_HOME**



The field on this screen is described in the following table.

| Field Title       | WAS_HOME  |
|-------------------|---|
| Field Description | Base directory for the IBM WebSphere Application Server installation. |
| Example           | /opt/IBM/SIF/WebSphere/AppServer                                      |

**Figure A-18 Access Via Configuration**



This screen is only displayed when installing Oracle Retail Back Office with the Labels and Tags module.

The fields on this screen are described in the following tables.

| Field Title       | dJava.jar Path              |
|-------------------|-----------------------------|
| Field Description | Path to the dJava.jar file. |
| Example           | /usr/dsign/dJava.jar        |

| Field Title       | dsign.ini Path   |
|-------------------|--|
| Field Description | Path to the AccessVia Print Engine configuration file. |
| Example           | /usr/dsign/program/dsign.ini                           |

**Figure A-19 Mail Session Details**

Back Office Installer - Oracle Retail

ORACLE

**Mail Session Details**

Please provide mail server details for the Back Office application

SMTP host: mail.example.com

From Address: admin@example.com

Buttons: Cancel, Back, Next, Install

The fields on this screen are described in the following tables.

| Field Title       | SMTP host                              |
|-------------------|--|
| Field Description | Host where the SMTP server is running. |
| Example           | mail.example.com                       |

| Field Title       | From Address                                      |
|-------------------|---|
| Field Description | From address in e-mails generated by Back Office. |
| Example           | admin@example.com                                 |

**Figure A–20 Application Server Details**

Back Office Installer - Oracle Retail

ORACLE

Application Server Details

Server Name: server1

Node Name:

Cell Name:

IIOP Port: 2809

Server Profile:

Timezone: America/Chicago

Cancel Back Next Install

The fields on this screen are described in the following tables.

| Field Title       | Server Name                       |
|-------------------|-----------------------------------|
| Field Description | Name of the IBM WebSphere server. |
| Example           | server1                           |

| Field Title       | Node Name                       |
|-------------------|---------------------------------|
| Field Description | Name of the IBM WebSphere node. |
| Example           | myhostNode01                    |

| Field Title       | Cell Name                       |
|-------------------|---------------------------------|
| Field Description | Name of the IBM WebSphere cell. |
| Example           | myhostNode01Cell                |

| Field Title       | IIOP port   |
|-------------------|---|
| Field Description | IIOP/BOOTSTRAP_ADDRESS port of the IBM WebSphere server. This port can be found in the following file:<br><WAS_PROFILE_DIR>/logs/AboutThisProfile.txt |
| Example           | 2809  |

| Field Title       | Server Profile                     |
|-------------------|------------------------------------|
| Field Description | Name of the IBM WebSphere profile. |
| Example           | AppSrv01                           |

| Field Title       | Timezone                                |
|-------------------|---|
| Field Description | Time zone where this server is running. |
| Example           | America/Chicago                         |

**Figure A-21 JMS Server Details**

The fields on this screen are described in the following tables.

| Field Title       | JMS Host Name   |
|-------------------|---|
| Field Description | Name of the JMS server.<br><br><b>Note:</b> Always use the actual host name and not the IP address or "localhost". There may be problems integrating with Point-of-Service if the actual host name is not used. |
| Example           | myhost  |

| Field Title       | JMS Port                            |
|-------------------|-------------------------------------|
| Field Description | Port number used by the JMS server. |
| Example           | 1414                                |




| Field Title       | JMS Username  |
|-------------------|---|
| Field Description | User name for the JMS server. This user must exist in the Back Office schema. |
| Example           | myuser  |

| Field Title       | JMS Password                 |
|-------------------|------------------------------|
| Field Description | Password for the JMS server. |
| Example           | mypassword                   |

| Field Title       | JMS Queue Manager              |
|-------------------|--------------------------------|
| Field Description | Name of the JMS queue manager. |
| Example           | bo.queue.manager               |


**Figure A–22** *Select JMS SSL Level*



The field on this screen is described in the following table. For more information, see ["Set up the JMS SSL Key Store" in Chapter 2](#).

| Field Title       | Select JMS SSL Level  |
|-------------------|---|
| Field Description | <p>JMS SSL level to be used.</p> <ul style="list-style-type: none"> <li>To use US strength, select <b>US Strength</b>(TRIPLE_DES_SHA_US). The next screen displayed is <a href="#">Figure A-23</a>.</li> <li>To use export strength, select <b>Export Strength</b>(RC4_MDS_EXPORT). The next screen displayed is <a href="#">Figure A-23</a>.</li> <li>To not use ssl support, select <b>No SSL Support</b>. The next screen displayed is <a href="#">Figure A-25</a>.</li> </ul> |
| Example           | US Strength(TRIPLE_DES_SHA_US)  |

**Figure A-23 Filter Based on Distinguished Name**




This screen is only displayed if **US Strength**(TRIPLE\_DES\_SHA\_US) or **Export Strength**(RC4\_MDS\_EXPORT) is selected on the Select JMS SSL Level screen.

The field on this screen is described in the following table.

| Field Title       | Filter based on Distinguished Name?   |
|-------------------|---|
| Field Description | This screen gives you the option to filter based on the distinguished name. |
| Example           | Yes   |

**Figure A-24 Distinguished Name Filter**




This screen is only displayed if **Yes** is selected on the Filter based on Distinguished Name screen.

The field on this screen is described in the following table.

| Field Title       | Filter Value                               |
|-------------------|--|
| Field Description | Distinguished name for the JMS SSL filter. |
| Example           | CN=bo.server.example.com                   |

Figure A-25 Central Office JMS Server Integration



The field on this screen is described in the following table.

| Field Title       | Integrate with Central Office JMS Server?   |
|-------------------|---|
| Field Description | <div>This screen gives you the option to integrate the Back Office application with a Central Office JMS server.</div> <div><b>Note:</b> If you select <b>Yes</b>, the Central Office application must be running in order for the Back Office files to be installed correctly.</div> |
| Example           | Yes   |

**Figure A–26 Central Office JMS Server Details**

The screenshot shows a window titled "Back Office Installer - Oracle Retail" with the Oracle logo. Below the logo is a section titled "Central Office JMS Server Details". This section contains five labeled input fields: "CO JMS Host Name", "CO JMS Port" (containing the text "1415"), "CO JMS Username", "CO JMS Password", and "CO JMS Queue Manager" (containing the text "co.queue.manager"). At the bottom of the window, there are four buttons: "Cancel", "Back", "Next", and "Install".

This screen is only displayed if **Yes** is selected on the Central Office JMS Server Integration screen.

The fields on this screen are described in the following tables.


| Field Title       | CO JMS Server Name   |
|-------------------|--|
| Field Description | Name of the Central Office JMS server.<br><br><b>Note:</b> Always use the actual host name and not the IP address or "localhost". There may be problems integrating with Point-of-Service if the actual host name is not used. |
| Example           | Server1  |

| Field Title       | CO JMS Server Port                                 |
|-------------------|--|
| Field Description | Port number used by the Central Office JMS server. |
| Example           | 1414   |

| Field Title       | CO JMS Username  |
|-------------------|--|
| Field Description | User name for the Central Office JMS server. This user must exist in the operating system where Central Office is running and the user must be in the mqm group. |
| Example           | myuser   |

|                          |  |
|--------------------------|--|
| <b>Field Title</b>       | <b>CO JMS Password</b>   |
| <b>Field Description</b> | Password for the user name entered in the CO JMS Username field. |
| <b>Field Title</b>       | <b>CO JMS Queue Manager</b>                                      |
| <b>Field Description</b> | Name of the Central Office JMS queue manager.                    |
| <b>Example</b>           | co.queue.manager   |


**Figure A-27** *Configure WebSphere MQ Option*



The field on this screen is described in the following table.

|                          |   |
|--------------------------|---|
| <b>Field Title</b>       | <b>Configure WebSphere MQ?</b>  |
| <b>Field Description</b> | IBM WebSphere MQ must be configured with a queue manager and the queues and topics required by Back Office before Back Office can be deployed. This screen gives you the option to configure IBM WebSphere MQ manually. If you choose No, see <a href="#">"Configure IBM WebSphere MQ"</a> in <a href="#">Chapter 2</a> for the manual steps you need to perform after the installer completes. |
| <b>Example</b>           | Yes   |

Figure A–28 WebSphere MQ Directory



This screen is only displayed if **Yes** is selected on the Configure WebSphere MQ Option screen.

The field on this screen is described in the following table.

| Field Title       | WebSphere MQ Dir                     |
|-------------------|--------------------------------------|
| Field Description | Base directory for IBM WebSphere MQ. |
| Example           | /opt/mqm                             |

**Figure A–29 JMS SSL Keystore Passwords**

The screenshot shows the 'JMS SSL Keystore Details' window. It has a title bar 'Back Office Installer - Oracle Retail' and the Oracle logo. The main area is titled 'JMS SSL Keystore Details' and contains a section 'Keystore Details'. This section lists several fields: 'Corporate CA Certificate File' with a text box containing '/tmp/root-cert.pem' and a 'Select File' button; 'MQ Keystore Password' with an empty text box; 'MQ Source Keystore' with a text box containing '/tmp/mq-keystore.jks' and a 'Select File' button; 'Password for MQ Source Keystore' with an empty text box; 'WebSphere Keystore Password' with an empty text box; 'WebSphere Source Keystore' with a text box containing '/tmp/was-keystore.jks' and a 'Select File' button; and 'Password for WebSphere Source Keystore' with an empty text box. Below these fields is a note: 'Note: The MQ source keystore must be an a directory accessible by the MQ user and the MQ user must have read permissions for the file.' At the bottom of the window are four buttons: 'Cancel', 'Back', 'Next', and 'Install'.

This screen is only displayed if **US Strength(TRIPLE\_DES\_SHA\_US)** or **Export Strength(RC4\_MDS\_EXPORT)** is selected on the Select JMS SSL Level screen.

The fields on this screen are described in the following tables.

| Field Title       | Corporate CA Certificate File               |
|-------------------|---|
| Field Description | Location of the corporate certificate file. |
| Example           | /tmp/root-cert.pem                          |

| Field Title       | MQ Keystore Password                 |
|-------------------|--------------------------------------|
| Field Description | Key Store password for WebSphere MQ. |

| Field Title       | MQ Source Keystore                                 |
|-------------------|--|
| Field Description | Location of the source Key Store for WebSphere MQ. |
| Example           | /tmp/mq-keystore.jks                               |

| Field Title       | Password for MQ Source Keystore   |
|-------------------|-----------------------------------|
| Field Description | Key Store password for MQ source. |


| Field Title       | WebSphere Keystore Password                              |
|-------------------|--|
| Field Description | Key Store password for the WebSphere Application Server. |



|                    |   |
|--------------------|---|
| <b>Field Title</b> | <b>WebSphere Source Keystore</b>                |
| Field Description  | Location of the source Key Store for WebSphere. |
| Example            | /tmp/was-keystore.jks                           |

|                    |   |
|--------------------|---|
| <b>Field Title</b> | <b>Password for WebSphere Source Keystore</b> |
| Field Description  | Key Store password for WebSphere.             |

**Figure A–30 Manual Deployment Option**



The field on this screen is described in the following table.

|                    |   |
|--------------------|---|
| <b>Field Title</b> | <b>Install files to app server?</b>   |
| Field Description  | By default, the installer will deploy the ear file. This screen gives you the option to configure the application in the staging area for use in a manual installation at a later time. This option can be used in situations where modifications to the deployed files must be reviewed by another party before being applied. |
| Example            | Yes   |

**Figure A–31 Application Deployment Details**

**Back Office Installer - Oracle Retail**

ORACLE

**Application Deployment Details**

The default values shown below are examples

Enter the deployment name for the Back Office application. This is the name by which the application will be identified in the application server.

App Deployment Name

Enter the web context root for this application. The web URL used to access the application will be https://server:port/contextroot/index.jsp


Context Root

The fields on this screen are described in the following tables.

| Field Title       | App Deployment Name  |
|-------------------|--|
| Field Description | Name by which this Back Office application will be identified in the application server. |
| Example           | BackOffice   |

| Field Title       | Context Root   |
|-------------------|--|
| Field Description | Path under the HTTPS URL that will be used to access the Back Office application. For example, a context root of 'backoffice' will result in the application being accessed at https://host:port/backoffice/index.jsp. |
| Example           | backoffice   |


Figure A-32 Install Parameters Option



The field on this screen is described in the following table.

| Field Title       | Install the parameters?  |
|-------------------|--|
| Field Description | The application parameters must be set up before Back Office can be used. This screen gives you the option to set up the parameters manually. If you choose No, see <a href="#">"Import Initial Parameters"</a> in <a href="#">Chapter 2</a> for the manual steps you need to perform after the installer completes. |
| Example           | Yes  |

**Figure A–33 Load Templates Option**




This screen is only displayed when installing Oracle Retail Back Office with the Labels and Tags module.

The field on this screen is described in the following table.

| Field Title       | Load the templates?  |
|-------------------|--|
| Field Description | <p>Sets whether sample templates for printing labels are loaded into the database after Back Office is installed. For more information, see <a href="#">"Labels and Tags Templates"</a> in <a href="#">Chapter 3</a>.</p> <ul style="list-style-type: none"><li>■ To load the templates, choose Yes.</li><li>■ To not load the templates, choose No.</li></ul> |
| Example           | Yes  |


Figure A-34 Value-Added Tax (VAT)




The field on this screen is described in the following table.

| Field Title       | Enable VAT?  |
|-------------------|--|
| Field Description | <div>Sets whether Value-Added Tax is used in Back Office.</div> <div><div></div><div>To enable Back Office to use VAT, choose Yes.</div><div></div><div>To not use VAT, choose No.</div></div> |
| Example           | No   |

**Figure A–35 Installation Progress**



**Figure A–36 Installation Complete**



After the installer completes, the Oracle Configuration Manager (OCM) installer runs if OCM is not already installed. For information on OCM, see ["Oracle Configuration Manager"](#) in [Chapter 2](#).

---

## Appendix: Installer Silent Mode

In addition to the GUI and text interfaces of the Back Office installer, there is a silent mode that can be run. This mode is useful if you wish to run a new installation and use the settings you provided in a previous installation. It is also useful if you encounter errors during an installation and wish to continue after resolving them.

The installer runs in two distinct phases. The first phase involves gathering settings from the user. At the end of the first phase, a properties file named `ant.install.properties` is created with the settings that were provided and the `cwallet.sso` file is created. In the second phase, this properties file is used to provide your settings for the installation.

To skip the first phase and re-use the `ant.install.properties` and `cwallet.sso` files from a previous run, follow these instructions:

1. Edit the `ant.install.properties` file and correct any invalid settings that may have caused the installer to fail in its previous run.
2. If the previous install was successful, the `cwallet.sso` file is found in the installation directory for that install. Copy the `cwallet.sso` file to `<INSTALL_DIR>` for this silent install.
3. Run the installer again with the silent argument.

```
install.sh silent websphere
```





---

## Appendix: Reinstalling Back Office

Back Office does not provide the capability to uninstall and reinstall the application. If you need to run the Back Office installer again, perform the following steps.

### Reinstalling Back Office on the IBM Stack

To reinstall:

1. Stop the WebSphere application server in the profile that contains Back Office.
2. Delete the profile.
3. Stop the WebSphere MQ queue manager and listener. For example, stop `bo.queue.manager`.
4. Delete the queue manager.
5. Recreate the profile.
6. Start the WebSphere application server in the profile.
7. Run the Back Office installer. For more information, see ["Run the Back Office Application Installer"](#) in [Chapter 2](#).



---

## Appendix: URL Reference

Both the database schema and application installers for the Back Office product will ask for several different URLs. These include the following.

### URLs for the IBM Stack

The following sections describe the URLs used for the IBM stack.

#### JDBC URL for a Database

Used by the Java application and by the installer to connect to the database.

Syntax: `jdbc:db2://<dbhost>:<dbport>/<dbname>`

- `<dbhost>`: host name of the database server
- `<dbport>`: database listener port
- `<dbname>`: system identifier for the database

For example, `jdbc:db2://myhost:50000/mydatabase`

#### JNDI Provider URL for an Application

Used for server-to-server calls between applications.

Syntax: `corbaloc:iiop:<host>:<iioport>`

- `<host>`: host name of the WebSphere server
- `<iioport>`: IIOP/BOOTSTRAP\_ADDRESS port of the WebSphere server. This can be found in the `<WAS_HOME>/profiles/<profile_name>/properties/portdef.props` file.

For example, `corbaloc:iiop:myhost:2809`



---

## Appendix: Common Installation Errors

This appendix describes some common errors encountered during installation of Back Office.

### Unreadable Buttons in the Installer

If you are unable to read the text within the installer buttons, it probably means that your JAVA\_HOME needs to be set to a version 1.6 JDK. Set JAVA\_HOME to a Java development kit of version 1.6 or later and run the installer again.



---

## Appendix: Best Practices for Passwords

This appendix has information on the practices that should be followed for passwords. The following topics are covered:

- ["Password Guidelines"](#)
- ["Special Security Options for IBM DB2 Databases"](#)

### Password Guidelines

To make sure users and their passwords are properly protected, follow these guidelines. The guidelines are based on the Payment Card Industry Data Security Standard (PCI-DSS):

- Verify the identity of the user before resetting any passwords.
- Set first-time passwords to a unique value for each user and require the password to be changed immediately after the first use.
- Immediately revoke access for any terminated users.
- Remove inactive user accounts at least every 90 days.
- Enable accounts used by vendors for remote maintenance only during the time period when access is needed.
- Communicate password procedures and policies to all users who have access to cardholder data.
- Do not use group, shared, or generic accounts and passwords.
- Require user passwords to be changed at least every 90 days.
- Require a minimum password length of at least seven characters.
- Require that passwords contain both numeric and alphabetic characters.
- Do not accept a new password that is the same as any of the last four passwords used by a user.
- Limit the number of repeated access attempts by locking out the user ID after not more than six attempts.
- Set the lockout duration to thirty minutes or until an administrator enables the user ID.

## Special Security Options for IBM DB2 Databases

The security for DB2 is done at the operating system level. Consult your IBM DB2 documentation for information on creating a security profile that follows the password guidelines.



---

## Appendix: Secure JDBC with IBM DB2

This appendix has information on how to enable SSL for IBM DB2. Information from the DB2 V9 Information Center, *Global Security Kit Secure Sockets Layer Introduction*, and *iKeyman User's Guide* is included in this appendix.

IBM DB2 has supported SSL encryption since version 9.1 Fix Pack 3. Information on how to configure SSL on the server and client can be found at the following Web sites:

- <http://publib.boulder.ibm.com/infocenter/db2luw/v9/index.jsp?topic=/com.ibm.db2.udb.uprun.doc/doc/t0025241.htm>
- <http://www-1.ibm.com/support/docview.wss?uid=swg21249656>

### Summary

To secure JDBC on IBM DB2 requires the following:

- An SSL provider must be established on the DB2 server.
- The provider requires a digital certificate and corresponding private key to provide the secure communications.
- The client either needs to have a copy of the digital certificate or trust the signer of the server certificate.
- The client needs to be configured to use the secure service, and optionally use a FIPS-compliant SSL provider.

### Prerequisites

The information in this section is from the DB2 V9 Information Center.

1. Make sure you have the required fix pack version of DB2.

To determine the fix pack level you have, run the `db2level` command at the command line. If you have Version 9.1 with a fix pack version earlier than Fix Pack 3, you need to obtain Fix Pack 3 or a later version.

2. Make sure the GSKit is installed.

On linux, it is located in `/usr/local/ibm/gsk7`.

3. Make sure the GSKit libraries are in the path.

Make sure the `/usr/local/ibm/gsk7/lib` directory is included in `LD_LIBRARY_PATH`.

4. For information on how to check if the connection concentrator is in use, see the IBM documentation.

## Setting up the Key Store

The information in this section is from *Global Security Kit Secure Sockets Layer Introduction* and *iKeyman User's Guide*.

1. If you are not already logged in to the server, log in as the instance owner.
2. Start iKeyman GUI gsk7ikm.  
If the Java Cryptographic Extension(JCE) files were not found, make sure the JAVA\_HOME environment variable points to a JDK that contains the JCE.
3. Click **Key Database File** and then **New**.
4. Select a key database type, filename, and location.  
It is suggested that a CMS key database is created. This is consistent with the DB2 Infocenter example. For example:  

```
/home/db2inst1/GSKit/Keystore/key.kdb
```
5. Click **OK**. The Password Prompt window is displayed.
6. Enter a password for the key database.
7. Click **OK**. A confirmation window is displayed. Click **OK**.

## Creating a Self-signed Digital Certificate for Testing

The information in this section is from *Global Security Kit Secure Sockets Layer Introduction* and *iKeyman User's Guide*.

1. If you are not already logged in to the server, log in as the instance owner.
2. Start iKeyman GUI gsk7ikm.  
If the Java Cryptographic Extension(JCE) files were not found, make sure the JAVA\_HOME environment variable points to a JDK that contains the JCE.
3. Click **Key Database File** and then **Open**.
4. Select the key database file where you want to add the self-signed digital certificate.
5. Click **Open**. The Password Prompt window is displayed.
6. Select **Personal Certificates** from the menu.
7. Click **New Self-Signed**. The Create New Self-Signed Certificate Window is displayed.
8. Type a Key Label, such as `keytest`, for the self-signed digital certificate.
9. Type a **Common Name and Organization**, and select a **Country**. For the remaining fields, accept the default values or enter new values.
10. Click **OK**. The IBM Key Management Window is displayed. The Personal Certificates field shows the name of the self-signed digital certificate you created.

## Configuring the IBM DB2 Server

The information in this section is from the DB2 V9 Information Center.

1. If you are not already logged in to the server, log in as the instance owner.

## 2. Create an SSL configuration file:

- For Linux and UNIX:

<INSTHOME>/cfg/SSLconfig.ini

For example:

/home/db2inst1/sqllib/cfg/SSLconfig.ini

- For Windows:

<INSTHOME>\SSLconfig.ini

For example:

F:\IBM\SQLLIB\DB2\SSLconfig.ini

<INSTHOME> is the home directory of the instance.

---

**Caution:** It is recommended that you set the file permission to limit access to the `SSLconfig.ini`, as the file might contain sensitive data. For example, limit read and write authority on the file to members of the SYSADM group if the file contains the password for the Key Store.

---

- ## 3. Add SSL parameters to the SSL configuration file. The `SSLconfig.ini` file contains the SSL parameters that are used to load and start SSL. The list of SSL parameters are shown in the following table:

| SSL parameter name     | Description  |
|------------------------|--|
| DB2_SSL_KEYSTORE_FILE  | Fully qualified file name of the Key Store that stores the Server Certificate.                         |
| DB2_SSL_KEYSTORE_PW    | Password of the Key Store that stores the Server Certificate.  |
| DB2_SSL_KEYSTORE_LABEL | Label for the Server Certificate. If it is omitted, the default certificate for the Key Store is used. |
| DB2_SSL_LISTENER       | Service name or port number for the SSL listener.  |

The following is an example of an `SSLconfig.ini` file:

```
DB2_SSL_KEYSTORE_FILE=/home/db2inst1/GSKit/Keystore/key.kdb
DB2_SSL_LISTENER=20397
DB2_SSL_KEYSTORE_PW=abcd1234
```

- ## 4. Add the value SSL to the DB2COMM registry variable. For example, use the following command:

```
db2set -i <db2inst1> DB2COMM=SSL
```

where <db2inst1> is the IBM DB2 instance name.

The database manager can support multiple protocols at the same time. For example, to enable both TCP/IP and SSL communication protocols:

```
db2set -i <db2inst1> DB2COMM=SSL,TCPIP
```

5. Restart the IBM DB2 instance. For example, use the following commands:

```
db2stop
```

```
db2start
```

At this point, the server should be ready to start serving SSL connections. You can check the `db2diag.log` file for errors. There should be no errors pertaining to SSL after the restart.

## Exporting a Certificate from iKeyman

The information in this section is from *Global Security Kit Secure Sockets Layer Introduction* and *iKeyman User's Guide*.

In order to be able to talk to the server, the clients need to have a copy of the self-signed certificate from the server.

1. Start iKeyman. The IBM Key Management window is displayed.
2. Click **Key Database File** and then **Open**. The Open window is displayed.
3. Select the source key database. This is the database that contains the certificate you want to add to another database as a signer certificate.
4. Click **Open**. The Password Prompt window is displayed.
5. Enter the key database password and click **OK**. The IBM Key Management window is displayed. The title bar shows the name of the selected key database file, indicating that the file is open and ready.
6. Select the type of certificate you want to export: Personal or Signer.
7. Select the certificate that you want to add to another database.
  - If you selected Personal, click **Extract Certificate**.
  - If you selected Signer, click **Extract**.

The Extract a Certificate to a File window is displayed.

8. Click **Data type** and select a data type, such as Base64-encoded ASCII data. The data type needs to match the data type of the certificate stored in the certificate file. The iKeyman tool supports Base64-encoded ASCII files and binary DER-encoded certificates.
9. Enter the certificate file name and location where you want to store the certificate, or click **Browse** to select the name and location.
10. Click **OK**. The certificate is written to the specified file, and the IBM Key Management window is displayed.

## Configuring the IBM FIPS-compliant Provider for SSL (optional)

The information in this section is from the DB2 V9 Information Center.

The Sun JSSE SSL provider works with the IBM DB2 driver by following the above instructions. If you want to use the IBM FIPS-compliant provider, you have to use the IBM JDK and make the following configuration changes.

---

**Note:** If you are following the IBM documentation, note the following issues:

- Prior to the numbered steps, it says to add several lines to `java.security`. Do not add the lines.
  - Step two incorrectly shows setting `ssl.SocketFactory.provider` twice. It only needs to be done once.
- 

1. Set the `IBMJSSE2 FIPS` system property to enable FIPS mode:

```
com.ibm.jsse2.JSSEFIPS=true
```

2. Set security properties to ensure that all JSSE code uses the `IBMJSSE2` provider. The following example shows the entries in `java.security`.

```
ssl.SocketFactory.provider=com.ibm.jsse2.SSLSocketFactoryImpl
ssl.ServerSocketFactory.provider=com.ibm.jsse2.SSLServerSocketFactoryImpl
```

3. Add the `IBMJCEFIPS` cryptographic provider.

Add `com.ibm.crypto.fips.provider.IBMJCEFIPS` to the provider list before the `IBMJCE` provider. Do not remove the `IBMJCE` provider. The `IBMJCE` provider is required for Key Store support.

The following example shows the entries in `java.security`.

```
# List of providers and their preference orders (see above):
#
security.provider.1=com.ibm.jsse2.IBMJSSEProvider2
# inserted provider 2 for FIPS
security.provider.2=com.ibm.crypto.fips.provider.IBMJCEFIPS
security.provider.3=com.ibm.crypto.provider.IBMJCE
security.provider.4=com.ibm.security.jgss.IBMJGSSProvider
security.provider.5=com.ibm.security.cert.IBMCertPath
security.provider.6=com.ibm.security.sasl.IBMSASL
```

## Specific Instructions for Back Office

It is difficult to configure Oracle Retail Back Office to use secure JDBC from the start by using the URL that includes the `sslConnection` property and secure port number. The following instructions are for retrofitting it into the configuration after the install is complete.

To complete the configuration:

1. Install the database digital certificate into the application server truststore.
  - a. Log in to the WebSphere Integrated Solutions Console (Admin Console).
  - b. Expand the Security menu.
  - c. Click the **SSL certificate and key management** option.
  - d. In the Related Items list, click **Key stores and certificates**.
  - e. Click the **NodeDefaultTrustStore** link in the list.
  - f. In the Additional Properties list, click the **Signer certificates** link.
  - g. Click the **Add** button.

- h. Enter a distinct alias and the full path to the certificate file on the server in the File name field. Make sure the Data type corresponds to the type in the file. The certificate should appear in the list of Signer certificates.
2. Update all the data sources to use SSL. (jdbc/DataSource, jdbc/DimpDataSource, jdbc/DimpDataSource)
  - a. Log in to the WebSphere Integrated Solutions Console (Admin Console).
  - b. Expand the Resources menu option.
  - c. Expand the JDBC menu option.
  - d. Click the **Data sources** option. The list of data sources is displayed.
  - e. Click on the data source to be edited.
  - f. In the Additional Properties list, click the **Custom properties** link.
  - g. Click the **New** button.
  - h. Enter sslConnection in the Name field, true in the Value field, and click **OK**.
  - i. Click the data source name in the bread crumb trail to return to the data source edit page.
  - j. Change the Port number field from the TCPIP port to the SSL port.
  - k. Click **OK**.
  - l. Edit the remaining data sources.
  - m. Save the configuration.
3. Stop the server.
4. Edit the custom user registry properties in customRegistry.properties.
  - a. Change the JDBC URL to use the SSL port.
  - b. Append :sslConnection=true; to the end.
5. Start the server.

## Useful Links

For more information, see the following Web sites:

- <http://publib.boulder.ibm.com/infocenter/db2luw/v9/topic/com.ibm.db2.udb.apdv.java.doc/doc/rjvdsprp.htm>

This Web site has documentation of all the properties available in the DB2 Driver for JDBC.

- <http://publib.boulder.ibm.com/infocenter/db2luw/v9/topic/com.ibm.db2.udb.apdv.java.doc/doc/tjvjcccn.htm>

This Web site contains documentation of the URL syntax for connecting to DB2 using JDBC.

- <http://www.redbooks.ibm.com/abstracts/sg247555.html>

An IBM Redbook on security related issues with DB2, including auditing and data encryption. The IBM Form Number is SG24-7555-00.

---

## Appendix: Installation Order

This section provides a guideline for the order in which the Oracle Retail applications should be installed. If a retailer has chosen to use only some of the applications, the order is still valid, less the applications not being installed.

---

**Note:** The installation order is not meant to imply integration between products.

---

### Enterprise Installation Order

1. Oracle Retail Merchandising System (RMS), Oracle Retail Trade Management (RTM), Oracle Retail Sales Audit (ReSA), Optional: Oracle Retail Fiscal Management (ORFM)

---

**Note:** ORFM is an optional application for RMS if you are implementing Brazil localization.

---

2. Oracle Retail Service Layer (RSL)
3. Oracle Retail Extract, Transform, Load (RETL)
4. Oracle Retail Active Retail Intelligence (ARI)
5. Oracle Retail Warehouse Management System (RWMS)
6. Oracle Retail Allocation
7. Oracle Retail Invoice Matching (ReIM)
8. Oracle Retail Price Management (RPM)

---

**Note:** During installation of RPM, you are asked for the RIBforRPM provider URL. Since RIB is installed after RPM, make a note of the URL you enter. If you need to change the RIBforRPM provider URL after you install RIB, you can do so by editing the `remote_service_locator_info_ribserver.xml` file.

---

9. Oracle Retail Central Office (ORCO)
10. Oracle Retail Returns Management (ORRM)
11. Oracle Retail Back Office (ORBO) or Back Office with Labels and Tags (ORLAT)

**12. Oracle Retail Store Inventory Management (SIM)**

---

**Note:** During installation of SIM, you are asked for the RIB provider URL. Since RIB is installed after SIM, make a note of the URL you enter. If you need to change the RIB provider URL after you install RIB, you can do so by editing the `remote_service_locator_info_ribserver.xml` file.

---

- 13. Oracle Retail Predictive Application Server (RPAS)**
- 14. Oracle Retail Demand Forecasting (RDF)**
- 15. Oracle Retail Category Management (CM)**
- 16. Oracle Retail Replenishment Optimization (RO)**
- 17. Oracle Retail Analytic Parameter Calculator Replenishment Optimization (APC RO)**
- 18. Oracle Retail Regular Price Optimzation (RPO)**
- 19. Oracle Retail Merchandise Financial Planning (MFP)**
- 20. Oracle Retail Size Profile Optimization (SPO)**
- 21. Oracle Retail Assortment Planning (AP)**
- 22. Oracle Retail Item Planning (IP)**
- 23. Oracle Retail Item Planning Configured for COE (IP COE)**
- 24. Oracle Retail Advanced Inventory Planning (AIP)**
- 25. Oracle Retail Integration Bus (RIB)**
- 26. Oracle Retail Point-of-Service (ORPOS)**
- 27. Oracle Retail Markdown Optimization (MDO)**
- 28. Oracle Retail Clearance Optimization Engine (COE)**
- 29. Oracle Retail Analytic Parameter Calculator for Markdown Optimization (APC-MDO)**
- 30. Oracle Retail Analytic Parameter Calculator for Regular Price Optimization (APC-RPO)**
- 31. Oracle Retail Promotion Intelligence and Promotion Planning and Optimization (PI-PPO)**
- 32. Oracle Retail Workspace (ORW)**