
Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Developer's Guide

September 2009

Copyright © 1988, 2009, Oracle and/or its affiliates. All rights reserved.

Trademark Notice

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

License Restrictions Warranty/Consequential Damages Disclaimer

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007).
Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

Hazardous Applications Notice

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Third Party Content, Products, and Services Disclaimer

This software and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third party content, products and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third party content, products or services.

Contents

Preface

PeopleCode Developer's Guide Preface	xiii
Overview of PeopleCode Developer's Guide	xiii
PeopleCode Typographical Conventions	xiii

Chapter 1

Getting Started with PeopleCode	1
PeopleCode Overview	1
Creating PeopleCode Programs	2

Chapter 2

Understanding the PeopleCode Language	5
PeopleCode Language Structure	5
Data Types	5
Conventional Data Types	6
Object Data Types	7
Comments	9
Statements	10
Separators	11
Assignment Statements	11
Language Constructs	11
Branching Statements	12
Conditional Loops	15
Functions	15
Supported Functions	16
Function Definitions	16
Function Declarations	17
Function Calls	17
Function Return Values	18
Function Naming Conflicts	18
Expressions	19
Expression Fundamentals	19
Constants	19

Functions as Expressions	21
System Variables	21
Metastrings	21
Record Field References	22
Definition Name References	23
Reserved Word Summary Table	24
Variables	26
Supported Variable Types	26
User-Defined Variables	27
User-Defined Variable Declaration and Scope	27
Variable Declaration	28
User-Defined Variable Initialization	29
Restrictions on Variable Use	29
Scope of Local Variables	30
Duration of Local Variables	30
Variables and Functions	31
Recursive Functions	32
State of Shared Objects Using PeopleSoft Pure Internet Architecture	32
Operators	33
Math Operators	33
Operations on Dates and Times	34
String Concatenation	34
@ Operator	35
Comparison Operators	35
Boolean Operators	36

Chapter 3

Understanding Objects and Classes in PeopleCode	39
Classes and Objects	39
Classes	39
Objects	40
Object Instantiation	40
Creating and Using Objects	40
Instantiating Objects	41
Changing Properties	41
Invoking Methods	42
Copying Objects	43
Assigning Objects	43
Passing Objects	44

Chapter 4

Referencing Data in the Component Buffer	47
Understanding Component Buffer Structure and Contents	47
Component Buffer Contents	47
Rowsets and Scroll Areas	49
Record Fields and the Component Buffer	50
Specifying Data with Contextual References	51
Understanding Current Context	51
Using Contextual Row References	53
Using Contextual Buffer Field References	54
Specifying Data with References Using Scroll Path Syntax and Dot Notation	56
Understanding Scroll Paths	56
Structuring Scroll Path Syntax in PeopleTools 7.5	56
Referencing Scroll Levels, Rows, and Buffer Fields	59

Chapter 5

Accessing the Data Buffer	67
Understanding Data Buffer Access	67
Data Buffer Access	67
Access Classes	67
Data Buffer Model and Data Access Classes	68
Understanding Data Buffer Classes Examples	68
Employee Checklist Page Structure	69
Object Creation Examples	72
Data Buffer Hierarchy Examples	78
Rowset Examples	82
Hidden Work Scroll Example	84
Understanding Current Context	85
Accessing Secondary Component Buffer Data	87
Instantiating Rowsets Using Non-Component Buffer Data	87

Chapter 6

PeopleCode and the Component Processor	89
Understanding the Component Processor	89
Events Outside the Component Processor Flow	89
PeopleCode Program Triggers	90
Understanding PeopleCode Program Triggers	90

Accessing PeopleCode Programs	91
Associating Execution Order of Events and PeopleCode	93
Component Processor Behavior	96
Component Processor Behavior from Page Start to Page Display	97
Component Behavior Following User Actions in the Component	98
Processing Sequences	100
Flow Charts	101
Default Processing	101
Search Processing in Update Modes	104
Search Processing in Add Modes	108
Component Build Processing in Update Modes	111
Row Select Processing	112
Component Build Processing in Add Modes	115
Field Modification	116
Row Insert Processing	119
Row Delete Processing	121
Buttons	123
Prompts	123
Pop-Up Menu Display	124
Selected Item Processing	124
Save Processing	125
PeopleSoft Pure Internet Architecture Processing Considerations	127
Deferred Processing Mode	127
PeopleCode Events	130
Activate Event	131
FieldChange Event	131
FieldDefault Event	132
FieldEdit Event	132
FieldFormula Event	133
ItemSelected Event	133
PostBuild Event	134
PreBuild Event	134
PrePopup Event	134
RowDelete Event	135
RowInit Event	135
RowInsert Event	136
RowSelect Event	138
SaveEdit Event	138
SavePostChange Event	139
SavePreChange Event	139
SearchInit Event	140
SearchSave Event	141
Workflow Event	142
PeopleCode Execution in Pages with Multiple Scroll Areas	142

Chapter 7

PeopleCode and PeopleSoft Pure Internet Architecture	145
Considerations Using PeopleCode in PeopleSoft Pure Internet Architecture	145
Using PeopleCode with PeopleSoft Pure Internet Architecture	146
Using Internet Scripts	146
Using the Field Object Style Property	146
Using the HTML Area	147
Using HTML Definitions and the GetHTMLText Function	148
Using HTML Definitions and the GetJavaScriptURL Method	149
Using PeopleCode to Populate Key Fields in Search Dialog Boxes	150
Calling DLL Functions on the Application Server	150
Sample Cross-Platform External Test Function	151
Updating the Installation and PSOPTIONS Tables	153

Chapter 8

Using Methods and Built-In Functions	155
Understanding Restrictions on Method and Function Use	155
Think-Time Functions	156
WinMessage and MessageBox Functions	157
Program Execution with Fields Not in the Data Buffer	159
Errors and Warnings	159
DoSave Function	160
Record Class Database Methods	160
SQL Class Methods and Functions	161
Component Interface Restricted Functions	161
SearchInit PeopleCode Function Restrictions	161
CallAppEngine Function	162
ReturnToServer Function	162
GetPage Function	162
GetGrid and GetAnalyticGrid Functions	163
Publish Method	163
SyncRequest Method	163
Implementing Modal Transfers	163
Understanding Modal Transfers	164
Implementing Modal Transfers	165
Implementing the Multi-Row Insert Feature	166
Using the ImageReference Field	167
Inserting Rows Using PeopleCode	168
Using OLE Functions	169

Understanding OLE Functions	169
Using the Object Data Type	169
Sharing a Single Object Instance	170
Using the Exec and WinExec Functions	170
Using the Select and SelectNew Methods	171
Understanding the Select and SelectNew Methods	171
Using the Select Method	172
Using Standalone Rowsets	174
Understanding Standalone Rowsets	174
Using the Fill Method	175
Using the CopyTo Method	175
Adding Child Rowsets	176
Using Standalone Rowsets to Write a File	176
Using Standalone Rowsets to Read a File	179
Using Errors and Warnings	181
Using Error and Warning Syntax	181
Using Errors and Warnings in Edit Events	181
Using Errors and Warnings in RowSelect Events	182
Using Errors and Warnings in RowDelete Events	183
Using Errors and Warnings in Other Events	183
Using the RemoteCall Feature	183
Understanding RemoteCall Components	184
Deciding Between RemoteCall and PeopleSoft Process Scheduler	186
Modifying PeopleSoft Process Scheduler Programs to Run with RemoteCall	186

Chapter 9

Using HTML Trees and the GenerateTree Function	189
Using the GenerateTree Function	189
Understanding HTML Trees	189
Building HTML Tree Pages	190
Using HTML Tree Rowset Records	191
Using HTML Tree Actions (Events)	194
Initializing HTML Trees	195
Processing Events Passed from a Tree to an Application	198
Adding Mouse-Over Ability to HTML Trees	203
Adding Visual Selection Node Indicators	204
Specifying Override Images	204

Chapter 10

Using File Attachments and PeopleCode	205
--	------------

Using File Attachments in Applications	205
Understanding File Attachment Architecture	205
Debugging File Attachment Problems	206
Configuring Multiple Application Servers to Support File Attachments	208
Viewing File Attachments	208
Using Chunking with Attachments	210
Using the Microsoft Windows NT 4 FTP Server	211
Using Non-DNS URLs with UNIX	212
Using Attachment Functions	212
File Name Considerations	216
Converting User Filenames	217
Naming URLs and File Attachments	217

Chapter 11

Accessing PeopleCode and Events	219
Understanding PeopleCode Programs and Events	219
Understanding Automatic Backup of PeopleCode	220
Accessing PeopleCode in Application Designer	220
Accessing Record Field PeopleCode	222
Understanding Record Field PeopleCode	222
Accessing Record Field PeopleCode from a Record Definition	223
Accessing Record Field PeopleCode from a Page Definition	224
Accessing Component Record Field PeopleCode	226
Understanding Component Record Field PeopleCode	226
Accessing Component Record Field PeopleCode	226
Accessing Component Record PeopleCode	227
Understanding Component Record PeopleCode	227
Accessing Component Record PeopleCode	228
Accessing Component PeopleCode	228
Understanding Component PeopleCode	229
Accessing Component PeopleCode	229
Accessing Page PeopleCode	229
Understanding Page PeopleCode	229
Accessing Page PeopleCode	230
Accessing Menu Item PeopleCode	230
Understanding Menu Item PeopleCode	230
Defining PeopleCode Pop-Up Menu Items	231
Accessing Menu Item PeopleCode	231
Copying PeopleCode with a Parent Definition	231
Upgrading PeopleCode Programs	232

Chapter 12

Using the PeopleCode Editor	233
Navigating Between PeopleCode Programs	233
Understanding the PeopleCode Editor Window	233
Navigating Between Programs Associated With a Definition and Its Children	235
Navigating Between Programs Associated With Events	235
Using the PeopleCode Editor	236
Understanding the PeopleCode Editor	237
Writing and Editing PeopleCode	237
Find and Replace Dialogs	238
Go To Dialog	239
Validate Syntax Utility	239
Formatting Code Automatically	240
Using Drag-and-Drop Editing	240
Accessing PeopleCode External Functions	241
Accessing PeopleCode Application Packages and Application Classes	241
Accessing Definitions and Associated PeopleCode	243
Accessing Help	244
Setting up Help	244
Changing Colors in the PeopleCode Editor	245
Selecting a Font for the PeopleCode Editor	245
Changing Word Wrap in the PeopleCode Editor	245
Using the PeopleCode Event Properties	247
Generating PeopleCode Using Drag-and-Drop	247
Generating Definition References	247
Generating PeopleCode for a Business Interlink	248
Generating PeopleCode for a Component Interface	248
Generating PeopleCode for a File Layout	249

Chapter 13

Using the SQL Editor	251
Understanding the SQL Editor Window	251
Accessing SQL Definition Properties	252
Accessing the SQL Editor	253
Creating SQL Definitions	253
Creating Dynamic View or SQL View Records	254
Accessing the SQL Editor from Application Engine Programs	255
Using the SQL Editor	256

Chapter 14

Creating Application Packages and Classes	259
Understanding Application Packages	259
Creating Application Packages	260
Understanding Package Names	260
Creating Application Package Definitions	261
Using the Application Package Editor	262
Editing Application Package Classes	263

Chapter 15

Debugging Your Application	265
Understanding the PeopleCode Debugger	265
Accessing the PeopleCode Debugger	265
Using PeopleCode Debugger Features	268
Visible Current Line of Execution	268
Visible Breakpoints	268
Hover Inspect	269
Single Debugger	269
Variables Panes	270
Call Stack Pane	273
Setting Values for Variables and Properties	275
General Debugging Tips	276
Using PeopleCode Debugger Options	278
Setting Up the Debugging Environment	281
Compiling All PeopleCode Programs at Once	281
Setting PeopleCode Debugger Log Options	282
Interpreting the PeopleCode Debugger Log File	285
Log File Contents	285
Other Items in the Log File	286
Using Application Logging	287
Setting the Application Log Fence in the Configuration File	287
Using the Log Fence with PeopleSoft Analytic Calculation Engine	288
Using the Find In Feature	288
Searching for SQL Injection	292
Using Cross-Reference Reports	292

Chapter 16

Improving Your PeopleCode	295
Reducing Trips to the Server	295
Counting Server Trips	296
Using Deferred Mode	296
Hiding and Disabling Fields	297
Using the Refresh Button	297
Updating Totals and Balances	297
Using Warning Messages	298
Using the Fastest Algorithm	298
Using Better Coding Techniques for Improved Performance	298
Running a SQL Trace	299
Optimizing SQL	299
Using the GetNextNumberWithGaps Function	299
Consolidating PeopleCode Programs	299
Moving PeopleCode to a Component or Page Definition	299
Sending Messages in the SavePostChange Event	300
Using Metadata and the RowsetCache Class	300
Setting MaxCacheMemory	300
Writing More Efficient Code	300
Writing More Efficient Code Examples	305
Searching PeopleCode for SQL Injection	310
Preventing SQL Injection	311

Appendix A

PeopleCode Editor Short Cut Keys	313
PeopleCode Editor Short Cut Keys	313

Index	317
--------------------	------------

PeopleCode Developer's Guide Preface

This preface provides an overview of the PeopleCode Developer's Guide and lists typographical conventions used in PeopleCode.

Overview of PeopleCode Developer's Guide

This PeopleBook covers the concepts of PeopleCode, the programming language used in the development of PeopleSoft applications. Its chapters describe techniques for adding PeopleCode to applications, tips for using PeopleCode, the interaction of PeopleCode and the Component Processor, and a number of other specialized topics, such as the use of the PeopleCode debugger and referencing data in the component buffer.

The accompanying books, the *Enterprise 8.49: PeopleCode API Reference* and the *Enterprise 8.49: PeopleCode Language Reference*, contain the reference material for the PeopleCode language. The chapters in these books describe the syntax and fundamental elements of the PeopleCode language.

The "About These PeopleBooks" preface contains general product line information, such as related documentation, common page elements, and typographical conventions. It also contains a glossary of useful terms that are used in PeopleBooks.

PeopleCode Typographical Conventions

Throughout this book, we use typographical conventions to distinguish between different elements of the PeopleCode language, such as bold to indicate function names, italics for arguments, and so on.

This table describes the typographical conventions used in PeopleCode:

<i>Font Type</i>	<i>Description</i>
monospace font	Indicates a PeopleCode program or other example.
Keyword	In PeopleCode syntax, keyword entries indicate function names, method names, language constructs, and PeopleCode reserved words that must be included literally in the function call.
<i>Variable</i>	In PeopleCode syntax, items in <i>variable</i> font are placeholders for arguments that your program must supply.
...	In PeopleCode syntax, ellipses indicate that the preceding item or series can be repeated any number of times.

Font Type	Description
<code>{ Option1 Option2 }</code>	In PeopleCode syntax, when multiple options are available, they are enclosed in curly braces and separated by a pipe.
<code>[]</code>	In PeopleCode syntax, optional items are enclosed in square brackets.
<code>&Parameter</code>	In PeopleCode syntax, an ampersand before a parameter indicates that the parameter is an already instantiated object.

PeopleBooks and the Online PeopleSoft Library

A companion PeopleBook called PeopleBooks and the Online PeopleSoft Library contains general information, including:

- Understanding the PeopleSoft online library and related documentation.
- How to send PeopleSoft documentation comments and suggestions to Oracle.
- How to access hosted PeopleBooks, downloadable HTML PeopleBooks, and downloadable PDF PeopleBooks as well as documentation updates.
- Understanding PeopleBook structure.
- Typographical conventions and visual cues used in PeopleBooks.
- ISO country codes and currency codes.
- PeopleBooks that are common across multiple applications.
- Common elements used in PeopleBooks.
- Navigating the PeopleBooks interface and searching the PeopleSoft online library.
- Displaying and printing screen shots and graphics in PeopleBooks.
- How to manage the PeopleSoft online library including full-text searching and configuring a reverse proxy server.
- Understanding documentation integration and how to integrate customized documentation into the library.
- Glossary of useful PeopleSoft terms that are used in PeopleBooks.

You can find this companion PeopleBook in your PeopleSoft online library.

Chapter 1

Getting Started with PeopleCode

PeopleCode is the proprietary language used by PeopleSoft applications. This chapter provides an overview of PeopleCode and discusses how to create PeopleCode programs.

This chapter provides information to consider before you begin to use PeopleCode. In addition to the considerations presented in this section, you should take advantage of all PeopleSoft sources of information, including the installation guides, release notes, and PeopleBooks.

PeopleCode Overview

This section provides an overview of the conceptual information available about the PeopleCode language. The reference material, that is, the actual descriptions of the functions, methods and properties can be found in the following:

- *Enterprise 8.49 PeopleBook: PeopleCode Language Reference*

This book contains information about PeopleCode built-in functions, meta-SQL, system variables, and meta-HTML.

- *Enterprise 8.49 PeopleBook: PeopleCode API Reference*

This book contains information about all the classes delivered with PeopleTools, as well as specifics about each class's methods and properties.

PeopleCode resembles other programming languages. However, many aspects are unique to the language and the PeopleTools environment. To learn more about the language, see *Understanding the PeopleCode Language*.

See [Chapter 2, "Understanding the PeopleCode Language," page 5](#).

PeopleCode is an object-oriented language. To learn about objects and how they're used in PeopleCode, see *Understanding Objects and Classes in PeopleCode*.

See [Chapter 3, "Understanding Objects and Classes in PeopleCode," page 39](#).

The component buffer is the area in memory that stores data for the currently active component. Which fields are loaded into the component buffer, as well as how to access them, is covered in *Referencing Data in the Component Buffer*.

See [Chapter 4, "Referencing Data in the Component Buffer," page 47](#).

The system uses a data buffer as well as the component buffer. The data buffer is used to store data added from sources other than the component, such as from a Application Engine program, an application message, and so on. For information about this buffer, see *Accessing the Data Buffer*.

See [Chapter 5, "Accessing the Data Buffer," page 67.](#)

All PeopleCode is associated with a definition and an event. The events run in a particular order from the Component Processor. To learn more about the Component Processor and the standard event set, see PeopleCode and the Component Processor.

See [Chapter 6, "PeopleCode and the Component Processor," page 89.](#)

You should take into account certain considerations when creating applications to be used in the PeopleSoft Pure Internet Architecture. These include how to make your code more efficient when running on the internet, as well as considerations when using specific definitions.

See [Chapter 7, "PeopleCode and PeopleSoft Pure Internet Architecture," page 145.](#)

There are restrictions on using some of the functions and methods in the PeopleCode language, as well as considerations for others, like using standalone rowsets and the OLE functions. These are covered in the Using Methods and Built-in Functions chapter.

See [Chapter 8, "Using Methods and Built-In Functions," page 155.](#)

PeopleCode has a tremendous amount of specialized functionality, such as:

- Using the GenerateTree function to create a tree in your application.
- Viewing, adding, and deleting files.

See [Chapter 9, "Using HTML Trees and the GenerateTree Function," Using the GenerateTree Function, page 189.](#)

See [Chapter 10, "Using File Attachments and PeopleCode," page 205.](#)

Creating PeopleCode Programs

All PeopleCode programs are associated with a definition as well as an event. To learn more about where you can place your PeopleCode, and have it executed as part of the Component Processor event flow, see Accessing PeopleCode and Events.

See [Chapter 11, "Accessing PeopleCode and Events," page 219.](#)

Use the PeopleCode editor to create your PeopleCode programs. All the functionality of the PeopleCode editor is described in Using the PeopleCode Editor.

See [Chapter 12, "Using the PeopleCode Editor," page 233.](#)

Every PeopleCode program is associated with a definition. The following definitions have additional functionality associated with the PeopleCode editor:

- SQL definitions
- Application Package definitions

See [Chapter 13, "Using the SQL Editor," page 251.](#)

See [Chapter 14, "Creating Application Packages and Classes," page 259.](#)

After you have created your program, you must run it. Often, that involves fixing any errors that you find. The PeopleCode debugger is an integrated part of PeopleSoft Application Designer, and it has many useful tools for determining where code errors are occurring. All the functionality is described in Debugging your Application.

See Chapter 15, "Debugging Your Application," page 265.

After your PeopleCode program is running, you may want to either improve its performance or the user experience. Techniques for doing this are discussed in Improving Your PeopleCode.

See Chapter 16, "Improving Your PeopleCode," page 295.

Chapter 2

Understanding the PeopleCode Language

This chapter discusses:

- PeopleCode language structure.
- Data types.
- Comments
- Statements.
- Functions.
- Expressions.
- Variables
- Operators.

PeopleCode Language Structure

This chapter assumes that you are familiar with a programming language, such as C, Visual Basic, or Java.

In its fundamentals, PeopleCode syntax resembles other programming languages. Some aspects of the PeopleCode language, however, are specifically related to the PeopleTools environment. Definition name references, for example, enable you to refer to PeopleTools definitions, such as record definitions or pages, without using hard-coded string literals. Other language features, such as PeopleCode data types and metastrings, reflect the close interaction of PeopleTools and SQL. Dot notation, classes, and methods in PeopleCode are similar to other object-oriented languages, like Java.

Data Types

Conventional data types include number, date, string. Use them for basic computing. Object data types instantiate objects from PeopleTools classes. The appropriate use of each data type is demonstrated where the documentation discusses PeopleCode that uses that data type.

Declare variables before you use them.

This section discusses:

- Conventional data types.

- Object data types.

See Also

Chapter 2, "Understanding the PeopleCode Language," Variables, page 26

Conventional Data Types

PeopleCode includes these conventional data types:

- Any

When variables and function return values are declared as Any, the data type is indeterminate, enabling PeopleTools to determine the appropriate type of value based on context. Undeclared local variables are Any by default.

- Boolean
- Date
- DateTime
- Float
- Integer

Note. The Float and Integer data types should be used instead of Number only when a performance analysis indicates that the increased speed is useful and an application analysis indicates that the different representations will not affect the results of the computations.

- Number
- Object
- String
- Time

Considerations for Float, Integer, and Number Types

The Integer type is a number represented as a 32-bit signed twos complement number, so it has a range of -2,147,483,648 to 2,147,483,647.

The Float type is a number represented using the machine floating binary point (double precision) representation. This floating binary point representation is not appropriate for exact calculations involving decimal fractions; in particular, calculations involving money. For example, because a tenth (1/10 or .1) cannot be exactly represented in floating binary point, a floating binary point sum of .10 + .10 is not be equal to .20.

The Number type has a size limit of 34 digits, not including the decimal point, with a maximum of 32 digits to the right of the decimal point. Since the Number type is a floating decimal point representation, it is the appropriate data type for calculations involving money.

Operations (other than division) are done using integer arithmetic if the operands are both integers and the destination is an integer, even if the variable is declared as the Number type. The destination is considered to be an integer if one of the following is True:

- The destination is an assignment to an integer variable or parameter.
- The destination is an array subscript.
- The destination is the right-hand operand of a comparison and the left-hand operand is an integer.
- The destination is a when-expression part of an evaluate statement, and the expression evaluated at the start of the evaluate statement is an integer.
- The destination is a for-loop initial, limit, or step expression and the control variable of the for-loop is an integer.

Division (the / operator) is never performed using integer arithmetic. It is always performed using the floating-decimal-point arithmetic, even if the result variable is declared as an Integer type.

Follow these recommendations for assigning types to numbers:

- Use Number for most application data values.
- Use Integer when you are counting items, such as rows in a rowset.
- Use Float only when you are tuning the code for performance (after it is already working).

In addition, you should only use the Float type when you are certain that the resulting loss of precision will not affect the application and that the increase in the speed of the computation makes a difference to the transaction. In general, few applications should use the Float type.

Object Data Types

For most classes in PeopleTools, you need a corresponding data type to instantiate objects from that class.

See [Chapter 3, "Understanding Objects and Classes in PeopleCode," page 39](#).

PeopleCode includes these data buffer access types:

- Field
- Record
- Row
- Rowset

PeopleCode includes these display data types:

- AnalyticGrid
- Chart
- Gantt
- Grid

- GridColumn
- OrgChart
- Page
- RatingBoxChart

PeopleCode includes these internet script data types:

- Cookie
- Request
- Response

PeopleCode includes these miscellaneous data types:

- ASection
- AnalyticInstance
- Array
- Crypt
- Exception
- File
- Interlink
- BIDocs

Note. BIDocs and Interlink objects used in PeopleCode programs run on the application server can only be declared as type Local. You can declare Interlinks as Global only in an Application Engine program.

See [Chapter 2, "Understanding the PeopleCode Language," User-Defined Variable Declaration and Scope, page 27.](#)

- JavaObject

Note. JavaObject objects can only be declared as type Local.

- Message
- MCFIMInfo
- OptEngine
- PostReport
- ProcessRequest
- RowsetCache
- SoapDoc

- SQL
- SyncServer
- TransformData

Note. TransformData objects can only be declared as type Local.

- XmlDoc
- XmlNode

Note. XmlNode objects can only be declared as type Local.

API Object Types

Use this data type for any ApiObject, such as a session object, a tree object, a component interface, a portal registry, and so on.

The following ApiObject data type objects can be declared as type Global:

- Session
- PSMessages collection
- PSMessages
- All tree classes (trees, tree structures, nodes, levels, and so on)
- All query classes

All other ApiObject data type objects (such as all the PortalRegistry classes) must be declared as Local.

Comments

Use comments to explain, preferably in language comprehensible to anyone reading your program, what your code does. Comments also enable you to differentiate between PeopleCode delivered with the product and PeopleCode that you add or change. This differentiation helps in your analysis for debugging and upgrades.

Note. Use comments to place a unique identifier marking any changes or enhancements that you have made to a PeopleSoft application. This marker makes it possible for you to search for all the changes you have made, which is particularly helpful when you are upgrading a database.

You insert comments into PeopleCode in these ways:

- You can surround comments with /* at the beginning and */ at the end.
- You can use a REM (remark) statement for commenting.

Put a semicolon at the end of a REM comment. If you do not, everything up to the end of the next statement is treated as part of the comment.

- You can surround commented text with `<*` at the start and `*>` at the end.

Use this type of comment to enclose one set of comments within another set. You generally use this when you are testing code and want to comment out a section that already contains comments.

Warning! In application classes, you will see the use of `/+ +/` style comments. *Do not use these in your PeopleCode.* These annotations are generated by the compiler. If you use them, they are removed by the system the next time you validate, compile, or save your PeopleCode. They are used to provide signature information on application class methods and properties, and they are regenerated each time the compiler compiles your application class PeopleCode. Instead, use the standard commenting mechanisms listed above.

Note. Commented text cannot exceed a maximum of 16383 characters.

The following code sample shows comment formatting:

```
<* this program is no longer valid commenting out
entire thing

REM This is an example of commenting PeopleCode;
/* ----- Logic for Compensation Change ----- */
/* Recalculate compensation change for next row.
Next row is based on prior value of EFFDT. */

calc_next_compchg(&OLDDT, EFFSEQ, 0);

/* Recalculate compensation change for current row and next row.
Next row is based on new value of EFFDT. */

calc_comp_change(EFFDT, EFFSEQ, COMP_FREQUENCY, COMP_RATE,
CHANGE_AMT, CHANGE_PCT);

calc_next_compchg(EFFDT, EFFSEQ, 0);

*>
```

Note. All text between the `<*` and `*>` comment markers is scanned. If you have mismatched quotation marks, invalid assignments, and so on, you may receive an error when using this type of comment.

Statements

A statement can be a declaration, an assignment, a program construct (such as a Break statement or a conditional loop), or a subroutine call.

This section discusses:

- Separators.
- Assignment statements.
- Language constructs.
- Branching statements.
- Conditional loops.

Separators

PeopleCode statements are generally terminated with a semicolon. The PeopleCode language accepts semicolons even if they are not required, such as after the last statement completed within an If statement. This functionality enables you to consistently add semicolons after each statement.

Extra spaces are ignored. They are removed by the PeopleCode Editor when you save the code.

Assignment Statements

The assignment statement is the most basic type of statement in PeopleCode. It consists of an equal sign with a variable name on the left and an expression on the right:

```
variableName = expression;
```

The expression on the right is evaluated, and the result is placed in the variable named on the left. Depending on the data types involved, the assignment is passed either by value or by reference.

Assignment by Value

In most types of assignments, the result of the right-hand expression is assigned to the variable as a newly created value, in the variable's own allocated memory area. Subsequent changes to the value of that variable have no effect on any other data.

Assignment by Reference

When both sides of an assignment statement are object variables, the result of the assignment is not to create a copy of the object in a unique memory location and assign it to the variable. Instead, the variable points to the object's memory location. Additional variables can point to the same object location.

For example, both &AN and &AN2 are arrays of type Number. Assigning &AN2 to &AN does *not* assign a copy of &AN2 to &AN. Both array objects point to the same information in memory.

```
Local array of number &AN, &AN2;
Local number &NUM;

&AN = CreateArray(100, 200, 300);
&AN2 = &AN;
&NUM = &AN[1];
```

In the code example, &AN2 and &AN point to the same object: an array of three numbers. If you were to change the value of &AN[2] to 500 and then reference the value of &AN2[2], you would get 500, not 300. On the other hand, assigning &NUM to the first element in &AN (100) is *not* an object assignment. It is an assignment by value. If you changed &AN[1] to 500, then &NUM remains 200.

Note. In PeopleCode, the equal sign can function as either an assignment operator or a comparison operator, depending on context.

Language Constructs

PeopleCode language constructs include:

- Branching structures: If and Evaluate.
- Loops and conditional loops: For, Repeat, and While.
- Break, Continue, and Exit statements loop control and terminating programs.
- The Return statement for returning from functions.
- Variable and function declaration statements: Global, Local, and Component for variables, and Declare Function for functions.
- The Function statement for defining functions.
- Class definition statements.
- Try, Catch, and Throw statements for error handling.

Functions as Subroutines

PeopleCode, like C, does not have subroutines as we generally refer to them. PeopleCode subroutines are the subset of PeopleCode functions only that are defined to return no value or to return a value optionally. Calling a subroutine is the same as calling a function with no return value:

```
function_name( [param_list] );
```

See Also

Chapter 2, "Understanding the PeopleCode Language," Branching Statements, page 12

Chapter 2, "Understanding the PeopleCode Language," Functions, page 15

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Function

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Declare Function

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," CreateException

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Try

Branching Statements

Branching statements control program flow based on evaluation of conditional expressions.

If, Then, and Else statements

The syntax of If, Then, and Else statements is:

```

If condition Then
    [statement_list_1]
[Else
    [statement_list_2]]
End-if;

```

This statement evaluates the Boolean expression *condition*. If *condition* is True, then the If statement executes the statements in *statement_list_1*. If *condition* is False, then the program executes the statements in the Else clause; if there is no Else clause, the program continues to the next statement.

Evaluate Statement

Use the Evaluate statement to check multiple conditions. Its syntax is:

```

Evaluate left_term
    When [relop_1] right_term_1
        [statement_list]
    .
    .
    .

    When [relop_n] right_term_n
        [statement_list]
    [When-other
        [statement_list]]
End-evaluate;

```

The Evaluate statement takes an expression, *left_term*, and compares it to compatible expressions (*right_term*) using the relational operators (*relop*) in a sequence of When clauses. If *relop* is omitted, then the equal sign is assumed. If the result of the comparison is True, the program executes the statements in the When clause, and then moves on to evaluate the comparison in the following When clause. The program executes the statements in all of the When clauses for which the comparison evaluates to True. If none of the When comparisons evaluates to True, the program executes the statement in the When-other clause, if one is provided. For example, the following Evaluate statement executes only the first When clause.

&USE_FREQUENCY in the following example can only have one of three string values:

```

evaluate &USE_FREQUENCY
when = "never"
    PROD_USE_FREQ = 0;
when = "sometimes"
    PROD_USE_FREQ = 1;
when = "frequently"
    PROD_USE_FREQ = 2;
when-other
    Error "Unexpected value assigned to &USE_FREQUENCY."
end-evaluate;

```

To end the Evaluate statement after the execution of a When clause, you can add a Break statement at the end of the clause, as in the following example:

```

evaluate &USE_FREQUENCY
when = "never"
    PROD_USE_FREQ = 0;
    Break;
when = "sometimes"
    PROD_USE_FREQ = 1;
    Break;
when = "frequently"
    PROD_USE_FREQ = 2;
    Break;
when-other
    Error "Unexpected value assigned to &USE_FREQUENCY."
end-evaluate;

```

In rare cases, you may want to make it possible for more than one When clause to execute, as shown in the following example:

```

evaluate &PURCHASE_AMT
when >= 100000
    BASE_DISCOUNT = "Y";
when >= 250000
    SPECIAL_SERVICES = "Y";
when >= 1000000
    MUST_GROVEL = "Y";
end-evaluate;

```

For Statement

The For statement repeats a sequence of statements a specified number of times. Its syntax is:

```

For count = expression1 to expression2
    [Step i];
    statement_list
End-for;

```

The For statement initializes the value of *count* to *expression1*, and then increments *count* by *i* each time after it executes the statements in *statement_list*. The program continues in this loop until *count* is equal to *expression2*. If the Step clause is omitted, then *i* equals one. To count backwards from a higher value to a lower value, use a negative value for *i*. You can exit a For loop using a Break statement.

The following example demonstrates the For statement:

```

&MAX = 10;
for &COUNT = 1 to &MAX;
    WinMessage("Executing statement list, count = " | &COUNT);
end-for;

```

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," If

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Evaluate

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," For

Conditional Loops

Conditional loops, Repeat and While, repeat a sequence of statements, evaluating a conditional expression each time through the loop. The loop terminates when the condition evaluates to True. You can exit from a conditional loop using a Break statement. If the Break statement is in a loop embedded in another loop, the break applies only to the inside loop.

Repeat Statement

The syntax of the Repeat statement is:

```
Repeat
    statement_list
Until logical_expression;
```

The Repeat statement executes the statements in *statement_list* once, and then evaluates *logical_expression*. If *logical_expression* is False, the sequence of statements is repeated until *logical_expression* is True.

While Statement

The syntax of the While statement is:

```
While logical_expression
    statement_list
End-while;
```

The While statement evaluates *logical_expression* before executing the statements in *statement_list*. It continues to repeat the sequence of statements until *logical_expression* evaluates to False.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Repeat

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," While

Functions

This section discusses:

- Supported functions.
- Function definitions.
- Function declarations.
- Function calls.
- Function return values.

- Function naming conflicts.

See Also

Chapter 3, "Understanding Objects and Classes in PeopleCode," page 39

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions"

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Function

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Declare Function

Supported Functions

PeopleCode supports the following types of functions:

- Built-in: The standard set of PeopleCode functions. These can be called without being declared.
- Internal: Functions that are defined (using the Function statement) within the PeopleCode program in which they are called.
- External PeopleCode: PeopleCode functions defined outside the calling program. These are generally contained in record definitions that serve as function libraries.
- External non-PeopleCode: Functions stored in external (C-callable) libraries.

Note. PeopleSoft Analytic Calculation Engine provides its own set of built-in functions.

See *Enterprise PeopleTools 8.50 PeopleBook: Analytic Calculation Engine*, "Using Built-in Functions in Analytic Models."

In addition, PeopleCode supports methods. The main differences between a built-in function and a method are:

- A built-in function, in your code, is on a line by itself, and it does not (generally) have any dependencies. You do not have to instantiate an object before you can use the function.
- A method can only be executed by an object (using dot notation). You must instantiate the object first.

Function Definitions

PeopleCode functions can be defined in any PeopleCode program. Function definitions must be placed at the top of the program, along with any variable and external function declarations.

By convention, PeopleCode programs are stored in records whose names begin in FUNCLIB_, and they are always attached to the FieldFormula event.

Note. Application classes can provide an alternative, and sometimes cleaner, mechanism for separating functionality than the functions stored in FUNCLIBs.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Function

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Application Classes"

Function Declarations

If you call an external function from a PeopleCode program, you must declare the function at the top of the program. The syntax of the function declaration varies, depending on whether the external function is written in PeopleCode or compiled in a dynamic link library.

The following is an example of a function declaration of a function that is in another FUNCLIB record definition:

```
Declare Function UpdatePSLOCK PeopleCode FUNCLIB_NODES.MSGNODENAME FieldFormula;
```

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Declare Function

Function Calls

Functions are called with this syntax:

```
function_name( [param_list] )
```

The parameter list (*param_list*) is a list of expressions, separated by commas, that the function expects you to supply. Items in the parameter list can be optional or required.

You can check the values of parameters that get passed to functions at runtime in the Parameter window of the PeopleCode debugger.

If the return value is required, then the function must be called as an expression, for example:

```
&RESULT = Product(&RAISE_PERCENT, .01, EMPL_SALARY);
```

If the function has an optional return value, it can be called as a subroutine. If the function has no return value, it *must* be called as a subroutine:

```
WinMessage(64, "I can't do that, " | &OPER_NICKNAME | ".");
```

Parameters are always passed to internal and external PeopleCode functions by reference. If the function is supposed to change the data the caller passes, you must also pass in a variable.

Built-in function parameters can be passed by reference or by value, depending on the function. External C function parameters can be passed by value or by reference, depending on the declaration and type.

See Also

[Chapter 15, "Debugging Your Application," page 265](#)

[Chapter 2, "Understanding the PeopleCode Language," Variables and Functions, page 31](#)

Function Return Values

Functions can return values of any supported data type; some functions do not return any value.

Optional return values occur only in built-in functions. You cannot define a function that optionally returns a value. Optional return values are typical in functions that return a Boolean value indicating whether execution was successful. For example, the following call to `DeleteRow` ignores the Boolean return value and deletes a row:

```
DeleteRow(RECORD.BUS_EXPENSE_PER, &L1_ROW, RECORD.BUS_EXPENSE_DTL, &L2_ROW);
```

The following example checks the return value and returns a message saying whether it succeeded:

```
if DeleteRow(RECORD.BUS_EXPENSE_PER, &L1_ROW, RECORD.BUS_EXPENSE_DTL, &L2_ROW) then
    WinMessage("Row deleted.");
else
    WinMessage("Sorry -- couldn't delete that row.");
end-if;
```

Function Naming Conflicts

If you define a function with the same name as a built-in function, the function that you defined takes precedence over the built-in function.

Anytime you compile the PeopleCode in the PeopleCode Editor, a warning message appears in the Validate tab, indicating that a user-defined function has the same name as an existing built-in function.

In addition, if you select **Compile All PeopleCode**, an error message is generated in the log file for every user-defined function that has the same name as a built-in function.

The following is an example error message: User-defined function `IsNumber` is overriding the built-in function of the same name. (2,98)

If you notice that you named a function the same as a built-in function, and that the built-in function does what you're trying to achieve, replace your function with a reference to the built-in function. The built-in function is probably more efficient. In addition, using the built-in function reduces confusion for people who maintain your code, because if they miss the warning message in the Validate tab, they might assume the built-in function is being called when it is not.

Expressions

This section discusses:

- Expression fundamentals.
- Constants.
- Functions as expressions.
- System variables.
- Metastrings.
- Record field references.
- Definition name references.
- Reserved word summary table.

See Also

Chapter 2, "Understanding the PeopleCode Language," Variables, page 26

Expression Fundamentals

Expressions evaluate to values of PeopleCode data types. A simple PeopleCode expression can consist of a constant, a temporary variable, a system variable, a record field reference, or a function call. Simple expressions can be modified by unary operators (such as a negative sign or logical NOT), or combined into compound expressions using binary operators (such a plus sign or logical AND).

Definition name references evaluate to strings equal to the name of a PeopleTools definition, such as a record or page. They enable you to refer to definitions without using string literals, which are difficult to maintain.

Metastrings (also called meta-SQL) are special expressions used within SQL string literals. At runtime, the metastrings expand into the appropriate SQL for the current database platform.

Constants

PeopleCode supports numeric, string, and Boolean constants, as well as user-defined constants. It also supports the constant Null, which indicates an object reference that does not refer to a valid object.

Note. You can express Date, DateTime, and Time values by converting from String and Number constants using the Date, Date3, DateTime6, DateTimeValue, DateValue, Time3, TimePart, and the TimeValue functions. You can also format a DateTime value as text using FormatDateTime.

Numeric Constants

Numeric constants can be any decimal number. Some examples are:

- 7
- 0.8725
- -172.0036

String Constants

String constants can be delimited by using either single (') or double (") quotation marks. If a quotation mark occurs as part of a string, the string can be surrounded by the other delimiter type. As an alternative, you can include the delimiter twice. Some examples are:

- "This is a string constant."
- 'So is this.'
- 'She said, "This is a string constant."'
- "She said, ""This is a string constant."""

Use the following code to include a literal quotation mark as part of your string:

```
&cDblQuote = '''; /* singlequote doublequote singlequote */
```

The following also produces a string with two double quotation marks in it:

```
&cDblQuote = """"; /* dquote dquote dquote dquote */
```

You can also directly embed the doubled double quotation mark in strings, such as:

```
&sImage = Char(10) | '<IMG SRC="%IMAGE(' | &pImageName | ')"' ;
```

Strings must be contained on a single line. If you need to create a multi-line string, you must use concatenation to connect the lines to be a single sting.

Boolean Constants

Boolean constants represent a truth value. The two possible values are True and False.

Null Constant

Null constants represent an object reference value that does not refer to a valid object. This means that calling a method on the object or trying to get or set a property of it fails. The Null constant is just the keyword Null.

User-Defined Constants

You can define constants at the start of a PeopleCode program. Then you can use the declared constant anywhere that the corresponding value would be allowed. Constants can be defined as numbers, strings, or Boolean values.

User-defined constants can only be declared as Local.

The following is an example of user-defined constant declarations:

```
Constant &Start_New_Instance = True;
Constant &Display_Mode = 0;
Constant &AddMode = "A":
Local Field &Start_Date;
. . .
MyFunction(&Start_New_Instance, &Display_Mode, &Add_Mode);
```

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions"

Functions as Expressions

You can use any function that returns a value as an expression. The function can be used on the right side of an assignment statement, passed as a parameter to another function, or combined with other expressions to form a compound expression.

See Also

[Chapter 2, "Understanding the PeopleCode Language," Functions, page 15](#)

System Variables

System variables are preceded by a percent (%) symbol whenever they appear in a program. Use these variables to get the current date and time, or to get information about the user, the current language, the current record, page, or component, and more.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "System Variables"

Metastrings

Metastrings are special SQL expressions. The metastrings, also called meta-SQL, are preceded with a percent (%) symbol, and can be included directly in string literals. They expand at runtime into an appropriate substring for the current database platform. Metastrings are used in or with:

- `SQLExec`.
- Scroll buffer functions (`ScrollSelect` and its relatives).
- PeopleSoft Application Designer to construct dynamic views.
- Some rowset object methods (`Select`, `SelectNew`, `Fill`, and so on).

- SQL objects.
- Application Engine.
- Some record class methods (Insert, Update, and so on).
- COBOL.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," SQLExec

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," ScrollSelect

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "Meta-SQL"

Record Field References

Use record field references to retrieve the value stored in a record field or to assign a value to a record field.

Record Field Reference Syntax

References to record fields have the following form:

```
[recordname.]fieldname
```

You must supply the *recordname* only if the record field and your PeopleCode program are in different record definitions.

For example, suppose that in a database for veterinarians you have two records, PET_OWNER and PET. A program in the record definition PET_OWNER must refer to the PET_BREED record field in the PET record definition as PET.PET_BREED.

However, a program in the PET record definition can refer to this same record field more directly as PET_BREED.

If the program is in the PET_BREED record field itself, it can refer to this record field using the caret (^) symbol.

The PeopleCode Editor replaces the caret symbol with the actual record field name.

You can also use object dot notation to refer to record fields, for example:

```
&FIELD = GetRecord(RECORD.PET_OWNER).GetField(FIELD.PET_BREED) ;
```

See [Chapter 4, "Referencing Data in the Component Buffer," page 47](#).

Legal Record Field Names

A record field name consists of two parts, the record name and the field name, separated by a period.

The field names used in PeopleCode are consistent with the field names allowed in the field definition. Case is ignored, although the PeopleCode Editor for the sake of convention, automatically formats field names in uppercase. A field name can be 1 to 18 characters, consisting of alphanumeric characters determined by your current language setting in Microsoft Windows, and characters #, @, \$, and _.

A record name can be 1 to 15 characters, consisting of alphanumeric letters determined by your current language setting in Microsoft Windows, and characters #, @, \$, and _.

Definition Name References

Definition name references are special expressions that reference the name of a PeopleTools definition, such as a record, page, component, business interlink, and so on. Syntactically, a definition name reference consists of a reserved word indicating the type of definition, followed by a period, then the name of the PeopleTools definition. For example, the definition name reference `RECORD.BUS_EXPENSE_PER` refers to the definition name `BUS_EXPENSE_PER`.

Generally, definition name references are passed as parameters to functions. If you attempt to pass a string literal instead of a definition name reference to such a function, you receive a syntax error.

You also use definition name references outside function parameter lists, for example, in comparisons:

```
If (%Page = PAGE.SOMEPAGE) Then
    /* do stuff specific to SOMEPAGE */
End-If;
```

In these cases, the definition name reference evaluates to a string literal. Using the definition name reference instead of a string literal enables PeopleTools to maintain the code if the definition name changes.

If you use the definition name reference, and the name of the definition changes, the change automatically ripples through the code, so you do not have to change it or maintain it.

In the PeopleCode Editor, if you place your cursor over any definition name reference and right-click, you can select View Definition to open the definition.

In addition, for most definitions, if you specify a definition that was not created in PeopleSoft Application Designer, you receive an error message when you try to save your program.

Legal and Illegal Definition Names

Legal definition names, as far as definition name references are concerned, consist of alphanumeric letters determined by your current language setting in Microsoft Windows, and the characters #, @, \$, and _.

In some cases, however, the definition supports the use of other characters. You can, for example, have a menu item named A&M stored in the menu definition even though & is an illegal character in the definition name reference. The illegal character results in an error when you validate the syntax or attempt to save the PeopleCode.

You can avoid this problem in two ways:

- Rename the definition so that it uses only legal characters.
- Enclose the name of the definition in quotation marks in the reference, for example:
`ITEMNAME."A&M"`

The second solution is a commonly used workaround in cases where the definition name contains illegal characters. If you use this notation, the definition name reference is not treated as a string literal: PeopleTools maintains the reference the same way as it does other definition name references.

Note. If your definition name begins with a number, you must enclose the name in quotation marks when you use it in a definition name reference. For example, `CompIntfc."1_DISCIPLIN_ACTN"`.

Reserved Word Summary Table

The following table summarizes the reserved words used in definition name references:

<i>Reserved Word</i>	<i>Common Usage</i>
BARNAME	Used with transfers and modal transfers.
BUSACTIVITY	Used with TriggerBusinessEvent.
BUSEVENT	Used with TriggerBusinessEvent.
BUSPROCESS	Used with TriggerBusinessEvent.
COMPINTFC	Used with Component Interface Classes.
COMPONENT	Used with transfers and modal transfers, as well as for generating URLs.
FIELD	Used with methods and functions to designate a field.
FILELAYOUT	Used with the SetFileLayout File class method.
HTML	Used with the GetHTMLText function.
IMAGE	Used in with functions and methods to designate an image.
INTERLINK	Used with the GetInterlink function.
ITEMNAME	Used with transfers and modal transfers.
MENUNAME	Used with transfers and modal transfers.

Reserved Word	Common Usage
MESSAGE	Used with Messaging functions and methods.
MOBILEPAGE	Used to identify a mobile page (used with transfers.)
NODE	Used with transfers and modal transfers, as well as generating URLs.
PAGE	Used with transfers and modal transfers to pass the page item name (instead of the page name), and with controls and other functions to pass the page name.
PORTAL	Used with transfers and modal transfers, as well as generating URLs.
RECORD	Used in functions and methods to designate a record.
SCROLL	The name of the scroll area in the page. This name is always equal to the primary record of the scroll.
SQL	Used with SQL definitions.
STYLESHEET	Used with style sheets.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," TriggerBusinessEvent

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," GetHTMLText

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," GetInterlink

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Component Interface Classes"

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Message Classes"

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "File Class," SetFileLayout

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "SQL Class"

Variables

This section discusses.

- Supported variable types.
- User-defined variables.
- User-defined variable declaration and scope.
- Variable declaration.
- User-defined variable initialization.
- Restrictions on variable use.
- Scope of local variables.
- Duration of local variables.
- Variables and functions.
- Recursive functions.
- State of shared objects using PeopleSoft Pure Internet Architecture.

See Also

Chapter 2, "Understanding the PeopleCode Language," System Variables, page 21

Supported Variable Types

PeopleCode supports these types of variables:

- | | |
|-------------------------------|---|
| User-defined variables | These variable names are preceded by an & character wherever they appear in a program. Variable names can be 1 to 1000 characters, consisting of letters A through Z and a through z, digits 0 through 9, and characters #, @, \$, and _. |
| System variables | System variables provide access to system information. System variables have a prefix of the % character rather than the & character. Use these variables wherever you can use a constant, passing them as parameters to functions or assigning their values to fields or to temporary variables. |

User-Defined Variables

A user-defined variable can hold the contents of a record field for program code clarity. For example, you may give a variable a more descriptive name than a record field, based on the context of the program. If the record field is from another record, you may assign it to a temporary variable rather than always using the record field reference. This makes it easier to enter the program, and can also make the program easier to read.

Also, if you find yourself calling the same function repeatedly to get a value, you may be able to avoid some processing by calling the function once and placing the result in a variable.

User-Defined Variable Declaration and Scope

The difference between the variable declarations concerns their life spans:

- Global

The variable is valid for the entire session.

- Component

The variable is valid while any page in the component in which the variable is defined stays active.

- Local

The variable is valid for the duration of the PeopleCode program or function in which the variable is defined.

You can declare variables using the Global, Local, or Component statements, or you can use local variables without declaring them. Here are some examples:

```
Local Number &AGE;
Global String &OPER_NICKNAME;
Component Rowset &MY_ROWSET;
Local Any &SOME_FIELD;
Local ApiObject &MYTREE;
Local Boolean &Compare = True;
```

Variable declarations are usually placed above the main body of a PeopleCode program (along with function declarations and definitions). The exception is the Local declaration, which you can use within a function or the main section of a program. You can declare variables as any of the PeopleCode data types. If a variable is declared as an Any data type, or if a variable is not declared, PeopleTools uses an appropriate data type based on context.

Note. Declare a variable as an explicit data type unless the variable will hold a value of an unknown data type.

Global variables can be accessed from different components and applications, including an Application Engine program. A global variable must be declared, however, in each PeopleCode program where it's used. Use global variables rarely, because they are difficult to maintain.

Global variables are not available to a portal or applications on separate databases.

Component variables remain defined and keep their values while any page in the component in which they are defined remains active. Similar to a global variable, a component variable must be declared in each PeopleCode program where it is used.

Component variables act the same as global variables when an Application Engine program is called from a page (using CallAppEngine).


Component variables remain defined after a TransferPage, DoModal, or DoModalComponent function. However, variables declared as Component do not remain defined after using the Transfer function, whether you are transferring within the same component or not.

Local variables declared at the top of a PeopleCode program (or within the main, that is, non-function, part of a program) remain in scope for the life of that PeopleCode program. Local variables declared within a function are valid to the end of the function and not beyond.

You can check the values of Local, Global, and Component variables at runtime in the different variable windows of the PeopleCode debugger. Local variables declared within a function appear in the Function Parameters window.

Variable Declaration

Declare variables before you use them. If you do not declare a variable, it is automatically declared with the scope Local and the data type Any. You receive a warning message in the Validation tab of the PeopleSoft Application Designer output window for every variable that is not declared when you save the PeopleCode program, as shown in the following example:



Validation tab with auto-declared variables

If you declared all the variables, you can use these values to ensure you do not have misspellings. For example, if you declared a variable as &END_DATE and then accidentally spell it as &EDN_DATE, the "new variable" appears on the Validate tab when you save the program.

Another reason to declare variables is for the design-time checking. If you declare a variable of one data type and then assign to it a value of a different type, the PeopleCode Editor catches that assignment as a design-time error when you try to save the program. With an undeclared variable, the assignment error does not appear until runtime.

The following example produces a design-time error when you try to save the program:

```
Local Field &DATE;

&DATE = GetRecord(RECORD.DERIVED_HR);
```

In addition, if you declare variables, the Find Object Reference feature finds embedded definitions. For example, suppose you wanted to find all occurrences of the field DEPT_ID. If you have not declared &MyRecord as a record, Find Object References does not find the following reference of the field DEPT_ID:

```
&MyRecord.DEPT_ID.Visible = False;
```

User-Defined Variable Initialization

To declare and initialize variables in one step, use the following format:

```
Local String &MyString = "New";
```

```
Local Date &MyDate = %Date;
```

This method is available only for variables with the scope of Local.

Though you can declare more than one variable on a single line, you can only initialize one variable on a line. The following code creates a syntax error when you try to save the program:

```
Local Number &N1, &N2 = 5;
```

You cannot declare a variable, then initialize it in a second declaration statement. The following produces a duplicate declaration error when you try to save the program:

```
Global Number &N1;
...
Local String &N1 = "Str"; /* Duplicate definition. */
```

If you do not initialize variables, either when you declare them or before you use them, strings are initialized as Null strings, dates and times as Null, and numbers as zero.

Restrictions on Variable Use

The following data types can only be declared as Local:

- JavaObject
- Interlink

Note. Interlink objects can be declared as type Global in an Application Engine program.

- TransformData
- XmlNode

The following ApiObject data type objects can be declared as Global:

- Session
- PSMessages collection
- PSMessage
- All tree classes (trees, tree structures, nodes, levels, and so on)
- Query classes

All other ApiObject data type objects (such as all the PortalRegistry classes) must be declared as Local.

Scope of Local Variables

The two types of local variables are: program-local and function-local.

- A program-local variable is declared as local in the main part of the program and is local to that program.
- A function-local variable is declared as local inside a function and is local only to that function.

See [Chapter 2, "Understanding the PeopleCode Language," Recursive Functions, page 32.](#)

A program-local variable can be affected by statements anywhere in the program. For example, suppose `RECORD_A.FIELD_A.FieldFormula` has two functions, `FUNC_1` and `FUNC_2`, and both modify a local variable named `&TEMP`. They could affect each other, as they both use the same variable name in the same PeopleCode program.

If, however, `FUNC_3` is defined in `RECORD_B.FIELD_B.FieldFormula` and makes reference to `&TEMP`, it is *not* the same `&TEMP` as in `RECORD_A.FIELD_A.FieldFormula`. This difference becomes important when `FUNC_1` calls `FUNC_3`. Technically, both functions exist at the same time, one inside the other, but `&TEMP` is a different variable for each of them. However, if `FUNC_1` calls `FUNC_2`, then `&TEMP` is the same variable for both.

Duration of Local Variables

A local variable is valid for the duration of the PeopleCode program or function in which it is defined. A PeopleCode program is defined as what the PeopleCode Editor in Application Designer presents in a single window: a chunk of PeopleCode text associated with a single item (a record field event, a component record event, and so on.)

When the system evaluates a PeopleCode program and calls a function in the same PeopleCode program, a new program evaluation is not started.

However, when a function from a different PeopleCode program is called (that is, some PeopleCode text associated with a different item), the current PeopleCode program is suspended, and the Component Processor starts evaluating the new program. This means that any local variables in the calling program (called A) are no longer available. Those in the called program (called B) are available.

Even if the local variables in the A program have the same name as those in the B program, they are different variables and are stored separately.

If the called program (B) in turn calls a function in program A, a new set of program A's variables are allocated, and the called function in A uses these new variables. Thus, this second use of program A gets another lifetime, until execution returns to program B.

The following is an example of pseudocode to show how this might work. (This is non-compiled, non-working code. To use this example, you'd have to enter a similar program without the external declaration of the function in the other, not yet compiled, one.)

```

Program A (Rec.Field.FieldChange):
local number &temp;
declare function B1 PeopleCode Rec.Field FieldFormula;
/* Uncomment this declaration and comment above to compile this the first time.
   function B1
   end-function;
*/

function A1
WinMessage("A1: &temp is " | &temp);
&temp = &temp + 1;
A2();
B1();
A2();
end-function;

function A2
WinMessage("A2: &temp is " | &temp);
&temp = &temp + 1;
end-function;

A1();

Program B (Rec.Field.FieldFormula):
local number &temp;
declare function A2 PeopleCode Rec.Field FieldChange;

function B1
WinMessage("B1: &temp is " | &temp);
&temp = &temp + 1;
A2();
end-function;

```

When this is compiled and run, it produces the following output:

```

A1: &temp is 0
A2: &temp is 1
B1: &temp is 0
A2: &temp is 0
A2: &temp is 2

```

Variables and Functions

PeopleCode variables are always passed to functions by reference. This means, among other things, that a function can change the value of a variable passed to it so that the variable has the new value on return to the calling routine.

For example, the Amortize built-in function expects you to pass it variables into which it places the amount of a loan payment applied towards interest (&PYMNT_INTRST), the amount of the payment applied towards principal (&PYMNT_PRIN), and the remaining balance (&BAL). It calculates these values based on information that the calling routine supplies in other parameters:

```

&INTRST_RT=12;
&PRSNT_BAL=100;
&PYMNT_AMNT=50;
&PYMNT_NBR=1;
Amortize(&INTRST_RT, &PRSNT_BAL, &PYMNT_AMNT, &PYMNT_NBR,
&PYMNT_INTRST, &PYMNT_PRIN, &BAL);
&RESULT = "Int=" | String(&PYMNT_INTRST) | " Prin=" |
String(&PYMNT_PRIN) | " Bal=" | String(&BAL);

```

Recursive Functions

PeopleCode supports True recursive functions. A function can call itself, and each possibly recursive call of the function has its own independent copy of the parameters and function-local variables.

When writing recursive functions, be careful about passing variables as parameters, because PeopleCode implements such calls by reference. This means that if you call a function such as:

```
Function Func(&n as Number)
&n = 3;
End-Function;
local &x = 5;
Func(&x);
```

After the call to Func(&x), &x has the value 3, not 5. If the call was Func(Value(&x)), after the call &x is still 5.

State of Shared Objects Using PeopleSoft Pure Internet Architecture

Consider the following scenario:

- A local and a global variable refer to the same object.
- That object is used in a modal component.
- Instead of completing the modal component, the user clicks the browser Back button.

In general, the global state of the object is restored. If the object has not been destroyed from the global state, the global state of the object is used for local references; otherwise, the local state is used for local references.

Here is an example:

```
Global array of number &Global_Array;
Local array of number &Local_Array;

&Global_Array = CreateArray(1, 2, 3);
&Local_Array = &Global_Array
DoModal(Page.PAGENAME, "", -1, -1, 1, Record.SHAREDREC, 1);
/* return to here */
&Local_Array[1] = -1;
&Global_Array[2] = -2;
WinMessage(&Local_Array is " | &Local_Array.Join());
WinMessage(&Global_Array is " | &Global_Array.Join());
```

The following program, program 2, is located on the modal page the user is transferred to:

```
Global array of number &Global_Array;
&Global_Array[3] = -3;
```

The following program, program 3, is also located on the modal page:

```
Global array of number &Global_Array;
&Global_Array = CreateArray(1, 2, -3);
```

If program 2 is run, the output is the following:

&Local_Array is -1, -2, -3

&Global_Array is -1, -2, -3

However, if program 3 is run, thereby destroying the original global state, the output is the following:

&Local_Array is -1, 2, 3

&Global_Array is 1, -2, -3

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "System Variables"

[Chapter 15, "Debugging Your Application," page 265](#)

Operators

PeopleCode expressions can be modified and combined using math, string, comparison, and Boolean operators.

This section discusses:

- Math operators.
- Operations on dates and times.
- String concatenation.
- @ operator.
- Comparison operators.
- Boolean operators.

Math Operators

PeopleCode uses standard mathematical operators:

- +
Add
- -
Subtract (or unary negative sign)
- *
Multiply
- /
Divide

- **

Exponential

Exponentiation occurs before multiplication and division; multiplication and division occur before addition and subtraction. Otherwise, math expressions are evaluated from left to right. You can use parentheses to force the order of operator precedence.

The minus sign can also, of course, be used as a negation operator, as in the following expressions:

```
-10
- &NUM
- Product (&PERCENT_CUT, .01, SALARY)
```

Operations on Dates and Times

You can add or subtract two date values or two time values, which provides a Number result. In the case of dates, the number represents the difference between the two dates in days. In the case of time, the number represents the difference in seconds. You can also add and subtract numbers to or from a time or date, which results in another date or time. Again, in the case of days, the number represents days, and in the case of time, the number represents seconds.

The following table summarizes these operations:

Operation	Result Type	Result Represents
Time + number of seconds	Time	Resulting time
Date + number of days	Date	Resulting date
Date - date	Number	Difference in days
Time - time	Number	Difference in seconds
Date + time	DateTime	Date and time combined

String Concatenation

The string concatenation operator (|) is used to combine strings. For example, assuming &OPER_NICKNAME is "Dave", the following statement sets &RETORT to "I can't do that, Dave."

```
&RETORT = "I can't do that, " | &OPER_NICKNAME | " ."
```

The concatenation operator automatically converts its operands to strings. This conversion makes it easy to write statements that display mixed data types. For example:

```
&DAYS_LEFT = &CHRISTMAS - %Date;
WinMessage("Today is " | %Date | ". Only " | &DAYS_LEFT | " shopping days left!");
```

@ Operator

The @ operator converts a string storing a definition reference into the definition. This is useful, for example, if you want to store definition references in the database as strings and retrieve them for use in PeopleCode; or if you want to obtain a definition reference in the form of a string from the operator using the Prompt function.

To take a simple example, if the record field EMPLID is currently equal to 8001, the following expression evaluates to 8001:

```
@ "EMPLID"
```

The following example uses the @ operator to convert strings storing a record reference and a record field reference:

```
&STR1 = "RECORD.BUS_EXPENSE_PER";
&STR2 = "BUS_EXPENSE_DTL.EMPLID";
&STR3 = FetchValue(@(&STR1), CurrentRowNumber(1), @(&STR2), 1);
WinMessage(&STR3, 64);
```

Note. String literals that reference definitions are not maintained by PeopleTools. If you store definition references as strings, then convert them with the @ operator in the code, this creates maintenance problems whenever definition names change.

The following function takes a rowset and a record, passed in from another program, and performs some processing. The GetRecord method does not take a variable for the record, however, you can dereference the record name using the @ symbol. Because the record name is never hard-coded as a string, if the record name changes, this code does not have to change.

```
Function Get_My_Row(&PASSED_ROWSET, &PASSED_RECORD)

    For &ROWSET_ROW = 1 To &PASSED_ROWSET.RowCount
        &UNDERLYINGREC = "RECORD." | &PASSED_ROWSET.DBRecordName;
        &ROW_RECORD = &PASSED_ROWSET.GetRow(&ROWSET_ROW).GetRecord(@&UNDERLYINGREC);

        /* Do other processing */
    End-For;

End-Function;
```

Comparison Operators

Comparison operators compare two expressions of the same data type. The result of the comparison is a Boolean value. The following table summarizes these operators:

<i>Operator</i>	<i>Meaning</i>
=	Equal
!=	Not equal

Operator	Meaning
<>	Not equal
<	Less than
<=	Less than or equal to
>	Greater than
>=	Greater than or equal to

You can precede any of the comparison operators with the word *Not*, for example:

- Not=
- Not<
- Not>=

Expressions formed with comparison operators form logical terms that can be combined using Boolean operators.

String comparisons are case-sensitive. You can use the Upper or Lower built-in functions to do a case-insensitive comparison.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Lower

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Upper

Boolean Operators

The logical operators AND, OR, and NOT are used to combine Boolean expressions. The following table shows the results of combining two Boolean expressions with AND and OR operators:

Expression 1	Operator	Expression 2	Result
False	AND	False	False
False	AND	True	False

<i>Expression 1</i>	<i>Operator</i>	<i>Expression 2</i>	<i>Result</i>
True	AND	True	True
False	OR	False	False
False	OR	True	True
True	OR	True	True

The NOT operator negates Boolean expressions, changing a True value to False and a False value to True.

In complex logical expressions using the operations AND, OR, and NOT, NOT takes the highest precedence, AND is next, and OR is lowest. Use parentheses to override precedence. (Generally, it is a good idea to use parentheses in logical expressions anyway, because it makes them easier to decipher.) If used on the right side of an assignment statement, Boolean expressions must be enclosed in parentheses.

The following are examples of statements containing Boolean expressions:

```
&FLAG = (Not (&FLAG)); /* toggles a Boolean */
if ((&HAS_FLEAS or &HAS_TICKS) and
    SOAP_QTY <= MIN_SOAP_QTY) then
    SOAP_QTY = SOAP_QTY + OrderFleaSoap(SOAP_ORDER_QTY);
end-if;
```


Chapter 3

Understanding Objects and Classes in PeopleCode

This chapter discusses:

- Classes and objects
- Creating and using objects.
- Assigning objects.
- Passing objects.

Classes and Objects

PeopleSoft delivers classes of objects that you can manipulate with PeopleCode. In addition, you can extend the existing classes or create your own. The delivered classes may or may not have a graphic user interface equivalent; some are representations of data structures that occur only at runtime. With PeopleCode, you can manipulate data in the data buffer easily and consistently. These classes enable you to write code that's more readable, more easily maintained, and more useful.

This section discusses:

- Classes.
- Objects.
- Object instantiation.

Classes

A *class* is the formal definition of an object and acts as a template from which an instance of an object is created at runtime. The class defines the properties of the object and the methods used to control the object's behavior.

PeopleSoft delivers predefined classes, such as Array, File, Field, SQL, and so on. You can create your own classes using the Application class. You can also extend the functionality of the existing classes using the Application class.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Application Classes"

Objects

An *object* represents a unique instance of a data structure defined by the template provided by its class. Each object has its own values for the variables belonging to its class and responds to methods defined by that class. This is the same for classes provided by PeopleSoft and for classes you create yourself.

After an object has been created (instantiated) from a class, you can change its properties. A *property* is an attribute of an object. Properties define:

- Object characteristics, such as name or value.
- The state of an object, such as deleted or changed.

Some properties are read-only and cannot be set, such as Name or Author. Other properties can be set, such as Value or Label.

Objects are different from other data structures. They include code (in the form of *methods*), not just static data. A *method* is a procedure or routine, associated with one or more classes, that acts on an object.

An analogy to illustrate the difference between an object and its class is the difference between a car and the blue Citroen with license plate number TS5800B. A class is a general category, while the object is a specific instance of that class. Each car comes with standard characteristics, such as four wheels, an engine, or brakes, that define the class and are the template from which the individual car is created. You can change the properties of an individual car by personalizing it with bumper stickers or racing stripes, which is like changing the Name or Visible property of an object. The model and date that the car is created are similar to read-only properties because you cannot alter them. A tune-up acts on the individual car and changes its behavior, much as a method acts on an object.

Object Instantiation

A class is the blueprint for something, like a bicycle, a car, or a data structure. An object is the actual thing that is built using that class (or blueprint.) From the blueprint for a bicycle, you can build a specific mountain bike with 23 gears and tight suspension. From the blueprint of a data structure class, you build a specific instance of that class. *Instantiation* is the term for building that copy, or an instance, of a class.

Creating and Using Objects

This section discusses how to:

- Instantiate objects.
- Change object properties.
- Invoke methods.

- Copy objects.

Instantiating Objects

Generally you instantiate objects (create them from their classes) using built-in functions or methods of other objects. Some objects are instantiated from data already existing in the data buffer. Think about this kind of object instantiation as taking a chunk of data from the buffer, encapsulating it in code (methods and properties), manipulating it, then freeing the references. Some objects can be instantiated from a previously created definition, such as a page or file layout definition, instead of from data.

The following example creates a field object:

```
Local field &MyField

&MyField = GetField();
```

Get functions, which include functions such as `GetField`, `GetRecord`, and so on, generally provide access to data that already exists, whether in the data buffers or from an existing definition.

Create functions, which include functions such as `CreateObject`, `CreateArray`, `CreateRecord`, generally create defined objects that do not yet exist in the data buffer. Create functions create only a buffer structure. They do not populate it with data. For example, the following function returns a record object for a record that already exists in the component buffer:

```
&REC = GetRecord();
```

The following example creates a standalone record. However, there is no data in `&REC2`. The specified record definition must be created previously, but the record does not have to exist in either the component or data buffer:

```
&REC2 = CreateRecord(EMP_CHKLIST_ITM);
```

Objects with no built-in functions can only be instantiated from a session object (such as tree classes, component interfaces, and so on). For most of these classes, when you use a Get function, all you get is an identifier for the object. To fully instantiate the object, you must use an Open method.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Session Class"

Changing Properties

To set or get characteristics of an object, or to determine the state of an object, you must access its properties through *dot notation* syntax. Follow the reference to the object with a period, followed by the property, and assign it a value. The format is generally as follows:

```
Object.Property = Value
```

The following example hides the field `&MYFIELD`:

```
&MYFIELD.Visible = False
```

You can return information about an object by returning the value of one of its properties. In the following example, &X is a variable that is assigned the value found in the field &MYFIELD:

```
&X = &MYFIELD.Value
```

In the following example, a property is used as the test for a condition:

```
If &ROWSET.ActiveRowCount <> &I Then
```

Invoking Methods

You also use dot notation to execute methods. Follow the reference to the object with a period, then with the method name and any parameters the method takes. The format is generally:

```
Object.method();
```

You can string methods and property values together into one statement. The following example strings together the GetField method with the Name property:

```
If &REC_BASE.GetField(&R).Name = &REC_RELLANG.GetField(&J).Name Then
```

Some methods return a Boolean value: True if the method executes successfully; False if it does not. The following method compares all like-named fields of the current record object with the specified record. This method returns as True if all like-named fields have the same value:

```
If &MYRECORD.CompareFields(&OTHERRECORD) Then
```

Other methods return a reference to an object. The GetCurrEffRow method returns a row object:

```
&MYROW = &MYROWSET.GetCurrEffRow();
```

Some methods do not return anything. Each method's documentation indicates what it returns.

Many objects have default methods. Instead of entering the name of the method explicitly, you can use that method's parameters. Objects with default methods are *composite objects*; that is, they contain additional objects within them. The default method is generally the method used to get the lower-level object.

A good example of a composite object is a record object. Record definitions are composed of field definitions. The default method for a record object is GetField.

The following lines of code are equivalent:

```
&FIELD = &RECORD.GetField(FIELD.EMPLID);
&FIELD = &RECORD.EMPLID;
```

Note. If the field you're accessing has the same name as a record property (such as NAME) you cannot use the shortcut method for accessing the field. You must use the GetField method.

Another example of default methods concerns rowsets and rows. Rowsets are made up of rows, so the default method for a rowset is GetRow. The two specified lines of code are equivalent: They both get the fifth row of the rowset:

```
&ROWSET = GetRowSet();

/*the next two lines of code are equivalent */

&ROW = &ROWSET.GetRow(5);
&ROW = &ROWSET(5);
```

The following example illustrates the long way of enabling the Name field on a second-level scroll area (the code is executing on the first-level scroll area):

```
GetRowset( SCROLL.EMPLOYEE_CHECKLIST ).GetRow(1) .
GetRecord(EMPL_CHKLIST_ITM).GetField(FIELD.NAME).Enabled = True;
```

Using default methods enables you to shorten the previous code to the following:

```
GetRowset( SCROLL.EMPLOYEE_CHECKLIST )(1) .EMPL_CHKLIST_ITM.NAME .
Enabled = True;
```

Expressions of the form *class.name.property* or *class.name.method(..)* are converted to a corresponding object. For example, the code `&temp = RECORD.JOB.IsChanged;` is evaluated as if it were `&temp = GetRecord(RECORD.JOB).IsChanged;`

Furthermore, the code `JOB.EMPLID.Visible = False;` is evaluated as if it were `GetField(JOB.EMPLID).Visible = False;`

Copying Objects

Many of the classes delivered with PeopleTools have some sort of copy method, such as the rowset class `CopyTo`, the tree class `Copy`, and so on. Unless specifically identified (such as the message class `CopyRowsetDelta`) all copy methods use the current data of the object. This may be different than the original data values if the object was retrieved from the database and the values in it have been changed either by an end-user or a PeopleCode program.

Assigning Objects


When you assign one object to another, you do not create a copy of the object, but only make a copy of the reference.

In the following example, `&A1` and `&A2` refer to the same object. The assignment of `&A1` to `&A2` does not allocate any database memory or copy any part of the original object. It makes `&A2` refer to the same object to which `&A1` refers.

```
Local Array of Number &A1, &A2;


&A1 = CreateArray(2, 4, 6, 8, 10);
&A2 = &A1;
```

The following diagram shows how both references point to the same object:



Representation of two arrays

If the next statement is `&A2[5] = 12;`, then `&A1[5]` also equals 12, as shown in the following diagram:



Representation of two arrays with same content

The following example is *not* considered an object assignment:

```
Local number &NUM;
Local Array of Number &A1;

&A1 = CreateArray(2, 4, 6, 8, 10);
&NUM = &A1[3];
```

`&NUM` is of data type Number, which is not an object type. If you later change the value of `&NUM` in the program, you will not change the element in the array.

Passing Objects

All PeopleCode objects can be passed as function parameters. You can pass complex data structures between PeopleCode functions (as opposed to passing long lists of fields). If a function is passed an object, the function works on the actual object, not on a copy of the object.

In the following simple example, a reference to the Visible property is passed, not the *value* of Visible. This enables the `MyPeopleCodeFunction` either to get or set the value of the Visible property:

```
MyPeopleCodeFunction(&MyField.Visible);
```

In the following example, the function `Process_Rowset` loops through every row and record in the rowset passed to it and executes an Update statement on each record in the rowset. This function can be called from any PeopleCode program and can process any rowset that is passed to it.

```
Local Rowset &RS;
Local Record &REC;

Function Process_RowSet(&ROWSET as Rowset);

    For &I = 1 To &ROWSET.RowCount
        For &J = 1 To &ROWSET.Recordcount
            &REC = &ROWSET.GetRow(&I).GetRecord(&J);
            &REC.Update();
        End-For;
    End-For;
End-Function;

&RS = GetLevel0();

Process_RowSet(&RS);
```

The following function takes a rowset and a record passed in from another program. GetRecord does not take a variable for the record; however, you can use the @ symbol to dereference the record name.

```
Function Get_My_Row(&PASSED_ROWSET, &PASSED_RECORD)

    For &ROWSET_ROW = 1 To &PASSED_ROWSET.RowCount
        &UNDERLYINGREC = "RECORD." | &PASSED_ROWSET.DBRecordName;
        &ROW_RECORD = &PASSED_ROWSET.GetRow(&ROWSET_ROW).GetRecord(@&UNDERLYINGREC);

        /* Do other processing */
    End-For;

End-Function;
```


Chapter 4

Referencing Data in the Component Buffer

This chapter provides an overview of component buffer structure and contents and discusses how to:

- Specify data with contextual references.
- Specify data with references using scroll path syntax and dot notation.

Understanding Component Buffer Structure and Contents

This section discusses:

- Component buffer contents.
- Rowsets and scroll areas.
- Record fields in the component buffer.

See Also

Chapter 4, "Referencing Data in the Component Buffer," Specifying Data with References Using Scroll Path Syntax and Dot Notation, page 56

Component Buffer Contents

PeopleCode frequently must refer to data in the component buffer, the area in memory that stores data for the currently active component.

The two methods for specifying a piece of data in the component buffer from within PeopleCode are:

- Contextual references, which refer to data relative to the location of the currently executing PeopleCode program.
- References using scroll path syntax, which provide a complete, or absolute, path through the component buffer to the referenced component.

In addition to the built-in functions used to access the component buffer, PeopleCode provides enhanced access to structured data buffers using the object syntax. Use the object-oriented PeopleCode to resolve contextual ambiguities when you reference a nonprimary record field that appears on more than one scroll level in a component. As with built-in functions, object syntax provides for both relative and absolute references to component buffer data.

See [Chapter 3, "Understanding Objects and Classes in PeopleCode," page 39.](#)

The component buffer consists of rows of buffer fields that hold data for the records associated with page controls, including primary scroll records, related display records, derived/work records, and Translate table records. PeopleCode can reference buffer fields associated with page controls and other buffer fields from the primary scroll record and related display records.

See [Chapter 4, "Referencing Data in the Component Buffer," Record Fields and the Component Buffer, page 50.](#)

Primary scroll records are the principal SQL tables or views associated with page scroll levels. A primary scroll record uniquely identifies a scroll level in the context of its page: each scroll level can have only one primary scroll record, and the same primary scroll record cannot occur on more than one scroll area at the same level of the page. Parent-child relations between primary scroll records determine the dependency structure of the scroll areas on the page. The primary record on a level one scroll area must be a child of the primary record on level zero, the primary record on a level two scroll area must be a child of the primary record on its enclosing level one scroll area, and the primary record on a level three scroll area must be a child of the primary record on its enclosing level two scroll area.


Note. Level zero may have multiple records.

The hierarchical relations among scroll areas, controlled by hierarchical relations among primary scroll records, enable the user and PeopleCode to drill down through the scroll hierarchy to access any buffer field, including related display, derived/work, and Translate table buffer fields, which occupy space on the same rows as the primary scroll record buffer fields with which they are associated.

For example, to access a page field on level two of a page, a user must:

1. Select a field on level one of the page.
2. Scroll to and select the field on level two of the page.

The following diagram illustrates this scroll path taken by the user:



Scroll path to a buffer field

To access the same field in the component buffer, PeopleCode must:

1. Specify a scroll area and row on scroll level one: this selects a subset of dependent rows on level two.
2. Specify a scroll area and row on scroll level two.
3. Specify the recordname.fieldname on the level two row.

PeopleCode component buffer functions use a common scroll path syntax for locating scrolls, rows, and fields in multiple-scroll pages.

Rowsets and Scroll Areas

Rowsets enable more consistent, more convenient, and less ambiguous manipulation of buffer data than previous built-in functions could achieve. It's a hierarchical data object that can represent an entire scroll area and all of its subordinate scroll areas.

A rowset can contain the entire contents of a component buffer, or the contents of any lower-level scroll area plus all of its subordinate buffer data. The hierarchical structure of component levels—scroll area, row, record, field—is provided by the new object data types, Rowset, Row, Record, and Field.

You can access any rowset, row, record, or field within the buffer using the dot notation inherent in PeopleTools 8 object-oriented programming. This enables you to reference fields within a record object, records within a row object, and rows within a rowset object as properties of the parent objects.

See Also

[Chapter 5, "Accessing the Data Buffer," page 67](#)

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Rowset Class"

[Chapter 3, "Understanding Objects and Classes in PeopleCode," page 39](#)

Record Fields and the Component Buffer

The record fields in the component buffer are a superset of those accessible to the user through page controls. In most cases, PeopleCode can reference any record field in a scroll area's primary scroll record or in a related display record, not just those fields that are associated with page controls. The following table lists record types and locations:

<i>Type and Location of Record</i>	<i>Presence in Component Buffer</i>
Primary record on scroll levels greater than zero	On scroll levels greater than zero, all record fields from the primary scroll record are in the component buffer. PeopleCode can refer to any record field on the primary scroll record, even if it is not associated with a page control.
Primary record on scroll level zero	If scroll level zero of a page contains only controls associated with primary scroll record fields that are search keys or alternate search keys, then only the search key and alternate search key fields are in the component buffer, not the entire record. The values for the fields come from the keylist, and the record cannot run RowInit PeopleCode. If level zero contains at least one record field from the primary scroll record that is not a search key or alternate search key, then all the record fields from the primary scroll record are available in the buffer. (For this reason, you may sometimes need to add one such record field at level zero of the page to make sure that all the record fields of the level-zero primary record can be referenced from PeopleCode.)
Related display record fields	The buffer contains the related display record field, plus any record fields from the related display record that are referenced by PeopleCode programs. You can reference any record field in a related display record.
Derived/work record fields	Only derived/work record fields associated with page controls are in the component buffer. Other record fields from the derived/work record cannot be referenced from PeopleCode.

<i>Type and Location of Record</i>	<i>Presence in Component Buffer</i>
Translate table record fields	Only Translate table fields associated with page controls are available in the component buffer. Other fields from the Translate table cannot be referenced from PeopleCode.

Note. In RowSelect PeopleCode, you can refer only to record fields on the record that is currently being processed.

Specifying Data with Contextual References

In a contextual reference, PeopleCode refers to a row or buffer field determined by the context in which a PeopleCode program is currently executing.

This section includes an overview of current context and discusses how to:

- Use contextual row references.
- Use contextual buffer field references.


Understanding Current Context

All PeopleCode programs, with the exception of programs associated with standard menu items, execute in a current context. The current context determines which buffer fields can be contextually referenced from PeopleCode, and which row of data is the current row on each scroll level at the time a PeopleCode program is executing.

The current context comprises a subset of the buffer fields in the component buffer, determined by the row of data where a PeopleCode program is executing. The current context includes:

- All buffer fields in the row of data where the PeopleCode program is executing.
- All buffer fields in rows that are hierarchically superior to the row where the PeopleCode program is executing.

In the following diagram, all rows enclosed in dotted rectangles are part of the current context:




Context of PeopleCode executing on a level two scroll area

In the preceding diagram, a PeopleCode program is executing in a buffer field on row R3 on scroll level two. The rows in scroll level two are dependent on row R2 on scroll level one. The rows in scroll level one are dependent on the single row at scroll level zero. The current context consists of all the buffer fields at level two row R3, level one row R2, and level zero row R1. The rows in the current context on levels one and two are the current rows on their respective scroll areas. The single row on level zero is always current and is included in any current context. All rows other than the current rows and the level zero row are outside the current context. No current row can be determined on scroll areas below the one where the PeopleCode is executing.

With PeopleTools 8, contextual references work within the structure of a rowset object, and can include references to all field objects, record objects, row objects, and rowset objects in the current context.

Contextual Reference Processing Order

PeopleCode resolves contextual references at runtime by first checking the row where the PeopleCode program is executing. If PeopleCode does not find an appropriate buffer field, it looks in progressively higher rows in the current context. The following diagram indicates this processing order:



Processing order of a contextual reference

In typical pages, this processing order is not significant; however, if the same record occurs on more than one level of a page, you should understand how the direct reference is resolved.

Using Contextual Row References

A contextual row reference refers to a row in the current context on level one or lower in the page. Because each scroll area uses a unique primary record, the name of that record uniquely identifies whichever row is in the current context for that scroll level. A contextual row reference uses a **RECORD.recordname** component name reference to specify the scroll level of the intended row, resulting in a reference to the current row at the specified scroll level.

For example, you can use contextual row references with the RecordDeleted, RecordNew, and RecordChanged functions:

```
If RecordDeleted(RECORD.SOME_REC) Then...
```

With PeopleTools 8 object-oriented programming, a row can be referenced by specifying parent rows or rowsets of the current rowset:

```
If GetRowSet().ParentRowset.ParentRow.IsDeleted Then...
```

In early versions of PeopleTools, you could make contextual row references using a *recordname.fieldname* expression:

```
HideRow(SOME_REC.ANY_FIELD)
```

```
If RecordDeleted(SOME_REC.ANY_FIELD) Then...
```

This syntax is still supported.

See Also

[Chapter 4, "Referencing Data in the Component Buffer," Understanding Current Context, page 51](#)

Using Contextual Buffer Field References

A contextual buffer field reference is a type of PeopleCode expression that refers to a buffer field by specifying a record field. The row of the buffer field is determined by the current context of the PeopleCode program where the reference is made. You can use a contextual buffer field reference to retrieve or update the value in the buffer field, to pass the buffer field value to a function, or to reference an instance of a page control associated with the buffer field. The following statements use contextual buffer field references:

```
/* Assigns value of variable to buffer field */
SOME_RECORD.SOME_FIELD = &VAL;
/* Assigns value of buffer field to variable */
&VAL = SOME_RECORD.SOME_FIELD;
/* Hides instance of control associated with buffer field */
Hide(SOME_RECORD.SOME_FIELD);
```

With PeopleTools 8 object-oriented programming, a field object incorporates information about both the record field on which the buffer field is based and the page control with which the buffer field is associated. By referring to the field object, you either make a contextual buffer field reference or you change an interface attribute of the associated page control, depending on the object property you use. The following example has the same effect as a contextual buffer field reference:

```
/* Assigns value of a variable to a buffer field */
&MYFIELD.Value = &SOMEVAL;
```

Contextual Buffer Field Reference Ambiguity

Nonprimary record fields may appear on more than one scroll level in a page. For example, a page may use a derived/work field DERIVED_JS.CALC_1 as a work field on level one and level two of the same page. This creates distinct DERIVED_JS.CALC_1 buffer fields for rows on both levels. Because of the order in which PeopleCode resolves contextual buffer field references, if the contextual reference &VAL = DERIVED_JS.CALC_1; executes in a PeopleCode program on a level-two row, the reference always retrieves the buffer field value on the current row on level two. PeopleCode on level two is unable to retrieve the value of the DERIVED_JS.CALC_1 on level one using a contextual reference.

To explicitly reference the DERIVED_JS.CALC_1 buffer field on level one, use a component buffer function with a scroll path:

```
&VAL = FetchValue(SCROLL.level1_scrollname, CurrentRowNumber(1), DERIVED_JS.CALC_1 => 1);
```

The `CurrentRowNumber` function returns the current row on level one, or the parent row of the level two row where the PeopleCode program is executing.

Ambiguous Contextual References to Buffer Fields on Level Zero

Level zero of a page contains only a single row of data, and the buffer fields in this row are always in the current context. For this reason you can almost always refer to a level zero buffer field using a contextual reference. However, referential ambiguity can make it impossible to reference a buffer field on level zero contextually. For example, a page may use a derived/work field `DERIVED_JS.CALC_1` as a work field on level zero and level one of the same page. This creates distinct `DERIVED_JS.CALC_1` buffer fields for rows on both levels. Because of the order in which PeopleCode resolves contextual field references, if the `&VAL = DERIVED_JS.CALC_1`; contextual reference executes in a PeopleCode program on a level-one row, it always retrieves the buffer field value on the current row on level one.

To explicitly reference the `DERIVED_JS.CALC_1` buffer field on level zero, you must use a component buffer function with this syntax:

```
Function([recordname.]fieldname, rownum)
```

Here *rownum*, because it is on level zero, is always equal to one. In the previous example of the `DERIVED_JS.CALC_1` field, you would use this statement:

```
&VAL = FetchValue(DERIVED_JS.CALC_1, 1);
```

Ambiguous References with Objects

With PeopleTools 8 object-oriented programming, even if two field objects that are in different rowsets contain buffer data that's based on the same underlying record field, references to those objects are inherently unique, because each is instantiated with respect to a specific point in the hierarchy of the buffer. Any manipulation of a field object's interface properties affects only the page control with which it's associated.

The following example instantiates a field object using the long form, to emphasize the hierarchical form of the data. It then hides the field's associated page control. Because this is a unique instance of the field, based on its hierarchy, hiding this field does not affect the visibility of any other page control associated with the same record field:

```
&MYFIELD = GetRowset(ROLLBACK.EMPL_CHECKLIST).GetRow(&I).
GetRecord(RECORD.EMPL_CHECKLIST).GetField(EMPL_CHECKLIST.EMPLID);
&MYFIELD.Visible = False;
/* the same code, using the "short" form */
&MYFIELD = GetRowset(ROLLBACK.EMPL_CHECKLIST).GetRow(&I).
EMPL_CHECKLIST.EMPLID;
```

Note. Any change in a field object's value affects both the underlying record field and the value of any other field object oriented on the same record field. This behavior is the same as the behavior of contextual buffer field references that alter the field value.

See Also

Chapter 4, "Referencing Data in the Component Buffer," Specifying Data with References Using Scroll Path Syntax and Dot Notation, page 56

Specifying Data with References Using Scroll Path Syntax and Dot Notation

This section provides an overview of scroll paths and discusses how to:

- Structure scroll path syntax in PeopleTools 7.5.
- Reference scroll levels, rows, and buffer fields.

See Also

[Chapter 5, "Accessing the Data Buffer," page 67](#)

Understanding Scroll Paths

A scroll path is a construction found in the parameter lists of many component buffer functions, which specifies a scroll level in the currently active page. Additional parameters are required to locate a row or a buffer field at the specified scroll level.

PeopleTools 7.5 scroll path syntax enables you to eliminate ambiguous references, which, although rare, do sometimes occur in complex components.

See [Chapter 4, "Referencing Data in the Component Buffer," Using Contextual Buffer Field References, page 54.](#)

PeopleTools 8 adds the convenience of object-oriented dot notation and default methods, which produce inherently non-ambiguous references, to PeopleCode programs. There are examples of dot notation in this section and examples of the scroll path syntax available in PeopleTools 7.5, which is still valid in PeopleTools 8.

Structuring Scroll Path Syntax in PeopleTools 7.5

PeopleTools 7.5 offers two constructions for scroll paths: a standard scroll path syntax and an alternative syntax using a **SCROLL**.*scrollname* expression. The latter is more powerful in that it can process some rare cases where a **RECORD**.*recordname* expression results in an ambiguous reference.

Scroll Path Syntax with **RECORD**.*recordname*

Here is the standard scroll path syntax:

```
[RECORD.level1_recname, level1_row, [RECORD.level2_recname, level2_row, ]] RECORD.⇒  
target_recname
```

If the target level (the level you want to reference) is one, you must supply only the **RECORD**.*target_recname* parameter. If the target scroll level is greater than one, you must provide scroll name and row level parameters for all hierarchically superior scroll levels, beginning at level one. The following table indicates the scroll path syntax for the three possible target scroll levels:

<i>Target Level</i>	<i>Scroll Path Syntax</i>
1	RECORD .target_recname
2	RECORD .level1_recname, level1_row, RECORD .target_recname
3	RECORD .level1_recname, level1_row, RECORD .level2_recname, level2_row, RECORD .target_recname

If you are referring to a row or a buffer field, additional parameters are required after the scroll path.

The following table describes the standard scroll path syntax parameters:

<i>Syntax Parameters</i>	<i>Description</i>
RECORD .level1_recname	Specifies the name of a record associated with scroll level one, normally the primary scroll record. This parameter is required if the target scroll level is two or three.
level1_row	An integer that selects a row on scroll level one. This parameter is required if the target scroll level is two or three.
RECORD .level2_recname	Specifies the name of a record associated with scroll level two, normally the primary scroll record. This parameter is required if the target row is on scroll level three.
level2_row	An integer that selects a row on scroll level two. This parameter is required if the target row is on scroll level three.
RECORD .target_recname	Specifies a record associated with the target scroll level, generally the primary scroll record. The scroll can be on level one, two, or three of the active page.

Scroll Path Syntax with *SCROLL.scrollname*

As an alternative to **RECORD.recordname** expressions in scroll path constructions, PeopleTools 7.5 permits use of a **SCROLL.scrollname** expression. Scroll paths using **SCROLL.scrollname** are functionally identical to those using **RECORD.recordname**, except that **SCROLL.scrollname** expressions are more strict: they can refer only to a scroll level's primary record; whereas **RECORD.recordname** expressions can refer to any record in the scroll level, which in some rare cases can result in ambiguous references. (This can occur, for example, if the **RECORD.recordname** expression inadvertently references a related display record in another page in the component.) Use of **RECORD.recordname** is still permitted, and there is no requirement to use the **SCROLL.scrollname** alternative unless it is needed to avoid an ambiguous reference.

The *scrollname* is the same as the scroll level's primary record name.

The scroll name cannot be viewed or changed through the PeopleSoft Application Designer interface. Here is the complete scroll path syntax using **SCROLL.scrollname** expressions:

```
[SCROLL.level1_scrollname, level1_row, [SCROLL.level2_scrollname, level2_row, ]], =>
SCROLL.target_scrollname
```

The target scroll level in this construction is the scroll level that you want to specify. If the target level is one, you need to supply only the **SCROLL.target_scrollname** parameter. If the target scroll level is greater than one, you need to provide scroll name and row-level parameters for hierarchically superior scroll levels, beginning at level one. The following table indicates the scroll path syntax for the three possible target scroll levels:

<i>Target Level</i>	<i>Scroll Path Syntax</i>
1	SCROLL.target_scrollname
2	SCROLL.level1_scrollname , <i>level1_row</i> , SCROLL.target_ <i>scrollname</i>
3	SCROLL.level1_scrollname , <i>level1_row</i> , SCROLL.level2_ <i>scrollname</i> , <i>level2_row</i> , SCROLL.target_scrollname

If the component you are referring to is a row or a buffer field, additional parameters are required after the scroll path.

The following table describes the alternative scroll path syntax parameters:

<i>Parameter</i>	<i>Description</i>
SCROLL.level1_scrollname	Specifies the name of the page's level-one scroll area. This is always the same as the name of the scroll level's primary scroll record. This parameter is required if the target scroll level is two or three.
<i>level1_row</i>	An integer that selects a row on scroll level one. This parameter is required if the target scroll level is two or three.
SCROLL.level2_scrollname	Specifies the name of the page's level two scroll area. This is always the same as the name of the scroll level's primary scroll record. This parameter is required if the target row is on scroll level three.
<i>level2_row</i>	An integer that selects a row on scroll level two. This parameter is required if the target row is on scroll level three.
SCROLL.target_scrollname	The scroll name of the target scroll level, which can be level one, two, or three of the active page.

See Also

Chapter 4, "Referencing Data in the Component Buffer," Referencing Scroll Levels, Rows, and Buffer Fields, page 59

Referencing Scroll Levels, Rows, and Buffer Fields

You can reference a scroll level using the *scrollpath* construct only. Functions that reference rows for buffer fields require additional parameters. The following table summarizes the three types of component buffer references:

<i>Target Component</i>	<i>Reference Syntax</i>	<i>Example Function</i>
Scroll level	<code>scrollpath</code>	<code>HideScroll(scrollpath);</code>
Row	<code>scrollpath, row_number</code>	<code>HideRow(scrollpath, row_⇒ number);</code>
Field	<code>scrollpath, row_number, [recordname.]fieldname</code>	<code>FetchValue(scrollpath, row_⇒ ⇒ ⇒ number, fieldname);</code>

PeopleTools 8 provides an alternative to the scroll level, row, and field components in the form of the data buffer classes Rowset, Row, Record, and Field, which you reference using dot notation with object methods and properties. The following table demonstrates the syntax for instantiating and manipulating objects in the current context from these classes:

<i>Target Object</i>	<i>Example Instantiation</i>	<i>Example Operation</i>
Rowset	<code>&MYROWSET = GetRowset();</code>	<code>&MYROWSET.Refresh();</code>
Row	<code>&MYROW = GetRow();</code>	<code>&MYROW.CopyTo(&SOMEROW);</code>
Record	<code>&MYRECORD = GetRecord();</code>	<code>&MYREC.CompareFields(&REC);</code>
Field	<code>&MYFIELD = GetRecord(). fieldname;</code>	<code>&MYFIELD.Label = "Last Name";</code>

The following sections provide examples of functions using scroll path syntax, which refer to an example page from a fictitious veterinary clinic database. The page has three scroll levels, shown in the following table:

<i>Level</i>	<i>Scroll Name (Primary Scroll Record Name)</i>
0	VET
1	OWNER
2	PET
3	VISIT

The examples given for PeopleTools 8 object-oriented syntax assumes that the following initializing code was executed:

```
Local Rowset   &VET_SCROLL, &OWNER_SCROLL, &PET_SCROLL, &VISIT_SCROLL;

&VET_SCROLL = GetLevel0();
&OWNER_SCROLL = &VET_SCROLL.GetRow(1).GetRowSet(SCROLL.OWNER);
&PET_SCROLL = &OWNER_SCROLL.GetRow(2).GetRowSet(SCROLL.PET);
&VISIT_SCROLL = &PET_SCROLL.GetRow(2).GetRowSet(SCROLL.VISIT);
```

Referring to Scroll Levels

The HideScroll function provides an example of a reference to a scroll level. The syntax of the function is:

HideScroll(*scrollpath*)

where *scrollpath* is

[**RECORD.level1_recname**, *level1_row*, [**RECORD.level2_recname**, *level2_row*,]] **RECORD.**⇒
target_recname

To reference the level 1 scroll in the example, use this syntax:

```
HideScroll(RECORD.OWNER);
```

This hides the OWNER, PET, and VISIT scroll areas on the example page.


In PeopleTools 8, the object-oriented version of this is:

```
&OWNER_SCROLL.HideAllRows();
```

To hide scroll levels two and below, supply the primary record and row in scroll level one, and then the record identifying the target scroll area:

```
HideScroll(RECORD.OWNER, &L1ROW, RECORD.PET);
```

The following diagram shows the scroll path of this statement, assuming that the value of &L1ROW is 2:



Sample scroll path

Similarly, to hide the VISIT scroll area on level three, you specify rows on scroll levels one and two.

```
HideScroll(RECORD.OWNER, &L1ROW, RECORD.PET, &L2ROW, RECORD.VISIT);
```

To use the **SCROLL.scrollname** syntax, the previous example could be written as the following:

```
HideScroll(SCROLL.OWNER, &L1ROW, SCROLL.PET, &L2ROW, SCROLL.VISIT);
```

In PeopleTools 8, the object-oriented version of this is:

```
&VISIT_SCROLL.HideAllRows();
```

Referring to Rows

Referring to rows is the same as referring to scroll areas, except that you need to specify the row you want to select on the target scroll area. As an example, examine the HideRow function, which hides a specific row in the level three scroll area of the page. Here is the function syntax:

```
HideRow(scrollpath, target_row)
```

To hide row number &ROW_NUM on level one:

```
HideRow(RECORD.OWNER, &ROW_NUM);
```

To do the same using the **SCROLL.scrollname** syntax:

```
HideRow(SCROLL.OWNER, &ROW_NUM);
```

In PeopleTools 8, the object-oriented version of this for the OWNER rowset is:

```
&OWNER_SCROLL(&ROW_NUM).Visible = False;
```


On level two:

```
HideRow(RECORD.OWNER, &L1_ROW), RECORD.PET, &ROW_NUM);
```

In PeopleTools 8, the object-oriented version of this for the PET rowset is:

```
&PET_SCROLL(&ROW_NUM).Visible = False;
```

The following diagram indicates the scroll path of this statement, assuming that the value of &L1_ROW is 2 and that &ROW_NUM is equal to 2:



Scroll path statement

On level three:

```
HideRow(RECORD.OWNER, CurrentRowNumber(1), RECORD.PET,  
CurrentRowNumber(2), RECORD.VISIT, &ROW_NUM);
```

In PeopleTools 8, the object-oriented version of this for the VISIT rowset is:

```
&VISIT_SCROLL(&ROW_NUM).Visible = False;
```

Referring to Buffer Fields

Buffer field references require a `[recordname].fieldname` parameter to specify a record field. The combination of scroll level, row number, and record field name uniquely identifies the buffer field. Here is the syntax:

```
FetchValue(scrollpath, target_row, [recordname].fieldname)
```

Assume, for example, that record definitions in the veterinary database have the following fields that you want to reference:

Record	Sample Field
OWNER	OWNER_NAME

Record	Sample Field
PET	PET_BREED
VISIT	VISIT_REASON

You could use the following examples to retrieve values on levels one, two, or three from a PeopleCode program executing on level zero.

To fetch a value of the OWNER_NAME field on the current row of scroll area one:

```
&SOMENAME = FetchValue(RECORD.OWNER, &L1_ROW, OWNER.OWNER_NAME);
```

In PeopleTools 8, the object-oriented version of this for the OWNER rowset is:

```
&SOMENAME = &OWNER_SCROLL(&L1_ROW).OWNER.OWNER_NAME;
```


To fetch PET_BREED on level two:

```
&SOMEBREED = FetchValue(RECORD.OWNER, &L1_ROW, RECORD.PET, &L2_ROW, PET.PET_BREED);
```

In PeopleTools 8, the object-oriented version of this for the PET rowset is:

```
&SOMEBREED = &PET_SCROLL(&L2_ROW).PET.PET_BREED;
```

The following diagram indicates the scroll path to the target field, assuming that &L1_ROW equals 2, &L2_ROW equals 2, and field F3 is PET.PET_BREED:



Scroll path to target field

To fetch VISIT_REASON on level three:

```
&SOMEREASON = FetchValue(RECORD.OWNER, &L1_ROW, RECORD.PET,
&L2_ROW, RECORD.VISIT, &L3_ROW, VISIT.VISIT_REASON);
```

To do the same using the **SCROLL**.*scrollname* syntax:

```
&SOMEREASON = FetchValue(SCROLL.OWNER, &L1_ROW, SCROLL.PET,
&L2_ROW, SCROLL.VISIT, &L3_ROW, SCROLL.VISIT_REASON);
```

In PeopleTools 8, the object-oriented version of this is:

```
&SOMEREASON = &VISIT_SCROLL(&L3_ROW).VISIT.VISIT_REASON;
```

Using CurrentRowNumber

The CurrentRowNumber function returns the current row, as determined by the current context, for a specific scroll level in the active page. CurrentRowNumber is often used to determine a value for the *level1_row* and *level2_row* parameters in scroll path constructions. Because current row numbers are determined by the current context, CurrentRowNumber cannot determine a current row on a scroll level outside the current context (a scroll level below the level where the PeopleCode program is currently executing).

For example, you could use a statement like this to retrieve the value of a buffer field on level three of the PET_VISITS page, in a PeopleCode program executing on level two:

```
&VAL = FetchValue(RECORD.OWNER, CurrentRowNumber(1),
RECORD.PET, CurrentRowNumber(2), RECORD.VISIT, &TARGETROW,
VISIT_REASON);
```

Because the PeopleCode program is executing on level two, CurrentRowNumber can return values for levels one and two, but not three, because level three is outside of the current context and has no current row number.

Looping Through Scroll Levels

Component buffer functions are often used in For loops to loop through the rows on scroll levels below the level where the PeopleCode program is executing. The following loop, for example could be used in PeopleCode executing on a level two record field to loop through rows of data on level three:

```
For &I = 1 To ActiveRowCount(RECORD.OWNER,
CurrentRowNumber(1), RECORD.PET, CurrentRowNumber(2), RECORD.VISIT)
    &VAL = FetchValue(RECORD.OWNER, CurrentRowNumber(1),
RECORD.PET, CurrentRowNumber(2), RECORD.VISIT, &I, VISIT_REASON);
    If &VAL = "Fleas" Then
        /* do something about fleas */
    End-If;
End-For;
```

A similar construct may be used in accessing other level two or level one scroll areas, such as work scroll areas.

In these constructions, the ActiveRowCount function is often used to determine the upper bounds of the loop. When ActiveRowCount is used for this purpose, the loop goes through all of the active rows in the scroll (rows that have not been specified as deleted). If you use TotalRowCount to determine the upper bounds of the loop, the loop goes through all of the rows in the scroll area: first those that have not been specified as deleted, then those that have been specified as deleted.

See Also

Chapter 4, "Referencing Data in the Component Buffer," Structuring Scroll Path Syntax in PeopleTools 7.5, page 56

Chapter 4, "Referencing Data in the Component Buffer," Understanding Current Context, page 51

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," CurrentRowNumber

Chapter 5

Accessing the Data Buffer

This chapter provides overviews of data buffer access, data buffer class examples, and current context, and discusses how to:

- Access secondary component buffer data.
- Instantiate rowsets using non-component buffer data.

Understanding Data Buffer Access

This section discusses:

- Data buffer access.
- Access classes.
- Data buffer model and data access objects.

Data Buffer Access

In addition to the built-in functions you use to access the component buffer, classes of objects are available that provide access to structured data buffers using the PeopleCode object syntax.

The data buffers accessed by these classes are typically the component buffers that are loaded when you open a component. However, these classes may also be used to access data from general data buffers, loaded by an Application Engine program, a component interface, and so on.

The methods and properties of these classes provide functionality that is similar to what has been available using built-in functions. However, they also provide improved consistency, flexibility, and new functionality.

Access Classes

The four data buffer classes are: Rowset, Row, Record, and Field. These four classes are the foundation for accessing component buffer data through the new object syntax.

A field object, which is instantiated from the Field class, is a single instance of data within a record. It is based on a field definition.

A record object, which is instantiated from the Record class, is a single instance of a data within a row. It is based on a record definition. A record object consists of one to n fields.

A row object, which is instantiated from the Row class, is a single row of data that consists of one to n records of data. A single row in a component scroll area is a row. A row may have one to n child rowsets. For example, a row in a level two scroll area may have n level three child rowsets.

A rowset object is a data structure used to describe hierarchical data. It is made up of a collection of rows. A component scroll area is a rowset. You can also have a level zero rowset.

Data Buffer Model and Data Access Classes

The data model assumed by the data buffer classes is that of a PeopleTools component, where scroll bars or grids are used to describe a hierarchical, multiple-occurrence data structure. You can access these classes using dot notation.

The four data buffer classes relate to each other in a hierarchical manner. The main points to understand these relationships are:

- A record contains one or more fields.
- A row contains one or more records and zero or more child rowsets.
- A rowset contains one or more rows.

For component buffers, think of a rowset as a scroll area on a page that contains all of the data in that scroll area. A level zero rowset contains all the data for the entire component. You can use rowsets with application messages, file layouts, business interlinks, and other definitions in addition to components. A level zero rowset from a component buffer only contains one row: the keys that the user specifies to initiate that component. A level zero rowset from data that is not a component, such as a message or a file layout, might contain more than one level zero row.

The following is basic PeopleCode that traverses through a two-level component buffer using dot notation syntax. Level zero is based on record QA_INVEST_HDR, and level one is based on record QA_INVEST_LN.

```
Local Rowset &HDR_ROWSET, &LINE_ROWSET;
Local Record &HDR_REC, &LINE_REC;
&HDR_ROWSET = GetLevel0();

For &I = 1 to &HDR_ROWSET.RowCount
    &HDR_REC = &HDR_ROWSET(&I).QA_INVEST_HDR;
    &EMPLID = &HDR_REC.EMPLID.Value;
    &LINE_ROWSET = &HDR_ROWSET(&I).GetRowset(1);
    For &J = 1 to &LINE_ROWSET.RowCount
        &LINE_REC = &LINE_ROWSET(&J).QA_INVEST_LN;
        &LINE_SUM = &LINE_SUM + &LINE_REC.AMOUNT.Value;
    End-For;
End-For;
```

Each rowset is declared and instantiated. In general, your code is easier to read and maintain if you follow this practice.

Understanding Data Buffer Classes Examples

This section discusses:

- Employee Checklist page structure.
- Object creation examples.
- Data buffer hierarchy examples.
- Rowset examples.
- Hidden work scroll area example.

Employee Checklist Page Structure

Most of the examples in this section use the Employee Checklist page.

Employee Checklist

Schumacher,Simon

ID: 8001

*Checklist Date: 08/11/2000

Checklist: 000003

Repatriation Checklist

Responsible ID: 6602

Peppen,Jacques

Comment:

*Chklist Seq	*Chklist Itm	*Briefing Status	*Status Date	
100	000015	Briefing with Human Resources	Initiated	08/11/2000
200	000025	Repatriation Discussion	Initiated	08/11/2000
300	000029	Career/Placement discussion	Initiated	08/11/2000

Save

Return to Search


Employee Checklist page

This page has the following record structure:

Scroll Level	Associated Primary Record	Rowset and Variable Name
Level zero	PERSONAL_DATA	Level zero rowset: &RS0
Level one scroll area	EMPL_CHECKLIST	Level one rowset: &RS1

Scroll Level	Associated Primary Record	Rowset and Variable Name
Level one hidden work scroll area	CHECKLIST_ITEM	Level one rowset: &RS1H
Level two scroll area	EMPL_CHKLIST_ITM	Level two rowset: &RS2

Another way of looking at the structure of a component is to use the Structure view. All the scroll areas are labeled, and the primary record is associated with each:



EMPLOYEE_CHECKLIST structure

In the example, the visible level one scroll area also has only one row. That row is made up of the following records:

- EMPL_CHECKLIST
- DERIVED_HR
- CHECKLIST_TBL
- PERSONAL_DATA

You can see which records are associated with a scroll area by looking at the Order view for a page:

EMPLOYEE_CHECKLIST.ENG (Page)								
Page Designer		Order						
	Lv	Label	Type	Field	Record	Display Control	Related Field	
1	0	Frame	Frame			<input type="checkbox"/>	<input type="checkbox"/>	
2	0	Frame	Frame			<input type="checkbox"/>	<input type="checkbox"/>	
3	0	Frame	Frame			<input type="checkbox"/>	<input type="checkbox"/>	
4	0	Employee Name	Edit Box	NAME	PERSONAL_DATA	<input type="checkbox"/>	<input type="checkbox"/>	
5	0	ID	Edit Box	EMPLID	PERSONAL_DATA	<input type="checkbox"/>	<input type="checkbox"/>	
6	1	Checklist Item Tbl	Scroll Bar			<input type="checkbox"/>	<input type="checkbox"/>	
7	1	Checklist Sequen	Edit Box	CHECKLIST_SEQ	CHECKLIST_ITEM	<input type="checkbox"/>	<input type="checkbox"/>	
8	1	Scroll Bar 1	Scroll Bar			<input type="checkbox"/>	<input type="checkbox"/>	
9	1	Checklist Date	Edit Box	CHECKLIST_DT	EMPL_CHECKLIST	<input type="checkbox"/>	<input type="checkbox"/>	
10	1	derived_hr.effdt	Edit Box	EFFDT	DERIVED_HR	<input type="checkbox"/>	<input type="checkbox"/>	
11	1	Checklist	Edit Box	CHECKLIST_CD	EMPL_CHECKLIST	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
12	1	Checklist Descripti	Edit Box	DESCR	CHECKLIST_TBL	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
13	1	Responsible ID	Edit Box	RESPONSIBLE_I	EMPL_CHECKLIST	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
14	1	Responsible Nam	Edit Box	NAME	PERSONAL_DATA	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
15	1	Comment	Long Edit Box	COMMENTS	EMPL_CHECKLIST	<input type="checkbox"/>	<input type="checkbox"/>	
16	2	Scroll Bar 2	Scroll Bar			<input type="checkbox"/>	<input type="checkbox"/>	
17	2	Chklst Seq	Edit Box	CHECKLIST_SEQ	EMPL_CHKLST_ITM	<input type="checkbox"/>	<input type="checkbox"/>	
18	2	Chklst Itm	Edit Box	CHKLST_ITEM_C	EMPL_CHKLST_ITM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
19	2	Briefing Descriptio	Edit Box	DESCR	CHKLST_ITEM_TBL	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
20	2	Briefing Status	Drop Down List	BRIEFING_STAT	EMPL_CHKLST_ITM	<input type="checkbox"/>	<input type="checkbox"/>	

EMPLOYEE_CHECKLIST page Order view showing records

The level two rowset has three rows. Each row is made up of two records: the primary record, EMPL_CHKLST_ITM, and CHKLST_ITM_TBL, the record associated with the related display field DESCR. The following example shows the rowset:

The screenshot displays a web form titled "Employee Checklist". At the top, it shows the employee name "Schumacher, Simon" and ID "8001". Below this, there are input fields for "Checklist Date" (08/11/2000), "Checklist" (000003), and "Responsible ID" (6602), with a "Repatriation Checklist" label. A "Comment" text area is also present. The main part of the form is a table with four columns: "*Chklist Seq", "*Chklist itm", "*Briefing Status", and "*Status Date". The table contains three rows of data. The second row is highlighted with a black border. Labels on the left side of the form point to specific elements: "Level2 Rowset" points to the table, "Row2 for level2 rowset" points to the second row, and "Field" points to the first column of the table. At the bottom, there are "Save" and "Return to Search" buttons.

*Chklist Seq	*Chklist itm	*Briefing Status	*Status Date
100	000015	Briefing with Human Resources	Initiated 08/11/2000
200	000025	Repatriation Discussion	Initiated 08/11/2000
300	000029	Career/Placement discussion	Initiated 08/11/2000

EMPLOYEE_CHECKLIST rowsets and rows

Every record has fields associated with it, such as NAME, EMPLID and CHECKLIST_SEQ. These fields are associated with the record definitions; they are not the fields that appear on the page.

Object Creation Examples

When declaring variables, using the class with the same name as the data buffer access data type (rowset objects should be declared as type Rowset, field objects as type Field, and so on). Data buffer access class objects can be of type Local, Global, or Component.

The following declarations are assumed throughout the examples that follow:

```
Local Rowset &LEVEL0, &ROWSET;
Local Row &ROW;
Local Record &REC;
Local Field &FIELD;
```

Level Zero Access

The following code instantiates a rowset object, from the Rowset class, that references the level zero rowset, containing all the page data. It stores the object in the &LEVEL0 variable.

```
&LEVEL0 = GetLevel0();
```

The level zero rowset contains all the rows, rowsets, records, and fields underneath it.

If the level zero rowset is formed from component buffer data, then the level zero rowset has one row of data and that row contains all the child rowsets, which in turn contain rows of data that contain other child rowsets.

If the level zero rowset is formed from buffer data, such as from an application message, then the level zero rowset may contain more than one row of data. Each row of the level zero rowset contains all the child rowsets associated with that row, which in turn contain rows of data that contain other child rowsets.

Use a level zero rowset when you want an absolute path to a lower-level object or to do some processing on the entire data buffer. For example, suppose you load all new data into the component buffers and want to redraw the page. You could use the following code:

```
/* Do processing to reload Component Buffers */
&LEVEL0 = GetLevel0();
&LEVEL0.Refresh();
```

Rowset Object


The following code instantiates a rowset object that references the rowset that contains the currently running PeopleCode program:

```
&ROWSET = GetRowset();
```

You might later use the &ROWSET variable and the ActiveRowCount property to iterate over all the rows of the rowset, to access a specific row (using the GetRow method), or to hide a child rowset (by setting the Visible property).

The level one rowset contains all the level two rowsets. However, the level two rowsets can only be accessed using the different rows of the level one rowset. From the level zero or level one rowset, you can only access a level two rowset by using the level one rowset and the appropriate row.

For example, suppose your program is running on some field of row five of a level two scroll area, which is on row three of its level one scroll area. The resulting rowset contains all the rows of the level two scroll area that are under the row three of the level one scroll area. The rowset does not contain any data that is under any other level two scroll areas. The following diagram illustrates these results:



Level two rowset from level one row

A further illustration uses an example from the Employee Checklist page.

Suppose that one employee was associated with three different checklists: Foreign Loan Departure, Foreign Loan Arrival, and Foreign Loan Host. The checklist code field (CHECKLIST_CD) on the first level of the page drives the entries on the second level. Each row in the level one rowset produces a different level two rowset.

The Foreign Loan Departure checklist (000001) produces a checklist that contains such items as Briefing with Human Resources and Apply for Visas/Work permits, as shown in the following example:

Employee Checklist

Schumacher,Simon ID: 8001

*Checklist Date: 08/11/2000 Checklist: 000001 Foreign Loan Departure Chcklst

Responsible ID: 6602 Peppen,Jacques

Comment:

<Previous + 1 of 3 - Next>

*Chklist Seq	*Chklist Itm	*Briefing Status	*Status Date
100	000015 Briefing with Human Resources	Initiated	08/11/2000
200	000030 Apply for Visas/Work Permits	Initiated	08/11/2000
300	000009 Reconfirm Relocation Package	Initiated	08/11/2000
400	000001 Select moving/storage company	Initiated	08/11/2000

Save Return to Search

EMPLOYEE_CHECKLIST Foreign Loan Departure checklist

The Foreign Loan Arrival checklist (0000004) produces a checklist that contains items such as Register at Consulate and Open New Foreign Bank Accounts, as shown in the following example:

Employee Checklist

Schumacher,Simon

ID: 8001

*Checklist Date:

08/11/2000

Checklist:

000004

Foreign Loan Arrival Checklist

Responsible ID:

7705

Holt,Susan

Comment:

Previous

+

2 of 3

-

Next>

*Chklist Seq	*Chklist Itm	*Briefing Status	*Status Date
100	000022 Register at Consulate	Initiated	08/11/2000
200	000008 Open new foreign bank accounts	Initiated	08/11/2000
300	000018 Register children in school	Initiated	08/11/2000
400	000019 Join Newcomer's Club	Initiated	08/11/2000

Save

Return to Search

EMPLOYEE_CHECKLIST Foreign Load Arrival Checklist

Row Object

When you create a page, you put fields from different records onto the page. You can think of this as creating a type of pseudo-SQL join. The row returned from this pseudo-join is a row object.

For example, the first level scroll area of the EMPLOYEE_CHECKLIST page contains the following fields, associated with these records:

Field	Record
CHECKLIST_DT	EMPL_CHECKLIST
CHECKLIST_CD	EMPL_CHECKLIST
COMMENTS	EMPL_CHECKLIST
DESCR	CHECKLIST_TBL
NAME	PERSONAL_DATA

<i>Field</i>	<i>Record</i>
RESPONSIBLE_ID	EMPL_CHECKLIST

The pseudo-SQL join might look like this:

```
JOIN A.CHECKLIST_DT, A.CHECKLIST_CD, A.COMMENTS, B.DESCR, C.NAME, A.RESPONSIBLE_ID
FROM PS_EMPL_CHECKLIST A, PS_CHECKLIST_TBL B, PS_PERSONAL_DATA C, WHERE. . .
```

What goes into the Where clause is determined by the level zero of the page. For our example, the value is WHERE EMPLID=8001.

When the component is opened, data is loaded into the component buffers. Any row returned by the pseudo-SQL statement is a level one row object. The following table shows a returned row:

<i>CHECKLIST_DT</i>	<i>CHECKLIST_CD</i>	<i>COMMENTS</i>	<i>DESCR</i>	<i>NAME</i>	<i>RESPONSIBLE_ID</i>
12/03/98	000001		Foreign Loan Department Checklist	Peppen, Jacques	6602

Record Object

A record definition is a definition of what your underlying SQL database tables look like and how they process data. After you create record definitions, you build the underlying SQL tables that contain the application data that your users enter online in your production environment.

When you create a record object using the CreateRecord function, you are creating an area in the data buffers that has the same structure as the record definition, but no data.

When you instantiate a record object from the Record class using some variation of GetRecord, that record object references a single row of data in the SQL table.

Note. The data in the record that you retrieve is based on the row, which is analogous to setting keys to return a unique record.

The following code instantiates a record object for referencing the EMPL_CHECKLIST record of the specified row:

```
&REC = &ROW.GetRecord(RECORD.EMPL_CHECKLIST);
```

Using the short method, the following line of code is identical to the previous line:

```
&REC = &ROW.EMPL_CHECKLIST;
```

You might later use the &REC variable and the CopyFieldsTo property to copy all like-named fields from one record to another. In the following example, two row objects are created, the copy from row (COPYFRMROW) and the copy to row (COPYTROW). Using these rows, like-named fields are copied from CHECKLIST_ITEM to EMPL_CHKLIST_ITM.

```
For &I = 1 To &ROWSET1.ActiveRowCount
    &COPYFRMROW = &ROWSET1.GetRow(&I);
    &COPYTROW = &RS2.GetRow(&I);
    &COPYFRMROW.CHECKLIST_ITEM.CopyFieldsTo(&COPYTROW.EMPL_CHKLIST_ITM);
End-For;
```

A row may contain more than one record: in addition to the primary database record, you may have a related display record or a derived record. You can access these records as well. The level one rowset, &ROWSET1, is made up of many records. The following accesses two of them: EMPL_CHECKLIST and DERIVED_HR.

```
&REC1 = &ROW.EMPL_CHECKLIST;
&REC2 = &ROW.DERIVED_HR;
```

Field Object

The following instantiates a field object, from the Field class, that is used to access a specific field in the record:

```
&FIELD = &REC.GetField(FIELD.CHECKLIST_CD);
```

You might later use the *&FIELD* variable as a condition:

```
If ALL(&FIELD) Then
```

Here is another example:

```
If &FIELD.Value = "N" Then
```

Note. The data in the field that you retrieve is based on the record, which is in turn based on the row.

You can also set the value of a field. Using the GetField function does not create a copy of the data from the component buffer. Setting the value or a property of the field object sets the actual component buffer field or property.

See [Chapter 3, "Understanding Objects and Classes in PeopleCode," Assigning Objects, page 43](#).

In the following example, the type of field is verified, and the value is replaced with the tangent of that value if it is a number

```
If &FIELD.Type <> "NUMBER" Then
    /* do error recording */
Else
    &FIELD.Value = Tan(&FIELD.Value);
End-If;
```

Data Buffer Hierarchy Examples

Suppose you want to access the BRIEFING_STATUS field at level two of the following page:

Employee Checklist

Schumacher,Simon
ID: 8001

*Checklist Date: 08/11/2000
Checklist: 000003
Repatriation Checklist

Responsible ID: 6602
Peppen,Jacques

Comment:

*Chklist Seq	*Chklist Item	*Briefing Status	*Status Date
100	000015 Briefing with Human Resources	Initiated	08/11/2000
200	000025 Repatriation Discussion	Initiated	08/11/2000
300	000029 Career/Placement discussion	Initiated	08/11/2000

Save
Return to Search

EMPLOYEE_CHECKLIST repatriation checklist

First, determine where your code is running. For this example, the code is starting at a field on a record at level zero. However, you do not always have to start at level zero.

If you start with level zero, you must traverse the data hierarchy, through the level one rowset to the level two rowset, before you can access the record that contains the field.

Obtaining the Rowset

You first obtain the level zero rowset, which is the PERSONAL_DATA rowset. You do not need to know the name of the level zero rowset to access it:

```
&LEVEL0 = GetLevel0();
```

Obtaining Rows

The next object to get is a row. As the following code is working with data that is loaded from a page, only one row is at level zero. However, if you have rowsets that are populated with data that is not based on component buffers (for example, an application message), you may have more than one row at level zero.

```
&LEVEL0_ROW = &LEVEL0(1);
```

Obtaining Child Rowsets

To obtain the level two rowset, traverse through the level one rowset first. Therefore, the next object to get is the level one rowset, as shown in the following example:

```
&LEVEL1 = &LEVEL0_ROW.GetRowset( SCROLL.EMPL_CHECKLIST );
```

Obtaining Subsequent Rows

If you are traversing a page, obtain the appropriate row after you get a rowset. To process all the rows of the rowset, set this functionality up in a loop, as shown in the following example:

```
For &I = 1 to &LEVEL1.ActiveRowCount
    &LEVEL1_ROW = &LEVEL1(&I);
    . . .
End-For;
```

Obtaining Subsequent Rowsets and Rows

Traverse another level in the page structure to access the second level rowset, and then use a loop to access the rows in the level two rowset.

Because we are processing all the rows at level one, we are just adding code to the previous For loop. As we process through all the rows at level two, we are adding a second For loop. The new code is in bold in the following example:

```
For &I = 1 to &LEVEL1.ActiveRowCount
    &LEVEL1_ROW = &LEVEL1(&I);
    &LEVEL2 = &LEVEL1_ROW.GetRowset( SCROLL.
EMPL_CHKLIST_ITM);
    For &J = 1 to &LEVEL2.ActiveRowCount
        &LEVEL2_ROW = &LEVEL2(&J);
        . . .
    End-For;
End-For;
```

Obtaining Records

A row always contains a record, and it may contain only a child rowset, depending on how your page is set up. GetRecord is the default method for a row, so all you have to specify is the record name.

Because we are processing all the rows at level two, we just add code to the For loops of the previous example. The new code is in bold:

```
For &I = 1 to &LEVEL1.ActiveRowCount
    &LEVEL1_ROW = &LEVEL1(&I);
    &LEVEL2 = &LEVEL1_ROW.GetRowset( SCROLL.EMPL_CHKLIST_ITM );
    For &J = 1 to &LEVEL2.ActiveRowCount
        &LEVEL2_ROW = &LEVEL2(&J);
        &RECORD = &LEVEL2_ROW.EMPL_CHKLIST_ITM;
        . . .
    End-For;
End-For;
```

Obtaining Fields

Records are made up of fields. GetField is the default method for a record, so all you have to specify is the field name.

Because we are processing all the rows at the level one, we are just adding code to the For loops of the previous example. The new code is in bold:

```
For &I = 1 to &LEVEL1.ActiveRowCount
    &LEVEL1_ROW = &LEVEL1(&I);
    &LEVEL2 = &LEVEL1_ROW.GetRowset(SCROLL.EMPL_CHKLIST_ITM);
    For &J = 1 to &LEVEL2.ActiveRowCount
        &LEVEL2_ROW = &LEVEL2(&J);
        &RECORD = &LEVEL2_ROW.EMPL_CHKLIST_ITM;
        &FIELD = &RECORD.BRIEFING_STATUS;
        /* Do processing */
    End-For;
End-For;
```

Using Shortcuts

The previous code is the long way of accessing this field. The following example uses shortcuts to access the field in one line of code. The following code assumes all rows are level one:

Rowset

Row

Rowset

Row

Rowset

Row

Record

Field

```
&FIELD=Get Level0()(1).EMPL_CHECKLIST(1).EMPL_CHKLIST_ITM(1).EMPL_CHKLIST_ITM.BRIEFING_STATUS;
```

Rowset example

Here's another method of expressing the code:

Object Type	Code
Rowset	&LEVEL0 = GetLevel0();
Row	&LEVEL0_ROW = &LEVEL0(1);
Rowset	&LEVEL1 = &LEVEL0_ROW.GetRowset(SCROLL.EMPL_CHECKLIST);
	For &I = 1 to &LEVEL1.ActiveRowCount
Row	&LEVEL1_ROW = &LEVEL1(&I);
Rowset	&LEVEL2 = &LEVEL1_ROW.GetRowset(SCROLL.EMPL_CHKLIST_ITM);
	For &J = 1 to &LEVEL2.ActiveRowCount
Row	&LEVEL2_ROW = &LEVEL2(&J);
Record	&RECORD = &LEVEL2_ROW.EMPL_CHKLIST_ITM;

<i>Object Type</i>	<i>Code</i>
Field	<code>&FIELD = &RECORD.BRIEFING_STATUS;</code>
	<code>/* Do processing */</code>
	<code>End-For;</code>
	<code>End-For;</code>

Rowset Examples

The following code example traverses up to four levels of rowsets and could easily be modified to do more. This example only processes the first record in every rowset. To process every record, set up another For loop (For &R = 1 to &LEVELX.RECORDCOUNT, and so on). Notice the use of the ChildCount function (to process all children rowsets within a rowset), ActiveRowCount, IsChanged, and dot notation.

In the following example, ellipses indicate where application-specific code should go.

```

&Level0_ROWSET = GetLevel0();
For &A0 = 1 To &Level0_ROWSET.ActiveRowCount

    ...

    /*****
    /* Process Level 1 Records */
    /*-----*/
    If &Level0_ROWSET(&A0).ChildCount > 0 Then
    For &B1 = 1 To &Level0_ROWSET(&A0).ChildCount
        &LEVEL1_ROWSET = &Level0_ROWSET(&A0).GetRowset(&B1);
        For &A1 = 1 To &LEVEL1_ROWSET.ActiveRowCount
            If &LEVEL1_ROWSET(&A1).GetRecord(1).IsChanged Then

                ...

                /*****
                /* Process Level 2 Records */
                /*-----*/
                If &LEVEL1_ROWSET(&A1).ChildCount > 0 Then
                For &B2 = 1 To &LEVEL1_ROWSET(&A1).ChildCount
                    &LEVEL2_ROWSET = &LEVEL1_ROWSET(&A1).GetRowset(&B2);
                    For &A2 = 1 To &LEVEL2_ROWSET.ActiveRowCount
                        If &LEVEL2_ROWSET(&A2).GetRecord(1).IsChanged Then

                            ...

                            /*****
                            /* Process Level 3 Records */
                            /*-----*/
                            If &LEVEL2_ROWSET(&A2).ChildCount > 0 Then
                            For &B3 = 1 To &LEVEL1_ROWSET(&A2).ChildCount
                                &LEVEL3_ROWSET = &LEVEL2_ROWSET(&A2).GetRowset(&B3);
                                For &A3 = 1 To &LEVEL3_ROWSET.ActiveRowCount
                                    If &LEVEL3_ROWSET(&A3).GetRecord(1).IsChanged Then

                                        ...

                                        End-If; /* A3 - IsChanged */
                                        End-For; /* A3 - Loop */
                                    End-For; /* B3 - Loop */
                                    End-If; /* A2 - ChildCount > 0 */
                                /*-----*/
                            /* End of Process Level 3 Records */
                            /*****

                                End-If; /* A2 - IsChanged */
                                End-For; /* A2 - Loop */
                                End-For; /* B2 - Loop */
                                End-If; /* A1 - ChildCount > 0 */
                            /*-----*/
                            /* End of Process Level 2 Records */
                            /*****

                                End-If; /* A1 - IsChanged */
                                End-For; /* A1 - Loop */
                                End-For; /* B1 - Loop */
                                End-If; /* A0 - ChildCount > 0 */
                            /*-----*/
                            /* End of Process Level 1 Records */
                            /*****

                                End-For; /* A0 - Loop */

```

Hidden Work Scroll Example

In the FieldChange event for the CHECKLIST_CD field on the EMPL_CHECKLIST record, a PeopleCode program does the following:

1. Flushes the rowset and hidden work scroll area.
2. Performs a Select statement on the hidden work scroll area based on the value of the CHECKLIST_CD field and the effective date.
3. Clears the level two scroll area.
4. Copies like-named fields from the hidden work scroll area to the level two scroll area.

The following example shows how to do this using built-in functions.

```
&CURRENT_ROW_L1 = CurrentRowNumber(1);

&ACTIVE_ROW_L2 = ActiveRowCount(RECORD.EMPL_CHECKLIST,
&CURRENT_ROW_L1, RECORD.EMPL_CHKLIST_ITM);

If All(CHECKLIST_CD) Then
    ScrollFlush(RECORD.CHECKLIST_ITEM);
    ScrollSelect(1, RECORD.CHECKLIST_ITEM, RECORD.CHECKLIST_ITEM,
"Where Checklist_Cd = :1 and EffDt = (Select Max(EffDt) From
PS_Checklist_Item Where Checklist_Cd = :2)",
CHECKLIST_CD, CHECKLIST_CD);

    &FOUNDDOC = FetchValue(CHECKLIST_ITEM.CHKLIST_ITEM_CD, 1);
    &SELECT_ROW = ActiveRowCount(RECORD.CHECKLIST_ITEM);

    For &I = 1 To &ACTIVE_ROW_L2
        DeleteRow(RECORD.EMPL_CHECKLIST, &CURRENT_ROW_L1, RECORD.EMPL_CHKLIST_ITM, 1);
    End-For;

    If All(&FOUNDDOC) Then
        For &I = 1 To &SELECT_ROW
            CopyFields(1, RECORD.CHECKLIST_ITEM, &I, 2,
RECORD.EMPL_CHECKLIST, &CURRENT_ROW_L1, RECORD.EMPL_CHKLIST_ITM, &I);
            If &I <> &SELECT_ROW Then
                InsertRow(RECORD.EMPL_CHECKLIST, &CURRENT_ROW_L1,
RECORD.EMPL_CHKLIST_ITM, &I);
            End-If;
        End-For;
    End-If;
End-If;
```

The following example performs the same function as the previous code, only it uses the data buffer classes:

1. Flushes the rowset and hidden work scroll area (&RS1H).
2. Performs a Select statement on &RS1H based on the value of the CHECKLIST_CD field and the effective date.
3. Clears the level two rowset (&RS2).

4. Copies like-named fields from &RS1H to &RS1.

```

Local Rowset &RS0, &RS1, &RS2, &RS1H;

&RS0 = GetLevel0();
&RS1 = GetRowset();
&RS2 = GetRowset(SCROLL.EMPL_CHKLIST_ITM);
&RS1H = &RS0.GetRow(1).GetRowset(SCROLL.CHECKLIST_ITEM);

&MYFIELD = CHECKLIST_CD;

If All(&MYFIELD) Then
    &RS1H.Flush();
    &RS1H.Select(RECORD.CHECKLIST_ITEM, "where Checklist_CD = :1
and EffDt = (Select Max(EffDt) from PS_CHECKLIST_ITEM
Where CheckList_CD = :2)", CHECKLIST_CD, CHECKLIST_CD);

    For &I = 1 To &RS2.ActiveRowCount
        &RS2.DeleteRow(1);
    End-For;

&FOUND = &RS1H.GetCurrEffRow().CHECKLIST_ITEM. CHKLST_ITEM_CD.Value;


If All(&FOUND) Then
    For &I = 1 To &RS1H.ActiveRowCount
        &COPYFRMROW = &RS1H.getrow(&I);
        &COPYTROW = &RS2.getrow(&I);
        &COPYFRMROW.CHECKLIST_ITEM.CopyFieldsTo(&COPYTROW.EMPL_CHKLIST_ITM);
        If &I <> &RS1H.ActiveRowCount Then
            &RS2.InsertRow(&I);
        End-If;
    End-For;
End-If;
End-If;

```

Understanding Current Context

Most PeopleCode programs run in a current context. The current context determines which buffer fields can be contextually referenced from PeopleCode, and which row of data is the current row on each scroll level at the time a PeopleCode program is running.

The current context for the data buffer access classes is similar to the current context for accessing the component buffer, as shown in the following diagram:



Current context for rowsets

In this example, a PeopleCode program is running in a buffer field on the second row of the level one rowset. The following code returns a row object for the second row of the level one rowset, because that is the row that is the current context.

```
Local Row &ROW
&ROW = GetRow();
```

The following code returns the B2 level two rowset because of the current context:

```
Local Rowset &ROWSET2
&ROWSET2 = &ROW.GetRowset(SCROLL.EMPL_CHKLIST_ITM);
```

This code does not return either the C2 or the A2 rowsets. It returns only the rowset associated with the second row of the level one rowset.

Creating Records or Rowsets and Current Context

When you instantiate a record object using the `CreateRecord` function, you are only creating an area in the data buffers that has the same structure as the record definition. It does not contain any data. This record object does not have a parent rowset and is not associated with a row. It is a freestanding record object and, therefore, is not considered part of the current context.

The same concept applies when you instantiate a rowset object using the `CreateRowset` function. You are only creating an area in the data buffers that has the same structure as the records or rowset that the new rowset is based on. The rowset does not contain any data. This type of rowset does not have a parent rowset or row.

See Also

Chapter 4, "Referencing Data in the Component Buffer," Specifying Data with Contextual References, page 51

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," `CreateRecord`

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," `CreateRowset`

Accessing Secondary Component Buffer Data

When a secondary page is run, the data for its buffers is copied from the parent component to a buffer structure for the secondary page. That is, two copies of this data are made. The data buffer classes give access to both of these copies of the data. Direct field references (*recname.fieldname*) always use the current context to determine which value to access. So, in general, when using a secondary page, make sure that references are based on the secondary page.

Instantiating Rowsets Using Non-Component Buffer Data

Both the application message and the file layout technologies represent hierarchical data, and both use the rowset, row, record, and field hierarchy. Though you use different methods to instantiate a rowset object for this data, you still use the same rowset, row, record, and field methods and properties to manipulate the data. (Any exceptions are marked in the documentation.)

To instantiate a rowset for a message:

```
&MSG = CreateMessage(OPERATION.EMPLOYEE_DATA);  
&MYROWSET = &MSG.GetRowset();
```

To instantiate a rowset for a file layout:

```
&MYFILE = GetFile(&SOMENAME, "R");  
  
If &MYFILE.IsOpen Then  
    &MYFILE.SetFileLayout(FILELAYOUT.SOMELAYOUT);  
    &MYROWSET = &MYFILE.ReadRowset();  
End-if;
```

In an Application Engine program, the default state record is considered the primary record and the main record in context. You can access the default state record using the following:

```
&STATERECORD = GetRecord();
```

If you have more than one state record associated with an Application Engine program, you can access them the same way you would access other, nonprimary data records, by specifying the record name. For example:

```
&ALTSTATE = GetRecord(RECORD.AE_STATE_ALT);
```

See Also

[Chapter 8, "Using Methods and Built-In Functions," Using Standalone Rowsets, page 174](#)

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Integration Broker, "Managing Messages"

Enterprise PeopleTools 8.50 PeopleBook: Application Engine, "Using Meta-SQL and PeopleCode"

Chapter 6

PeopleCode and the Component Processor

This chapter provides an overview of the Component Processor and discusses:

- Events outside the Component Processor flow.
- PeopleCode program triggers.
- Component Processor behavior.
- Processing sequences.
- PeopleSoft Pure Internet Architecture processing considerations.
- Deferred processing mode.
- PeopleCode events.
- PeopleCode execution in pages with multiple scroll areas.

Understanding the Component Processor

The Component Processor is the PeopleTools runtime engine that controls processing of an application from the time that a user requests a component from an application menu until the database is updated and processing of the component is complete.

Events Outside the Component Processor Flow

An Application Engine program can have a PeopleCode program as an action. Though the right-hand drop-down list box on the PeopleCode Editor window displays the text *OnExecute*, the PeopleCode program really is not an event. Any PeopleCode contained in an Application Engine action is executed only when the action is executed.

A component interface can have user-defined methods associated with it. These methods are not part of any processor flow; they are called as needed by the program executing the component interface.

Security has a signon event during signon. This is actually PeopleCode programs on a record field that you have specified in setting up security.

Though application packages have a right-hand drop-down list box on the PeopleCode Editor window that displays the text *OnExecute*, this is not an event. Any PeopleCode contained in the application class is only executed when called explicitly in a PeopleCode program.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Component Interface Classes"

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Application Classes"

Enterprise PeopleTools 8.50 PeopleBook: Application Engine, "Creating Application Engine Programs," Specifying PeopleCode Actions

Enterprise PeopleTools 8.50 PeopleBook: Security Administration, "Understanding PeopleSoft Security"

PeopleCode Program Triggers

This section provides an overview of PeopleCode program triggers and discusses how to:

- Access PeopleCode programs.
- Associate execution order of events and PeopleCode.

Understanding PeopleCode Program Triggers

PeopleCode can be associated with a PeopleCode record field, a component record, and many other items. PeopleCode events are initiated at particular times, in particular sequences, during the course of the Component Processor's flow of execution. When an event is initiated, it triggers PeopleCode programs on specific objects.

The following items have events that are part of the Component Processor flow:

<i>Items</i>	<i>Event Triggers</i>
Menu items	Programs associated with the menu item
Component record fields	Programs on specific rows of data
Component records	Programs on specific rows of data
Components	Programs associated with the component
Pages	Programs associated with the page

<i>Items</i>	<i>Event Triggers</i>
Record fields	Programs on specific rows of data

Suppose a user changes the data in a page field, and then presses Tab to move out of the field. This user action initiates the FieldEdit PeopleCode event. The FieldEdit event affects only the field and row where the change took place. If a FieldEdit PeopleCode program is associated with that record field, the program is executed once.

If you have two FieldEdit PeopleCode programs, one associated with the record field and a second associated with the component record field, both programs execute, but only on the specific field and row of data. The FieldEdit PeopleCode program associated with the first record field is initiated first, and then the FieldEdit PeopleCode program associated with the first component record field is initiated.

By contrast, suppose a user has opened a component for updating. As part of building the component, the Component Processor initiates the RowInit event. This event triggers RowInit PeopleCode programs on every record field on every row of data in the component. In a scroll area with multiple rows of data, every RowInit PeopleCode program is executed once for each row.

In addition, if you have RowInit PeopleCode associated with both the record field and the component record, both programs are executed against every record field on every row of data in the component. The RowInit PeopleCode program associated with the first record field is initiated first, and then the RowInit PeopleCode program associated with the first component record is initiated. If you set the value of a field with the record field RowInit PeopleCode, and then reset the field with the component record RowInit PeopleCode, the second value appears to the user.

When you develop with PeopleCode, you must consider when and where your programs are triggered during execution of the Component Processor flow.

This section discusses how to:

- Access PeopleCode programs.
- Understand the execution order of events and PeopleCode.

See Also

Chapter 6, "PeopleCode and the Component Processor," Associating Execution Order of Events and PeopleCode, page 93

Accessing PeopleCode Programs

Every PeopleCode program is associated with a PeopleCode event and is often referred to by that name, such as RowInit PeopleCode or FieldChange PeopleCode. These programs are accessible from, and associated with, different items. The following table lists items and associated events.

Note.

During search processing in update modes or add mode, the SearchInit and SearchSave events (in the Component Record column of the table) are available only for the search record associated with a component.

<i>Record Field Events</i>	<i>Component Record Field Events</i>	<i>Component Record Events</i>	<i>Component Events</i>	<i>Page Events</i>	<i>Menu Events</i>
FieldChange FieldDefault FieldEdit FieldFormula PrePopup RowDelete RowInit RowInsert RowSelect SaveEdit SavePostChg SavePreChg SearchInit SearchSave Workflow	FieldChange FieldDefault FieldEdit PrePopup	RowDelete RowInit RowInsert RowSelect SaveEdit SavePostChg SavePreChg SeachInit SearchSave	PostBuild PreBuild SavePostChg SavePreChg Workflow	Activate	ItemSelected

The following table lists types of PeopleCode programs and where to access them in PeopleSoft Application Designer.

<i>PeopleCode Programs</i>	<i>Location in PeopleSoft Application Designer</i>
Record field	Record definitions and page definitions
Component record field, component record, and component	Component definitions
Menu item	Menu definitions
Page field	Page definitions

Associating Execution Order of Events and PeopleCode

In PeopleSoft, the component is the representation of a transaction. Therefore, any PeopleCode that is associated with a transaction should be in events associated with some level of the component. Code that should be executed every time a field is edited should be at the record field level. If you associate code with the correct transaction, you do not have to check for the component that is issuing it (such as surrounding your code with dozens of `If %Component =` statements). Records are more reusable, and code is more maintainable.

For example, if you have start and end dates for a course, you would always want to make sure that the end date was after the start date. Your program to check the dates would go on the SaveEdit at the record field level.


All similarly named component events are initiated after the like-named record event. The PeopleCode program associated with the record field event is initiated first, and then the PeopleCode program associated with the like-named component event is initiated. If you set the value of a field with the record field PeopleCode, and then reset the field with like-named component PeopleCode, the second value is displayed to the user.

Events After Field Changes

The following events occur after a user changes a field:

```
Record.recordA.fieldA.FieldEdit -> Component.recordA.fieldA.FieldEdit ->
Record.recordB.fieldB.FieldEdit -> Component.recordB.fieldB.FieldEdit ->
Record.recordA.fieldA.FieldChange -> Component.recordA.fieldA.FieldChange ->
Record.recordB.fieldB.FieldChange -> Component.recordB.fieldB.FieldChange ->
```

The following diagram shows the event flow:



Flow of events and PeopleCode programs after a user changes a field

Events After User Saves

The following events occur after a user saves:

```
Record.recordA.fieldA.SaveEdit ->
Record.recordA.fieldB.SaveEdit ->
Record.recordA.fieldC.SaveEdit ->
Component.recordA.SaveEdit

Record.recordB.fieldA.SaveEdit ->
Record.recordB.fieldB.SaveEdit ->
Record.recordB.fieldC.SaveEdit ->
Component.recordB.SaveEdit

Record.recordA.fieldA.SavePreChange ->
Record.recordA.fieldB.SavePreChange ->
Record.recordA.fieldC.SavePreChange ->
Component.recordA.SavePreChange


Record.recordB.fieldA.SavePreChange ->
Record.recordB.fieldB.SavePreChange ->
Record.recordB.fieldC.SavePreChange ->
Component.recordB.SavePreChange

Record.recordA.fieldA.WorkFlow ->
Record.recordB.fieldB.WorkFlow ->
Record.reocrdC.fieldC.WorkFlow
Component.Workflow

Record.recordA.fieldA.SavePostChange ->
Record.recordA.fieldB.SavePostChange ->
Record.recordA.fieldC.SavePostChange ->
Component.recordA.SavePostChange

Record.recordB.fieldA.SavePostChange ->
Component.recordB.SavePostChange
Component.SavePostChange
```

The following diagram shows the event flow:



Flow of PeopleCode programs after SavePostChange event

Note. SaveEdit does not fire for deleted rows, but SavePreChange, Workflow, and SavePostChange do.

Component Processor Behavior

This section discusses:

- Component Processor behavior from page start to page display.
- Component Processor behavior following user actions in the component.

Note. Components behave differently when run in deferred mode .

See Also

Chapter 6, "PeopleCode and the Component Processor," Deferred Processing Mode, page 127


Chapter 6, "PeopleCode and the Component Processor," Processing Sequences, page 100

Component Processor Behavior from Page Start to Page Display

Before a user selects a component, the system is in reset state, in which no component is displayed. The Component Processor flow of execution begins when a user selects a component from a PeopleSoft menu. The Component Processor then:

1. Performs search processing, in which it obtains and saves search key values for the component.
2. Retrieves from the database server any data needed to build the component.
3. Builds the component, creating buffers for the component data.
4. Performs any additional processing for the component or the page.
5. Displays the component and waits for user action.

The following flowchart shows the flow of execution at a high level:



Processing up to Page Display

Component Behavior Following User Actions in the Component

After a component is built and displayed, the Component Processor can respond to a number of possible user actions. The following table lists the user actions and briefly describes the resulting processing:

See [Chapter 6, "PeopleCode and the Component Processor," Processing Sequences, page 100.](#)

<i>User Action</i>	<i>Description</i>
Row Insert Processing	<p>When a user requests a row insert, the Component Processor adds a row of data in the active scroll area, then displays the page again and waits for another action.</p> <p>See Chapter 6, "PeopleCode and the Component Processor," Row Insert Processing, page 119.</p>
Row Delete Processing	<p>When a user requests a row delete, the Component Processor flags the current row as deleted, then displays the page again and waits for another action.</p> <p>See Chapter 6, "PeopleCode and the Component Processor," Row Delete Processing, page 121.</p>

<i>User Action</i>	<i>Description</i>
Field Modification	<p>If a user edits a page field, then leaves the field, the Component Processor performs standard edits (such as checking the data type and checking for values out of range). If the contents of the field do not pass the standard system edits, the Component Processor redisplay the page with an error or warning message and changes the field's color to the system color for field edit errors, usually red. Until the user corrects the error, the Component Processor does not let the user save changes or navigate to another field. If the contents of the field pass the standard system edits, the system redisplay the page and waits for further action.</p> <p>See Chapter 6, "PeopleCode and the Component Processor," Field Modification, page 116.</p>
Prompts	<p>If a user clicks the prompt icon next to a field, a list of values for the prompt field appears. If the Allow Search Events for Prompt Dialogs checkbox is selected in the record field properties for the search key, the SearchInit event will trigger before the prompt dialog appears. If the user clicks the Look Up button the SearchSave event will trigger.</p> <p>If the end-user clicks the detail button next to a date field, a calendar appears.</p> <p>If the user clicks Return To Search, or presses Alt+2, a search page appears, enabling the user to enter an alternate search key or partial value.</p> <p>See Chapter 6, "PeopleCode and the Component Processor," Prompts, page 123 and Chapter 6, "PeopleCode and the Component Processor," Search Processing in Update Modes, page 104.</p>
Pop-up Menu Display	<p>If a user clicks the pop-up icon next to a field, a pop-up menu appears. This can be a default pop-up menu or one that has been defined by the developer. If the user clicks the pop-up icon at the bottom of the page, the pop-up menu for the page appears.</p> <p>See Chapter 6, "PeopleCode and the Component Processor," Pop-Up Menu Display, page 124.</p>
ItemSelected Processing	<p>A user can select an item from a pop-up menu to execute a command.</p> <p>See Chapter 6, "PeopleCode and the Component Processor," Selected Item Processing, page 124.</p>

<i>User Action</i>	<i>Description</i>
Push Button	A user can click a button to execute a command. <u>See Chapter 6, "PeopleCode and the Component Processor," Buttons, page 123.</u>
Save Processing	A user can direct the system to save a component by clicking Save or by pressing Alt+1. If any component data has been modified, the system also prompts the user to save a component when the Next or List button is clicked, or when a new action or component is selected. The Component Processor first validates the data in the component, and then updates the database with the changed component data. After the update, a SQL Commit command finalizes the changes. <u>See Chapter 6, "PeopleCode and the Component Processor," Save Processing, page 125.</u>


Processing Sequences

This section presents an overview of flow charts and discusses:

- Default processing.
- Search processing in update mode.
- Search processing in add mode.
- Component build processing in update mode.
- Row select processing.
- Component build processing in add mode.
- Field modification.
- Row insert processing.
- Row delete processing.
- Buttons.
- Prompts.
- Pop-up menu display.
- Selected item processing.
- Save processing.

Flow Charts


Actions and PeopleCode events can occur in various sequences within the Component Processor's flow of execution. Flow charts represent each sequence. In a flow chart, different shapes and colors represent different concepts.




Blue rectangles represent actions taken by the system.



Dark rhomboids represent branches (decision points) in the logic.



Dark ellipses represent PeopleCode events.



Light ellipses are subprocesses.

Most processing sequences correspond to high-level component processor behaviors. However, two important subsequences occur only in the context of a larger sequence. These subsequences are:

- Default processing, which occurs in a number of different contexts.
- Row select processing, which most commonly occurs as a part of component build in any of the update action modes.

Row select processing also occurs when a ScrollSelect or related function is executed to load data into a scroll area.

See [Chapter 6, "PeopleCode and the Component Processor," Component Processor Behavior, page 96](#); [Chapter 6, "PeopleCode and the Component Processor," Default Processing, page 101](#) and [Chapter 6, "PeopleCode and the Component Processor," Row Select Processing, page 112](#).

Note. Variations may occur in processing sequences, particularly when a PeopleCode function within a processing sequence initiates another processing sequence. For example, if a row of data is inserted or deleted programmatically during the component build sequence, a row insert or row delete sequence is initiated. Also note that components that run in deferred mode behave differently.

See [Chapter 6, "PeopleCode and the Component Processor," Deferred Processing Mode, page 127](#).

Default Processing

In default processing, any blank fields in the component are set to their default values. You can specify the default value either in the record field properties or in FieldDefault PeopleCode. If no default value is specified, the field is left blank.

Note. In PeopleSoft Pure Internet Architecture, if a user changes a field, but there is nothing to cause a trip to the server on that field, default processing and FieldFormula PeopleCode do not run. They only run when another event causes a trip to the server.

Default processing is relatively complex. The following two sections describe how default processing works on the level of the individual field, and how default processing works in the broader context of the component.


Field-Level Default Processing

During default processing, the Component Processor examines all fields in all rows of the component. On each field, it performs the following:

1. If the field is set to NULL (blank) for a character field, or set to 0 for a numeric field, the Component Processor sets the field to any default value specified in the record field properties for that field.
2. If no default value for the field is defined in the record field properties, then the Component Processor initiates the FieldDefault event, which triggers any FieldDefault PeopleCode associated with the record field or the component record field.
3. If an error or warning executes in any FieldDefault PeopleCode, a runtime error occurs.

Important! Avoid using error and warning statements in FieldDefault PeopleCode.

The following flowchart shows this logic:



Field-level default sequence flow

Default Processing on Component Level

Under normal circumstances, default processing in a component is relatively simple: each field on each row of data undergoes field-level default processing. For typical development tasks, this is all you need to be concerned with. However, the complete context of default processing is somewhat more complex.

See [Chapter 6, "PeopleCode and the Component Processor," Default Processing, page 101.](#)

During component-level default processing, the Component Processor performs these tasks:

1. Field-level default processing is performed on all fields on all rows of data in the component.
2. If any field is still blank and any other field in the component has changed, field-level default processing may be repeated, in case a condition changed that causes default processing to now assign a value to something that was previously left blank.
3. The FieldFormula Event is initiated on all fields on all rows of data in the component.


This PeopleCode event is often used for FUNCLIB_ (function library) record definitions to store shared functions, so normally no PeopleCode programs execute.

4. If the FieldFormula Event changed anything, field-level default processing is performed again, in case FieldFormula PeopleCode changed a field value to blank, or changed something that causes default processing to now assign a value to a field that was previously left blank.

Because there should not be any FieldFormula PeopleCode, this is unlikely to affect the development process or performance.

5. If any field is still blank and any other field in the component has changed, field-level default processing is repeated.

The following flowchart shows this logic:



Default processing on component level

Search Processing in Update Modes

If a user selects any of the update action modes (Update, Update/Display All, or Correction), the Component Processor begins update mode search processing, which includes the following steps:

1. The SearchInit PeopleCode event is initiated, which triggers any SearchInit PeopleCode associated with the record field or the component search record, on the keys or alternate search keys in the component search record.

This enables you to control the search page field values or the search page appearance programmatically, or to perform other processing prior to the appearance of the search page.

Note. Set the search record for the component in the component properties.

For example, the following program in SearchInit PeopleCode on the component search key record field EMPLID sets the search key page field to the user's employee ID, makes the page field unavailable for entry, and enables the user to modify the user's own data in the component:

```
EMPLID = %EmployeeId;  
&Field = GetField(EMPLID).Enabled = False;  
AllowEmplIdChg(True);
```

Note. Generally, the system search processing displays the search page. You can use the SearchInit event, and the SetSearchDialogBehavior function, to set the behavior of the search page before it is displayed. If SetSearchDialogBehavior is set to *Force display*, the dialog box is displayed even if all required keys have been provided. You can also set SetSearchDialogBehavior to *skip if possible*. In addition, you can force search processing to always occur by selecting Force Search Processing in the component definition properties in PeopleSoft Application Designer.

2. The search page and prompt list appear, in which the user can enter search keys or select an advanced search to enter alternate search keys.

Note. Normally, the values in the search page are not set to default values. However, if the SearchDefault function was executed in SearchInit PeopleCode for any of the search key or alternate search fields, those fields in the dialog box are set to their system default values. No other default processing occurs (that is, the FieldDefault event is not initiated).

3. The user enters a value or partial value in the search page, and then clicks Search.

4. The SearchSave PeopleCode event is initiated, which triggers any SearchSave PeopleCode associated with the record field or the component search record, on the search keys or alternate search keys in the search record.

This enables you to validate the user entry in the search page by testing the value in the search record field in PeopleCode and, if necessary, issuing an error or warning. If an error is executed in SearchSave, the user is sent back to the search page. If a warning is executed, the user can click OK to continue or click Cancel to return to the search page and enter new values.

If partial values are entered, such that the Component Processor can select multiple rows, then the prompt list dialog box is filled, and the user can select a value. If key values from the search page are blank, or if the system cannot select any data based on the user entry in the search page, the system displays a message and redisplay the search page. If the values entered produce a unique value, the prompt list is not filled. Instead, the user is taken directly to the page.


Note. Normally, no system edits are applied when the user changes a field in the search page. However, if the SearchEdit property is executed for specific search page fields in SearchInit PeopleCode, the system edits are applied to those fields after the user changes a field and either leaves the field or clicks Search. In addition, the SearchEdit property can also be set in metadata for the record field definition.

If the user entry in the field fails the system edits, the system displays a message, highlights the field in question, and returns the user to the dialog box. The FieldEdit and SaveEdit PeopleCode events are not initiated. The SearchSave event is not initiated after values are selected from the search list. To validate data entered in the search page, use the Component PreBuild event.

5. The Component Processor buffers the search key values.

If the user then opens another component while this component is active, the Component Processor uses the same search key values and bypasses the search page.

The following flowchart shows this logic. (It does not show the effects of executing the SearchDefault and SearchEdit Field class properties.)



Search processing logic in update mode

Note. You can use the `IsSearchDialog` built-in function to create PeopleCode that runs only during search processing. To create processes that run only in a specific action mode, use the `%Mode` system variable. This could be useful in code that is part of a library function and that is invoked in places other than from the search page. It could also be used in PeopleCode associated with a record field that appears in pages and in the search page.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," SetSearchDialogBehavior

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Field Class," SearchDefault

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "System Variables," %Mode

Search Processing in Add Modes

When a user opens a component in add or data-entry modes, the following actions occur:

1. The Component Processor runs default processing on the high-level keys that appear in the Add or Data Entry dialog box.
2. The Component Processor initiates the RowInit event, which triggers any RowInit PeopleCode associated with the record field or the component record, on the Add or Data Entry dialog box fields.
3. The Component Processor initiates the SearchInit event on dialog fields, which triggers any SearchInit PeopleCode associated with the record field or the component search record.

This enables you to execute PeopleCode programs before the dialog box appears.

4. The Component Processor displays the Add or Data Entry dialog box.
5. If the user changes a dialog box field, and then leaves the field or clicks OK, the following actions occur:
 - In add mode only, a field modification processing sequence occurs.

See [Chapter 6, "PeopleCode and the Component Processor," Field Modification, page 116](#).

- Default processing is run on the Add or Data Entry dialog box fields.

Normally this does not have any effect, because the fields have a value.

6. When the user clicks OK in the dialog box, the SaveEdit event is initiated, which triggers any PeopleCode associated with the record field or the component record.
7. The Component Processor initiates the SearchSave event, which triggers any SearchSave PeopleCode associated with the record field or the component search record.

This enables you to validate user entry in the dialog box. If an error is executed in SearchSave, the user is sent back to the Add or Data Entry dialog box. If a warning is executed, the user can click OK to continue or click Cancel to return to the dialog box and enter new values.


8. The Component Processor buffers the search key values and continues processing.

Note. If you compare the following diagram with search processing in update modes, notice that the add modes are considerably more complex and involve more PeopleCode events. However, in practice, PeopleCode development is similar in both cases. PeopleCode that runs before the dialog box appears (for example, to control dialog box appearance or set values in the dialog box fields) generally is placed in the SearchInit event; PeopleCode that validates user entry in the dialog box is placed in the SearchSave event.

See Chapter 6, "PeopleCode and the Component Processor," Search Processing in Update Modes, page 104.

The following flowchart shows this logic.

Failed



Search processing logic in add and data-entry modes

Note. You can use the `IsSearchDialog` function to create PeopleCode that runs only during search processing. To create processes that run only in a specific action mode, use the `%Mode` system variable. This could be useful in code that is part of a library function and that is invoked in places other than from the search page. It could also be used in PeopleCode associated with a record field that appears in pages and in the search page.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," `IsSearchDialog`

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "System Variables," `%Mode`

Component Build Processing in Update Modes

After the Component Processor has saved the search keys values for the component, it uses the search key values to select rows of data from the database server using a SQL Select statement. After the rows are retrieved, the Component Processor performs these actions:

1. Performs row select processing, in which rows of data that have already been selected from the database server can be filtered before they are added to the component buffer.

See [Chapter 6, "PeopleCode and the Component Processor," Row Select Processing, page 112.](#)

2. Initiates the `PreBuild` event, which triggers any `PreBuild` PeopleCode associated with the component record, enabling you to set global or component scope variables that can be used later by PeopleCode located in other events.

The `PreBuild` event is also used to validate data entered in the search page, after a prompt list is displayed.

Note. If a `PreBuild` PeopleCode program issues an error or warning, the user is returned to the search page. If there is no search page, that is, the search record has no keys, a blank component page appears.

3. Performs default processing on all the rows and fields in the component.

See [Chapter 6, "PeopleCode and the Component Processor," Default Processing, page 101.](#)

4. Initiates the `RowInit` event, which triggers any `RowInit` PeopleCode associated with the record field or the component record.


The `RowInit` event enables you to programmatically initialize the values of non-blank fields in the component.

5. Initiates the `PostBuild` event, which triggers any `PostBuild` PeopleCode associated with the component record, enabling you to set global or component scope variables that can be used later by PeopleCode located in other events.

6. Initiates the `Activate` event, which triggers any `Activate` PeopleCode associated with the page about to be displayed, enabling you to programmatically control the display of that page.

7. Displays the component and waits for end-user action.

The following flowchart shows this logic.



Component build processing in update modes

Row Select Processing

Row select processing enables PeopleCode to filter out rows of data after they have been retrieved from the database server and before they are copied to the component buffers. Row select processing uses a SQL Select statement .

Row select processing is a subprocess of component build processing in add modes. It also occurs after a ScrollSelect or related function is executed.

See [Chapter 6, "PeopleCode and the Component Processor," Component Build Processing in Add Modes, page 115.](#)

Note. Instead of using row select processing, it is more efficient to filter out the rows using a search view, an effective-dated record, the Select method, or ScrollSelect or a related function, before the rows are sent to the browser.

In row select processing, the following actions occur:

1. The Component Processor checks for more rows to add to the component.
2. The Component Processor initiates the RowSelect event, which triggers any RowSelect PeopleCode associated with the record field or component record.


This enables PeopleCode to filter rows using the StopFetching and DiscardRow functions. StopFetching causes the system to add the current row to the component, and then to stop adding rows to the component. DiscardRow filters out a current row, and then continues the row select process.

3. If neither the StopFetching nor DiscardRow function is called, the Component Processor adds the rows to the page and checks for the next row.

The process continues until there are no more rows to add to the component buffers. If both StopFetching and DiscardRow are called, the current row is not added to the page, and no more rows are added to the page.

Note. In RowSelect PeopleCode, you can refer only to record fields on the record that is currently being processed, because the buffers are in the process of being populated. This means that the data might not be present.

The following flowchart shows this logic:



RowSelect processing logic

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," StopFetching

Component Build Processing in Add Modes

After search processing in add or data-entry modes, the Component Processor:

1. Initiates the PreBuild event.
2. Runs default processing on all page fields.


This enables you to set default fields programmatically using FieldDefault PeopleCode.

3. Initiates the RowInit event on all fields in the component, which triggers any RowInit PeopleCode associated with the record field or component record.

This enables you to initialize the state of page controls, using RowInit PeopleCode, before the controls are displayed. (RowInit enables you to set the values of non-blank fields programmatically, whereas default processing is used to set blank fields to their default values.)

4. Initiates the PostBuild event, which triggers any PostBuild PeopleCode associated with the component record, enabling you to set global or component scope variables that can be used later by PeopleCode located in other events.
5. Initiates the Activate event, which triggers any Activate PeopleCode associated with the page about to be displayed, enabling you to programmatically control the display of that page.
6. Displays a new component, using the search keys obtained from the Add or Data Entry dialog box, with other fields set to their default values.

The following flowchart shows the logic:



Logic of component build processing in add modes

Field Modification

The field modification processing sequence occurs after a user does any of the following:

- Changes the contents of a field, and then leaves the field.
- Changes the state of a radio button or check box.
- Clicks a command button.

In this sequence, the following actions occur:

1. The Component Processor performs standard system edits.

To reduce trips to the server, some processing must be done locally on the machine where the browser is located, while some is performed on the server.

Standard system edits can be done either in the browser, utilizing local JavaScript code, or on the application server. The following table outlines where these system edits are done.

<i>System Edits</i>	<i>Location of Execution</i>
Checking data type	Browser
Formatting	Application server or browser
Updating current or history record	Application server
Effective date	Application server
Effective date or sequence	Application server
New effective date in range	Application server
Duplicate key	Application server
Current level is not effective-dated but one of its child scroll areas is	Application server
Required field	Browser
Date range	Browser
Prompt table	Application server
Translate table	Browser
Yes/no table	Depends on the field type. Browser if the field is a check box. Application server if the field is an edit box and the values are <i>Y</i> or <i>N</i> .

Note. Default processing for the field can be done in the browser only if the default value is specified as a constant in the record field properties. If the field contains a default, these defaults occur only upon component initialization. Then, if a user replaces a default value with a blank, the field is not initialized again. The required fields check is not performed on derived work fields when you press Tab to move out of a field.

If the data fails the system edits, the Component Processor displays an error message and highlights the field in the system color for errors (usually red).

2. If the field passes the system edits, Component Processor initiates the FieldEdit PeopleCode event, which triggers any FieldEdit PeopleCode associated with the record field or the component record field.

This enables you to perform additional data validation in PeopleCode. If an Error statement is called in any FieldEdit PeopleCode, the Component Processor treats the error as it does a system edit failure; a message is displayed, and the field is highlighted. If a Warning statement is executed in any FieldEdit PeopleCode, a warning message appears, alerting the user to a possible problem, but the system accepts the change to the field.


3. If the field change is accepted, the Component Processor writes the change to the component buffer, then initiates the FieldChange event, which triggers any FieldChange PeopleCode associated with the record field or the component record field.

This event enables you to add processes other than validation initiated by the changed field value, such as changes to page appearance or recalculation of values in other page fields. An Error or Warning statement in any FieldChange PeopleCode causes a runtime error.

Important! Do not use Error or Warning statements in FieldChange PeopleCode. All data validation should be performed in FieldEdit PeopleCode.

After FieldChange processing, Component Processor runs default processing on all page fields, then redisplay the page. If the user has changed the field value to a blank, or if SetDefault or a related function is executed, and the changed field has a default value specified in the record field definition or any FieldDefault PeopleCode, the field is initialized again to the default value.

The following flowchart shows this logic:



Logic of field modification processing

Row Insert Processing

Row insert processing occurs when:

- A user requests a row insert in a scroll area by pressing Alt+7, by clicking the Insert Row button, or by clicking the New button.
- A PeopleCode RowInsert function or a InsertRow method requests a row insert.

In either case, the Component Processor performs these actions:

1. Inserts a new row of data into the active scroll area.

If the scroll area has a dependent scroll area, the system inserts a single new row into the blank scroll area, and the system continues until it reaches the lowest-level scroll area.

2. Initiates the RowInsert PeopleCode event, which triggers any RowInsert PeopleCode associated with the record field or the component record.

This event processes fields only on the inserted row and any dependent rows that were inserted on lower-level scroll areas.

3. Runs default processing on all component fields.

Normally this affects only the inserted row fields and fields on dependent rows, because other rows already have undergone default processing.


4. Initiates the RowInit PeopleCode event, which triggers any RowInit PeopleCode associated with the record field or the component record.

This event affects fields only on the inserted row and any dependent rows that were inserted.

5. Redisplays the page and waits for user action.

Important! Do not use Error or Warning statements in RowInsert PeopleCode. All data validation should be performed in FieldEdit or SaveEdit PeopleCode.

The following flowchart shows this logic:



Logic of row insert processing

Note. If none of the data fields in the new row are changed after the row has been inserted (either programmatically or by the user), the new row is not inserted into the database when the page is saved.

Row Delete Processing

Row delete processing occurs when:

- A user requests a row delete in a scroll area by pressing Alt+8, by clicking the Delete Row button, or by clicking the Delete button.
- A PeopleCode RowDelete function or a DeleteRow method requests a row delete.

In either case, these actions occur:

1. The Component Processor initiates the RowDelete PeopleCode event, which triggers RowDelete PeopleCode associated with the record field or the component record.

This event processes fields on the deleted row and any dependent child scroll areas. RowDelete PeopleCode enables you to check for conditions and control whether a user can delete the row. An Error statement displays a message and prevents the user from deleting the row. A Warning statement displays a message alerting the user about possible consequences of the deletion, but permits deletion of the row.


2. If the deletion is rejected, the page is redisplayed after the error message.
3. If the deletion is accepted, the row, and any child scroll areas dependent on the row, are flagged as deleted.

The row no longer appears in the page, but it is not physically deleted from the buffer and can be accessed by PeopleCode all the way through the SavePostChange event (note, however, that SaveEdit PeopleCode is not run on deleted rows).

4. The Component Processor runs default processing on all component fields.
5. The Component Processor redisplay the page and waits for a user action

Note. PeopleCode programs are triggered on rows flagged as deleted in SavePreChange and SavePostChange PeopleCode. Use the IsDeleted row class property to test whether a row has been flagged as deleted. You can also access rows flagged as deleted by looping through the rows of a scroll area using a For loop delimited by the value returned by the RowCount rowset property.

The following flowchart shows this logic:



Logic of row delete processing

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Row Class," IsDeleted

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Rowset Class," RowCount

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," For

Buttons

When a user presses a button, this initiates the same processing as changing a field. Typically, PeopleCode programs started by button are placed in the FieldChange event.

See Also

Chapter 6, "PeopleCode and the Component Processor," Field Modification, page 116

Prompts

If the Allow Search Events for Prompt Dialogs checkbox is selected for the Record Field properties for a search key on a prompt table record, the search processing events are enabled for that field. When the user selects the prompt icon, the SearchInit event for that field executes before the search dialog displays. When the user selects the Look Up button on a prompt dialog the SearchSave event for the field executes.

Search event processing on prompt dialogs can affect performance. Oracle recommends that you limit the use of search events in prompt dialogs to simple tasks such as showing and hiding fields or character manipulation. Do not use the search events on prompt dialogs for complex functions such as AddKeyListItem, ClearKeyList, ClearSearchDefault, ClearSearchEdit, IsSearchDialog, SetSearchDefault, SetSearchDialogBehavior, or SetSearchEdit, and so on.

By default, Allow Search Events for Prompt Dialogs is off, in which case no PeopleCode event is initiated as a result of prompts.

No PeopleCode events are initiated as a result of the user returning to the search page or displaying a calendar. This process is controlled automatically by the system.

Note. When the value of a field is changed using a prompt, the standard field modification processing occurs.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Application Designer Developer's Guide, "Creating Record Definitions," Setting Record Field Use Properties

Chapter 6, "PeopleCode and the Component Processor," Field Modification, page 116

Chapter 6, "PeopleCode and the Component Processor," Search Processing in Update Modes, page 104

Pop-Up Menu Display


To display a pop-up menu, a user can click the pop-up button, either next to a field or at the bottom of a page (if the page has a pop-up menu associated with it.) The user can open a standard pop-up menu on a page field if no pop-up menu has been defined by an application developer for that page field.

The PrePopup PeopleCode event initiates only if the user opens a pop-up menu defined by an application developer on a page field. It does not initiate for a pop-up menu attached to the page background.

The PrePopup PeopleCode event enables you to disable, check, or hide menu items in the pop-up menu.

PrePopup PeopleCode menu item operations (such as HideMenuItem, EnableMenuItem, and so on) work with pop-up menus attached to a grid, not a field in a grid, only if the PrePopup PeopleCode meant to operate on that pop-up menu resides in the record field that is attached to the first column in the grid. It does not matter if the first field is visible or hidden.

The following flowchart shows this logic:




Logic of PrePopup even processing

Selected Item Processing

Selected item processing occurs when a user selects a menu item from a pop-up menu. This initiates the ItemSelected PeopleCode event, which is a menu PeopleCode event.

The following flowchart shows this logic:



Logic of selected item processing

Save Processing

A user can direct the system to save a component by clicking Save or by pressing Alt+1.

An application can prompt the user to save a component when the Next or List button is clicked, or when a new action or component is selected. If the user clicks Save after being prompted, save processing begins.

The following actions occur in save processing:

1. The Component Processor initiates the SaveEdit PeopleCode event, which triggers any SaveEdit PeopleCode associated with a record field or a component record.

This enables you to cross-validate page fields before saving, checking consistency among the page field values. An Error statement in SaveEdit PeopleCode displays a message and then redisplay the page, stopping the save. A Warning statement enables the user to cancel save processing by clicking Cancel, or to continue with save processing by clicking OK.

2. The Component Processor initiates the SavePreChange event, which triggers any SavePreChange PeopleCode associated with a record field, a component record, or a component.

SavePreChange PeopleCode enables you to process data after validation and before the database is updated.

3. The Component Processor initiates the Workflow event, which triggers any Workflow PeopleCode associated with a record field or a component.

Workflow PeopleCode should be used only for workflow-related processing (TriggerBusinessEvent and related functions).

4. The Component Processor updates the database with the changed component data, performing any necessary SQL Insert, Update, and Delete statements.

5. The Component Processor initiates the SavePostChange PeopleCode event, which triggers any SavePostChange PeopleCode associated with a record field, a component record, or a component.


You can use SavePostChange PeopleCode for processing that must occur after the database update, such as updates to other database tables not in the component buffer.

6. The Component Processor issues a SQL Commit statement to the database server.

7. The Component Processor redisplay the component.

Important! Never use an Error or Warning statement in any save processing event other than SaveEdit. Perform all component data validation in SaveEdit.

The following flow chart shows the logic of this sequence:



Logic of save processing

PeopleSoft Pure Internet Architecture Processing Considerations

Keep the following points in mind concerning the PeopleSoft Pure Internet Architecture:

- If a user changes a field that field has nothing to cause a trip to the server, then default processing and FieldFormula PeopleCode do not run.

These processes only run when another event causes a trip to the server.

Other fields that depend on the first field using FieldFormula or default PeopleCode are not updated until the next time a server trip occurs.

- In applications that run on the PeopleSoft portal, external, dynamic link information must be placed in RowInit PeopleCode.

If it is placed in FieldChange PeopleCode, it will not work.

Deferred Processing Mode

When a component runs in deferred processing mode, trips to the server are reduced. When deploying some pages in the browser, you may want the user to be able to input data with minimal interruption or trips to the server. Each trip to the server can slow down your application. By specifying a component as deferred processing mode, you can achieve better performance.

PeopleSoft applications use Asynchronous JavaScript and XML (AJAX) technology to limit server trips and perform partial page refreshes. With a partial page refresh, the browser refreshes the entire page only when the user navigates to a new page. Any server trips triggered by PeopleCode functions such as FieldChange and FieldEdit for related display fields do not redraw the entire page; the refresh updates only the changed fields. Because of AJAX technology, much of the communication with the server happens in the background. You continue to work uninterrupted during the process.

Even with AJAX and partial page refresh, Oracle recommends that you leverage deferred processing mode to limit network traffic. Although server trips are reduced, if you selectively disable deferred processing you will incur not only additional network traffic to process the request, you will also add additional processing on the webserver and appserver to deal with this request.

See *Enterprise PeopleTools 8.50 PeopleBook: Using PeopleSoft Applications*, "Working With Pages."

If you specified deferred processing mode for a component, you can then specify whether a page within a component, or a field on a page, also performs processing in deferred mode. The default is for all pages and components to allow deferred processing. By default, fields do not allow deferred processing.

If you specify that a field or page allows deferred processing but do not set the component to deferred processing mode, then the deferred processing mode is not initiated. You must set the component first.

The characteristics of this mode are:

1. Field modification processing is deferred.

No field modification processing is done in the browser. FieldEdit and FieldChange PeopleCode, as well as other edits, such as required field checks, formats, and so on, do not run until a specific user action occurs. Several actions cause field modification processing to execute, for example, clicking a button or link, navigating to another page in the component, and saving the page. The following actions do not cause field processing:

- Clicking an external link.
- Clicking a list (performing a search).
- Clicking a process button.

Deferred processing mode affects the appearance of pages in significant ways. For example, related processing is not done when the user presses Tab to move out of a field. Avoid related fields for components that use this mode.

2. Drop-down list box values are static while the page appears in the browser.

Drop-down list box values are generated on the application server when generating the HTML for the page.

If translate values are used to populate the drop-down list box, and the current record contains an effective date, that date is static while the page is displayed. This means the drop-down list box values may become out of date.

If prompt table values are used to populate the drop-down list box, the high-order key field values for the prompt table are static while the page is displayed. This means the drop-down list box values may become out of date.

Avoid interdependencies in drop-down lists used on pages executed in deferred mode, because the lists may quickly become out of date.

3. No field modification processing is done during prompt button processing.

When the user clicks a prompt button, a trip is made to the application server (if values were not already downloaded) to select the search results from the database and to generate the HTML for the prompt dialog box. During this trip to the application server, field modification processing for the field being prompted is not performed, because this may cause an error message for another field on the page, and this error may confuse the user. When deferred changes are made to other fields, field modification processing for these fields is done before prompting. The field modification for the prompted field is done after returning from the prompt page. While the system displays the page, the high-order key field values for the prompt table should be static or not require field modification processing. Display-only drop-down list box, radio button, and check box fields do not require field modification processing. Field values that do not require field modification processing are temporarily written to the component buffer, without any field modification processing being performed on them, including FieldEdit and FieldChange PeopleCode. The system restores the original state of the page processor before returning to the browser.

4. Field modification processing executes in field layout order.

The entire field modification processing sequence executes in field layout order for each field. If a field passes the system edits and FieldEdit PeopleCode, the field value is written to the component buffer. If an error occurs, field modification processing stops, and the system generates new HTML for the page, with the field in error highlighted and sent to the browser.

5. PeopleCode dependencies between fields on the page do not work as expected.

Avoid PeopleCode dependencies between fields on pages displayed in deferred processing mode. Also, avoid FieldChange PeopleCode that changes the display.

The following are examples of PeopleCode dependencies between fields on the page and the application server's action. In the following examples, field A comes before field B, which comes before field C.

- Field A has FieldChange PeopleCode that hides field B or it makes unavailable for entry.

The value in field B of the page that was submitted from the browser is discarded.

- Field B has FieldChange PeopleCode that hides field A or makes it unavailable for entry.

The change made by the user for field A, if any, remains in the component buffer.

- Field A has FieldChange PeopleCode that changes the value in the component buffer for field B.

If the value in field B of the page that was submitted from the browser passes the system edits and FieldEdit PeopleCode, it is written to the component buffer, overriding the change made by field A's FieldChange PeopleCode.

- Field B has FieldChange PeopleCode that changes the value in the component buffer for field A.

The change made by field B's FieldChange PeopleCode overrides the change made by the user to field A, if any.

- Field A has FieldChange PeopleCode that unhides field B or makes it available for entry.

Field B has the value that was already in the component buffer. If the user requests a different page or finishes, the user may not have the opportunity to enter a value into field B, and therefore the value may not be correct.

- Field B has FieldChange PeopleCode that changes the value in the component buffer for field A, but field C has FieldChange PeopleCode that hides field B or makes it unavailable for entry.

The change made by field B's FieldChange PeopleCode, a field that is now hidden or unavailable for entry, overrides the change made by the user to field A, if any.

Avoid such dependencies by moving FieldChange PeopleCode logic from individual fields to save processing for the component or FieldChange PeopleCode on a PeopleCode command button.

6. Not all buttons cause field modification processing to execute.

External links, list (search), and process buttons do not cause field modification processing to execute.

7. You can use a PeopleCode command button to cause field modification processing to execute.

An application can include a button for the sole purpose of causing field modification processing to execute. The result is a new page showing any display changes that resulted from field modification processing.

In addition, if the user clicks the Refresh button, or presses Alt + 0, deferred processing is executed.

Note. The Refresh button does not refresh the page from the database. It simply causes a server trip so any deferred PeopleCode changes get processed. If the page has no deferred changes or the deferred changes do not cause any errors or other changes on the page, it may appear to the user as if nothing happened.

8. A scroll button (link) causes field modification processing to execute.

PeopleCode Events

This section discusses:

- Activate event.
- FieldChange event.
- FieldDefault event.
- FieldEdit event.
- FieldFormula event.
- ItemSelected event.
- PostBuild event.
- PreBuild event.
- PrePopup event.
- RowDelete event.
- RowInit event.
- RowInsert event.
- RowSelect event.
- SaveEdit event.
- SavePostChange event.
- SavePreChange event.
- SearchInit event.
- SearchSave event.
- Workflow event.

Note. The term *PeopleCode type* is still frequently used, but it does not fit into the PeopleTools object-based, event-driven metaphor. The term *PeopleCode event* should now be used instead. However, it's often convenient to qualify a class of PeopleCode programs triggered by a specific event with the event name; for example, PeopleCode programs associated with the RowInit events are collectively referred to as *RowInit PeopleCode*.

Activate Event

The Activate event is initiated each time that a page is activated, including when a page is first displayed by a user, or if a user presses Tab between different pages in a component. Each page has its own Activate event.

Activate PeopleCode associated with a popup page executes after the page activate event for the main page. When fields on the main page change and trigger updates on the popup page the page activate event for the popup page is executed.

The Activate event segregates PeopleCode that is related to a specific page from the rest of the application's PeopleCode. Place PeopleCode related to page display or page processing, such as enabling a field or hiding a scroll area, in this event. Also, you can use this event for security validation: if an user does not have clearance to view a page in a component, you would put the code for hiding the page in this event.

Note. PeopleSoft builds a page grid one row at a time. Because the Grid class applies to a complete grid, you cannot attach PeopleCode that uses the Grid class to events that occur before the grid is built; the earliest event you can use is the Activate event. The Activate event is not associated with a specific row and record at the point of execution. This means you cannot use functions such as GetRecord, GetRow, and so on, which rely on context, without specifying more context.

Activate PeopleCode can only be associated with pages.

This event is valid only for pages that are defined as standard or secondary. This event is not supported for subpages.

Note. If your application uses the MessageBox built-in function in the Activate event with a message from the message catalog that's defined as type Error, Warning or Cancel, all component processing stops with an error message to that effect. If the message has a type of Message, processing does not stop.

See Also

Chapter 6, "PeopleCode and the Component Processor," Component Build Processing in Update Modes, page 111

Chapter 6, "PeopleCode and the Component Processor," Component Build Processing in Add Modes, page 115

FieldChange Event

Use FieldChange PeopleCode to recalculate page field values, change the appearance of page controls, or perform other processing that results from a field change other than data validation. To validate the contents of the field, use the FieldEdit event.

See Chapter 6, "PeopleCode and the Component Processor," FieldEdit Event, page 132.

The FieldChange event applies to the field and row that just changed.

FieldChange PeopleCode is often paired with RowInit PeopleCode. In these RowInit/FieldChange pairs, the RowInit PeopleCode checks values in the component and initializes the state or value of page controls accordingly. FieldChange PeopleCode then rechecks the values in the component during page execution and resets the state or value of page controls.

To take a simple example, suppose you have a derived/work field called **PRODUCT**, the value of which is always the product of page field **A** and page field **B**. When the component is initialized, you would use **RowInit** PeopleCode to initialize **PRODUCT** equal to $A \times B$ when the component starts up or when a new row is inserted. You could then attach **FieldChange** PeopleCode programs to both **A** and **B** which also set **PRODUCT** equal to $A \times B$. Whenever a user changes the value of either **A** or **B**, **PRODUCT** is recalculated.

FieldChange PeopleCode can be associated with record fields and component record fields.

See Also

Chapter 6, "PeopleCode and the Component Processor," Field Modification, page 116

FieldDefault Event

The **FieldDefault** PeopleCode event enables you to programmatically set fields to default values when they are initially displayed. This event is initiated on all page fields as part of many different processes; however, it triggers PeopleCode programs only when the following conditions are all True:

- The page field is still blank after applying any default value specified in the record field properties.

This is True if there is no default specified, if a null value is specified, or if a 0 is specified for a numeric field.

- The field has a **FieldDefault** PeopleCode program.

In practice, **FieldDefault** PeopleCode normally sets fields by default when new data is being added to the component; that is, in **Add** mode and when a new row is inserted into a scroll area.

If a field value is changed, whether through PeopleCode or by a user, the **IsChanged** property for the row is set to True. The exception to this is when a change is done in the **FieldDefault** or **FieldFormula** events. If a value is set in **FieldDefault** or **FieldFormula**, the row is not marked as changed.

At save time, all newly inserted and changed rows are written to the database. All newly inserted but not changed rows are not written to the database.

You must attach **FieldDefault** PeopleCode to the field where the default value is being populated.

Note. An error or warning issued from **FieldDefault** PeopleCode causes a runtime error.

FieldDefault PeopleCode can be associated with record fields and component record fields.

See Also

Chapter 6, "PeopleCode and the Component Processor," Default Processing, page 101

FieldEdit Event

Use **FieldEdit** PeopleCode to validate the contents of a field, supplementing standard system edits. If the data does not pass the validation, the PeopleCode program should display a message using the **Error** statement, which redisplay the page, displaying an error message and turning the field red.

To permit the field edit but alert the user to a possible problem, use a Warning statement instead of an Error statement. A Warning statement displays a warning dialog box with OK and Explain buttons. It permits field contents to be changed and continues processing as usual after the user clicks OK.

If the validation must check for consistency across page fields, then use SaveEdit PeopleCode instead of FieldEdit.

The FieldEdit event applies to the field and row that just changed.

FieldEdit PeopleCode can be associated with record fields and component record fields.

See Also

Chapter 6, "PeopleCode and the Component Processor," Field Modification, page 116

FieldFormula Event

The FieldFormula event is not currently used. Because FieldFormula PeopleCode initiates in many different contexts and triggers PeopleCode on every field on every row in the component buffer, it can seriously degrade application performance. Use RowInit and FieldChange events rather than FieldFormula.

If a field value is changed, whether through PeopleCode or by a user, the IsChanged property for the row is usually set to True. However, if a value is set in FieldDefault or FieldFormula, the row is not marked as changed.

At save time, all newly inserted and changed rows are written to the database. All newly inserted but not changed rows are not written to the database.

Note. In PeopleSoft Pure Internet Architecture, if a user changes a field but that field has nothing to cause a trip to the server, then default processing and FieldFormula PeopleCode do not run. They only run when another event causes a trip to the server.

As a matter of convention, FieldFormula is now often used in FUNCLIB_ (function library) record definitions to store shared functions. However, you can store shared functions in any PeopleCode event.

FieldFormula PeopleCode is only associated with record fields.

ItemSelected Event

The ItemSelected event is initiated whenever a user selects a menu item from a pop-up menu. In pop-up menus, ItemSelected PeopleCode executes in the context of the page field from where the pop-up menu is attached, which means that you can freely reference and change page fields, just as you could from a button.

Note. This event, and all its associated PeopleCode, does not initiate if run from a component interface.

ItemSelected PeopleCode is only associated with pop-up menu items.

See Also

Chapter 6, "PeopleCode and the Component Processor," Selected Item Processing, page 124

PostBuild Event

The PostBuild event is initiated after all the other component build events have been initiated. This event is often used to hide or unhide pages. It is also used to set component variables.

PostBuild PeopleCode is only associated with components.

PreBuild Event

The PreBuild event is initiated before the rest of the component build events. This event is often used to hide or unhide pages. It is also used to set component variables.

Note. If a PreBuild PeopleCode program issues an error or warning, the user is returned to the search page. If the search record has no keys, a blank component page appears.

Also use the PreBuild event to validate data entered in a search page after a prompt list is displayed. For example, after a user selects key values on a search, the PreBuild PeopleCode program runs, catches the error condition, and issues an error message. The user receives and acknowledges the error message. The component is canceled (because of the error), and the user is returned to the search page. PreBuild PeopleCode is only associated with components.

PrePopup Event

The PrePopup event is initiated just before the display of a pop-up menu.

You can use PrePopup PeopleCode to control the appearance of the pop-up menu.

Note. This event, and all its associated PeopleCode, does not initiate if run from a component interface.

PrePopup PeopleCode can be associated with record fields and component record fields.

See Also

Chapter 6, "PeopleCode and the Component Processor," Pop-Up Menu Display, page 124

RowDelete Event

The RowDelete event is initiated whenever a user attempts to delete a row of data from a page scroll area. Use RowDelete PeopleCode to prevent the deletion of a row (using an Error or Warning statement) or to perform any other processing contingent on row deletion. For example, you could have a page field called Total on scroll area level zero whose value is the sum of all the Extension page fields on scroll area level one. If the user deleted a row on scroll area level one, you could use RowDelete PeopleCode to recalculate the value of the Total field.

The RowDelete event triggers PeopleCode on any field on the row of data that is being flagged as deleted.

Note. RowDelete does not trigger programs on derived/work records.

RowDelete PeopleCode can be associated with record fields and component records.

Deleting All Rows from a Scroll Area

When the last row of a scroll area is deleted, a new, dummy row is automatically added. As part of the RowInsert event, RowInit PeopleCode is run on this dummy row. If a field is changed by RowInit (even if it's left blank), the row is no longer new, and therefore is not reused by any of the ScrollSelect functions or the Select method. In this case, you may want to move your initialization code from the RowInit event to FieldDefault.

See Also

[Chapter 6, "PeopleCode and the Component Processor," Row Delete Processing, page 121](#)

[Chapter 8, "Using Methods and Built-In Functions," Using Errors and Warnings in RowDelete Events, page 183](#)

RowInit Event

The RowInit event is initiated the first time that the Component Processor encounters a row of data. Use it to set the initial state of component controls during component build processing and row insert processing. The RowInit event also occurs after a Select or SelectAll Rowset method, or a ScrollSelect or related function, is executed.

Note. Generally, if none of the fields in the new row are changed after the row is inserted (either by a user pressing Alt+7 or programmatically) when the page is saved, the new row is not inserted into the database. However, if the ChangeOnInit rowset class property is set to False, you can set values for fields a new row in RowInsert or RowInit PeopleCode, and the row will not be saved.

RowInit is not field-specific. It triggers PeopleCode on all fields and on all rows in the component buffer.

Do not use Error or Warning statements in RowInit PeopleCode. They cause a runtime error.

RowInit PeopleCode is often paired with FieldChange PeopleCode. In these RowInit/FieldChange pairs, the RowInit PeopleCode checks values in the component and initializes the state or value of page controls accordingly. FieldChange PeopleCode then rechecks the values in the component during page execution and resets the state or value of page controls.

For a simple example, suppose you have a derived/work field called **PRODUCT**, the value of which is always the product of page field **A** and page field **B**. When the component is initialized, use **RowInit** PeopleCode to initialize **PRODUCT** equal to $A \times B$ when the component starts up or when a new row is inserted. You could then attach **FieldChange** PeopleCode programs to both **A** and **B**, which also sets **PRODUCT** equal to $A \times B$. Whenever a user changes the value of either **A** or **B**, **PRODUCT** is recalculated.

RowInit PeopleCode can be associated with record fields and component records.

RowInit Exceptions

In certain rare circumstances, the Component Processor does not run **RowInit** PeopleCode for some record fields. The Component Processor runs **RowInit** PeopleCode when it loads the record from the database. However, in some cases, the record can be initialized entirely from the keys for the component. When this happens, **RowInit** PeopleCode is not run.

For **RowInit** to not run, the following must all be True:

- The record is at level zero.
- Every record field that is present in the data buffers is also present in the keys for the component.

The Component Processor determines if the field is required by the component. In practice, this usually means that the field is associated with a page field, possibly hidden, for some page of the component. It could also mean that the field is referenced by some PeopleCode program that is attached to an event on some other field of the component.

- Every record field that is present in the data buffers is display-only.

RowInit not running is not considered to be an error. The purpose of **RowInit** PeopleCode is to complete initialization of data on the row after it has been read from the database. Because the data in this special circumstance is coming from the keylist, it was already initialized correctly by whatever processing produced the keylist. More general initialization of the component should be done in **PostBuild** PeopleCode, not **RowInit**.

See Also

Chapter 6, "PeopleCode and the Component Processor," Component Build Processing in Add Modes, page 115

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Rowset Class," **ChangeOnInit**

RowInsert Event

When a user adds a row of data, the Component Processor generates a **RowInsert** event. You should use **RowInsert** PeopleCode for processing specific to the insertion of new rows. Do not put PeopleCode in **RowInsert** that already exists in **RowInit**, because a **RowInit** event always initiates after the **RowInsert** event, which will cause your code to be run twice.

Note. Generally, if none of the fields in the new row are changed after the row has been inserted (either by a user pressing **Alt+7** or programmatically), when the page is saved, the new row is not inserted into the database. However, if the **ChangeOnInit** rowset class property is set to **False**, you can set values for fields a new row in **RowInsert** or **RowInit** PeopleCode, and the row won't be saved.

The RowInsert event triggers PeopleCode on any field on the inserted row of data.

Do not use a warning or error in RowInsert.

You can prevent a user from inserting rows into a scroll area by selecting the No Row Insert check box in the scroll bar's page field properties, as shown in the following illustration. However, you cannot prevent row insertion conditionally.

The screenshot shows the 'Page Field Properties' dialog box with the 'General' tab selected. The 'Scroll Attributes' section has 'Occurs Level' and 'Occurs Count' both set to 1. The 'Field Use Options' section has 'Invisible', 'No Auto Select', and 'No Row Delete' unchecked, while 'Default Width' and 'No Row Insert' are checked. The 'Scroll Action Buttons' section has 'Previous Page', 'Row Insert', 'Top', and 'Show Row Counter' unchecked, while 'Next Page', 'Row Delete', and 'Bottom' are checked. The 'Popup Menu' is empty. The 'Field Help Context Number' is empty with an '< Auto Assign' button. The 'Allow Deferred Processing' checkbox is checked. 'OK' and 'Cancel' buttons are at the bottom.

Setting row insert properties in page field properties for a scroll bar

Note. RowInsert does not trigger PeopleCode on derived/work fields.

RowInsert PeopleCode can be associated with record fields and component records.

See Also

Chapter 6, "PeopleCode and the Component Processor," Row Insert Processing, page 119

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Rowset Class," ChangeOnInit

RowSelect Event

The RowSelect event is initiated at the beginning of the component build process in any of the update action modes (Update, Update/Display All, Correction). RowSelect PeopleCode is used to filter out rows of data as they are being read into the component buffer. This event also occurs after a ScrollSelect or related function is executed.

A DiscardRow function in RowSelect PeopleCode causes the Component Processor to skip the current row of data and continue to process other rows. A StopFetching statement causes the Component Processor to accept the current row of data, and then stop reading additional rows. If both statements are executed, the program skips the current row of data, and then stops reading additional rows.

PeopleSoft applications rarely use RowSelect, because it's inefficient to filter out rows of data after they've already been selected. Instead, screen out rows of data using search record views and effective-dated tables, which filter out the rows before they're selected. You could also use a ScrollSelect or related function to programmatically select rows of data into the component buffer.

In previous versions of PeopleTools, the Warning and Error statements were used instead of DiscardRow and StopFetching. Warning and Error statements still work as before in RowSelect, but their use is discouraged.

Note. In RowSelect PeopleCode, you can refer to record fields only on the record that is currently being processed. This event, and all its associated PeopleCode, does not initiate if run from a component interface.

RowSelect PeopleCode can be associated with record fields and component records.

See Also

Chapter 6, "PeopleCode and the Component Processor," Row Select Processing, page 112

SaveEdit Event

The SaveEdit event is initiated whenever a user attempts to save the component. You can use SaveEdit PeopleCode to validate the consistency of data in component fields. Whenever a validation involves more than one component field, you should use SaveEdit PeopleCode. If a validation involves only one page field, use FieldEdit PeopleCode.

SaveEdit is not field-specific. It triggers associated PeopleCode on every row of data in the component buffers except rows flagged as deleted.

An Error statement in SaveEdit PeopleCode displays a message and redisplay the component without saving data. A Warning statement enables the user to click OK and save the data, or to click Cancel and return to the component without saving.

Use the SetCursorPos function to set the cursor position to a specific page field following a warning or error in SaveEdit, to show the user the field (or at least one of the fields) that is causing the problem. Make sure to call SetCursorPos before the error or warning, because these may terminate the PeopleCode program.

SaveEdit PeopleCode can be associated with record fields and components.

See Also

Chapter 6, "PeopleCode and the Component Processor," Save Processing, page 125

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," SetCursorPos

SavePostChange Event

After the Component Processor updates the database, it initiates the SavePostChange event. You can use SavePostChange PeopleCode to update tables not in your component using the SQLExec built-in function.

An error or warning in SavePostChange PeopleCode causes a runtime error. Avoid errors and warnings in this event.

The system issues a SQL Commit statement after SavePostChange PeopleCode completes successfully.

If you are executing Workflow PeopleCode, keep in mind that if the Workflow PeopleCode fails, SavePostChange PeopleCode is not executed. If your component has both Workflow and SavePostChange PeopleCode, consider moving the SavePostChange PeopleCode to SavePreChange or Workflow.

If you are doing messaging, your Publish PeopleCode should go into this event.

SavePostChange does not execute if there is an error during the save. For example, if there is a data conflict error because another user updated the same data at the same time, SavePostChange does not execute.

Important! Never issue a SQL Commit or Rollback statement manually from within a SQLExec function. Let the Component Processor issue these SQL commands.

SavePostChange PeopleCode can be associated with record fields, components, and component records.

See Also

Chapter 6, "PeopleCode and the Component Processor," Save Processing, page 125

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," SQLExec

SavePreChange Event

The SavePreChange event is initiated after SaveEdit completes without errors. SavePreChange PeopleCode provides one final opportunity to manipulate data before the system updates the database; for instance, you could use SavePreChange PeopleCode to set sequential high-level keys. If SavePreChange runs successfully, a Workflow event is generated, and then the Component Processor issues appropriate Insert, Update, or Delete SQL statements.

SavePreChange PeopleCode is not field-specific: it triggers PeopleCode on all fields and on all rows of data in the component buffer.

SavePreChange PeopleCode can be associated with record fields, components, and component records.

See Also

Chapter 6, "PeopleCode and the Component Processor," Save Processing, page 125

SearchInit Event

The SearchInit event is generated just before a search, add, or data-entry dialog box is displayed. SearchInit triggers associated PeopleCode in the search key fields of the search record. This enables you to control processing before a user enters values for search keys in the dialog box. In some cases, you may want to set the value of the search dialog fields programmatically. For example, the following program in SearchInit PeopleCode on the component search key record field EMPLID sets the search key page field to the user's employee ID, makes the page field unavailable for entry, and enables the user to modify the user's own data in the component:

```
EMPLID = %EmployeeId;
Gray (EMPLID);
AllowEmplIdChg (True);
```

You can activate system defaults and system edits in the search page by calling SetSeachDefault and SetSearchEdit in SearchInit PeopleCode. You can also control the behavior of the search page, either forcing it to appear even if all the required keys have been provided, or by skipping it if possible, with the SetSeachDialogBehavior function. You can also force search processing to always occur by selecting the Force Search Processing check box in the component properties in PeopleSoft Application Designer.

Note. This event, and all its associated PeopleCode, does not initiate if run from a component interface.

SearchInit PeopleCode can be associated with record fields on search records and prompt table records and on component search records and component prompt table records.

SearchInit with Prompt Dialogs

Beginning with PeopleTools 8.50 you can put PeopleCode on the SearchInit and SearchSave events on the search keys of prompt table records. SearchInit and SearchSave events will only execute if the Allow Search Events for Prompt Dialogs checkbox was selected for the search key's record field properties in Application Designer. By default Allow Search Events for Prompt Dialogs is off.

Note. Search processing with prompt dialogs can affect performance. Oracle recommends that you limit the use of PeopleCode with prompt dialogs.

SearchInit PeopleCode Function Restrictions

You cannot use the following functions in SearchInit PeopleCode:

- DoModal
- DoModalComponent
- Transfer
- TransferExact

- TransferNode
- TransferPage
- TransferPortal

See Also

[Chapter 6, "PeopleCode and the Component Processor," Prompts, page 123](#)

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," SetSearchDefault

[Chapter 6, "PeopleCode and the Component Processor," Search Processing in Update Modes, page 104](#)

[Chapter 6, "PeopleCode and the Component Processor," Search Processing in Add Modes, page 108](#)

SearchSave Event

SearchSave PeopleCode is executed for all search key fields on a search, add, or data-entry dialog box after a user clicks Search. This enables you to control processing after search key values are entered, but before the search based on these keys is executed. A typical use of this feature is to provide cross-field edits for selecting a minimum set of key information. This event is also used to force a user to enter a value in at least one field, even if it's a partial value, to help narrow a search for tables with many rows.

Note. SearchSave is not initiated when values are selected from the search list. To validate data entered in the search page, use the Component PreBuild event.

You can use Error and Warning statements in SearchSave PeopleCode to send the user back to the search page if the user entry does not pass validations implemented in the PeopleCode.

Note. This event, and all its associated PeopleCode, is not initiated if run from a component interface.

SearchSave PeopleCode can be associated with record fields and component search records.

Note. Do not use the %Menu system variable in this event. You may get unexpected results.

SearchSave with Prompt Dialogs

Beginning with PeopleTools 8.50 you can put PeopleCode on the SearchInit and SearchSave events on the search keys of prompt table records. SearchInit and SearchSave events will only execute if the Allow Search Events for Prompt Dialogs checkbox is selected for the search key's record field properties in Application Designer. By default Allow Search Events for Prompt Dialogs is off.

Note. Search processing with prompt dialogs can affect performance. Oracle recommends that you limit the use of PeopleCode with prompt dialogs.

See Also

[Chapter 6, "PeopleCode and the Component Processor," Prompts, page 123](#)

[Chapter 6, "PeopleCode and the Component Processor," Search Processing in Update Modes, page 104](#)

[Chapter 6, "PeopleCode and the Component Processor," Search Processing in Add Modes, page 108](#)

Workflow Event

Workflow PeopleCode executes immediately after the SavePreChange event and before the database update that precedes the SavePostChange event. The Workflow event segregates PeopleCode related to workflow from the rest of the application's PeopleCode. Only PeopleCode related to workflow (such as TriggerBusinessEvent) should be in workflow programs. Your program should deal with the Workflow event only after any SavePreChange processing is complete.

Workflow PeopleCode is not field-specific: it triggers PeopleCode on all fields and on all rows of data in the component buffer.

WorkFlow PeopleCode can be associated with record fields and components.

See Also

[Chapter 6, "PeopleCode and the Component Processor," Save Processing, page 125](#)

Enterprise PeopleTools 8.50 PeopleBook: Workflow Technology, "Defining Event Triggers," Writing Workflow PeopleCode

PeopleCode Execution in Pages with Multiple Scroll Areas

Components with multiple levels can have multiple rows of data from multiple primary record definitions. You must know the order in which the system processes buffers for this data, because it applies PeopleCode in the same order.

The Component Processor uses a depth-first algorithm to process rows in multiple-scroll-area pages, starting with a row at level zero, drilling down to dependent rows on lower levels, and then working up the hierarchy until the system has processed all the dependent rows of the last row on the highest level.

Scroll Level One

When pages have only one scroll bar, the Component Processor processes record definitions at scroll level zero, and then all rows of data at scroll level one.

Data is retrieved for all rows with a single Select statement, and then it is merged with buffer structures.

Scroll Level Two

With scroll bars at multiple scroll levels, the system processes a single row of data at scroll level one, and then it processes all subordinate rows of data at scroll level two. After processing all subordinate data at scroll level two, it processes the next row for scroll level one, and all the subordinate data for that row. The system continues in this fashion until all data is processed.

Scroll Level Three

The Component Processor uses the same method for processing subordinate data at scroll level three. Data is retrieved for all rows with a single Select statement, and then merged with buffer structures. The Component Processor processes a single row of data at scroll level two, and it processes all subordinate data at scroll level three. After processing all subordinate data at scroll level three, it processes the next row for scroll level two and all the subordinates data for that row. The system continues in this fashion until all data is processed..

See Also

Chapter 4, "Referencing Data in the Component Buffer," Understanding Component Buffer Structure and Contents, page 47

Chapter 7

PeopleCode and PeopleSoft Pure Internet Architecture

The chapter discusses how to:

- Using PeopleCode in PeopleSoft Pure Internet Architecture.
- Using PeopleCode with PeopleSoft Pure Internet Architecture
- Call dynamic link library (DLL) functions on the application server.
- Update the Installation and PSOPTIONS tables.

Considerations Using PeopleCode in PeopleSoft Pure Internet Architecture

Consider the following points when writing PeopleCode programs for PeopleSoft Pure Internet Architecture:

- To help your application run efficiently, avoid using field-level PeopleCode events (FieldEdit and FieldChange).

Each field-level PeopleCode program requires a trip to the application server.

The majority of PeopleCode programs run on the application server as part of the component build and save process. Do not hesitate to use PeopleCode for building and saving components.

- If a user changes a field but nothing on that field will cause a trip to the server, then default processing and FieldFormula PeopleCode do not run.

This processing occurs only when another event causes a trip to the server.

Other fields that depend on the first field using FieldFormula or default PeopleCode are not updated until the next time a server trip occurs.

- In applications that run on the PeopleSoft portal, external dynamic link information must be placed in RowInit PeopleCode.

If external dynamic link information is placed in FieldChange PeopleCode, it will not work.

- Trips to the server are reduced when a component runs in deferred processing mode.

Each trip to the server results in the page being completely refreshed on the browser, which may cause the display to flicker. It can also slow down your application. Deferred processing mode results in better performance.

See Also

Chapter 6, "PeopleCode and the Component Processor," Deferred Processing Mode, page 127

Using PeopleCode with PeopleSoft Pure Internet Architecture

This section discusses how to:

- Use internet scripts.
- Use the field object Style property.
- Use the HTML area.
- Use HTML definitions and the GetHTMLText function.
- Use HTML definitions and the GetJavaScriptURL method.
- Use PeopleCode to populate key fields in search dialog boxes

Using Internet Scripts

An internet script is a specialized PeopleCode function that generates dynamic web content. Internet scripts interact with web clients (browsers) using a request-response paradigm based on HTTP.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Internet Script Classes (iScript)"

Using the Field Object Style Property

In PeopleSoft Application Designer, on the Use tab of the page definition properties, you can associate a page with a style sheet component.

The style sheet has several classes of styles defined for it. You can edit each style class to change the font, the color, the background, and so on. Then, you can dynamically change the style of a field using the Style field class property. The style sheet does not change, only the style class associated with that field changes.

The following example changes the style class of a field depending on a value entered by the user. This code is in the FieldChange event.

```

Local Field &field;

&field = GetField();

If TESTFIELD1 = 1 Then;
    &field.Style = "PSHYPERLINK";
End-If;

If TESTFIELD1 = 2 Then;
    &field.Style = "PSIMAGE";
End-If;

```

The following examples show the fields with different styles:

TESTFIELD1: 

Field with PSHYPERLINK style

TESTFIELD1: 

Field with PSIMAGE style

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Application Designer Developer's Guide, "Creating Style Sheet Definitions"

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Field Class"

Using the HTML Area

Two methods are used to populate an HTML area control. Both require accessing the HTML area in the PeopleSoft Application Designer. One method is to select Constant on the HTML tab of the HTML page field properties dialog and enter HTML directly into the page field dialog.

The other method is to select Value on the HTML tab of the HTML page field properties dialog and associate the control with a record field. At runtime, populate that field with the text that you want to appear in the HTML area.

If you are using an HTML area to add form controls to a page, you can use GetParameter request class method in PeopleCode to get the user input from those controls.

Note. When you associate an HTML area control with a field, make sure the field is long enough to contain the data you want to pass to it. For example, if you associate an HTML area control with a field that is only 10 characters long, only the first 10 characters of your text will appear.

The following code populates an HTML area with a simple bulleted list. This code is in the RowInit event of the record field associated with the HTML control.

```
Local Field &HTMLField;

&HTMLField = GetField();
&HTMLField.Value = "<ul><li>Item one</li><li>Item two</li></ul>";
```

The following code is in the FieldChange event of a button. It populates an HTML area (associated with the record field CHART_DATA.HTMLAREA) with a simple list.

```
Local Field &HTMLField;

&HTMLField = GetRecord(Record.CHART_DATA).HTMLAREA;
&HTMLField.Value = "<ul><li>Item one</li><li>Item two</li></ul>";
```

The following code populates an HTML area (associated with the record DERIVED_HTML and the field HTMLAREA) with the output of the GenerateTree function:

```
DERIVED_HTML.HTMLAREA = GenerateTree(&TREECTL);
```

The following tags are unsupported by the HTML area control:

- Body
- Frame
- Frameset
- Form
- Head
- HTML
- Meta
- Title

See Also

[Chapter 9, "Using HTML Trees and the GenerateTree Function," Using the GenerateTree Function, page 189](#)

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Application Designer Developer's Guide, "Creating HTML Definitions"

Using HTML Definitions and the GetHTMLText Function

If you are using the same HTML text in more than one place or if it is a large, unwieldy string, you can create an HTML definition in PeopleSoft Application Designer, and then use the GetHTMLText function to populate an HTML area control.

The following is the HTML string to create a simple table:

```

<P>
<TABLE>

  <TR bgColor=#008000>
    <TD>
      <P><FONT color=#f5f5dc face="Arial, Helvetica, sans-serif"
        size=2>message 1 </FONT></P></TD></TR>
  <TR bgColor=#0000cd>
    <TD>
      <P><FONT color=#00ffff face="Arial, Helvetica, sans-serif"
        size=2>message 2</FONT></P></TD></TR>
</TABLE></P>

```

This HTML is saved to an HTML definition called TABLE_HTML.

This code is in the RowInit event of the record field associated with the HTML area control:

```

Local Field &HTMLField;

&HTMLField = GetField();
&string = GetHTMLText(HTML.TABLE_HTML);
&HTMLField.Value = &string;

```

This code produces the following:

```

message 1
message 2

```

HTML definition example

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," GetHTMLText

Using HTML Definitions and the GetJavaScriptURL Method

HTML definitions can contain JavaScript programs in addition to HTML. If you have an HTML definition that contains JavaScript, use the GetJavaScriptURL Response method to access and execute the script.

This example assumes the existence in the database of a HTML definition called HelloWorld_JS that contains some JavaScript:

```

Function IScript_TestJavaScript()

  %Response.WriteLine("<script src= " |
  %Response.GetJavaScriptURL(HTML.HelloWorld_JS) | "></script>");

End-Function;

```

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Internet Script Classes (iScript)," `GetJavaScriptURL`

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Application Designer Developer's Guide, "Creating HTML Definitions"

Using PeopleCode to Populate Key Fields in Search Dialog Boxes

In a PeopleSoft Pure Internet Architecture application, you typically want users to directly access their own data. To facilitate this, you may want to use `SearchInit` PeopleCode to populate standard key fields in search page fields and then make the fields unavailable for entry. You might assign the search key field a default value based on the user ID or alias the user entered when signing in.

You must also call the `AllowEmplIdChg` function, which enables users to change their own data. This function takes a single Boolean parameter in which you pass `True` to allow employees to change their own data.

Here is a simple example of such a `SearchInit` program, using `%EmployeeId` to identify the user:

```
EMPLID = %EmployeeId;

Gray (EMPLID);

AllowEmplIdChg (True);
```

Calling DLL Functions on the Application Server

To support processes running on an application server, you can declare and call functions compiled in Microsoft Windows DLLs and in UNIX shared libraries (or shared objects, depending on the specific UNIX platform). You can do this either with a special PeopleCode declaration, or using the business interlink framework.

When you call out to a DLL using PeopleCode, on Microsoft Windows NT application servers, the DLL file has to be on the path. On UNIX application servers, the shared library file must be on the library path (as defined for the specific UNIX platform).

The PeopleCode declaration and function call syntax remains unchanged. For example, the following PeopleCode could be used to declare and call a function `LogMsg` in an external library `Testdll.dll` on a Microsoft Windows client or a Windows application server, or a `libtestdll.so` on an UNIX application server. The UNIX shared library's extension varies by the specific UNIX platform.

```
Declare Function LogMsg Library "testdll" (string, string)
    Returns integer;

&res = LogMsg("\temp\test.log", "This is a test");
```

Sample Cross-Platform External Test Function

Following is the C source code for a sample cross-platform test file. It is a basic function that opens a log file and appends a line to it. If you compile the code using a C++ compiler, the functions must be declared using `extern C`, to ensure C-language linkage.

This file contains an interface function required for non-Microsoft-Windows environments. This function is compiled only when compiling for a non-Windows environment (for example, UNIX). The interface function references a provided header file, `pcmext.h`. The interface function is passed type codes that can be optionally used for parameter checking.

```

/*
 * Simple test function for calling from PeopleCode.
 * This is passed two strings, a file name and a message.
 * It creates the specified file and writes the message
 * to it.
 */
#include <stdlib.h>
#include <stdio.h>
#include <string.h>

#ifdef _WINDOWS
#define DLLEXPORT __declspec(dllexport)
#define LINKAGE __stdcall
#else
#define DLLEXPORT
#define LINKAGE
#endif

DLLEXPORT int LINKAGE LogMsg(char * fname, char * msg);

/*****
 * PeopleCode External call test function.
 *
 * Parameters are two strings (filename and message)
 * Result is 0 if error, 1 if OK
 *
 * To call this function, the following PeopleCode is
 * used
 *
 * Declare Function LogMsg Library "testdll"
 * (string, string)
 * Returns integer;
 *
 * &res = LogMsg("\temp\test.log", "This is a test");
 *****/

DLLEXPORT int LINKAGE LogMsg(char * fname, char * msg)
{
    FILE *fp;

    fp = fopen(fname, "a");          /* append */
    if (fp == NULL) return 0;

    fprintf(fp, "%s\n", msg);
    fclose(fp);
    return 1;
}

#ifdef _WINDOWS

/*****
 * Interface function.
 *
 * This is not needed for Windows....
 *****/

#include "pcmext.h"
#include "assert.h"

void LogMsg_intf(int nParam, void ** ppParams, EXTPARAMDESC * pDesc)

```

```
{
    int    rc;

    /* Some error checking */
    assert(nParam == 2);
    assert(pDesc[0].eExtType == EXTTYPE_STRING
        && pDesc[1].eExtType == EXTTYPE_STRING
        && pDesc[2].eExtType == EXTTYPE_INT);

    rc = LogMsg((char *)ppParams[0],
        (char *)ppParams[1]);
    *(int *)ppParams[2] = rc;
}

#endif
```

Updating the Installation and PSOPTIONS Tables

When an application updates either the PSOPTIONS or the Installation table it must call UpdateSysVersion from the SavePreChange PeopleCode event. This way, updates take effect at the next page load. Otherwise, the change does not take effect at the client workstation until the user signs out and signs back in.

Important! Only a database administrator or the equivalent should change these tables.

Chapter 8

Using Methods and Built-In Functions

This chapter provides an overview of restrictions on method and function use and discusses how to:

- Implement modal transfers.
- Implement the multi-row insert feature.
- Use the ImageReference field.
- Insert rows using PeopleCode.
- Use object linking and embedding (OLE) functions.
- Use the Select and SelectNew methods.
- Use standalone rowsets.
- Use errors and warnings.
- Use the RemoteCall feature.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions"

Understanding Restrictions on Method and Function Use

This section discusses:

- Think-time functions.
- WinMessage and MessageBox functions.
- Program execution with fields not in the data buffer.
- Errors and warnings.
- DoSave function.
- Record class database methods.
- SQL class methods and functions.

- Component interface restricted functions.
- SearchInit PeopleCode function restrictions.
- CallAppEngine function.
- ReturnToServer function.
- GetPage function.
- GetGrid function.
- Publish method.
- SyncRequest method.

Think-Time Functions

Think-time functions suspend processing either until the user has taken some action (such as clicking a button in a message box) or until an external process has run to completion (for example, a remote process).

Avoid think-time functions in the following PeopleCode events:

- SavePreChange.
- Workflow.
- RowSelect.
- SavePostChange.
- Any PeopleCode event that executes as a result of a ScrollSelect, ScrollSelectNew, RowScrollSelect, or RowScrollSelectNew function call.
- Any PeopleCode event that executes as a result of a Select or SelectNew rowset method.

Violation of this rule can result in application failure.

The following are think-time functions:

- Calls to an external DLL.
- DoCancel.
- DoModal.
- DoModalComponent.
- Exec (this is think-time only when synchronous).
- File attachment functions AddAttachment, ViewAttachment, and DetachAttachment.
- InsertImage.
- Object functions, such as CreateObject, ObjectDoMethod, ObjectSetProperty, and ObjectGetProperty (these are think-time only when the object requires user action).

- Prompt.
- RemoteCall.
- RevalidatePassword.
- WinExec (think-time only when synchronous).
- WinMessage and MessageBox (depending on the *style* parameter).

WinMessage and MessageBox Functions

The WinMessage and MessageBox functions sometimes behave as think-time functions, depending on the value passed in the function's *style* parameter, which controls, among other things, the number of buttons displayed in the message dialog box.

Note. The *style* parameter is ignored if the message has any severity other than Message.

Here is the syntax of both functions:

```
MessageBox(style, title, message_set, message_num, default_txt [, paramlist])
```

```
WinMessage(message [, style] [, title])
```

Note. The WinMessage function is supported for compatibility with previous releases of PeopleTools. New applications should use MessageBox instead.

If the *style* parameter specifies more than one button, the function behaves as a think-time function and is subject to the same restrictions as other think-time functions (that is, it should never be used from SavePreChange through SavePostChange PeopleCode, or in RowSelect).

If the *style* parameter specifies a single button (that is, the OK button), then the function can be called in any PeopleCode event.

Note. In the Microsoft Windows client, MessageBox dialog boxes include an Explain button to display more detailed information stored in the message catalog. The presence of the Explain button has no bearing on whether a message box behaves as a think-time function.

The *style* parameter is optional in WinMessage. If *style* is omitted, WinMessage displays OK and Cancel buttons, which causes the function to behave as a think-time function. To avoid this situation, always pass an appropriate value in the WinMessage *style* parameter.

The following table shows the values that can be passed in the *style* parameter. To calculate the value to pass, make one selection from each category in the table, then add the selections.

Category	Value	Constant	Meaning
Buttons	0	%MsgStyle_OK	The message box contains one button: OK.

Category	Value	Constant	Meaning
Buttons	1	%MsgStyle_OKCancel	The message box contains two buttons: OK and Cancel.
Buttons	2	%MsgStyle_AbortRetryIgnore	The message box contains three buttons: Abort, Retry, and Ignore.
Buttons	3	%MsgStyle_YesNoCancel	The message box contains three buttons: Yes, No, and Cancel.
Buttons	4	%MsgStyle_YesNo	The message box contains two buttons: Yes and No.
Buttons	5	%MsgStyle_RetryCancel	The message box contains two buttons: Retry and Cancel.

Note. The following values for *style* can only be used in the Microsoft Windows client. They have no affect in PeopleSoft Pure Internet Architecture.

Category	Value	Constant	Meaning
Default Button	0	%MsgDefault_First	The first button is the default.
Default Button	256	%MsgDefault_Second	The second button is the default.
Default Button	512	%MsgDefault_Third	The third button is the default.
Icon	0	%MsgIcon_None	None
Icon	16	%MsgIcon_Error	A stop-sign icon appears in the message box.
Icon	32	%MsgIcon_Query	A question-mark icon appears in the message box.

Category	Value	Constant	Meaning
Icon	48	%MsgIcon_Warning	An exclamation-point icon appears in the message box.
Icon	64	%MsgIcon_Info	An icon consisting of a lowercase letter <i>i</i> in a circle appears in the message box.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," MessageBox

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," WinMessage

Program Execution with Fields Not in the Data Buffer

Under certain conditions, when you access a field that is not in the data buffer, a portion of your PeopleCode program is skipped. The skip occurs when:

- The reference is in the Import Manager.
- The reference is from the FieldDefault or FieldFormula events.

After the call to the invalid field, execution skips to the next top-level statement. Top-level statements are not nested inside other statements. The start of a PeopleCode program is a top-level statement. Nesting begins with the first conditional statement (such as While or If) or the first function call.

For example, if your code is executing in a function and inside an If ... then ... end-if statement, and it runs into the skip conditions, the next statement executed is the one after the End-if statement, still inside the function.

Errors and Warnings

Errors and warnings should not be used in FieldDefault, FieldFormula, RowInit, FieldChange, RowInsert, SavePreChange, WorkFlow, and SavePostChange PeopleCode events. An error or warning in these events causes a runtime error that forces cancellation of the component.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Warning

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Error

DoSave Function

Use DoSave only in FieldEdit, FieldChange, or MenuItemSelected PeopleCode events.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," DoSave

Record Class Database Methods

You use the following record class methods to update the database:

- Delete
- Insert
- Save
- Update

Only use these methods in the following events (events that allow database updates):

- SavePreChange
- WorkFlow
- SavePostChange
- FieldChange
- Application Engine PeopleCode action

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Record Class"

SQL Class Methods and Functions

Use the SQL class to update the database. Use these functions and methods only in the following events (events that allow database updates):

- SavePreChange
- WorkFlow
- SavePostChange
- FieldChange
- Application Engine PeopleCode action

Component Interface Restricted Functions

PeopleCode events and functions that relate exclusively to graphical user interfaces and online processing cannot be used by component interfaces. These include:

- Menu PeopleCode and pop-up menus.

The ItemSelected and PrePopup PeopleCode events are not supported. In addition, the DisableMenuItem, EnableMenuItem, and HideMenuItem functions are not supported.

- Transfers between components, including modal transfers.

The DoModal, EndModal, IsModal, Transfer, TransferPage, DoModalComponent, and IsModalComponent functions cannot be used.

- Cursor positioning by the SetCursorPos function.
- The SetControlValue function.
- The WinMessage function.

When executed using a component interface, these functions do nothing and return a default value.

Using the Transfer function terminates the current PeopleCode program.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Component Interfaces, "Programming Component Interfaces Using PeopleCode"

SearchInit PeopleCode Function Restrictions

You cannot use the following functions in SearchInit PeopleCode:

- DoModal

- DoModalComponent
- Transfer
- TransferPage

CallAppEngine Function

Use the CallAppEngine function only in events that allow database updates, because, generally, if you are calling Application Engine, you intend to perform database updates. This category of events includes the following PeopleCode events:

- SavePreChange (Page)
- SavePostChange (Page)
- Workflow
- FieldChange

CallAppEngine cannot be used in a Application Engine PeopleCode action. If you need to access one Application Engine program from another Application Engine program, use the CallSection action.

See Also

Enterprise PeopleTools 8.50 PeopleBook: Application Engine, "Creating Application Engine Programs"

ReturnToServer Function

The ReturnToServer function returns a value from a PeopleCode application messaging program to the publication or subscription server. You would use this in either your publication or subscription routing code, not in one of the standard Component Processor events.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Integration Broker, "Managing Messages"

GetPage Function

The GetPage function cannot be used until after the Component Processor has loaded the page. You should not use this function in an event prior to the PostBuild event.

See Also

Chapter 6, "PeopleCode and the Component Processor," page 89

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," GetPage

GetGrid and GetAnalyticGrid Functions

PeopleSoft builds a grid one row at a time. Because the grid and AnalyticGrid classes apply to a complete grid, you cannot use either the GetGrid or GetAnalyticGrid functions in an event prior to the Activate event.

See Also

Chapter 6, "PeopleCode and the Component Processor," page 89

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," GetGrid

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Analytic Grid Classes"

Publish Method

If you are using PeopleSoft Integration Broker, your sending PeopleCode should go in the SavePostChange event, for either the record or the component.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Integration Broker, "Managing Messages"

SyncRequest Method

If you are using PeopleSoft Integration Broker, your SyncRequest PeopleCode should go in the SavePostChange event, for either the record or the component.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Integration Broker, "Managing Messages"

Implementing Modal Transfers

This section provides an overview of modal transfers and discusses how to implement modal transfers.

Understanding Modal Transfers

When you use modal transfers to transfer from one component (the *originating* component) to another component (the *modal* component), the user must click the OK or Cancel buttons on the modal component before returning to the originating component.

Modal transfers provide some control over the order in which the user fills in pages, which is useful where data in the originating component can be derived from data entered by the user into the modal component.


Limit use of this feature, as it forces users to complete interaction with the modal page before returning to the main component.

Note. Modal transfers cannot be initiated from SearchInit PeopleCode.

A modal component resembles a Microsoft Windows modal dialog box. It displays three buttons: OK, Cancel, and Apply. No toolbars or windows are available while the modal component has the focus. The OK button saves changes to the modal component and returns the user to the originating component. The Apply button saves changes to the modal component without returning to the originating component. The Cancel button returns the user to the originating component without saving changes to the modal component.

Modal components are generally smaller than the page from which they are invoked. Remember that OK and Cancel buttons are added at runtime, thus increasing the size of the pages.

The originating component and the modal component share record fields in a derived/work record called a *shared work record*. The derived/work fields of this record provide the two components with an area in memory where they can share data. Edit boxes in both components are associated with the same derived/work field, so that changes made to this field in the originating component are reflected in the modal component, and vice versa. The following diagram illustrates this shared memory:



Edit boxes on the originating and modal components share the same data

Edit boxes associated with the same derived/work fields must be placed at level zero in both the originating component and the modal component.

You can use the shared fields to:

- Pass values assigned to the search keys in the modal component search record.

If these fields are missing or invalid, the search page appears, enabling the user to enter search keys.

- Pass other values from the originating component to the modal component.
- Pass values back from the modal component to the originating component.

Implementing Modal Transfers

Any component accessible through an application menu system can be accessed using a modal transfer. However, to implement a modal transfer, you must modify pages in both the originating component and the modal component. After these modifications are complete, you can implement the modal transfer using the `DoModalComponent` function from a page in the originating component.

Before beginning this process, you should answer the following questions:

- Should the originating component provide search key values for the modal component?
If so, what are the search keys? (Check the modal component's search record.)
- Does the originating component need to pass any data to the modal component?
If so, what record fields are needed to store this data?
- Does the modal component need to pass any data back to the originating component?
If so, what record fields are needed to store this data?

To implement a modal transfer:

1. Create derived/work record fields for sharing data between the originating and modal components.

Create a new derived/work record or open an existing derived/work record. If suitable record fields exist, you can use them; otherwise create new record fields for any data that needs to be shared between the components. These can be search keys for the modal component, data to pass to the modal component, or data to pass back to the originating component.

2. Add derived work fields to the level-zero area of the originating component.

Add one edit box for each of the derived/work fields that you need to share between the originating and modal components to the level-zero area of the page from which the transfer will take place. You probably want to make the edit boxes invisible.

3. Add the same derived work fields to the level-zero area of the modal component.

Add one edit box for each of the edit boxes that you added in the previous step to the level-zero area of the page to which you are transferring. You probably want to make the edit boxes invisible.

4. Add `PeopleCode` to pass values into the derived/work fields in the originating component.

To provide search key values or pass data to the modal page, write `PeopleCode` that assigns appropriate values to the derived/work fields before `DoModalComponent` is called.

For example, if the modal component search key is `PERSONAL_DATA.EMPLID`, you could place the following assignment statement in the derived/work field's `RowInit` event:

```
EMPLID = PERSONAL_DATA.EMPLID
```

You also might assign these values in the same program where `DoModalComponent` is called.

5. Add PeopleCode to access and change the derived/work fields in the modal component.

No PeopleCode is required to pass search key values during the search. However, if other data has been passed to the modal component, you may need PeopleCode to access and use the data. You may also need to assign new values to the shared fields so that they can be used by the originating component.

It is possible that the component was accessed through the menu system and not through a modal transfer. To write PeopleCode that runs only in the component when it is running modally, use the `IsModalComponent` function:

```
If IsModalComponent() Then
    /* PeopleCode for modal execution only. */
End-If
```

6. Add PeopleCode to access changed derived/work fields in the originating component.

If the modal component has altered the data in the shared work fields, you can write PeopleCode to access and use the data after `DoModalComponent` has executed.

Note. You can use the `EndModalComponent` function as a programmatic implementation of the OK and Cancel buttons.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," `DoModalComponent`

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," `IsModal`

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," `EndModalComponent`

Implementing the Multi-Row Insert Feature

Enabling the multi-row insert feature in grids or scroll areas can reduce response times for transactions that usually require entering many rows of data. With the multi-row feature, users specify the number of rows to add to a grid or scroll area, and empty rows appear for data entry.

This feature cannot be used with effective-dated grids or scroll areas. In addition, the feature may not apply if the entire row is populated using PeopleCode, especially if the data is copied from prior rows. If the feature does apply in this case, the default value of the `ChangeOnInit` property can be used (the default value is `True`, which means any PeopleCode updates done in the `RowInit` or `RowInsert` events set the `IsChanged` and `IsNew` properties to `True`).

To use the multi-row insert feature:

1. Specify deferred mode processing.

The multi-row feature reduces transaction times by eliminating excess server trips. To take full advantage of this feature, the transaction should be set to execute in deferred mode. Deferred mode should be set for the component, all pages in the component, and all fields on those pages.

2. Enable the multi-row feature.

For each grid or scroll area where appropriate, select the Allow Multi-row Insert check box under the Use tab in the grid or scroll area property sheet.

3. Add ChangeOnInit PeopleCode.

Setting the ChangeOnInit property for a rowset to False enables PeopleCode to modify data in the rowset during RowInit and RowInsert events without flagging the rows as changed. This ensures that only user changes cause the affected row to be saved.

Note. Each rowset that is referenced by a grid or scroll area with the multi-row feature enabled should have the ChangeOnInit property for the rowset set to False. This includes lower-level rowsets. In addition, this property must be set prior to any RowInsert or RowInit PeopleCode for the affected row.

4. Empty rows at save.

After a transaction is saved, any empty rows are discarded before the page is redisplayed to the user. An empty row means that the user did not access the data because PeopleCode or record defaults may have been used to initialize the row for the initial display.

Note. PeopleCode save processing (SaveEdit and SavePreChange) PeopleCode executes for all rows in the buffer (including the empty ones). Therefore, SaveEdit and SavePreChange PeopleCode should be coded so that it is executed only if the field contains data, or if the row properties IsNew and IsChanged are both True. An alternative method is adding PeopleCode in the first save program in the component, to explicitly delete any row based on the IsNew and IsChanged properties. If you choose this method, then rows should be deleted from the bottom of the data buffer to the top (last row first).

See Also

Chapter 6, "PeopleCode and the Component Processor," Deferred Processing Mode, page 127

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Rowset Class," ChangeOnInit

Using the ImageReference Field

To associate an image definition with a field at runtime, the field has to be of type ImageReference. An example of this is referencing a red, yellow, or green light on a page, depending on the context.

To change the image value of an ImageReference field:

1. Create a field of type ImageReference.
2. Create the images you want to use.

These images must be saved in PeopleSoft Application Designer as image definitions.

3. Add the field to a record that will be accessed by the page.
4. Add an image control to the page and associate the image control with the ImageReference field.

5. Assign the field value.

Use the keyword **Image** to assign a value to the field. For example:

```
Local Record &MyRec;
Global Number &MyResult;

&MyRec = GetRecord();
If &MyResult Then
    &MyRec.MyImageField.Value = Image.THUMBSUP;
Else
    &MyRec.MyImageField.Value = Image.THUMBSDOWN;
End-If;
```

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Application Designer Developer's Guide, "Creating Field Definitions"

Inserting Rows Using PeopleCode

When inserting rows using PeopleCode, you can either use the Insert method with a record object or create a SQL Insert statement using the SQL object. If you do a single insert, use the Record Insert method. If you are in a loop and, therefore, calling the insert more than once, use the SQL object. The SQL object uses dedicated cursors and, if the database you are working with supports it, bulk insert.

A *dedicated cursor* means that the SQL gets compiled only once on the database, so PeopleTools looks for the meta-SQL only once. This can increase performance.

For *bulk insert*, inserted rows are buffered and sent to the database server only when the buffer is full or a commit occurs. This reduces the number of round-trips to the database. Again, this can increase performance.

The following is an example of using the Record Insert method:

```
&REC = CreateRecord(Record.GREG);
&REC.DESCR.Value = "Y" | &I;
&REC.EMPLID.Value = &I;
&REC.Insert();
```

The following is an example using a SQL object to insert rows:

```
&SQL = CreateSQL("%INSERT(:1)");
&REC = CreateRecord(Record.GREG);
&SQL.BulkMode = True;
For &I = 1 to 10
    &REC.DESCR.Value = "Y" | &I;
    &REC.EMPLID.Value = &I;
    &SQL.Execute(&REC);
End-For;
```

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Record Class," Insert

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "SQL Class"

Using OLE Functions

This section provides an overview of OLE functions and discusses how to:

- Use the Object data type.
- Share a single object instance.
- Use the Exec and WinExec functions.

Understanding OLE Functions

OLE automation is a Microsoft Windows protocol that enables one application to control another's operation. The applications communicate by means of an OLE object. One of the applications (called the automation server) makes available an OLE object that the second application (the client application) can use to send commands to the server application. The OLE object has methods associated with it, each of which corresponds to an action that the server application can perform. The client runs the methods, which cause the server application to perform the specified actions.

PeopleCode includes a set of functions that enable your PeopleCode program to be an OLE client. You can connect to any application that's registered as an OLE automation server and invoke its methods.

Note. Differences in Microsoft Windows applications from one release to the next (that is, properties becoming methods or vice versa) can cause problems with the ObjectGetProperty, ObjectSetProperty and ObjectDoMethod functions.

See the documentation for the OLE-automated application.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions"

Using the Object Data Type

To support OLE, PeopleCode has a special data type, Object, which it uses for OLE objects. The purpose of the Object data type is to hold OLE objects during the course of a session so that you can run its methods. You cannot store Object data for any extended period of time.

Important! Object is a valid data type for variables, but not for record fields. Because OLE objects are by nature temporary, you cannot store Object data in a record field, including work record fields.

Some OLE object methods return data to the client. You can use such methods to get data from the automation server, if the method returns the data in a PeopleCode-supported data type. If the method returns data in an spreadsheet, for example, you cannot accept the data, because PeopleCode does not support spreadsheets.

Sharing a Single Object Instance

When you need the services of an OLE automation server, you create an instance of its OLE object, using the CreateObject function. After you have the object, you can run its methods as often as you like. You do not need to create a new instance of the object each time.

In a typical scenario, you have a PeopleSoft component that needs to access Microsoft Excel or Word, or some other automation server, perhaps one you have created yourself. Various PeopleCode programs associated with the component must run OLE object methods.

Rather than create a new instance of the OLE object in each PeopleCode program, you should create one instance of the OLE object in a PeopleCode program that runs when the component starts (such as RowInit) and assign it to a global variable. Then, any PeopleCode program can reference the object and invoke its methods.

Using the Exec and WinExec Functions

The WinExec and Exec built-in functions provide another way to start another application from PeopleCode. Unlike the OLE functions, however, Exec and WinExec do not enable you to control what actions the application takes after you start it. You can start the application, and if you use the synchronous option you can find out when it closes, but you cannot affect its course or receive any data in return.

WinExec is appropriate in two situations:

- When you want to start an application and continue processing.
- When you have a short, unvarying process that you want to run, such as copying a file.

The Exec function, unlike WinExec and the OLE functions, is not Microsoft Windows-specific. You can run it on an application server to call an executable on the application server platform, which in PeopleTools release 7 and later can be either Windows NT or UNIX.

Important! If you use the WinExec function with its synchronous option, the PeopleCode program (and the PeopleSoft application) remain paused until the called program is complete. If you start a program that waits for user input, such as Notepad, the application appears to hang until the user closes the called program. The synchronous option also imposes limits on the PeopleCode.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Exec

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," WinExec

Using the Select and SelectNew Methods

This section provides an overview of the Select method and discusses how to use the Select method.

Understanding the Select and SelectNew Methods

The Select and SelectNew methods, like the ScrollSelect functions, enable you to control the process of selecting data into a page scroll area. The Select method selects rows from a table or view and adds the rows to either a rowset or a row. Let's call the record definition of the table or view that it selected from the *select record*. Let's call the primary database record of the top-level rowset object executing the method the *default scroll record*.

The select record can be the same as the default scroll record, or it can be a different record definition that has the same key fields as the default scroll record. If you define a select record that differs from the default scroll record, you can restrict the number of fields loaded into the buffers by including only the fields you actually need.

You can use these methods only with a rowset. A rowset can be thought of as a page scroll area.

A level zero rowset starts at the top level of the page, level zero, and contains all the data in the component buffers. A child rowset is contained by an upper-level rowset, also called the parent rowset. For example, a level one rowset could be considered the child rowset of a level zero, or parent, rowset. Or a level two rowset could be the child rowset of a level one rowset. The data contained in a child rowset depends on the row of the parent rowset.

When a rowset is selected into, any autoselected child rowsets are also read. The child rowsets are read using a Where clause that filters the rows according to the Where clause used for the parent rowset, using a Subselect.

The Select method automatically places child rowsets in the rowset object executing the method under the correct parent row. If it cannot match a child rowset to a parent row, an error occurs.

The Select method also accepts an optional SQL string that can contain a Where clause restricting the number of rows selected into the scroll area. The SQL string can also contain an Order By clause, enabling you to sort the rows.

The Select and SelectNew methods generate an SQL Select statement at runtime, based on the fields in the select record and the Where clause passed to them in the function call. This gives Select and SelectNew a significant advantage over the SQLExec function: they enable you to change the structure of the select record without affecting the PeopleCode program, unless the field affected is referred to in the Where clause string. This can make the application easier to maintain.

Also, if you use one of the meta-SQL constructs or shortcuts in the Where clause, such as %KeyEqual or %List, even if a field has changed, you do not have to change your code.

Unlike the ScrollSelect functions, neither Select or SelectNew allow you to operate in turbo mode.

Note. In addition to these methods, the SelectByKey record class method enables you to select into a record object. If you're only interested in selecting a single row of data, consider this method instead.

See Also

[Chapter 5, "Accessing the Data Buffer," page 67](#)

Using the Select Method

The syntax of the Select method is:

```
select ([paramlist], RECORD.selrecord [, wherestr, bindvars]);
```

Where *paramlist* is a list of child rowsets, given in the following form:

```
SCROLL.scrollname1 [SCROLL., scrollname2] . . .
```

The first *scrollname* must be a child rowset of the rowset object executing the method, the second *scrollname* must be a child of the first child, and so on.

This syntax does the following:

- Specifies an optional child rowset into which to read the selected rows.
- Specifies the select record from which to select rows.
- Passes a string containing a SQL Where clause to restrict the selection of rows or an Order By clause to sort the rows, or both.

Specifying Child Rowsets

The first part of the Select syntax specifies a child rowset into which rows are selected. This parameter is optional.

If you do not specify any child rowsets in *paramlist*, Select selects from a SQL table or view specified by *selrecord* into the rowset object executing the method. For example, suppose you've instantiated a level one rowset &BUS_EXPENSES_PER. The following would select into this rowset:

```
Local Rowset &BUS_EXPENSES_PER;

&BUS_EXPENSES_PER = GetRowset(SCROLL.BUS_EXPSNESE_PER);
&BUS_EXPENSES_PER.Select(RECORD.BUS_EXPENSE_VW,
"WHERE SETID = :1 and CUST_ID = :2", SETID, CUST_ID);
```

If the rowset executing the method is a level zero rowset, and you specify the Select method without specifying any child rowsets with *paramlist*, the method reads only a single row, because only one row is allowed at level zero.

Note. For developers familiar with previous releases of PeopleCode: In this situation, the Select method is acting like the RowScrollSelect function.

If you specify a child rowset in *paramlist*, the Select method selects from a SQL table or view specified by *selrecord* into the child rowset specified in *paramlist*, under the appropriate row of the rowset executing the method.

In the following example, rows are selected into a child rowset BUS_EXPENSE_DTL, matching level-one keys, and with the charge amount equal to or exceeding 200, sorting by that amount:

```
Local Record &REC_EXP;
Local Rowset &BUS_EXPENSE_PER;

&REC_EXP = GetRecord(RECORD.BUSINESS_EXPENSE_PER;
&BUS_EXPENSE_PER = GetRowset(SCROLL.BUS_EXPENSE_PER);
&BUS_EXPENSE_PER.Select(SCROLL.BUS_EXPENSE_DTL,
RECORD.BUS_EXPENSE_DTL, "WHERE %KeyEqual(:1) AND EXPENSE_AMT
>= 200 ORDER BY EXPENSE_AMT", &REC_EXP);
```

Specifying the Select Record

The record definition of the table or view being selected from is called the *select record*, and identified with RECORD.*selrecord*. The select record can be the same as the primary database record associated with the rowset executing the method, or it can be a different record definition that has compatible fields.

The select record must be defined in PeopleSoft Application Designer and be a built SQL table or view (using Build, Project), unless the select record is the same record as the primary database record associated with the rowset.

The select record can contain fewer fields than the primary record associated with the rowset, although it must contain any key fields to maintain dependencies with other records.

If you define a select record that differs from the primary database record for the rowset, you can restrict the number of fields that are loaded into the buffers on the client work station by including only the fields you actually need.

The Where Clause

The Select method accepts a SQL string that can contain a Where clause restricting the number of rows selected into the object. The SQL string can also contain an Order By clause to sort the rows.

Select and SelectNew generate a SQL Select statement at runtime, based on the fields in the select record and the Where clause passed to them in the method parameters.

To avoid errors, the Where clause should explicitly select matching key fields on parent and child rows. You do this using the %KeyEqual meta-SQL.

Select Like RowScrollSelect

If the rowset executing the method is a level zero rowset, and you specify Select without specifying any child rowsets with *paramlist*, the method reads only a single row, because only one row is allowed at level zero.

Note. For developers familiar with previous releases of PeopleCode: In this situation, the Select method is acting like the RowScrollSelect function.

If you qualify the lower-level rowset so that it only returns one row, it acts like the RowScrollSelect method.

```
&RSLVL1 = GetRowset(SCROLL.PHYSICAL_INV);
&RSLVL2 = &RSLVL1(&PHYSICAL_ROW).GetRowset(SCROLL.PO_RECEIVED_INV);
&REC2 = &RSLVL2.PO_RECEIVED_INV;
If &PO_ROW = 0 Then
    &RSLVL2.Select(PO_RECEIVED_INV, "WHERE %KeyEqual(:1)
and qty_available > 0", &REC2);
End-if;
```

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "Meta-SQL," %KeyEqual

Using Standalone Rowsets

This section provides an overview of standalone rowsets and discusses how to:

- Use the Fill rowset method.
- Use the CopyTo rowset method.
- Add child rowsets.
- Use standalone rowsets to write a file.
- Use standalone rowsets to read a file.

Understanding Standalone Rowsets

Standalone rowsets are not associated with a component or page. Use them to work on data that is not associated with a component or page buffer. In earlier releases, this was done using derived work records. You still must build work pages.

Note. Standalone rowsets are not connected to the Component Processor, so there are no database updates when they are manipulated. Delete and insert actions on these types of rowsets are not automatically applied at save time.

As with any PeopleTools object, the scope of standalone rowsets can be Local, Global, or Component. Consider the following code:

```
Local Rowset &MYRS;

&MYRS = CreateRowset(RECORD.SOMEREC);
```

This code creates a rowset with SOMEREC as the level zero record. The rowset is unpopulated. Functionally, it is the same as an array of rows.

Using the Fill Method

The Fill method fills the rowset by reading records from the database, by first flushing out all the contents of the rowset. A Where clause must be provided to get all the relevant rows.

```
Local Rowset &MYRS;
Local String &EMPLID;

&MYRS = CreateRowset(RECORD.SOMEREC);
&EMPLID = '8001';

&MYRS.Fill("where EMPLID = :1", &EMPLID);
```

Use the Fill method with standalone rowsets, created using the CreateRowset function. Do not use Fill with component buffer rowsets.

Using the CopyTo Method

The CopyTo method copies like-named fields from a source rowset to a destination rowset. To perform the copy, it uses like-named records for matching, unless specified. It works on any rowset except the Application Engine state records. The following is an example:

```
Local Rowset &MYRS1, MYRS2;
Local String &EMPLID;

&MYRS1 = CreateRowset(RECORD.SOMEREC);
&MYRS2 = CreateRowset(RECORD.SOMEREC);

&EMPLID = '8001';

&MYRS1.Fill("where EMPLID = :1", &EMPLID);
&MYRS1.CopyTo(&MYRS2);
```

After running the previous code segment, &MYRS2 contains that same data as &MYRS1. Both &MYRS1 and &MYRS2 were built using like-named records.

To use the CopyTo method where there are no like-named records, you must specify the source and destination records. The following code copies only like-named fields:

```
Local Rowset &MYRS1, MYRS2;
Local String &EMPLID;

&MYRS1 = CreateRowset(RECORD.SOMEREC1);
&MYRS2 = CreateRowset(RECORD.SOMEREC2);

&EMPLID = '8001';

&MYRS1.Fill("where EMPLID = :1", &EMPLID);
&MYRS1.CopyTo(&MYRS2, RECORD.SOMEREC1, RECORD.SOMEREC2);
```

Adding Child Rowsets

The first parameter of the `CreateRowset` method determines the top-level structure. If you pass the name of the record as the first parameter, the rowset is based on a record. You can also base the structure on a different rowset. In the following example, `&MYRS2` inherits the structure of `&MYRS1`:

```
Local Rowset &MYRS1, MYRS2;

&MYRS1 = CreateRowset(RECORD.SOMEREC1);
&MYRS2 = CreateRowset(&MYRS1);
```

To add a child rowset, suppose the following records describe a relationship. The structure is made up of three records:

- PERSONAL_DATA
- BUS_EXPENSE_PER
- BUS_EXPENSE_DTL

To build rowsets with child rowsets, use code like the following:

```
Local Rowset &rsBusExp, &rsBusExpPer, &rsBusExpDtl;


&rsBusExpDtl = CreateRowset(Record.BUS_EXPENSE_DTL);
&rsBusExpPer = CreateRowset(Record.BUS_EXPENSE_PER, &rsBusExpDtl);
&rsBusExp = CreateRowset(Record.PERSONAL_DATA, &rsBusExpPer);
```

Another variation is

```
&rsBusExp = CreateRowset(Record.PERSONAL_DATA,
CreateRowset(Record.BUS_EXPENSE_PER,
CreateRowset(Record.BUS_EXPENSE_DTL)));
```

Using Standalone Rowsets to Write a File

The following is an example of using standalone rowsets along with a file layout to write a file:



File layout example

The following example writes a file using a file layout that contains parent-child records:

```

Local File &MYFILE;
Local Rowset &rsBusExp, &rsBusExpPer, &rsBusExpDtl;
Local Record &rBusExp, &rBusExpPer, &rBusExpDtl;
Local SQL &SQL1, &SQL2, &SQL3;

&rBusExp = CreateRecord(Record.PERSONAL_DATA);
&rBusExpPer = CreateRecord(Record.BUS_EXPENSE_PER);
&rBusExpDtl = CreateRecord(Record.BUS_EXPENSE_DTL);

&rsBusExp = CreateRowset(Record.PERSONAL_DATA,
CreateRowset(Record.BUS_EXPENSE_PER,
CreateRowset(Record.BUS_EXPENSE_DTL)));
&rsBusExpPer = &rsBusExp.GetRow(1).GetRowset(1);

&MYFILE = GetFile("c:\temp\BUS_EXP.out", "W", %FilePath_Absolute);
&MYFILE.SetFileLayout(FileLayout.BUS_EXP_OUT);

&EMPLID = "8001";

&SQL1 = CreateSQL("%selectall(:1) where EMPLID = :2", &rBusExp, &EMPLID);
&SQL2 = CreateSQL("%selectall(:1) where EMPLID = :2", &rBusExpPer, &EMPLID);

While &SQL1.Fetch(&rBusExp)
    &rBusExp.CopyFieldsTo(&rsBusExp.GetRow(1).PERSONAL_DATA);
    &I = 1;
    While &SQL2.Fetch(&rBusExpPer)
        &rBusExpPer.CopyFieldsTo(&rsBusExpPer(&I).BUS_EXPENSE_PER);
        &J = 1;
        &SQL3 = CreateSQL("%selectall(:1) where EMPLID = :2
and EXPENSE_PERIOD_DT = :3", &rBusExpDtl, &EMPLID,
&rBusExpPer(&I).BUS_EXPENSE_PER.EXPENSE_PERIOD_DT.Value);
        &rsBusExpDtl = &rsBusExpPer.GetRow(&I).GetRowset(1);
        While &SQL3.Fetch(&rBusExpDtl)
            &rBusExpDtl.CopyFieldsTo(&rsBusExpDtl(&J).BUS_EXPENSE_DTL);
            &rBusExpDtl.InsertRow(&J);
            &J = &J + 1;
        End-While;

        &rsBusExpPer.InsertRow(&I);
        &I = &I + 1;
    End-While;
    &MYFILE.WriteRowset(&rsBusExp);
End-While;
&MYFILE.Close();

```

The previous code generates the following output file.

AA8001	Schumacher, Simon		
BB8001	06/11/1989YNA0	Customer Go-Live Celebration	
CC8001	06/11/1989		
	06/01/198908226.83	USDEntertain Clients	⇒
10100			
BB8001	08/31/1989YNA0	Customer Focus Group Meeting	
CC8001	08/31/198908/11/1989012401.58	USDCustomer Visit	⇒
10100			
CC8001	08/31/198908/12/198904250.48	USDCustomer Visit	⇒
10100			
CC8001	08/31/198908/12/198902498.34	USDCustomer Visit	⇒
10100			
BB8001	03/01/1998YYP0	Attend Asia/Pacific Conference	
CC8001	03/01/199802/15/1998011200	USDConference	⇒
00001			
CC8001	03/01/199802/16/19980220000	JPYConference	⇒
00001			
BB8001	05/29/1998NNP0	Annual Subscription	
CC8001	05/29/199805/29/199814125.93	USDSoftware, Inc.	⇒
10100			
BB8001	08/22/1998NNP0	Regional Users Group Meeting	
CC8001	08/22/199808/22/19981045.69	USDDrive to Meeting	⇒
10100			
CC8001	08/22/199808/22/19980912.44	USDCity Parking	⇒
10100			
BB8001	12/12/1998NNP0	Customer Visit: Nevco	
CC8001	12/12/199812/02/199801945.67	USDCustomer Feedback	⇒
00001			
CC8001	12/12/199812/02/19981010.54	USDTo Airport	⇒
00001			
CC8001	12/12/199812/03/19980610	USDAirport Tax	⇒
00001			
CC8001	12/12/199812/03/199804149.58	USDCustomer Feedback	⇒
00001			
CC8001	12/12/199812/04/1998055.65	USDCheck Voicemail	⇒
00001			
CC8001	12/12/199812/04/19980988	USDAirport Parking	⇒
00001			
CC8001	12/12/199812/04/199802246.95	USDCustomer Feedback	⇒
00001			
CC8001	12/12/199812/04/199803135.69	USDCustomer Feedback	00001

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Application Designer Developer's Guide, "Constructing File Layouts and Performing Data Interchanges"

Using Standalone Rowsets to Read a File

The following code shows an example of reading in a file and inserting the rows into the database:

```

Local File &MYFILE;
Local Rowset &rsBusExp, &rsBusExpPer, &rsBusExpDtl;
Local Record &rBusExp, &rBusExpPer, &rBusExpDtl;
Local SQL &SQL1;

&rBusExp = CreateRecord(Record.PERSONAL_DATA);
&rBusExpPer = CreateRecord(Record.BUS_EXPENSE_PER);
&rBusExpDtl = CreateRecord(Record.BUS_EXPENSE_DTL);

&rsBusExp = CreateRowset(Record.PERSONAL_DATA,
CreateRowset(Record.BUS_EXPENSE_PER,
CreateRowset(Record.BUS_EXPENSE_DTL)));

&MYFILE = GetFile("c:\temp\BUS_EXP.out", "R", %FilePath_Absolute);
&MYFILE.SetFileLayout(FileLayout.BUS_EXP_OUT);

&SQL1 = CreateSQL("%Insert(:1)");

&rsBusExp = &MYFILE.ReadRowset();
While &rsBusExp <> Null;
    &rsBusExp.GetRow(1).PERSONAL_DATA.CopyFieldsTo(&rBusExp);
    &rsBusExpPer = &rsBusExp.GetRow(1).GetRowset(1);
    For &I = 1 To &rsBusExpPer.ActiveRowCount
        &rBusExpPer(&I).BUS_EXPENSE_PER.CopyFieldsTo(&rBusExpPer);
        &rBusExpPer.ExecuteEdits(%Edit_Required);
        If &rBusExpPer.IsEditError Then
            For &K = 1 To &rBusExpPer.FieldCount
                &MYFIELD = &rBusExpPer.GetField(&K);
                If &MYFIELD.EditError Then
                    &MSGNUM = &MYFIELD.MessageNumber;
                    &MSGSET = &MYFIELD.MessageSetNumber;
                End-If;
            End-For;
        Else
            &SQL1.Execute(&rBusExpPer);
            &rsBusExpDtl = &rBusExpPer.GetRow(&I).GetRowset(1);
            For &J = 1 To &rsBusExpDtl.ActiveRowCount
                &rBusExpDtl(&J).BUS_EXPENSE_DTL.CopyFieldsTo(&rBusExpDtl);
                &rBusExpDtl.ExecuteEdits(%Edit_Required);
                If &rBusExpDtl.IsEditError Then
                    For &K = 1 To &rBusExpDtl.FieldCount
                        &MYFIELD = &rBusExpDtl.GetField(&K);
                        If &MYFIELD.EditError Then
                            &MSGNUM = &MYFIELD.MessageNumber;
                            &MSGSET = &MYFIELD.MessageSetNumber;
                        End-If;
                    End-For;
                Else
                    &SQL1.Execute(&rBusExpDtl);
                End-If;
            End-For;
        End-If;
    End-For;
    &rsBusExp = &MYFILE.ReadRowset();
End-While;
&MYFILE.Close();

```

Using Errors and Warnings

For the most part, errors and warnings display messages to users informing them about invalid data. For this reason, they are almost always placed in `FieldEdit` or `SaveEdit` PeopleCode, or in `SearchSave` PeopleCode for validation during search processing. In conjunction with edits, errors stop processing, while warnings allow processing to continue. When errors and warnings appear in places other than `FieldEdit` or `SaveEdit`, their effects vary.

This section discusses how to:

- Use errors and warning syntax.
- Use errors and warnings in edit events.
- Use errors and warnings in `RowSelect` events.
- Use errors and warnings in `RowDelete` events.
- Use errors and warnings in other events.

Using Error and Warning Syntax

Errors and warnings require only a message that the Component Processor displays to users. You can code the message into the error or warning statement, or you can use the message catalog. Use the message catalog with the `MsgGet`, `MsgGetExplainText`, and similar functions.

Errors and warnings use the same syntax. For example:

```
Error MsgGet(11100, 180, "Message not found.");  
Warning MsgGet(11100, 180, "Message not found.");
```

Using Errors and Warnings in Edit Events

You can use the following PeopleCode events for validation edits: `FieldEdit` and `SaveEdit`. The Component Processor applies `FieldEdit` when the user changes a field, and `SaveEdit` when the user saves a component. Errors and warnings in these events display a message. Most errors and warnings appear in these event types, although you can use errors and warnings elsewhere.

FieldEdit Event Errors

You can use either the record field or component record field event. The record field event for each record runs before the component record field event for that record.

An error in `FieldEdit` prevents the system from accepting the new value of a field. The Component Processor highlights the problem field. The user must either change the field back to its original value or to something else which does not trigger the error. A warning enables the Component Processor to accept the new data. The Component Processor does not highlight a field that has warnings.

SaveEdit Event Errors

You can use the record field or the component record event. All record field events for a record run before the component record events.

An error in SaveEdit prevents the system from saving any row of data. The Component Processor does not update the database for any field if one field has an error. Although the Component Processor displays an error message, it does not turn any field red. Unlike FieldEdit errors, SaveEdit errors can happen anywhere on a page or component, for any row of data. The data causing the error may appear on a different page within the same group, or a row of data not currently displayed. If this is the case, the field in error is brought into view by the system.

A warning in SaveEdit also is applied to all data in the page or component, but the Component Processor will accept the data, if told to by the user. In a FieldEdit warning, the Component Processor displays a message box with the text and two buttons: OK and the standard Explain (the Explain button returns an explanation for the last message retrieved with the MsgGet function). In a SaveEdit warning, the message box contains an additional button, Cancel. OK accepts the data, overriding the warning and continuing the save process. Cancel ends the save process.

Because errors and warnings apply to all rows of data and all pages in a group, you must provide the user explicit information about what caused the error. Typically, you use the message catalog function to store messages and substitute variables into them. However, you can also facilitate this by concatenating in a field value. For example, if you have a stack of historical data on the page, you could use the following error statement:

```
Error ("The value exceeds the maximum on "|effdt|".");
```

Using Errors and Warnings in RowSelect Events

RowSelect PeopleCode filters out rows of data after the system applies search record criteria. It also can stop the Component Processor from reading additional rows of data.

Note. Errors and warnings should no longer be used in RowSelect processing; instead, use DiscardRow and StopFetching. The behavior of errors and warnings in RowSelect PeopleCode is retained for compatibility with previous releases of PeopleTools.

A warning causes the Component Processor to reject the current row, but the Component Processor continues reading more data. An error prevents more data coming into the page or component. The Component Processor accepts the row that causes the error, but does not read any more data. To reject the current row and stop loading additional rows, issue a warning and an error.

You must specify text for an error or warning, but the Component Processor does not display messages from RowSelect. You can still use the message text as a way of documenting the program.

See Also

Chapter 11, "Accessing PeopleCode and Events," page 219

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," DiscardRow

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," StopFetching

Using Errors and Warnings in RowDelete Events

When you delete a row of data, the system prompts you to confirm. If you confirm, any record field RowDelete PeopleCode runs, and any component record RowDelete PeopleCode also runs. Errors and warnings in RowDelete display a message box.

A warning from RowDelete presents two choices: accept the RowDelete (the OK button), or cancel the RowDelete (the Cancel button). An error from RowDelete PeopleCode prevents the Component Processor from removing that row of data from the page.

Using Errors and Warnings in Other Events

Do not put errors or warning in PeopleCode attached to the FieldDefault, FieldFormula, RowInit, FieldChange, RowInsert, SavePreChange, WorkFlow, and SavePostChange events. These event types activate processing that a user has no direct control over. However, the Component Processor may issue its own errors and warnings when it runs PeopleCode and encounters an unrecoverable error. The Component Processor cancels the transaction to avoid unpredictable results.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Warning

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Error

Using the RemoteCall Feature

This section provides an overview of RemoteCall components and discusses how to:

- Decide between RemoteCall and PeopleSoft Process Scheduler.
- Modify PeopleSoft Process Scheduler programs to run with RemoteCall.

See Also

Chapter 8, "Using Methods and Built-In Functions," Think-Time Functions, page 156

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," CallAppEngine

Understanding RemoteCall Components

RemoteCall is a PeopleTools feature that enables executing a COBOL program remotely from within a PeopleSoft application. Remote calls are made using the RemoteCall PeopleCode function.

Because all PeopleCode runs on the application server, the RemoteCall PeopleCode function has more limited utility. However, RemoteCall can enable you to take advantage of existing COBOL processes.

In the application server configuration file, you can specify where the COBOL executables are located.

See *Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration*, "Setting Application Server Domain Parameters," Remote Call Options.

The RemoteCall function is a synchronous call. The PeopleSoft system passes parameters to the remote program, and then waits while the program runs. When the remote program is done, it returns any results or status information to the client, which then resumes execution. This means that RemoteCall is a think-time function. RemoteCall is designed for fast response time, and has an application programming interface (API) that provides programs with the response time needed for transaction processing. However, RemoteCall has no scheduling or multistep job capabilities. Each execution of RemoteCall is independent.

Note. For PeopleTools 8, you can no longer use RemoteCall to execute an Application Engine program. Use the CallAppEngine function instead.

The RemoteCall PeopleTools feature consists of the following components:

- PeopleCode program.

This interface consists of the RemoteCall PeopleCode function. It is used from PeopleCode to start a remote program and process results. The PeopleCode program does not include any special code to specify where the remote program is executed. You can configure Oracle Tuxedo to locally execute the program for testing.

- Remote program API.

This is used by the remote COBOL program to receive or pass parameters and return status information.

- PeopleSoft RemoteCall service.

The PeopleSoft application server, PSAPPSRV, advertises the RemoteCall service. The service receives requests from clients and starts the requested program. When the program is completed, it passes the parameters and status code back to the client.

- Oracle Tuxedo.

Oracle Tuxedo is a message-based transaction monitor for distributed applications. No direct Oracle Tuxedo calls need to be implemented in PeopleCode or remote programs.

PeopleCode Program

You can execute the RemoteCall function from PeopleCode associated with any Component Processor event except SavePostChange, SavePreChange, Workflow, RowSelect, or in any PeopleCode event resulting from a ScrollSelect or related function call. However, remote programs that change data should not be run as part of a SaveEdit process, because the remote program may complete successfully even though an error occurs later in the save process.

To call a remote program that changes data, use FieldChange PeopleCode in a record field associated with a command button, or from a pop-up menu item.

Do not use RemoteCall if you expect the remote program to return a large amount of data to the client, because data is passed back only through the parameters of the PeopleCode API.

Authorization to run a remote program is like authorization to run a PeopleCode program. Because a remote program is started from PeopleCode, the user has authorization to use the page that executes the PeopleCode.

The remote program runs in a different unit of work from the page. A commit is issued by PeopleTools if needed on the client before RemoteCall is called. This means that, by default, the remote program does not know about any database changes unless the page is saved before the program is called. After the remote program starts, it runs to completion and commits or ends before returning to the page. In this way, the remote program and the page do not have locking contention. To ensure that the save has actually been done, use the DoSaveNow built-in function.

When using RemoteCall to execute a COBOL program, two types of errors can occur:

- PeopleTools errors.

An error could occur in PeopleTools or Oracle Tuxedo, or the service might not be found. These are treated as hard errors by PeopleCode. An error message box appears, and that piece of PeopleCode is terminated. In the case of a PeopleTools error, the remote program always either returns a code of zero or terminates with a message due to a system error.

- Application-specific errors.

Any error information specific to the remote application must be passed back in regular data variables, and the application can process these in an application-specific way. If you have a status code on which the application depends, you should initialize it to an invalid value to be sure the COBOL program does return the status code.

Because the remote program is executed synchronously, users receive an hourglass icon and cannot do anything in the current window until the remote application completes. They could move to another window and do processing there, or they could open another PeopleSoft window. They cannot cancel the remote program after it starts. If the program does not terminate in a timely fashion (as determined by the RemoteCall timeout set with PeopleSoft Configuration Manager), RemoteCall attempts to terminate the process and returns an error indicating that the program was terminated.

Remote Program API

The remote program API provides the functions to get and put data between the network and the COBOL program. These functions are implemented in C, but are callable from COBOL through the PTPNETRT program. For an example, see the PTPNTEST.CBL program.

Note. If these APIs are called when the program is not running as a remote program, ACTION-GET and ACTION-PUT return an error. All other actions return without doing anything.

If an unexpected error is found, call PTPNETRT with ACTION-RESET, then with ACTION-PUT to send back any error status variables, then with ACTION-DONE to send the buffer.

PeopleSoft RemoteCall Service

The RemoteCall service serves as a bridge between the PeopleCode API and remote COBOL programs. RemoteCall is one of many services advertised from the PSAPPSRV Oracle Tuxedo server, and can be configured as part of the standard domain setup and administration.

The client sends the RemoteCall service request, consisting of the connect information and the program name, as well as any other parameters for the program, to the application server. The RemoteCall service then executes the program and passes it the connect string.

RemoteCall Programming Guidelines

Keep the following points in mind when using RemoteCall:

- Do not use RemoteCall for long-running batch jobs.

As a general rule, if you think execution will take more than 15 seconds, you should not be using RemoteCall, but should instead use PeopleSoft Process Scheduler.

- RemoteCall is meant for running jobs on the server.

It should not be used to invoke client-only programs. Support for local calling with RemoteCall is provided solely as a debugging and development aid. For client-only programs, use Declare Function, then call the external function from a library.

- If you do not want to modify an existing program, then pass only the program name and run control, and do not return any parameters.

This way, the program requires few changes to run as a remote function.

Deciding Between RemoteCall and PeopleSoft Process Scheduler

COBOL application programs initiated by the RemoteCall service use the same COBOL application architecture used by PeopleSoft Process Scheduler. After being initiated by the dispatcher, COBOL application programs call the COBOL SQL API program, PTPSQLRT, to connect to the relational database management system to compile and execute SQL statements. You can design and implement COBOL programs to be understood by both PeopleSoft Process Scheduler and RemoteCall.

Follow these guidelines to select the optimal method for running a particular COBOL program:

- Use PeopleSoft Process Scheduler for asynchronous processes, or processes that can be scheduled, are multistep, or that require printed output.
- Use RemoteCall for synchronous processes that are quick (transaction processing types of processes).

Modifying PeopleSoft Process Scheduler Programs to Run with RemoteCall

To enable an existing program that runs under PeopleSoft Process Scheduler to run under RemoteCall as well, make the following changes:

- Include the PTCNETRT copy member.
- Include the PTCNCHEK member before the connection call to PTPSQLRT.
- Add the call to PTPNETRT ACTION-DONE just before the program terminates (after the call to disconnect from the database).

This should be conditional on whether you are RUNNING-REMOTE-CALL.

- If you are running as a RemoteCall, ensure that PROCESS-INSTANCE OF PRUNSTATUS is not set.

Otherwise your calls to PTCPSTAT try to update the PSPRCSRQST table. This does not cause an error, but it is unnecessary processing.

This program can now run from PeopleSoft Process Scheduler or from RemoteCall. If a program has to pass parameters, it must have RemoteCall-specific ACTION-GET and ACTION-PUT calls.

Chapter 9

Using HTML Trees and the GenerateTree Function

This chapter discusses the GenerateTree function.

Using the GenerateTree Function

This section provides an overview of HTML trees and discusses how to:

- Build HTML tree pages.
- Use HTML tree rowset records.
- Use tree actions (events).
- Initialize HTML trees.
- Process events passed from a tree to an application.
- Add mouse-over ability to HTML trees.
- Add visual selection node indicators.
- Specify override images.

Understanding HTML Trees

Use the GenerateTree function to display data in a tree format. The result of the GenerateTree function is an HTML string, which can appear in an HTML area control. The tree generated by GenerateTree is called an HTML tree.

The GenerateTree function displays data from a rowset. You can populate this rowset using existing record data. You can also use the tree classes to display data from trees created using PeopleSoft Tree Manager.

To use this function, you must set up a page for displaying the data and populate a standalone rowset with the data to be displayed.

The following example shows an HTML tree:



HTML tree example

The positional links at the top of the page (First,Previous,Next, Last,Left,Right) enable the user to navigate around the tree. These links are automatically generated as part of the execution of GenerateTree.

When a node is collapsed, a plus sign appears on the node icon, and the node's children are hidden. When a node is expanded, all child nodes appear, and the icon displays a minus sign. Icons without a plus or minus sign are terminal nodes, which have no children and cannot be expanded or collapsed.

Building HTML Tree Pages


The page you use to display the HTML tree must contain:

- An HTML area used to display the HTML tree.
- A character field that has a page field name, is at least 46 characters long, and is invisible.

Note. The edit box should be invisible, but not display-only. An invisible edit box cannot be seen by the user, but it still has a buffer that can be written to. Page fields that have been specified as invisible do not need to be marked as Modifiable from HTML unless they are located on a page that is not active when GenerateTree is called. For example, if your application calls GenerateTree from one page and then saves the result in a field that is displayed by an HTML area on another page in the component, the associated event field must be marked both Invisible and Modifiable from HTML.

Events are sent to the application from the HTML tree using the invisible field. The events are processed by FieldChange PeopleCode that is attached to the invisible field.

This is an example page for an HTML tree:



Example of PeopleSoft Application Designer HTML tree page

The large area that is selected in the example is the HTML area that displays the HTML tree. The HTML area is attached to the `DERIVED_HTML.HTMLAREA` field for this example.

The white edit box is the invisible field used to pass events from the HTML tree to the application. It is attached to the `DERIVED_HTML.TREECTLEVENT` field for this example.

The edit box must have a page field name. In this example, the page field name is `TREECTLEVENT`.

Using HTML Tree Rowset Records

The `GenerateTree` function takes a prebuilt and populated rowset as a parameter. This rowset must have a certain structure and contain certain fields. In the following examples, the rowset is standalone, that is, the rowset is created using the `CreateRowset` function. The fields necessary for the rowset are contained in the following record definitions:

- The header record `TREECTL_HRD`, containing the subrecord `TREECTL_HDR_SBR`.
- The node record `TREECTL_NDE`, containing the subrecord `TREECTL_NDE_SBR`.

The header record is the level zero record of the HTML tree rowset. It contains options for the HTML tree, such as the name of the collapsed node image, the height of the images, the number of pixels to indent each node, and so on.

The node record is the level one record of the HTML tree rowset. It contains the tree data and information about the data, such as the dynamic range leaf, the level, and so on.

The level one scroll area contains a row for each node or leaf in the tree data.

To store additional application data with each node in the tree, you can incorporate the TREECTL_NDE_SBR into a record of your definition and use your record to define the HTML tree rowset.

For example, you might want to store application key values with each node record, so that when a user selects a node, you have the data you need to perform the action that you want.

This table describes the relevant fields in TREECTL_HDR_SBR:

Field	Description
PAGE_NAME	Name of the page that contains the HTML area and the invisible field used to process the HTML tree events.
PAGE_FIELD_NAME	Page field name of the invisible field used to process the HTML tree events.
PAGE_SIZE	Number of nodes or leaves to send to the browser at a time. Set to 0 to send all visible nodes or leaves to the browser. The default value is 0.
DISPLAY_LEVELS	Number of levels to display on the browser at a time. The default value is 8.
COLLAPSED_IMAGE	Collapsed node image name. The default value is PT_TREE_COLLAPSED.
EXPANDED_IMAGE	Expanded node image name. The default value is PT_TREE_EXPANDED.
END_NODE_IMAGE	End node image name. The default value is PT_TREE_END_NODE.
LEAF_IMAGE	Leaf image name. The default value is PT_TREE_LEAF.
IMAGE_WIDTH	Image width in pixels. All four images need to be the same width. The default value is 15 pixels.
IMAGE_HEIGHT	Image height in pixels. All four images need to be the same height. The default value is 12 pixels.
INDENT_PIXELS	Number of pixels to indent each level. The default value is 20 pixels.
TREECTL_VERSION	Version of the HTML tree. The default value is 812. Used with the DESCR_IMAGE field in the TREECTL_HDR_SBR record.

This table describes the relevant fields in TREECTL_NDE_SBR:

Field	Description
LEAF_FLAG	If this is a leaf, set to Y. The default value is N.

Field	Description
TREE_NODE	Node name.
DESCR	(Optional) Node description.
RANGE_FROM	The range from value of the leaf.
RANGE_TO	The range to value of the leaf.
DYNAMIC_FLAG	If this leaf has a dynamic range, set to Y. The default value is N.
ACTIVE_FLAG	Set to N for the node or leaf not to be a link. The default value is Y.
DISPLAY_OPTION	Set to N to display the name only. Set to D to display the description only. Set to B to display both the name and the description. Used for nodes only. The default value is B.
STYLECLASSNAME	Use to control the style of the link associated with the node or leaf. The default value is PSHYPERLINK.
PARENT_FLAG	If this node is a parent and its direct children are loaded now, set to Y. If this node is a parent and its direct children are loaded on demand, set to X. If this node is not a parent, set to N. The default value is N.
TREE_LEVEL_NUM	Set to the level of the node. The default value is 1.
LEVEL_OFFSET	If a child node is to appear more than one level to the right of its parent, specify the number of additional levels. The default value is 0.
DESCR_IMAGE	Use to display an image after the node or leaf image and before the name or description. The two images are separated by a space. The new image is not scaled. This field takes a string value, the name of an image definition created in PeopleSoft Application Designer. This field is only recognized if the TREECTL_VERSION field is greater than or equal to 812.
EXPANDED_FLAG	When the EXPANDED_FLAG of a node is set to Y, the GenerateTree function expects the immediate children of the node to be loaded into the &TREECTL rowset (such as in PostBuild), and GenerateTree generates HTML such that the node is expanded and its immediate children appear.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," CreateRowset

Using HTML Tree Actions (Events)

The GenerateTree function works with an HTML area control and an invisible field. When a user selects a node, expands a node, collapses a node, or uses one of the navigation links, that event (user action) is passed to the invisible field, and the FieldChange PeopleCode for the invisible field is executed.

The FieldChange PeopleCode example program (below) checks for expanding (or collapsing) a node and selecting a node by checking the first character in the invisible field. The following example checks for whether a node is selected:

```
If Left(TREECTLEVENT, 1) = "S" Then
```

In your application, you can check for the following user actions:

<i>Event</i>	<i>Description</i>
<i>T_n</i>	Expand or collapse the node, whichever is the opposite of the previous state. <i>N</i> is the row number of the node in the TREECTL_NODE rowset.
<i>X_n</i>	Expand the node, but load the children first. The children are loaded in PeopleCode, and then the event is passed to GenerateTree so that the HTML can be generated with the node expanded. <i>N</i> is the row number of the node in the TREECTL_NODE rowset.
F	Display the first page.
P	Display the previous page.
N	Display the next page.
L	Display the last page.
Q	Move the display left one level.
R	Move the display to the right one level.
<i>S_n</i>	Select the node or leaf. <i>N</i> is the row number of the node or leaf in the TREECTL_NODE rowset.

Note. Drag-and-drop functionality is not supported in an HTML tree.

Initializing HTML Trees

For this example, the PeopleCode for initializing the HTML tree was put into the PostBuild event of the component that contained the page with the HTML area used with the HTML tree.

The PostBuild PeopleCode Example program is an example of how to initialize the HTML tree using the Tree classes and load only the root node into the HTML tree rowset.

The first time a user expands a node, the direct children of the node are loaded into the HTML tree rowset by the FieldChange PeopleCode Example program, shown in the following section. This chunking functionality enables the HTML tree to support trees of any size with good performance.

You cannot simply copy either the PostBuild or FieldChange PeopleCode example programs into your application. You must modify them to make them work with your data. You must make these changes to the PostBuild PeopleCode to initialize HTML trees:

1. Set the PAGE_NAME and PAGE_FIELD_NAME fields.

The PAGE_NAME field contains the name of the page that contains the HTML area and the invisible field that processes HTML tree events. The PAGE_FIELD_NAME field is the page field name of the invisible field that is used to process the HTML tree events.

Note. The PAGE_FIELD_NAME field is the page field name of the invisible field, not the invisible field name.

2. Set tree-specific variables.

The `&SET_ID`, `&USERKEYVALUE`, `&TREE_NAME`, `&TREE_DT`, and `&BRANCH_NAME` variables contain specific information about the tree. Set these values to the tree you want to open. In the example PeopleCode that follows, these variables are set as follows:

```
&SET_ID = PSTREEDEFN_VW.SETID;
&USERKEYVALUE = " ";
&TREE_NAME = PSTREEDEFN_VW.TREE_NAME;
&TREE_DT = PSTREEDEFN_VW.EFFDT;
&BRANCH_NAME = " ";
```

3. Set the PAGE_SIZE field.

If you do not want the page to expand vertically to display the tree, set the PAGE_SIZE to a number of rows that will fit inside the HTML area. If some vertical expansion is okay, but you do not want the page to get too large, set the PAGE_SIZE to whatever value you like. Set the PAGE_SIZE to 0 if you do not care how big the page gets.

4. Set the DISPLAY_LEVELS field to the number of levels that will fit inside the HTML area.

If this field is set too large, wrapping may occur. Positional links at the top of the HTML area enable the user to navigate as the tree expands.

5. (Optional) Set the DISPLAY_OPTION field.

The default for the DISPLAY_OPTION field is to display both the node name and the description. You can display just the node name or just the description. The values for this field are:

<i>Field Value</i>	<i>Description</i>
<i>N</i>	Display the name only.
<i>D</i>	Display the description only.
<i>B</i>	Display both the name and description.

6. (Optional) Set the STYLECLASSNAME field for the root node.

The STYLECLASSNAME field controls the style of the link associated with a node or leaf. The default for the STYLECLASSNAME is *PSHYPERLINK*. If *PSHYPERLINK* is not the style you want to use, change this field value to the style you want.

7. Change the last line to assign the output of GenerateTree to the field attached to the HTML area that will display the tree.

In the example that follows, the HTML area control is the DERIVED_HTML.HTMLAREA. You must specify the record and field name associated with the HTML area control on your page.

PostBuild PeopleCode Example

The PeopleCode for initializing the HTML tree for this example was put into the PostBuild event of the component that contained the page with the HTML area used with the HTML tree.

This example shows how to initialize the HTML tree using the tree classes and load only the root node into the HTML tree rowset:

```

Component Rowset &TREECTL;

&NODE_ROWSET = CreateRowset(Record.TREECTL_NODE);
&TREECTL = CreateRowset(Record.TREECTL_HDR, &NODE_ROWSET);

&TREECTL.InsertRow(1);
&REC = &TREECTL.GetRow(2).GetRecord(1);

/* Set the HDR options:

1) PAGE_NAME - Name of the page that contains the HTML Area
and the invisible field that will be used to process the HTML
tree events.
2) PAGE_FIELD_NAME - Page field name of the invisible field that
will be used to process the HTML tree events.
3) PAGE_SIZE - Number of nodes or leaves to send to the browser at
a time.
Set to 0 to send all of the visible nodes or leaves to the browser.
Default value: 0
4) DISPLAY_LEVELS - Number of levels to display on the browser at
a time. Default value: 8
5) COLLAPSED_IMAGE - Collapsed node image name.
Default value: PT_TREE_COLLAPSED
6) EXPANDED_IMAGE - Expanded node image name.
Default value: PT_TREE_EXPANDED
7) END_NODE_IMAGE - End node image name.
Default value: PT_TREE_END_NODE
8) LEAF_IMAGE - Leaf image name. Default value: PT_TREE_LEAF
9) IMAGE_WIDTH - Image width.
All four images need to be the same size. Default value: 15
10) IMAGE_HEIGHT - Image height. Default value: 12
11) INDENT_PIXELS - Number of pixels to indent each level.
Default value: 20
*/
&REC.GetField(Field.PAGE_NAME).Value = "TREECTL_TEST";
&REC.GetField(Field.PAGE_FIELD_NAME).Value = "TREECTLEVENT";
&REC.GetField(Field.PAGE_SIZE).Value = 15;
&REC.GetField(Field.DISPLAY_LEVELS).Value = 8;
&REC.GetField(Field.COLLAPSED_IMAGE).Value = "PT_TREE_COLLAPSED";
&REC.GetField(Field.EXPANDED_IMAGE).Value = "PT_TREE_EXPANDED";
&REC.GetField(Field.END_NODE_IMAGE).Value = "PT_TREE_END_NODE";
&REC.GetField(Field.LEAF_IMAGE).Value = "PT_TREE_LEAF";
&REC.GetField(Field.IMAGE_WIDTH).Value = 15;
&REC.GetField(Field.IMAGE_HEIGHT).Value = 12;
&REC.GetField(Field.INDENT_PIXELS).Value = 20;

&SET_ID = PSTREEDEFN_VW.SETID;
&USERKEYVALUE = "";
&TREE_NAME = PSTREEDEFN_VW.TREE_NAME;
&TREE_DT = PSTREEDEFN_VW.EFFDT;
&BRANCH_NAME = "";

&MYSESSION = %Session;
&SRC_TREE = &MYSESSION.GetTree();
&RES = &SRC_TREE.OPEN(&SET_ID, &USERKEYVALUE, &TREE_NAME,
&TREE_DT, &BRANCH_NAME, False);

/* Just insert the root node into the &TREECTL Rowset.
If the root node has children, set the &PARENT_FLAG to 'X',
so that its children will be loaded on demand. */

&ROOT_NODE = &SRC_TREE.FindRoot();

If &ROOT_NODE.HasChildren Then

```

```

        &PARENT_FLAG = "X";
Else
        &PARENT_FLAG = "N";
End-If;

&NODE_ROWSET = &TREECTL.GetRow(2).GetRowset(1);
&NODE_ROWSET.InsertRow(1);
&REC = &NODE_ROWSET.GetRow(2).GetRecord(1);

/* Set the NODE values:

1) LEAF_FLAG - If this is a leaf set to "Y". Default value: N
2) TREE_NODE - Node name.
3) DESCR - Node description. (optional)
4) RANGE_FROM - Leaf's range from value.
5) RANGE_TO - Leaf's range to value.
6) DYNAMIC_FLAG - If this leaf has a dynamic range, set to "Y".
Default value: N
7) ACTIVE_FLAG - Set to "N" for the node or leaf not to be a link.
Default value: Y
8) DISPLAY_OPTION - Set to "N" to display the name only.
Set to "D" to display the description only.
Set to "B" to display both the name and the description.
Only used for nodes. Default value: B
9) STYLECLASSNAME - Used to control the style of the link
associated with the node or leaf. Default value: PSHYPERLINK
10) PARENT_FLAG - If this node is a parent and its direct
children will be loaded now, set to "Y". If this node is a
parent and its direct children are to be loaded on demand,
set to "X". Default value: N
11) TREE_LEVEL_NUM - Set to the node's level. Default value: 1
12) LEVEL_OFFSET - If a child node is to be displayed more than
one level to the right of its parent, specify the number of
additional levels. Default value: 0
*/
&REC.GetField(Field.LEAF_FLAG).Value = "N";
&REC.GetField(Field.TREE_NODE).Value = &ROOT_NODE.NAME;
&REC.GetField(Field.DESCR).Value = &ROOT_NODE.DESCRPTION;
&REC.GetField(Field.RANGE_FROM).Value = "";
&REC.GetField(Field.RANGE_TO).Value = "";
&REC.GetField(Field.DYNAMIC_FLAG).Value = "N";
&REC.GetField(Field.ACTIVE_FLAG).Value = "Y";
&REC.GetField(Field.DISPLAY_OPTION).Value = "B";
&REC.GetField(Field.STYLECLASSNAME).Value = "PSHYPERLINK";
&REC.GetField(Field.PARENT_FLAG).Value = &PARENT_FLAG;
&REC.GetField(Field.TREE_LEVEL_NUM).Value = 1;
&REC.GetField(Field.LEVEL_OFFSET).Value = 0;

&SRC_TREE.Close();
DERIVED_HTML.HTMAREA = GenerateTree(&TREECTL);

```

Processing Events Passed from a Tree to an Application

To modify the FieldChange PeopleCode to load the direct children of the node into the HTML trees, use the following FieldChange PeopleCode to process the events passed from an HTML tree to an application. The code that processes the load children event loads the direct children of a node the first time the node is expanded by the user. Changes that you must make to the FieldChange PeopleCode are as follows.

1. Globally change TREECTLEVENT to the name of the invisible field used to process the events.

2. Set the tree-specific variables.

The `&SET_ID`, `&USERKEYVALUE`, `&TREE_NAME`, `&TREE_DT`, and `&BRANCH_NAME` variables contain specific information about the tree. Set these values to the tree you want to open. In the example PeopleCode that follows, they are set like this:

```
&SET_ID = PSTREEDEFN_VW.SETID;
&USERKEYVALUE = " ";
&TREE_NAME = PSTREEDEFN_VW.TREE_NAME;
&TREE_DT = PSTREEDEFN_VW.EFFDT;
&BRANCH_NAME = " ";
```

3. (Optional) Set the DISPLAY_OPTION field.

The default for the `DISPLAY_OPTION` field is to display both the node name and the description. You can display just the node name or just the description. The values for this field are:

<i>Field Value</i>	<i>Description</i>
N	Display the name only.
D	Display the description only.
B	Display both the name and description.

4. (Optional) Set the STYLECLASSNAME field for the root node.

The `STYLECLASSNAME` field controls the style of the link associated with a node or leaf. The default for the `STYLECLASSNAME` is `PSHYPERLINK`. If `PSHYPERLINK` is not the style you want to use, change this field value to the style you want.

5. Change the assignment of the output of every GenerateTree call to the field attached to the HTML area that will display the tree.

In this example, the HTML area control is the `DERIVED_HTML.HTMLAREA`. You must specify the record and field name associated with the HTML area control on your page.

6. Change the code that processes the select event to perform the action you want when the user selects a node or leaf.

This section is marked as Process Select Event in the following code sample.

FieldChange PeopleCode Example

The following is the PostBuild PeopleCode example:

```

Component Rowset &TREECTL;

/* process load children event */
If Left(TREECTLEVENT, 1) = "X" Then
    &ROW = Value(Right(TREECTLEVENT, Len(TREECTLEVENT) - 1)) + 1;
    &NODE_ROWSET = &TREECTL.GetRow(2).GetRowset(1);
    &PARENT_REC = &NODE_ROWSET.GetRow(&ROW).GetRecord(1);
    &PARENT_LEVEL = &PARENT_REC.GetField(Field.TREE_LEVEL_NUM).Value;
    &ROW = &ROW + 1;

    &SET_ID = PSTREEDEFN_VW.SETID;
    &USERKEYVALUE = "";
    &TREE_NAME = PSTREEDEFN_VW.TREE_NAME;
    &TREE_DT = PSTREEDEFN_VW.EFFDT;
    &BRANCH_NAME = "";

    &MYSESSION = %Session;
    &SRC_TREE = &MYSESSION.GetTree();
    &RES = &SRC_TREE.OPEN(&SET_ID, &USERKEYVALUE, &TREE_NAME,
&TREE_DT, &BRANCH_NAME, False);

    /* Find the parent node and expand the tree one level below
the parent. Insert just the direct children of the parent node
into the &TREECTL Rowset. If any of the child nodes have
children, set their PARENT_FLAG to 'X', so that their children
are loaded on demand. */

    &PARENT_NODE = &SRC_TREE.FindNode(&PARENT_REC.
GetField(Field.TREE_NODE).Value, "");
    If &PARENT_NODE.HasChildren Then
        &PARENT_NODE.Expand(2);

    If &PARENT_NODE.HasChildLeaves Then
        /* Load the child leaves into the &TREECTL Rowset. */
        &FIRST = True;
        &CHILD_LEAF = &PARENT_NODE.FirstChildLeaf;
        While &FIRST Or
            &CHILD_LEAF.HasNextSib
            If &FIRST Then
                &FIRST = False;
            Else
                &CHILD_LEAF = &CHILD_LEAF.NextSib;
            End-If;
            If &CHILD_LEAF.Dynamic = True Then
                &RANGE_FROM = "";
                &RANGE_TO = "";
                &DYNAMIC_RANGE = "Y";
            Else
                &RANGE_FROM = &CHILD_LEAF.RangeFrom;
                &RANGE_TO = &CHILD_LEAF.RangeTo;
                &DYNAMIC_RANGE = "N";
            End-If;

            &NODE_ROWSET.InsertRow(&ROW - 1);
            &REC = &NODE_ROWSET.GetRow(&ROW).GetRecord(1);

            /* Set the NODE values:

1) LEAF_FLAG - If this is a leaf set to "Y". Default value: N
2) TREE_NODE - Node name.
3) DESCR - Node description. (optional)
4) RANGE_FROM - Leaf's range from value.
5) RANGE_TO - Leaf's range to value.
6) DYNAMIC_FLAG - If this leaf has a dynamic range, set to "Y".

```

```

Default value: N
7) ACTIVE_FLAG - Set to "N" for the node or leaf not to be a link.
   Default value: Y
8) DISPLAY_OPTION - Set to "N" to display the name only.
   Set to "D" to display the description only.
   Set to "B" to display both the name and the description.
   Only used for nodes. Default value: B
9) STYLECLASSNAME - Used to control the style of the link
   associated with the node or leaf. Default value: PSHYPERLINK
10) PARENT_FLAG - If this node is a parent and its direct
   children will be loaded now, set to "Y". If this node is a
   parent and its direct children are to be loaded on demand,
   set to "X". Default value: N
11) TREE_LEVEL_NUM - Set to the node's level. Default value: 1
12) LEVEL_OFFSET - If a child node is to be displayed more than
   one level to the right of its parent, specify the number of
   additional levels. Default value: 0
*/

      &REC.GetField(Field.LEAF_FLAG).Value = "Y";
      &REC.GetField(Field.TREE_NODE).Value = "";
      &REC.GetField(Field.DESCR).Value = "";
      &REC.GetField(Field.RANGE_FROM).Value = &RANGE_FROM;
      &REC.GetField(Field.RANGE_TO).Value = &RANGE_TO;
      &REC.GetField(Field.DYNAMIC_FLAG).Value =
&DYNAMIC_RANGE;
      &REC.GetField(Field.ACTIVE_FLAG).Value = "Y";
      &REC.GetField(Field.DISPLAY_OPTION).Value = "B";
      &REC.GetField(Field.STYLECLASSNAME).Value =
"PSHYPERLINK";
      /* Leaves never have children. */
      &REC.GetField(Field.PARENT_FLAG).Value = "N";
      &REC.GetField(Field.TREE_LEVEL_NUM).Value =
&PARENT_LEVEL + 1;
      &REC.GetField(Field.LEVEL_OFFSET).Value = 0;

      &ROW = &ROW + 1;
    End-While;
  End-If;

  If &PARENT_NODE.HasChildNodes Then
    /* Load the child nodes into the &TREECTL Rowset. */
    &FIRST = True;
    &CHILD_NODE = &PARENT_NODE.FirstChildNode;
    While &FIRST Or
      &CHILD_NODE.HasNextSib
      If &FIRST Then
        &FIRST = False;
      Else
        &CHILD_NODE = &CHILD_NODE.NextSib;
      End-If;
      If &CHILD_NODE.HasChildren Then
        &PARENT_FLAG = "X";
      Else
        &PARENT_FLAG = "N";
      End-If;

      /* If the tree uses strict levels, set the
&LEVEL_OFFSET to the number of levels that the child node is to
the right of its parent minus 1. */
      If &SRC_TREE.LevelUse = "S" Then
        &LEVEL_OFFSET = &CHILD_NODE.LevelNumber -
&PARENT_NODE.LevelNumber - 1;
      Else
        &LEVEL_OFFSET = 0;

```

```

End-If;

&NODE_ROWSET.InsertRow(&ROW - 1);
&REC = &NODE_ROWSET.GetRow(&ROW).GetRecord(1);
&REC.GetField(Field.LEAF_FLAG).Value = "N";
&REC.GetField(Field.TREE_NODE).Value = &CHILD_NODE.Name;
&REC.GetField(Field.DESCR).Value =
&CHILD_NODE.Description;
&REC.GetField(Field.RANGE_FROM).Value = "";
&REC.GetField(Field.RANGE_TO).Value = "";
&REC.GetField(Field.DYNAMIC_FLAG).Value = "N";
&REC.GetField(Field.ACTIVE_FLAG).Value = "Y";
&REC.GetField(Field.DISPLAY_OPTION).Value = "B";
&REC.GetField(Field.STYLECLASSNAME).Value =
"PSHYPERLINK";
&REC.GetField(Field.PARENT_FLAG).Value = &PARENT_FLAG;
&REC.GetField(Field.TREE_LEVEL_NUM).Value =
&PARENT_LEVEL + 1;
&REC.GetField(Field.LEVEL_OFFSET).Value = &LEVEL_OFFSET;

&ROW = &ROW + 1;
End-While;
End-If;

/* change the parent's PARENT_FLAG from 'X' to 'Y' */
&PARENT_REC.GetField(Field.PARENT_FLAG).Value = "Y";

HTMLAREA = GenerateTree(&TREETL, TREETLEVENT);
End-If;

&SRC_TREE.Close();
Else

    /* Process select event. */

    /* As an example, just display the selected node name or
leaf range as a MessageBox. */

    If Left(TREETLEVENT, 1) = "S" Then
        &ROW = Value(Right(TREETLEVENT, Len(TREETLEVENT) - 1)) + 1;
        &NODE_ROWSET = &TREETL.GetRow(2).GetRowset(1);
        &REC = &NODE_ROWSET.GetRow(&ROW).GetRecord(1);
        If &REC.GetField(Field.LEAF_FLAG).Value = "N" Then
            MessageBox(0, "", 0, 0, "The selected node is %1.",
&REC.GetField(Field.TREE_NODE).Value);
        Else
            If &REC.GetField(Field.DYNAMIC_FLAG).Value = "N" Then
                If &REC.GetField(Field.RANGE_FROM).Value =
&REC.GetField(Field.RANGE_TO).Value Then
                    &TEMP = "[" | &REC.GetField(Field.RANGE_FROM).
Value | "]";
                Else
                    &TEMP = "[" | &REC.GetField(Field.RANGE_FROM).
Value | " - " | &REC.GetField(Field.RANGE_TO).Value | "]";
                End-If;
            Else
                &TEMP = "[ ]";
            End-If;
            MessageBox(0, "", 0, 0, "The selected leaf is %1.", &TEMP);
        End-If;
    Else
        /* process all other events */
        HTMLAREA = GenerateTree(&TREETL, TREETLEVENT);
    End-If;

```

```
End-If;

/* done processing the event, so clear it */
TREETLEVENT = "";
```

See Also

[Chapter 9, "Using HTML Trees and the GenerateTree Function," Using HTML Tree Actions \(Events\), page 194](#)

Adding Mouse-Over Ability to HTML Trees

To add mouse-over ability to HTML tree elements, you must add fields to the TREETL_HDR_SBR record and PeopleCode to the program to set the values and the images.

1. Add the following fields to the TREETL_HDR_SBR (tree control header subrecord) record.

- COLLAPSED_MSGNUM
- COLLAPSED_MSGSET
- END_NODE_MSGNUM
- END_NODE_MSGSET
- EXPANDED_MSGNUM
- EXPANDED_MSGSET
- LEAF_NODE_MSGNUM
- LEAF_NODE_MSGSET

2. Add the following PeopleCode to set the message set and number for the mouse-over text:

```
&REC.GetField(Field.EXPANDED_MSGSET).Value = 2;
&REC.GetField(Field.EXPANDED_MSGNUM).Value = 903;
&REC.GetField(Field.COLLAPSED_MSGSET).Value = 2;
&REC.GetField(Field.COLLAPSED_MSGNUM).Value = 904;
&REC.GetField(Field.END_NODE_MSGSET).Value = 2;
&REC.GetField(Field.END_NODE_MSGNUM).Value = 905;
&REC.GetField(Field.LEAF_MSGSET).Value = 2;
&REC.GetField(Field.LEAF_MSGNUM).Value = 906;
```

3. Add the following fields to the TREETL_NDE_SBR record:

- DESCR_MSGNUM
- DESCR_MSGSET

4. Add PeopleCode to set the DESCR_MSGNUM and DESCR_MSGSET fields.

These two fields should be set to the correct message number and message set values that contain the text to be used as the mouse-over text.

Adding Visual Selection Node Indicators

Sometimes, users need a visual indicator, such as a different color or style, to indicate which node is selected. This example shows a selected node style:



Example of selected node style

To add selected node highlighting:

1. Add the field NODESELECTEDSTYLE to the TREECTL_HDR_SBR record.
2. Add PeopleCode to set the NODESELECTEDSTYLE field to provide the highlighting effect.

The NODESELECTEDSTYLE field takes the name of a style class.

The following example uses the PSTREENODESELECTED style:

```
&REC.GetField(Field.NODESELECTEDSTYLE).Value = "PSTREENODESELECTED";
```

You can set the style of the selected node when processing the select event.

Note. You also must reset the style of the previous selected node when processing the select event. To find the previous selected node, you can search the node rowset looking for a node with a STYLECLASSNAME equal to the style you set for selected nodes. Alternatively, you can keep a global variable with the index of the node in the rowset. If you keep an index variable, however, you may have to update the index when processing the load children event.

Specifying Override Images

You specify different images to represent the nodes in a tree by using the TREECTL_NODE record.

To specify override images:

1. Add the following fields to the tree control node record:
 - OVERRIDE_IMAGE
 - OVERRIDE_MSGSET
 - OVERRIDE_MSGNUM
2. Add PeopleCode to use the override values when writing tree control node records.

Chapter 10

Using File Attachments and PeopleCode

This chapter discusses how to use file attachments in applications.

Using File Attachments in Applications

This section provides an overview of file attachment architecture and discusses how to:

- Debug file attachment problems.
- Configure multiple application servers to support file attachments.
- View file attachments.
- Use chunking with attachments.
- Use the Microsoft Windows NT 4 FTP server.
- Use non-DNS URLs with UNIX.
- Use attachment functions.
- Name URLs and file attachments.
- Convert user filenames.

Understanding File Attachment Architecture

File attachments are supported by using PeopleCode built-in functions that implement the transfer of a file to or from a browser using the application server. The file is either stored on, or retrieved from, an FTP server or database table, referred to as the data storage system.

Files can be transferred back and forth from the browser to the data storage system (by way of the web server and application server) or transferred back and forth from the application server file system to the data storage system.

The browser-to-web server transfer is performed using a standard HTML form construct. This can be done securely in an encrypted fashion if the web server uses Secure Sockets Layer (SSL) to communicate to the browser.

When a file is uploaded, after the file is received at the web server, 1 megabytes chunks are brought from the web server to the application server and temporarily stored in a PeopleTools table in the database.

Note. The 1-megabyte transfer size cannot be customized.

Once the entire file is transferred, the application server reassembles the file as a temporary file on the application server's file system, deletes the temporary copy from the PeopleTools table in the database, and sends the file to its ultimate destination on either an FTP server the target database table

Note. When the user selects a file for uploading, file size is not checked until after the file is transferred to the web server. If the final destination of the file is a database table, then it gets rechunked (as specified by the value of Max Chunk File Size field on the PSOPTIONS page) when that insertion happens.

Once the file gets to the web server the file size is compared to the value of the AddAttachment function's MaxSize parameter.

See [Chapter 10, "Using File Attachments and PeopleCode," Using Chunking with Attachments, page 210](#) and *Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference*, "PeopleCode Built-in Functions," ContainsOnlyCharType.

The web server-to-application server transfer is performed by using Oracle Jolt, which is securely encrypted. Because this transfer is done using the standard Oracle Jolt mechanism, no additional settings to the firewall are required (you do not need to open additional ports).

By using separately named subdirectories for each attachment, support for the simultaneous transfer of identically named files is guaranteed, and attachments will not be mixed up.

The application server-data storage system transfer is performed using either FTP or directly to a database table.

Note. The file attachment functionality does not support SFTP.

No log file or script is involved for writing to database tables. For debugging, these commands leave traces in the PeopleCode trace files if PeopleCode statement tracing (2048) is on.

Note. The search API does not work with database attachments.

See *Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference*, "Search Classes," Understanding Search Class.

File attachment architecture is designed to be used in a frame template. This is because when a file is being uploaded to a content site, the browser is communicating directly with the content site and its database. This means that the work being done is on the content site, while the portal site is unaffected. Frame templates enable you to direct the upload work to the site that it is intended for. There is no proxy work being done.

However, if you want to use HTML templates, you must first ensure that the portal site can handle the request. You should look into any performance issues that may occur on the portal site if the file is big or the network is slow.

Debugging File Attachment Problems

Error information will be written to log file. For more detailed logging you may enable Trace by setting TracePC to 2048 on application server.

See *Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration*, "Using PeopleSoft Configuration Manager," Specifying Trace Settings and *Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference*, "PeopleCode Built-in Functions," TransformExCache.

If the file transfer wasn't successful, error messages in the log can help you determine the problem.

A common reason that a transfer fails is that the FTP server was not accessible from the application server. This error could be due to a wrong password or wrong account name, or because the application server was unable to resolve the FTP server hostname. Perhaps the FTP server was down and the application server was unable to route to it. Try pinging the FTP server from the application server system, and then try to FTP to the FTP server from the application server.

If you have a Microsoft Windows file server, the hostname for the system may not be associated with a fixed IP address and may not be resolvable using the Domain Name System (DNS). If the application server is on a UNIX machine (such as Solaris, HP-UX, or AIX), the application server can only resolve the hostname using DNS (or perhaps the Network Information System [NIS] or an `/etc/hosts` file), but *not* using WinBeui or WINS. Therefore, the application server will not be able to convert the hostname indicated for the Microsoft Windows file server into an IP address and route to it.

If you suspect this is the problem, try the following:

1. Telnet to the UNIX application server.
2. Try to ping the suspect hostname.

For example:

```
ping TCARREON052500
```

If this fails, you must resolve the problem by either specifying the IP address in the FTP URL or by putting your hostname into DNS, NIS, or a hosts file so that UNIX can resolve it.

Debugging Paths

In general, FTP servers require the full path from the top-level directory, rather than the path from the home directory (a relative path). If you've been able to add an attachment but can't view it, verify that you're using a full, absolute path, as opposed to a relative path.

Attachments with non-ASCII Filenames

To successfully upload attachments whose filename comes from a language which uses a non-ASCII string, such as Japanese, from your web browser to either an FTP server or database table, Oracle recommends running the application server in an environment that supports non—ASCII character languages.

If the destination for your attachment is an FTP server, Oracle recommends that the FTP server also be running in an environment that supports the same language or locale as the filenames used. (The web server can be running on either an English environment or a non—ASCII character language environment.)

If your environment does not fully support non-ASCII characters, then the file-processing system will convert file names into names that are fully ASCII strings that, at upload time, will be passed back to the calling PeopleCode program rather than the original name of the file as selected by the end-user. This means that it may be more difficult for an end-user to later identify the renamed file for further processing, such as viewing.

Viewing Error Messages

If you want your user to be able to view error messages (such as the file is too large, the file was not found, or the data in the file is corrupt) when attaching files, add one of the following lines of PeopleCode to the FILE_ATTACH_WRK record, to the ATTACHADD field, immediately above the line

```
&ORIGSYSFILENAME = &ATTACHSYSFILENAME;;
```

```
&MESSAGE_LVL=1;
```

Or

```
&MESSAGE_LVL=2;
```

Configuring Multiple Application Servers to Support File Attachments

When you have multiple application servers, the /tmp/PSFTP/DomainIDxxx directory is created by the first application server process to run on your application server. The assumption is that all such application server processes run with the same user ID. However, a single computer might run application servers with many user IDs.

The default /tmp/PSFTP is created so that all users can access it (777 permissions, or drwxrwxrwx). For proper security, however, the DomainIDxxx directory is created so that only that application server can access that directory (711 permissions, or drwx--x--x). If multiple users need read and write access, you must change the permissions.

When using file objects, the service request can be sent to different application servers, so that if a file was created under one application server machine environment and that service is next serviced on a different application server machine, the file might not exist. Therefore, your application should check that the file is open, particularly when returning from a user interaction (since the process of the handling user interface results in a serialization/deserialization of all the transaction states.)

Note. The file attachment functionality does not support running multiple application servers concurrently to support the same application. This can happen if a load-balancer is used or your web server is configured to do Jolt Session Pooling. Because a file attachment operation is such a complex process, if the application switches application servers in the middle of such an operation, the operation may fail.

Viewing File Attachments

When viewing a file attachment, the browser invokes a viewer based on the content-type Multipurpose Internet Mail Extensions (MIME) category sent in the response header from the web server.

For example, if the user tried to view an MP3 file, the response header sent to the browser by the web server would indicate the audio/MPEG content type.

```
HTTP/1.1 200 OK
Server: Microsoft-IIS/5.0
Date: Mon, 01 Oct 2001 21:25:51 GMT
Content-Type: audio/mpeg
Accept-Ranges: bytes
Last-Modified: Mon, 01 Oct 2001 21:00:26 GMT
ETag: "78e21918bc4ac11:cc8"
Content-Length: 60
```

Notice that the Content-Type is audio/mpeg. The browser uses this MIME type to determine that a viewer for audio/MPEG is appropriate. If the web server did not send this content-type header, the browser would not be able to determine the nature of the file being transmitted, and it would be unable to invoke the correct application. The browser would try to display the file as text/plain, which might be the wrong assumption.

The web server determines the MIME type by looking at the extension of the attachment file and mapping it to a MIME type. The mapping is done in the following ways, depending on the web server and platform:

- For Microsoft IIS, the mapping is done by using the standard Microsoft Windows extension association mechanism.
- For Apache, the mapping is done by editing a configuration file called mime.types.
- For WebLogic, a file called web.xml does the mapping.

The file web.xml is located in the WEB-INF subdirectory. This file contains a section that looks like this:

```
</mime-mapping>
<mime-mapping>
  <extension>
    doc
  </extension>
  <mime-type>
    application/msword
  </mime-type>
</mime-mapping>
<mime-mapping>
  <extension>
    xls
  </extension>
  <mime-type>
    application/vnd.ms-excel
  </mime-type>
</mime-mapping>
```

Let's say you want to add an extension that causes log files to be interpreted as plain text files.

To determine the correct MIME type, check Request for Comments (RFC) documents 2045, 2046, 2047, 2048, and 2077, which discuss internet media types and the internet media type registry.

After checking the RFCs, you determine that the correct MIME type is text/plain. The following is an example of code you would add to the previous section of web.xml:

```

</mime-mapping>
<mime-mapping>
  <extension>
    doc
  </extension>
  <mime-type>
    application/msword
  </mime-type>
</mime-mapping>
<mime-mapping>
  <extension>
    log
  </extension>
  <mime-type>
    text/plain
  </mime-type>
</mime-mapping>
<mime-mapping>
  <extension>
    xls
  </extension>
  <mime-type>
    application/vnd.ms-excel
  </mime-type>
</mime-mapping>

```

Once you save the file, the log extension is associated with the content type of text/plain.

Note. You must restart the WebLogic server before these changes are recognized.

Similar mappings can be achieved on other web servers, such as IBM WebSphere or Netscape Enterprise Server.

See your web server documentation.

Note. When trying to view the objects, the extension must exactly match what is set up in the web.xml file. This value is case-sensitive. If the object view appears garbled, chances are that either the extension is not set up in the web.xml file or there is a case mismatch.

Using Chunking with Attachments

When writing data to database tables, the data is automatically chunked, or stored, in different rows of the database table. The size of each chunk is determined by the Max Chunk File Size field on the PSOPTIONS page.

Because each file is chunked, you cannot pull data directly from the table. You should use the provided attachment functions, which automatically put the data back together into one file for you. Because the chunk size is stored with the file, if you change the system chunk size you can still retrieve files with different chunk sizes.

See *Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration*, "Using PeopleTools Utilities," PeopleTools Options.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," CopyAttachments

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," AddAttachment

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," PutAttachment

Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration, "Using PeopleTools Utilities," PeopleTools Options

Using the Microsoft Windows NT 4 FTP Server

If you are using FTP and running Microsoft Windows NT 4 with the standard Microsoft FTP server, you must consider this point:

Non-Microsoft FTP server programs on Microsoft Windows NT, the Microsoft Windows 2000 FTP server, as well as all UNIX FTP servers, execute a chroot command to the home directory of the FTP server automatically.

However, the Windows NT 4 FTP server does not follow this behavior. When an FTP client connects to the Microsoft FTP server, the client can gain access to the entire drive, not just the FTP home directory.

For example, suppose you are running the Microsoft Windows NT 4 FTP server and the home directory is `c:\inetpub\ftproot`.

When you log in, your current directory is `c:\inetpub\ftproot`.

When you type the following, your current directory becomes `c:\`:

```
cd \
```

If you are not running the Microsoft Windows NT 4 FTP server and the home directory is the same—`c:\inetpub\ftproot`—then when you type the following:

```
cd \
```

Your current directory becomes `c:\inetpub\ftproot`.

You *must* know the FTP server associated with the URL.

If you are using a Windows NT 4 FTP server or another FTP server that shows this behavior, your URLs should have the following format: `ftp://ftp:ftp@NT4system/inetpub/ftproot/tmp`. Note that the home directory of the FTP server must be appended to the address.

If you are not using these sorts of servers, your URLs should have the following format:
`ftp://ftp:ftp@NT4system/tmp`.

Using Non-DNS URLs with UNIX

The URL passed to file attachments generally has the following format:
`ftp://user:pass@systemname/dir1/dir2.`

This format assumes that the domain name *systemName* can be resolved with DNS.

Some Microsoft Windows systems can resolve *systemName* even when it cannot be resolved with DNS. However, some UNIX systems cannot these resolve names.

If you are using a UNIX system and the domain name cannot be resolved with DNS, then use the IP address. The following example assumes *systemName* has the IP address of 123.123.123.123:
`ftp://user:pass@123.123.123.123/dir1/dir2.`

To determine the IP address, try to ping the system by typing the following:

```
ping systemName
```

You should use domain names that can be resolved. Only use IP addresses when absolutely necessary.

Using Attachment Functions

To store file references in a database, you must create a record that receives the file references. This record can be called anything, but it must have the FILE_ATTACH_SBR subrecord included in it. You must also include the FILE_ATTACH_WRK work record in your component when using the file attachment functions

Follow these steps to develop an application that uses file attachments:

1. Determine how the file will be stored.

The file can be stored on an FTP server or in the database.

- Storing the file on an FTP server.

Although you can either have the user enter the FTP location or you can store the FTP location in a URL definition using the URL Maintenance page (People Tools, Administration, Utilities, URL Maintenance), Oracle recommends that you use a URL definition since that approach gives you the flexibility of later changing the storage location of your files without having to modify your PeopleCode.

Use a URL definition if you need to mask the FTP user ID and password. If the URL object only contains a portion of the string that will be passed to the file-processing function, for example, if the the user ID and password are added the full URL at runtime, then you can use the GetUrl function to get the underlying FTP URL.

You must use a URL definition with secure FTP (FTPS).

- Storing the file in the database.

To store the file in the database, create a new target record, for instance MYAPP_ATTACH_CONTENT, and insert the FILE_ATTDET_SBR subrecord into it. The target record must have no other fields. If you need to store other information, store it as part of the file reference, as described in the next step, or create another record and use it in the component.

2. Create a custom record to store the file reference information and any additional information, for instance MYAPP_ATTACH_REF. The new record must include the subrecord FILE_ATTACH_SBR. Add fields for any other information related to the transaction you want to store. Your program should populate this record with the file name, URL, and any other information you want to save.
3. Clone the FILE_ATTACH_WRK record to create a custom derived/work record. Give it a unique name, for instance MYAPP_ATTACH_WRK. Save the PeopleCode with the new record. You can use the sample PeopleCode on the record as the basis for your own application.

Note. The FILE_ATTACH_WRK record is delivered as a sample only. It is not intended for use as part of an application running in production unless it is customized.

It is important to create your own program. Oracle may change the delivered sample PeopleCode in future releases. Any application that directly uses the sample PeopleCode may fail. Customizing your application makes it easier to manage during upgrades and your PeopleCode can be reused in other components that use file attachment functionality.

4. Use the records you created in the previous steps to create the file attachment page and component.

The custom derived/work record has fields with FieldChange PeopleCode that you can use for Add, Detach, Delete, and View buttons.

Add PeopleCode, probably at the component record field level, to invoke the underlying functions in the custom derived/work record when the user clicks on one of the buttons.

5. Create a URL definition (PeopleTools, Administration, Utilities, URL Maintenance). Use one of these formats:
 - ftp://ftpuser:password@ftpMachineName/
 - ftps://ftpsuser:password@ftpsMachineName
 - record://MYAPP_ATTACH_CONTENT

See *Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration*, "Using PeopleTools Utilities," URL Maintenance.

The following table summarizes the delivered record definitions for use in a file attachment application:

<i>Field</i>	<i>Example</i>	<i>Description</i>
FILE_ATTDET_SBR	MYAPP_ATTACH_CONTENT	Insert this record in the custom record that will store the attached files. No other fields should be added to this record.
FILE_ATTACH_SBR	MYAPP_ATTACH_REF	Use the subrecord FILE_ATTACH_SBR or the fields ATTACHSYSFILENAME and ATTACHUSERFILE to store the system file name and the user file name in the custom record that will be used on the page to allow users to specify URL_ID, FTP location, or record name.

Field	Example	Description
FILE_ATTACH_WRK	MYAPP_ATTACH_WRK	This record can be used to clone and create your own custom derived record to provide Add, Delete, Detach, View buttons. You can modify the delivered sample code to meet your file attachment requirements.

The FILE_ATTACH_SBR subrecord contains the following fields:

Field	Description
ATTACHSYSFILENAME	The system file name.
ATTACHUSERFILE	The user file name.

No PeopleCode is associated with this subrecord. You should include this subrecord in target records for using attachments.

The FILE_ATTACH_WRK work record contains the following fields:

Field	Description
ATTACHADD	Contains a PeopleCode program used for adding attachments (the AddAttachment built-in function).
ATTACHDELETE	Contains a PeopleCode program used for deleting attachments (the DeleteAttachment built-in function).
ATTACHVIEW	Contains a PeopleCode program used for viewing attachments (the ViewAttachment built-in function).

For storing attachments in the database, you must create a record that receives the attachments. This record can be called anything, but it must have the FILE_ATTDET_SBR subrecord included in it, and it can contain no additional fields. The subrecord FILE_ATTDET_SBR has the following fields:

Field	Description
ATTACHSYSFILENAME	A unique system file name.
FILE_SEQ	The file sequence number (used in chunking).
VERSION	Version number.
FILE_SIZE	The physical size of the file.
LASTUPDDTTM	Last update date and time.
LASTUPDOPRID	The employee ID of the last user to update the attachment.

<i>Field</i>	<i>Description</i>
FILE_DATA	The data of the file.

Secure File Transfer Using FTPS

When transferring a file using secure FTP (FTPS), the file attachment function expects the URL parameter to be a URL ID, not a string. Use the URL Maintenance page (PeopleTools, Utilities, Administration, URLs) to create a URL definition.

When you create a URL for FTPS you will need to enter values for Certificate Alias, Verify Host, Verify Peer and SSL Usage.

See *Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration*, "Using PeopleTools Utilities," Adding Secure FTP (FTPS) URLs.

Coding Considerations Using the Attachment Functions

All file attachments are performed using PeopleCode built-in functions, such as AddAttachment, ViewAttachment, GetAttachment, and so on. These functions move a file into and out of a file storage system, either the database or a file system. The file system movement is done using the FTP protocol.

Because these functions abstract the storage of the attachments, you can use either database or FTP file systems. The system to be used is determined by the URL passed as the first parameter in the attachment built-in function. The actual value of the URL is maintained on the URL Maintenance page. You don't know whether users will store attachments in a database or a file system.

The following PeopleCode functions are used with administration work:

- DeleteAttachment deletes unwanted attachments.

This cannot be rolled back. For example, suppose a user selects to view an attachment, and then cancels before the attachment appears. A copy of the attachment may still be in the user's temp directory.
- CopyAttachments moves all of the attachments specified from one file storage system (database or FTP) to another (database or FTP).
- CleanAttachments is an audit-like script that removes attachments that exist in the database that are not referenced by any record field.

If you only have a few files to copy using CopyAttachments, you may want to use the CopyFiles page (part of the PeopleTools Administration pages). The CleanAttachments function is also available from this page.

To schedule a regular job to clean up orphaned file attachments, you can use the Application Engine program CLEANATT84.

Store all references to attachments using the standard ATTACHSYSFILENAME field. Do not reuse this field to store incomplete or nonstandard versions of the name. For example, you should not store the full URL version of the attachment in this column and then use PeopleCode to parse the URL before invoking attachment commands. While this method may work for get or put attachment calls, the Clean Attachments function deletes any file stored in a table that does not have a corresponding reference stored in ATTACHSYSFILENAME.

Scanning Attachments for Viruses

Files uploaded using AddAttachment can be scanned for viruses. See *Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference*, "AddAttachment" for details.

See *Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference*, "PeopleCode Built-in Functions," AddAttachment.

Copying Files Using the File Attachment Functions

Use the CopyAttachments function to move a group of attachments from one archive to another, such as when you want to move files from one FTP server to another or if you want to move all the files in a database record onto an FTP server. It does not create new system file links.

If you want to create a new file attachment by making a copy of an existing file attachment (both the system file link and the file itself), do the following:

1. Use GetAttachment to retrieve the file from the repository (either from the FTP server or from a database record) and place it on your application server (or process scheduler system if you are using Application Engine).
2. Use PutAttachment to move the file from the application server (or process scheduler system), and place it into the new archive location.
3. Save the new system file link that you passed as a parameter to PutAttachment so that you can subsequently use it. In general, this action is part of the page transaction when you save the record that has the FILE_ATTACH_SBR subrecord in it.

Errors in CopyAttachments

Because CopyAttachments is designed to work with multiple files, to track errors when using CopyAttachments set your PeopleCode trace to 2112 and your SQL trace to 15 so that errors will be written to the appropriate trace files.

See Also

Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration, "Using PeopleTools Utilities," Copy File Attachments

File Name Considerations

If a user specifies a local filename (using the functions GetAttachment , DetachAttachment , PutAttachment). with any of the following characters, the process will be stopped and an error (%Attachment_Failed) will be returned to user. The actual error message can be found in the logs.

- * (asterisk)
- : colon)
- " (quotation mark)

- < (less than symbol)
- > (greater than symbol)
- ? (question mark)

When the file is transferred, the following characters are replaced with an underscore:

- space
- semicolon
- plus sign
- percent sign
- ampersand
- apostrophe
- exclamation point
- pound sign
- dollar sign

Converting User Filenames

If a user attaches a file through the browser dialog box generated by the AddAttachment function, the filename may be converted before that filename is returned to the AddAttachment call for storage.

For example, the file My Resume.doc is returned through the AddAttachment parameter as My_Resume.doc, with the space changed to an underscore.

No comparable mapping occurs for user filenames with the PutAttachment function, which requires the user filename as an input parameter rather than an output parameter that is returned to the user.

Instead, before storing the ATTACHUSERFILE value, you should invoke code similar to this:

```
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, " ", "_");
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, ";", "_");
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, "+", "_");
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, "%", "_");
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, "&", "_");
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, "'", "_");
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, "!", "_");
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, "@", "_");
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, "#", "_");
&ATTACHUSERFILE = Substitute(&ATTACHUSERFILE, "$", "_");
```

Naming URLs and File Attachments

If you change a URL on the URL Maintenance page from FTP to record, you may have to reboot your application server before you can use the URL in your PeopleCode program.

Chapter 11

Accessing PeopleCode and Events

This chapter provides overviews of PeopleCode programs and events and PeopleCode automatic backup, and discusses how to:

- Access PeopleCode in Application Designer.
- Access record field PeopleCode.
- Access component record field PeopleCode.
- Access component record PeopleCode.
- Access component PeopleCode.
- Access page PeopleCode.
- Access menu item PeopleCode.
- Copy PeopleCode with a parent definition.
- Upgrade PeopleCode programs.

Understanding PeopleCode Programs and Events

Every PeopleCode program is associated with an aspect of a Application Designer definition and an event. Events are predefined points either in the Component Processor flow or in the program flow. As each event is encountered, it fires on each component, triggering any PeopleCode program associated with that component and that event. Each definition in Application Designer can have an *event set*, that is, a group of events appropriate to that definition. A definition can have zero or one PeopleCode programs for each event in its event set.

Some definitions have events that fall outside the Component Processor flow. These definitions include Application Engine programs, component interfaces, and application packages. In addition, security has a signon event, which is described in the documentation for the definition or topic.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Component Interface Classes"

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Application Classes"

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Integration Broker, "Managing Messages," Adding Message Definitions

Enterprise PeopleTools 8.50 PeopleBook: Application Engine, "Creating Application Engine Programs," Specifying PeopleCode Actions

Enterprise PeopleTools 8.50 PeopleBook: Security Administration, "Understanding PeopleSoft Security"

Understanding Automatic Backup of PeopleCode

A PeopleCode program is automatically saved to a file while you are working on it. This checkpoint occurs at the following times:

- Every 10 keystrokes.
- On a save command, just before the save is executed (in case the save does not actually execute because the code is invalid).
- When another PeopleCode program is selected to be edited (if you have two PeopleCode editor windows open at the same time and you move from one to the other).

The file is saved to your temp directory, as specified in your environment, in a file with the following name:

`PPCMMDDYY_HHMMSS.txt`

, where MMDDYY represents the month, date, and year of the checkpoint, respectively, and HHMMSS represents the hour, minute, and second of the checkpoint, respectively.

The top of the checkpoint file contains the following information:

`[PeopleCode Checkpoint File]`


`[RECORD.recordnameFIELD.fieldnameMETHOD.eventname]`

If your PeopleCode program saves successfully, checkpoint files associated with that program are automatically deleted.

Accessing PeopleCode in Application Designer

You can access PeopleCode associated with Application Designer definitions in several ways.

For record fields and pop-up menu items, the Project view displays PeopleCode programs within the project hierarchy using a lightning bolt icon. The programs are children of the fields and pop-up menu items with which they are associated, and they are named according to their associated events, such as ItemSelected, RowInit, or SaveEdit, as shown in the following example. Double-click a record field or pop-up menu item program in the Project view to start the PeopleCode Editor and load that program for editing.



Example of PeopleCode programs in the Project view hierarchy

You can associate PeopleCode with other types of definitions, such as:

- Components
- Pages
- Component interfaces

Such PeopleCode programs do not appear in the Project view. Instead, you right-click the name of the definition and select View PeopleCode. You can also access these programs from their associated definitions.

PeopleCode can also be associated with:

- Component records (specific records included in components).

- Component record fields (specific record fields included in components).

Because component record fields and component records do not appear in the Project view, you must access their associated programs through their parent definitions.

See Also

[Chapter 11, "Accessing PeopleCode and Events," Accessing Record Field PeopleCode, page 222](#)

[Chapter 11, "Accessing PeopleCode and Events," Accessing Component PeopleCode, page 228](#)

Accessing Record Field PeopleCode

This section provides an overview of the record field event set and discusses how to:

- Access record field PeopleCode from a record definition.
- Access record field PeopleCode from a page definition.

Understanding Record Field PeopleCode

A record is a table-level definition. Record definitions are of different types, such as SQL table, dynamic view, derived/work, and so on.

Record fields are child definitions of records. Record field PeopleCode programs are child definitions of record fields. A record field can have zero or one PeopleCode programs for each event in the record field event set.

The following events are associated with a record field:

- FieldChange Event
- FieldDefault Event
- FieldEdit Event
- FieldFormula Event
- RowInit Event
- RowSelect Event
- RowDelete Event
- PrePopup Event
- SaveEdit Event
- SavePreChange Event
- Workflow Event


- SavePostChange Event
- SearchInit Event
- SearchSave event

See Also

Chapter 6, "PeopleCode and the Component Processor," page 89

Accessing Record Field PeopleCode from a Record Definition

Record definition fields that have PeopleCode associated with them appear in bold type in record views.



Num	Field Name	Type	Len	Format	H	Short Name	Long Name
1	EMPLID	Char	11	Upper		ID	EmpID
2	CHECKLIST_DT	Date	10			Chklist Dt	Checklist Date
3	CHECKLIST_CD	Char	6	Upper		Checklist	Checklist Code
4	RESPONSIBLE_ID	Char	11	Upper		Resp ID	Responsible ID
5	COMMENTS	Long	0			Comment	Comment

Record definition showing three fields associated with PeopleCode

In the previous example, the first three fields (in boldface font) have PeopleCode associated with them. If you expand the subrecords in a record definition, any fields in the subrecord that have PeopleCode associated with them also appear in bold type.

To access record field PeopleCode from an open record definition:

1. Click the PeopleCode Display button on the toolbar.

A grid appears with a column for each event in the record field event set. Each cell represents a field-event combination. The column names are abbreviations of the record field event names, for example, *FCh* for the FieldChange event and *RIn* for the RowInit event. A check mark appears in the appropriate cell for each field/event combination that has an associated PeopleCode program.

2. Access the PeopleCode using one of these methods:

- Double-click the cell.
- Right-click the cell and select View PeopleCode.
- Select View, PeopleCode.

The PeopleCode Editor appears. If the field/event combination has an associated program, it appears in the editor.

See Also

Chapter 11, "Accessing PeopleCode and Events," Understanding Record Field PeopleCode, page 222

Chapter 12, "Using the PeopleCode Editor," page 233

Accessing Record Field PeopleCode from a Page Definition

You can associate a PeopleCode program with any page control that you can associate with a record field.

To access record field PeopleCode from a page definition, right-click a page control and select View Record PeopleCode. The PeopleCode Editor appears, displaying the first event in the event set associated with the underlying record field of that control.

Button controls are a special case. You can associate a PeopleCode program with a button only if its destination is defined as PeopleCode Command. When the user clicks a button defined using this method, the FieldEdit and FieldChange events are triggered, so the PeopleCode must be associated with one of those two events. Typically, you use the FieldChange event. The following example shows button properties:

Page Field Properties

Type | Label | General

Type

☒ Push Button ☐ Hyperlink

Destination: PeopleCode Command

Record Name: DIMENSION_WRK

Field Name: PB_DIM_OPTIONS

☐ Enable When Page is Display Only

☐ Open in New Window

Alignment

☐ Left ☐ Centered ☐ Right

Actions

Action Type:

Related Control:

Secondary Page

Page:

External Link

☐ Dynamic ☐ Static

URL ID:

Internal Link

Menu:

Component:

Page:

Action:

☐ Use data from current page in search

Process

Type:

Name:

OK Cancel

Page Field Properties dialog box for buttons

To define a command button:

1. In the page definition, double-click the button to access its properties.
2. Select *PeopleCode Command* as the button destination.
3. Select the record and field with which your button and PeopleCode are associated.

You should associate the button with a derived/work record field, which separates its PeopleCode from the PeopleCode associated with any of the page's other underlying record fields. You can then store generic PeopleCode with this field so that you can reuse it with buttons on other pages.

4. Click OK to return to the page.

Right-click the command button and select View PeopleCode to access the PeopleCode Editor.

See Also

[Chapter 12, "Using the PeopleCode Editor," page 233](#)

Accessing Component Record Field PeopleCode

This section provides an overview of component record field PeopleCode and discusses how to access component record field PeopleCode.

Understanding Component Record Field PeopleCode

Component record field PeopleCode is associated with a record field, but only with respect to a component and one of its events. Use this type of association to tailor your programs to a particular component. This PeopleCode is accessible only through the component structure view, not from a record definition.

The following events are associated with a component record field:


- FieldChange Event
- FieldDefault Event
- FieldEdit Event
- PrePopup Event

See Also

Chapter 6, "PeopleCode and the Component Processor," page 89

Accessing Component Record Field PeopleCode

To access PeopleCode associated with a component record field, open the component, click the Select tab, select a field, right-click the field name, and select View PeopleCode. A lightning bolt appears next to the field name if PeopleCode is associated with the field at the component level. If PeopleCode is associated with the field at the record level, then a lightning bolt does not appear, as shown in the following example:



Accessing component record field PeopleCode from the component structure

Note. The Structure tab displays only the runtime state of the PeopleCode. That is, it only displays record field PeopleCode. For example, PeopleCode programs that are orphaned as a result of a page definition change do not appear on the Structure tab. Orphaned PeopleCode programs do appear, however, in the PeopleCode Editor, which displays the design-time view of PeopleCode.

The PeopleCode Editor appears. If that field has associated PeopleCode, then the first program in the component record field event set appears in the editor.

See Also

[Chapter 12, "Using the PeopleCode Editor," page 233](#)

[Chapter 11, "Accessing PeopleCode and Events," Accessing Record Field PeopleCode, page 222](#)

Accessing Component Record PeopleCode

This section provides an overview of component record PeopleCode and discusses how to access component record PeopleCode.

Understanding Component Record PeopleCode

Component record PeopleCode is associated with a record definition, but only with respect to a component and one of its events. Use this type of association to tailor programs to a particular component. This PeopleCode is directly accessible through the component structure view, not from the record definition.

Search records and non-search records in components have different associated event sets. The following events are associated with component search records:

- SearchInit Event
- SearchSave Event

The following events are associated with component non-search records:

- RowDelete Event
- RowInit Event

In rare circumstances, the Component Processor does not run RowInit PeopleCode for some record fields. The Component Processor runs RowInit PeopleCode when it loads the record from the database. However, in some cases, the record can be initialized entirely from the keys for the component. When this happens, RowInit PeopleCode is not run.

- RowSelect Event
- SaveEdit Event
- SavePostChange Event
- SavePreChange Event

See Also

Chapter 6, "PeopleCode and the Component Processor," page 89

Accessing Component Record PeopleCode

To access PeopleCode associated with a component record, open the structure view of the component, select a record, right-click the record name, and select View PeopleCode.

The PeopleCode Editor appears. If the record has associated PeopleCode, then the first program in the component record event set appears in the editor.

See Also

Chapter 12, "Using the PeopleCode Editor," page 233

Accessing Component PeopleCode

This section provides an overview of component PeopleCode and discusses how to access component PeopleCode.

Understanding Component PeopleCode

Component PeopleCode is associated with a component definition and an event.

The following events can be associated with a component:

- PostBuild Event
- PreBuild Event
- SavePostChange Event
- SavePreChange Event
- Workflow Event

See Also

Chapter 6, "PeopleCode and the Component Processor," page 89

Accessing Component PeopleCode

To access PeopleCode associated with a component, open its structure view, select the component name, right-click the name, and select View PeopleCode.

The PeopleCode Editor appears. If the component has associated PeopleCode, the first program in the component event set appears in the editor.

See Also

Chapter 12, "Using the PeopleCode Editor," page 233

Accessing Page PeopleCode

This section provides an overview of page PeopleCode and discusses how to access page PeopleCode.

Understanding Page PeopleCode

Page PeopleCode is associated with a page definition. The page event set consists of a single event, the Activate event, which fires every time the page is activated. This event is valid only for pages that are defined as standard or secondary, and it is not supported for subpages.

See Also

Chapter 6, "PeopleCode and the Component Processor," page 89

Accessing Page PeopleCode

To access PeopleCode associated with a page, right-click any part of the page definition and select View Page PeopleCode.

Note. Page PeopleCode can only be accessed in this way. You cannot access Page PeopleCode from the component definition Structure tab, from a project, or any other way.

The PeopleCode Editor appears. If the page has associated PeopleCode, it appears in the editor.

Note. The term *page PeopleCode* refers to PeopleCode programs owned by pages. Do not confuse *page PeopleCode* with PeopleCode properties related to the appearance of pages, such as the Visible Page Class property.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Page Class"

Chapter 12, "Using the PeopleCode Editor," page 233

Accessing Menu Item PeopleCode

This section provides an overview of menu item PeopleCode and discusses how to:

- Define PeopleCode pop-up menu items.
- Access menu item PeopleCode.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Application Designer Developer's Guide, "Creating Menu Definitions"

Chapter 12, "Using the PeopleCode Editor," page 233

Understanding Menu Item PeopleCode

PeopleTools menus are one of two types, either pop-up or standard, both of which are standalone definitions in the project hierarchy. However, you can only associate PeopleCode with menu items in pop-up menus.

The menu item event set consists of a single event, the ItemSelected Event. This event fires whenever an user selects a menu item from a pop-up menu.

Note. Do not confuse *menu item PeopleCode* with PeopleCode functions related to the appearance of menu items, such as CheckMenuItem.

See Also

Chapter 6, "PeopleCode and the Component Processor," ItemSelected Event, page 133

Defining PeopleCode Pop-Up Menu Items

To define a PeopleCode pop-up menu item:

1. In the open pop-up menu definition, double-click the menu item to access its properties.
If you are creating a new menu item, double-click the empty rectangle at the bottom of the pop-up menu.
The Menu Item Properties dialog box appears.
2. If this is a new menu item, enter a name and a label for the item.
3. Select *PeopleCode* from the Type group box.
4. Click OK to close the Menu Item Properties dialog box.

Accessing Menu Item PeopleCode

To access pop-up menu item PeopleCode:

1. Open the pop-up menu definition.
2. Right-click the menu item and select View PeopleCode.

The PeopleCode Editor appears, displaying the associated program for that menu item, if any.

Copying PeopleCode with a Parent Definition

When you copy a Application Designer definition that contains PeopleCode, you can choose whether to copy all PeopleCode programs and the definition. Each copy of the definition receives a separate copy of the PeopleCode programs.

To copy a definition with its PeopleCode:

1. Open the definition you want to copy.
2. Select File, Save As.

The Save As dialog appears.

3. Type a name for the new definition in the dialog box.
4. Click OK, and then click Yes to copy the PeopleCode.

Click Yes to copy all PeopleCode associated with the definition.

Upgrading PeopleCode Programs

You can upgrade PeopleCode programs independently of the definitions with which they are associated. Refer to the upgrade instructions for your product for details.

Chapter 12

Using the PeopleCode Editor

This chapter discusses how to:

- Navigate between PeopleCode programs.
- Use the PeopleCode Editor.
- Generate PeopleCode using drag-and-drop.

Navigating Between PeopleCode Programs

After you access a PeopleCode program associated with a Application Designer definition, you can access programs associated with other related definitions without having to close the editor window.

This section provides an overview of the PeopleCode Editor window and discusses how to:


- Navigate between programs associated with a definition and its children.
- Navigate between programs associated with a definition's event set.

See Also

[Chapter 11, "Accessing PeopleCode and Events," page 219](#)

Understanding the PeopleCode Editor Window

Application Designer supplies an independent editor window for each parent definition, such as a record, component interface, or an analytic model, for which you invoke the editor. The editor window's title bar displays the name and type of the parent definition, as shown in the following illustration:



PeopleCode Editor window with record field PeopleCode

The editor window contains the main edit pane, the drop-down definition list at the upper-left, and the drop-down event list at the upper-right. The drop-down lists enable you to navigate directly to the PeopleCode associated with related child definitions, for example, fields within a record and their event sets.

Note. When you make a selection from either drop-down list box, your selected entry has a yellow background, indicating that you must click the edit pane before you can start typing.

You can open as many editor windows as you want and resize them in Application Designer. Each line of code wraps automatically based on the window's current width. A vertical scroll bar appears if the program has more lines than the editor can display in the edit pane.

Note. You cannot open two editor windows for a single parent definition, or for any two of its child definitions.

See Also

[Chapter 12, "Using the PeopleCode Editor," Navigating Between Programs Associated With a Definition and Its Children, page 235](#)

[Chapter 12, "Using the PeopleCode Editor," Navigating Between Programs Associated With Events, page 235](#)

Navigating Between Programs Associated With a Definition and Its Children

You use the drop-down definition list to navigate between PeopleCode programs that are associated with a parent definition and its children. The list displays the complete hierarchy of child definitions to which you can navigate; bold items have PeopleCode associated with at least one event in the item's event set. The structure of the definition list depends on the type of parent definition. Parent definitions include:

- Records.

Select record fields from the record drop-down list. The record name appears at the top of the list as a visual clue to clarify the location of the record fields, but you cannot associate PeopleCode with a record.

- Components.

Select component records and component record fields from the component drop-down list.

- Pages.


Select the page definition from the page drop-down list.

- Pop-up menus.

Select pop-up menu items from the menu drop-down list. The menu and menu bars appear in the list as visual clues, but you cannot associate PeopleCode with these elements.

Navigating Between Programs Associated With Events

Use the PeopleCode Editor's drop-down event list to select an event from the event set of the currently selected definition. Use this event list to navigate between PeopleCode programs that are associated with that definition. For every definition-event combination with associated PeopleCode, the event name is displayed in bold, and it appears at the top of the event list, as shown in the following illustration:



Selecting an event from the PeopleCode Editor

See Also

[Chapter 11, "Accessing PeopleCode and Events," page 219](#)

[Chapter 6, "PeopleCode and the Component Processor," page 89](#)

Using the PeopleCode Editor

This section provides an overview of the PeopleCode Editor and color-coded language elements and discusses how to:

- Write and edit PeopleCode.
- Format code automatically.
- Use drag-and-drop editing.
- Access PeopleCode external functions.
- Access definitions and associated PeopleCode.
- Access help.
- Set up help.
- Change colors in the PeopleCode Editor.

- Select a font for the PeopleCode Editor.
- Change word wrap in the PeopleCode Editor.
- Use PeopleCode Event properties.

Understanding the PeopleCode Editor

The PeopleCode Editor works much like any other text editor, but has capabilities specifically geared toward the PeopleTools environment. Some of its features include:

- Editing functions are integrated with the menus and toolbar of Application Designer and are also accessible from a pop-up window.
- It checks, formats, and saves all programs associated with Application Designer definitions simultaneously when any definition is saved.
- It includes a Validate Syntax command for checking and formatting a single PeopleCode program without saving.
- It supports standard Microsoft Windows drag-and-drop editing.
- It supports color-coding for the different elements of the PeopleCode language.
- It supports word wrap based on either the size of the editor window or a specific number of characters per line.
- You can open separate instances of the editor simultaneously, and you can use a drag-and-drop text operation between programs.
- You can open the definition with which the current set of PeopleCode programs is associated from within the PeopleCode Editor.
- You can open a field, record, page, file layout, or other definitions from a PeopleCode reference to the field, record, page, or file layout, and so on.
- You can access PeopleCode programs associated with a field, record, page or file layout, or other definitions from a PeopleCode reference to the field, record, page, or file layout, and so on.
- You can open a PeopleCode Editor window containing an external function definition from a function declaration or function call.
- You can press F1 with the cursor in a PeopleCode built-in function, method, meta-SQL, and so on, to open the PeopleSoft help for that item.

Writing and Editing PeopleCode

The PeopleCode Editor supports standard editing function commands such as Save, Cancel, Cut, Copy, Paste, Find, Replace, and Undo, from the PeopleCode Editor pop-up menu. Cut, Copy, and Paste use standard Microsoft Windows keyboard shortcuts. You can also cut, copy, and paste within the same PeopleCode program or across multiple programs.

Use these buttons to perform editing functions:



Save the current PeopleCode program. You can also use the key combination CTRL+S.



Cut the selected text or item. You can also use the CTRL+X or SHIFT+DEL key combinations.



Copy the selected text or item. You can also use the CTRL+C or CTRL+INS key combinations.



Paste from the clipboard. You can also use the CTRL+V or SHIFT+INS key combinations.



Find specified text. You can also use the key combination CTRL+F.



Find and replace specified text. You can also use the key combination CTRL+H.



Validate the current PeopleCode program.

Undo the last change. Use the CTRL+Z or ALT+BACKSPACE key combinations.


Cancel the current operation. Use Esc key.

See Also

[Appendix A, "PeopleCode Editor Short Cut Keys," page 313](#)

Find and Replace Dialogs

When you use the Find and Replace functions, any text string that is highlighted appears when either the Find or Replace dialog boxes are called. For example, if you select the method `ActiveRowCount` it appears in the Find dialog box when it's called, as shown in the following example:



Find dialog box


You can move through finding and replacing text strings one string at a time, or click Replace All to replace globally. The Undo function is available to undo the last replace or replace all.

The Mark All button places a bookmark next to all lines that have the matching text. Use Shift+ctrl+f2 to remove all bookmarks.

With the Replace dialog box, you can select to replace text either in a selected section or a whole file (that is, a PeopleCode program.)

Go To Dialog

Use the Go To dialog box to specify a line number in the current program, then go to that line. If you have line wrap not enabled, you can specify to go to statement numbers instead of line numbers.



Go To dialog box

Validate Syntax Utility

To check the syntax of the current PeopleCode program and format it if it is syntactically correct, do one of the following:

- Click the Validate Syntax button on the Application Designer toolbar.
- Within Application Designer, select Tools, Validate Syntax.
- Right-click in the PeopleCode Editor window, then select Validate Syntax.

The Validate utility has several functions, such as finding undeclared variables, mismatching data types, or invalid methods or properties for a class. You can check either a single component or an entire project.

Errors or warnings produced by the Validate utility are displayed in the Validate tab at the bottom of the PeopleCode Editor window.

Any variables that you don't declare are automatically declared for you, and a warning message appears in the Validate tab for each undeclared variable. You can right-click in the Validate tab and select Clear to delete all the warnings listed there, then use the Validate utility again to ensure that your code runs without errors or warnings.

Note. This feature is convenient if you have written multiple PeopleCode programs and you want to check the syntax of one without saving. All PeopleCode programs associated with an item (record, component, and so on) are checked prior to saving.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Application Designer Developer's Guide, "Working With Projects," Validating Projects

Chapter 15, "Debugging Your Application," Compiling All PeopleCode Programs at Once, page 281

Formatting Code Automatically

You do not need to format your PeopleCode statements; you need only to use the correct syntax. When you save or validate, the system formats the code according to the rules in the PeopleCode tables, no matter how you entered it originally. The PeopleCode Editor automatically converts field names to uppercase and indents statements.

PeopleCode is case-insensitive, except for quoted literals. PeopleCode does not format anything surrounded by quotation marks. String comparisons, however, are case-sensitive. When you compare the contents of a field or a variable to a string literal, make sure the literal is in the correct case.

All field names in a PeopleCode program must be fully qualified, even if the field is on the same record definition as the PeopleCode program. However, you only need to type in the name of the field. The editor validates if the field exists on the current record, and reformats the field name to *recordname.fieldname*.

Using Drag-and-Drop Editing

In addition to the standard keyboard shortcuts and toolbar buttons, you can copy or move text within a window or between two PeopleCode Editor windows by using the mouse and the CTRL key.

Note. You cannot open two editor windows for a single parent definition, or for any two of its child definitions.

To move text between instances of the PeopleCode Editor:

1. Select the text you want to move.
2. Place the mouse over the text and drag the text to the other PeopleCode Editor window.
3. When the cursor appears at the place where you want to insert the text, release the mouse button.

To copy text between instances of the PeopleCode Editor:

1. Select the text you want to move.
2. Hold down the CTRL key as you drag the text to the other PeopleCode Editor window.
3. When the cursor appears at the place where you want to insert the text, release the mouse button.

Accessing PeopleCode External Functions

An external PeopleCode function is a function written in PeopleCode (as opposed to a built-in function or external DLL function) and defined in a program outside the one from which it is called. External PeopleCode functions can be defined in any record PeopleCode program, but typically they are stored in the FieldFormula event in records beginning with *FUNCLIB_*.

The PeopleCode Editor provides immediate access to external PeopleCode function definitions. Right-click the function name in the program where the function is called, then select View Function *FunctionName*. This opens a new PeopleCode Editor window containing the external function definition.

Note. Internet scripts are contained in records similar to FUNCLIB_ records. However, their names begin with *WEBLIB_*.

Accessing PeopleCode Application Packages and Application Classes


The PeopleCode Editor provides immediate access to application packages, application classes, and application class method definitions.

Right-click the package, class, or method name and, depending on the context, select from:

- View Application Package
- View Application Class
- View Application Class Method


This opens the application package or a new PeopleCode Editor window containing the application class.

The following example shows the context menu for a fully-qualified application class name.



Context menu with options for View Application Package and View Application Class

The following example shows the context menu for a method.



Context menu with options for View Application Class Method and View Application Class

Note. The application class context menu is not available for methods that are called by indirection.

In the following example the method `CallMe` would not be available to view using the context menu.

```
Object0.GetObject().CallMe();
```

Accessing Methods in Derived Classes

A method that is defined only in the superclass is not available if you attempt to view it using View Application Class Method with the derived class, or subclass.

For example, in the following code snippet `CCI_CRM` extends `CCI_BASE`. The method `Validate` is not defined in `CCI_CRM`; it is available to `CCI_CRM` by extension. The method `Submit`, on the other hand, is overridden in `CCI_CRM`.

If you right-click `Validate` and select View Application Class Method, the cursor will be placed at the beginning of the application class `CCR_CRM`, not at the method definition in `CCI_BASE`.

If you right-click `Submit` and select View Application Class Method, you will be taken to the method definition for `Submit` in `CCI_CRM`.

```
Import EOCC:CCI_CRM;
&CCI = Create EOCC:CCI_CRM();
&CCI.Validate(&Card);
&CCI.Submit(&Card);
```

This may be helpful when you need to know whether a method has been overridden.

Accessing Definitions and Associated PeopleCode

You can open fields, records, pages, application packages, and other definitions from the PeopleCode Editor. Or you can open a new PeopleCode Editor window containing the programs associated with a field, record, page, application class, or other definition.

To open a definition from the PeopleCode Editor, right-click a PeopleCode definition reference and select View Definition or View Application Package.

For example, you could open definitions by clicking the following references:

- `Record.BUS_EXPENSE_PER`
- `BUS_EXPENSE_PER.EXPENSE_PERIOD_DT`
- `Page.BUSINESS_EXPENSES`
- `PT_BRANDING:BrandingBase`

If you access a record definition from a record field reference (that is, *recordname.fieldname*) the specified record field is selected when the record definition opens.

To open a new PeopleCode editor window, right-click a reference to the definition and select View PeopleCode or, for application class PeopleCode, select View Application Class Method or View Application Class.

For example, you can access record PeopleCode from the following record and record field references:

- Record.BUS_EXPENSE_PER
- BUS_EXPENSE_PER.EXPENSE_PERIOD_DT

Note. You can only view the PeopleCode and definition when the text is in the format *recordname.fieldname*. If the text is in the format *method(i).recordname,method(i).fieldname*, or *&MyRecord.Fieldname*, the View PeopleCode and View Definition commands are not available.

You can access application class PeopleCode from the following references:

- PT_BRANDING:BrandingBase
- %This.ValidateSave(&aErrs)

Accessing Help

The PeopleCode Editor has context-sensitive online help for all PeopleCode built-in functions, methods, properties, system variables, and meta-SQL. To access online help, place the cursor in the name of what you want to look up, then press F1. If there is a corresponding entry in the online reference system it appears; otherwise a No Help Available error message appears.

If more than one entry is applicable, a pop-up window that lists all applicable entries appears. Select the correct entry.

See Also

Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration, "Using PeopleTools Utilities," PeopleTools Options

Setting up Help

To set up the help, use the F1 Help URL field on the PeopleTools Options page to specify where the documentation is stored.

The format of the URL is as follows:

http://doc_location/f1search.htm?ContextID=%CONTEXT_ID%&LangCD=%LANG_CD%

The *doc_location* specifies where the documentation files are located on your system. The rest of the URL exactly the above format.

For example, you might place the following URL in the F1 Help URL field:

http://Pandora/doc/f1search.htm?ContextID=%CONTEXT_ID%&LangCD=%LANG_CD%

After you specify the help location, you must exit all PeopleTools sessions and start again before you can access the help.

Changing Colors in the PeopleCode Editor

You can change the display (foreground) color for many language elements in the PeopleCode Editor, including quoted strings, keywords, and built-in functions. You can also change the background color.

To change the display colors:

1. Select Edit, Display Font and Colors.
2. Select the language element that you want to change.
3. Select the foreground color.

If you click the Automatic check box, the default color is used.

A box displaying the selected color is only available if the Automatic check box is not selected.

If you click the box displaying the selected color, the standard color chart for your display appears. If you click Other from this dialog or click the drop-down list on the Font and Color Settings dialog box, the custom color chart for your display appears.

4. Select the background color.

If you click Reset All, the default colors for the PeopleCode language elements are reassigned.

Selecting a Font for the PeopleCode Editor

The default font for the PeopleCode Editor is 9-point Courier New.

To change the PeopleCode Editor font, select Edit, Display Fonts and Colors. Use this dialog box to change the font for the editor.

Note. When you select a font for the PeopleCode Editor, the font selection dialog box provides choices based on a character set appropriate for your international version of Microsoft Windows. If you experience trouble embedding foreign characters (such as Thai characters) in PeopleCode, you might need to change the font setting. If you are trying to display Thai characters in Microsoft Windows 95, you might also need to change your keyboard input settings for the characters to display correctly. You can change your keyboard input settings from the Input Locales tab on the Windows Regional Settings control panel, or on the Keyboard control panel.


Changing Word Wrap in the PeopleCode Editor

The PeopleCode Editor supports text word wrapping. You can turn word wrapping on and off for an open editor window. You can also specify the default value for word wrap, as well as whether the text wraps to the editor's window size or to a fixed number of characters per line.

To turn word wrapping on or off for an open editor window, go to Edit, Word Wrap. After you close Application Designer, all word wrap values are reset to the default value for the editor.

Specifying Word Wrap Options

Go to the Tools, Options dialog box, Editors tab, to specify the word wrap options.




Options dialog box: Editors tab

Enable (word wrap)	Specify whether word wrap is the default mode when opening the editor. If this box is not checked, wrapping text based on window size is the default.
Wrap on Window Size	Specify whether the text wraps based on the size of the window.
Wrap on Line Size	Specify whether the text wraps based on the number of characters in a line. If this box is checked, you can specify the number of maximum number of characters per line.
Maximum Characters per Line	Specify the maximum number of characters allowed for a line before the text wraps. The default value is 90. Valid values are between 25 and 2000.

Using the PeopleCode Event Properties

To access the PeopleCode Event properties, open a PeopleCode editor window, then either press Alt + Enter or click the Properties button.



PeopleCode Event Properties dialog box

Note. This dialog box has been deprecated. It has no effect on the location of the execution of code.

Generating PeopleCode Using Drag-and-Drop

You can generate references to definitions using a drag-and-drop operation. You can also generate PeopleCode templates for accessing business interlinks and component interfaces.

This section discusses how to:

- Generate definition references.
- Generate PeopleCode for a business interlink.
- Generate PeopleCode for a component interface.
- Generate PeopleCode for a file layout.

Generating Definition References

When you drag definitions, such as menus, records, record fields, and pages, from a project into an open PeopleCode editor window, you generate a reference to the definition. For example, suppose your project contain a component named QEACTIONITY_GUIDE_1. If you drag the QEACTIONITY_GUIDE_1 component definition from the project into an open PeopleCode window, the word QEACTIONITY_GUIDE_1 prefixed with the keyword **COMPONENT** is written to the PeopleCode program in the place where you dragged the definition.

Generating PeopleCode for a Business Interlink

After you create a business interlink definition, you use PeopleCode to instantiate an interlink object and activate the interlink plug-in. This PeopleCode can be long and complex. Rather than write it directly, you can drag and drop the business interlink definition from the Application Designer Project view into an open PeopleCode edit pane. PeopleCode Application Designer analyzes the definition and generates initial PeopleCode as a template, which you can modify to suit your purpose.

The following is a snippet of the code that is generated:

```
/* ==>

/* ==>
This is a dynamically generated PeopleCode template to be
used only as a helper to the application developer.
You need to replace all references to '<*>' OR default values
with references to PeopleCode variables and/or a Rec.Fields.*/

/* ==> Declare and instantiate: */
Local Interlink &QE_AE_NONSSL__1;
Local BIDocs &inDoc;
Local BIDocs &outDoc;
Local boolean &RSLT;
Local number &EXECSRSLT;
&QE_AE_NONSSL__1 = GetInterlink(INTERLINK.QE_AE_NONSSL_BI);
.
.
.
.
```

Generating PeopleCode for a Component Interface

After you create a component interface definition, you can use PeopleCode to access it. This PeopleCode can be long and complex. Rather than write it directly, you can drag and drop the component interface definition from the Application Designer Project view into an open PeopleCode edit pane. Application Designer analyzes the definition and generates initial PeopleCode as a template, which you can modify to meet your requirements.

The following is a snippet of the code that is generated:

```
/* ==>

This is a dynamically generated PeopleCode template to be
used only as a helper to the application developer.
You need to replace all references to '<*>' OR default values
with references to PeopleCode variables and/or a Rec.Fields. */

Local ApiObject &oSession;
Local ApiObject &oCurrencyCdCi;
Local ApiObject &oPSMessageCollection;
Local ApiObject &oPSMessage;
Local File &LogFile;
Local number &i;
Local String &strErrMsgSetNum, &strErrMsgNum, &strErrMsgText,
&strErrType;
.
.
.
```

You can also access a component interface using the component object model (COM). You can automatically generate a Visual Basic template, a Java template, or a C template, similar to the PeopleCode template, to begin.

To generate a template:

1. Open a component interface in Application Designer.
2. Right-click anywhere in the open component interface and select a template type.

You must save the component interface before generating the template.

When the template is successfully generated, a message appears with the full path and name of the file containing the template.

3. Open the generated file and modify the source code to meet the needs of your application.

The following is the initial code snippet that is generated for a Visual Basic template:

```
Option Explicit
'====>
'This is a dynamically generated Visual Basic template to be
'used only as a helper to the application developer.
'You need to replace all references to '<*>' OR default
'values with references to Visual Basic variables.

Dim oSession As PeopleSoft_PeopleSoft.Session

Private Sub ErrorHandler()
'***** Display PeopleSoft Error Messages *****
If Not oSession Is Nothing Then
    If oSession.ErrorPending Or oSession.WarningPending Then
        Dim oPSMessageCollection As PSMessageCollection
        Dim oPSMessage As PSMessage
        Set oPSMessageCollection = oSession.PSMessages
        Dim i As Integer
        For i = 1 To oPSMessageCollection.Count
            Set oPSMessage = oPSMessageCollection.Item(i)
            Debug.Print "(" & oPSMessage.MessageNumber & "," &
oPSMessage.MessageSetNumber & ") : " & oPSMessage.Text
        Next i
        '***** Done processing messages in the collection;
        '***** OK to delete *****
        oPSMessageCollection.DeleteAll
    End If
End If
End Sub
.
.
.
.
```

Generating PeopleCode for a File Layout

After you create a file layout definition, you can use PeopleCode to access it. This PeopleCode can be long and complex. Rather than write it directly, you can drag and drop the file layout definition from the PeopleCode Application Designer Project view into an open PeopleCode edit pane. Application Designer analyzes the definition and generates initial PeopleCode as a template, which you can modify to meet your requirements.

This example shows some of the code that is generated:

```
Function EditRecord(&REC As Record) Returns boolean ;
Local integer &E;

REM    &REC.ExecuteEdits(%Edit_Required + %Edit_DateRange +
%Edit_YesNo + %Edit_TranslateTable + %Edit_PromptTable +
%Edit_OneZero);

    &REC.ExecuteEdits(%Edit_Required + %Edit_DateRange +
%Edit_YesNo + %Edit_OneZero);
    If &REC.IsEditError Then
        For &E = 1 To &REC.FieldCount
            &MYFIELD = &REC.GetField(&E);
            If &MYFIELD.EditError Then
                &MSGNUM = &MYFIELD.MessageNumber;
                &MSGSET = &MYFIELD.MessageSetNumber;
                &LOGFILE.WriteLine("****Record:" | &REC.Name | ",
Field:" | &MYFIELD.Name );
                &LOGFILE.WriteLine("*****" | MsgGet(&MSGSET,
&MSGNUM, ""));
            End-If;
        End-For;
        Return False;
    Else
        Return True;
    End-If;
End-Function;
.
.
.
.
```

Chapter 13

Using the SQL Editor

This chapter provides an overview of the SQL editor window and discusses how to:

- Access SQL definition properties.
- Access the SQL editor.
- Use the SQL editor.

See Also

Chapter 12, "Using the PeopleCode Editor," page 233


Understanding the SQL Editor Window

Use the SQL Editor to create SQL for SQL definitions, record views, and Application Engine programs.

The SQL Editor and the PeopleCode editor interfaces are similar. You can add, delete, and change text; you can use the find and replace function; and you can validate the SQL. When you save a SQL definition, the code is automatically formatted (indented and so on) the same as it is for a PeopleCode program. You can select the colors for displaying keywords, comments, operators, and so on. You can also specify word wrap options.

See Chapter 12, "Using the PeopleCode Editor," Using the PeopleCode Editor, page 236.

The title bar of the editor window displays either the name of the SQL definition or the name of the component that contains the SQL. For example, if the SQL statement is part of an Application Engine program, then the names of the program, the section, the step, and the action are listed in the title bar, as shown in the following example:



Example of Application Engine program SQL in the SQL editor window

The editor window consists of the main edit pane. For SQL definitions and SQL used with records, a drop-down database list appears at the upper left. For SQL definitions, a drop-down effective-date list is available at the upper right.

Note. When you make a selection from either drop-down list box, your selected entry has a yellow background, indicating that you must click the edit pane before you can start typing.

Accessing SQL Definition Properties

Do one of the following to access the definition properties for the SQL definition:

- Press ALT+Enter.
- Select File, Definition Properties.
- Right-click in the definition and select Definition Properties.

Use general properties to specify a description for the SQL definition as well as additional comments. The description appears in Application Designer search lists.

Use the advanced properties to display an effective date with the SQL definition.

Note. The Audit SQL field on the Advanced Properties tab is not used.

Accessing the SQL Editor


This section discusses how to:

- Create SQL definitions.
- Create dynamic view or SQL view records.
- Access the SQL editor from Application Engine programs.

You access the SQL editor differently for each type of component.

Creating SQL Definitions

A SQL definition contains SQL statements, which can be entire SQL programs or just fragments that you want to reuse. You can access, create, change, or delete SQL definitions using Application Designer, or you can use the SQL class in PeopleCode. You can upgrade SQL definitions, and you can add them to a project. The following example shows a SQL definition:



Example of SQL definition with effective date

To create a SQL definition:

1. From Application Designer, select File, New, SQL.

2. Specify the database type to associate with the SQL definition.

You can associate more than one database type with a single SQL definition. In PeopleCode, you can specify the appropriate database type for the program. However, at least one of the SQL statements must be of type Default.

3. (Optional) Specify an effective date.

To specify an effective date with your SQL definition:

- a. Access the object properties by selecting File, Object Properties.

Alternatively, select the SQL definition, right-click it, and then select Object Properties, or press ALT + ENTER.

- b. Click the Advanced tab, and then click Show Effective Date.

When you click OK, the SQL definition shows a date in the right-hand drop-down menu.

4. Enter the SQL code.

You do not need to format your code. The SQL editor formats it when you save the SQL definition.


See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleSoft Application Designer Developer's Guide, "Using PeopleSoft Application Designer"

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "SQL Class"

Creating Dynamic View or SQL View Records

When you create a SQL view or dynamic view record definition, you enter a SQL view *Select* statement to indicate the field values that you want to join and the tables that contain the field values. You do this in the SQL editor, as shown in the following example:



SQL editor for SQL view record definition

Access the SQL editor with record definitions.

1. Open or create a dynamic view or SQL view record definition.
2. Select the Record Type tab.
3. Click the Click to Open SQL Editor button.

You can select a database type, but not an effective date, from the SQL editor for dynamic view and SQL view record definitions.

Note. You must be sure to save record definitions of the SQL View type before opening the SQL editor. Once the SQL editor is open, the Save options are disabled and inaccessible. If you do not save your changes before opening the SQL editor, you may lose your work.

See Also

Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration, "Using PeopleTools Utilities," PeopleTools Options


Accessing the SQL Editor from Application Engine Programs

You can access the SQL editor from the following action types:

- Do Select
- Do Until

- Do When
- Do While
- SQL

The following example shows an Application Engine program in the SQL editor:



Example of an Application Engine program in the SQL editor window

Access the SQL editor in an Application Engine program.

1. Open the Application Engine program.
2. Select the action.
3. Either right-click and select View SQL, or select View, SQL.

Select the database type and effective date for this SQL in the section, not in the SQL editor.

Using the SQL Editor

The SQL editor works similarly to any other text editor. Many of the same functions are available as in the PeopleCode editor, for example, cut, paste, find, and replace.

When you right-click in an open SQL editor window, you see available functions for the SQL editor:

Format Display	
Validate Syntax	
Resolve Meta SQL	
Delete Statement	F8
Cut	Ctrl+X
Copy	Ctrl+C
Paste	Ctrl+V
Undo	Ctrl+Z
Find...	Ctrl+F
Replace...	Ctrl+H
Object Properties...	

SQL editor shortcut menu

This table describes the functions that are available in the SQL editor but not the PeopleCode editor:

Function	Description
Format Display	You do not need to format your SQL statements; you only need to use the correct syntax. When you save or validate, the system formats the code according to the rules in the PeopleCode tables, no matter how you entered it originally. It automatically converts field names to uppercase and indents statements. The resulting look of SQL is consistent with other programs in the system.
Resolve Meta-SQL	If the SQL contains meta-SQL, select Resolve Meta-SQL to expand the meta-SQL statement in the output window. This option is on the Meta-SQL tab.
Delete Statement	You can delete standalone SQL statements. This menu item is not enabled with SQL statements that have a database type of Default with no effective date, or for statements that have a database type of Default and an effective date of 01/01/1900.

This example, using Resolve Meta-SQL, shows how the following code expands:

```
%Join(COMMON_FIELDS, PSAEAPPLDEFN ABC, PSAESECTDEFN XYZ)
```



Meta-SQL expanded in the output window

See Also

Chapter 12, "Using the PeopleCode Editor," Writing and Editing PeopleCode, page 237

Chapter 14

Creating Application Packages and Classes

This chapter provides an overview of application packages and discusses how to:

- Create application packages.
- Use the Application Package Editor.
- Edit application package classes.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Application Classes"

Understanding Application Packages


Use the Application Packages Editor to create application packages. A package contains other packages or application classes. A subpackage is any package within a primary, or parent, package.

The title bar of the editor window displays the name of the application package definition. The main window displays the classes and other application packages that make up the application package definition.

The application package hierarchy is displayed as a tree structure. You can use the expand icon (+) and the collapse icon (-) to expand or collapse individual nodes.

To expand all the nodes in a package select View, Expand All or click the Expand All Nodes button on the toolbar. To collapse all the nodes in a package select View, Collapse All or click the Collapse All Nodes button on the toolbar.

In the following example, PTAF_UTILITIES is the primary package, and Encryption, Exception Utilities, Integration, and so on, are subpackages. Printable Document is a class in the PTAF_UTILITIES application package, while Base64 and PSCipher are classes in the Encryption subpackage.



Application Package Editor main window


Creating Application Packages

This section provides an overview of package names and discusses how to create application package definitions.

Understanding Package Names

You can create a subpackage with the same name as another package or subpackage within the same application package definition, as long as the fully qualified name is unique for each subpackage. Each subpackage is differentiated by the full path name of the class (from the package definition name and the subpackage name).

For example, suppose in the application class PT_FRUIT, where PT_FRUIT is the primary class, you had the following structure of subpackages (no classes are listed in this example):



Example of application package naming conventions

In this example, three subpackages are named `Raw`, but the fully qualified name for each is unique. For example, the first one is qualified by the name of the primary package. Its fully qualified name is `PT_FRUIT:Raw`.

The other `Raw` subpackages are also qualified by the subpackages that contain them. Their names are `PT_FRUIT:Recipies:Raw` and `PT_FRUIT:Smoothies:Raw`.

Similarly, you cannot create two classes with the same name within a given package or subpackage. You can create classes with the same name within the same application package definition, just like subpackages, as long as the fully qualified name is unique. Each class is differentiated by the full path name of the class.

Note. You cannot create a structure for which more than two levels of subpackages are defined below the primary package.

Creating Application Package Definitions

This section discusses how to create a new application package or insert a new package or class into an application package.

To create a new application package, access Application Designer and select **File, New, Application Package**.

To insert a new package or class, open an application package definition. Select a package or subpackage and select **Insert, Package** or **Insert, Application Class**.

Application package names and application class names must begin with an alphabetic character and must consist of only alphanumeric characters and underscores (`_`).

Note. In certain cases you may encounter an error if you use **Save As** to create a new application package.


The error occurs when you choose to save the PeopleCode with the application package and the PeopleCode uses a `%This` system variable. The `%This` system variable is used in application class PeopleCode to refer to the current object.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode API Reference, "Application Classes," Using `%This` with Constructors

Using the Application Package Editor

When you right-click an open Application Package Editor window, you see the available functions:



Application Package Editor pop-up menu


Cut, Copy, and Paste	Not available for this release. Instead, insert new subpackage and class nodes where needed and use the clipboard to copy and paste PeopleCode text from class to class. To copy the primary package, select File, Save As.
Delete	Click to delete either a class or a package. The PeopleCode text is not actually deleted until you save the application package. Deleted PeopleCode classes can be recovered by reinserting the class node, as long as you have not saved in the interim.
Insert App Class (insert application class)	Click to insert an application class. Because classes cannot have children (subclasses), they can be inserted only into an existing package.
Insert Package	Click to insert an application package. You can only insert packages into an existing package or subpackage.
Rename	Click to rename either a class or a subpackage. When you save the definition, all PeopleCode programs associated with the renamed class are also updated. To rename the primary package definition, select File, Rename.
View PeopleCode	Click to view the associated PeopleCode. PeopleCode can be defined only for application classes, and it is not directly related to package nodes.
Print	Click to print the application package definition, including all the PeopleCode in the classes.

Editing Application Package Classes

From an application package, you can access the PeopleCode programs associated with the classes of the package.

The Application Packages Editor and the PeopleCode Editor interfaces are similar. You can add, delete, and change text, you can use the find and replace functions, and you can validate syntax. When you save application packages, the code is automatically formatted (indented and so on), just as it is in the PeopleCode Editor.

The editor window contains the main edit pane, the drop-down definition list at the upper-left, and the drop-down event list at the upper-right, as shown in the following example:



Example of Application Packages Editor window

Only one event is defined for an application class, OnExecute. This is not an event in the Component Processor flow. The application class runs when called.

The drop-down list at the upper-left enables you to navigate directly to the PeopleCode associated with every class in the package, as well as to every subpackage and its classes.

To edit an application class:

1. Open the application package.
2. Select a class.
3. Either select View, PeopleCode or right-click and select View PeopleCode.

A PeopleCode Editor window appears.

See Also

Chapter 12, "Using the PeopleCode Editor," Writing and Editing PeopleCode, page 237

Chapter 15

Debugging Your Application

This chapter provides an overview of the PeopleCode debugger and discusses how to:

- Access the PeopleCode debugger.
- Use PeopleCode debugger features.
- Use PeopleCode debugger options.
- Set up the debugging environment.
- Compile PeopleCode programs at once.
- Set PeopleCode debugger log options.
- Interpret the PeopleCode debugger log file.
- Use application logging.
- Use the Find In feature.
- Use cross-reference reports.

Understanding the PeopleCode Debugger

The PeopleCode debugger is an integrated part of Application Designer. The interface to the debugger has a visual indicator of breakpoints, an arrow indicating the current line, and the ability to step through code. You can inspect the value of a variable by holding the cursor over it and reading the pop-up bubble help. The debugger also provides variable inspection windows for global variables, local variables, function parameters, and component-scoped variables. It also enables PeopleCode objects to be expanded, so you can inspect their component parts.

Note. The PeopleCode debugger does not work on Microsoft Windows 95 or Windows 98.

Do not try to use the PeopleCode debugger with the SwitchUser function. Only the first user is logged into the PeopleCode debugger. Once the switch occurs, breakpoints, logging, and so on are no longer executed.

Accessing the PeopleCode Debugger

Note. You can start a debugging session either before or after you start a PeopleSoft component.

1. Determine whether to run Application Designer in two-tier mode or three-tier mode.

If you are debugging Application Engine or component interface PeopleCode, run Application Designer in two-tier mode, with a direct connection to the database.

If you are debugging an application in PeopleSoft Pure Internet Architecture (PIA), run Application Designer in three-tier mode, through the application server. You must be logged on to PIA and to Application Designer using the same user ID.


2. Access the debugger through Application Designer by selecting Debug, PeopleCode Debugger Mode.

The Local Variables watch pane and the Call Stack pane open. PeopleCode programs that had breakpoints set from your previous debugging session are opened also, and the breakpoints are restored.

If you did not have breakpoints set, open the PeopleCode program you want to debug and enter debug mode. The debugger will open with the current PeopleCode program and you can set your breakpoints.

Note. If you have already opened the debugger and then closed it, the menu may not change correctly to enable you to access the debugger a second time. If this occurs, click the Local Variables window, and then try the Debug menu again.

In PIA, navigate to the point where the breakpoint occurs. Your application pauses and the Application Designer icon flashes in the task bar. Switch to Application Designer to step through your program or continue running it.



Application Designer icon flashes in the toolbar when the application hits a breakpoint

If the debugger does not engage, check that you used the same user ID to log into PIA and Application Designer, then check your application server configuration to verify that PeopleCode debugger is enabled.

Note. Your security administrator has options for allowing users to access different parts of Application Designer, including the PeopleCode debugger. If you are having problems accessing the debugger, you may need to contact your system administrator about your security access. You can access the PeopleCode debugger from outside a firewall.


Using PeopleCode Debugger Features

This section discusses:

- Visible current line of execution.
- Visible breakpoints.
- Hover inspect.
- Single debugger.
- Variable panes.
- General debugging tips.

Visible Current Line of Execution

This example shows the current line indicator (green arrow displayed in left-hand gutter):



PeopleCode debugger with current line of execution

Visible Breakpoints


The PeopleCode debugger supports visual indicators that signify breakpoint locations. In the following example, the current line indicator (green arrow) is shown at the first line, and the breakpoint (red dot displayed in left-hand gutter) is on line 8:

All breakpoints are saved when Exit Debug Mode is selected.

Note. You cannot set breakpoints in function declarations, variable declarations, or comments.

Hover Inspect

If the program is already running, you can see the actual values for the variables by holding the cursor over them. The current value appears in a pop-up window, as shown in the following example:



PeopleCode debugger with breakpoint, current line of execution, and hover inspect

Hover inspect is implemented only for simple variables and fields.

Hover inspect is not implemented for object expressions (for example, rowset assignments and array assignments).

Single Debugger

Each PeopleSoft session you run on a machine can have its own debugging session. However, only one instance of the PeopleCode debugger can occur per session. If more than one instance of Application Designer is running for a session, only one may be the active debugger at a given time.

From within a running instance of Application Designer, any component in the same session is also placed into debug mode.

After the session is in debug mode, any component that is started and that belongs to that session automatically goes into debug mode.

Similarly, Application Engine PeopleCode and component interface PeopleCode can be debugged.

After you exit debug mode by selecting Debug, Exit Debug Mode or by exiting Application Designer, all components in that session go out of debug mode. If you exit a component, debugging continues with any remaining open and running components.

If more than one Application Designer session is running, the Application Designer session that is used as a debugger is the first one to be started.

In debug mode, a PeopleCode Editor window opens for every item (for example, record, component, or page) that has PeopleCode in it when that PeopleCode is executed. If a component has more than one event with a PeopleCode program, then only one window opens per item. For example, if you have a record that has PeopleCode in both the SearchSave and RowInit events, only one PeopleCode Editor window opens: first it contains the SearchSave PeopleCode program, and then the RowInit program. If you have PeopleCode in the RowInit event for two different records that are part of the same component, two PeopleCode Editor windows open, one for each RowInit PeopleCode program.

Variables Panes

The four types of variables panes are:

- Local
- Global
- Component
- Parameter

The Local, Global, and Component variable panes show local, global, and component variables, respectively. The Parameter variable pane shows the value of parameters passed in function declarations.

From the variables pane, you can check the value of the variables you have in the program. These values are updated as the code runs. The following example shows the variables pane:

Local Name	Local Value
+ &RS0	Rowset
+ &RS1	Rowset
+ &RS2	Rowset
+ &RS1H	Rowset
&MYFIELD	000003
&I	2
&FOUND	000015
©FRMROW	<no value>
©TROW	<no value>

Local Variables pane

In addition, you can expand any of the objects to see its properties by clicking the plus sign next to the variable name. In the following example, a level one rowset is expanded. You can see the properties, such as ActiveRowCount and DBRecordName, that are part of the rowset.

Local Variables	
Local Name	Local Value
⊕ &RS0	Rowset
⊖ &RS1	Rowset
└─ RowCount	1
└─ ActiveRowCount	1
└─ DeleteEnabled	True
└─ InsertEnabled	True
└─ Level	1
└─ EffDt	
└─ EffSeq	0.00
⊕ ParentRowset	
⊕ ParentRow	
└─ Name	EMPL_CHECKLIST
└─ DBRecordName	EMPL_CHECKLIST
└─ IsEditError	False
└─ TopRowNumber	1
⊕ GetRow(...)	
⊕ &RS2	Rowset
⊕ &RS1H	Rowset
&MYFIELD	<no value>
&I	<no value>

Local Variables pane with rowset object expanded

In addition, some objects contain other objects: a rowset contains rows, rows contain records or child rowsets, and records contain fields. You can expand these secondary objects to see their properties. In the following example, the first row of a rowset is expanded, as is the EMPL_CHECKLIST record:

Local Variables	
Local Name	Local Value
<input checked="" type="checkbox"/> &RS1	Rowset
RowCount	1
ActiveRowCount	1
DeleteEnabled	True
InsertEnabled	True
Level	1
EffDt	
EffSeq	0.00
<input checked="" type="checkbox"/> ParentRowset	
<input checked="" type="checkbox"/> ParentRow	
Name	EMPL_CHECKLIST
DBRecordName	EMPL_CHECKLIST
IsEditError	False
TopRowNumber	1
<input checked="" type="checkbox"/> GetRow(...)	
<input checked="" type="checkbox"/> (1)	
RecordCount	4
ChildCount	1
RowNumber	1
Visible	True
Selected	False
IsChanged	True
IsDeleted	False
IsNew	True
<input checked="" type="checkbox"/> ParentRowset	
IsEditError	False
Style	
<input checked="" type="checkbox"/> GetRecord(...)	
<input checked="" type="checkbox"/> EMPL_CHECKLIST	
IsDeleted	False
IsChanged	True
Name	EMPL_CHECKLIST
FieldCount	5

Variable pane with rowset, row, and record expanded (shown with condensed font)

Field Values

When you view a field object in the debugger, the value of the field is listed in the Value column. Therefore, you do not have to navigate to the Value property to see the value of a field.

The following example shows the PERSONAL_DATA record and the values of the fields:

Local Variables	
Local Name	
<input type="checkbox"/> PERSONAL_DATA	
<input type="checkbox"/> IsDeleted	False
<input type="checkbox"/> IsChanged	True
<input type="checkbox"/> Name	PERSONAL_DATA
<input type="checkbox"/> FieldCount	83
<input checked="" type="checkbox"/> ParentRow	
<input type="checkbox"/> RelLangRecName	
<input type="checkbox"/> IsEditError	False
<input type="checkbox"/> GetField(...)	
<input checked="" type="checkbox"/> EMPLID	8001
<input checked="" type="checkbox"/> NAME	Schumacher,Simom
<input checked="" type="checkbox"/> NAME_PREFIX	Mr
<input checked="" type="checkbox"/> NAME_SUFFIX	
<input checked="" type="checkbox"/> LAST_NAME_SRCH	SCHUMACHER
<input checked="" type="checkbox"/> FIRST_NAME_SRCH	SIMOM
<input checked="" type="checkbox"/> ADDRESS1	461 Haven Ct
<input checked="" type="checkbox"/> ADDRESS2	
<input checked="" type="checkbox"/> ADDRESS3	
<input checked="" type="checkbox"/> ADDRESS4	
<input checked="" type="checkbox"/> CITY	Moraga

PERSONAL_DATA record field values

In addition, the only fields that appear in the debugger are the fields that are actually in the Component Buffer. For example, suppose you have a derived work record, but you do not access all the fields in the work record. Only the fields that you access and that are in the Component Buffer actually appear in the debugger.

See Also

[Chapter 4, "Referencing Data in the Component Buffer," Record Fields and the Component Buffer, page 50](#)

Call Stack Pane

The Call Stack pane appears by default when the PeopleCode debugger is started. To reopen it, select Debug, View Call Stack Window.

The Call Stack pane displays a stack of PeopleCode functions and methods that are currently active but not completed. You can use the Call Stack pane to observe the flow of an application as it executes a series of nested functions. When a function is called, it is pushed onto the top of the stack. When the function returns, it is popped off the stack.

The Call Stack pane displays the currently executing function at the top of the stack and older function calls below that, in reverse calling order. You can navigate to the source code of a function from the call stack window. The variables panes update to reflect values for the selected function.

The Call Stack pane is updated and usable when execution is stopped at a breakpoint.


Call Stack Indicators

The Call Stack displays a current line indicator and a selected function indicator in the gutter.

The current line indicator is a green arrow that shows where in the call stack the execution stopped. The current line indicator always appears in the call stack pane.

The selected function indicator is a yellow triangle that marks the current function being displayed by the Edit and Variables windows. The selected function indicator does not appear when the current function is at the execution point.

You can hover over a function name to see the full program path in a pop-up window, as shown in the following example.



Call Stack pane example showing execution pointer, selected function indicator, and hover pop-up

The Call Stack pane is updated, when necessary, with each change of the debug state.


Go To Source Code

Right-click on a function to access a context menu with these options:

Options	Description
Copy	Copies the text of the selection in the call stack to the clipboard.
Select All	Selects all rows in the call stack. You can also use standard shift-click and CTRL-click actions to select multiple rows.
Go To Source Code	Displays the selected function in the Edit window. In addition, the active variables windows will be updated in sync with the Call Stack and Edit windows. Double-click a function name to go to the source code.

When the displayed source code is at the execution point, the execution pointer icon (green arrow) appears in the source window.

When the displayed source code is not at the execution point, the selected function icon (yellow triangle) appears in the source window.



Source code pane and call stack pane showing the yellow triangle execution pointer

Viewing source code for functions that are not at the top of the stack does not change the point of execution. Nor does it disable the ability to continue execution. For example, in the previous example, selecting Go would cause the program execution to continue at "FUNCLIB_PORTAL.PORTAL_GEN_FUNC.FieldFormula PortalOpen" and not at the function in the source code window.


During debugging it is easier to go back to the previous code event from the call stack window as compared to trying to keep track of where the control was transferred and then finding the right opened PeopleCode window in Application Designer. This can be useful when trying to understand the component design and PeopleCode flow.

Setting Values for Variables and Properties

Setting the value of a variable or property in the debugger gives you the flexibility to try out changes and see the results in real time or to recover from a logic error and continue.

You can change the value of variables or properties in the Local Variables, Component Variables, Function Parameters, and Component Buffers panes. Only variables or properties with conventional data types (Any, Boolean, Date, DateTime, Float, Integer, Number, String, Time) can be changed. You cannot assign a new object to an object variable. Values that are not editable appear on a gray background.

While the debugger is running and halted at a breakpoint, select a field in the value column, such as the Local Value column in the example, and revise the value.



Local Variables pane showing a drop-down list to set the value for a Boolean variable

The debugger performs data type checking to prevent entry of incorrect data type values. For example, character strings are not allowed for integer data types, and so on. However, data integrity is not verified, so be aware that changing variable values at runtime can corrupt program execution as well as program data. For example, setting an integer value higher than what is permitted in the function could cause a crash when execution continues. It is the developer's responsibility to enter an appropriate value.

Modifying a variable in a debugger pane changes the value in memory only. The change does not trigger any PeopleCode events and does not cause any PeopleCode flags to be set.

General Debugging Tips

The following are general tips for debugging your application:

- If you are having problems determining if the correct data is being loaded into the component buffers, use the View Component Buffers view window to see all the values currently in the component buffer.

This is equivalent to putting a GetLevel0 function at the start of a program.

Use the &LEVEL0 variable to navigate through all the levels of the rowset object, see the row, records, fields, and so on. This shows you everything that has been loaded into the component buffers for that component.

- While at a breakpoint, if you lose track of the window, or the location within the window, that is displaying the green execution location arrow, you can use the Execution Location Properties menu item's ViewCode button to find your current execution location again.
- Objects remain expanded in the variable windows as you move through PeopleCode.

This enables quick inspection of the state of an object as you step through the PeopleCode. However, there is a performance cost for using this feature. If you are finished examining an object, you may want to collapse it to improve the response speed.


- If a database transaction has been started (either for you by PeopleTools, or by you in PeopleCode) other users of that database are blocked from accessing that database until the transaction is complete.

If you are stepping through PeopleCode while this transaction is open, you could potentially block other users for an extended period of time. You may want to use a private database for debugging to avoid blocking other users.

- Using the debugger is resource intensive and will impact overall system performance. Oracle recommends that you do not run debugger on your production system unless the issue you are trying to debug cannot be replicated in any other environment. If that is the case, debug when there is the least activity on the system. As an alternative you can try PeopleCode tracing.
- To create a file that contains all the PeopleCode for a project (or database), use the Find In feature and search for ;.

Be sure to select *Save PeopleCode to File*.

The following example shows the Find In dialog box:




Find In dialog box

DoModal Considerations

If you set the PeopleCode debugger to break at start and you are using the DoModal PeopleCode function, the DoModal window may appear behind the PeopleCode debugger window. The debugger may appear to have stopped, but it has not. Be sure to check that other windows have not opened while you are debugging the code.

Using PeopleCode Debugger Options

While the debugger is running, you can use the Debug menu to select other options:




PeopleCode debugger options

- Exit Debug Mode

Exits debug mode. When you exit debug mode, all breakpoints are automatically saved. If you close Application Designer, you automatically exit debug mode.
- Abort Running Program


Stops the PeopleCode program that is currently running.
- Execution Location Properties

Displays the location of the running code in a dialog box. This display includes the record name, field name, event name, and line number of the code. It also indicates if the code is executing on the client or server. You can view the exact code by clicking View Code.



Execution Location Properties dialog box

- Break at Start** Pauses execution of the component on the first line of every PeopleCode program that executes in the component. If you start a component with Break at Start selected and then you start a second component, the PeopleCode associated with the second component is stopped at the first line of the first PeopleCode program as well, as part of the same debugging session.
- Toggle Break at Cursor** Removes the breakpoint if the line the cursor is currently on has a breakpoint. Adds a breakpoint if the line the cursor is currently on does not have a breakpoint.
- Edit Breakpoints** Opens a dialog box that displays the lines that have breakpoints. From this dialog box, you can display the code that contains the breakpoint by clicking View Code. You can also remove one or all breakpoints.




Breakpoints dialog box

Go	Continues processing until the next breakpoint. If Break At Start is enabled, processing pauses at the next PeopleCode program.
Step	Executes the current line of the PeopleCode program, stepping into functions.
Step Over	Steps through each line of the PeopleCode program, one line at a time, but steps over the functions; the functions are executed, but not stepped into.
Run to Return	Processes past the return of the current function, and then pauses.
Step Instruction	Processes low-level, pseudo-machine code instructions internal to PeopleCode. This option is used in conjunction with Log Options.
View Call Stack Window	Opens a separate window for viewing the call stack. The Call Stack window displays a stack of PeopleCode functions and methods that are currently active but not completed. You can use the Call Stack window to observe the flow of an application as it executes a series of nested functions.
View Global Variables	Opens a separate window for watching global variables.
View Component Variables	Opens a separate window for watching component variables.
View Local Variables	Opens a separate window for watching local variables.
View Function Parameters	Opens a separate window for watching user-specified parameters in function calls.
View Component Buffers	Opens a separate window for viewing the current component buffers. This is equivalent to getting a level zero rowset for the component.

Note. The previous five windows update continuously as the program executes.

Options Enables you to select between opening a dialog box for general options or for specifying log options.



General Options dialog box

The General Options dialog box enables you to specify conditions of the view windows. The default is for both of these options to be selected.

- Enable Auto Scroll** If you select this check box and you click a plus symbol next to a variable name in a view window, the variable you clicked scrolls to the top of the window.
- Enable Condensed Font** Select to display all view windows with a smaller font.

Additional Features

- Break at Termination** After you are in debug mode, generally, any PeopleCode program in the session that terminates abnormally first breaks in the debugger. In addition, the error message appears in the PeopleCode log in the bottom window of Application Designer.

See Also

Chapter 15, "Debugging Your Application," Setting PeopleCode Debugger Log Options, page 282

Setting Up the Debugging Environment

You can use the PeopleCode debugger for two-tier and three-tier debugging. The database and application can reside on remote servers; they do not need to reside on the local machine.

Two-tier debugging works out of the box. Setting up three-tier debugging requires you to make a few modifications in PSADMIN (PSAPPSRV.CFG) to enable debugging.


You can connect to a Microsoft Windows NT server domain that is not on your local machine. You do not have to configure a local domain to do this. You also do not have to have PeopleTools software installed locally for three-tier debugging.

See Also

Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration, "Tracing, Logging, and Debugging," Setting Up the PeopleCode Debugger

Compiling All PeopleCode Programs at Once

In addition to checking individual programs, you can compile all PeopleCode programs either in a database or in a project to check for errors. This option opens and compiles every PeopleCode program. This process can be run on an as-needed basis to check for corruption in your programs. Run this option after an upgrade to verify that all the programs were upgraded correctly. You run this option from the Tools menu:



Tools menu - Compile All PeopleCode option

To compile all PeopleCode programs:

1. Open Application Designer while accessing the database that contains the PeopleCode that you want to check.
2. Select the compile option to use.

Select Tools, Compile All PeopleCode or Tools, Compile Project PeopleCode.


3. Click Compile in the Compile All PeopleCode dialog box.

Errors appear in the PeopleCode log display window.

Note. If you specified a log file in the debugger log options, then all errors are written to the log file as well.


Setting PeopleCode Debugger Log Options

Use the PeopleCode debugger to view PeopleCode that is executed while you step through your application. Select Debug, Log Options to access the PeopleCode Log Options dialog box.



PeopleCode Log Options dialog box

All log information appears in the PeopleCode log window, at the bottom of Application Designer.



PeopleCode log window

You can record what you see in a log file. Also, you can tailor the log results to record a variety of online information.

If you exit debug mode but do not close Application Designer, all the log options that you specified are still there when you start debug mode again.

When you close the Application Designer, all log options are clear. The next time you enter debugging mode, you must reselect debug log options.

See [Chapter 15, "Debugging Your Application," Interpreting the PeopleCode Debugger Log File, page 285.](#)

All the options available in the Log Options dialog box are also available in PeopleSoft Configuration Manager, on the Trace tab, in the PeopleCode Trace section.

Execution Trace Options

Execution trace is set to trace each PeopleCode statement. You can also trace the start of each program or each program instruction.

Data Trace Options

This table describes the data trace options:

<i>Option</i>	<i>Description</i>
Assignments	Records each assignment made to a field.
Fetches	Records the field values retrieved from a PeopleCode fetch.
Stack	Indicates the contents of the internal machine stack. Typically, only PeopleSoft staff developing PeopleCode language enhancements use this option.

Call Trace Options

The call trace options, described in the following table, enable you to record the values of external calls, internal calls, returns, and function parameters.

<i>Option</i>	<i>Description</i>
External calls	Traces each call to external (PeopleCode) functions.
Internal calls	Records each call to internal subroutines.
Returns	Logs the occurrence of program returns.
Function parameters	Logs the value of individual PeopleCode function parameters.

Log To File

When you select this option, you must specify the name of a file, or you receive an error and logging to file is disabled.

If you do not specify a directory location, the file is placed in the same directory from which you are running PeopleTools.

See Also

Enterprise PeopleTools 8.50 PeopleBook: PeopleCode Language Reference, "PeopleCode Built-in Functions," Quote

Enterprise PeopleTools 8.50 PeopleBook: System and Server Administration, "Setting Application Server Domain Parameters," PSTOOLS Options

- using syntax 181
 - using the Warning statement 138
 - validating PeopleCode syntax 239
- web servers
 - transferring files 205
 - viewing file attachments 208
- While statement 15
- Windows
 - calling DLL functions on application servers 150
 - debugging file attachments 207
 - MessageBox dialog boxes 157
 - using non-DNS URLs for file attachments 212
 - using OLE functions 169
 - using PeopleCode Debugger 265
 - using the NT 4 FTP server 211
 - using the WinExec function 170
- WinExec function 170
- WinMessage function 157
- Workflow event
 - save processing 125
 - using 142
 - using the SavePostChange event 139
- work records
 - FILE_ATTACH_WRK 212
 - understanding 164

X

- XmlNode objects
 - scope restrictions 9