# ORACLE AGILE ENGINEERING DATA MANAGEMENT - BUG FIXES FOR AGILE E6.1

November 13, 2008

Part No. E13931-01

| FIS-ID | BugDB-ID | Module | Description |
|---|---|---|---|
| 6040 | - | DTV | Typographical error on warning message: Menu selections in English. |
| 6635 | - | GTM | The folder "Summary classification attributes" (selection EDB-GTM-FLD-ATT-AGG in the resp. button-noselect-menu) is missing in the document, item and project forms. This should be adapted (look also FIS-ID 6628 and 6636). |
| 6724 | - | LGV | The LogiView constant B_SLASH is defined as B_SHLASH |
| 7164 | - | ECI | "eci_sel_typ" is called, the user selects MORE THAN one record and calls the menu function "Selection to CAD".<br><br>Afterwards, the message "No connection active" appears fairly often (selected records -1) on the DTV-client-side. |
| 7437 | - | LGV | The following LGV-variables exist twice or three times in the axalant2000SP2-reference dump: ARP_PROJ_ID, RP_PROJ_NAME, ARP_PROJ_REV, ARP_PROJ_VER, EPL_OBJ_ENT, EPL_WRK_CID, EP_ASS_FLD_NAME, EP_ASS_FLD_TITLE, EP_CHECKOUT_DIR, GDM_DOC_NAM, GDM_DOC_TLI, GDM_ |
| 8283 | - | OTH | The description of the configuration parameters EDB-GTM-INHERIT-ATT and EDB-GTM-LOCAL-FIRST is missing in the dump. The configuration parameter EDB-GTM-TIT is not contained in the standard dump. Besides that the parameters are not in the Online help. |
| 8729 | - | ECI | In the function "Selection to CAD" the LGV-procedure P_DFM/DFM_SELCTION_CAD is called through the submenu EDB-ECX-SEL-SLS with lgv_sel_run.<br><br>Therefore, the LogiView procedure is called for each record which causes the message "Widget invalid in lgv_sel_run", if more than one record was selected. |
| 9025 | - | JET | If a radio button menu is created in a way that the radio buttons (the selections of that menu) are placed side by side, it is displayed correctly in the DTV-client. In the java client (resp. web client), however, the radio buttons are always placed one below the other. |
| 9712 | - | GTM | In a classification list an attribute is inserted which has a drop down menu at its attribute field (the attribute has values assigned). The field cannot be corrected manually by writing a value into the field (without using the menu) directly but a value has to be selected from the menu. |
| 10020 | 7106522 | DTV | If file_choose is called with the parameter /FILE=*.* more than one file can be chosen. If you select many files it can happen that the |

| FIS-ID | BugDB-ID | Module | Description |
|---|---|---|---|
| | | | server crashes. It seems to have to do with the length of the file names. The limit seems to be a length of 512 which must not be exceeded. |
| 10027 | 7106529 | WEB | It should be possible to call the TCL function FormToList from the Web- and the Java Client and the mask should be displayed then. For that purpose it is necessary that this call is acknowledged by both clients and the mask is mapped which is opened by this call.<br><br>Also see FIS-ID 10833. |
| 10030 | | MOA | Setting the inheritance flag to "n" in an existing project structure does not work. The entire record is deleted. |
| 10067 | | OTH | Wrong definition of fields in database: The value from T_FIELD.C_NAME (varchar2(50)) is stored in T_QRY_CND.TABLE_FIELD, which is defined only as varchar2(40) when storing a search query. |
| 10221 | 7106575 | OTH | Project form, subfolder "Navigator": Select a project and set it into update mode. Now click on one of the navigator symbols (for ex. document or item). A select widget for creating a relation from the current project to the selected document / item opens. Chose a document / item and confirm the selection with the right mouse key. The selection widget disappears and the number of the document / item appears in the appropriate field (column "identification").<br><br>After storing the project and refreshing the mask the just inserted relation is gone again (it was not created at all) |
| 10304 | 7106404 | GTM | The fields T_GRP_PRC.STRING_VAL_(lng) and T_GRP_PRC.STRING_VAL_SL are in the database with varchar2(255) and in the DTV repository with S255. Other fields, like T_GRP_ART.STRING_VAL_(lng), T_GRP_DOC.STRING_VAL_(lng) were shortened in Agile e6.0 to varchar2(80) due to a restriction on table and field widths. |
| 10313 | 7106411 | DTV | The trash basket is not displayed on a workstation with two monitors<br><br>Remark support:<br><br>The trash basket displays properly when opened on the primary monitor. However, when PLM is opened on the secondary monitor the position of the trash basket is calculated wrong, so that the widget is opened far outside of the secondary monitor. |
| 10393 | | DTV | Checking in a file with the button "save existing file in Agile e6" (office suite toolbar) opens the trash basket. It has to be closed manually |
| 10399 | 7107123 | WFL | 1. Create a process template (Record in T_PRC_DAT)<br><br>2. Open Project form<br><br>3. Create a new project<br><br>4. Switch to tab 'Processes'<br><br>5. Just created process template is visible<br><br>Problem: Constraint field T_PRC_DAT.EDB_PRO_REF is missing in list |

| FIS-ID | BugDB-ID | Module | Description |
|---|---|---|---|
| | | | EDB-PRC-ALL-SLI-C |
| 10401 | | OFS | In the Office Suite toolbar the second button is pressed (Check in existing file to Agile e6) a second time. Now following error appears if no other mask is already open: After the actual check in of the file, usually the Office mask is opened and the currently created document is displayed. However, this does not happen here. Only if the user presses the return key the mask is opened. |
| 10414 | 7104480 | LGV | Problem: Lists/forms for logic model and procedures contain attributes for change & release management, namely- Version- State- Current flag. Since these attributes have no functionality, they should finally be removed. At least from the user interface. |
| 10585 | 7108710 | ECI | Function eci_sel_ret does not seem to be able to handle multi selects any more. The first part can still be loaded into the CAD system but for all further documents a message appears: "No active connection!" and they are not loaded.<br><br>Widget-save-flag was set to "on".<br><br>If directly at the fist call, two documents are selected in PLM and then "Selection to CAD" is chosen for the second document, the message "No active connection!" comes up although both C_IDs were sent to the ECI-client (eci_test).<br><br>A single call of eci_sel_ret returns -1 |
| 10601 | 7108723 | NSV | Dump error: The description in the field T_NUM_GEN.NSV_MEMO_GER/ENG/FRA is wrong for the following number variants<br><br>EDB-RDL   intern firm-number(EDB-ORGANIZATION)<br><br>EDB-EXP   intern person number (EDB-PERSON)<br><br>PRP-ID   range of numbers for maps<br><br>PRP-USER   range of numbers<br><br>EDB-ITM-STR-EDBID Number cycle for creating clear EBD_Ids |
| 10604 | 7108726 | BRW | Dump error: TOP-Menu: System ->Structure Browser -> Configuration Elements The description in the German field "TYP" (T_OBJ_TYP_DAT.EDB_OBJ_TYP_GER) is wrong for document types (keys) - for all types the value is 'Stored Document' |
| 10605 | 7108727 | BRW | Dump error: Write error in mask name "T_MASK.TITLE_GER for structure browser "EDB-PRP-OBJ-TYP-SLI": Konfigurationselementen instead of Konfigurationselemente. |
| 10607 | 7108729 | QRY | An entry in "QUERY_xx" is producedwhen storing a search request in the field T_EXP_DAT.edb_DESCRIPTION. This entry should be called "STORED-QUERY xx". Error in LGV line 520 PrpExplorer/AddExpObj(PRP_STR_2,"U",user(),EDB_FAV_NAME,strprint("QUERY %d" ... |
| 10716 | 7108151 | DTV | When opening an empty combined mask (for example the item navigator) and change to a sub list e.g. to the folder "Documents" it is possible to insert a document via drag and drop into this relation list although no item is active in the main part of the mask. |

3

| FIS-ID | BugDB-ID | Module | Description |
|---|---|---|---|
| 10804 | 7107303 | OTH | In some EDB masks the keyword LIST resp. LIST_A is missing or LIST is used instead of LIST_A and vice versa. Following masks are affected: LIST_A instead of LIST in the pre-mask-USX: EDB-CPS-MDL-FLT-C and EDB-CPS-NTR-FLT-C. No LIST_A (or LIST instead) in the edit-action-USX: EDB-CHG-AFC-PRD-CNS, EDB-CHG-AFC-PRD-VLI, <br><br>EDB-CHG-OPR-LUT-VLI, EDB-CPS-CMP-FNC-MSLI, EDB-CPS-CMP-FNC-SLI, EDB-CPS-CMP-MV-SLI, <br><br>EDB-CPS-CMP-NV-SLI, EDB-CPS-CMP-SLI and EDB-EWO-AFC-PRD-VLI. <br><br>LIST in the pre-action-USX: EDB-TXT-CATEGORY-SFR <br><br>No LIST_A in the post-action-USX: EDB-RMT-RQ-ART-RLI-C |
| 10904 | 7107834 | LGV | LVF masks do not support long text fields properly: Is there a field which contains more than 255 characters or a Carriage Return with the function F8 when an empty long text editor opens. The text is not loaded into the editor. It does not work to read o |
| 10934 | 7108181 | BAS | With the internal editor, if you have only one new line character and you were to delete it, all of the text beyond the 253rd character is lost immediately. |
| 10965 | 7108397 | OTH | The list EDB-CHK-TRA-RLI is used as a sub list in form EDB-CHK-CFR. So the length and width is both set to zero. BUT: this list is also used in selection EDB-CRM-CHS. So this selection opens a list with zero values for width and length. Please copy list EDB-CHK-TRA-RLI to EDB-CHK-TRA-RLI-C and use the copy in the folder of EDB-CHK-CFR as it is made for many other lists. |
| 10966 | - | OTH | The following defaults ( T_DEFAULT) are removed from the online help: <br><br>EDB-WFL-MAL-CRE-CTRL <br><br>EDB-WFL-MAL-BEG-TIME |
| 9899 | - | FMS | It is not possible to check in a file with about 4 Gigabytes of size with the fileserver. Following error message appears: <br><br>File "t3000.zip" could not be copied! <br><br>Server-Message: FMS Client: Sio error -6 during FMS-ERR-SIO-SEND-SOC |
| 10972 | 7108402 | NSV | If the number server exceeds the maximum value of a number cycle, the source sets a database lock when the next number should be taken but does not unlock it anymore. The number server keeps locked until the end of that session. |
| 10991 | 7108484 | ROL | If in the list of roles a role is selected and the user chooses "form" from the menu, the role form is opened but the general tab remains empty. |
| 11024 | 7108701 | DTV | The userexit prt_mod_grp works only correctly as long as the assignment of groups per user does not exceed 300. <br><br>If a user has more than 300 groups assigned, the call of prt_mod_grp() creates a selection menu with only exactly 300 assigned groups. The rest is missing. If the group should be changed |

| FIS-ID | BugDB-ID | Module | Description |
|--------|----------|--------|-------------|
|  |  |  | to a group that comes after 300 (according to the sorting of the group assignment mask) with the command prt_mod_grp("Group301") the command returns 0 although the change of the group was not executed. |
| 11050 | 7107229 | DTV | Re-opened problem as described in FIS#6308 in Agile e6.0.2 standard dump. The default R-MAX value for EDB-LGV-DT-CFR is 100 again. This should be changed along with a number of other R-Max values, for example, EDB-LGV-LM-VAR which only allows 100 variables. If you want to export a LM that has more than 100 variables, the additional variables will get truncated. |
| 11058 | 7107235 | OTH | If the text of a field has more than one '&' character, the text is not copied correctly in Excel using drag&drop. It doesn't matter from which mask it is dragged. The first & comes over correctly, the second is doubled, the third tripled and so on |
| 11068 | 7107243 | CDD | After opening the plot order form it is not possible to save and execute the plot job. Only closing the form is possible. |
| 11116 |  | DTV | Wrong behavior of trash basket: open e.g. the 3D model mask in maximized mode, save a Word document to the watched folder Office Suite, the Office Suite mask opens, after save and close of this mask the trash basket is in the foreground. |
| 11126 | 7107849 | ECI | If the function eci_sel_typ is called with the 'widget remains' flag set to "ON" then in PLM the mask that was called with eci_sel_typ remains open, even if the user returns to CAD. That's way this mask can be accessed again via ECI afterwards. Until now, however, when the mask was called again with eci_sel_typ, it popped automatically into the foreground if it was covered by other PLM-masks in the meantime. In Agile e6.0.2, however, the mask remains in the background and the user has to search for it first before the user is able to continue working. |
| 11141 | 7107861 | DTV | The Agile PLM trash basket window is moved to the right edge and then the entire PLM window is moved to the left so that it protrudes the left screen edge by several centimeters. Now, the trash window is opened but it is positioned in the invisible area of the PLM window. Unfortunately, user cannot access the trash basket any longer - not even when moving the PLM Window back to the right so it is visible again. In this case it is not possible to rollback records from the trash. |
| 11169 |  | OTH | The userexit documentation for xedb_get_rec is outdated (comes from CADIM). (A selection widget comes up if more than one record with the mentioned ID was found) this has to be documented correctly to clarify that this userexit should not be used with (relation) masks that are called in batch mode for insert. |
| 11235 |  | QRY | When doing a query in a form in a numeric field with more than one criteria (e.g. LEV_IND <330 & !220), saving this query as a saved search (T_QRY_CND), then only a part of the criteria is stored (<330). The part string with '!' (e.g. !220) is missing in the query clause. |
| 11242 |  | QRY | If a query is done with the enhanced query form (to be able to save |

| FIS-ID | BugDB-ID | Module | Description |
|--------|----------|--------|-------------|
| | | | it as a stored query) only 50 characters can be put into each string field for the query. These are very often too few. Here, the default QUERYSIZE should be evaluated for the size of the fields in that mask. |
| 11246 | | CHG | Code rule in form cannot be longer than 255 chars. |
| 11251 | 7107482 | DTV | In the windows menu (below the TOP menu) there are errors: The content of a mask is not always displayed correctly (as the current record is displayed there additionally). After copying or scrolling inside a mask, the display is not refreshed. It seems the refresh takes place only if a new mask (a new window) is opened but not if the current record inside a mask changes or if a mask is closed. |
| 11258 | | WEB | Create an empty selection list with LogiView with select_ent ("entity") var (variable) RES=execute (1,"choose /MAX_REC=100 /NO_QUERY"). In the Windows client an empty selection list opens (parameter /NO_QUERY) which is correct, while in the Web client the list is always populated (filled) which takes sometimes a very long time (depending on the amount of records found). The error is also in the Java client: the list is filled. |
| 11272 | | BOM | Symptom: When calling the multi level structure of an item (userexit xedb_hierarcy_ver), the "parent item" is locked for a short time. Why? The user is only able to read …<br><br>Problem-1: The article with user A is in update mode (locked) user b cannot make multi-level structure definition - the list is empty!!!<br><br>Problem-2: If user A and user B call simultaneously a multi-level structure, only one user gets the correct entries. |
| 11291 | | WEB | Symptom: Open a mask via a hyperlink in the web client and search in this mask (after deleting the search string) no search result is returned, this works fine in the windows client. |
| 11308 | 7107917 | WEB | As soon as there is more than one web client window open (because of link calls out of office applications) only the last opened web client window can be used. All other web client windows show only an hourglass then. |
| 11309 | 7107918 | WEB | If the web client is called through a link (URL) which contains the REVISION parameter, the version view is always changed according to the value of that parameter:<br><br>REVISION=LATEST -> Version view = Development;<br>REVISION=RELEASED -> Version view = Production, Date =<br><br>@NOW; Otherwise, the version view is ALWAYS set to GLOBAL.<br><br>It must be possible, too, that the version view does not change if the calling URL contains the REVISION parameter. |
| 11321 | | DTV | If the client is started with a long user name (> 85 characters) the daemon crashes on Sun Solaris and on Windows servers. A message appears: 'daemon on host <Hostname> with rpc number <Daemon number> is not answering requests!', but the color bar does not start anymore. |

| FIS-ID | BugDB-ID | Module | Description |
|--------|----------|--------|-------------|
| 11371 | | ECI | Java Client: If the CAX interface uses ECI functions eci_rea_cax_str and eci_rea_cax_fil several times, these functions do not work reliably. With the DTV-Client they work. |
| 11382 | | BRW | If a user with German language set wants to rename a favorite folder in the internal browser a mask with a wrong (English) request appears: "Please define a new name for this Sub Project". |
| 11395 | | MOA | For revisioning of items and documents a LogiView procedure calls xcpy_str as follows: xcpy_str("all /VER /BATCH"). Sometimes, it happens that when creating a revision, the C_ID in T_MASTER_DAT already exists. xcpy_str stops with error 17 (ERR_XCPY_ABORT). In the message window following message is displayed: Element with identical index already exists ! (Trash empty ?) |
| 11401 | | FMS | The current timestamps in file server log are not detailed enough. Milliseconds are missing and times between two actions are missing. |
| 11410 | | QRY | In the enhanced query form, queries which are combined with & or \| (Example: A11931 \| A12123 \| A12124 \| A12125) are not executed correctly. |
| 11460 | | CRM | Symptom: When Viewing a document from a remote site via online replication, the following error message appears: Error in 'xstr_nxt_sta' (NoSuchMaskException: NoSuchMaskException) |
| 11461 | | MOA | Symptom: MultiOrgAccessRights activated (EDB-ROL-ACTIVE=4) tolerance correction does not work for organizations (still checks projects). |
| 11467 | | DFM | Symptom: When executing replication orders in batch the following error message appears: xfile_dis_OrderFileReplication: record FMS-0000000000001011 is actual on site nj Record "10-FMS-0000000000001011" is currently locked by user "DEMOEP_M" ! Error in 'xstr_nxt_sta' (NoSuchMaskException: NoSuchMaskException) |
| 11503 | | MOA | Symptom: The function "Copy with structure or Create a new version" does not work if "Multi Org Access Rights" is activated and the refine and/or aggregate relations should be copied. Error message: Position number must be unique! Element is already assigned to structure with identical values for Revision and PNo. Copy procedure has been aborted by trigger 'EP_CPY/EDB_DOCUMENT_NumAgg'. |
| 11504 | | MOA | Symptom: The function "Organisation=>Change type of document" does not work if "Multi Org Access Rights" is active. |
| 11508 | | GTM | Performance loss, when storing records in the classification list of a certain class. |
| 11510 | | DTV | C_IDs were only generated in a range of 1,000,000,000 to 1,000,032,767. |
| 11515 | | OFS | Symptom: Office-Suite: Send mail function sends the original file (e.g. doc) instead of the archive file (pdf). |
| 11537 | | EPQ | Symptom: After loading the file dtv_cdd.dat and PLM restart, it is |

| FIS-ID | BugDB-ID | Module | Description |
|--------|----------|--------|-------------|
| | | | not possible to create the views CDD_V_USRPLT and CDD_V_GRPPLT. |
| | | | Error message: Error code = 4506 – Connection Impl::errorHandler Code = 0x80040e14 Code meaning = IDispatch error #3092 Providercode = 4506 Source = Microsoft SQL Native Client Description = Column names in each view or function must be unique. Column name 'C_ID' in view or function 'CDD_V_USRPLT' is specified more than once. |
| 11543 | | MOA | Wrong error message in MOA: Multiorganizational Access Rights are activated. |
| | | | 1.) User1 creates an item record. |
| | | | 2.) User2 assigns this record to an organization. |
| | | | 3.) User1 tries to delete that item again but gets the (correct) message: "Record is explicitly assigned to an organization. Delete assignment first!" |
| | | | 4.) User1 tries to delete the assignment of item and organization, but gets the (wrong) message:"There are no explicit assigned organizations for this record." |
| | | | Correct would be a message that states that the assignment can only be deleted by User2. |
| 11585 | | CAX | Fast loading a Pro/E drawing from PLM does not function if a 3D-model of the drawing (directly or indirectly associated to the drawing) is controlled by a Pro/E-layout or a Pro/E-layout-structure ("multilevel layouts")! The layout(s) will not be retrieved from PLM. |
| 11612 | | DMS | The list EDB-DOC-RES-SLI shows reserved documents with all their files. The title of this list is confusing, since the list actually shows all files for a document, no matter which file had been checked out. |
| 7924 | - | DTV | cch_nop_del does not work with external tables. |
| 9668 | 7105923 | DTV | In a combined form the upper part has the focus (but is not in edit mode!). Now the user has still the possibility to execute a query in the sublist from, the sublist's noselect menu. By doing so, only the sublist changes into query mode. But the button area of the sublist stays inactive (buttons are grayed out) and has to be activated by a separate mouse click in the sublist.For a lot of users, this behavior is a problem because they assume that the buttons of a sublist cannot be used in query mode. |
| 9712 | 7106447 | GTM | In a classification list an attribute is inserted which has a drop down menu at its attribute field (the attribute has values assigned). The field cannot be corrected by hand by writing directly a value into the field (without using the menu), but a value has to be selected from the menu. Otherwise, the following error message appears: |
| | | | "The value has been corrected (Attribute: G_5, Line: 100)" and the old value comes back into the field. Because the attribute value is a free value "T_AVL_DAT.C_CHK_TYP" = "N" it is not ok to correct the value afterwards again, because the menu is just a help for the user, it is not a must! |
| | | | The current behavior of the system could be accepted if a message appears that explains why the value has to be chosen from the |

| FIS-ID | BugDB-ID | Module | Description |
|--------|----------|--------|-------------|
| | | | menu: "Please delete the old value first by selecting the emty value from the menu. By doing so it is ensured that the references to the attribute values keep consistent."<br><br>The online documentation must be adapted additionally! |
| 09715 | 7106450 | DTV | Drag and drop from text editor to PLM does not work properly.<br><br>- Open text editor and type a search criteria (e.g. "A5E%")<br><br>- copy text with right click into clipboard<br><br>- open the item mask in PLM and insert text by "paste" function with right click<br><br>- execute search<br><br>An error is shown that indicates no search criteria are inserted, although it can be seen in the mask.<br><br>Do the same with ctrl-c / ctrl-v and it works.<br><br>The problem is the 'insert' not the 'copy' (copy with right mouse button and insert with ctrl-v, works well)". |
| 09814 | 7105383 | DTV | "When text is inserted with right mouse click - paste the existing text is overwritten instead of appended at the actual cursor position". |
| 09954 | 7105570 | BRW | "When the browser window is released from the left-most position the window is always in foreground.<br><br>Request:<br><br>It should behave like any other mask so that in case another window is activated it switches to background". |
| 10061 | 7107052 | OTH | Module: Change and Release Management<br><br>Prerequisite: Effectivity management is activated for the "BOM" respectively "in items" relation.<br><br>Description: Revision (with structure) an item and checkmark the "in items" relation to be duplicated as part of the revisioning. The old "in items" relation (assigning parent assembly to old revision of item) will not become ineffective, when the new "in items" relation (assigning parent assembly to new revision of item) is set effective.<br><br>Workaround: Old "in items" relation has to be set ineffective manually. |
| 10084 | 7105445 | OFS | "It is not possible to recheck-in an Office document with the button "Save to PLM" in the Office toolbar if the multi-wildcard was switched (for example from % to *). Always a new document is created then. In the LogiView procedures GdmExecute/Shell (lines 60, 210, 290 and 380) and GdmExecute/DocTyp (lines 70, 170 and 480) a % is hard coded as multiwildcard.<br><br>The entire GDM LogiView procedures have to be checked as there are many places in the Office Suite where the percentage sign (%) is hard coded." |
| 10224 | 7106578 | BRW | Open Manager > Structure Broser > Browser Configuration. Put mask into search mode and search e.g. for ST% in the field Group/User. Execute the search. The search result doesn't show what I was |

| FIS-ID | BugDB-ID | Module | Description |
|---|---|---|---|
| | | | searching for. |
| | | | The entry EDBCUSTO \| EDB \| GLOBAL is set automatically |
| 10458 | 7106933 | FMS | When checking in files >2 GB, the following message is displayed in the message window: |
| | | | File "hg77_05_ana_lay.tar.gz" could not be copied! |
| | | | Server message: FMS Client: Sio error -6 during FMS-ERR-SIO-SEND-SOC |
| | | | Does a timeout or a size limitation exist? |
| 10508 | 7107749 | BRW | "If you click in the favorites browser with the right mouse button on the entries "Favorites" or "Stored Queries" a menu appears that has two selections "NoSelect-Entry". But there are different functionalities behind them. In German language the menus are empty." |
| 10517 | 7107756 | FMS | "The fileserver can't handle files bigger than about 2GB, the fms_cli shows strange values for the transport, although the fms_srv terminated the checkin already! also happens with 5.0.1 |
| 10561 | 7108333 | DTV | "When editing a record with the functions "Cut" and "Paste" of the right mouse button menu an error occurs: As long as the user is in edit mode it seems that everything works fine but when storing the record the changes are canceled and the record remains unchanged. Probably the fields are not set dirty after these functions are executed. |
| | | | It is the same in query mode. |
| | | | When you work with Ctrl-X and Ctrl-V everything is ok." |
| 10676 | 7107796 | JCL | "In the Java - and Web client for all versions (PLM5PRP, Agile e5.1 and Agile e6.0.1) the error occurs that no combined mask can be opened directly with a different folder than the first (general) folder. |
| | | | So the following construction (which works correctly in the Windows client) does not work in the Java- and Webclient: |
| | | | bvb_usx_opn_ent (EDB-ARTICLE /EDB-F=EDB-ART-CFR R>EDB-ARTICLE STR EDB-ART-STR-RLI-C). It seems that the last part (R>EDB-ARTICLE STR EDB-ART-STR-RLI-C) is ignored." |
| 10695 | 7108066 | EXP | "Symptom: |
| | | | If you click MyWorkplace--> project-favorites nothing happens. |
| | | | Reproduction: |
| | | | Create new dataset "pro1" in EDB-PRO-CFR. Save this as a favorite. |
| | | | Create another dataset "pro2" in EDB-PRO-CFR. |
| | | | Add pro1 to pro2 part list |
| | | | Reason: |
| | | | There is a pre-act-usx in EDB-PRO-SLB: … bvb_uti_pre_qry (T_PRO_DAT.AGG_FLAG 0)" |

| FIS-ID | BugDB-ID | Module | Description |
|--------|----------|--------|-------------|
| 10697 | 7108068 | WFL | "Sending external mails with attachment is not possible using the server side sending via userexit exm_snd_ext (MAILER=NOTIFIER). <br><br>Message: <br><br>server side sending via notifier is initiated <br><br>java.io.FileNotFoundException: nullFTP-Server.doc <br><br>Error in JBOSS-logfile: <br><br>java.io.FileNotFoundException: nullFTP-Server.doc (System is not able to find the file) <br><br>It works if you use the parameter -x additionally or instead of -t. <br><br>Reproduction: <br><br>run RES = @exm_snd_ext('"-s'test SR249472 exm_snd_ext'-t'Text bla …'-r'eu-support@agile.com'-i'F:\Agile_e6\tmp\'-a'FTP-Server.doc'/MAILER=NOTIFIER")" |
| 10806 | 7107305 | DTV | "A document number is taken over into the clipboard (with Ctrl-C). Afterwards, in a new mask the query mode is opened and this value from the clipboard is put into the appropriate field (document number) with the context menu (right mouse key) -> Insert. <br><br>Now the value is in the mask but when executing the query on the database the value is not taken into account (can be seen directly in the SQL trace). (see also FIS-ID 10561)" |
| 10822 | 7107314 | GTM | A multilingual attribute was created in the attribute pool (German / English) and a list of attribute values was assigned while for each attribute value both languages were filled (with CTRL-L). <br><br>Now, the attribute is assigned to a class, an item is inserted into that class, and an attribute value is selected by using the drop down menu (in German). If PLM is now started with a user that has English data- and surface language the attribute stays empty -> The multilingual value was not written into the appropriate field. |
| 10913 | 7107942 | DTV | "Longtext fields should be better supported and easier to use. <br><br>Mandatory carriage returns should not be required." |
| 10976 | 7108404 | JCL | In the javaclient a LVF-mask does not open if the last field of the field sequence is an integer field and the appropriate variable is initialized in the LogiView procedure before the LVF mask is called. |
| 11061 | 7107238 | DTV | "A combined form with two form folders is opened - all fields of the folders are also available in the main form, but they are invisible. <br><br>Besides that, at least one list folder exists. <br><br>The mask is refreshed so that more records are found than the mask limit: the reload button appears. <br><br>If the user changes to the second form folder the reload button is greyed out. It is only available again if the user refreshes the mask once more. But there is no reason that the reload button is greyed out as the records are all still available in the mask. <br><br>If the user changes to a list folder for comparison the reload button disappears also (depending on the number of records and the mask |

| FIS-ID | BugDB-ID | Module | Description |
|---|---|---|---|
| | | | limit of the sublist) but reappears again if the user clicks into the main mask again (without refreshing the main mask). This additional click, however, has no effect for form folders." |
| 11089 | 7107455 | DTV | "The view mode (Ctrl-O) can be canceled in the current Windows client only by pressing the return key or the right mouse key. For a "normal" user this is very unusual, however. Therefore, it is requested that the view mode can be finished with the ESC key, too (or instead). |
| 11161 | 7108417 | JCL | The selection list in the Toolbar in the Java Client is not updated, like with the Windows Client.<br><br>Reproduction:(by the example of the SCM toolbar)<br><br>-set SCM toolbar active/visible<br><br>-open the list with the changes (button: change)<br><br>-insert 2 or 3 changes, if there are no changes present<br><br>-select a change and run the function "set number".<br><br>--> In the windows client the toolbox is refreshed, but not in the java client" |
| 11194 | 7108511 | DTV | "If records are copied by drag&drop from PLM to Excel, a maximum of 512 characters is taken over from a longtext field.<br><br>The rest is cut off. Also with Ctrl-C and Ctrl-V it is like that. The reason seems to be in DTV. |
| 11205 | 7108812 | LGV | "If a string variable that contains more than 160 characters is written in the message window with the LogiView command put (VARIABLE), a line break is inserted automatically at position 161. This leads to errors if that way a URL is put to the message window which could be usually copied by the user to the browser but is unusable this time because of the line break.<br><br>As a workaround the output can be done with TCL (RES=@TCL(strcat ("MesWri \"\" \"", VARIABLE, "\"")).<br><br>However, TCL will be desupported from Agile e6.1 on. Therefore, the output with LogiView should be working correctly until then." |
| 11323 | 7107929 | ROL | "Loading of ProE documents of type ASM with eci_sel_typ needs two times the call "selection to CAD". Otherwise, the system hangs waiting for another mouse click.<br><br>The error can be reproduced without ECI, too: Just select a record in the Pro/E-list and call "Load to CAD": The message "No active connection" does not appear. A second "Load to CAD" call and the message appears." |
| 11374 | 7108456 | DTV | If T_MAS_FLD.C_LEN_VIS >1 and the filed is no longtext-field, then the field cannot be expanded by F8.<br><br>This only works if c_len_vis =1<br><br>Impact:<br><br>Comment fields that are defined for viewing more text at once in forms cannot be expanded to view the whole text. |

| FIS-ID | BugDB-ID | Module | Description |
|---|---|---|---|
| | | | The user has to change to the list. |
| | | | Steps to reproduce: |
| | | | Define a comment field with row > 1 |
| | | | Put that field in edit or view mode and press F8 |
| | | | The field will not be expanded" |
| 11378 | 7108459 | DTV | "If a textfield is defined and filled with more than 256 characters you can move the delimiter of this field in a list form over the 255 character border. |
| | | | In e5.1 the continuation marks disappear, in e6.0.3 wrong characters are shown." |
| 11403 | 7108546 | WEB | "With the webclient it is possible to enter more characters into multiline text fields (string fields) on forms than what can be stored in the database making it possible to experience a data loss. User may not realize that all data is not saved. |
| | | | This is still reproducible with the Agile e6.0.4 Web client. |
| 11436 | 7108765 | WDT | "Symptom: |
| | | | When running into the Web Presentation Service timeout from the Web Development Toolkit (WDT), a white page is shown after relogin. |
| | | | The web application does not re-route into the right URL. |
| | | | Steps to reproduce: |
| | | | Define default.jsp using frames |
| | | | Open WDT form |
| | | | Wait for timeout |
| | | | Click hyperlink |
| | | | Re-login" |
| 11470 | 7107400 | FMS | "New fms_srv from fis 11437 does not work with webclient, |
| 11491 | 7107419 | DTV | "Expand a field in query or edit mode with F8, the edit window contains only a part of the string if the string is longer than input field. If the cursor is on pos1 the string is shown completely. If the cursor is in the middle at the end of the field, only a substring is shown. |
| | | | The edit window size matches the length of the string but you have to pres POS1 to see the whole string. |
| | | | In PLM 5.1 you cannot see this behavior. In 5.1 the whole string is shown. |
| | | | Steps to Reproduce: |
| | | | Enter a search string that is longer than the field. Place the cursor at the end of the string and press F8" |
| 11506 | 7107628 | PMS | "In widget EDB-POS-PRO-SUB field T_PRO_DAT.PROJ_ID is too short. Width is 20, has to be 40. |

| FIS-ID | BugDB-ID | Module | Description |
|--------|----------|--------|-------------|
| | | | Steps to reproduce: |
| | | | Check the mask EDB-POS-PRO-SUB." |
| 11557 | 7107964 | JCL | LogiView function 'file_choose' allows selecting a file but also a directory. For the latter the programmer passes "*.dir" as the default file name (see online help for file_choose). |
| | | | This does not work in the Java Client. |
| 11601 | 7108280 | EPQ | "In a replicated environment (post-CADIM version), the update function has changed. Customer cannot manually update a system field directly from logiview. The update function causes the epq to form an sql statement that attempts to update the same field T_USER.C_UPD_DAT twice resulting in an update failure. Customer prefers that the update function work the same whether a database is replicated or not." |
| 11608 | 7108285 | GTM | After the update of more than one record by Ctrl-r the reference values (ATT_VAL_REF) are not updated properly. |
| 11686 | 7108786 | GTM | In the attributes pool a float attribute is defined that gets an attribute value containing a formula (with reference to another float attribute; example: 10.5-{4}). |
| | | | If then the user selects that formula for an item in the classification list the server crashes with the message: |
| | | | "DataView Server not responding". The error can only be reproduced on AIX but also in Agile e6.0.4. |
| 11699 | 7108796 | CDD | "An entry to the field Scale Format on the document assignment of a plot order causes an error given. |
| | | | Step to reproduce: Enter the field Scale Format on the document assignment of a plot order." |
| 11700 | 7108797 | CDD | "On the Mask CDD-PLO-PAC-TFR-LGV the entries "Undo" und "Restore" are missing in the Update and Query-Menu. |
| | | | Steps to reproduce: Open the Update or Qery Menu in the plot order form." |
| 11701 | 7108798 | CDD | "Plotting from the document list opens the plot order form at the end even if no document is assigned. |
| | | | Steps to reproduce: Select some documents with a non plotable status. |
| | | | Create a plot order." |
| 11702 | 7108799 | CDD | "With default view list a wrong plot order list is opened and the plot order is not set to the edit mode. |
| | | | Steps to reproduce: Set default view to list |
| | | | Create a plot order" |
| 11703 | 7108800 | CDD | "After saving, the changes in field Scale Format are lost. |
| | | | Steps to reproduce: Change the value of Scale Format in the document. |

| FIS-ID | BugDB-ID | Module | Description |
|---|---|---|---|
| | | | Save." |
| - | 7244219 | ECI | When attempting to execute a LogiView procedure from an edit button menu (userexit: lgv_edt_run) twice in the Java-Client the following error occurs:. |
| | | | ERROR |
| | | | ---------------------- |
| | | | Semantic error, function "mode": |
| | | | LogiView has not been called as an action userexit (working mode is missing)! |
| | | | Error in procedure SCE_604/SR6966093_994 (row 10) !. |
| | | | The error occurs only with the Java-Client - not with the DTV-Client. |
| - | 7229762 | DOC | Name of workflow mail variables are incorrect in the online help wfl.chm. From Agile e6.0 to Agile e6.0.1 we changed the source / the variable names e.g. from "personPrefix" to "PersonPrefix" |
| | | | List of all changed variables: |
| | | | personPrefix to PersonPrefix |
| | | | personName to PersonName |
| | | | text to Text |
| | | | userName to UserName |
| | | | from to FROM. |
| | | | The name of the workflow mail variables have been corrected in the online help. |
| | 7304371 | GTM | (duplicate of BugID 7107314) |
| | | | Steps to Reproduce:<br>1. Create an attribute Color (S20, multilingual) with values:<br>Black/Schwarz/LN3, White/Weiß/LN3, Blue/Blau/LN3, Red/Rot/LN3<br>2. Create a class TEST (entity = EDB-ARTICLE) and assign the attribute Color to it<br>3. Insert an item in the Classification List and select a value from the menu (e.g. Black).<br>4. Check other languages >> all other fields are empty<br>5. Update the item, select another value from the menu (e.g. Red).<br>6. Check other languages  >> all other fields are empty<br>Error: the multilingual fields should be updated |
| | 7365538 | MPA | When attempting to call the userexit "xpdw_ksa_vie_dwn" to create a sub-project to the current project, and canceling the action by closing the sub-project list, the following error occurs: |
| | | | Errorcode: 1 |
| | 7327053 | CRM | When attempting to create a new item record using a lifecycle with the initial progress indicator "0" the following error occurs: |
| | | | Release Procedure is not defined ! |
| | 7255554 | CRM | It is not possible to release a document record if the userexit xedbusr_rst_prd is used in the release procedure and the predecessor |

| FIS-ID | BugDB-ID | Module | Description |
|---|---|---|---|
| | | | was only valid until a date in the past and furthermore there is a predecessor of the predecessor where the validity was linear (without interruption or time gap). (Example: Revision 0: Valid Until: 23.02.2007 09:34:09; Revision 1: Valid From: 23.02.2007 09:34:10 (linear without interruption), Valid Until: 14.07.2008 11:55:42; Revision 2: try to release it now: Valid From: would be something like 15.07.2008 09:11:21 -&gt; with time gap between the two releases). However, the status does not change and following message appears in the massage bar: Element "2D Drawing SR 6975357.994-0-2-Raytheon-0" cannot be transferred into desired state! No valid time period! WORKAROUNDS Create a new status transition without xedbusr_rst_prd that is just used for such cases (like a manager function). Only if applicable. |
| | 7241082 | JCL | Problem Statement: Radio buttons that are customized to appear horizontally do not appear correctly in the Java client. |
| | 7237439 | MOA | When logged in as a standard user (without manager access rights) in a MOA @ environment, a job has to be selected during the login procedure. If the user wants to change the job, the same mask appears again but the field with the organizational unit stays empty. |
| | 7237364 | MOA | The system checks on father access only when MOA is switched on. It is not possible to permit access to certain relations when no father access is given. To have the system behave like before, the userexit xpdw_vfg_str_pre has to be removed and instead the PDW-access must be handled additionally in the standard pre-action userexit of the mask (here: xartst_pre_action). WORKAROUNDS The PDW-access must be reprogrammed by LogiView and called from EP/Insert_Str. |
| | 7207615 | MOA | Unable to delete a revision of any entity when Multi Organizational Access Rights or Multi Project Access Rights are switched on. |
| | 7197192 | MPA | Bug in xpdw_men_del_ass_pro: If the first parameter (principal-ID) is set the PROJ_ID of the project or the EDB_ID of the organizational unit from which to delete the assignment, no selection list should open. However, the userexit does not check this parameter and always opens a selection list with all the projects or organizations the object is assigned to. |
| | 7175214 | MOA | xpdw_rel_eda does not work correctly with aggregate lists. In aggregate lists it determines the wrong table to check for the head organization. WORKAROUNDS: Remove insert button from aggregate lists and insert these relations only in refine lists. |

| FIS-ID | BugDB-ID | Module | Description |
|--------|----------|--------|-------------|
| 11353 | 7108249 | DMS | The Usx xedb_rel_eda allows changing released documents records in the refine list.<br><br>Steps to reproduce:<br><br>Create a document-document relation with parent record "in work" and child record "released".<br><br>Update the child record |