

**Oracle® Retail Analytic Parameter Calculator for
Regular Price Optimization**

Installation Guide

Release 13.4.2

E51777-01

January 2014

Copyright © 2014, Oracle and/or its affiliates. All rights reserved.

Primary Author: Melissa Artley

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Licensing Note: This media pack includes a Restricted Use license for Oracle Retail Predictive Application Server (RPAS) - Enterprise Engine to support Oracle® Retail Analytic Parameter Calculator for Regular Price Optimization only.

Value-Added Reseller (VAR) Language

Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

(i) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.

(ii) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.

(iii) the software component known as **Access Via**[™] licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.

(iv) the software component known as **Adobe Flex**[™] licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.

Contents

Send Us Your Comments	vii
Preface	ix
Audience	ix
Documentation Accessibility	ix
Related Documentation	ix
Customer Support	x
Review Patch Documentation	x
Oracle Retail Documentation on the Oracle Technology Network	x
Conventions	x
 1 Introduction	
Check for the Current Version of the Installation Guide	1-1
Hardware and Software Requirements	1-2
Supported Oracle Integration Technology	1-2
Supported Oracle Retail Products	1-2
Road Map for Installing APC-RPO	1-2
 2 Full Installation: UNIX Environments	
Preparation	2-1
Environment Variable Setup Script	2-1
Additional Environment Variables	2-2
Downloading and Extracting the APC-RPO Media Pack	2-2
Installing Analytic Parameter Calculator for Regular Price Optimization	2-2
Postinstallation Configuration	2-10
Online Help File	2-10
Configuration Files for the RPAS Fusion Client	2-10
 3 Patch Installation	
Upgrade Prerequisites	3-1
Upgrade Process	3-1
Upgrade to Key RPAS Versions	3-1
Upgrade and Patch to RPAS Release 13.2.3	3-2
Convert for Integer Indexing	3-2

Upgrade and Patch to RPAS Release 13.3 or Later	3-2
For the PC	3-2
For the Server	3-2

A Appendix: Installation Order

Enterprise Installation Order	A-1
-------------------------------------	-----

Send Us Your Comments

Oracle Retail Analytic Parameter Calculator for Regular Price Optimization
Installation Guide, Release 13.4.2.

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

Note: Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the Online Documentation available on the Oracle Technology Network Web site. It contains the most current Documentation Library plus all documents revised or released recently.

Send your comments to us using the electronic mail address:
retail-doc_us@oracle.com.

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at <http://www.oracle.com>.

Preface

Oracle Retail Installation Guides contain the requirements and procedures that are necessary for the retailer to install Oracle Retail products.

This document provides detailed instructions on how you can install the Analytic Parameter Calculator for Regular Price Optimization application. This document does not describe how to create the actual configuration.

Audience

This Installation Guide is for the following audiences:

- System administrators and operations personnel
- Database administrators
- System analysts and programmers
- Integrators and implementation staff personnel

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documentation

For more information, see the following documents in the Oracle Retail Analytic Parameter Calculator for Regular Price Optimization Release 13.4.2 documentation set:

- *Oracle Retail Analytic Parameter Calculator for Regular Price Optimization Release Notes*
- Oracle Retail Predictive Application Server documentation

For more information on RPAS, see the documents in the Oracle Retail Predictive Application Server Release 13.4.2 documentation set.

Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:

<https://support.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

Review Patch Documentation

When you install the application for the first time, you install either a base release (for example, 13.4) or a later patch release (for example, 13.4.2). If you are installing the base release, additional patch, and bundled hot fix releases, read the documentation for all releases that have occurred since the base release before you begin installation. Documentation for patch and bundled hot fix releases can contain critical information related to the base release, as well as information about code changes since the base release.

Oracle Retail Documentation on the Oracle Technology Network

Documentation is packaged with each Oracle Retail product release. Oracle Retail product documentation is also available on the following Web site:

http://www.oracle.com/technology/documentation/oracle_retail.html

(Data Model documents are not available through Oracle Technology Network. These documents are packaged with released code, or you can obtain them through My Oracle Support.)

Documentation should be available on this Web site within a month after a product release.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Introduction

This document provides instructions on installing Oracle Retail Analytic Parameter Calculator for Regular Price Optimization (APC-RPO). This document does not describe how to create the actual configuration.

Supplemental installation guides are referenced in this document. The *Oracle Retail Predictive Application Server Installation Guide* and *Oracle Retail Predictive Application Server Configuration Tools User Guide* must be obtained prior to beginning the installation process. Read these documents in their entirety before beginning the installation.

This chapter provides the hardware and software requirements for APC-RPO. It also provides information on the supported Oracle Retail products and the road map to install the APC-RPO application. It includes the following:

- [Check for the Current Version of the Installation Guide](#)
- [Hardware and Software Requirements](#)
- [Supported Oracle Integration Technology](#)
- [Supported Oracle Retail Products](#)
- [Road Map for Installing APC-RPO](#)

Check for the Current Version of the Installation Guide

Corrected versions of Oracle Retail Installation Guides may be published whenever critical corrections are required. For critical corrections, the rerelease of an installation guide may not be attached to a release; the document will simply be replaced on the Oracle Technology Network Web site.

Before you begin installation, check to be sure that you have the most recent version of this installation guide. Oracle Retail installation guides are available on the Oracle Technology Network at the following URL:

http://www.oracle.com/technology/documentation/oracle_retail.html

An updated version of an installation guide is indicated by part number, as well as print date (month and year). An updated version uses the same part number, with a higher-numbered suffix. For example, part number E123456-02 is an updated version of an installation guide with part number E123456-01.

If a more recent version of this installation guide is available, that version supersedes all previous versions. Only use the newest version for your installation.

Hardware and Software Requirements

Table 1–1 provides information about the current release.

Table 1–1 Hardware and Software Requirements

Requirement	Details
Supported RPAS Version	13.4.2
Oracle Retail Batch Script Architecture (BSA)	13.4.2
Required Software	<p>Java Development Kit (JDK) 1.6</p> <p>Note: There are specific JDK versions needed for each of the supported operating systems for the Oracle Retail Predictive Application Server (RPAS). For the list of JDK versions, see the <i>Oracle Retail Predictive Application Server Installation Guide</i>.</p> <p>Note: When installing Java, avoid enabling AutoUpdate because it may update the Java version without prompting.</p>

Note: RPAS applications, such as APC-RPO, run on the Oracle Retail Predictive Application Server (RPAS) platform. For information about the hardware and software requirements for RPAS, see the supported RPAS version of the *Oracle Retail Predictive Application Server Installation Guide*.

Supported Oracle Integration Technology

The following Oracle integration technology is supported:

- Oracle Data Integrator (ODI) 11.1.1.6

Supported Oracle Retail Products

Table 1–2 provides information about the supported Oracle Retail products.

Table 1–2 Supported Oracle Retail Products

Product	Version
Oracle Retail Demand Forecasting (RDF)	13.4.2
Oracle Retail Regular Price Optimization (RPO)	13.4.2

Road Map for Installing APC-RPO

This guide explains how you can install and set up the APC-RPO application. In order to install APC-RPO for production, you must perform the following tasks in a sequence:

Task	Description
<i>Pre-installation Tasks</i>	
1.	Install and set up the RPAS Infrastructure. For more information, refer to the <i>Oracle Retail Predictive Application Server Installation Guide</i> .

Task	Description
2.	Install and set up the RPAS Client. RPAS Release 13.4.2 includes the RPAS Classic Client and RPAS Fusion Client. For more information, refer to the <i>Oracle Retail Predictive Application Server Installation Guide</i> .
3.	Oracle Retail Batch Scripting Architecture (BSA) must be installed prior to installing APC-RPO. For information about installing BSA, see the <i>Oracle Retail Batch Script Architecture Implementation Guide</i> .
<i>Installation Task</i>	
4.	Access the APC-RPO installation software and install the application. For more information, see Chapter 2, "Full Installation: UNIX Environments" .

Note: Refer to chapter, "Creating a Multi-solution Taskflow" in the *Oracle Retail Predictive Application Server Configuration Tools User Guide* for information about the Multi-solution Taskflow.

Full Installation: UNIX Environments

The installation of the server-side RPAS components on UNIX operating systems is accomplished using Java-based installation programs that are included with the installation package.

The Analytic Parameter Calculator for Regular Price Optimization (APC-RPO) Installer automates the following:

- Installation of the APC-RPO mock install configuration.
- Installation of the APC-RPO configuration for the RPAS Fusion Client. For more information on installing the RPAS Fusion Client, refer to the *Oracle Retail Predictive Application Server Installation Guide*.
- Creation of a sample APC-RPO domain.

This document assumes that the RPAS installer process (from the *Oracle Retail Predictive Application Server Installation Guide*) has been completed prior to using the APC-RPO installer.

Preparation

The RPAS server components required prior to this installation process are available from Oracle's E-Delivery web site, <http://edelivery.oracle.com>, and My Oracle Support, <https://support.oracle.com>.

Environment Variable Setup Script

Before running the solution installer, source your `retaillogin.ksh` script. The script is located in the root of the base directory where RPAS was installed unless the default was overwritten when specifying directory paths.

Source the script from inside the directory where the script is located:

```
./retaillogin.ksh
```

Or, include the full path after the period ".":

```
./<base_directory>/retaillogin.ksh
```

Notes: The preceding period and space (". ") must be included at the beginning of the command when running the script.

Include this path and script in the `.profile` in your home directory (`~/profile`) if you want to have this environment setup script run during login.

This script sets up the environment variables, such as `RPAS_HOME` and `RIDE_HOME`, which are required for RPAS to run properly.

Additional Environment Variables

In addition to the running of `retaillogin.ksh`, export the following environment variables prior to starting the installer.

All Platforms:

```
export RPAS_JAVA_CLASSPATH="$RPAS_HOME/applib/aaajni.jar:  
$RPAS_HOME/applib/aaiaPCRPO.jar:$RPAS_JAVA_CLASSPATH"
```

Note: There are additional Java environment variables that must be set for your particular operation system. These variables are the same for all applications on RPAS. See the “Java Environment” section of the *Oracle Retail Predictive Application Server Installation Guide* for these environment variables.

Downloading and Extracting the APC-RPO Media Pack

The following procedure provides information about downloading and extracting the APC-RPO media pack and its contents:

1. Create a directory to store the APC-RPO media pack on the target server. This directory is referred to as **[APC-RPO Installation]**. It is the location where the APC-RPO installation routine is run.
2. Download and extract the media pack to this location. After it is extracted, two directories open, **CDROM** and **DOCS**.

The **CDROM** folder contains the `apcrpo.zip` file. This file contains the APC-RPO solution.

The **DOCS** folder contains the APC-RPO documentation.

Installing Analytic Parameter Calculator for Regular Price Optimization

Perform the following steps to install APC-RPO:

1. Extract the APC-RPO installer from the **[APC-RPO Installation]** directory.

```
cd CDROM  
unzip apcrpo.zip
```

2. From the **[APC-RPO Installation]/CDROM** directory, run the following commands to run the APC-RPO installer:

```
cd apcrpo  
./install.sh
```

Note: The command must be run with the preceding period and slash (`./`).

If you are running this process on an X-Windows emulator (such as Exceed), graphical user interface to the Installer appears. If you are running in console mode through a terminal emulator, the text interface to the installer appears.

In both cases, the requested information is identical. In the GUI, you may be shown a check box to signal whether you want a component installed; in text mode, you are prompted for a response of **true** or **false**.


Note: In text mode, the default value appears in square brackets []. To use the default value and continue, press **Enter**. If you want to use a different value, enter the new value. When prompted to create a directory, respond with **yes** and press **Enter**.

3. The [Analytic Parameter Calculator for Regular Price Optimization Installer Window](#) opens and displays the components that are installed during installation process and the required components.

Click **Next** to continue.


Note: Oracle Retail Batch Scripting Architecture (BSA) must be installed prior to installing APC-RPO. For information about installing BSA, see the *Oracle Retail Batch Script Architecture Implementation Guide*.

Figure 2–1 Analytic Parameter Calculator for Regular Price Optimization Installer Window



4. The [Choose Components to Install Window](#) opens.

Figure 2–2 *Choose Components to Install Window*



Select one or both of the following options:


- **APCRPO** — Select this option to install the Analytic Parameter Calculator for Regular Price Optimization application with the domain.
- **RPAS Fusion Client configuration** — Select this option to install the RPAS Fusion Client configuration for APC-RPO. For more information, see [Configuration Files for the RPAS Fusion Client](#).

Note: If you do not want to install the RPAS Fusion Client configuration, clear this check box and skip steps 7 and 8.

Click **Next** to continue.

5. The **Base Paths for Solution Window** opens.

Figure 2–3 Base Paths for Solution Window



Enter the relevant information in the following fields:


- **Dir to store solution** — Enter the directory path where your solution should be stored.
- **APCRPO domain path** — Enter the directory path where the domain should be stored.
- **Path to retaillogin.ksh script** - Enter the path and file name to the retaillogin.ksh script created during RPAS installation.

Note: Ensure that the installation paths are located outside the installer directory [APC-RPO Installation].

Click **Next** to continue.

- The [Install Tasks Window](#) opens.

Figure 2–4 *Install Tasks Window*



Select or clear the **Create APCRPO Domain** option:

- To create the APC-RPO domain, select the **Create APCRPO Domain** option, which is selected by default.

Note: Domain builds use the environment specified in the `retaillogin.ksh` environment setup script. If you change any environment details, edit the `retaillogin.ksh` script and any subsequent scripts called by `retaillogin.ksh`.

For more information about the `retaillogin.ksh`, see the [Environment Variable Setup Script](#) section.

- To install all required components to support the APC-RPO domain, but not create the actual APC-RPO domain, clear the check box.

Click **Next** to continue.

7. The [Fusion Location Information Window](#) opens.

Figure 2–5 Fusion Location Information Window

Enter the relevant information in the following fields:

Field	Description
Enter the number of RPAS Fusion Client servers to install these configurations on: (1-4)	Enter the number of servers running the RPAS Fusion Client where you want to install the APC-RPO configuration. In case the RPAS Fusion Client is running on a single server, enter 1. If you have a clustered installation, you can enter up to four servers
Enter the RPAS server hostname:	Enter the hostname of the RPAS server.
Enter the RPAS server port:	Enter the port number of the RPAS server.
RPAS Solution Path	Enter the location of the RPAS domain for APC-RPO.

Note: The [Fusion Location Information Windows](#) open when you select the RPAS Fusion Client configuration check box on the [Choose Components to Install Window](#).

If you are not installing the RPAS Fusion Client configuration, proceed to step 9.

Click **Next** to continue.

8. Based on the number of servers you entered, the [Fusion Location Information \(Details\) Window](#) opens.

Figure 2–6 Fusion Location Information (Details) Window

Enter the server details in the following set of fields for each configuration:

Field	Description
Hostname or IP	Enter the host name or IP address of the server where the RPAS Fusion Client is installed.
Configuration Directory	Enter the location of the config directory available at the location where the RPAS Fusion Client is installed.
Login username	Enter the user name to log on to the server where the RPAS Fusion Client is installed.
Login password	Enter the password associated with the user name.
Login username alias	Specify an alias name for the administrative user. Specifying an alias name for the administrative user enhances the security for the application. When left blank, the alias name defaults to the administrative user name.


Note: As part of the Oracle Software Security Assurance, sensitive information such as user credentials for the RPAS Fusion Client are encrypted and stored in a secure location in the application installation directory. This location is called the Oracle Wallet.

When the installation starts, the administrative user credentials will be retrieved from the Oracle Wallet based on the alias name specified in this window.

Click **Next** to continue.

9. The **Installation Progress Window** opens. To start the installation, click **Install**.

Figure 2–7 Installation Progress Window



This window also displays the progress of the installation routine. Click **Show Details** to view the log output as the installation is performed. If you do not select to view the details, a graphical representation of the installation steps appears. As each step is completed, the color changes to show you the progress.

You can toggle between detailed mode at any time during or after the installation.

10. When the installation has finished, the Finished message appears. Click **OK** to close the dialog box.
11. To view the installation details, click **Show Details**. The window displays two tabs, the Output tab and the Error tab. It is recommended that you review these tabs for any issues that may have occurred during the installation process.

If you want to view the log again at a later date, a text copy is saved in the directory **[APC-RPO Installation]**. The log file is named based on the product and timestamp, followed by the `.log` extension.

Created as part of this process is the `make_domain.apcrpo` file located in **[Solution Install Dir]** entered previously. This file contains all of the required parameters needed to support the domain installation. If necessary, this file may be modified if the default parameters are not appropriate for your particular environment.

Note: The domain install process may also include postinstallation data loading scripts specific to the APC-RPO configuration. These scripts, if present, may also be modified.

For additional information on installing RPAS domains manually, see the *Oracle Retail Predictive Application Server Installation Guide*.

12. Click **Exit** to close the installer.

Postinstallation Configuration

Before starting the DomainDaemon, you must first set the following configuration property files and the APCRPO_HOME environment variable.

Online Help File

If you are on AIX and you have re-installed APC-RPO, you must edit a help file to use the APC-RPO online help in the RPAS Fusion Client.

Manually edit the [fusion client installation dir]/config/Help/ohwconfig.xml file by removing the following duplicate line:

```
<helpSet xmlns="" id="<shortProductName>"
location="<shortProductName>/<shortProductName>-help.hs"/>
```

Caution: If this duplicate line is not removed, a “500 Page Not Found” error occurs when attempting to access the online help in the RPAS Fusion Client.

Configuration Files for the RPAS Fusion Client

Note: This section describes the optional installation method that involves setting up the RPAS Fusion Client configuration and online help for the APC-RPO configuration. If you chose to install the Fusion Client configuration files using the APC-RPO installer, you can skip this section.

Before proceeding ahead, ensure that you have appropriate access privileges on the server running the RPAS Fusion Client.

Along with the files to install the APC-RPO solution and domain, the APC-RPO installation media pack also includes the RPAS Fusion Client configuration and online help files that you must install if you want to use APC-RPO on the RPAS Fusion Client.

These files are available at the following location within the [APC-RPO Installation] directory:

[APC-RPO Installation]/apcrpo/fusion

During the APC-RPO installation, these files are automatically copied over to the configuration directory where the RPAS Fusion Client is installed. The installation also ensures that the following RPAS Fusion Client configuration files are updated to reflect the APC-RPO installation:

- Foundation.xml - Located in the [RPAS Fusion Client Installation]/config/rpas directory. This XML file includes the domain configuration available for use with the RPAS Fusion Client.
- ohwconfig.xml - Located in the [RPAS Fusion Client Installation]/config/Help directory. This XML file includes the online help configuration for the RPAS Fusion Client.

If you do not install the Fusion Client configuration files during the APC-RPO installation, you can choose to do one of the following tasks:

- Run the APC-RPO installer again, and select to install only the RPAS Fusion Client configuration.
- Run the RPAS Fusion Client installer again, and specify the APC-RPO domain configuration. For more information on the RPAS Fusion Client installation, refer to the *Oracle Retail Predictive Application Server Installation Guide*.
- Configure the RPAS Fusion Client for APC-RPO manually. For more information, see the “Configuring Additional Domains” section in the *Oracle Retail Predictive Application Server Administration Guide for the Fusion Client*.

Patch Installation

This chapter describes how to upgrade APC-RPO from a previous release to Release 13.4.2.

Upgrade Prerequisites

In order to upgrade APC-RPO, first verify the following criteria for the RPAS system:

- Verify that RPAS is currently installed and is at Release 13.3 or later. If not, refer to the section, [Upgrade to Key RPAS Versions](#).
- Verify that the UNIX operating system is updated to the currently supported version. Refer to the “Hardware and Software Requirements” section of the *Oracle Retail Predictive Application Server Installation Guide*.
- Verify that the environment variables are correctly set for both the server and PC; if they are not, follow these instructions to set them:
 - Change directories to the original RPAS installation directory (such as the one created by the most recent installer), and run `retaillogin.ksh` to set all environment variables. For example:

```
$ cd /retail
$ . ./retaillogin.ksh
```

Notes: After you have run the script, verify that the environment variables all point to the correct locations on your environment.

If you have updated Java since the last installation of RPAS, verify that the `JAVA_HOME` path is correct. If not, update your `retaillogin.ksh` script and source it again as previously outlined.

Upgrade Process

The following process outlines how to upgrade APC-RPO to the latest version using the RPAS Configuration Tools.

Upgrade to Key RPAS Versions

Before you upgrade to a post-13.3 release, ensure that you have upgraded and patched to RPAS Release 13.2.3.

This list defines the upgrade process that is described in the following sections.

1. [Upgrade and Patch to RPAS Release 13.2.3](#)

2. [Convert for Integer Indexing](#)
3. [Upgrade and Patch to RPAS Release 13.3 or Later](#)

Upgrade and Patch to RPAS Release 13.2.3

Upgrading your domain to a 13.3 or later RPAS domain requires that you first upgrade it to a 13.2.3 domain. For instructions, see the “Upgrading and Patching Domains” section in the 13.2.3 release of either the Classic Client or Fusion Client version of the *Oracle Retail Predictive Application Server Administration Guide*.

After upgrading, you must run a configuration patch over the domain to ensure compatibility with the RPAS version, regardless of whether there are any configuration changes.

Convert for Integer Indexing

Upgrading to a 13.3 or later RPAS domain requires the use of the `convertDomain` utility, which may not copy the entire contents of the source domain to the destination domain. For files that are not copied by `convertDomain`, you may need to copy them manually.

For information about what is and is not copied, see the “`convertDomain`” section in the 13.3 release of either the Classic Client or Fusion Client version of the *Oracle Retail Predictive Application Server Administration Guide*.

Upgrade and Patch to RPAS Release 13.3 or Later

The following process outlines how to upgrade APC-RPO to the current version using the RPAS Configuration Tools.

Note: After upgrading, you must run a configuration patch over the domain to ensure compatibility with the latest RPAS version, regardless of whether there are any configuration changes.

For the PC

Follow these instructions for the PC to upgrade to the current version:

1. Open RPAS Configuration Tools.
2. In RPAS Configuration Tools, load your previous configuration of APC-RPO:
 - a. From the Configuration Tools File menu, select **Open**.
 - b. From the Open window, locate the configuration file and click **Open**.
3. If your configuration requires updating, dialog boxes will prompt you to upgrade. Follow the instructions given in the dialog boxes.
4. In the RPAS Configuration Tools File menu, click **Save** to save the configuration.
5. Zip the configuration in Cygwin and transfer the `.zip` file to the RPAS server.

For the Server

Follow these instructions for the server to upgrade to the current version:

1. Upgrade the RPAS server and the RPAS Fusion Client configuration by running the installer:

- a. Begin the installer as described in the [Installing Analytic Parameter Calculator for Regular Price Optimization](#) section.
 - b. Complete steps 1-5.
 - c. At step 6, the [Install Tasks Window](#), clear the **Create APCRPO Domain** option.
 - d. Finish the remaining steps of the installer.
2. Unzip the updated configuration and note where it is saved.
 3. Upgrade your APC-RPO domain to a 13.4.2 domain. Run the following command:


```
buildAPCRPO.sh -d <domain path> -c <config path> -i
<input path> -l <log path> -p
```

Table 3–1 Supported Parameters for buildAPCRPO.sh

Flag	Where:	Is the Path for the:	Default Value*
-c	<config path>	configurations	\$PWD/ ../config
-i	<input path>	input files	\$PWD/ ../input
-l	<log path>	log file	\$PWD/ ../
-d	<domain path>	domain	\$PWD/ ../domain
-m	<max process#>	number of max processes for loading measures	1
-f	<log file >	log file	build_domain.log
-p	<make patch build >	domain patching	none
-u	<show usage of this script>	show usage of this script	none
-n	<configName>	configuration name	APCRPO
-r	<partionDimension>	partion dimension	dept
* Where \$PWD is the current directory			

Note: The flag -p must be used for domain patching.

Appendix: Installation Order

This section provides a guideline for the order in which the Oracle Retail applications should be installed. If a retailer has chosen to use only some of the applications, the order is still valid, less the applications not being installed.

Note: The installation order is not meant to imply integration between products.

Enterprise Installation Order

1. Oracle Retail Merchandising System (RMS), Oracle Retail Trade Management (RTM), Oracle Retail Sales Audit (ReSA), Optional: Oracle Retail Fiscal Management (ORFM)

Note: ORFM is an optional application for RMS if you are implementing Brazil localization.

2. Oracle Retail Service Layer (RSL)
3. Oracle Retail Extract, Transform, Load (RETL)
4. Oracle Retail Active Retail Intelligence (ARI)
5. Oracle Retail Warehouse Management System (RWMS)
6. Oracle Retail Allocation
7. Oracle Retail Invoice Matching (ReIM)
8. Oracle Retail Price Management (RPM)

Note: During installation of RPM, you are asked for the RIBforRPM provider URL. Since RIB is installed after RPM, make a note of the URL you enter. If you need to change the RIBforRPM provider URL after you install RIB, you can do so by editing the `remote_service_locator_info_ribserver.xml` file.

9. Oracle Retail Central Office (ORCO)
10. Oracle Retail Returns Management (ORRM)
11. Oracle Retail Back Office (ORBO) or Back Office with Labels and Tags (ORLAT)
12. Oracle Retail Store Inventory Management (SIM)

Note: During installation of SIM, you are asked for the RIB provider URL. Since RIB is installed after SIM, make a note of the URL you enter. If you need to change the RIB provider URL after you install RIB, you can do so by editing the `remote_service_locator_info_ribserver.xml` file.

13. Oracle Retail Predictive Application Server (RPAS)
14. Oracle Retail Demand Forecasting (RDF)
15. Oracle Retail Category Management (RCM)
16. Oracle Retail Replenishment Optimization (RO)
17. Oracle Retail Analytic Parameter Calculator Replenishment Optimization (APC RO)
18. Oracle Retail Regular Price Optimization (RPO)
19. Oracle Retail Merchandise Financial Planning (MFP)
20. Oracle Retail Size Profile Optimization (SPO)
21. Oracle Retail Assortment Planning (AP)
22. Oracle Retail Item Planning (IP)
23. Oracle Retail Item Planning Configured for COE (IP COE)
24. Oracle Retail Advanced Inventory Planning (AIP)
25. Oracle Retail Integration Bus (RIB)
26. Oracle Retail Point-of-Service (ORPOS)
27. Oracle Retail Markdown Optimization (MDO)
28. Oracle Retail Clearance Optimization Engine (COE)
29. Oracle Retail Analytic Parameter Calculator for Markdown Optimization (APC-MDO)
30. Oracle Retail Analytic Parameter Calculator for Regular Price Optimization (APC-RPO)
31. Oracle Retail Promotion Intelligence and Promotion Planning and Optimization (PI-PPO)
32. Oracle Retail Analytics
33. Oracle Retail Workspace (ORW)